The Multi-Armed Bandit Problem Under the Mean-Variance Setting

Hongda Hu^{*}

Arthur Charpentier[†]

Mario Ghossoub[‡]

Alexander Schied[§]

First version: December 18, 2022 This version: May 2, 2024

Abstract

The classical multi-armed bandit problem involves a learner and a collection of arms with unknown reward distributions. At each round, the learner selects an arm and receives new information. The learner faces a tradeoff between exploiting the current information and exploring all arms. The objective is to maximize the expected cumulative reward over all rounds. Such an objective does not involve a risk-reward tradeoff, which is fundamental in many areas of application. In this paper, we build upon Sani et al. (2012)'s extension of the classical problem to a mean-variance setting. We relax their assumptions of independent arms and bounded rewards, and we consider sub-Gaussian arms. We introduce the Risk-Aware Lower Confidence Bound algorithm to solve the problem, and study some of its properties. We perform numerical simulations to demonstrate that, in both independent and dependent scenarios, our approach outperforms the algorithm suggested by Sani et al. (2012)

Keywords: multiarmed bandits, mean-variance regret analysis, sub-Gaussian distribution, online optimization

1 Introduction

The multi-armed bandit (MAB) problem is a type of online learning and sequential decision-making problem. A classical MAB problem involves K independent arms, each with its own independent

^{*}Department of Statistics and Actuarial Science, University of Waterloo

[†]Université du Québec à Montréal

[‡]Department of Statistics and Actuarial Science, University of Waterloo

[§]Department of Statistics and Actuarial Science, University of Waterloo, aschied@uwaterloo.ca

We are grateful to three anonymous reviewers for comments that have greatly helped us to improve this paper. H.H. and A.S. gratefully acknowledge support from the Natural Sciences and Engineering Research Council of Canada through grant RGPIN-2017-04054. H.H. and M.G. gratefully acknowledges support from the Natural Sciences and Engineering Research Council of Canada through grant RGPIN-2018-03961. A.C. acknowledges the financial support of the AXA Research Fund through the joint research initiative *use and value of unusual data in actuarial science*, as well as from the Natural Sciences and Engineering Research Council of Canada through grant RGPIN-2019-07077.

reward distribution, and a learner. In the problem, each arm generates a random reward from the underlying probability distribution, which is unknown in advance. At each round, the learner selects one arm among K arms and receives a new observation from that arm. The learner often faces a tradeoff between exploiting the current information and exploring all arms. Given a finite number of n rounds, the design objective aims to maximize the cumulative reward over n rounds.

The MAB framework has been applied to a wide range of real-world problems, including clinical trials (Durand et al. (2018)), recommendation systems (Mary et al. (2015)), telecommunication (Boldrini et al. (2018)) and finance (Shen et al. (2015)). For example, in finance (Shen et al. (2015)), the actions correspond to the proposed portfolio composition, and the reward represents the performance of the proposed portfolio. The exploration–exploitation dilemma in the above example is whether to try a new portfolio composition or keep using the current portfolio with the best historical performance.

As is standard in the literature, we measure the welfare implications of a given selection policy by the notion of regret. The latter is defined as the difference between the expected cumulative rewards under the true distribution and the empirical distribution.

1.1 Related Work

The MAB problem has been explored by Thompson (1933) and Robbins (1952) as a useful tool for constructing online sequential decision algorithms. Thompson (1933) proposed a Bayes-optimal approach that directly maximizes expected cumulative rewards with respect to a given prior distribution. Robbins (1952) first formalized the classic MAB problem, in which each arm follows an unknown distribution over [0,1], and rewards are independent draws from the distribution corresponding to the chosen arm. Since then, a number of methods have been developed to solve the MAB problem. Most of the possible ways to solve the MAB problem can be defined into three categories:

- ε -greedy algorithm: is a straightforward method for balancing exploration and exploitation by employing a greedy policy to take action with a probability of $1 - \varepsilon$, and a random action with a small probability of ε .
- Upper confidence bounds (UCB) algorithm: is often phrased as "optimism in the face of uncertainty". The algorithm uses the observed data so far to assign a value (i.e., upper confidence bound index) to each arm, where the arm with the higher index value will be selected with a higher probability in the next round. Strong theoretical guarantees on the rate of regret can be attained by implementing the UCB algorithm. Early work on using UCB to solve MAB problems was done by Lai and Robbins (1985), Agrawal (1995) and Auer et al. (2002). The technique of upper confidence bounds (UCB) for the asymptotic analysis of regret was introduced by Lai and Robbins (1985), who demonstrated that the minimum regret has a logarithmic order in n. As a simpler formulation, Agrawal (1995) discusses the MAB problem under a finite-time setting. Auer et al. (2002) conduct a finite-time analysis of the classic MAB with bounded rewards using the UCB algorithm.
- *Thompson sampling:* is the first algorithm for the bandit problem proposed by Thompson (1933). Thompson sampling has a simple idea. By implementing Thompson sampling, the

learner selects a prior over a set of possible bandit environments at the start. In each round, the learner makes an action chosen randomly from the posterior. Thompson Sampling has been empirically proved to be effective by Chapelle and Li (2011). In comparison to the UCB algorithm, Thompson Sampling does not have strong theoretical guarantees on regret. Zhu and Tan (2020), Baudry et al. (2021), and Chang and Tan (2022) conducted theoretical analysis and established consistent guarantees on regret.

In the classic MAB formulation, the learner maximizes the expected cumulative reward within a finite time frame. Nevertheless, in real practice, maximizing the expected reward may not be the ultimate goal. For instance, in portfolio selection, the portfolio that performs best during a period of the economic boom may lead to a substantial loss when the economy is struggling. In clinical trials, the treatment that works best on average may result in side effects for some patients. In many cases, a learner's primary goal may be to effectively balance risk and return. There is no universally accepted definition of risk. Among various risk modelling paradigms, the mean-variance paradigm (Markowitz (1968)) and the expected utility theory (Morgenstern and Von Neumann (1953)) are the two fundamental risk modelling paradigms.

The work of Sani et al. (2012), in which the criteria of mean-variance of data was first introduced, is the most important reference to our study. Sani et al. (2012) study the problem where each arm's distribution is bounded, and the learner's objective is to minimize the mean-variance of rewards collected over a finite time. Their proposed Mean-Variance Lower Confidence Bound (MVLCB) algorithm achieves a learning regret of $\mathcal{O}((\log(n))^2/n)$. As an improvement, Vakili and Zhao (2016) analyze the problem under the mean-variance setting, but with the assumption that the square of the underlying X is sub-Gaussian. Vakili and Zhao (2016)'s algorithm achieves a learning regret of $\mathcal{O}(\log(n))/n$. Furthermore, Vakili and Zhao (2015) extend the previous setup by taking into account the value-at-risk (VaR) of total rewards over a finite time horizon and ending with a learning regret of $\mathcal{O}((f(n)\log(n))/n)$, where f(n) is a positive increasing diverging sequence. Zhu and Tan (2020) examine the possibilities of Thompson sampling methods for solving mean-variance MAB and provide a detailed regret analysis for Gaussian and Bernoulli bandits with comparable learning regret $\mathcal{O}((\log(n))/n)$. In addition, they run a large number of simulations to compare their algorithms against existing UCB-based methods for different risk tolerances. As another way of measuring the risk, conditional-value-at-risk (CVaR) has been studied in solving risk-averse MAB by Galichet et al. (2014), Kagrecha et al. (2019) and Prashanth et al. (2020). Galichet et al. (2014) show that their proposed algorithm's learning regret under the CVaR scheme is $\mathcal{O}((\log(n))/n)$. As a follow-up, Kagrecha et al. (2019) conduct a theoretical study of CVaR-based algorithm for MAB with unbounded rewards, and Prashanth et al. (2020) compare the performance of CVaR-based algorithm under light-tailed and heavy-tailed distributions.

Both Sani et al. (2012) and Galichet et al. (2014) study the risk-aware MAB problem by assuming independent bounded arms. Such an assumption limits the application of their results. In real-life problems, multiple arms may expose the same source of risk, and the distribution of each arm may not necessarily be bounded. As a pioneer, Liu et al. (2021) create a risk-aware UCB algorithm for Gaussian distributions that has a learning regret of $\mathcal{O}((\log(n))/n)$. The Thompson sampling methods are then used by Gupta et al. (2021) to analyze the correlated bandit problems, where the underlying distributions are bounded. They categorize the arms as competitive or non-competitive, assuming that correlations between the arms arise from a latent random source. For the competitive group, their algorithm produces a learning regret of $\mathcal{O}((\log(n))/n)$, whereas for the non-competitive group, it can only produce $\mathcal{O}(1)$.

Bandit learning algorithms are now widely used in a variety of fields. However, the application of bandit learning to finance has received little attention from researchers due to the inherent difference between financial assets and classic bandits.

- *Independence:* the classic MAB problem assumes i.i.d. reward distributions for each arm, which does not apply to financial asset returns. Assets are correlated in the financial markets, and the performance of one asset can reveal important information about the other assets. A lower regret bound can be obtained by exploiting the dependence; for example, Gupta et al. (2021) pioneered the analysis of the correlated MAB problem.
- *Single pull:* the classic MAB problem only allows one arm to be pulled at each round, while portfolio selection strategies often result in a basket of financial assets for investment.
- *Risk-return balance:* the classic MAB problem is only concerned with maximizing mean reward, while good portfolio selection strategies focus on risk-adjusted return (i.e., Sharpe ratio, mean-variance).
- *Historical data:* the classic MAB problem has no historical data, whereas sufficient historical data is available for publicly traded financial assets.

Shen et al. (2015) use a principal component decomposition (PCA) to construct an orthogonal portfolio from correlated assets, and they derive the optimal portfolio strategy using the UCB framework based on risk-adjusted reward. Later, Shen et al. (2015) treat classic portfolio strategies in finance as strategic arms, and they leverage the Thompson sampling method to mix two different strategic arms.

1.2 Contributions

We analyze the risk-aware Multi-Armed Bandit (MAB) problem using the Upper Confidence Bound (UCB) methodology proposed by Lai and Robbins (1985). In contrast to their work, we factor in risk by adopting a mean-variance framework. Shifting from a sole focus on rewards to a consideration of risk-reward balance, our algorithm can be applied to a broader range of problems compared to the UCB algorithm proposed by Lai and Robbins (1985). Comparing our methodology to another well-known MAB method proposed by Thompson (1933), we attain mathematically rigorous bounds on the realized regret. In contrast, much of the literature that adopts the Thompson sampling method can demonstrate the effectiveness of the algorithms only empirically.

Next, Sani et al. (2012) serves as our primary reference, being the first to introduce the meanvariance MAB problem. In their paper, they assume i.i.d. arms taking values in [0, 1] and state a learning regret of $\mathcal{O}((\log(n))^2/n)$. Note, however, that the algorithm in Sani et al. (2012) requires a fixed runtime n. That is, if the algorithm is set up to run for m time periods, then its parameters, and consequently its policy, will differ from those prescribed for a runtime of $n \neq m$. This fact somewhat limits the interpretation of the asymptotics for the learning regret. By contrast, the algorithm we introduce in this paper does not require that the runtime n is fixed from the start. This algorithm is a member of the extensive family of Lower Confidence Bound algorithms, and we call it the Risk Aware Lower Confidence Bound (RALCB) algorithm. In comparison to Sani et al. (2012), we also allow for a larger class of arms distributions, namely the sub-Gaussian distributions, and we do not the individual arms to be independent. In addition, we are able to bound the expected regret by $\mathcal{O}((\log(n))/n)$.

Subsequent to our mathematical analysis, we perform numerous numerical simulations to assess and compare the performance of our algorithm against the one proposed by Sani et al. (2012). Across diverse risk-return scenarios, our algorithm rapidly identifies optimal arms, consistently surpassing the performance of the MVLCB algorithm suggested by Sani et al. (2012). Moreover, we illustrate the robustness of our algorithm by applying it to real-world data taken from financial markets.

The rest of this paper is organized as follows: In Section 2, we introduce the MAB problem under the mean-variance setting. In Section 3, the confidence-bound algorithm is introduced, and its theoretical characteristics are examined in Section 3.1. A possible extension of MAB problems is examined in Section 3.1.2. The theoretical findings are then supported by a set of numerical simulations in Section 4. Results of supporting proofs are provided in Section 5.

2 Problem Formulation

In this section, we introduce notation and define the risk-aware MAB problem. The classic Karmed bandit problem has a finite action set $\mathcal{A} := \{1, ..., K\}$. The learner interacts with the environment sequentially over time. Let X_t^i denote the *t*-th observed real-valued reward from pulling arm $i \in \{1, ..., K\}$, modeled as a random variable on a given probability space $(\Omega, \mathcal{F}, \mathbb{P})$. We assume that each X_t^i belongs to the class of sub-Gaussian random variables. That is, there is a constant $\theta \ge 0$ such that for all $\lambda \in \mathbb{R}$:

$$\mathbb{E}_{\mathbb{P}}[e^{\lambda(X-\mathbb{E}_{\mathbb{P}}[X])}] \le e^{\frac{\lambda^2\theta^2}{2}}.$$
(1)

The parameter θ will henceforth be called a *sub-Gaussianity parameter* for X. Clearly, all Gaussian random variables are sub-Gaussian, and so are all bounded random variables. We refer to Wainwright (2019) for a discussion of the mathematical properties of sub-Gaussian random variables.

We let $\mathbf{X}_t := (X_t^1, X_t^2, ..., X_t^K)$ and assume that the random vectors $\mathbf{X}_1, \mathbf{X}_2, ...$ are independent and identically distributed (i.i.d.), while for each fixed t, the random variables $X_t^1, X_t^2, ..., X_t^K$ may be dependent. In each round t, the learner selects an arm $\pi_t \in \mathcal{A}$ based on the information available at t. This will be formalized by defining a *learning policy* as a sequence $\pi_1, \pi_2, ...$ of random variables taking values in $\mathcal{A} = \{1, ..., K\}$, such that π_t depends only on $(X_{T_{\pi_1,1}}^{\pi_1}, ..., X_{T_{\pi_{t-1},t-1}}^{\pi_{t-1}}, \pi_1, ..., \pi_{t-1})$, where

$$T_{i,t} := \sum_{s=1}^t \mathbb{1}_{\{\pi_s = i\}}$$

counts the number of times arm *i* has been pulled by time *t*. The environment then samples a reward $X_{T_{\pi_t,t}}^{\pi_t}$ and reveals it to the learner. As a result, each decision of the learner is based on past observations.

In the classic MAB problem, the goal of the learner is to maximize the expected cumulative reward. In this paper, we also take the risk into consideration. To effectively balance the expected reward and the risk, we use the same mean-variance setting as in Sani et al. (2012). Let the coefficient of absolute risk tolerance $\rho \in [0, 1]$ be given and fixed, and define for every arm i,

$$\mathrm{MV}_{i}^{\rho} \coloneqq (1-\rho)\sigma_{i}^{2} - \rho\mu_{i}, \qquad (2)$$

where μ_i and σ_i^2 denote the mean and variance of X_i . The optimal arms are given by $\arg\min_{i\in\mathcal{A}} \mathrm{MV}_i^{\rho}$, and we will often use the notation i_0^{ρ} to denote an optimal arm.

Given a learning policy π_t and its corresponding performance over n rounds, the empirical mean-variance of the learning policy by round n can be defined as

$$\widehat{\mathrm{MV}}_{n}^{\rho}(\pi) := (1-\rho)\widehat{\sigma}_{n}^{2}(\pi) - \rho\widehat{\mu}_{n}(\pi), \tag{3}$$

where

$$\hat{\mu}_n(\pi) := \frac{1}{n} \sum_{i=1}^K \sum_{t=1}^{T_{i,n}} X_t^i, \qquad \hat{\sigma}_n^2(\pi) := \frac{1}{n} \sum_{i=1}^K \sum_{t=1}^{T_{i,n}} (X_t^i - \hat{\mu}_n(\pi))^2.$$
(4)

The objective of the risk-aware MAB problem is to find a policy π that asymptotically minimizes $\widehat{\mathrm{MV}}_{n}^{\rho}(\pi)$ for a given risk-tolerance factor ρ .

To compare the performance of different learning policies π over n rounds, we introduce the learning regret:

$$\mathcal{R}_n(\pi) := \widehat{\mathrm{MV}}_n^{\rho}(\pi) - \min_{i \in \mathcal{A}} \mathrm{MV}_i^{\rho},\tag{5}$$

which is the difference between the policy's empirical mean-variance and the optimal mean-variance. As a consequence, the objective becomes to generate an algorithm for which the regret decreases in expectation as n increases.

Remark 2.1. By examining the extreme values of risk tolerance, we observe that the minimization of the learning regret (5) includes the following two special cases.

- As $\rho = 1$, the problem reduces to the standard expected reward maximization problem.
- For $\rho = 0$, the problem transforms into a variance minimization problem.

3 RALCB Algorithm

In this section, we introduce our Risk-Aware Lower-Confidence Bound Algorithm (RALCB) and state our main results. To this end, we fix a parameter $\theta > 0$ that is a common sub-Gaussianity parameter for all arms. That is,

$$\mathbb{E}_{\mathbb{P}}[e^{\lambda(X_i - \mathbb{E}_{\mathbb{P}}[X_i])}] \le e^{\frac{\lambda^2 \theta^2}{2}} \tag{6}$$

holds for all $\lambda \in \mathbb{R}$ and $i \in \mathcal{A}$. In typical applications of the multi-armed bandit problem, the exact distribution of the arms will not be known in advance. We therefore emphasize that the parameter

 θ only needs to be some number such that (6) holds. In many situations, it will be possible to infer such an a priori bound by means of historical data or by functional bounds on the ranges of certain arms. We will see below that our bounds on the regret will improve when we are able to take a smaller θ , with the optimal lower bound given by

$$\theta^* := \inf\left\{\theta: \text{ for all } \lambda \in \mathbb{R} \text{ and } i \in \mathcal{A}, \mathbb{E}_{\mathbb{P}}\left[e^{\lambda\left(X_i - \mathbb{E}_{\mathbb{P}}[X_i]\right)}\right] \le e^{\frac{\lambda^2 \theta^2}{2}}\right\}.$$
(7)

For each arm i, we can define the empirical mean-variance with t samples as

$$\widehat{\mathrm{MV}}_{i,t}^{\rho} := (1-\rho)\widehat{\sigma}_{i,t}^2 - \rho\widehat{\mu}_{i,t},\tag{8}$$

where

$$\hat{\mu}_{i,t} := \frac{1}{t} \sum_{s=1}^{t} X_s^i, \qquad \hat{\sigma}_{i,t}^2 := \frac{1}{t} \sum_{s=1}^{t} (X_s^i - \hat{\mu}_{i,t})^2.$$
(9)

We furthermore define

$$\varphi(x) := 32(1-\rho)\theta^2 \max\left(\sqrt{x/2}, x\right) + (1-\rho)\theta^2 x + \rho\theta\sqrt{x}$$

and

$$V_{i,t-1}^{\text{RALCB}} := \widehat{\text{MV}}_{i,t-1}^{\rho} - \varphi\left(\frac{8\log(t)}{T_{i,t-1}}\right).$$
(10)

In comparison to the Mean-Variance Lower Confidence Bound Algorithm (MVLCB) introduced by Sani et al. (2012),

$$V_{i,t-1}^{\text{MVLCB}} = \widehat{\text{MV}}_{i,t-1}^{\rho} - (5+\rho) \sqrt{\frac{\log(1/\delta)}{T_{i,t-1}}},$$
(11)

our approach shares the same exploitation term but diverges in the exploration term. First, the exploration term of MVLCB is characterized by a parameter δ , depending upon the time horizon n. In contrast, our algorithm adopts a dynamic approach by updating the exploration term at each time step t. This adaptation enables us to discuss the asymptotic performance of the regret. Second, with a precise φ function, our algorithm can handle all sub-Gaussian random variables, whereas the exploration term in the MVLCB algorithm is only designed for bounded random variables taking values in [0, 1].

Furthermore, Zhao (2019) introduced a relevant algorithm addressing the mean-variance Multi-Armed Bandit (MAB) problem, termed the Mean-Variance Upper Confidence Bound Algorithm (MVUCB), under more restrictive underlying assumptions. It is based on the following index,

$$V_{i,t-1}^{\text{MVUCB}} = \widehat{\text{MV}}_{i,t-1}^{\rho} - b \sqrt{\frac{\log(t)}{T_{i,t-1}}}.$$
(12)

In their framework, the exploration term is updated over time, but they do not provide an explicit formulation for the policy parameter b.

Algorithm 1 Risk-Aware Lower-Confidence Bound Algorithm (RALCB)

```
1: Input: \theta, K, \rho.
 2: for each t = 1, 2, ..., K do
             Play arm \pi_t = t and observe X_1^{\pi_t}.
 3:
 4: end for
 5: Update \widehat{\mathrm{MV}}_{i,1}^{\rho} for i = 1, ..., K by Equation (8).
 6: Set T_{i,K} = 1 for i = 1, ..., K.
 7: for each t = K + 1, K + 2, ... do
             for each i = 1, 2, ..., K do
 8:
                     Compute V_{i,T_{i,t-1}}^{\text{RALCB}} = \widehat{\mathrm{MV}}_{i,T_{i,t-1}}^{\rho} - \varphi\left(\frac{8\log(t)}{T_{i,t-1}}\right).
 9:
10:
              end for
             Return \pi_t = \arg\min_{i=1,\dots,K} V_{i,T_{i,t-1}}^{\text{RALCB}}.
Update T_{i,t} = T_{i,t-1} + 1 for i = 1, \dots, K.
11:
12:
             Observe X_{T_i t}^{\pi_t}.
13:
             Update \widehat{\mathrm{MV}}_{i,T_{i,t}}^{\rho} by Equation (8).
14:
15: end for
```

Let us explain intuitively how the RALCB algorithm works. At each time t, the algorithm chooses an arm that minimizes the corresponding upper confidence index $V_{i,t-1}^{\text{RALCB}}$. That is, the algorithm chooses the policy response

$$\pi_t = \operatorname*{arg\,min}_{i=1,\dots,K} V_{i,t-1}^{\text{RALCB}} = \operatorname*{arg\,min}_{i\in\mathcal{A}} \left(\widehat{\mathrm{MV}}_{i,t-1}^{\rho} - \varphi\left(\frac{8\log(t)}{T_{i,t-1}}\right) \right).$$

Therefore, the arm i is selected by the algorithm in either of the following two scenarios:

- $\widehat{\mathrm{MV}}_{i,t-1}^{\rho}$ is small: the algorithm tends to exploit the best performer.
- $\varphi\left(\frac{8\log(t)}{T_{i,t-1}}\right)$ is large: the algorithm tends to explore alternative arms with insufficient observations.

3.1 Regret Analysis

3.1.1 Upper Bound Analysis

Theorem 3.1. Suppose that \mathcal{A}^0 is the set of optimal arms given by $\arg\min_{i\in\mathcal{A}} \mathrm{MV}_i^{\rho}$. The expected regret of the RALCB algorithm after n rounds can be upper bounded as:

$$\mathbb{E}[\mathcal{R}_n(\pi)] \le \frac{1}{n} \sum_{i \in \mathcal{A} \setminus \mathcal{A}^0} \left(\frac{8 \log(n)}{\varphi^{-1}(\Delta_i/2)} + 5 \right) \left(\Delta_i + 2\Gamma_{i,\max}^2 \right) + \frac{5}{n} \sum_{i=1}^K \sigma_i^2, \tag{13}$$

where
$$\Delta_i := \left(\sigma_i^2 - \sigma_{i_0^0}^2\right) - \rho\left(\mu_i - \mu_{i_0^0}\right), \Gamma_{i,\max} := \max\left\{|\mu_i - \mu_h| : h = 1, \dots, K\right\}, and$$

$$\varphi^{-1}(x) = \begin{cases} \left(\frac{-(\rho\theta + 16\sqrt{2}(1-\rho)\theta^2) + \sqrt{(\rho\theta + 16\sqrt{2}(1-\rho)\theta^2)^2 + 4(1-\rho)\theta^2}x}{2(1-\rho)\theta^2}\right)^2 & x \in [0, \frac{17}{2}(1-\rho)\theta^2 + \frac{\sqrt{2}}{2}\rho\theta), \\ \left(\frac{-\rho\theta + \sqrt{\rho^2\theta^2 + 132(1-\rho)\theta^2}x}{66(1-\rho)\theta^2}\right)^2 & x \in [\frac{17}{2}(1-\rho)\theta^2 + \frac{\sqrt{2}}{2}\rho\theta, \infty), \end{cases}$$

is the inverse function of the function φ defined in (6).

The regret upper bound presented by Sani et al. (2012) is a finite-time version due to its dependence on the confidence level δ , which requires that the number n of rounds is fixed from the beginning. As a result, their algorithm requires prior knowledge of n. In contrast, our paper adopts a dynamic approach by updating the confidence index at each time step t. This adaptation enables us to deal with scenarios where the horizon is not predetermined. It also allows us to discuss the asymptotic performance of the regret.

Remark 3.1. Based on the results in Theorem 3.1, we can notice that the upper bound of the expected regret decreases as $\mathcal{O}((\log(n))/n)$. Taking $n \to \infty$, the expected regret of the RALCB algorithm satisfies:

$$\lim_{n \to \infty} \mathbb{E}[\mathcal{R}_n(\pi)] = 0. \tag{14}$$

According to Definition 4.2 in Zhao (2019), the RALCB algorithm is hence a consistent policy. By substituting Equation (5) into Equation (14), we can obtain:

$$\lim_{n \to \infty} \mathbb{E}[\widehat{\mathrm{MV}}_{n}^{\rho}(\pi)] = \min_{i \in \mathcal{A}} \mathrm{MV}_{i}^{\rho}.$$
(15)

According to Equation (15), we can conclude that the expectation of the empirical mean-variance of the RALCB algorithm converges to the mean-variance of the optimal arms.

Remark 3.2. By examining the increasing function $\varphi(x)$, expressed as:

$$\varphi(x) = \begin{cases} 32(1-\rho)\theta^2\sqrt{x/2} + \rho\theta\sqrt{x} + (1-\rho)\theta^2 x & x \in \left[0, \frac{1}{2}\right) \\ 32(1-\rho)\theta^2 x + \rho\theta\sqrt{x} & x \in \left[\frac{1}{2}, \infty\right), \end{cases}$$

it is evident that $\varphi(x)$ is a decreasing function of θ if x is fixed. Thus, by substituting θ with a smaller $\tilde{\theta}$, the value $\varphi^{-1}(\Delta_i/2)$ increases, and in turn the upper bound (13) for the expected regret becomes tighter. The optimal bound is achieved for

$$\theta^* := \inf \left\{ \theta : \text{ for all } \lambda \in \mathbb{R} \text{ and } i \in \mathcal{A}, \mathbb{E}_{\mathbb{P}} \left[e^{\lambda \left(X_i - \mathbb{E}_{\mathbb{P}}[X_i] \right)} \right] \le e^{\frac{\lambda^2 \theta^2}{2}} \right\}.$$

We emphasize once again, though, that in typical applications the exact distributions of the arm will be unknown, which highlights the fact that our algorithm works with any a priori bound $\theta \geq \theta^*$.

Moreover, we can derive a high probability upper bound for the regret of the RALCB algorithm. **Theorem 3.2.** Suppose that \mathcal{A}^0 is the set of optimal arms given by $\arg\min_{i\in\mathcal{A}} MV_i^{\rho}$. With probability at least $1 - K/n^3$, the regret of the RALCB algorithm at time n is upper bounded by:

$$\mathcal{R}_{n}(\pi) \leq \frac{1}{n} \sum_{i \in \mathcal{A} \setminus \mathcal{A}^{0}} \left(\frac{8 \log(n)}{\varphi^{-1}(\Delta_{i}/2)} + 5 \right) \left(\Delta_{i} + 2\Gamma_{i,\max}^{2} \right) + \frac{\varphi\left(\frac{8K \log(n)}{n}\right)}{\theta} + \frac{16\sqrt{2}K\theta \log(n)}{n}.$$
(16)

Remark 3.3. For $\rho = 1$, the risk-averse MAB model simplifies to the classic risk-neutral MAB (i.e., a reward maximization problem). The index becomes:

$$V_{i,t-1}^{\text{RALCB}} = \widehat{\mu}_{i,t-1} + \theta \sqrt{\frac{8\log(t)}{T_{i,t-1}}}.$$

And, the regret upper bounds presented in Theorems 3.1 and 3.2 replicate the bounds on riskneutral regret, comparable to the regret achieved by Auer et al. (2002) who explored the UCB approach for Gaussian distributions.

For $\rho = 0$, the risk-averse MAB model transforms into the risk-focused MAB (i.e., a variance minimization problem). The index becomes:

$$V_{i,t-1}^{\text{RALCB}} = \hat{\sigma}_{i,t-1}^2 - 32\theta^2 \max\left(\sqrt{\frac{8\log(t)}{T_{i,t-1}}}, \frac{8\log(t)}{T_{i,t-1}}\right) - \theta^2 \frac{8\log(t)}{T_{i,t-1}}$$

The regret upper bounds, as provided in Theorems 3.1 and 3.2, produce comparable results achieved by Audibert et al. (2009) who explored the UCB approach for bounded random variables.

3.1.2 Drawing multiple arms

In contrast to many papers on multi-armed bandits, we do not assume that the individual arms are independent. A dependence between arms arises naturally, e.g., if we allow the learner to pull multiple arms at each round. Then, the K-armed problem is transformed into a P-armed problem, where P counts the total of possible arm combinations. As a result, we now have a new action set $\mathcal{A}^* := \{1, ..., P\}$. At time t, the reward Y_t^j of an arm $j \in \mathcal{A}^*$ is a convex combination of the rewards X_t^i of single arms. For example,

$$\begin{bmatrix} Y_t^1 \\ Y_t^2 \\ \vdots \\ Y_t^P \end{bmatrix} = \begin{bmatrix} w_{11} & w_{12} & \cdots & w_{1K} \\ w_{21} & w_{22} & \cdots & w_{2K} \\ \vdots & \vdots & \ddots & \vdots \\ w_{P1} & w_{P2} & \cdots & w_{PK} \end{bmatrix} \times \begin{bmatrix} X_t^1 \\ X_t^2 \\ \vdots \\ X_t^K \end{bmatrix},$$

where $w_{i,j} \in [0,1]$ and $\sum_{i \in \mathcal{A}} w_{i,j} = 1$ for all $i \in \{1, ..., K\}$ and $j \in \{1, ..., P\}$. The weights $w_{i,j}$ are specified at the start and fixed over rounds. We illustrate the above transformation in the following example:

Example 3.1. Starting with the 3-armed bandit problem (i.e., K = 3), we want to pull two arms at each round. The problem is then converted into a 3-armed bandit problem (i.e., P = 3). We assign equal weights to two arms in each combination (i.e., $w_{1,j} = w_{2,j} = 0.5$ for each j). Then we

have:

$$\begin{bmatrix} Y_t^1 \\ Y_t^2 \\ Y_t^2 \\ Y_t^2 \end{bmatrix} = \begin{bmatrix} 0.5 & 0.5 & 0 \\ 0.5 & 0 & 0.5 \\ 0 & 0.5 & 0.5 \end{bmatrix} \times \begin{bmatrix} X_t^1 \\ X_t^2 \\ X_t^3 \end{bmatrix}.$$

Theorem 2.7 in Rivasplata (2012) reveals a useful property of sub-Gaussian random variables:

Proposition 3.1. Let X and Y be sub-Gaussian random variables with parameters θ_X and θ_Y respectively. Then for any $w \in [0, 1]$, wX + (1 - w)Y is still a sub-Gaussian random variable with a parameter $w\theta_X + (1 - w)\theta_Y$.

The above proposition states that without an independence assumption, a convex combination of sub-Gaussian random variables is still sub-Gaussian but with an updated parameter. Therefore, our results can be used when the learner can pull more than one arm during each round.

Example 3.2. To demonstrate the limited impact of drawing multiple arms on the algorithm's performance, we conducted tests on the bandit problem with K = 3, where the arms are normally distributed and each pair of arms share the same correlation coefficients $\tau_{1,2} = \tau_{2,3} = \tau_{1,3} = 0.2$. The parameter settings for each arm are $\mu = (0.1, 0.41, 0.79)$ and $\sigma^2 = (0.05, 0.44, 0.85)$. Subsequently, we performed the bandit transformation based on the matrix outlined in Example 3.1 (i.e., P = 3). Presented below is the cumulative regret comparison between the two cases:



Figure 1: Cumulative regret comparison averaged over 1000 runs for RALCB algorithms before and after the transformation over different choices of $\tilde{\rho} := \rho/(1-\rho)$.

The presented results indicate that the algorithm's performance is minimally affected by the above transformation. This observation confirms the capability of our algorithm to effectively deal with pulling multiple arms.

4 Numerical Experiments

We perform a numerical analysis of our algorithm in this section. Vakili and Zhao (2016) analyze the risk-aware MAB problem, but the square of the underlying X is assumed to be sub-Gaussian

in their algorithm, making comparison with our results difficult. Zhu and Tan (2020) and Liu et al. (2021) propose two risk-averse MAB algorithms with a commitment to good numerical performance, although both algorithms are explicitly targeting Gaussian bandits. As a result, we use the MVLCB method proposed by Sani et al. (2012) as the benchmark for a fair comparison. Note that Sani et al. (2012) use the mean-variance functional

$$\mathrm{mv}_i^{\widetilde{\rho}} := \sigma_i^2 - \widetilde{\rho}\mu_i,$$

whose minimization is equivalent to the minimization of

$$\mathrm{MV}_{i}^{\rho} = (1-\rho)\sigma_{i}^{2} - \rho\mu_{i} = (1-\rho)\mathrm{mv}_{i}^{\rho}$$

if we let

$$\widetilde{\rho} := \frac{\rho}{1-\rho}$$

as long as $\rho \in [0, 1)$. To facilitate the comparison between our results and the ones in Sani et al. (2012), we will use $\tilde{\rho}$ as the risk aversion parameter throughout this section. A sketch of the MVLCB algorithm from Sani et al. (2012) is reported in Algorithm 2.

Algorithm 2 The Mean-Variance Lower Confidence Bound Algorithm (MVLCB)

```
1: Input: n, \theta, K, \tilde{\rho}.
 2: for each t = 1, 2, ..., K do
 3:
               Play arm \pi_t = t and observe X_1^{\pi_t}.
 4: end for
 5: Update \widehat{\mathrm{MV}}_{i,1}^{\rho} for i = 1, ..., K by Equation (8).
 6: Set T_{i,K} = 1 for i = 1, ..., K.
 7: for each t = K + 1, K + 2, ..., n do
               for each i = 1, 2, ..., K do
 8:
                      Compute V_{i,t-1}^{\text{MVLCB}} = \widehat{\text{MV}}_{i,t-1}^{\widetilde{\rho}} - (5+\widetilde{\rho})\sqrt{\frac{8\log(n)}{T_{i,t-1}}}.
 9:
10:
               end for
                \begin{array}{l} \text{Return } \pi_t = \arg\min_{i=1,...,K} V_{i,T_{i,t-1}}^{\text{MVLCB}}. \\ \text{Update } T_{i,t} = T_{i,t-1} + 1 \text{ for } i=1,...,K. \end{array} 
11:
12:
13:
               Observe X_{T_{i,t}}^{\pi_t}.
               Update \widehat{\mathrm{MV}}_{i,T_{i,t}}^{\rho} by Equation (8).
14:
15: end for
```

We report numerical simulations to validate our theoretical results in the previous sections. Here, we consider the bandit problem with K = 15 arms, where the reward of each arm is independent and follows a Gaussian distribution. The parameter setting for each arm is the same as the experiments from Sani et al. (2012), which guarantees that the observations lie in the interval [0, 1] with 95% confidence.

- $\mu = (0.1, 0.2, 0.23, 0.27, 0.32, 0.32, 0.34, 0.41, 0.43, 0.54, 0.55, 0.56, 0.67, 0.71, 0.79).$
- $\sigma^2 = (0.05, 0.34, 0.28, 0.09, 0.23, 0.72, 0.19, 0.14, 0.44, 0.53, 0.24, 0.36, 0.56, 0.49, 0.85).$

We compare the performance of two algorithms under three scenarios:

- Variance minimization: $\tilde{\rho} = 10^{-3}$, optimal arm is $i_0^{0.001} = 1$.
- Risk-return balance: $\tilde{\rho} = 1$, optimal arm is $i_0^1 = 11$.
- Reward maximization: $\tilde{\rho} = 10^3$, optimal arm is $i_0^{1000} = 15$.

4.1 Variance Minimization Scenario

In the variance minimization scenario (i.e., $\tilde{\rho} = 10^{-3}$), the optimal arm is $i_0^{0.001} = 1$. We run both algorithms over 1000 runs with a time horizon of n = 30000. In Figure 2, we record the pulls of arms at each time point for two algorithms.



Figure 2: Record of arms pulled at each time point in a single simulation for two algorithms under $\tilde{\rho} = 10^{-3}$.

From Figure 2, we can conclude that:

- 1. Under the RALCB algorithm, the optimal arm (i.e., $i_0^{0.001} = 1$) has been pulled more frequently than under the MVLCB algorithm.
- 2. In the long run, the RALCB algorithm starts picking the best arms consistently, with a small chance of exploration.
- 3. Under the variance minimization scenario, the MVLCB algorithm fails to identify the optimal arms.

In Figure 3, we present the cumulative regret and mean regret, which is averaged over 1000 runs with a time horizon of n = 30000.



Figure 3: Regret performance averaged over 1000 runs for two algorithms under $\tilde{\rho} = 10^{-3}$.

From Figure 3, we can conclude that:

- 1. The RALCB algorithm achieves a lower cumulative regret than the MVLCB algorithm. The cumulative regret of the RALCB algorithm goes flat faster than that of the MVLCB algorithm.
- 2. The RALCB algorithm outperforms the MVLCB algorithm in terms of mean regret. The decreasing rate of the mean regret for RALCB is higher than the one for MVLCB.

4.2 Risk-return Balance Scenario

In the risk-return balance scenario (i.e., $\tilde{\rho} = 1$), the optimal arm is $i_0^1 = 11$. We run both algorithms over 1000 runs with a time horizon of n = 30000. In Figure 4, we record the pulls of arms at each time point for two algorithms.



Figure 4: Record of arms pulled at each time point in a single simulation for two algorithms under $\tilde{\rho} = 1$.

We can deduce from Figure 4 that:

1. The optimal arm (i.e., $i_0^1 = 11$) has been pulled more frequently under the RALCB algorithm than under the MVLCB algorithm.

- 2. In the long run, the RALCB algorithm can find the best arms with a low chance of picking suboptimal arms with the same mean-variance.
- 3. Under the risk-return balance scenario, the MVLCB algorithm fails to identify the optimal arms.

In Figure 5, we present the cumulative regret and mean regret, which is averaged over 1000 runs with a time horizon of n = 30000.



Figure 5: Regret performance averaged over 1000 runs for two algorithms under $\tilde{\rho} = 1$.

From Figure 5, we can conclude that:

- 1. The RALCB algorithm achieves a lower cumulative regret than the MVLCB algorithm.
- 2. The RALCB algorithm outperforms the MVLCB algorithm in terms of mean regret. The decreasing rate of the mean regret for RALCB is higher than the one for MVCLB.

4.3 Reward Maximization Scenario

In the reward maximization scenario (i.e., $\tilde{\rho} = 10^3$), the optimal arm is $i_0^{1000} = 15$. We run both algorithms over 1000 runs with a time horizon of n = 30000. In Figure 6, we record the pulls of arms at each time point for two algorithms.



Figure 6: Record of arms pulled at each time point in a single simulation for two algorithms under $\tilde{\rho} = 10^3$.

From Figure 6, we can conclude that:

1. In the long run, both algorithms can identify the optimal arms with a small probability of exploration.

In Figure 7, we present the cumulative regret and mean regret, which is averaged over 1000 runs with a time horizon of n = 30000.



Figure 7: Regret performance averaged over 1000 runs for two algorithms under $\tilde{\rho} = 10^3$.

From Figure 7, we can conclude that:

- 1. Two algorithms perform similarly, with a high cumulative regret.
- 2. The RALCB algorithm slightly outperforms the MVLCB algorithm in terms of mean regret. The decreasing rate of the mean regret for RALCB is similar to the one for MVCLB.

4.4 Algorithm Evaluation and Comparison

In order to validate our algorithms further and to observe how they perform in terms of $\tilde{\rho}$, we ran our algorithms with different choices of $\tilde{\rho}$:

 $\widetilde{\rho} = (0, 0.001, 0.01, 0.1, 0.3, 1, 3, 5, 7, 10, 20, 50, 100, 1000, 10000).$

The time horizon n = 10000 is fixed, and the regret is averaged over 1000 runs. We record the total number of pulls for each arm by time n for two algorithms in Figure 8.

MVLCB Algorithm															
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
rho=0	4363	1637	2104	3730	2295	804	2682	3083	1375	1138	2233	1650	1066	1133	707
rho=0.001	4285	1846	2015	3680	2316	772	2624	3085	1313	1084	2312	1743	3 1082	1211	632
rho=0.01	4299	1677	2069	3669	2410	788	2647	3093	1374	1099	2292	1683	3 1149	1181	570
rho=0.1	3849	1689	1930	3581	2370	877	2538	3178	1404	1164	2446	1757	1170	1338	709
rho=0.3	3208	1526	1780	3349	2307	827	2638	3219	1491	1206	2608	1925	5 1364	1663	889
rho=1	1730	1195	1410	2361	2003	754	2225	3117	1493	1601	3454	2319	2016	2737	1585
rho=3	632	597	725	1058	1109	661	1143	1756	1127	1827	3230	2664	3605	6164	3702
rho=10	195	282	282	348	392	348	400	608	525	1015	1349	1760	3692	5136	13668
rho=100	93	153	130	140	247	163	178	266	294	432	612	458	3 1673	3965	21196
rho=1000	79	95	140	152	230	129	170	212	297	548	589	513	3 2046	2110	22690
DAL CD 41															
KALCE ALGO	orithm	1													
KALCB ALGO	1	1 23		4 5	6	7	7	89	10	11	12	13	1	4 :	15
rho=0	1 27443	1 2 3 110	152	4 5 763	6 206	68	222	89 374	10 85	11 60	12 189	13 106	1. 90	4 : 74	L5 58
rho=0 rho=0.001	27443 27049	1 2 3 5 110 9 101	152 202	4 5 763 1104	6 206 156	7 68 56	7 222 254	8 9 374 441	10 85 99	11 60 67	12 189 178	13 106 120	90 63	1 : 74 65	L5 58 45
rho=0 rho=0.001 rho=0.01	27443 27049 27055	2 3 110 101 87	152 202 220	4 5 763 1104 1156	6 206 156 158	68 56 62	7 222 254 171	8 9 374 441 381	10 85 99 85	11 60 67 69	12 189 178 224	13 106 120 144	14 90 63 62	1 : 74 65 89	L5 58 45 37
rho=0 rho=0.001 rho=0.01 rho=0.1	1 27443 27049 27055 24778	2 3 110 101 87 164	152 202 220 189	4 5 763 1104 1156 2336	6 206 156 158 276	68 56 62 77	222 254 171 428	8 9 374 441 381 824	10 85 99 85 81 1	11 60 67 69 07	12 189 178 224 353	13 106 120 144 139	90 63 62 98	1 : 74 65 89 99	15 58 45 37 51
rho=0 rho=0.001 rho=0.01 rho=0.1 rho=0.3	1 27443 27049 27055 24778 5634	1 2 3 110 101 87 164 206	152 202 220 189 352	4 5 763 1104 1156 2336 12891	6 206 156 158 276 564	68 56 62 77 102	222 254 171 428 764	8 9 374 441 381 824 7041	10 85 99 85 81 1 172 1	11 60 67 69 07 28_1	12 189 178 224 353 403	13 106 120 144 139 280	90 63 62 98 146	4 74 65 89 99 231	L5 58 45 37 51 86
rho=0 rho=0.001 rho=0.01 rho=0.1 rho=0.3 rho=1	1 27443 27049 27055 24778 5634 652	2 3 110 101 87 164 206 2314	152 202 220 189 352 454	4 5 763 1104 1156 2336 12891 1460	6 206 156 158 276 564 912	68 56 62 77 102 130	222 254 171 428 764 1072	8 9 374 441 381 824 7041 6104	10 85 99 85 81 1 172 1 423 4	11 60 67 69 07 28 1 53 14	12 189 178 224 353 403 078 1	13 106 120 144 139 280 410	90 63 62 98 146 570	4 74 65 89 99 231 1761	15 58 45 37 51 86 207
RALCB Algo rho=0.001 rho=0.01 rho=0.1 rho=0.3 rho=1 rho=3	1 27443 27049 27055 24778 5634 652 180	3 110 101 87 164 206 314 178	152 202 220 189 352 454 278	4 5 763 1104 1156 2336 12891 1460 373	6 206 156 158 276 564 912 337	68 56 62 77 102 130 177	222 254 171 428 764 1072 463	8 9 374 441 381 824 7041 6104 656	10 85 99 85 81 1 172 1 423 4 401 8	11 60 67 69 07 28 1 53 14 82 2	12 189 178 224 353 403 078 1 576	13 106 120 144 139 280 410 873 3	90 63 62 98 146 570 3331 1	4 74 65 89 99 231 1761 5724	15 58 45 37 51 86 207 3571
rho=0 rho=0.001 rho=0.01 rho=0.1 rho=0.3 rho=1 rho=3 rho=10	1 27443 27049 27055 24778 5634 652 180 111	2 3 110 101 87 164 206 314 178 117	152 202 220 189 352 454 278 132	4 5 763 1104 1156 2336 12891 1460 373 178	6 206 156 158 276 564 912 337 174	68 56 62 77 102 130 177 172	222 254 171 428 764 1072 463 204	8 9 374 441 381 824 7041 6104 656 290	10 85 99 85 81 1 172 1 423 4 401 8 346 3	11 60 67 69 07 28 1 53 14 82 2 03	12 189 178 224 353 403 078 1 576 831	13 106 120 144 139 280 410 873 3 685 1	90 63 62 98 146 570 3331 1	4 74 65 89 99 231 1761 5724 5178	L5 58 45 37 51 86 207 3571 19377
rho=0 rho=0.001 rho=0.01 rho=0.1 rho=0.3 rho=1 rho=3 rho=10 rho=100	1 27443 27049 27055 24778 5634 652 180 111 65	2 3 110 101 87 164 206 314 178 117 5 77	152 202 220 189 352 454 278 132 122	4 5 763 1104 1156 2336 12891 1460 373 178 124	6 206 156 158 276 564 912 337 174 116	68 56 62 77 102 130 177 172 119	222 254 171 428 764 1072 463 204 139	8 9 374 441 381 824 7041 6104 656 290 223	10 85 99 85 81 1 172 1 423 4 401 8 346 3 284 4	11 60 67 69 07 28 1 53 14 82 2 03 30	12 189 178 224 353 403 078 1 576 831 523	13 106 120 144 139 280 410 873 3 685 1 658 1	90 63 62 98 146 570 3331 1 902 663	4 74 65 89 99 231 1761 5724 5178 2720	L5 58 45 37 51 86 207 3571 19377 22737

Figure 8: Record of total arms pulled in a single simulation by two algorithms under different $\tilde{\rho}$. The highlighted ones are the optimal arms under each $\tilde{\rho}$.

From Figure 8, we can conclude that:

- 1. Under all different $\tilde{\rho}$, the RALCB algorithm pulls the optimal arms more frequently than the MVLCB algorithm.
- 2. Both algorithms can distinguish the optimal arms from suboptimal arms better when $\tilde{\rho}$ is small.

We report the cumulative regrets in Figure 9,



Figure 9: Cumulative regret comparison averaged over 1000 runs for two algorithms over different choices of $\tilde{\rho}$.

From Figure 9, we observe the outperformance of RALCB over MVLCB when $\tilde{\rho}$ is small. But, the performance gap narrows as $\tilde{\rho}$ increases.

It is evident from Theorem 3.2 that when the number of arms, K, is large, the regret bound increases. To empirically examine this correlation between average regret and the growing number of arms, we conducted a numerical test. Every arm in the simulation is considered to be an independent Gaussian arm with different parameters. The results, depicted in Figure 10, indicate that the average regret will increase with the number of arms K and this observed relationship demonstrates a nearly linear correlation. Such a pattern is consistent in both the risk-neutral case (Auer et al. (2002)) and the risk-aware case (Sani et al. (2012)). This trend holds true as the upper bounds of the expected regret are linear in the number of arms.



Figure 10: Average regret comparison averaged over 1000 runs for RALCB algorithms over different choices of K. In the graph, the solid line signifies the average regret derived from the simulation, while the dashed line represents the corresponding theoretical regret for different values of K.

Remark 4.1. Section 3.1.2 illustrates that our algorithm can be used to analyze the dependent case.

However, analyzing correlations among arms is impossible in our current setting, where only one arm is pulled in each round. There is no way to exploit the correlation among arms without altering the underlying model setup (i.e. additional information regarding the prior structure and multiple arms are pulled simultaneously).

Under the dependent scenario, we compare the performance of our algorithm over different choices of correlation coefficients (i.e., we use $\tau_{i,j}$ to denote the correlation coefficients between arm *i* and arm *j*). As a starting point, we assume each pair of arms share the same correlation coefficients (i.e., $\tau_{i,j} = \tau$, $\forall i, j$). We are working on analyzing the performance changes as the correlations increase, where

$$\tau = (-0.5, -0.2, 0, 0.2, 0.5, 1).$$

Figure 11 illustrates the influence of correlation τ on the performance of the RALCB algorithm under different risk aversion $\tilde{\rho}$ parameters.



(a) Cumulative regret over different τ (b) Cumulative regret comparison over different $\tilde{\rho}$

Figure 11: Cumulative regret comparison over different choices of τ and $\tilde{\rho}$.

Based on Figure 11, it is evident that our algorithm consistently yields identical cumulative regret across various dependent scenarios. Without further information on the underlying structure or modifying the model setup, the examination of correlations among arms is unfeasible using our algorithm. The extension to examine correlated arms is left to future work.

The numerical simulations discussed so far where all based on synthetic data sampled from standard classes of distributions. In the sequel, our goal is to illustrate the robustness of our algorithm by applying it to real-world data with unknown distributions. To this end, we choose financial data due to its wide availability. We emphasize, however, that financial data is publicly available, so that portfolio construction is typically not an application area for MAB algorithms, which inherently assume that the reward is only revealed for that arm that is drawn while the rewards of all other arms remain hidden. So the purpose of the following numerical experiments is solely the illustration of the robustness of our algorithm. We design experiments and evaluate the performance of our proposed algorithm (i.e., the RALCB algorithm) in portfolio selection to the performance of UCB algorithm, the ε -greedy algorithm and equally weighted (EW) strategy. In

the experiment, we implement actual stock market data to test the performance of the above four algorithms. The dataset we use is S&P500, which is the most frequent trading stock market data. We select 30 stocks from the S&P500 stock pool based on size, age, and earning per share: AAPL, MSFT, UNH, JNJ, XOM, PNR, AIG, VNO, DISH, NWL, BK, STT, CL, HIG, ED, CMA, ALL, AMAT, BSX, MU, HAL, RCL, CCL, APA, HRL, AEE, FAST, TRMB, NWL, AFL. In our dataset, we have weekly observations of all 30 ETFs over the time period 1996/02/26 to 2021/02/26.

Figure 12 presents the change in portfolio wealth by following different algorithms over time. We notice that when the market turns down during the middle of the timeline, wealth for MAB-based algorithms drops dramatically. The main reason is that MAB-based algorithms must spend time learning new parameters because the underlying parameters estimated from the history are no longer valid. Overall, the RALCB algorithm achieves the best long-term performance and the highest wealth at the end.



Figure 12: The curves of cumulative wealth across the investment periods (1996-2021) for different algorithms.

To compare the performance of four investment algorithms, we use the standard criteria in finance proposed by Zhu et al. (2019): Cumulative Wealth (CW), Volatility (VO), Sharpe Ratio (SR) and Maximum Drawdown (MDD).

Table 1 summarizes portfolio performance as measured by the SR, CW, and VO for all benchmarks tested, with the bold values indicating the winners. The risk-free (Rf) rate, which is based on the historical average of the 10-Year Treasury Rate, is assumed to be 4.38% yearly for generating the SR. Among all algorithms, RALCB algorithm is the one with the highest cumulative wealth. However, EW does a better job of risk-return balancing than RALCB. The main reason is that the RALCB algorithm only permits the investment of one stock per period, which naturally increases the portfolio's volatility.

1996-2021	UCB	RALCB	ε -greedy	EW
CW	2.3579	7.4988	2.4741	7.3485
VO	0.3777	0.2926	0.3151	0.1921
SR (Rf=4.38%)	-0.0784	0.1480	-0.0490	0.7330
MDD	0.9191	0.7432	0.3648	0.2978

Table 1: Performance of four different algorithms on real data. RALCB outperforms the other algorithms in terms of wealth accumulation. EW does a better job of risk-return balancing than RALCB.

In our next application, the arms consist of the following S&P 500 sector ETFs: GDX, IBB, ITB, IYE, IYR, KBE, KRE, OIH, SMH, VNQ, XHB, XLB, XLF, XLI, XLK, XLP, XLU, XLV, XLY, XME, XOP, XRT. In our dataset, we have daily observations of all 22 ETFs over the time period 2006/06/22 to 2022/11/18.

Figure 13 presents the change in portfolio wealth by following different algorithms over time. We notice that, by investing in ETFs, the RALCB algorithm achieves better long-term performance than the other algorithms.



Figure 13: The curves of cumulative wealth across the investment periods (2006-2022) for different algorithms.

Again, we use the standard criteria in finance proposed by Zhu et al. (2019) to compare the

performance of four investment algorithms:

2006-2022	UCB	RALCB	ε -greedy	EW
CW	2.5629	4.8620	2.1932	3.7621
VO	0.1004	0.0824	0.1444	0.1056
SR (Rf=4.38%)	-0.2771	-0.1396	-0.2205	-0.2190
MDD	0.6579	0.4213	0.6588	0.5616

Table 2: Performance of four different algorithms on ETFs investment. RALCB outperforms the other algorithms in terms of all financial criteria.

Table 2 summarizes portfolio performance as measured by the SR, CW, and VO for all benchmarks tested, with the bold values indicating the winners. The risk-free (Rf) rate is again assumed to be 4.38% yearly.

5 Proofs

This section consists of two parts. First, we derive the high-probability confidence bounds on the empirical mean-variance through an application of the Chernoff–Hoeffding inequality. In the second part, we report a complete analysis of the learning regret of the RALCB algorithm. Unless otherwise stated, all identities and inequalities between random variables are stated in \mathbb{P} -a.s. in the following proofs.

5.1 Concentration Analysis

To derive a high-probability bound on the expected pseudo regret, we will build high-probability confidence bounds on the empirical mean and variance through an application of the Chernoff-Hoeffding inequality. Recall that we assume that the rewards of each arm belong to the class of sub-Gaussian random variables. Therefore, we analyze the concentration of empirical mean and variance via sub-Gaussian and sub-exponential distributions. In this section, we let $\{X_t\}_{t\geq 0}$ be i.i.d. sub-Gaussian random variables with mean μ , variance σ^2 , and sub-Gaussianity parameter θ . We start by providing a concentration bound for the empirical mean $\hat{\mu}_n := \frac{1}{n} \sum_{t=1}^n X_t$.

Lemma 5.1. For every n > 0 and $\delta \in (0, 1)$, with probability at least $1 - \delta$,

$$|\hat{\mu}_n - \mu| \le \theta \sqrt{\frac{2\log(2/\delta)}{n}}.$$
(17)

Proof. According to Markov's inequality and (1), we have for $a \ge 0$ and all $\lambda > 0$,

$$\mathbb{P}[|\hat{\mu}_n - \mu| \ge a] \le \mathbb{P}\left[e^{-\lambda \sum_{t=1}^n (X_t - \mu)} \ge e^{\lambda na}\right] + \mathbb{P}\left[e^{\lambda \sum_{t=1}^n (X_t - \mu)} \ge e^{\lambda na}\right] \le 2e^{\frac{1}{2}\lambda^2 \theta^2 - \lambda na} \le 2e^{-na^2/(2\theta^2)}.$$

The result thus follows by taking $\delta = 2e^{-na^2/(2\theta^2)}$.

Now we derive a concentration inequality for the sample variance $\hat{\sigma}_n^2 := \frac{1}{n} \sum_{t=1}^n (X_t - \hat{\mu}_n)^2$. Its proof uses the notion of sub-exponential random variables. Recall that a random variable Z is called sub-exponential with parameter $\gamma > 0$ if $\mathbb{E}[Z] = 0$ and $\mathbb{E}[e^{sZ}] \leq e^{s^2 \gamma^2/2}$ for all $s \in \mathbb{R}$ with $|s| \leq 1/\gamma$; see, e.g., Wainwright (2019) and Rigollet and Hütter (2015).

Lemma 5.2. For every n > 0 and $\delta \in (0, 1)$, we have that with probability at least $1 - \delta$,

$$\left|\hat{\sigma}_n^2 - \sigma^2 + (\hat{\mu}_n - \mu)^2\right| \le 32\theta^2 \max\left(\sqrt{\frac{\log(2/\delta)}{n}}, \frac{2\log(2/\delta)}{n}\right).$$
(18)

Proof. We may assume without loss of generality that $\mu = 0$. Lemma 1.12 in Rigollet and Hütter (2015) states that $Z_t := X_t^2$ is sub-exponential with parameter $16\theta^2$. An application of Proposition 2.9 in Wainwright (2019) hence yields that

$$\mathbb{P}\left(\left|\frac{1}{n}\sum_{i=1}^{n}(X_{i})^{2}-\sigma^{2}\right|>a\right)\leq2\exp\left(-\frac{n}{2}g(a)\right),$$
(19)

where $g(a) := \min(\frac{a^2}{512\theta^4}, \frac{a}{32\theta^2})$. Moreover,

$$\left|\frac{1}{n}\sum_{i=1}^{n} (X_i)^2 - \sigma^2\right| = \left|\hat{\sigma}_n^2 - \sigma^2 + \hat{\mu}_n^2\right|.$$

Therefore, we have,

$$\mathbb{P}\left(\left|\hat{\sigma}_{n}^{2}-\sigma^{2}+\hat{\mu}_{n}^{2}\right|>a\right)\leq2\exp\left(-\frac{n}{2}g(a)\right).$$
(20)

By setting $\delta := 2 \exp\left(-\frac{n}{2}g(a)\right)$ and writing a in terms of δ on the left side of the inequality (20), we obtain:

$$\mathbb{P}\left(\left|\hat{\sigma}_{n}^{2} - \sigma^{2} + \hat{\mu}_{n}^{2}\right| > 32\theta^{2} \max\left(\sqrt{\frac{\log(2/\delta)}{n}}, \frac{2\log(2/\delta)}{n}\right)\right) \le \delta.$$
(21)

Alternatively, with a probability of at least $1 - \delta$,

$$\left|\hat{\sigma}_{n}^{2} - \sigma^{2} + (\hat{\mu}_{n} - \mu)^{2}\right| \leq 32\theta^{2} \max\left(\sqrt{\frac{\log(2/\delta)}{n}}, \frac{2\log(2/\delta)}{n}\right).$$

In our analysis, we assume the rewards of each arm belong to the class of sub-Gaussian random variables with different parameters. With Lemma 5.1 and Lemma 5.2, we can construct the following concentration inequality on the empirical mean-variance $\widehat{\mathrm{MV}}_n^{\rho} := (1-\rho)\hat{\sigma}_n^2 - \rho\hat{\mu}_n$, where the true mean-variance defined as $\mathrm{MV}^{\rho} := (1-\rho)\sigma^2 - \rho\mu$.

Lemma 5.3. Then, for every n > 0 and $\delta \in (0, 1)$, we have that with probability at least $1 - \delta$,

$$\left|\widehat{\mathrm{MV}}_{n}^{\rho} - \mathrm{MV}^{\rho}\right| \leq \varphi\left(\frac{2\log(2/\delta)}{n}\right),\tag{22}$$

where,

$$\varphi(x) := 32\theta^2 \max\left(\sqrt{x/2}, x\right) + \theta^2 x + \rho \theta \sqrt{x}/(1-\rho).$$

Proof. Let

$$A_n := \left\{ |\hat{\mu}_n - \mu| \le \theta \sqrt{\frac{2\log(2/\delta)}{n}} \right\},\,$$

and

$$B_n := \left\{ \left| \hat{\sigma}_n^2 - \sigma^2 + (\hat{\mu}_n - \mu)^2 \right| \le 32\theta^2 \max\left(\sqrt{\frac{\log(2/\delta)}{n}}, \frac{2\log(2/\delta)}{n}\right) \right\}.$$

By Lemma 5.1 and 5.2, we have $\mathbb{P}(A) \ge 1 - \delta$ and $\mathbb{P}(B) \ge 1 - \delta$. Now, we define

$$C_n := \left\{ \left| \widehat{\mathrm{MV}}_n^{\rho} - \mathrm{MV}^{\rho} \right| \le \varphi \left(\frac{2 \log(2/\delta)}{n} \right) \right\}.$$

According to the triangle inequality, we have:

$$\begin{split} \left| \widehat{\mathrm{MV}}_{n}^{\rho} - \mathrm{MV}^{\rho} \right| &\leq (1 - \rho) \left| \hat{\sigma}_{n}^{2} - \sigma^{2} \right| + \rho |\hat{\mu}_{n} - \mu| \\ &\leq (1 - \rho) \left| \hat{\sigma}_{n}^{2} - \sigma^{2} + (\hat{\mu}_{n} - \mu)^{2} \right| + (1 - \rho)(\hat{\mu}_{n} - \mu)^{2} + \rho |\hat{\mu}_{n} - \mu|. \end{split}$$

As a result, $A_n \cap B_n \subseteq C_n$. Therefore, we have:

$$\mathbb{P}\left[C_{n}^{c}\right] \leq \mathbb{P}\left[C_{n}^{c}\right] \leq \mathbb{P}\left[A_{n}^{c} \cup B_{n}^{c}\right] \leq \mathbb{P}\left[A_{n}^{c}\right] + \mathbb{P}\left[B_{n}^{c}\right] \leq \delta.$$

5.2	Regret	Analysis
0.4	regree	Allarysis

.

5.2.1 Expected Regret

Given the definition of regret in Equation (5), Sani et al. (2012) derived the following upper bound for the regret. For $i_0^{\rho} \in \arg\min_{i \in \mathcal{A}} \mathrm{MV}_i^{\rho}$, $\widehat{\Delta}_i := (1 - \rho) \left(\hat{\sigma}_{i,n}^2 - \sigma_{i_0}^2 \right) - \rho \left(\hat{\mu}_{i,n} - \mu_{i_0^{\rho}} \right)$, and $\widehat{\Gamma}_{i,h} := |\hat{\mu}_{i,n} - \hat{\mu}_{h,n}|$. With probability 1, the regret for a learning algorithm π_t over *n* rounds can be bounded as follows,

$$\mathcal{R}_n(\pi) \le \frac{1}{n} \sum_{i=1}^K T_{i,n} \widehat{\Delta}_i + \frac{1}{n^2} \sum_{i=1}^K \sum_{h \ne i} T_{i,n} T_{h,n} \widehat{\Gamma}_{i,h}^2.$$

$$(23)$$

This result applies to any strategies addressing the mean-variance Multi-Armed Bandit (MAB) problem, including the RALCB algorithm. The right-hand side of (23) consists of two main components. The first term reflects regret as the difference in mean-variance between the best arm and the suboptimal arms. The second term represents exploration risk, being a weighted variance of the means. Excessive exploration increases regret, while consistently pulling a single arm eliminates exploration risk, though it may be suboptimal in terms of overall regret.

The upper bound (23) suggests that a bound on the pulls is sufficient to bound the regret. Subsequently, by computing expectations on both sides, as outlined in Zhu and Tan (2020), we obtain:

$$\mathbb{E}[\mathcal{R}_n(\pi)] \le \frac{1}{n} \sum_{i \in \mathcal{A} \setminus \mathcal{A}^0} \mathbb{E}[T_{i,n}](\Delta_i + 2\Gamma_{i,\max}^2) + \frac{5}{n} \sum_{i=1}^K \sigma_i^2,$$
(24)

where $\Delta_i := (1-\rho) \left(\sigma_i^2 - \sigma_{i_0^\rho}^2\right) - \rho \left(\mu_i - \mu_{i_0^\rho}\right)$, $\Gamma_{i,\max} := \max \left\{ |\mu_i - \mu_h| : h = 1, \ldots, K \right\}$ and \mathcal{A}^0 is the set of optimal arms given by $\arg \min_{i \in \mathcal{A}} \mathrm{MV}_i^{\rho}$. This result also holds true for any strategies dealing with the mean-variance Multi-Armed Bandit (MAB) problem, including the RALCB algorithm. Equation (24) shows that to recover a bound on the expected regret, it suffices to bound the number of pulls of each suboptimal arm. Following an idea of Sani et al. (2012), we now derive an upper bound for the number of pulls in expectation.

Lemma 5.4. Suppose that $i_0^{\rho} \in \arg\min_{i \in \mathcal{A}} \mathrm{MV}_i^{\rho}$. The expected number of pulls of any suboptimal arm $i \neq i_0^{\rho}$ in RALCB can be upper bounded by

$$\mathbb{E}\left[T_{i,n}\right] \le \frac{8\log(n)}{\varphi^{-1}(\Delta_i/2)} + 5,\tag{25}$$

where n > 0 and φ^{-1} is the inverse function of φ and is given by

$$\varphi^{-1}(x) = \begin{cases} \left(\frac{-(\rho\theta + 16\sqrt{2}\theta^2) + \sqrt{(\rho\theta + 16\sqrt{2}\theta^2)^2 + 4\theta^2 x}}{2\theta^2}\right)^2 & x \in [0, \frac{17}{2}\theta^2 + \frac{\sqrt{2}}{2}\rho\theta), \\ \left(\frac{-\rho\theta + \sqrt{\rho^2\theta^2 + 132\theta^2 x}}{66\theta^2}\right)^2 & x \in [\frac{17}{2}\theta^2 + \frac{\sqrt{2}}{2}\rho\theta, \infty). \end{cases}$$

Proof. Let i be a suboptimal arm and ℓ be an arbitrary positive integer.

$$T_{i,n} = 1 + \sum_{t=K+1}^{n} \mathbb{1}_{\{\pi_t = i\}}$$

$$\leq \ell + \sum_{t=\ell+1}^{n} \mathbb{1}_{\{\pi_t = i, T_{i,t} \geq \ell\}}$$

$$= \ell + \sum_{t=\ell+1}^{n} \mathbb{1}_{\{V_{i,t}^{\text{RALCB}} \leq V_{i_0^{P,t}}^{\text{RALCB}}, T_{i,t} \geq \ell\}}.$$

In the above, with setting $\delta := 2/t^4$:

$$\begin{split} \mathbb{1}_{\left\{V_{i,t}^{\text{RALCB}} \leq V_{i_{0}^{\rho},t}^{\text{RALCB}}, T_{i,t} \geq \ell\right\}} &= \mathbb{1}_{\left\{\widehat{\text{MV}}_{i,T_{i,t}}^{\rho} - \varphi\left(\frac{8\log(t)}{T_{i,t}}\right) \leq \widehat{\text{MV}}_{i_{0}^{\rho},T_{i_{0}^{\rho},t}}^{\rho} - \varphi\left(\frac{8\log(t)}{T_{i_{0}^{\rho},t}}\right), T_{i,t} \geq \ell\right\}} \\ &\leq \mathbb{1}_{\left\{\min_{\ell \leq m \leq t} \widehat{\text{MV}}_{i,m}^{\rho} - \varphi\left(\frac{8\log(t)}{m}\right) \leq \max_{0 < h \leq t} \widehat{\text{MV}}_{i_{0}^{\rho},h}^{\rho} - \varphi\left(\frac{8\log(t)}{h}\right)\right\}} \\ &\leq \sum_{h=1}^{t} \sum_{m=\ell}^{t} \mathbb{1}_{\left\{\widehat{\text{MV}}_{i,m}^{\rho} - \varphi\left(\frac{8\log(t)}{m}\right) \leq \widehat{\text{MV}}_{i_{0}^{\rho},h}^{\rho} - \varphi\left(\frac{8\log(t)}{h}\right)\right\}} \end{split}$$

Consider that $\widehat{\mathrm{MV}}_{i,m}^{\rho} - \varphi\left(\frac{8\log(t)}{m}\right) - \widehat{\mathrm{MV}}_{i_0^{\rho},h}^{\rho} + \varphi\left(\frac{8\log(t)}{h}\right)$ can be expressed as the sum of three terms:

$$\begin{split} \widehat{\mathrm{MV}}_{i,m}^{\rho} &- \varphi \left(\frac{8 \log(t)}{m} \right) - \widehat{\mathrm{MV}}_{i_{0}^{\rho},h}^{\rho} + \varphi \left(\frac{8 \log(t)}{h} \right) \\ &= \left(\widehat{\mathrm{MV}}_{i,m}^{\rho} + \varphi \left(\frac{8 \log(t)}{m} \right) - \mathrm{MV}_{i}^{\rho} \right) - \left(\widehat{\mathrm{MV}}_{i_{0}^{\rho},h}^{\rho} - \varphi \left(\frac{8 \log(t)}{h} \right) - \mathrm{MV}_{i_{0}^{\rho}}^{\rho} \right) \\ &+ \left(\mathrm{MV}_{i}^{\rho} - \mathrm{MV}_{i_{0}^{\rho}}^{\rho} - 2\varphi \left(\frac{8 \log(t)}{m} \right) \right). \end{split}$$

For $m \ge \ell$ and $\ell = \left\lceil \frac{8 \log(t)}{\varphi^{-1}(\Delta_i/2)} \right\rceil$, the last term above is positive. Therefore,

$$T_{i,n} \leq \ell + \sum_{t=\ell+1}^{n} \sum_{h=1}^{t} \sum_{m=\ell}^{t} \mathbb{1}_{\left\{\widehat{\mathrm{MV}}_{i,m}^{\rho} + \varphi\left(\frac{8\log(t)}{m}\right) - \mathrm{MV}_{i}^{\rho} \leq 0\right\}} + \sum_{t=\ell+1}^{n} \sum_{h=1}^{t} \sum_{m=\ell}^{t} \mathbb{1}_{\left\{\widehat{\mathrm{MV}}_{i_{0}}^{\rho}, h} - \varphi\left(\frac{8\log(t)}{h}\right) - \mathrm{MV}_{i_{0}}^{\rho} \geq 0\right\}}$$

Set $\delta := 2/t^4$, provided that $t \ge 2$. Note that or each arm $i, X_1^i, ..., X_m^i$ are i.i.d. sub-Gaussian random variables with mean μ_i and variance σ_i^2 . Hence we may apply Lemma 5.3, which yields that

$$\mathbb{P}\left[\widehat{\mathrm{MV}}_{i,m}^{\rho} + \varphi\left(\frac{8\log(t)}{m}\right) - \mathrm{MV}_{i}^{\rho} \le 0\right] \le 2/t^{4}.$$

Similarly, we have

$$\mathbb{P}\left[\widehat{\mathrm{MV}}_{i_0^{\rho},h}^{\rho} - \varphi\left(\frac{8\log(t)}{h}\right) - \mathrm{MV}_{i_0^{\rho}}^{\rho} \ge 0\right] \le 2/t^4.$$

Hence,

$$\mathbb{E} \left[T_{i,n} \right] \leq \ell + 2 \sum_{t=\ell+1}^{n} \sum_{h=1}^{t} \sum_{m=\ell}^{t} 2/t^{4}$$
$$\leq \frac{8 \log(n)}{\varphi^{-1}(\Delta_{i}/2)} + 1 + 4 \int_{\ell}^{\infty} t^{-2} dt$$
$$= \frac{8 \log(n)}{\varphi^{-1}(\Delta_{i}/2)} + 1 + 4\ell^{-1}$$
$$\leq \frac{8 \log(n)}{\varphi^{-1}(\Delta_{i}/2)} + 5.$$

The last inequality holds because each arm has at least been pulled once.

5.2.2 High Probability Regret

Consider $X_1^i, ..., X_t^i$ are i.i.d. sub-Gaussian random variables with mean μ_i and variance σ_i^2 , as well as empirical mean $\hat{\mu}_{i,t}$ and variance $\hat{\sigma}_{i,t}^2$. Take θ such that $\mathbb{E}_{\mathbb{P}}[e^{a(X-\mathbb{E}_{\mathbb{P}}[X])}] \leq e^{\frac{a^2\theta^2}{2}}$ holds for all $a \in \mathbb{R}$ and $i \in \mathcal{A}$. The empirical and true mean-variance are defined as $\widehat{\mathrm{MV}}_{i,s}^{\rho} := (1-\rho)\hat{\sigma}_{i,s}^2 - \rho\hat{\mu}_{i,s}$ and $\mathrm{MV}_i^{\rho} := (1-\rho)\sigma_i^2 - \rho\mu_i$ respectively.

Lemma 5.5. For t > 0 and $\delta \in (0, 1/2tK)$, we have:

$$\mathbb{P}\left[\max_{\substack{i=1,\dots,K\\s=1,\dots,t}}\left|\widehat{\mathrm{MV}}_{i,s}^{\rho} - \mathrm{MV}_{i}^{\rho}\right| \ge \varphi\left(\frac{2\log(2/\delta)}{s}\right)\right] \le 2tK\delta.$$

Proof. Let

$$A_{i,s} := \left\{ \left| \hat{\mu}_{i,s} - \mu_i \right| \le \theta \sqrt{\frac{2\log(2/\delta)}{s}} \right\}$$

and

$$B_{i,s} := \left\{ \left| \hat{\sigma}_{i,s}^2 - \sigma_i^2 + \left(\hat{\mu}_{i,s} - \mu_i \right)^2 \right| \le 32\theta^2 \max\left(\sqrt{\frac{\log(2/\delta)}{s}}, \frac{2\log(2/\delta)}{s} \right) \right\}.$$

By Lemma 5.1 and 5.2, we have $\mathbb{P}(A_{i,s}) \geq 1 - \delta$ and $\mathbb{P}(B_{i,s}) \geq 1 - \delta$. Now, we define

$$C_{i,s} := \left\{ \left| \widehat{\mathrm{MV}}_{i,s}^{\rho} - \mathrm{MV}_{i}^{\rho} \right| \le \varphi \left(\frac{2 \log(2/\delta)}{s} \right) \right\}.$$

According to the triangle inequality, we have for any i and t:

$$\begin{aligned} \left| \widehat{\mathrm{MV}}_{i,s}^{\rho} - \mathrm{MV}_{i}^{\rho} \right| &\leq (1 - \rho) \left| \hat{\sigma}_{i,s}^{2} - \sigma_{i}^{2} \right| + \rho \left| \hat{\mu}_{i,s} - \mu_{i} \right| \\ &\leq (1 - \rho) \left| \hat{\sigma}_{i,s}^{2} - \sigma_{i}^{2} + \left(\hat{\mu}_{i,s} - \mu_{i} \right)^{2} \right| + (1 - \rho) \left(\hat{\mu}_{i,s} - \mu_{i} \right)^{2} + \rho \left| \hat{\mu}_{i,s} - \mu_{i} \right| \end{aligned}$$

As a result, for any i and $t, A_{i,s} \cap B_{i,s} \subseteq C_{i,s}$. Through the union bound, we have:

$$\mathbb{P}\left[\bigcup_{i=1}^{K}\bigcup_{s=1}^{t}C_{i,s}^{c}\right] \leq \sum_{i,s}\mathbb{P}\left[C_{i,s}^{c}\right] \leq \sum_{i,s}\mathbb{P}\left[A_{i,s}^{c}\cup B_{i,s}^{c}\right] \leq \sum_{i,s}\left(\mathbb{P}\left[A_{i,s}^{c}\right] + \mathbb{P}\left[B_{i,s}^{c}\right]\right) \leq 2tK\delta.$$

Now, we can turn to the proof of Theorem 3.2.

Proof of Theorem 3.2. First, we derive the claimed upper bound for the regret. By the definitions

in Section 5.2, we have:

$$\widehat{\Delta}_{i} = \Delta_{i} + (1 - \rho) \left(\widehat{\sigma}_{i, T_{i, t}}^{2} - \sigma_{i}^{2} \right) - \rho \left(\widehat{\mu}_{i, T_{i, t}} - \mu_{i} \right),$$

and

$$\left|\widehat{\Gamma}_{i,h}\right| = \left|\Gamma_{i,h} - \mu_i + \mu_h + \hat{\mu}_{i,T_{i,t}} - \hat{\mu}_{h,T_{h,t}}\right|.$$

According to Lemma 5.5, by setting $\delta = 2/t^4$ and given $s \leq t$, we can construct a high-probability event:

$$\mathcal{E}_t := \left\{ \forall i = 1, ..., K, \ \forall s = 1, ..., t, \ |\hat{\mu}_{i,s} - \mu_i| \le \theta \sqrt{\frac{8\log(t)}{s}}, \ \left| \hat{\sigma}_{i,s}^2 - \sigma_i^2 + (\hat{\mu}_{i,s} - \mu_i)^2 \right| \le 32\theta^2 \max\left(\sqrt{\frac{4\log(t)}{s}}, \frac{8\log(t)}{s}\right) \right\}.$$

Through the union bound over arms and periods, we have $\mathbb{P}[\mathcal{E}_t^c] \leq K/t^3$ where $t \in (K^{1/3}, \infty)$. With probability at least $1 - K/t^3$, by Lemma 5.1, we have $\left|\widehat{\Gamma}_{i,h}\right| \leq \left|\Gamma_{i,h}\right| + \theta\sqrt{8\log(t)/T_{i,t}} + \theta\sqrt{8\log(t)/T_{h,t}}$. By Lemma 5.5, with probability at least $1 - K/t^3$, we also have $\widehat{\Delta}_i \leq \Delta_i + \varphi(8\log(t)/T_{i,t})$. According to (23),

$$\begin{split} \mathcal{R}_{t}(\pi) &\leq \frac{1}{t} \sum_{i=1}^{K} T_{i,t} \widehat{\Delta}_{i} + \frac{1}{t^{2}} \sum_{i=1}^{K} \sum_{h \neq i} T_{i,t} T_{h,t} \widehat{\Gamma}_{i,h}^{2} \\ &\leq \frac{1}{t} \sum_{i=1}^{K} T_{i,t} \left(\Delta_{i} + \varphi \left(\frac{8 \log(t)}{T_{i,t}} \right) \right) \\ &+ \frac{1}{t^{2}} \sum_{i=1}^{K} \sum_{h \neq i} T_{i,t} T_{h,t} \left(\left| \Gamma_{i,h} \right| + \theta \sqrt{\frac{8 \log(t)}{T_{i,t}}} + \theta \sqrt{\frac{8 \log(t)}{T_{h,t}}} \right)^{2} \\ &\leq \frac{1}{t} \sum_{i=1}^{K} T_{i,t} \Delta_{i} + \frac{1}{t} \sum_{i=1}^{K} T_{i,t} \varphi \left(\frac{8 \log(t)}{T_{i,t}} \right) + \frac{2}{t^{2}} \sum_{i=1}^{K} \sum_{h \neq i} T_{i,t} T_{h,t} \Gamma_{i,h}^{2} \\ &+ \frac{8\theta^{2} \sqrt{2}}{t^{2}} \sum_{i=1}^{K} \sum_{h \neq i} T_{h,t} \log(t) + \frac{8\theta^{2} \sqrt{2}}{t^{2}} \sum_{i=1}^{K} \sum_{i \neq i} T_{h,t} \log(t) \\ &\leq \frac{1}{t} \sum_{i=1}^{K} T_{i,t} \Delta_{i} + \frac{2}{t^{2}} \sum_{i=1}^{K} \sum_{h \neq i} T_{i,t} T_{h,t} \Gamma_{i,h}^{2} \\ &+ 32(1 - \rho)\theta \max \left(\sqrt{\frac{8K \log(t)}{t}}, \frac{4K \log(t)}{t} \right) + 4(1 + 4\sqrt{2})(1 - \rho) \frac{K\theta \log(t)}{t} + \rho\theta \sqrt{\frac{8K \log(t)}{t}} \\ &\leq \frac{1}{t} \sum_{i=1}^{K} T_{i,t} \Delta_{i} + \frac{2}{t^{2}} \sum_{i=1}^{K} \sum_{h \neq i} T_{i,t} T_{h,t} \Gamma_{i,h}^{2} + \frac{\varphi \left(\frac{8K \log(t)}{t} \right)}{\theta} + \frac{16\sqrt{2}(1 - \rho)K\theta \log(t)}{t}, \end{split}$$

with probability $1 - K/t^3$. In the next to last passage we used Jensen's inequality for concave functions and leveraged the facts that K - 1 < K and $\sum_i T_{i,t} \leq t$. Based on (24) and Lemma 5.4,

we can obtain:

$$\frac{1}{t} \sum_{i=1}^{K} T_{i,t} \Delta_i + \frac{2}{t^2} \sum_{i=1}^{K} \sum_{h \neq i} T_{i,t} T_{h,t} \Gamma_{i,h}^2 \leq \frac{1}{t} \sum_{i \in \mathcal{A} \setminus \mathcal{A}^0} T_{i,t} (\Delta_i + 2\Gamma_{i,\max}^2) \\
\leq \frac{1}{t} \sum_{i \in \mathcal{A} \setminus \mathcal{A}^0} \left(\frac{8 \log(t)}{\varphi^{-1}(\Delta_i/2)} + 5 \right) (\Delta_i + 2\Gamma_{i,\max}^2),$$

with probability at least $1 - K/t^3$. Combining the above results gives us the stated regret bound.

References

- Agrawal, R. (1995). Sample mean based index policies by $\mathcal{O}(\log n)$ regret for the multi-armed bandit problem. Advances in Applied Probability, 27(4):1054–1078.
- Audibert, J.-Y., Munos, R., and Szepesvári, C. (2009). Exploration-exploitation tradeoff using variance estimates in multi-armed bandits. *Theoretical Computer Science*, 410(19):1876–1902.
- Auer, P., Cesa-Bianchi, N., and Fischer, P. (2002). Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 47(2):235–256.
- Baudry, D., Gautron, R., Kaufmann, E., and Maillard, O. (2021). Optimal thompson sampling strategies for support-aware cvar bandits. In *International Conference on Machine Learning*, pages 716–726. PMLR.
- Boldrini, S., De Nardis, L., Caso, G., Le, M. T. P., Fiorina, J., and Di Benedetto, M.-G. (2018). muMAB: A multi-armed bandit model for wireless network selection. *Algorithms*, 11(2).
- Chang, J. Q. and Tan, V. Y. (2022). A unifying theory of thompson sampling for continuous risk-averse bandits. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 6159–6166.
- Chapelle, O. and Li, L. (2011). An empirical evaluation of Thompson sampling. In Advances in Neural Information Processing Systems, volume 24. Curran Associates, Inc.
- Durand, A., Achilleos, C., Iacovides, D., Strati, K., Mitsis, G. D., and Pineau, J. (2018). Contextual bandits for adapting treatment in a mouse model of de novo carcinogenesis. In Proceedings of the 3rd Machine Learning for Healthcare Conference, volume 85 of Proceedings of Machine Learning Research, pages 67–82. PMLR.
- Galichet, N., Sebag, M., and Teytaud, O. (2014). Exploration vs exploitation vs safety: Risk-averse multi-armed bandits. CoRR, abs/1401.1123.
- Gupta, S., Chaudhari, S., Joshi, G., and Yagan, O. (2021). Multi-armed bandits with correlated arms. *IEEE Transactions on Information Theory*, 67(10):6711–6732.
- Kagrecha, A., Nair, J., and Jagannathan, K. P. (2019). Distribution oblivious, risk-aware algorithms for multi-armed bandits with unbounded rewards. CoRR, abs/1906.00569.

- Lai, T. and Robbins, H. (1985). Asymptotically efficient adaptive allocation rules. Advances in Applied Mathematics, 6(1):4–22.
- Liu, X., Derakhshani, M., Lambotharan, S., and van der Schaar, M. (2021). Risk-aware multi-armed bandits with refined upper confidence bounds. *IEEE Signal Processing Letters*, 28:269–273.
- Markowitz, H. M. (1968). Portfolio Selection: Efficient Diversification of Investments. Yale University Press.
- Mary, J., Gaudel, R., and Preux, P. (2015). Bandits and recommender systems. In *Machine Learning, Optimization, and Big Data*, pages 325–336, Cham. Springer International Publishing.
- Morgenstern, O. and Von Neumann, J. (1953). *Theory of Games and Economic Behavior*. Princeton University Press.
- Prashanth, L., Jagannathan, K. P., and Kolla, R. K. (2020). Concentration bounds for CVaR estimation: The cases of light-tailed and heavy-tailed distributions. In *ICML*, pages 5577–5586.
- Rigollet, P. and Hütter, J.-C. (2015). High dimensional statistics. In *Lecture notes for course* 18.S997. MIT OpenCourseWare.
- Rivasplata, O. (2012). Subgaussian random variables: An expository note. *Internet publication*, *PDF*, 5.
- Robbins, H. (1952). Some aspects of the sequential design of experiments. Bulletin of the American Mathematical Society, 58(5):527 535.
- Sani, A., Lazaric, A., and Munos, R. (2012). Risk-aversion in multi-armed bandits. Advances in Neural Information Processing Systems, 25.
- Shen, W., Wang, J., Jiang, Y., and Zha, H. (2015). Portfolio choices with orthogonal bandit learning. In *IJCAI*.
- Thompson, W. R. (1933). On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3/4):285–294.
- Vakili, S. and Zhao, Q. (2015). Mean-variance and value at risk in multi-armed bandit problems. In 2015 53rd Annual Allerton Conference on Communication, Control, and Computing (Allerton), pages 1330–1335.
- Vakili, S. and Zhao, Q. (2016). Risk-averse multi-armed bandit problems under mean-variance measure. *IEEE Journal of Selected Topics in Signal Processing*, 10(6):1093–1111.
- Wainwright, M. J. (2019). High-Dimensional Statistics: A Non-Asymptotic Viewpoint, volume 48. Cambridge University Press.
- Zhao, Q. (2019). Multi-armed bandits: Theory and applications to online learning in networks. Synthesis Lectures on Communication Networks, 12(1):1–165.
- Zhu, M., Zheng, X., Wang, Y., Li, Y., and Liang, Q. (2019). Adaptive portfolio by solving multiarmed bandit via Thompson sampling. arXiv preprint arXiv:1911.05309.
- Zhu, Q. and Tan, V. (2020). Thompson sampling algorithms for mean-variance bandits. In Proceedings of the 37th International Conference on Machine Learning, volume 119 of Proceedings of Machine Learning Research, pages 11599–11608. PMLR.