Corruptions of Supervised Learning Problems: Typology and Mitigations

Laura Iacovissi University of Tübingen and Tübingen AI Center laura.iacovissi@uni-tuebingen.de Nan Lu University of Tübingen and Tübingen AI Center nan.lu@uni-tuebingen.de Robert C. Williamson University of Tübingen and Tübingen AI Center bob.williamson@uni-tuebingen.de

Abstract

Corruption is notoriously widespread in data collection. Despite extensive research, the existing literature on corruption predominantly focuses on specific settings and learning scenarios, lacking a unified view. There is still a limited understanding of how to effectively model and mitigate corruption in machine learning problems. In this work, we develop a general theory of corruption from a fresh information-theoretic perspective—with Markov kernels as a foundational mathematical tool. We generalize the definition of corruption beyond the concept of distributional shift: corruption includes all modifications of a learning problem, including changes in model class and loss function. We will focus here on changes in probability distributions. This perspective leads to three novel opportunities. First, it enables the construction of a provably exhaustive framework for pairwise Markovian *corruptions* that has not been achieved before. The framework not only allows us to study corruption types based on their input space, but also serves to unify prior works on specific corruption models and establish a consistent nomenclature. Second, it facilitates a systematic analysis of the consequences of corruption on learning tasks by comparing Bayes risks in the clean and corrupted scenarios. This examination sheds light on complexities arising from joint and dependent corruptions on both labels and attributes, a realm scarcely explored in existing research. Notably, while label corruptions affect only the loss function, more intricate cases involving attribute corruptions extend the influence beyond the loss to affect the hypothesis class. Third, building upon these results, we investigate mitigations for various corruption types. We expand the existing loss-correction results for label corruption, including also the dependent type. We identify the necessity to generalize the classical corruption-corrected learning framework to a new paradigm with weaker requirements, so as to include other forms of corruptions beyond just labels. Within the latter setting, we provide a negative result for loss correction in the attribute and the joint corruption case.

Keywords: supervised learning, information theory, Markov kernels, Markovian corruption, loss correction

1 Introduction

Machine learning starts with data. The most widespread conception of data defines them as atomic facts, perfectly describing some reality of interest [1]. In learning theories, this is reflected by the often-used assumption that training and test data are drawn identically and independently from some fixed probability distribution. The goal of learning then construed as identifying and synthesizing patterns based on the knowledge, or information, embedded in these data. In practice, however, corruption regularly occurs in data collection. This creates a mismatch between training and test distributions, forcing us to learn from imperfect facts.

We should thus doubt the view of data as static facts, and consider them as a dynamic element of a learning task [2]. In addition to the traditional emphasis on prediction models and loss functions in machine learning, one may focus on the data dynamic itself, so as to understand how different processes may have led us to the observation of certain data, and furthermore, how they subsequently impact the learning process. While the necessity of investigating this topic is recognized both at a practical [3, 4, 5] and a theoretical [6, 7] level, no standardized way to model and analyze the dynamic generative process of data has been so far created.

In the field of machine learning, changes in such dynamic process are often referred to as *distribution shift* or *noisy data*. We prefer the more inclusive terminology *corruption*, borrowing it from the computer science literature. Our conceptualization of corruption goes beyond the definition of distribution shift or noisy data: it encompasses all modifications to a learning problem, including alterations in the choice of loss function, hypothesis class, or probability distribution from which we draw the data. We give an interpretation of corruption which challenges the idea that its effect on a data distribution is inherently pejorative; instead, we think it as a *modification process*. Whether the corruption is positive, negative, or neutral, depends on the specific context in which it is applied. A similar stance has been taken in the recent work from Mémoli et al. [8], where they additionally propose a pseudo-metric to quantify the changes in a supervised learning problem under such general corruptions. They define corruption in an analogous general fashion we envisioned, plus changes in the attribute and label sets. In the present paper, we specifically focus on modifications of the probability distribution, aiming to address the lack of understanding of *data as a process*. However, we emphasize that this is only one of the possible ways a learning problem can change.

In view of understanding corruption as a dynamic element of learning, there has been a surge of research focusing on specific data corruption models [9, 10, 11, 12, 13, 14, 15]. However, these approaches cannot, even in principle, answer questions regarding the comparison of different types of corruption. Moreover, the absence of a uniform and established nomenclature in the literature further complicates the situation. A comprehensive framework for data corruption is needed to overcome these challenges.

Whilst there have been existing attempts to build such a framework, certain limitations persist in terms of homogeneity and exhaustiveness. A famous early endeavor is Quiñonero-Candela et al. [14], grouping together works about the multi-faceted topic of dataset shift, yet not in a unifying or comprehensive manner. Later on, several studies sought to offer a more homogeneous view of corruption [16, 17, 18, 19]; nonetheless, these frameworks typically rely on corruption-invariant assumptions of the marginal or conditional probabilities. The extent of their exhaustiveness in representing all potential corruption models within their framework is merely conjectured, or left unexplored.

Therefore, the primary objective of this work is to improve the existing understanding of corruption by introducing an information-theoretic perspective, while making use of the classical probabilistic approaches. Probability distributions are the only representation of data that will be used in this work, so the terms "data" and "data distribution" are used interchangeably. A probabilistic and information-theoretic approach allows us to systematically study and compare the possible types of corruption in supervised learning problems, providing a general framework for analyzing their mitigation as an initial step toward unraveling these fundamental inquiries.

Table 1: Examples of models proposed in the literature that capture data dynamics with probabilistic descriptions. Here, X represents the attribute, and Y represents the label.

Models	Descriptions	
Attribute noise [20, 21, 22, 23]	P(X) is corrupted due to, e.g., additive attribute noise or missingness, while the labels remain untouched	
Random classification noise [9, 24, 25]	Considering $P(Y X)P(X)$, $P(Y X)$ is corrupted by flipping each label independently with a constant probability, while $P(X)$ remains invariant	
Class-conditional noise [11, 12, 26, 23]	Considering $P(Y X)P(X)$, $P(Y X)$ is corrupted by flipping labels with a probability dependent on the label, while $P(X)$ remains invariant	
Instance-dependent noise [27]	Considering $P(Y X)P(X)$, $P(Y X)$ is corrupted by flipping labels with a probability dependent on the instance, while $P(X)$ remains invariant	
Instance- & label-dependent noise [27, 28, 29, 30]	Considering $P(Y X)P(X)$, $P(Y X)$ is corrupted by flipping labels with an instance- & label-dependent probability, while $P(X)$ remains invariant	
Mutually contaminated distributions [31, 32, 33, 34]	Considering $P(X Y)P(Y)$, $P(X Y)$ is corrupted by a mixture model, and $P(Y)$ can also be corrupted	
Combined simple noise [23]	Considering $P(Y X)P(X)$, $P(X)$ is corrupted by additive noise, and $P(Y X)$ is corrupted by flipping labels with a probability dependent on the label	
Target shift [35, 36, 37, 38]	Considering $P(X Y)P(Y)$, $P(Y)$ is corrupted while $P(X Y)$ remains invariant	
Covariate shift [13, 39, 40, 15]	Considering $P(Y X)P(X)$, $P(X)$ is corrupted while $P(Y X)$ remains invariant	
Generalized target shift [10, 41, 42]	Considering $P(X Y)P(Y)$, $P(Y)$ and $P(X Y)$ are corrupted, subject to specific invariance assumptions on conditional distributions in the latent space	
Style transfer [43, 44, 45]	To model it probabilistically, we express it as $P(X Y)$ being changed given the designated style	
Adversarial noise [46, 47, 48, 49, 50]	To model it probabilistically, we express it as $P(X)$ being intentionally corrupted by an adversary to alter the correct prediction for each instance	
Concept drift [51, 52, 53]	P(X, Y) changes over time	
Concept shift [54, 55, 56]	Considering $P(Y X)P(X)$, $P(Y X)$ changes over time	
Sampling shift [57, 55, 56]	Considering $P(Y X)P(X)$, $P(X)$ changes over time, while $P(Y X)$ is invariant	
Selection bias [14]	$P(X, Y)$ is corrupted to $\tilde{P}(X, Y)$ s.t. $\tilde{P} \ll P, \alpha \coloneqq \frac{d\tilde{P}}{dP} \& \alpha _{\infty} < \infty$	

1.1 Motivations, approach, and contributions

We observed a continued surge of research papers dedicated to specific models of corruption, predominantly relying on explanations of changes and invariance in specific probabilities. In Tab. 1, we provide a non-comprehensive list of such models that can be conceptualized as corruption in our sense. Rather than adding to this already diverse landscape, we propose a taxonomy to systematically organize them. This taxonomy serves as a comprehensive map of probabilistic corruption models, currently absent in the field. Our approach distinguishes itself from the majority of papers in this line, which often propose new corruption models and tailored mitigation algorithms. We, on the other hand, explore their mitigation without the aim of introducing a new algorithm, but for gaining a deeper understanding of theory behind the existing ones. Details about our contributions are summarized in the following.

Understanding corruptions and their types A common definition of corruption found in the literature is the one of distributional shift. We shape our notion of Markovian corruption

inspired by such concept and making use of Markov kernels. However, attributing failures in learning solely to changes in probability distributions might be restrictive. For this reason we broaden the concept of corruption to a general one that includes changes in model class and loss function. Focusing on Markovian corruption, we establish a taxonomy grounded in its dependence on the input and output spaces in § 3. This allows us to uncover commonalities among different models of corruptions (refer to Tab. 2 for the correspondence of Tab. 1 in our taxonomy), thus transcending the diverse bespoke terminologies used by different authors. This methodology broadens our understanding of corruptions, shedding light on previously overlooked instances in the literature, such as joint and dependent corruptions. Our resulting framework is proven to be exhaustive for all possible pairwise probabilistic corruptions. While progress has been notable, there are areas yet to be investigated. Arguments may be made for non-probabilistic corruptions that change the probability associated with events in a manner not adhering to probability principles. In this context, we analyze two popular corruption models and demonstrate that they are non-Markovian; however, a comprehensive study of this class of corruptions is left to future investigations.

An information-theoretic view on the consequences of corruption We further explore the implications of different types of corruptions within our taxonomy on learning from an information-theoretic view. The conventional method for comparing a clean and corrupted experiment is through the measures of information, using the Data Processing Inequality, which generally states that the amount of information can only decrease or stay constant as a result of "information processing". Recently, Williamson and Cranko [23] examined the information-risk connection, established the relationship between measures of information and the Bayes risk of a statistical decision problem, and yielded Information Processing Equalities. These findings offer valuable insights into understanding how changes in information relate to changes in Bayes risk. Therefore, we follow the spirit of the authors and connect the Bayes risk of clean and corrupted supervised learning problems through equality results. Such equalities, illustrated in § 4, effectively prove the equivalence between two learning problems: the former corrupted in a Markovian fashion, the latter via general corruption changing model class and loss function via a Markov kernel. A feature of this analysis is its neat avoidance of dependence on specific algorithms, which provides an agnostic means of comparison for corruption types. Such comparison is, in our results, qualitative, and lays the foundation for future quantitative studies. One of our main findings amounts to understanding that for corruptions on Y, only the loss function is affected while the model class remains untouched by the corruption kernel; however, for more intricate cases involving corruptions also on X, both the loss function and the model class are influenced by the corresponding factorized corruption kernel.

A systematic analysis of mitigation for our corruption types Applying the Bayes Risk results, we derive corruption-corrected loss functions for all the different corruption instances within our framework (§ 5). We first identify the need of generalizing the concept of corrected learning since it becomes outmoded when not only considering label corruptions. Within the generalized corrected learning framework, we find a hierarchy-induced set of results on how the optimization problem changes under various corruptions, and how to abstractly compute their loss corrections in Theorems 20 and 21. We conclude that more complex corruptions are more detrimental, and require more sophisticated designs than noise mitigation via classical loss correction. In particular, we prove that in our setting classical loss correction is still not enough for achieving full mitigation in a corruption setting that involves a attribute

corruption, unveiling an additional fundamental difference between label corruption and attribute corruption.

2 Technical Background

2.1 Markov kernels

We now introduce the mathematical machinery used for modeling corruption in learning problems; that is, Markov kernels and some of their relevant properties. The material reported here is drawn from [58, 59, 26, 60, 61]; the reader can refer to them for a comprehensive understanding of kernels in probability and learning theory.

Definition 1 (Klenke [58]). Let (X_1, X_1) and (X_2, X_2) be standard Borel measure spaces, i.e. Polish spaces with a Borel σ -algebra. Let κ be a mapping from $X_1 \times X_2$ into $[0, +\infty]$. Then, κ is called a **kernel** from (X_1, X_1) to (X_2, X_2) if

- *1. the mapping* $x_1 \rightarrow \kappa(x_1, B)$ *is* X_1 *-measurable for every set* $B \in X_2$ *, and*
- 2. the mapping $B \to \kappa(x_1, B)$ is a measure on (X_2, X_2) for every $x_1 \in X_1$.

A kernel is said to be a **Markov kernel** if $\kappa(x_1, X_2) = 1 \forall x_1 \in X_1$, *i.e., it maps to a probability measure; this is denoted by the compact notation* $\kappa : X_1 \rightsquigarrow X_2$.^{*a*} *The set* X_1 *is said to be the domain of* κ , and X_2 *its image, i.e.,*

$$D(\kappa) = X_1, \quad I(\kappa) = X_2.$$

We refer to the set of kernels as $\mathcal{T}(X_1, X_2)$ *and its subset of Markov kernels as* $\mathcal{M}(X_1, X_2)$ *.*

^aThis notation is borrowed from category theory, see [62] for a primer.

To better grasp the concept of Markov kernel, we can think of it as a parameterized family $\kappa_{x_1}(\cdot), x_1 \in X_1$ of probability measures on the space (X_2, X_2) . It can interpreted as an *observation channel*, a concept rooted in information theory and properly formalized in [63]. In this context, a Markov kernel serves as a detailed probabilistic description of the generative process leading from a "hidden value" X_1 to *observed* distribution on X_2 .

Additionally, we can notice that Markov kernels clearly resemble conditional probabilities.¹ As such, for finite spaces they can we represented as stochastic matrices.

Special kinds of kernels, which will extensively used in our analysis, are:

• A Markov kernel defined on the trivial domain space, taking values of a probability distribution ν . This kernel will therefore be equivalent to the probability distribution. We can formally write

$$\kappa_{\nu}: \{*\} \rightsquigarrow X_1, \quad \kappa_{\nu} \equiv \nu, \quad \nu \in \mathcal{P}(X_1),$$

with $(\{*\}, \{\{*\}, \emptyset\})$ a measurable space with only one element. In the text, we will simplify the notation by directly using ν instead of κ_{ν} ;

• A Dirac delta kernel, i.e., an identity kernel, defined as $\delta_{X_1} : X_1 \rightsquigarrow X_1$, such that for all $A \in X_1$, we have $\delta_{X_1}(x, A) = 1$ if $x \in X_1$, $\delta_{X_1}(x, A) = 0$ otherwise.

¹In fact, they are proved to be *regular conditional probabilities*, see Çinlar [59] for more details.

Kernel actions A Markov kernel naturally induces two useful functionals, one on distributions and one on functions. They are defined as:

$$\kappa : \mathcal{P}(X_1) \to \mathcal{P}(X_2) \qquad \mu \kappa(B) \coloneqq \int_{X_1} \mu(dx_1) \kappa(x_1, B) \qquad \forall B \in X_2,$$

$$\kappa \cdot : L^0(X_2, \mathbb{R}) \to L^0(X_1, \mathbb{R}) \qquad \kappa f(x_1) \coloneqq \int_{X_2} \kappa(x_1, dx_2) f(x_2) \qquad \forall x_1 \in X_1,$$

provided the integral exists and assuming that $\mathcal{P}(X)$ refers to the set of probabilities on a set *X*. We refer to these operators as the *actions* of kernels on distributions and functions, respectively.

Equipped with these new operators, Markov kernels can now be seen as a point-wise probabilistic description of the distortion process applied to a probability distribution μ on X_1 , transforming it into another *observed* distribution on X_2 ; equivalently, we can make a similar comment for functions f of X_2 . Again, Markov kernels are nothing else than observation channels.

Kernel operations Kernels can be combined through different operations. We introduce them here briefly, mainly inspired by [60, 61], covering all the necessary properties for this work. We will use henceforth the notation (X_i, X_i) for a measurable space, presuming the existence of some fixed, suitable σ -algebras X_i for X_i . We remark that specifying the kernel action operator κf for all measurable f effectively defines a kernel as $\kappa(x_1, B) \coloneqq \kappa \chi_B(x_1)$ [59, Remark 6.4], where $\chi_B(x_1)$ is the indicator function for $x_1 \in X_1$, $B \in X_2$.

The first set of operations defined here can be referred to as *in-series operations*, given that the involved kernels are required to satisfy specific conditions on the spaces for which they are defined. These operations impose a *more stringent set of feasibility conditions*.

P1 Given $\kappa : X_1 \rightsquigarrow X_2$ and $\lambda : X_2 \rightsquigarrow X_3$, their *chain composition* is a kernel $\kappa \circ \lambda : X_1 \rightsquigarrow X_3$ uniquely determined by the following kernel action:

$$(\kappa \circ \lambda)f(x_1) \coloneqq \int_{X_2} \kappa(x_1, dx_2) \int_{X_3} \lambda(x_2, dx_3)f(x_3) ,$$

where $f : X_3 \rightarrow \mathbb{R}$ is a positive X_3 -measurable function.

P2 Given $\kappa : X_1 \rightsquigarrow X_2$ and $\lambda : X_1 \times X_2 \rightsquigarrow X_3$, their *product composition* is a kernel $\kappa \times \lambda : X_1 \rightsquigarrow X_2 \times X_3$ uniquely determined by the following kernel action:

$$(\kappa \times \lambda) f(x_1) \coloneqq \int_{X_2} \kappa(x_1, dx_2) \int_{X_3} \lambda((x_1, x_2), dx_3) f(x_2, x_3) ,$$

for every *f* positive $X_2 \times X_3$ -measurable.

We underline that a probability distribution is a specific instance of a Markov kernel, constant on its parameter space. Therefore, P1 and P2 are well defined for $\kappa : \{*\} \rightsquigarrow X_2 \equiv_{x_1 \in X_1} \nu, \nu$ on (X_2, X_2) and $\lambda : X_2 \rightsquigarrow X_3$ for the former, $\lambda : \{*\} \times X_2 \rightsquigarrow X_3$ for the latter. This allows us to write distribution-kernel combinations with the same notation used for the kernel-kernel ones, i.e. as $v \circ \lambda$ and $v \times \lambda$ ² Both the aforementioned operations are ways to *generate new probability measures*:

- $\nu \circ \lambda$ is equivalent to the kernel action on probabilities, $\lambda \nu$, so we adopt the \circ notation for it from now on;
- ν × λ is the kernel version of the Bayes decomposition of a joint probability into marginal
 ν and conditional probability λ.

The second set of operations defined here can be referred to as *parallel operations*. Compared to in-series operations as in P1 and P2, it allows for more flexible combinations of kernels.

P3 Given $\kappa : X_1 \rightsquigarrow X_2$ and $\lambda : X_3 \rightsquigarrow X_4$, their *superposition* is a kernel $\kappa \otimes \lambda : X_1 \times X_3 \rightsquigarrow X_2 \times X_4$ uniquely determined by the following kernel action:

$$(\kappa \otimes \lambda)f(x_1, x_3) \coloneqq \int_{X_2} \kappa(x_1, dx_2) \int_{X_4} \lambda(x_3, dx_4) f(x_2, x_4) ,$$

where $f : X_2 \times X_4 \rightarrow \mathbb{R}$ is positive $X_2 \times X_4$ -measurable.

Observe that no restriction is imposed on the parameter spaces to be equal, e.g., $X_1 = X_3$, or Cartesian products with some space in common, e.g., $X_1 = Y_1 \times Y_2$, $X_3 = Y_1 \times Y_3$. When this happens, the actions of the two kernels "superpose" on the same space. However, in case we have more than one measure acting on the same space, the superposition integral would be ill-defined, making some combinations unfeasible. Because of these properties, we say that P3 is the operation with the *weakest feasibility conditions*, the set of rules to fulfill for a well-defined operation.

The last set of operations, introduced by us, can be described as a mid-way between the chain composition P1 and the superposition P3.

P4 Given $\kappa : X_1 \times X_2 \rightsquigarrow X_3$ and $\lambda : X_1 \times X_3 \rightsquigarrow X_4$, their *partial chain composition* is a kernel $\kappa \circ_{X_3} \lambda : X_1 \times X_2 \rightsquigarrow X_4$ uniquely determined by the following kernel action:

$$(\kappa \circ_{X_3} \lambda) f(x_1, x_2) \coloneqq \int_{X_3} \kappa((x_1, x_2), dx_3) \int_{X_4} \lambda((x_1, x_3), dx_4) f(x_4) ,$$

where $f : X_4 \to \mathbb{R}$ is a positive X_4 -measurable function.

Essentially, this operation only chains the kernels on the specified space, here X_3 , while superposing them on the common parameter, X_1 .

2.2 Statistical experiments and supervised learning

After establishing the notation for working with kernels, we are now ready to deploy the framework in the learning context. The content presented here is connected to the literature on *statistical experiments* and *decision theory* [64, 65]. We summarize the key concepts crucial to our analysis and direct readers to relevant books for a more comprehensive perspective.

²True up to a "projection" on the right type, since e.g. $\nu \circ \lambda \in \mathcal{M}(\{*\}, X_3)$ while $\lambda \nu \in \mathcal{P}(X_3)$. However, we prefer not to delve into this level of detail and keep the following presentation simpler.

The general learning problem In statistical decision theory, a general decision problem can be viewed as a two-player game between *nature* and *decision-maker*. Here, nature represents an unknown process that generates the observed phenomena; the decision-maker observes the said phenomena and seeks to find the optimal action for each observation within the context of a given task. Slightly more formally, nature here stands for the (stochastic) force choosing an *observation* $o \in O$ given some hidden *state* $\theta \in \Theta$. The stochastic process generating o given θ is referred to as the *experiment E*.

Definition 2. An *experiment* $E : \Theta \rightsquigarrow O$ is a Markov kernel from the hidden state space to the observation space of a given decision problem.

The parameter space Θ and the observation space O are fixed by the setting of the decision problem. We need to specify an additional set, the decision space A, to introduce the modeling of the decision-maker.³ Having observed the phenomena, the decision-maker aims to construct a *decision rule* D mapping from the observation space O to the action space A. The decision-making task can be represented by the transition diagram $\Theta \xrightarrow[experiment]{E} O \xrightarrow[decision rule]{D} A$, where the decision rule is also modeled by a Markov kernel, hence is interpreted as a *stochastic rule* fixing a probability on the action space A instead of the classical deterministic view. In order to evaluate the performance of the decision maker with respect the optimal decision, one introduces the concept of loss function and therefore of learning problem.

Definition 3. A general learning problem \mathcal{L} is defined as the triple $\mathcal{L} = (\ell, \mathcal{H}, P)$, where $\ell : \mathcal{P}(A) \times A \to \mathbb{R}$ is a loss function in $L^0(\mathcal{P}(A) \times A, \mathbb{R}), \mathcal{H} \subseteq \mathcal{M}(O, A)$ is a decision class, or model class, and $P := \pi_{\theta} \times E, \pi_{\theta} \in \mathcal{P}(\Theta)$ is the joint probability distribution generating data. We say that a problem \mathcal{L} is defined on a measurable space $(\Theta \times O \times A, \Omega \times O \times \mathcal{A})$.

Supervised learning through risk minimization In the specific setup of *supervised learning*, the observation space O is the attribute space $X \subset \mathbb{R}^d$, $d \ge 1$, while both states Θ and actions A correspond to the label space Y. Then, the experiment E leads to a probability associated with the attribute X, given the state Y, so $E : Y \rightsquigarrow X$. Here we focus on the classification task, that assumes the label space to be *finite*,⁴ while no constraint is imposed on X apart from being a compact subset of \mathbb{R}^d .

Definition 4. A supervised learning problem is a general learning problem $\mathcal{L} = (\ell, \mathcal{H}, P)$ in which the data amount to couples of labels Y and attributes X, i.e., $P := \pi_Y \times E \in \mathcal{P}(Z), Z := X \times Y$. Consequently, $\ell \in L^0(P(Y) \times Y, \mathbb{R}_{\geq 0}), \mathcal{H} \subseteq \mathcal{M}(X, Y)$, and the corresponding measurable space is $(X \times Y, X \times \mathcal{Y})$.

The definition above fits in the general decision problem framework by considering the specific diagram $Y \xrightarrow{E} X \xrightarrow{h} Y$, where *h* is a decision rule chosen in $\mathcal{M}(X, Y)$, therefore choosing a probability on *Y* associated to a point in *X*.⁵ Its task can be formalized as a risk minimization

³For the ease of measure-theoretic complexity, assume all relevant spaces are measurable.

⁴All the stated results can be easily extended to regression cases by considering a continuous label space; we leave it for future application.

⁵This is, considering the hypothesis, or decision, as stochastic. Several techniques exist to transform a stochastic

problem, i.e., finding the optimal action $h \in \mathcal{M}(X, Y)$ by considering the *Bayes Risk* (BR) measure

$$BR_{\ell}(\pi_{Y} \times E) := \inf_{h \in \mathcal{M}(X,Y)} R_{\ell,h}(\pi_{Y} \times E); \quad R_{\ell,h}(\pi_{Y} \times E) := \mathbb{E}_{Y \sim \pi_{Y}} \mathbb{E}_{X \sim E_{Y}} \ell(h_{X}, Y) ,$$

where π_Y is a prior distribution on Y, R indicates the risk, and the notation κ_X stands for the kernel κ evaluated on the parameter X, e.g., h_X , E_Y (this subscript notation will be used throughout).⁶ Since in applications, one deploys a model with only limited representation capacity, we consider the *constrained version* of BR

$$\operatorname{BR}_{\ell,\mathcal{H}}(\pi_Y \times E) = \inf_{h \in \mathcal{H} \subseteq \mathcal{M}(X,Y)} \mathbb{E}_{\mathsf{Y} \sim \pi_Y} \mathbb{E}_{\mathsf{X} \sim E_{\mathsf{Y}}} \ell(h_{\mathsf{X}},\mathsf{Y}) ,$$

differing from the standard BR by being constrained to the minimization set \mathcal{H} . For this case to be well-specified, we need to enforce the condition of at least one of the minima of the unconstrained BR to be included in \mathcal{H} . For our convenience, we ask the minima considered to be the *h* matching the *F*, the true posterior.

For some cases, the formulation of learning problem in terms of the experiment can be restrictive; for this reason, we introduce an alternative way of writing \mathcal{L} starting from the *posterior kernel* $F : X \rightsquigarrow Y$. This can be naturally justified by considering the following simple proposition.

Proposition 5. A supervised learning problem $\mathcal{L} = (\ell, \mathcal{H}, P = \pi_Y \times E)$ on the measurable space $(X \times Y, X \times \mathcal{Y})$ can be equivalently expressed

- 1. using the posterior kernel, i.e., as $P = \pi_X \times F$ for some prior $\pi_X \in \mathcal{P}(X)$ on the attribute space. We will then refer to it as $\mathcal{L} = (\ell, \mathcal{H}, P = \pi_X \times F)$ on the measurable space $(X \times Y, X \times \mathcal{Y})$;
- 2. using the joint distribution *P*, *agnostic* regarding its factorization. We will then refer to it as $\mathcal{L} = (\ell, \mathcal{H}, P)$ on the measurable space (Z, Z).

We refer to an $\mathcal{L} = (\ell, \mathcal{H}, P = \pi_Y \times E)$ as generative, while an $\mathcal{L} = (\ell, \mathcal{H}, P = \pi_X \times F)$ as discriminative.

Since our focus in the following will exclusively be on supervised learning problems, we will simply term them *learning problems*.

3 A Taxonomy of Corruptions in Supervised Learning

In this section, we formally define our conceptualization of corruption within the context of a learning problem, utilizing the mathematical tool of Markov kernels. Given the diverse forms corruptions can take, we categorize them through a novel taxonomy based on its input and output spaces–essentially classifying them by *type*. We demonstrate the exhaustiveness of this general framework, which facilitates the systematic study of the various corruption types and combinations. Finally, through a cautious examination, we analyze the relationships between our taxonomy of corruption and existing corruption models, elucidating novel insights generated by our framework.

decision rule into a labeling function, or deterministic one, that assigns a point in *X* to a label in *Y*. For instance, in the binary case one can fix a thresholding parameter.

⁶We underline that the difference between the plain kernel and the subscript kernel, e.g. E and E_X , is caused by the evaluation of a kernel on a random variable, which effectively transforms it into a random variable itself.

3.1 Corruption definition and types

A learning problem comprises three key components: the loss function ℓ , the model class \mathcal{H} , and the probability distribution P from which we draw the data. In the field of machine learning, considerable attention has been devoted by engineers and researchers to the task of designing suitable loss functions or model architectures; however, less effort has been put into data, given that they are often not responsible for collecting them but rather for processing them [66].

In contrast to the traditional concept of corruption in machine learning, which only focuses on data generation and is defined as *distribution shift*—an alteration of the probability distribution to deviate from its original test counterpart—we argue that corruption can occur in any of the components. In this broader sense, opting for *surrogate losses* can be regarded as a form of corruption to the original loss function. For instance, surrogate losses are often chosen in place of the 0-1 loss in the classification problems [67]. Moreover, a *misspecified model*, such as when the model class of choice, e.g., linear functions, does not include the true model, e.g., a quadratic function, can also be considered a form of corruption. Therefore we define the general corruption as any alterations in (ℓ, \mathcal{H}, P) as follows.

Definition 6. A general corruption is a mapping sending a learning problem $\mathcal{L} = (\ell, \mathcal{H}, P)$ into another learning problem $\tilde{\mathcal{L}} = (\tilde{\ell}, \tilde{\mathcal{H}}, \tilde{P})$, where both $\mathcal{L}, \tilde{\mathcal{L}}$ are defined on a measurable space (Z, Z).

To initiate a comprehensive taxonomy of corruption, we begin by examining a specific case where corruption is defined as a Markov kernel with fixed input and output probability spaces.⁷ This definition subsumes a significant portion of existing literature, including classical works on distribution shift and noisy data. As such, our attention now turns to this subcase, formally defined below, with the aim of establishing connections between our types of corruption and the diverse corruption models laid out in previous studies. This, in turn, suggests that future work must extend beyond this subcase, as we have identified certain examples that are not covered by this definition (see § 3.2).

Definition 7. A Markovian corruption maps $\mathcal{L} = (\ell, \mathcal{H}, P)$ defined on (Z, Z) to another learning problem $\tilde{\mathcal{L}}$ on (Z, Z) through the action of a Markov kernel $\kappa : Z \rightsquigarrow Z$, such that $\tilde{\mathcal{L}} = (\ell, \mathcal{H}, \tilde{P} = P \circ \kappa)$.

We remark that the definition above does not necessarily assume the Markov kernel τ to be known. We only require τ to exist, and for us to know the values assumed by the kernel action when evaluated on *P*, i.e. $\tilde{P} = P \circ \kappa$. The kernel is therefore not uniquely identified by the corruption definition, since multiple Markov kernels can generate \tilde{P} from *P*. However, for the analysis carried on in the rest of the paper, we assume κ to be known.

The rationale behind this choice for modeling corruption lies in viewing a Markov kernel, or *observation channel* in the context of information theory, as a point-wise description of the stochastic process that leads to an observed probability distribution. This process is determined by external conditions that, in some sense, limit our ability of "seeing" the truth (probabilistic

⁷While Markov kernels have been utilized in formalizing corruption [26, 23], their primary foci were solely on label corruption, attribute corruption, or simple joint corruption.



Figure 1: *Hierarchy of partial corruption types.* The partial corruption types are hierarchically organized based on their dependence on the instance *X* and label *Y* space, as depicted through a tree structure. At the root of the tree lies the most general form of corruption, where the domain and image spaces are the joint one $X \times Y$, i.e., $D(\kappa) = I(\kappa) = X \times Y$. The arrows signify that a child node has its domain or image constant w.r.t. exactly one of the variables in its parent. Therefore, the children nodes can be expressed as subcases of their parent, but the parents generally cannot be expressed by only one of their children. The partial corruption types that cannot be combined with others are shown in dotted boxes. Note that corner cases involving independence from all variables or identity kernels are excluded from this analysis.

world), consequently giving rise to corruptions (distorted data distribution). Given the probabilistic focus of this work, we will from now on refer to Markovian corruption simply as *corruption*. For formal statements, we abuse the kernel notation and refer to the corruption induced by a kernel as the kernel itself, i.e., $\kappa : Z \rightsquigarrow Z$, or equivalently $\kappa \in \mathcal{M}(Z, Z)$.

A new taxonomy of partial corruptions Corruptions can be classified in different ways based on the domain and image of their associated kernels. Starting from the most general corruption, i.e., the corruption on $X \times Y$ space induced by $\kappa : X \times Y \rightsquigarrow X \times Y$, when one space (either Xor Y space) is absent in the image or domain of the corruption kernel, we will refer to them as *partial corruptions*. In Fig. 1, we present all possible types of partial corruption, with the exception of those that are identities (Dirac delta kernels) or constantly equal to a probability $(D(\kappa) = \{*\})$, as they can be seen as obvious subcases of other partial corruptions. We classify them based on their signature type, that is, which sets of X and Y constitute the domain and image of the corruption kernel. Specifically, we employ the following nomenclature: *joint* corruption when $D(\kappa) = I(\kappa) = X \times Y$; *1-parameter joint* corruption when $D(\kappa) = X \times Y$ and $I(\kappa)$ is either X or Y; *simple* corruption when $D(\kappa) = I(\kappa) \neq X \times Y$, so when they are either equal to X or Y; *2-dependent* when $D(\kappa) = X \times Y$ and $I(\kappa)$ is either X or Y; *1-dependent* when $D(\kappa) = X$ and $I(\kappa) = Y$ or the opposite.

Constructing joint corruption as a combination of partial ones We now aim to enumerate all possible ways of constructing joint corruptions, i.e., of the type $\kappa : X \times Y \rightsquigarrow X \times Y$, by combining the nodes in Fig. 1 through the superposition operation P3. To this end, we introduce an additional condition to be imposed on the combinations of partial corruptions.

Definition 8. A pairwise corruption is a joint corruption κ generated by superposition of two partial corruptions, $\tau \otimes \lambda$, such that none of the involved partial corruptions can be decomposed further as a combination of Markov kernel via the P1–3 operations.



Figure 2: *Feasible combinations of partial corruptions.* Joint corruptions, i.e. of type $\kappa : X \times Y \rightsquigarrow X \times Y$, are obtained by combining two compatible partial corruptions in Fig. 1. The tree structure is induced by that of the partial corruption types. Notice that we can only combine a partial corruption with $I(\tau) = X$ with another such that $I(\lambda) = Y$, following Proposition 9. Therefore, the arrows signify that both τ and λ in a child node inherit their domains from the parent node with either τ or λ constant w.r.t. exactly one of their domain variables.

Effectively, we are forbidding the use of additional "hidden" spaces beyond the specified domain and image so to ensure that our proposed taxonomy of combined partial corruptions (or, joint factorized corruptions) is complete.

The requirements introduced until now shape the objects that we will use throughout the paper to study corruption. We summarize them in the following assumption.

A0 Joint corruptions are required to be Markovian and act on probability distributions as per Def. 7, and to satisfy the pairwise corruption condition.

According to Def. 7, we must map a joint probability distribution on $X \times Y$ into another joint one. Therefore, we exclude the combination of a simple corruption with a 1-dependent corruption since such a pairing cannot generate a joint corruption.⁸ Additionally, combinations such as $(\tau \otimes \lambda)(x, d\tilde{x}d\tilde{y}) = \tau(x, d\tilde{x}d\tilde{y}) \otimes \lambda(x, d\tilde{y})$ are not allowed because, according to P3, the measure on the corrupted labels would be ill-defined. Therefore, enumerating all the possible combinations and checking which are feasible, we can see that only the ones with $I(\tau) = X$ and $I(\lambda) = Y$ or $I(\tau) = Y$ and $I(\lambda) = X$ respect the condition. Therefore we have informally shown the following proposition to hold, granted requiring without loss of generality τ to be an attribute corruption, and λ a label corruption.

Proposition 9. The set of feasible joint factorized corruptions of the form $\kappa = \tau \otimes \lambda$ respecting A0, and such that τ 's and λ 's types are within the ones listed in Fig. 1 only contains kernels κ such that $I(\tau) = X$ and $I(\lambda) = Y$.

Such set is depicted and hierarchically organized in Fig. 2. The proposition formalizes a desirable property of corruption, allowing it to change the distribution on attribute X and the

⁸Note that such combination is feasible if the 1-parameter joint corruption is seen as a subcase of a joint one, e.g., $\lambda(x, d\tilde{x}d\tilde{y})\mathbf{1}(y)$, where $\mathbf{1}(y)$ only trivially depends on y since it is the matrix with all entries equal to 1. Similarly, a 1-dependent corruption can be seen as a subcase of a 2-dependent one. The constraints we mention are only dimensional.

distribution on label Y in a distinguishable way, either independently or dependently. Therefore, corruptions with indistinguishable effects on label and attributes, such as 1-parameter joint ones, are incorporated in the class of joint and non-factorizable corruption, i.e. $\mathcal{M}(X \times Y, X \times Y)$.

Exhaustiveness of the taxonomy We say that the taxonomy of Markovian corruption proposed is *exhaustive* if, for every possible couple of distributions $(P, \tilde{P}) \in \mathcal{P}(Z) \times \mathcal{P}(Z)$, there exist a pairwise Markovian corruption from $\mathcal{L} = (\ell, \mathcal{H}, P)$ to $\tilde{\mathcal{L}} = (\ell, \mathcal{H}, \tilde{P})$ s.t. $\tilde{P} = P \circ \kappa$. The formal argument for proving exhaustiveness is based on the concept of coupling of probability spaces. A coupling is formally defined for two probability spaces $(Z_1, Z_1, P_1), (Z_2, Z_2, P_2)$ as a probability space $(Z_1 \times Z_2, \mathcal{Z}_1 \times \mathcal{Z}_2, P)$, such that the marginal probabilities associated to Pw.r.t. Z_i , $i \in \{1, 2\}$, are the respective P_i . By construction, Markov kernels with fixed input and output probabilities P, \tilde{P} are in bijection with all the possible couplings existent on $Z \times Z$ with two *fixed* probability measures; for us, P, \tilde{P} (see details in § S3). Hence, they represent all possible pairwise probabilistic dependencies between probability spaces, i.e., induced by a Markov kernel. Thanks to the reasoning above and what we proved in the previous paragraph, we can state the following:

Proposition 10. The taxonomy of factorized joint corruptions illustrated in Fig. 2 is exhaustive.

In the context of most machine learning research on corruption, the corruption process typically involves two environments, namely, the training one and the test one. Our definition of corruption (A0) covers all such pairwise cases. Furthermore, one may also apply this framework to settings with more than two spaces, e.g., learning from multiple domains [68], or concept drift across different time steps [51, 52, 53], by relaxing our assumptions. For these cases, we can employ a composed model, where different corruptions are acting together in a "sequential" (P1-P2) or "parallel" (P3) fashion and creating more complex patterns. We discuss further possibilities for applying this framework to n > 2 corrupted spaces in § S4.

A practical example Here, we present an illustration of a Markov kernel (in the finite case) within a practical scenario to facilitate for the reader the understanding of corruption through kernels. The provided example is adapted from [69] which considers the prediction of recidivism in the criminal justice system–predict who goes on to commit future crimes.

Surveys have shown that "in the case of drug crimes, whites are at least as likely as blacks to sell or use drugs; yet blacks are more than twice as likely to be arrested for drug-related offenses" [70]. Given this, we consider the observed outcome "rearrest", denoted as $\tilde{Y} \in Y := \{+1, -1\}$, as a corrupted version of the true outcome "reoffense", denoted as $Y \in Y := \{+1, -1\}$, depending on the attribute $X \in X = \{b, w\}$. Specifically, the disparity between Y and \tilde{Y} can be captured by a higher probability of flipping the reoffense label (Y = +1) to the no rearrest label ($\tilde{Y} = -1$) for white population (X = w) compared to the black population (X = b):

$$\alpha(w) > \alpha(b)$$
, where $\alpha(x) := P(\tilde{Y} = -1 | Y = +1, X = x)$.

Moreover, we employ another reasonable assumption that the corruption arises solely from the hidden recidivists, and not from erroneous arrests of individuals not committing the offense. In other words, the probability of flipping the no reoffense label (Y = -1) to the rearrest label ($\tilde{Y} = +1$) is zero for both the black and white populations:

$$\beta(w) = \beta(b) = 0$$
, where $\beta(x) := P(Y = +1 | Y = -1, X = x)$.

A possible Markov kernel modeling the setting would be therefore of the type $\lambda : X \times Y \rightsquigarrow Y$, exemplifying 2-dependent label corruption. More specifically, it can be written as a joint kernel $\delta_X \otimes \lambda$ where $\lambda : X \times Y \rightsquigarrow Y$. Being defined in discrete probability spaces, both δ_X and λ can be expressed as matrices with entries representing conditional probabilities. In particular, we rewrite for clarity λ as its parameterized version $\lambda_X|_{X=x} : Y \rightsquigarrow Y$ for $x \in X$, obtaining:

$$\begin{split} \delta_{\mathbf{X}} &\coloneqq \begin{bmatrix} P(\tilde{\mathbf{X}} = b \mid \mathbf{X} = b) & P(\tilde{\mathbf{X}} = b \mid \mathbf{X} = w) \\ P(\tilde{\mathbf{X}} = w \mid \mathbf{X} = b) & P(\tilde{\mathbf{X}} = w \mid \mathbf{X} = w) \end{bmatrix} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \\ \lambda_{\mathbf{X}} \Big|_{\mathbf{X} = \mathbf{X}} &\coloneqq \begin{bmatrix} P(\tilde{\mathbf{Y}} = 1 \mid \mathbf{Y} = +1, \mathbf{X} = \mathbf{X}) & 0 \\ P(\tilde{\mathbf{Y}} = -1 \mid \mathbf{Y} = +1, \mathbf{X} = \mathbf{X}) & 1 \end{bmatrix} = \begin{bmatrix} 1 - \alpha(\mathbf{X}) & 0 \\ \alpha(\mathbf{X}) & 1 \end{bmatrix}, \end{split}$$

where the entries are determined according to the given problem setting. To illustrate, consider an example of $\alpha(b) = 1/10$ and $\alpha(w) = 1/5$, yielding the following expressions:

$$\lambda_{\mathsf{X}}|_{\mathsf{X}=b} = \begin{bmatrix} 1 - \alpha(b) & 0\\ \alpha(b) & 1 \end{bmatrix} = \begin{bmatrix} 9/10 & 0\\ 1/10 & 1 \end{bmatrix} \text{ and } \lambda_{\mathsf{X}}|_{\mathsf{X}=w} = \begin{bmatrix} 1 - \alpha(w) & 0\\ \alpha(w) & 1 \end{bmatrix} = \begin{bmatrix} 4/5 & 0\\ 1/5 & 1 \end{bmatrix}.$$

From Def. 7 we know that a Markovian corruption makes sense when specifying a learning problem. Therefore, we additionally consider two different joint probabilities on $X \times Y$:

$$P_1 = [1/4, 1/4, 1/4, 1/4]^{\top}, \quad P_2 = [3/10, 2/10, 1/4, 1/4]^{\top},$$

where the specific order is assumed to be

$$P_i := [P_i(X = b, Y = +1), P_i(X = b, Y = -1), P_i(X = w, Y = +1), P_i(X = w, Y = -1)]^{\top}.$$

Note that in finite spaces, the superposition operation P3 reduces to the Kronecker product, hence we write the joint corruption kernel $\delta_X \otimes (\lambda : X \times Y \rightsquigarrow X \times Y)$ as

$$\delta_X \otimes \lambda = \left[\frac{1 \cdot \lambda_{\mathsf{X}} \big|_{\mathsf{X}=b} \left| 0 \cdot \lambda_{\mathsf{X}} \big|_{\mathsf{X}=w} \right|}{0 \cdot \lambda_{\mathsf{X}} \big|_{\mathsf{X}=w} \right] = \left[\frac{\lambda_{\mathsf{X}} \big|_{\mathsf{X}=b} \left| \mathbf{0} \right|}{\mathbf{0} \left| \lambda_{\mathsf{X}} \right|_{\mathsf{X}=w} } \right] = \begin{bmatrix} 9/10 & 0 & 0 & 0 \\ 1/10 & 1 & 0 & 0 \\ 0 & 0 & 4/5 & 0 \\ 0 & 0 & 1/5 & 1 \end{bmatrix},$$

which is a 4×4 block diagonal matrix. Then we can obtain the corrupted joint probabilities by composing them with the two original probabilities in the following manner:

$$P_{1} \circ (\delta_{X} \otimes \lambda) = \begin{bmatrix} 9/10 & 0 & 0 & 0 \\ 1/10 & 1 & 0 & 0 \\ 0 & 0 & 4/5 & 0 \\ 0 & 0 & 1/5 & 1 \end{bmatrix} \begin{bmatrix} 1/4 \\ 1/4 \\ 1/4 \\ 1/4 \end{bmatrix} \propto \begin{bmatrix} 45 \\ 55 \\ 40 \\ 60 \end{bmatrix},$$
$$P_{2} \circ (\delta_{X} \otimes \lambda) = \begin{bmatrix} 9/10 & 0 & 0 & 0 \\ 1/10 & 1 & 0 & 0 \\ 0 & 0 & 4/5 & 0 \\ 0 & 0 & 1/5 & 1 \end{bmatrix} \begin{bmatrix} 3/10 \\ 2/10 \\ 1/4 \\ 1/4 \end{bmatrix} \propto \begin{bmatrix} 54 \\ 46 \\ 40 \\ 60 \end{bmatrix}.$$

In this case, the chain composition operation P1 is reduced to matrix multiplication, and both results are computed through rescaling of a 1/200 factor.

Corruption name in literature	Corruption type	Kernel representation	
Attribute noise [20, 21, 22, 23]	simple	$\tau: X \rightsquigarrow X$	
Style transfer [43, 44, 45]	1-dep.	$\tau: \Upsilon \rightsquigarrow X$	
Adversarial noise [46, 47, 48, 49, 50]	2-dep.	$\tau: X \times Y \rightsquigarrow X$	
Random classification noise [9, 24, 25]	simple	$\lambda: \{*\} \rightsquigarrow Y$	
Class-conditional noise [11, 12, 26, 23]	simple	$\lambda: Y \rightsquigarrow Y$	
Instance-dependent noise [27]	1-dep.	$\lambda: X \rightsquigarrow Y$	
Instance- & label-dependent noise [27, 28, 29, 30]	2-dep.	$\lambda: X \times Y \rightsquigarrow Y$	
Combined simple noise [23]	two simple combined	$(\tau: X \rightsquigarrow X) \otimes (\lambda: Y \rightsquigarrow Y)$	
Generalized target shift [10, 41, 42]	two 2-dep. combined	$(\tau: X \times Y \rightsquigarrow X) \otimes (\lambda: X \times Y \rightsquigarrow Y)$	
Target shift [35, 36, 37, 38]	min. simple, max. 1-dep. & 2-dep. combined	$ \begin{aligned} \lambda : Y \rightsquigarrow Y, \\ (\tau : Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y) \end{aligned} $	
Concept shift [54, 55, 56]	min. simple, max. two 2-dep. combined	$ \begin{aligned} \lambda : Y \rightsquigarrow Y, \\ (\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y) \end{aligned} $	
Covariate shift [13, 39, 40, 15] Sampling shift [57, 55, 56]	min. simple, max. 2-dep. & 1-dep. combined	$\tau: X \rightsquigarrow X, (\tau: X \times Y \rightsquigarrow X) \otimes (\lambda: X \rightsquigarrow Y)$	
Concept drift [51, 52, 53]	can be any type, including the non-factorized one	-	
Mutually contaminated distributions [31, 32, 33, 34] Selection bias [14]	non-Markovian corruption	-	

Table 2: Illustration of the taxonomy with examples of existing corruption models. When only one kernel is indicated, missing variables remain unchanged. "dep." is short for "dependent".

Besides illustrating how Markovian corruptions technically act on probabilities, the example above clarifies that solely encoding assumptions on the corruption process in the Markov kernel might lead to incorrect conclusions. We exhibit two learning problem with different clean probability distributions that are mapped into corrupted probabilities with similar values. This underscores the importance of distinguishing between a Markov kernel, as defined in Def. 1, and Markovian corruption associated with a learning problem \mathcal{L} , as defined in Def. 7.

As a proof of concept, we have only compared the original and corrupted probability distributions, without consideration of the learning aspect–finding the optimal decision w.r.t. the Bayes risk measure. In the upcoming § 4, we present a systematic analysis of the consequences of different corruptions on a supervised learning problem by examining how their Bayes risk is changed, accompanied by discussions on strategies for mitigating these consequences in § 5.

3.2 Relations with existing paradigms

As presented, our taxonomy offers a novel perspective to consolidate existing work under a unified framework, hierarchically organized based on the notion of dependence on the instance and label space. Therefore, we reorganize the corruption models outlined in Tab. 1 and illustrate them within our taxonomy, as depicted in Tab. 2. ⁹ Notably, Tab. 2 unveils several new insights that are not readily evident from Tab. 1.

Firstly, it enables a qualitative comparison of different corruption models by considering their domain and image spaces (refer to Fig. 1 and Fig. 2). If a kernel exhibits more complexities in its domain and image, it will induce a more intricate form of corruption. Conversely, corruptions demonstrating less complexity in the domain and image of the associated kernel can be regarded as subcases of those with greater complexity. For example, instance-&label-dependent noise characterized as a 2-dependent label corruption $\lambda : X \times Y \rightsquigarrow Y$, is more intricate than class-conditional noise, a simple label corruption $\lambda : Y \rightsquigarrow Y$, with more dependence on X; the latter can be seen as a subcase of the former with its kernel being constant w.r.t. X.

Secondly, it reveals that some corruption models in Tab. 1 correspond to multiple corruption types or combinations of partial corruptions in our taxonomy. This is because their definitions in Tab. 1 often consider the corruption of either the probability in the *X* space or the *Y* space, leaving freedom for corrupting the other. In extreme cases like concept drift, which assumes corruption only in the joint distribution, it can be of any corruption type and may not even be factorized to partial corruptions.

Thirdly, it provides new insights into some corruptions that have been taken for granted to share the same probabilistic nature as others, but turn out to be non-Markovian corruptions. Examples include mutually contaminated distributions and selection bias, topics that will be further elaborated in the following.

Mutually contaminated distributions While being a term with less widespread recognition, *mutually contaminated distributions* (MCD) [31, 32, 33, 34] is a popular corruption model that has been studied in the literature under more familiar names, for example, *learning from positive and unlabeled data* [71, 72, 73, 74, 75] in the binary class case (with a specific mixing matrix defined below), and *learning from label proportions* [76, 77, 78, 79, 80]. Despite the popularity, less is understood about how MCD relates to other corruption models. Our framework offers new insights into such relationships and demonstrates how MCD extends beyond Markovian corruptions.

To initiate this analysis, we first formally define MCD in the sense of Tab. 1. Fix a measurable instance space *X*, and denote by *P* a distribution over $X \times [K]$ for $[K] := \{1, 2, \dots, K\}$ with random variables $(X, Y) \sim P$. Let $k \in [K]$, $P_k := \mathbb{P}(X | Y = k)$ be the class-conditional distribution, and $\pi_k := \mathbb{P}(Y = k)$ be the base rate.

Definition 11 (Katz-Samuels et al. [34]). *Given clean class-conditional distributions* $\mathbf{P}(x) = [P_1(x), \ldots, P_K(x)]$ and some mixing matrix $\mathbf{\Pi} = (\pi_{m,k})_{1 \le m \le M, 1 \le k \le K}$, under the MCD model, instead of observing K random samples from $\mathbf{P}(x)$, we observe M random samples from the contaminated class-conditional distributions $\tilde{\mathbf{P}}(x) = [\tilde{P}_1(x), \ldots, \tilde{P}_M(x)]$,

$$\tilde{P}_m(x) := \sum_{k=1}^K \pi_{m,k} P_k(x) \quad \forall x \in X ,$$

where $m \in [M]$ denotes the corrupted class, $\pi_{m,k} \ge 0$, and $\sum_m \pi_{m,k} = 1$; equally, in matrix

⁹Details about the relationships with these corruption instances are given in § S1, and discussions on the relationships with other data shift taxonomies are given in § S2.

form,

$$\tilde{\mathbf{P}}(x) = \mathbf{\Pi} \mathbf{P}(x) \quad \forall x \in X.$$

This definition has some clear differences with our definition of corruption. First, Def. 11 uses the class conditional probabilities \mathbf{P} , $\tilde{\mathbf{P}}$ instead of the joint probability. In our language, this means expressing corruption via the experiment *E*. Secondly, their mixing matrix $\boldsymbol{\Pi}$ is defined as a *row-stochastic matrix*, so it is practically a transposed Markov kernel defined on finite spaces. We can therefore translate the MCD into our notation as in the following:

$$\tilde{P}(A) = \sum_{Y} \int_{A} \int_{X} \delta_{X}(x, d\tilde{x}) \kappa_{M}(\tilde{y}, dy) E(y, dx) \,\tilde{\pi}(d\tilde{y}) \tag{1}$$

$$= \int_{A} \left[\left(\kappa_{M} \circ (E \circ \delta_{X}) \right) \times \tilde{\pi} \right] (d\tilde{x}, d\tilde{y}) \neq \int_{A} \left[\left(\delta_{X} \otimes \kappa_{M} \right) \circ (\pi \times E) \right] (d\tilde{x}, d\tilde{y}) , \qquad (2)$$

where now \tilde{P} and P are joint probabilities, $\kappa_M(\tilde{y}, dy) = \Pi_{\tilde{y}, y} \in \mathcal{M}(Y, Y)$, and $Y := [\max(K, M)]$ to get a square matrix. In particular, we underline that $\tilde{\pi}(d\tilde{y})$ is a marginal probability on the corrupted space, while $\pi(dy)$ is on the clean one. It is not specified by the authors of [34] how the corrupted marginal probability is obtained, nor whether it is the same one given in input as the clean one. Generally, we can always write the following relationship:

$$\tilde{\pi}(d\tilde{y}) = \int_{Y} \lambda_M(\hat{y}, d\tilde{y}) \, \pi(d\hat{y}) \,,$$

where $\lambda_M : Y \rightsquigarrow Y$, so the variable \hat{y} is defined on the clean probability space (Y, \mathcal{Y}, π) , \mathcal{Y} being a suitable σ -algebra. Such formula makes MCD *not pairwise*, as plugging it in Eq. (1) violates A0. This gets even clearer when looking at Eq. (2): the right-hand side would imply that there exists a single kernel in $(\delta_X \otimes \kappa_M)(x, \tilde{y}, d\tilde{x}dy) \in \mathcal{M}(X \times Y, X \times Y)$ representing the MCD corruption scheme, but such representation is not possible because of how the MCD kernel acts on *E* by definition. In addition, we underline that the existence of $(\delta_X \otimes \kappa_M)(x, \tilde{y}, d\tilde{x}dy)$ would still *not make a viable Markovian corruption* in the sense of Def. 7 because of the variables not being compatible with the probability *P* for generating $\tilde{P}(d\tilde{x}d\tilde{y}) = (P \circ (\delta_X \otimes \kappa_M))(d\tilde{x}d\tilde{y}) = \int_{X \times Y} P(dxdy) (\delta_X \otimes \kappa_M)(x, \tilde{y}, d\tilde{x}dy)$, the latter being an ill-posed integral since we have two measures on $y \in Y$.

In [32] the authors assume it plausible to have a corrupted label marginal totally unrelated to the original clean one; we model this case as a degenerate kernel constantly equal to the output probability, i.e. $\lambda_M(\hat{y}, d\tilde{y}) = \tilde{\pi}(d\tilde{y})$. The other extreme case is for the corrupted and clean marginals to not differ, and in such a case we are still in the presence of a corruption that is not pairwise. That because, having $\lambda_M(\hat{y}, d\tilde{y}) = \delta_Y(\hat{y}, d\tilde{y})$ we write the marginal

$$\pi(d\tilde{y}) = \int_{Y} \lambda_{M}(\hat{y}, d\tilde{y}) \, \pi(d\hat{y}) = \int_{Y} \delta_{Y}(\hat{y}, d\tilde{y}) \, \pi(d\hat{y})$$

We can lastly look at the comparison of MCD with *class-conditional noise* (CCN) to understand more in depth its non Markovian nature. Clearly we cannot reduce MCD to CCN, as we already shown in the above. However, in [32] they prove that CCN can be mapped to the MCD model in the binary case. It can be trivially extended to multi-class setting by taking

$$[\kappa_M]_{ij} \coloneqq \frac{[\lambda_C]_{ij}\tilde{\pi}_j}{\sum_{j=1}^{|Y|} [\lambda_C]_{ij}\tilde{\pi}_j},$$

where λ_C is the Markov kernel associated to CCN, and $\delta_X \otimes \lambda_C$ would be its joint form. In plain words, the usual definition of CCN via λ_C can be manipulated such that the κ_M will subsume the label corruption, and the marginal corruption of the MCD is assumed to be a delta, i.e. $\lambda_M = \delta_Y$. However, it would still act on the clean probability as a non-Markovian corruption, as we have proved above.

Selection bias Another example of corruption model that has been widely studied in the literature is selection bias. Different definitions has been proposed over the years, as we briefly discuss in § S1 in comparison with covariate shift. We demonstrate in the following that selection bias cannot be subsumed by the Markovian corruption framework, when considered with its classical formulation with the Radon–Nikodym derivative.

Definition 12 (Chapter 3.2, Quiñonero-Candela et al. [14]). Let $Z \subseteq \mathbb{R}^d$ and Borel σ -algebra \mathcal{Z} on Z form a measurable space. Consider a clean probability space (Z, \mathcal{Z}, P) and a corrupted one $(Z, \mathcal{Z}, \tilde{P})$, from which we aim to learn. We define selection bias as a general corruption such that $\mathcal{L} = (\ell, \mathcal{H}, P)$ and $\tilde{\mathcal{L}} = (\ell, \mathcal{H}, \tilde{P})$, and that fulfills the following conditions:

- 1. Support condition, or absolute continuity of the measures: $\exists \alpha \in L^1(Z, \mathbb{Z}, P)$ s.t. $\tilde{P}(A) = \int_A \alpha(z)P(dz) \ \forall A \in \mathbb{Z}$, where α is almost surely unique (Radon–Nikodym derivative);
- 2. Selection condition: $\sup_{z \in \mathbb{Z}} \alpha(z) < +\infty$.

Clearly, selection bias can in principle include different instances of our taxonomy, since its type is not specified not decided by its characterizing conditions. We now try to understand if it meets the requirement for being Markovian in the first place. Comparing it with the action of a general $\kappa \in \mathcal{M}(Z, Z)$ on the input probability *P*, we get the condition

$$\int_{A} \int_{Z} \kappa(z, d\tilde{z}) P(dz) = \int_{A} \alpha(z) P(dz) \quad \forall A \in \mathbb{Z} .$$

It is easy to check that the kernel satisfying the condition is $\kappa(z, d\tilde{z}) \coloneqq \delta_z(d\tilde{z})\alpha(z)$, which respects the definition of kernel, but does not fulfill the Markov property unless $\alpha(z) = 1 \forall z \in Z$. This kernel is defined such that *P* is corrupted into \tilde{P} , but it does not preserve mass for every input probability measure, therefore it is not what we are looking for to say that selection bias is a Markovian corruption. Is this κ the only possible guess?

Consider a general $\kappa \in \mathcal{M}(Z, Z)$. It can be rewritten through its density w.r.t. a suitable measure, i.e.,

$$\tilde{P}(A) = \int_{A} \int_{Z} \kappa(z, d\tilde{z}) P(dz) = \int_{A} \int_{Z} k(z, \tilde{z}) \nu(d\tilde{z}) P(dz) \quad \forall A \in \mathbb{Z},$$

and defining $\beta(\tilde{z}) \coloneqq \int_{Z} k(z, \tilde{z}) P(dz)$, we obtain $\tilde{P}(A) = \int_{A} \beta(\tilde{z}) \nu(d\tilde{z}) \quad \forall A \in \mathbb{Z}$. Imposing κ to act as selection bias, we get $\beta(z) = \alpha(z) \quad \forall z \in Z$ and $\nu = P \in \mathcal{P}(Z)$, $\mu \coloneqq \frac{\nu + P}{2}$ -a.e. On the other hand, the Markov condition asks

$$\int_{Z} k(z, \tilde{z}) \nu(d\tilde{z}) = \int_{Z} k(z, \tilde{z}) P(d\tilde{z}) = 1 \quad \forall z \in Z \Longrightarrow \beta(z) = \alpha(z) = 1 \quad \forall z \in Z$$

Hence, we reached a contradiction and proved that *selection bias cannot be directly represented as a Markov kernel* if we impose it to be acting on probabilities *exactly* as the Radon–Nikodym

derivative α . Obviously, there exists a Markovian corruption relating *P* and \tilde{P} , since they are probability measures and our exhaustiveness argument holds. However, that would not reflect the "natural" definition of selection bias, acting through the weighting function α .

4 Consequences of Corruption: Data Processing Equalities

Having identified all the types of pairwise Markovian corruptions, a natural consequent question is how to systematically compare them. To this end, we can draw insights from the theory of *comparison of statistical experiments* [81, 64]. Traditionally, experiments have been compared through Bayes Risk, or more generally, through measures of information, using what is known as the Data Processing Inequality, or Blackwell-Sherman-Stein Theorem.¹⁰ The result states that for an experiment *E* and its corrupted counterpart through a suitably defined Markov kernel κ , we have

$$BR_{\ell}[\pi \times E] \leq BR_{\ell}[\pi \times (E \circ \kappa)] \quad \forall \pi, \ell,$$

where the model class is not restricted. A key point of the theorem is the *for all* requirement, which makes the comparison not possible for pairs of experiments that change the direction of the inequality for some (π, ℓ) , inducing a partial order on the set of experiment. In addition, it is only stated for corruptions on *E* acting via P1.

Recently, in Williamson and Cranko [23], Data Processing Equality results have also been studied within the supervised learning framework and under an information-theoretic point of view. They include more realistic assumptions for Machine Learning, such as a restricted model class \mathcal{H} , a fixed loss of interest ℓ and a suitable prior distribution that associated to the experiment E uniquely identifies the joint distribution $P \in \mathcal{P}(X \times Y)$. More formally, they are of the form

$$\operatorname{BR}_{\widetilde{\ell \circ \mathcal{H}}}[\widetilde{\pi} \times \widetilde{E}] = \operatorname{BR}_{\ell \circ \mathcal{H}}[\pi \times E] ,$$

where the changes in the minimization set, $\ell \circ \mathcal{H} \coloneqq \{(x, y) \mapsto \ell(h_x, y) \mid h \in \mathcal{H} \subseteq \mathcal{M}(X, Y)\}$, and joint probability, $\pi \times E$, are indicated by a $(\tilde{\cdot})$ and determined by the Markov corruption relating the probability spaces. In computer science, data corruption has the consequence of "produc[ing] unexpected results when [the data are] accessed by the system or the related application" [83]. By fixing the learning problem we take a similar stance, and start analysing formally the "unexpected results" with respect to a specific application.

The equality trivially induces an equivalence relation on the space of all possible learning problems, that we write as

$$(\widetilde{\ell \circ \mathcal{H}}, \widetilde{P}) \equiv_{\scriptscriptstyle \mathrm{BR}} (\ell \circ \mathcal{H}, P)$$
.

Williamson and Cranko [23] only considered corruption acting on the sole experiment by composition, specifically they use what is referred by us as simple *X* and *Y* corruption.

Here we also adopt the equality approach to compare the clean and corrupted experiments through Bayes Risk for a fixed loss function. The equalities formally characterize how the optimization problem is affected by the different kinds of joint corruption in our taxonomy; the corruption is therefore acting on the joint probability distribution instead of on the experiment. A direct consequence is that some results are expressed in terms of experiments, others in

¹⁰See [64] for a primer in classical statistical learning theory and [82] for a modern overview from a machine learning perspective.

terms of posterior kernel. The section gives us quantitative results in terms of conserved "information" between corrupted and clean learning problems, and a bridge between the problems themselves. Interestingly, what we prove is that a Markovian corruption of the probability distribution is equivalent, in terms of Bayes Risk, to a non-Markovian corruption involving the loss and/or the model class and induced by a Markov kernel.

Notation and assumptions When introducing Markov kernels in Def. 1, we allowed it to be defined on different input and output spaces. However, we also align with a more classical view of kernels as related to Markov chains, considering them modification of the same set of objects while rearranging the probability measure defined on it. Hence, a corruption from $X \times Y$ to Y has to be considered as a *parameterized version* of the corruption on Y, where the parameter is x. For this reason, we also introduced the operation P4, which allows chaining while keeping a specified free parameter. A degenerate sub-case takes place when we deal with a kernel from X to Y. We will make use of the notation κ_y , κ_x to express the parameterization, which is a shortcut for the for $\kappa_{Y=y} = \kappa_y$, $\kappa_{X=x} = \kappa_x$ respectively.

Two key assumptions will be used in the following:

A1 The loss function $\ell : \mathcal{P}(Y) \times Y \to \mathbb{R}_{\geq 0}$ associated with the learning problem (ℓ, \mathcal{H}, P) is *proper* and *bounded*.

A2 The BR ground-truth minimizer $f^* := \ell(F_X, Y) \in \arg\min_f \mathbb{E}_{\tilde{p}}[f(X, Y)]$ for the unconstrained problem belongs to the minimization space $\ell \circ \mathcal{H}$, i.e., the model class is *not misspecified*.

The first assumption restricts the definition of loss function we gave in § 2.2; positivity and boundedness together ensure the Fubini-Tonelli's theorem to be applied safely in the proofs. As for properness, it is known that choosing a *proper loss* [84] guarantees optimal learning, wherein the minimization set contains the ground-truth class probability. Therefore, the first and second assumptions ensure that our Bayes Risk classifier corresponds to the true minimum F; otherwise we would have a misspecified model class in the Constrained BR, that does not contain the true posterior, and a loss that might be minimized for some suboptimal classifier. We remark that, as shown in Williamson et al. [85], a certain class of losses can be parameterized so to qualify as a proper loss; for this reason, the assumption of properness is not too restrictive.

In all the following statements, we write the joint corruption action on the learning problem as the superposition $\tau \otimes \lambda$, where $I(\tau) = X$ and $I(\lambda) = Y$. Their full signature will be provided in each theorem. Also, we use the notation $\kappa \mathcal{F} := {\kappa f, \forall f \in \mathcal{F}}$ for the action of a kernel on a compatible set of functions.

Existing result: Data Processing Equalities for combined simple noise As a first step, we can show that our framework subsumes the existing result proved by Williamson and Cranko [23]. In our taxonomy, their combined noise takes the name of combined simple noise.

Proposition 13 (BR under combined simple noise, Williamson and Cranko [23]). Let A1 and A2 hold. Consider the clean learning problem (ℓ, \mathcal{H}, P) , $E : Y \rightsquigarrow X$ its associated

experiment such that $P = \pi_Y \times E$ for a suitable π_Y , and $F : X \rightsquigarrow Y$ its associated posterior such that $P = \pi_X \times F$ for a suitable π_X . Let $(\tau : X \rightsquigarrow X) \otimes (\lambda : Y \rightsquigarrow Y)$ be a corruption acting on this problem. Then,

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ \left((E \circ \tau) \otimes \lambda\right)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_Y \times E\right), \quad (3)$$

or, equivalently

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ (\tau \otimes (F \circ \lambda))\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_X \times F\right).$$
(4)

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_y \circ h)](x), h \in \mathcal{H}\}.$$

Starting from this simpler result, we can easily observe some properties of corruption that will be conserved also in the next cases. Consider the hypotheses of Proposition 13, with $\tau \otimes \lambda = \delta_X \otimes \lambda$, i.e. a corruption acting only on labels. The formula in Eq. (4) therefore is:

$$\operatorname{BR}_{\ell \circ \mathcal{H}} \left[\pi_{X} \circ \left(\delta_{X} \otimes (F \circ \lambda) \right) \right] = \operatorname{BR}_{(\lambda \ell \circ \mathcal{H})} \left[\pi_{X} \times F \right].$$

When looking at the right-hand side, we see that the λ component only modifies the loss function, and leaves the model class untouched. That means, *simple label (Markovian) corruptions are equivalent in Bayes Risk to loss corruptions*, which is non-Markovian in the sense of Def. 7, but induced by a Markov kernel. On the other hand, when considering $\tau \otimes \lambda = \tau \otimes \delta_Y$, we obtain

$$\mathbf{BR}_{\ell\circ\mathcal{H}}\left[\pi_{Y}\circ\left((E\circ\tau)\otimes\delta_{Y}\right)\right]=\mathbf{BR}_{\tau(\ell\circ\mathcal{H})}\left[\pi_{Y}\times E\right],$$

and in this case notice that the action of $\kappa = \tau \otimes \lambda$ affects the whole minimization set when considering the Bayes Risk on the clean distribution.

Novel Data Processing Equalities for other corruptions We now present the results for each of the remaining corruption combinations in Fig. 2.

Theorem 14 (BR under 2-dependent τ , simple λ). Let A1 and A2 hold. Consider the learning problem (ℓ, \mathcal{H}, P) and suppose $E : Y \rightsquigarrow X$ is its associated experiment such that $P = \pi_Y \times E$ for a suitable π_Y . Let $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : Y \rightsquigarrow Y)$ be a corruption acting on this problem. Then,

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ \left((E \circ_X \tau) \otimes \lambda\right)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_Y \times E\right).$$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_y \circ h)](x, y), h \in \mathcal{H}\}.$$

Here in Theorem 14 we have shown the BR equality for the experiment E, in line with the Comparison of Experiments [64] and Information Equalities literature [23]. However, for some corruptions the equalities cannot be stated with E and the generative formulation of a learning problem, unless ignoring the joint corruption factorization formula. We hence use the posterior

kernel *F*, i.e. the discriminative formulation of a learning problem, and gain more insights about the minimization set while paying a price in elegance of the result.

Theorem 15 (BR under simple τ , 2-dependent λ). Let A1 and A2 hold. Consider the learning problem (ℓ, \mathcal{H}, P) and suppose $F : X \rightsquigarrow Y$ is its associated posterior such that $P = \pi_X \times F$ for a suitable π_X . Let $(\tau : X \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$ be a corruption acting on this problem. Then,

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ (\tau \otimes (F \circ_Y \lambda))\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_X \times F\right).$$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_{(x, y)} \circ h)](x), h \in \mathcal{H}\}.$$

We can notice, thanks to Theorems 14 and 15, that when corruption involves dependent structures in the factorization, the loss function or the whole minimization set are modified in a parameterized, *dependent* way. Consider, for instance, the action of $\lambda : X \times Y \rightsquigarrow Y$ on the minimization set, when $\tau = \delta_X$. By definition, it generates the measurable functions

$$\lambda \ell \circ \mathcal{H} = \{(x, y) \mapsto (\lambda \ell)(h_x, x, y) \mid h \in \mathcal{H}\} = \{(x, y) \mapsto (\lambda \ell_{(x, y)} \circ h)(x)\},\$$

which a is strong change in the definition of the loss function class considered, although a still valid choice. We additionally underline here that *corruptions on* Y *only affect the loss function and do not touch the model class, even in the dependent case.*

The next theorems cover the factorizations involving 1-dependent corruptions. In the first case, we are again forced to use either E or F, depending on the involved factors. We group the two results in one theorem for brevity.

Theorem 16 (BR under a 1-dependent and a 2-dependent). Let A1 and A2 hold. Consider the clean learning problem (ℓ, \mathcal{H}, P) , suppose $E : Y \rightsquigarrow X$ is its associated experiment such that $P = \pi_Y \times E$ for a suitable π_Y , and $F : X \rightsquigarrow Y$ its associated posterior such that $P = \pi_X \times F$ for a suitable π_X .

1. Let $(\tau : Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$ be a corruption acting on the problem. Then,

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ \left(\tau \otimes (E \circ_X \lambda)\right)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_Y \times E\right).$$
(5)

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_{(x, y)} \circ h)](y), h \in \mathcal{H}\}.$$

2. Let $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \rightsquigarrow Y)$ be a corruption acting on the problem. Then,

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ \left((F \circ_Y \tau) \otimes \lambda\right)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_X \times F\right).$$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_x \circ h)](x, y), h \in \mathcal{H}\}.$$

Since the 1-dependent κ and λ combination is a subcase of both previous corruptions, we can prove the result as a simple corollary. Notice that this implies both *E* and *F* formulations to hold.

Corollary 17 (BR under 1-dependent τ and λ). Let A1 and A2 hold. Consider the clean learning problem (ℓ, \mathcal{H}, P) , $E : Y \rightsquigarrow X$ its associated experiment such that $P = \pi_Y \times E$ for a suitable π_Y , and $F : X \rightsquigarrow Y$ its associated posterior such that $P = \pi_X \times F$ for a suitable π_X . Let $(\tau : Y \rightsquigarrow X) \otimes (\lambda : X \rightsquigarrow Y)$ be a corruption acting on the problem. Then,

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ (\tau \otimes (E \circ \lambda))\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_Y \times E\right).$$

or, equivalently,

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ ((F \circ \tau) \otimes \lambda)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_X \times F\right).$$
(6)

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_x \circ h)](y), h \in \mathcal{H}\}.$$

In all the Theorems involving a 1-dependent corruption, the minimization set is heavily modified. To better understand how, we take a closer look at the functions contained in the clean and corrupted minimization sets. To see it in details, we first need to slightly rework the notation for the minimization set. Consider the loss function $\ell(\cdot, y)$ as a parameterized one, i.e. $\ell_y(\cdot) : \mathcal{P}(Y) \to \mathbb{R}_{\geq 0}$; then, the set $\ell \circ \mathcal{H} := \{(x, y) \mapsto \ell(h_x, y) | h \in \mathcal{H} \subseteq \mathcal{M}(X, Y)\}$ can be equivalently rewritten as $\{(x, y) \mapsto (\ell_y \circ h)(x) | h \in \mathcal{H} \subseteq \mathcal{M}(X, Y)\}$.

In Eq. (5), we have again the kernel $\lambda \in \mathcal{M}(X \times Y, Y)$ acting on the loss; hence, we obtain $\tilde{\ell}_{(x,y)} = \tilde{\ell}(\cdot, x, y) \coloneqq (\lambda \ell)(\cdot, x, y)$. Additionally, the whole composition with the model h, i.e. $(\tilde{\ell}_{(x,y)} \circ h)(\tilde{x})$, is modified by the action of $\tau \in \mathcal{M}(Y, X)$, which "swaps" the input $\tilde{x} \in X$ with $y \in Y$ in addition to modifying the function itself. Combining them together, we get the new minimization set containing functions of the form $f(x, y) = [\tau(\tilde{\ell}_{(x,y)} \circ h)](y)$, which is not anymore comparable with the initial form $\ell_{\tilde{y}} \circ h(\tilde{x})$, nor interpretable as a performance evaluation for the model h.

A similar strong modification is observed for the minimization set in Eq. (6), which contains functions of the form $f(x, y) = [\tau(\tilde{\ell}_x \circ h)](y) \coloneqq [\tau((\lambda \ell)_x \circ h)](y)$. That because, the action of $\lambda \in \mathcal{M}(X, Y)$ on $\ell(\cdot, y)$ results in a new loss function $(\lambda \ell)_x(\cdot) \coloneqq \lambda \ell(\cdot, x)$, while the action on the composition with *h* is as described in the case above.

The final result of the factorization, involving $\tau : X \times Y \rightsquigarrow X$ and $\lambda : X \times Y \rightsquigarrow Y$, yields a negative implication as detailed in the following.

Theorem 18 (BR under 2-dependent κ and λ). Let A1 and A2 hold. Consider the clean learning problem (ℓ , \mathcal{H} , P), and let ($\tau : X \times Y \rightsquigarrow X$) \otimes ($\lambda : X \times Y \rightsquigarrow Y$) be a corruption acting on the problem. Then:

1. the action of such corruption on the joint probability P is equivalent to the one of the non-decomposed joint corruption;

2. the action on the minimization set $\ell \circ \mathcal{H}$ induces the following BR-equivalence

 $(\ell, \mathcal{H}, P \circ (\tau \otimes \lambda)) \equiv_{BR} (\tau(\lambda \ell \circ \mathcal{H}), P);$

3. *the functions contained in the new minimization set are defined as*

 $\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_{(x, y)} \circ h)](x, y), h \in \mathcal{H}\}.$

This predicament arises due to the full dependence on the joint space $X \times Y$ for both τ and λ , making it impossible in general to derive a meaningful decomposition of the action on *P* via P 1, 2 and 4. However, we can still discern the effect of λ on the loss, as achieved in all previous cases, and of τ on the full minimization set. For a detailed analysis and proof, see § S5.

5 Corruption-corrected Learning: Loss-correction Approaches

We now leverage our corruption framework and the derived Data Processing Equalities to reason about the problem "*can we ensure unbiased learning from biased data*?". In this context, "bias" refers to a non-identical joint corruption acting on a pre-existent target probability, giving rise to a corrupted training probability. The model trained on the biased data drawn from this corrupted training probability will then be tested on data drawn from the target probability, also called the clean probability. The concept of unbiased learning is harder to formalize depending on the type of corruption; we now make an effort to carefully state its definition.

Unbiased learning as corruption-corrected learning We start by redefining the concept of biased data as *corrupted probability distribution as data source*. That means, we assume the term *biased* to refer to a non-identical joint corruption acting on a pre-existent target probability, giving rise to a corrupted training distribution. The learned model will be then tested on the data drawn from a target probability, also called clean probability.

As for the goal of reaching *unbiased learning*, such a task can be interpreted in several different ways, each of them radically transforming its formalization. Existing work from van Rooyen and Williamson [26] and Patrini et al. [12] made use of the concept of *corruption-corrected learning* (cL). Namely, that is the ability of a model learned on the corrupted distribution \tilde{P} , to be optimal also for the clean distribution P but for a *different loss function*.¹¹ They therefore study the form of the *loss correction* which is enforcing such condition on the model. They additionally show this method to be equivalent to the "method of unbiased estimators" from Natarajan et al. [11]. In these works the underlying framework is similar to ours, although only accounting for the presence of simple Υ corruption, i.e., $\delta_X \otimes \lambda$, $\lambda : \Upsilon \rightsquigarrow \Upsilon$.

Another closely related loss correction paradigm is *importance weighting* (IW), originally introduced for the covariate shift case under model misspecification [13, 86, 40]. This loss correction technique has the goal of obtaining on the corrupted space a consistent estimator of the risk on clean distribution. This is a weaker requirement than the cL's goal of obtaining a consistent estimator of the loss function, as it is clear when looking at Liu and Tao [87], where the IW method is applied to label noise. An additional difference between the methods is

¹¹Patrini et al. [12] refers to this task as *forward correction*.

that, typically, whas the additional requirement for the clean distribution to be absolutely continuous w.r.t. the corrupted one, i.e., $P \ll \tilde{P}$. This further assumption allows for a simple loss correction formula based on the importance weights $w(x) \coloneqq \frac{dP}{d\bar{P}}(x)$, often rewritten using their densities w.r.t. the Lebesgue measure. Recently, various attempts to generalize the tw paradigm to more general distributional changes have been made [88, 89] with the goal of tackling also more complex scenarios of corruption that modern deep learning algorithms currently have to face. In these works, while the estimation of suitable weights is implemented in different ways, the loss correction always takes the form of $\ell(h(x), y) \coloneqq w(x, y) \ell(h(x), y)$. Such a formula is similar to the ones we will prove here, but obviously not a subcase; as already discussed in § 3, there is a fundamental difference between kernels and Radon-Nikodym derivatives. Additionally, we exclude the model class misspecification case as we only deal with Markovian corruptions, while *w* includes it. For these reasons, a direct comparison of iw-derived techniques with our setting is not possible on a theoretical level. However, as we will argue in the following, dealing with attribute noise that is not covariate shift, and even more generally with joint distributional shift, leads to severe consequences on the optimization problem. That is proved to happen under the most optimistic set of assumptions; no indication of it being generally easier in more complex cases involving model misspecification is given by our analysis. We provide a negative result at the end of the section, underlying the fundamental differences distinguishing label and attribute corruption. This ultimately suggests that, in case of uncertainty about the type of attribute noise present in the data, a practitioner should avoid using simple loss correction methods.

5.1 The Bayesian inverse of a Markov kernel

To study the CL problem under our framework, we first need to define a way to reverse the corruption process. In van Rooyen and Williamson [26] this problem was solved by introducing the subclass of *reconstructible kernels*: they are considered in finite spaces and are defined as the *left inverse of the stochastic matrix representing the Markov kernel*. It has the drawback of not necessarily being a transition kernel. For instance, in Patrini et al. [12] the authors underline that the corrected loss with reconstructible kernels can assume negative values. This issue exacerbates when employing unbounded losses, e.g., cross-entropy, where the corrected loss can be unbounded from below. Moreover, they discuss that loss correction with reconstructible kernels can be problematic when the condition number of the kernel matrix is large, since the reconstruction computation becomes highly sensitive to perturbations of the kernel matrix. We introduce here the Bayesian inverse of a Markov kernel, that instead preserves the Markov property.

Definition 19. The **Bayesian inverse** of a Markov kernel $\kappa : Z_1 \rightsquigarrow Z_2$ with the property $\tilde{P} = P \circ \kappa$ for $P \in \mathcal{P}(Z_1)$, $\tilde{P} \in \mathcal{P}(Z_2)$ is defined as a Markov kernel $\kappa^{\dagger} : Z_2 \rightsquigarrow Z_1$, such that 1. $P = \tilde{P} \circ \kappa^{\dagger}$, i.e., it reverses the action on the fixed input and output probabilities; 2. $P \times \kappa = \tilde{P} \times \kappa^{\dagger}$, i.e., it induces the same coupling for the fixed input and output probabilities.

We will refer to the Bayesian inverse of the corruption kernel as the *cleaning kernel*. In general, the Bayesian inverse is not unique, since it corresponds to a class of equivalence induced by the probability measures on Z_1 and Z_2 . However, we are always sure it exists given the assumption of using standard Borel measure spaces when defining Markov kernels. In the discrete case, the Bayesian inverse always exists and is defined by Bayes rule. Furthermore, it is uniquely defined \tilde{P} -a.s. More explanations about this object and its properties are given in § S3.

In the following, we assume $Z_1 = Z_2 = Z = X \times Y$ to match the setting of our taxonomy of corruption. The Bayesian inversion operation has the desirable property of preserving the expectations. More formally, one can easily prove that the following equality holds for all $f \in L^0(Z, \mathbb{R})$:

$$\mathbb{E}_{\mathsf{Z}\sim P}[f(\mathsf{Z})] = \mathbb{E}_{\tilde{\mathsf{Z}}\sim\tilde{P}=P\circ\kappa}[\kappa^{\dagger}f(\tilde{\mathsf{Z}})].$$
(7)

5.2 Corruption-corrected learning with Bayesian inverse

The CL paradigm, as defined in the literature, aims to find a formula for the corrected loss function $\tilde{\ell}$ that depends on ℓ and the considered corruption of the learning problem. In our case, the latter is identified by the kernel κ and its inversion κ^{\dagger} . We formally restate the paradigm as solving for some $\tilde{\ell}$ the problem

$$BR_{\ell \circ \mathcal{H}}(P) = BR_{\tilde{\ell} \circ \mathcal{H}}(\tilde{P}), \text{ minimized by the same } h^* \in \mathcal{H}.$$
(8)

Considering a cleaning kernel sending $\tilde{\mathcal{L}} = (\tilde{\ell}, \mathcal{H}, \tilde{P})$ to $\mathcal{L} = (\ell, \mathcal{H}, P)$ of the form $\kappa^{\dagger} = \delta_X \otimes \lambda, \lambda : Y \rightsquigarrow Y$, we recover the conditions of Proposition 13 and know that such corruption case only affects the loss function. Using the Bayesian inverse as in Def. 19, we can rewrite the corruption action on the learning problem as the equivalence relation

$$(\ell \circ \mathcal{H}, P) \equiv_{BR} (\lambda \ell \circ \mathcal{H}, P \circ (\delta_X \otimes \lambda^{\dagger})),$$

which is in line with the first part of the cL condition in Eq. (8), involving the BR. Thanks to the property of the weak derivative in Eq. (7), we are sure that

$$\mathbb{E}_{P}[(\ell \circ h)(Z)] = \mathbb{E}_{P \circ (\delta_{X} \otimes \lambda^{\dagger})}[(\lambda \ell \circ h)(Z)] \quad \forall h \in \mathcal{H}$$

Therefore the second part of Eq. (8) is fulfilled since the two quantities will be minimized on the same hypothesis, and the loss correction formula is $\tilde{\ell} = \lambda \ell$, analogously to [26].

We can extend such paradigm to the λ : $X \times Y \rightsquigarrow Y$ case, as from Theorem 15 we see that also in the dependent case label corruption only affects the loss function.

Theorem 20. Let (ℓ, \mathcal{H}, P) be a clean learning problem and $(\kappa^{\dagger}(\ell \circ \mathcal{H}), P \circ \kappa)$ its associated corrupted one. Let κ^{\dagger} be the joint cleaning kernel reversing κ , such that assumptions A1 and 2 hold for the said problems, and such that $\kappa^{\dagger} = \delta_X \otimes \lambda$. When $\lambda \in \mathcal{M}(Y, Y)$, we have

 $\tilde{\ell}(h(\tilde{x}), \tilde{y}) \coloneqq (\lambda \ell) (h(\tilde{x}), \tilde{y}) \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y,$

while, when $\mathcal{M}(X \times Y, Y)$ we have

$$\tilde{\ell}(h(\tilde{x}), \tilde{x}, \tilde{y}) \coloneqq (\lambda \ell) (h(\tilde{x}), \tilde{x}, \tilde{y}) \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y.$$

We defer the formal proof of the statement to § S6, and only underline here that our result matches the one from van Rooyen and Williamson [26], although using a correction that is in general different form the one induced by the kernel reconstruction.

5.3 Generalizing corruption-corrected learning beyond label corruption

For corruptions more complex than simple *Y* corruption, we cannot guarantee cL as previously stated. When starting from our BR results for cases where *X* corruption $\kappa \neq \delta_X$ is included in

the factorization of the full corruption, the model class will also be affected – see Proposition 13, Theorems 14 to 16 and 18, and Corollary 17. The equivalence relation therefore is general one, i.e.,

$$(\ell \circ \mathcal{H}, P) \equiv_{BR} (\kappa^{\dagger}(\ell \circ \mathcal{H}), P \circ \kappa).$$

Notice that if we assume for κ a feasible factorization from Fig. 2, we cannot say anything about the factorization of κ^{\dagger} unless we only deal with simple corruptions. For this reason, in the following we will assume a factorization $\kappa^{\dagger} = \tau \otimes \lambda$.

The corruption effect on loss and model class is, in this most general case, *indistinguishable*; we are not able to rewrite the set $\kappa^{\dagger}(\ell \circ \mathcal{H})$ as the composition $\tilde{\ell} \circ \tilde{\mathcal{H}}$, let alone $\tilde{\ell} \circ \mathcal{H}$ as per the CL case. In other words, our BR equalities do not allow to generalize CL to these other corruption cases cases. However, we can still gain some understanding on how corruptions involving a non-identical kernel corrupting the attributes change the corruption-corrected learning problem. For this reason, we formalize a weakened version of the CL paradigm, requiring to find a loss correction formula $\tilde{\ell}$ that depends on ℓ and κ^{\dagger} such that

$$\operatorname{BR}_{\ell \circ \mathcal{H}}(P) = \operatorname{BR}_{\tilde{\ell} \circ \mathcal{H}}(\tilde{P}) , \text{ minimized by the same } f^* \in (\ell \circ \mathcal{H}) \cap \kappa^{\dagger}(\ell \circ \mathcal{H}) .$$
(9)

We refer to this new paradigm as *generalized corruption-corrected learning* (GCL). As it is currently stated, it is not necessarily well-posed since the existence of such a f^* is not guaranteed. We then need to discuss which further assumptions are needed.

Additional assumption for GCL The use of the Bayesian inverse ensures the existence of a function $f^* \in \ell \circ \mathcal{H} \cap \kappa^{\dagger}(\ell \circ \mathcal{H})$ that minimizes the Bayes Risk, i.e.

$$f^* \in \underset{f \in \ell \circ \mathcal{H}}{\operatorname{arg\,min}} \mathbb{E}_P f(Z) \text{ and } f^* \in \underset{f \in \kappa^{\dagger}(\ell \circ \mathcal{H})}{\operatorname{arg\,min}} \mathbb{E}_{P \circ \kappa} f(Z) .$$

In general, we are not sure that the corrupted minimization set $\kappa^{\dagger}(\ell \circ \mathcal{H})$ can be rewritten in a factorized fashion, i.e. $\kappa^{\dagger}(\ell \circ \mathcal{H}) = \tilde{\ell} \circ \mathcal{H}$ for some corrected loss $\tilde{\ell}$. However, by introducing one further assumption, we can get to a loss correction results so that the learned hypothesis on \tilde{P} will have the same performance scores f^* as the optimal on (ℓ, \mathcal{H}, P) ,¹² while ensuring $f^* = \tilde{\ell} \circ \tilde{h}^* \in (\ell \circ \mathcal{H}) \cap \kappa^{\dagger}(\ell \circ \mathcal{H})$. This is, formally, solving the problem of GCL.

Let us consider the composed representation of the function f^* in the clean (test) minimization set, which is $f^* = \ell \circ h^*$. We want to construct a suitable composed representation for f^* also in the space $\kappa^{\dagger}(\ell \circ \mathcal{H})$, namely $f^* = \tilde{\ell} \circ \tilde{h}^*$ such that $\tilde{h}^* \in \mathcal{H}$ and \tilde{h}^* is a minimizer for $\tilde{\ell}$. This translates to the condition

$$f^* = \tilde{\ell} \circ \tilde{h}^* \in \kappa^{\dagger}(\ell \circ \mathcal{H}) \quad \text{s.t.} \quad \tilde{h}^* \in \underset{h \in \mathcal{H}}{\arg\min} \mathbb{E}_{\mathsf{Z} \sim P \circ \kappa} \left[(\tilde{\ell} \circ h)(\mathsf{Z}) \right] \ .$$

While we observe that we are guaranteed to have such $\tilde{\ell}$ at least in the case of \tilde{h}^* being invertible,¹³ the practical feasibility of this assumption, as well as whether alternative conditions may fulfill the goal of GCL, are beyond the scope of the current analysis. We postulate its existence as the first part of our assumption.

¹²In plain words, the values assumed by the loss on the best hypothesis.

¹³This is easy to check: take h^* invertible as a function $\tilde{h}^* : X \to \mathcal{P}(Y)$, it would ensure the existence of such a loss, since $\tilde{\ell}(p, y) := \ell(h^*((\tilde{h}^*)^{-1}(p)), y)$. A direct consequence of this is that requiring $h^* = \tilde{h}^*$ would imply $\ell = \tilde{\ell}$, which is not a case of interest since no correction would be needed.

Since in general $\kappa^{\dagger}(f^*) \neq f^*$, we have that: $\exists h' \in \mathcal{H}$ s.t. $\kappa^{\dagger}(\ell \circ h') = \tilde{\ell} \circ \tilde{h}^*$. We discard the case $h' = h^*$, so to avoid imposing the trivial condition $\ell \circ h^* = \tilde{\ell} \circ \tilde{h}^* = \kappa^{\dagger}(\ell \circ h^*) = f^*$. In this subcase, we would have that $BR_{\ell \circ \mathcal{H}}[P] = BR_{\ell \circ \mathcal{H}}[\kappa \circ P]$, i.e., the corruption is harmless to Bayes Risk. We choose the corrected loss function so that corrupted optimum is $\tilde{h}^* = h'$. This provides us a bridge between the the original and the corrected loss functions.

A3 There exist a loss function $\tilde{\ell}$ such that $f^* = \tilde{\ell} \circ \tilde{h}^* \in \kappa^{\dagger}(\ell \circ \mathcal{H})$, with f^* being also a minimizer of the problem $\min_{f \in \tilde{\ell} \circ \mathcal{H}} \mathbb{E}_{Z \sim P \circ \kappa} [f(Z)]$, and that satisfies the equality $\kappa^{\dagger}(\ell \circ \tilde{h}^*) = \tilde{\ell} \circ \tilde{h}^*$.

We can now proceed to reason about loss correction in this case. It is worth noting again that we do not delve into analyzing the restrictiveness of this assumption or methods to test the existence of such a structure; our interest is solely to showcase its implications for GCL.

Loss correction formula for GCL We now give the correction results for all the corruption case lying within the GCL paradigm, while deferring the proof to § S6. Recall that the notation $\mu #f(z)$ stands for the push-forward probability measure of the distribution μ through the function f. In the following we will use such notation for kernels. For instance, let $\tau(\tilde{x}, dx) \in \mathcal{M}(X, X)$ and $h(x, dy) \in \mathcal{M}(X, Y)$: by definition of kernel, τ is a measure when fixing $\tilde{x} \in X$ and $h: X \to \mathcal{P}(Y)$ is a function. Hence, if we write $(\tau #h)(\tilde{x})(A) := \tau(h^{-1}(A), \tilde{x})$, $A \subset \mathcal{P}(Y)$, that is a family of distributions defined on a set of probability measures on Y, evaluated on A and indexed by \tilde{x} . Since it is indexed and induced by Markov kernels, we can see it as a posterior probability on the set $\mathcal{P}(Y)$, given \tilde{x} .

Theorem 21. Let (ℓ, \mathcal{H}, P) be a clean learning problem and $(\kappa^{\dagger}(\ell \circ \mathcal{H}), P \circ \kappa)$ its associated corrupted one. Let κ^{\dagger} be the joint cleaning kernel reversing κ , such that assumptions A1 and 2 hold for the said problems, and such that A3 holds for $\kappa^{\dagger} = \tau \otimes \lambda$. Hence, provided that ℓ_{ξ} is a function in $L^{0}(\mathcal{P}(Y), (\tau \# h)(\xi))$, with ξ being either \tilde{x} or \tilde{y} depending on the case, we have:

1. When κ^{\dagger} is of the form $(\tau : X \rightsquigarrow X) \otimes (\lambda : Y \rightsquigarrow Y)$, or $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : Y \rightsquigarrow Y)$, or $(\tau : X \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$, we have

 $\tilde{\ell}(h, \tilde{x}, \tilde{y}) \coloneqq \mathbb{E}_{\mathsf{u} \sim (\tau \# h)(\tilde{x})} [\lambda \ell(\mathsf{u}, \tilde{y})] \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y.$

For the cases that involve a 2-dependent corruption, for the former κ^{\dagger} factorization we have $\lambda(\ell) = \lambda_{\tilde{x}}(\ell) - inducing \ \lambda\ell(\mathbf{u}, \tilde{x}, \tilde{y})$, while we get $(\tau \# h)(\tilde{x}) = (\tau \# h)(\tilde{x}, \tilde{y})$ for the latter.

2. When κ^{\dagger} is of the form $(\tau : Y \rightsquigarrow X) \otimes (\lambda : X \rightsquigarrow Y)$, we have

$$\tilde{\ell}(h, \tilde{x}, \tilde{y}) \coloneqq \mathbb{E}_{\mathsf{u} \sim (\tau \# h)(\tilde{y})} [\lambda \ell(\mathsf{u}, \tilde{x})] \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y.$$

3. When κ^{\dagger} is of the form $(\tau : Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$, or $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \rightsquigarrow Y)$, we respectively have

$$\begin{split} \bar{\ell}(h,\tilde{x},\tilde{y}) &\coloneqq \mathbb{E}_{\mathsf{u}\sim(\tau\#h)(\tilde{y})}[\lambda\ell(\mathsf{u},\tilde{x},\tilde{y})] \quad \forall (\tilde{x},\tilde{y}) \in X \times Y;\\ \bar{\ell}(h,\tilde{x},\tilde{y}) &\coloneqq \mathbb{E}_{\mathsf{u}\sim(\tau\#h)(\tilde{x},\tilde{y})}[\lambda\ell(\mathsf{u},\tilde{x})] \quad \forall (\tilde{x},\tilde{y}) \in X \times Y. \end{split}$$

4. When κ^{\dagger} is of the form $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$, we have

$$\tilde{\ell}(h, \tilde{x}, \tilde{y}) \coloneqq \mathbb{E}_{\mathsf{u} \sim (\tau \# h)(\tilde{x}, \tilde{y})} [\lambda \ell(\mathsf{u}, \tilde{x}, \tilde{y})] \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y.$$

Label vs attribute corruption The corrections found in this section are more complex than the ones defined in previous work [26, 12], which only considers a label noise setting similar to our cL for simple label corruption. Our version, Theorem 20, further extends the result by including the dependent label corruption. The second set of results, included in Theorem 21, are only valid in the GCL setting and assuming A3, and not for CL. Therefore, under a Bayes risk point of view and under our assumptions A1-A3, *there is a fundamental difference between label and attribute corruption:* they induce distinct corrupted learning settings, and traditional loss correction does not ensure unbiased learning in the sense of cL.

When minimized, the corrected losses will, by construction, give back the hypothesis \tilde{h}^* . Since $\ell \circ h^* = \tilde{\ell} \circ \tilde{h}^*$, we achieve the GCL goal. That is, we achieve unbiased learning in the sense of matching loss scores and in the distributional sense. However, if no additional condition is imposed, we have no guarantee for \tilde{h}^* to be somehow close to h^* ; this result should not be taken as new tool for defining robust losses. In fact, Theorem 21 should be interpreted as a *negative result*: even assuming that a factorization $\tilde{\ell} \circ \tilde{h}^*$ exists, and that \tilde{h}^* is close to h^* according to some metric, classical loss correction is still not enough for achieving generalization in a corruption setting that involves a attribute corruption. One should also account for the set of posterior probabilities $\tau \# \tilde{h}^*$ and average on it, instead of only "reweighting" the loss.

6 Conclusions

We proposed a comprehensive and unified framework for general corruption, extending its definition also to model class and loss function changes. We did so by using Markov kernels, and systematically studying corruption in three key aspects: classification, consequence, and correction. The choice of working with Markov kernels enables the use of information-theoretical tools, and provides an alternative interpretation of corruption as an *observation channel* through which we get to see our data distribution. This mathematical modelization allows to consider data as a dynamic element of a learning problem, as opposed to the view of data as static facts and true representations of reality.

We established a new taxonomy for Markovian corruption, yielding qualitative comparisons between corruption models in terms of the corruption hierarchy. To gain a deeper understanding of corruption, we analyzed their consequences by proving Data Processing Equalities for Bayes Risk. Given different possible factorizations of a corruption of the joint space, the learning problem is affected in different ways. Furthermore, we applied such equalities for obtaining loss correction formulas. Such an application is rather conventional, and usually leads to a proposed mitigation for the specific model considered. In this work, we do not propose any mitigation algorithm, but analyze the fundamental difference between label and attribute noise. The Data Processing Equality results together with the analysis carried on in Section § 5 lead us to the following conclusions:

- Label and attribute corruption differ in how they change the learning problem. The former does not influence the model class; the latter changes model class and loss function in a generally non-disentangable way.
- Classical corrected learning (CL) is not an adequate paradigm to study general corruption. For cases involving non-identical attribute corruption, we introduce a more general setting named generalized corrected learning (GCL).
- Loss correction formulas for attribute corruptions require strong assumptions and involve

an additional component, the expectation over the set of all $\tau #h$ predictions. This implies a negative result, that suggests that standard loss corrections techniques do not guarantee generalization when dealing with attribute corruption.

Limitations and future work We considered data as probability distributions, implicitly assuming that each dataset has an associated probabilistic generative process. We treated corruption as Markov kernels, under the strong assumption of having full access to their actions. We note that in some cases Markov kernels can be estimated from corrupted data [87, 90], but this question in general is still open and needs further investigation. We analyzed the consequences of corruption through Bayes risks without accounting for sampling or optimization. Bridging the gap between the distributional-level and the sample-level results would be the next step for this study, which requires tailored ad-hoc analyses. Other directions for making this framework more practically usable include developing quantitative methods to compare corruption severity and investigating the effects of optimization algorithms on the analysis.

From a more theoretical point of view, future work includes investigating the non-Markovian corruption classes and non-pairwise corruptions. As we pointed out in § 3, model misspecification lies within the general corruption class, and might be studied alone as well as an additional corruption "chained" to a Markovian one. Similarly, changes in loss function can be analyzed further. Such developments would effectively generalize beyond the limitations imposed by Assumptions A1 and 2. Additionally, the topic of non-probabilistic corruption [91, 92], only superficially touched in the present work, needs a deeper analysis. It is unclear whether the current theoretical tools, deployed when dealing with distributional changes, are enough for characterizing and potentially mitigating their consequences on learning problems.

Acknowledgments

This work was partially funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) under Germany's Excellence Strategy — EXC number 2064/1 — Project number 390727645, as well as by the German Federal Ministry of Education and Research (BMBF): Tübingen AI Center, FKZ: 01IS18039A. The authors thank the International Max Planck Research School for Intelligent Systems (IMPRS-IS) for supporting Laura Iacovissi. Additional thanks to Nicolò Zottino and Jack Brady for many helpful discussions, as well as Christian Fröhlich for giving valuable feedback on an earlier version.

S1 Related existing paradigms

A Markov kernel-based taxonomy is substantially different from previous work. Therefore, in this section, we carefully examine how existing corruption models fit into our taxonomy. This involves reformulating them as specific instances of Markov corruptions, thereby unveiling their relationships within the corruption hierarchy presented in Fig. 1a.

The primary challenge stems from the lack of consistency across the literature; different authors sometimes refer to the same corruption process with different names or use the same name to denote different settings. For instance, classical studies on concept drift [51, 53] generally define it as a mismatch in the joint distributions between two different learning environments,

e.g., training and test times. Meanwhile, works such as in Moreno-Torres et al. [16] characterize it further by necessitating unchanged attribute or label priors.

We attempt a partial unification of the corruption models we are aware of by establishing connections as depicted in Tab. 2, while additional technical intricacies regarding correspondences and relationships are elucidated in subsequent sections.

S1.1 Simple corruptions

The most well-known and widely studied corruptions in the literature are the simple cases, where the corruption solely acts on the feature space X or the label space Y. We discuss in the following various examples of simple corruptions, i.e. in the sets $\mathcal{M}(X, X)$ and $\mathcal{M}(Y, Y)$, as defined in Fig. 1.

Attribute noise The problem of attribute noise concerns errors that are introduced into the observations of attribute X, leaving the labels untouched [20, 21, 22, 23]. Widely studied examples of such errors include erroneous attribute values and missing attribute values. Instead of observing (X, Y), in the first case, one can only observe a distorted version of X, e.g. (X + N, Y) with some independent noise random variable N \perp X; in the second case, one's observation of X contains missing values.

Let $\mathbf{X} = (x_{ij})_{1 \le i \le n, 1 \le j \le d}$ be the complete input matrix, with |X| = n, and $\mathbf{M} = (m_{ij})_{1 \le i \le n, 1 \le j \le d}$ be the associated missingness indicator matrix such that $m_{ij} = 1$ if x_{ij} is observed and $m_{ij} = 0$ if x_{ij} is missing. Then the corresponding observed input matrix is $\mathbf{X}_o = \mathbf{X} \odot \mathbf{M}$ and its missing counterpart is $\mathbf{X}_m = \mathbf{X} - \mathbf{X}_o$, where \odot denotes Hadamard product. The missing value mechanisms are further categorized into three types based on their dependencies [93, 94]:¹⁴

- Missing completely at random (MCAR): the cause of missingness is entirely random, i.e., p(M | X) = p(M) does not depend on X₀ or X_m. This corresponds to having a trivial Markov kernel acting on the clean distribution, τ : {*} → X ≡ μ ∈ 𝒫(X).
- Missing not at random (MNAR): the cause of missingness depends on both observed variables and missing variables, i.e., p(M | X) = p(M | X_o, X_m). This case corresponds to our non-trivial τ : X → X.
- Missing at random (MAR): the cause of missingness depends on observed variables but not on missing variables, i.e., p(M | X) = p(M | X₀). This case is a sub-case of the non-trivial τ : X → X, which is not directly specifiable by our taxonomy because of the different premises it is built on.

Class-conditional noise (ccn) The problem of ccn arises in situations where, instead of observing the clean labels, one can only observe corrupted labels that have been flipped with a label-dependent probability, while the marginal distribution of the instance remains unchanged [11, 12, 26, 23]. ccn is an example of simple label corruption, $\mathcal{M}(Y, Y)$, that can be formulated as a corrupted posterior. For classification tasks, Y is assumed to be a finite space. Therefore the corruption $\lambda : Y \rightsquigarrow Y$ can be represented by a column-stochastic matrix $\mathbf{T} = (\rho_{ij})_{1 \le i \le |Y|, 1 \le j \le |Y|}$ which specifies the probability of the clean label $\mathbf{Y} = j$ being flipped to the corrupted label

¹⁴Assume the rows x_i , m_i are assigned a joint distribution. and X and M are treated as random variables.

 $\tilde{Y} = i$, i.e., $\forall i, j, \rho_{ij} = p(\tilde{Y} = i | Y = j)$. The corrupted joint distribution can be rewritten as $\tilde{P} = \sum_{Y} p(\tilde{Y} | Y) p(Y | X) p(X)$. In the literature, **T** is known as the noise transition matrix with its elements ρ_{ij} referred to as the noise rates, and is useful for designing loss correction approaches (our results in § 5 significantly generalize existing loss correction results in ccn to our broad class of simple, dependent and combined corruptions) [12]. Prior to the proposal of the ccn model, early studies primarily focused on a symmetric subcase of **T** in binary classification, known as random classification noise (RCN) [9, 24, 25]. Note that in RCN, the output of the corruption $\lambda : Y \rightsquigarrow Y$ remains constant w.r.t. its parameters. Recently, some variants of ccn have been further developed, for example, in Ishida et al. [95, 96], complementary labels are modeled via a symmetric **T** whose diagonal elements are all equal to zero.

S1.2 Dependent corruptions

Although simple corruptions have been well studied and understood, more complexities arise in dependent cases, yet they receive relatively less attention and understanding. We discuss in the following examples of the dependent corruptions in the sets $\mathcal{M}(Y, X)$, $\mathcal{M}(X, Y)$, $\mathcal{M}(X \times Y, X)$ and $\mathcal{M}(X \times Y, Y)$, as defined in Fig. 1a.

Style transfer Style transfer refers to the process of migrating the artistic style of a given image to the content of another image [43, 44]. The primary objective is to recreate the second image with the designated style of the first image. In recent developments, it has also been applied to audio signals [45]. If we represent the style of the first image by Y, and the second image and the reconstructed image as X and \tilde{X} respectively, style transfer serves as an illustrative example of $\tau : Y \rightsquigarrow X$ "corruption". Note that the aim here is to *learn how to corrupt* instead of learning in the presence of corruption. We mention this connection because our framework can also be used also with different purposes, but underline that our BR results are not applicable to this case. The process of style transfer can be formulated as a corrupted posterior.

Adversarial noise In contrast to additive random attribute noise, adversarial noise is specifically crafted by adversaries for each instance with the intent of changing the model's prediction of the correct label [46, 47, 48, 49, 50]. Such adversarial examples raise significant security concerns as they can be utilized to attack machine learning systems, even in scenarios where the adversary has no access to the underlying model. The adversarial noise is an example of $\tau \in \mathcal{M}(X \times Y, X)$ corruption that can be formulated as a corrupted experiment.

Instance-dependent noise (IDN) As a counterpart to CCN, the problem of IDN arises in situations where, instead of observing the clean labels, one can only observe corrupted labels that have been flipped with an instance-dependent (but not label-dependent) probability [97, 27]. It is a special case of the ILN noise model, which we will describe later. IDN is an example of $\lambda \in \mathcal{M}(X, Y)$ corruption that can be formulated as a corrupted experiment.

Instance- and label-dependent noise (ILN) ILN is the most general label noise model, which arises in situations where, instead of observing clean labels, one can only observe corrupted labels that have been flipped with an instance- and label-dependent probability [27, 28, 29, 30]. ILN is an example of $\lambda \in \mathcal{M}(X \times Y, Y)$ corruption that can be formulated as a corrupted posterior. Compared to the matrix representation **T** of the CCN corruption $\kappa_{Y\tilde{Y}}$, the ILN corruption $\kappa_{XY\tilde{Y}}$ can be represented by a matrix-valued function of the instance $\mathbf{T}(x) = (\rho_{ij}(x))_{1 \le i \le |\tilde{Y}|, 1 \le i \le |Y|}$

which specifies the probability that the instance X = x with the clean label Y = j being flipped to the corrupted label $\tilde{Y} = i$, i.e., $\forall i, j, \rho_{ij}(x) = p(\tilde{Y} = i | Y = j, X = x)$. Some subcases of ILN have also been studied in the literature, for example, the boundary-consistent noise, which considers a label flip probability based on a score function of the instance and label. The score aligns with the underlying class-posterior probability function, resulting in instances closer to the optimal decision boundary having a higher chance of its label being flipped [98].

S1.3 Combined corruptions

Given the simple and dependent corruptions, we can combine them to generate 2-parameter joint corruptions, i.e., $\mathcal{M}(X \times Y, X \times Y)$. Below, we discuss some examples of combined noise models illustrated in Fig. 1b.

Combined simple noise The simplest combined corruption is the combined simple noise, where the observations of attribute X are subject to some errors and the observed labels Y are flipped with a label-dependent probability [23]. Combined simple noise is an example of $\tau : X \rightsquigarrow X \otimes \lambda : Y \rightsquigarrow Y$ corruption that can be formulated as a corrupted experiment.

Target shift In the literature, target shift, also known as prior probability shift, refers to the situation where the prior probability p(Y) is changed while the conditional distribution p(X | Y) remains invariant across training and test domains [35, 36, 37, 38]. The definition is established by assuming certain invariance from a generative perspective of the learning problem, that is, considering it as a corruption of the experiment according to $P = \pi_Y \times E$. However, when examining the learning problem from a discriminative perspective, the change in p(Y) may cause changes in both p(X) and p(Y | X) due to the Bayes rule. Existing frameworks for the categorization of target shift do not capture these implications, as they are based on the notion of invariance from a single perspective of the *E* direction. In contrast, our framework categorizes corruptions based on their dependencies and therefore is advantageous by offering dual perspectives from both the *E* and *F* directions. Specifically, target shift is a subcase of $\tau : Y \rightsquigarrow X \otimes \lambda : X \times Y \rightsquigarrow Y$ corruption and can be formulated either as a corrupted experiment or as a corrupted posterior. The corrupted distribution is given by $\tilde{P} = (\pi_Y \times E) \circ (\tau \otimes \lambda)$ or $\tilde{P} = (\pi_X \times F) \circ (\tau \otimes \lambda)$.

Covariate shift In the literature, covariate shift refers to the situation where the marginal distribution p(X) is changed while the class-posterior probability p(Y | X) remains invariant across training and test domains [13, 39, 40, 15]. Similarly to target shift, the definition is based on assuming invariance from the discriminative perspective of the learning problem, treating it as a corruption of the posterior using $P = \pi_X \times F$. However, when viewed from a generative perspective, changes in p(X) may lead to changes in p(Y) and p(X | Y) due to the Bayes rule. Covariate shift is a subcase of $\tau : X \times Y \rightsquigarrow X \otimes \lambda : X \rightsquigarrow Y$ corruption and can be formulated either as a corrupted posterior or as a corrupted experiment. The corrupted distribution is given by $\tilde{P} = (\pi_Y \times E) \circ (\tau \otimes \lambda)$ or $\tilde{P} = (\pi_X \times F) \circ (\tau \otimes \lambda)$.

It is important to clarify that while covariate shift is sometimes used interchangeably with sample selection bias in certain literature, the two are not synonymous. This point is also mentioned by the author of the original covariate shift paper [13] in the book by Quiñonero-Candela et al. [14, Chapter 11]: they claim covariate shift to be a special form of selection bias when the latter is taken under assumption of missing at random, and in general, selection

bias without such a structure is difficult. However, based on our definition of selection bias in Def. 12, it is not true that covariate shift is a special form of selection bias. Nonetheless, various definitions exist in the literature and they can relate in different ways.

We introduce here a classical definition of selection bias, which leads to the one we gave in the main text, see [14, Chapter 3.2]. Let S be a binary selection variable deciding whether a datum is included in the training set (S = 1) or excluded from it (S = 0). The corrupted distribution by selection bias can be expressed as $\tilde{P}(X, Y) = P(X, Y | S = 1)$. By assuming the missing at random structure, where S is independent of Y given X: P(S | X, Y) = P(S | X), we recover covariate shift where $P(X | S = 1) \neq P(X)$ and P(Y | X, S) = P(Y | X).

Note that covariate shift is only harmful when the model class is misspecified [13]. This issue is typically addressed through importance-weighted empirical risk minimization–weighting the training losses according to the ratio of the test and training input densities [40, 89]. In such context, the additional assumption of $P \ll \tilde{P}$ is required so to obtain the weighted risk on the training set to be equal to the risk on the test set. This assumption is therefore in contrast with Def. 12, requiring for selection bias the support condition $\tilde{P} \ll P$.

More in general, selection bias necessitates both the support condition and the selection condition with bounded $\frac{dP}{d\tilde{P}}(x_i, y_i) \forall i \in [n]$, which are stronger than the original definition of covariate shift assuming only the change of marginal distribution p(X) and the invariance of the class-posterior probability p(Y | X). As a result, there exist covariate shift scenarios that cannot be attributed to selection bias when $\tilde{P} \ll P$ is not the case.

Generalized target shift In the literature, generalized target shift refers to the situation where the prior probability p(Y) and the conditional distribution p(X | Y) both change across training and test domains, however, with some invariance assumptions in the latent space [10, 41, 42]. Generalized target shift is a subcase of $\tau : X \times Y \rightsquigarrow X \otimes \lambda : X \times Y \rightsquigarrow Y$ corruption that can be formulated as a corrupted experiment. Note that simplified sub-examples can also manifest as a generalized target shift; however, it is important to avoid degenerating into the basic $\tau : X \rightsquigarrow X$ corruption, as it would violate the requirement of corrupting the label distribution.

Concept drift, concept shift, and sampling shift Concept drift refers to the situation where data evolves over time, leading to different categorizations depending on the nature of the change. Typically, concept drift between time point t_0 and t_1 is characterized by $p_{t_0}(X, Y) \neq p_{t_1}(X, Y)$ [51, 52, 53]. In our words, $p_{t_1}(X, Y)$ can be seen as a corrupted version of $p_{t_0}(X, Y)$. Given its generality, this case can be associated with every corruption in our framework; therefore, the most general correspondence is the $\tau : X \times Y \rightsquigarrow X \otimes \lambda : X \times Y \rightsquigarrow Y$ joint Markov kernel.

There are two types of concept drifts popular in the literature:

- Concept shift [54, 55, 56]: in this case, p(Y | X) changes over time, and such changes can occur with or without changes on p(X), often referred to as concept shift; in our framework, this is a subcase of $\tau : X \times Y \rightsquigarrow X \otimes \lambda : X \times Y \rightsquigarrow Y$ corruption. More details in Tab. S1.
- Sampling shift [57, 55, 56]: here, *p*(X) changes over time while *p*(Y | X) remains invariant, also known as virtual drift; in our framework, this is a subcase of *τ* : *X* × *Y* → *X* ⊗ *λ* : *X* → *Y* corruption. More details in Tab. S1.

Corrupted	Invariant	Name in [16]	DAG in [17]	Ours	References
at least one among { π_X , F , E }, according to compatibility	π_Y	concept shift when $Y \rightarrow X$	D ↓ X ← Y	subcase of $\kappa : X \rightsquigarrow X$	as sole attribute noise [20, 21, 22, 23]
at least one among $\{\pi_Y, F, E\}$, according to compatibility	π_X	concept shift when $X \rightarrow Y$	$X \rightarrow Y$	subcase of $\lambda : Y \rightsquigarrow Y$	as sole class- conditional noise [9, 24, 11, 12, 26, 23]; in general, [100, 101]
at least π_Y , causing π_X or F to change	Ε	prior probability shift when Y → X	D X ← Y	at least a $\lambda : Y \rightsquigarrow Y$ subcase, at most $\kappa : X \times Y \rightsquigarrow X$ \otimes $\lambda : X \times Y \rightsquigarrow Y$	or label shift, or class imbalance; [35, 36, 37, 38, 102]
at least π_X , causing π_Y or <i>E</i> to change	F	covariate shift when $X \rightarrow Y$	$\begin{array}{c} D \\ \downarrow \\ X \rightarrow Y \end{array}$	at least a $\kappa : X \rightsquigarrow X$ subcase, at most $\kappa : X \times Y \rightsquigarrow X$ \otimes $\lambda : X \times Y \rightsquigarrow Y$	[13, 39, 40, 15]

 Table S1: Traditional taxonomies resume.

However, in the literature, concept drift is also defined with more invariance assumptions. For example, in Moreno-Torres et al. [16], they define concept drift as p(Y | X) changing while p(X) remains invariant or p(X | Y) changing while p(Y) remains invariant. Similar to instance- and label-dependent noise and covariate shift, they are examples of $\lambda : X \times Y \rightsquigarrow Y$ corruption and $\tau : X \times Y \rightsquigarrow X \otimes \lambda : Y \rightsquigarrow Y$ corruption that involve more corrupted spaces at different time points.

S2 Comparison with other taxonomies

We notice that most of the taxonomies available in the literature are based on the notion of invariance, inducing taxonomies very different from ours. We here connect our work to other categorization paradigms for distribution shifts, although without claiming it to be a comprehensive review.

We divide taxonomies in two main groups: the traditional ones, focusing on identifying which probability in the set { π_Y , π_X , E, F} is forced to be left invariant and which one is forced to be corrupted [16], and the causal ones, where a causal graph structure is associated to the corruption process [99] and hidden structures are possibly involved so that some latent feature is left unchanged by the corruption [17, 19]. Notice that in none of the cited works the corrupted distribution is assumed to have a specific form or to be "close enough" to the clean one. We do not review these other cases, because too far from our point of view and objective.

Traditional and causal taxonomies Focusing on the first case, a complete *traditional taxonomy* has four types of possible corruptions. Taking into account which marginal or conditional

probability is forced to be corrupted, we obtain a finite number of corruption subcases of these four macro-types. However, the different cases obtained may overlap, as it is schematically shown in Tab. S1. The cases that have a clear correspondence with ours are the ones leaving invariant a marginal distribution, generating simple noises. All the other cases cannot be directly mapped into our taxonomy, so we explicitly write the range of corruption types covered by them.

As for *causal taxonomies*, based on causal graphs, they are more difficult to describe in a unified way since different applications lead to different notations. We then avoid doing so, and limit ourselves to qualitatively compare them with our work.

A common trend is to identify the current space we live in with a variable D, the *domain* or *environment*, possibly taking values in \mathbb{N} . This variable is then included in the causal graph indicating on what it is acting, as done in the examples in Tab. S1. In the case described by Def. 7 we restrict it to take values in {0, 1}, the clean and corrupted environments. This representation is again missing some our corruptions, since it is only possible to encode *X* and *Y* changing across domains and not whether other environments influence the current one. The shifts in Kull and Flach [17, Fig. 3] involving hidden variables (concept shift subcases) resemble our idea of a "latent process" influencing the current environment, but still fail to cover all the possible cross-domain influence in Fig. 1. An additional limitation of the causal approach lies in the in the causal assumption itself; we are forced, in this setting, to only consider one between *E* and *F* to be a valid representation of the generative process, while in our framework we are not forced to make this choice. We although still use it in case it is available.

In both the described classes of taxonomies, it not natural nor simple to define a hierarchy of corruptions. In particular, in the traditional taxonomy the specification of what is corrupted leaves room for other components to be forced to be influenced, creating overlaps between cases. As for composing them, a DAG representation of corruption model can facilitate their chaining. Nevertheless, feasibility rules are rather complex and unclear to understand, given the overlapping nature of the corruptions and identifiability problems for causal representations [103].

S3 Bayesian inversion in category theory

In this section, we provide a more formal definition of the Bayesian inverse of a Markov kernel, based on some existing results from category theory applied to Bayesian learning [104]. In fact, Bayesian update is exactly kernel inversion. These results guarantee the valid and proper utilization of the inverse kernel in the current paper. Before delving into the details, we introduce relevant categorical concepts, establishing the necessary background to proceed. For a comprehensive overview of category theory, we recommend interested readers to refer to Mac Lane [105].

Categorical concepts To begin, let Mes be the category of measurable spaces with measurable maps as morphisms, and Pol be the category of *Polish spaces*, i.e., separable metric spaces for which a complete metric exists, with continuous maps as morphisms. The functor \mathcal{B} : Pol \rightarrow Mes associates any Polish space to the measurable space with the same underlying set equipped with the Borel σ -algebra, and interprets continuous maps as measurable ones. Measurable spaces in the range of \mathcal{B} are *standard Borel spaces*, which are important because the

Table S2: Comparison of categorical concepts in Dahlqvist et al. [104] and probabilistic concepts in this paper.

Categorical	Probabilistic		
Kleisli category of Giry monad G, $K\ell$	measurable spaces as objects and Markov kernels as arrows		
arrows in category $1 \downarrow \mathcal{K}\ell$	$\mathcal{M}(X, Y)$ where X and Y have marginals p and q , respectively		
arrows in category $1 \downarrow F$	subset of the above $\mathcal{M}(X, Y)$ with measure-preserving maps induced by identical kernels δ		
Kleisli composition ° _G	chain composition \circ in P1 with transitional kernels		
α_Y^X : Hom _{Krn} $(X, -) \to \Gamma(X, -)$	product composition \times in P2 with a kernel and a probability		

regular conditional probabilities are known to exist in them, but not in general [106]. Therefore, they will be used as the building block of the Krn category in the subsequent Bayesian inversion theorem.

The *Giry monad* is the monad on a category of suitable spaces which sends each suitable space X to the space of suitable probability measures on X. In this case, the set of suitable spaces is the one of the Mes category induced by the functor \mathcal{B} . To define it more formally, we now consider the triple (\mathcal{P}, μ, δ):

- the functor \mathcal{P} is such that we assign to every space X in Mes the set of all probability measures on X, $\mathcal{P}(X)$. This is equipped with the smallest σ -algebra that makes the evaluation function $ev_B : \mathcal{P}(X) \to [0,1] = P \mapsto P(B)$ measurable, for B a measurable subset in X;
- the multiplication of the monad, $\mu : \mathcal{P}^2 \Rightarrow \mathcal{P}$, is defined by $\mu_X(Q)(B) = \int_{q \in \mathcal{P}(X)} ev_B(q) dQ$;
- the unit of the monad, $\delta : Id \Rightarrow \mathcal{P}$, sends a point $x \in X$ to the Dirac measure at x, δ_x .

This equips the endofunctor \mathcal{P} : Mes \rightarrow Mes into a monad, that is, the Giry monad $G := (\mathcal{P}, \mu, \delta)$ on measurable spaces.

The Kleisli category of G, denoted by $\mathcal{K}\ell$, has the same objects as Mes, and the morphism $f: X \rightsquigarrow Y$ in $\mathcal{K}\ell$ is a kernel $f: X \to \mathcal{P}(Y)$ in Mes. The Kleisli composition of kernel $f: X \rightsquigarrow Y$ with $g: Y \rightsquigarrow Z$ is given by $g \circ_G f = \mu_Z \circ \mathcal{P}(g) \circ f$. The action of the functor \mathcal{P} on a kernel results, by definition, in the push-forward operator $\mathcal{P}(g)(\cdot) := (\cdot) \circ g^{-1}$, defined on a suitable space of probabilities. Hence, \circ_G is the same as the chain composition we defined in **P1**.

The Bayesian inversion theorem Dahlqvist et al. [104] investigates how and when the Bayesian inversion of the Markov kernel is defined, both directly on the category of measurable spaces, and indirectly by considering the associated linear operators (i.e., Markov transition, see Çinlar [59]). Below, we only introduce the first result of the Bayesian inversion theorem, given the focus of Markov kernels we have in the current paper, and then describe the pseudo-inversion operation in **P4** in a more formal way.

The category of Markov kernel considered here is the one of *typed kernel*. Their definition is tied to a fixed probability p on X and a fixed probability q on Y, so that $f \circ_{G} p = q$, instead of

being characterized for every probability on X and every reachable output. In general, one can define Markov kernels as operators on the space of probabilities; that is not our interest, as we tie the concept of corruption to a specific couple on the clean and corrupted distribution. This remark is also crucial for understanding our notion of exhaustiveness in § S4.

The key object for building the inversion operation is the Krn category, similar to our notion of space of Markov kernels $\mathcal{M}(X, Y)$, but with an equivalence relation acting on it. We describe its construction in the following steps.

- 1. Let $F : \text{Mes} \to \mathcal{K}\ell$ be the functor embedding Mes into $\mathcal{K}\ell$ which acts identically on spaces and maps measurable arrows $f : X \to Y$ to Kleisli arrows $F(f) = \delta_Y \circ f$. This means that F(f) only allows one possible jump at each x in X, with δ_Y an identical jump (i.e., a deterministic kernel).
- 2. It further induces the category $1 \downarrow F$ of probabilities $p : 1 \rightsquigarrow \mathcal{P}(X)$, denoted by (X, p), and morphisms $f : (X, p) \rightsquigarrow_{\delta} (Y, q)$ as degenerate arrows $F(f) : X \rightsquigarrow Y$ s.t. $q = F(f) \circ_{G} p = P(f)(p) = p \circ f^{-1}$. In more familiar terms, this is saying that q is the push-forward of p along f. $1 \downarrow F$ includes all measure-preserving maps induced by degenerate arrows.
- 3. When the arrows are not degenerate, we obtain the supercategory $1 \downarrow \mathcal{K}\ell$ with the same objects. Specifically, in this category, an arrow from (X, p) to (Y, q) is any Kleisli arrow $f : X \rightsquigarrow Y$ s.t. $q = f \circ_{G} p$, and the arrows are what we denoted as $\mathcal{M}(X, Y)$, where X has marginal probability p and Y has marginal probability q.
- 4. Markov kernels cannot be inverted as they are, because of their *non-singularity*. Lemma 3 in Dahlqvist et al. [104] characterizes it by proving that for a kernel $f : (X, p) \rightsquigarrow (Y, q)$ there are *p*-negligibly many points jumping to *q*-negligible sets.

Once the non-singularity is understood, we can define an equivalence relation on $1 \downarrow \mathcal{K}\ell$ that allows a well-posed definition of the inverse kernel.

Definition. For all objects (X, p), (Y, q), $R_{(X,p),(Y,q)}$ is the smallest equivalence relation on $Hom_{1\downarrow K\ell}(X, Y)$ such that

$$(f, f') \in R_{(X,p),(Y,q)} \iff f = f' \ p - a.s.$$

They prove *R* to be a congruence relation on $1 \downarrow \mathcal{K}\ell$ in their Lemma 4. This congruence relation allows us to define the quotient category, with proper morphisms.

Definition. The category Krn is the quotient category $(1 \downarrow \mathcal{K}\ell)/R$.

Having defined the category, we have to build the functions that are going to constitute the Bayesian inversion operator, i.e., a bijection between $\text{Hom}_{Krn}((X, p), (Y, q))$ and $\text{Hom}_{Krn}((Y, q), (X, p))$. There are two mappings between the Krn category and the space of couplings associated to (X, p), (Y, q). The first is equivalent to the product composition we defined in **P2** applied to a kernel (i.e. conditional probability) and a probability, and is formally written as

$$\alpha_Y^X : \operatorname{Hom}_{\operatorname{Krn}}((X,p),(Y,q)) \to \Gamma((X,p),(Y,q)) \quad \text{s.t.} \quad \alpha_Y^X(f)(B_X \times B_Y) \coloneqq \int_{x \in B_X} f(x)(B_Y) dp \ ,$$

with $\Gamma((X, p), (Y, q)) \subset \mathcal{P}(X \times Y)$ the typed couplings associated to the marginals (X, p), (Y, q). The second is defined as its inverse operation, and it is decomposing a joint probability along a fixed marginal distribution, i.e.,

$$\begin{split} D_Y^X &: \Gamma((X,p),(Y,q)) \to \operatorname{Hom}_{\operatorname{Krn}}((X,p),(Y,q)) \\ \text{s.t.} \quad D_Y^X(\gamma) &\coloneqq \operatorname{P}(\pi_Y) \circ \pi_X^{\dagger}, \quad \gamma(B_X \times B_Y) \coloneqq \int_{x \in B_X} D_Y^X(\gamma)(x)(B_Y) dp \;, \end{split}$$

with $(\cdot)^{\dagger}$: adjoint operator. As one is the inverse of the other, they are both obviously bijective and the one-to-one correspondence between typed kernels and couplings is proved. Hence, we formally define the Bayesian inverse as in the following:

Definition. The Bayesian inverse of a typed kernel κ from (X, p) to (Y, q), is defined as

$$(\cdot)^{\dagger}: \kappa \mapsto \kappa^{\dagger} := \left(D_X^Y \circ P(\pi_Y \times \pi_X) \circ \alpha_Y^X \right)(\kappa),$$

with $P(\pi_Y \times \pi_X) : \Gamma((X, p), (Y, q)) \to \Gamma((Y, q), (X, p))$ being the permutation map.

As the Bayesian inverse has been defined as a bijection between $\text{Hom}_{\text{Krn}}((X, p), (Y, q))$ and $\text{Hom}_{\text{Krn}}((Y, q), (X, p))$, it is always guaranteed to exist in this setting.

Proposition. *The Bayesian inverse of a typed kernel* κ *from* (*X*, *p*) *to* (*Y*, *q*) *is equivalently one of the following objects:*

- 1. $\kappa^{\dagger} : (Y, q) \to (X, p) \in \operatorname{Krn} when \kappa \text{ is seen as element of Krn, such that } (\kappa^{\dagger} \circ_{G} \kappa) \circ_{G} q = \delta_{Y} \circ_{G} q$ and $(\kappa \circ \kappa^{\dagger}) \circ_{G} p = \delta_{X} \circ_{G} p$;
- 2. $\kappa^{\dagger} : Y \rightsquigarrow X \in \mathcal{M}(Y, X)$ when κ is seen as element of $\mathcal{M}(X, Y)$, such that $(\kappa^{\dagger} \circ_{G} \kappa) \circ_{G} q \equiv_{R} \delta_{Y} \circ_{G} q$ and $(\kappa \circ_{G} \kappa^{\dagger}) \circ_{G} p \equiv_{R} \delta_{X} \circ_{G} p$.

Here, $\delta_{(\cdot)}$ indicates the identical kernel on the set (\cdot) , induced by the Dirac delta distribution.

Remark. We can understand the Bayesian inverse of a corruption kernel $\kappa \in \mathcal{M}(Z, Z)$ from (Z, \mathcal{Z}, P) to $(Z, \mathcal{Z}, \tilde{P})$ that distorts $\tilde{P}(A) = \int_A \int_Z \kappa(z, d\tilde{z}) P(dz) \quad \forall A \in \mathcal{Z}$ as a Markov kernel $\kappa^{\dagger} \in \mathcal{M}(Z, Z)$ satisfying

$$\int_{B} \kappa(z, A) P(dz) = \int_{A} \kappa^{\dagger}(\tilde{z}, B) \tilde{P}(d\tilde{z}) \quad \forall A \in \mathcal{Z}, B \in \mathcal{Z}.$$

This formulation extends the discrete Bayes' rule $P(\tilde{z} | z)P(z) = P(z | \tilde{z})P(\tilde{z}) \forall z, \tilde{z} \in Z$. Hence, in the discrete case, the Bayesian inverse always exists and can be expressed as

$$\kappa^{\dagger}(z \mid \tilde{z}) \coloneqq \frac{P(z)\kappa(\tilde{z} \mid z)}{\tilde{P}(\tilde{z})} \text{ for } z, \tilde{z} \in Z \text{ with } \tilde{P}(\tilde{z}) \neq 0$$

This formula ensures the uniqueness of κ^{\dagger} within the support of \tilde{P} , as all components are unique. However, outside the support when \tilde{P} is zero, the uniqueness may not hold, requiring a non-fixed value for $\tilde{z} \in Z$ where $\tilde{P}(\tilde{z}) = 0$.

In the continuous case, the Bayesian inverse may not exist. To ensure $\kappa^{\dagger} \in \mathcal{M}(Z, Z)$ is welldefined, it must satisfy the conditions of being a Markov kernel, as defined in Def. 1, where the mapping $\tilde{z} \to \kappa^{\dagger}(\tilde{z}, B)$ is \mathcal{Z} -measurable for every set $B \in \mathcal{Z}$, and the mapping $B \to \kappa^{\dagger}(\tilde{z}, B)$ is a probability measure on (Z, \mathcal{Z}) for every $\tilde{z} \in Z$, for the standard Borel space (Z, \mathcal{Z}) . Under this condition, the Bayesian inverse always exists, and it is uniquely defined within the support of \tilde{P} , where uniqueness is represented by an equivalence class of kernels that are \tilde{P} -a.s. equal.



Figure S1: Possible non-degenerate relations among three probability spaces.

S4 Details on the exhaustiveness of the taxonomy

The definition of corruption that we give in Def. 7 is tight to the output and input distributions P and \tilde{P} . This, together with the fact that we use Markov kernels, makes the space of typed kernels correspond to our space of corruptions.

Pairwise Markovian corruption As we noticed in § S1, Markov kernels are not the only possibility for modeling corruption, but we proved that given a clean and corrupted space we can always find a Markov kernel that connects the two distributions. In particular, we define the operations α_Y^X and D_Y^X for typed kernels, where one is the inverse of the other by construction. They are the operations representing the bijection between the space of Markov kernels typed for *p*, *q* and the space of couplings with marginals *p*, *q*. Hence, they are proving that *for each couple of probability spaces, there exists a Markov kernel sending one into the other corresponding to a possible associated coupling*.

When the definition of corruption is directly made through Markov kernels, we call it a *Markovian corruption*. These are, in categorical terms, all the arrows in the Krn category. The reasoning above means that every pairwise Markovian corruption in the supervised learning setting is described by our taxonomy. Other possibilities are, having more than two spaces involved in the corruption process and having a non-stochastic mapping describing the corruption process as it has been defined. We discuss them in the following, providing examples.

Markovian corruption for more than two spaces When in the presence of three probability spaces, we have only two possible corruption configurations. We represent them in Fig. S1, where arrows represent non-trivial Markov kernels. We remark that we do not consider the triangular structures as in Fig. S1a and c with the spaces Z_2 , Z_3 coupled in some way, otherwise they would just be considered as a single (product) probability space, i.e. a pairwise corruption.

The simplest case is Fig. S1b, in which the spaces influence each other in a chain fashion. This is a clear subcase of our framework as we can integrate Z_2 by considering $\kappa_{Z_1Z_3} := \kappa_3 \circ \kappa_2 \circ \kappa_1$. We then obtain a pairwise corruption $\kappa_{Z_1Z_3}$, but we would pay the price of losing information about the role of the "latent" corruption process. To have a complete idea of how the chained corruption works, we can additionally study it as an iterative process and analyze its single components. This entire reasoning is true for a number of spaces Z_i , $i \in [n]$ with n > 3, and well models several settings for dynamical learning, e.g. online corrupted learning or concept drift over time [51, 107, 53].

The second option is, they act as per the diagrams in Fig. S1a and Fig. S1c, i.e. a triangular structure. In particular, case (a) reflects assumptions made in settings combining data from different domains [68, 26, 108], where we get to observe different data distributions obtained from the same clean one. They can be seen, in our framework, as a pairwise dependence between $Z_1 \times Z_2$ and Z_3 , or Z_1 and $Z_2 \times Z_3$. However, this formulation assumes some coupling on Z_2 , Z_3 , more complex than our originally assumed corruption. For now, we do not investigate the consequences of this gap as changes of the corruption effect, leaving it for future investigation. A similar idea can be stated for n > 2 spaces in the Cartesian product space, and for combinations of fork structures with fork structures via superposition.

S5 Proofs for Data Processing Equality results

We restate for clarity all the assumptions underlying the proofs.

- **A1** The loss function $\ell : \mathcal{P}(Y) \times Y \to \mathbb{R}_{\geq 0}$ associated with the learning problem (ℓ, \mathcal{H}, P) is proper and bounded.
- A2 The BR minimizer $f^* \in \arg \min_f \mathbb{E}_{\tilde{P}}[f(X, Y)]$ belongs to the minimization space $\ell \circ \mathcal{H}$, i.e. it minimizes also the associated Constrained BR.

Recall that π_Y is a prior distribution on *Y*, and the notation κ_X stands for the kernel κ evaluated on the parameter X, e.g., E_Y , F_X , and $\kappa_x := \kappa_{X=x}$. The kernel δ_Z denotes a kernel induced by the Dirac delta measure from (Z, Z) to (Z, Z).

In the proofs we will use a continuous notation for measures on *Y*, for the sake of simplicity and homogeneity. However, notice that all the λ kernels are actually (parameterized) stochastic matrices $\Lambda = [\Lambda_{\tilde{y}y}]$, where $\Lambda_{\tilde{y}y} = p(\tilde{Y} = \tilde{y} | Y = y)$ for simple corruptions and $\Lambda_{\tilde{y}y}(x) = p(\tilde{Y} = \tilde{y} | Y = y, X = x)$ for dependent corruptions. Note that both *y* and \tilde{y} range in *Y*, and thus they are squared matrices. In Theorem 15 and Lemma S2, the kernel λ acting on the function $\ell \circ \mathcal{H}$ is actually the transpose of the stochastic matrix Λ :

$$\sum_{\tilde{y}\in Y} \lambda_x(y, d\tilde{y}) \,\ell(h(x), \tilde{y}) = \sum_{\tilde{y}\in Y} \Lambda_{\tilde{y}y}^\top(x) \,\ell_{\tilde{y}}(h(x)) = \widetilde{(\ell_y \circ h)}(x) \,.$$

Below, Theorems 14 and 15 are proved based on the Lemmas concerning BR changes under dependent *X* and *Y* corruptions, respectively.

Lemma S1 (BR under X corruption). Let A1 and A2 hold. Consider the learning problem (ℓ, \mathcal{H}, P) and $E : Y \rightsquigarrow X$ its associated experiment such that $P = \pi_Y \times E$ for a suitable π_Y . Let $\tau \otimes \delta_Y$ be a corruption acting on this problem, with $\tau \in \mathcal{M}(X \times Y, X)$. Then, we obtain

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \delta_Y)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ \left((E \circ_X \tau) \otimes \delta_Y\right)\right) \equiv_{BR} \left(\tau(\ell \circ \mathcal{H}), \pi_Y \times E\right).$$

Moreover, if $\tau \in \mathcal{M}(X, X)$ *, we have*

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \delta_Y)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ \left((E \circ \tau) \otimes \delta_Y\right)\right) \equiv_{BR} \left(\tau(\ell \circ \mathcal{H}), \pi_Y \times E\right).$$

Proof. Let $A \in X \times \mathcal{Y}$. By definition of all the objects involved, the action of $\tau \otimes \delta_Y$ on *P* is

$$\begin{split} \tilde{P}(A) &= \int_{(\tilde{x},\tilde{y})\in A} \int_{(x,y)\in X\times Y} \tau_y(x,d\tilde{x}) \,\delta_y(d\tilde{y}) \,P(dxdy) \\ &= \int_{(\tilde{x},\tilde{y})\in A} \left[\sum_{y\in Y} \left(\int_{x\in X} \tau_y(x,d\tilde{x}) \,E_y(dx) \right) \delta_y(d\tilde{y}) \,\pi_y \right] \\ &= \int_{(\tilde{x},\tilde{y})\in A} \left[\sum_{y\in Y} (E \circ_X \tau)_y(d\tilde{x}) \,\delta_y(d\tilde{y}) \,\pi_y \right] \\ &= \left[\pi_y \circ \left((E \circ_X \tau) \otimes \delta_Y \right) \right] (A) \,. \end{split}$$

We can hence rewrite the risk w.r.t. \tilde{P} as

$$\mathbb{E}_{(\tilde{\mathbf{X}},\tilde{\mathbf{Y}})\sim\pi_{y}\circ[(E\circ_{X}\tau)\otimes\delta_{Y}]}\left[\ell(h_{\tilde{\mathbf{X}}},\tilde{\mathbf{Y}}))\right] = \sum_{y\in Y,\tilde{y}\in Y}\left[\int_{\tilde{x}\in X}\ell(h_{\tilde{x}},\tilde{y})\left(\int_{x\in X}\tau_{y}(x,d\tilde{x})E_{y}(dx)\right)\right]\delta_{y}(d\tilde{y})\pi_{y}$$
$$= \sum_{y\in Y}\left[\int_{x\in X}\left(\int_{\tilde{x}\in X}\left(\sum_{\tilde{y}\in Y}\delta_{y}(d\tilde{y})\ell(h_{\tilde{x}},\tilde{y})\right)\tau_{y}(x,d\tilde{x})\right)E_{y}(dx)\right]\pi_{y}$$
$$= \sum_{y\in Y}\left[\int_{x\in X}\left(\int_{\tilde{x}\in X}(\delta\ell_{y}\circ h)(\tilde{x})\tau_{y}(x,d\tilde{x})\right)E_{y}(dx)\right]\pi_{y}$$
$$= \sum_{y\in Y}\left[\int_{x\in X}\left[\tau(\delta\ell_{y}\circ h)](x,y)E_{y}(dx)\right]\pi_{y}$$
(S1)
$$= \mathbb{E}_{(\mathbf{X},\mathbf{Y})\sim(\pi_{Y}\times E)}\left[\left(\tau(\delta\ell_{Y}\circ h)\right)(\mathbf{X},\mathbf{Y})\right].$$

Let $\tilde{E}_y(d\tilde{x}) \coloneqq (E \circ_X \tau)_y(d\tilde{x})$. We have that the associated br is

$$\min_{h \in \mathcal{H}} \mathbb{E}_{(\tilde{\mathbf{X}}, \tilde{\mathbf{Y}}) \sim \pi_{Y} \circ [(E \circ_{X} \tau) \otimes \delta_{Y}]} \left[\ell(h_{\tilde{\mathbf{X}}}, \tilde{\mathbf{Y}})) \right] = \min_{h \in \mathcal{H}} \mathbb{E}_{\tilde{\mathbf{Y}} \sim \pi_{Y}} \mathbb{E}_{\tilde{\mathbf{X}} \sim \tilde{E}_{\tilde{\mathbf{Y}}}} \left[\ell(h_{\tilde{\mathbf{X}}}, \tilde{\mathbf{Y}})) \right]$$
$$= BR_{\ell \circ \mathcal{H}} [\pi_{Y} \circ (\tilde{E} \otimes \delta_{Y})],$$

$$\min_{h \in \mathcal{H}} \mathbb{E}_{(\mathsf{X},\mathsf{Y})\sim(\pi_{Y}\times E)} \left[\left(\tau(\delta\ell_{\mathsf{Y}} \circ h) \right)(\mathsf{X},\mathsf{Y}) \right] = \min_{f \in \tau(\ell \circ \mathcal{H})} \mathbb{E}_{(\mathsf{X},\mathsf{Y})\sim(\pi_{Y}\times E)} \left[f(\mathsf{X},\mathsf{Y}) \right] \\ = \mathsf{BR}_{\tau(\ell \circ \mathcal{H})} [\pi_{Y} \times E] \,, \tag{S2}$$

which are equal given the previous computations. We have defined and used in Eq. (S2) that $f(x, y) := [\tau(\delta \ell_y \circ h)](x, y), h \in \mathcal{H}$. Such functions are the ones populating the minimization set $\tau(\ell \circ \mathcal{H})$, denoting that τ acts on the composition of the loss and model class while δ only acts on ℓ and leaves it unchanged. If τ is simple, then the equations from Eq. (S1) lead to a slightly different model class:

$$BR_{\ell \circ \mathcal{H}} \left[\pi_Y \circ \left((E \circ \tau) \otimes \delta_Y \right) \right] = \min_{h \in \mathcal{H}} \sum_{y \in Y} \left[\int_{x \in X} [\tau(\delta \ell_y \circ h)](x) E_y(dx) \right] \pi_y$$
$$= \min_{f \in \tau(\ell \circ \mathcal{H})} \sum_{y \in Y} \left[\int_{x \in X} f(x, y) E_y(dx) \right] \pi_y = BR_{\tau(\ell \circ \mathcal{H})}(\pi_Y \times E) \,.$$

Theorem (BR under 2-dependent τ , simple λ , Theorem 14). Let A1 and A2 hold. Consider the learning problem (ℓ, \mathcal{H}, P) and $E : Y \rightsquigarrow X$ its associated experiment such that $P = \pi_Y \times E$ for a suitable π_Y . Let $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : Y \rightsquigarrow Y)$ be a corruption acting on this problem, then, we obtain

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ \left((E \circ_X \tau) \otimes \lambda\right)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_Y \times E\right).$$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) := \{ (x, y) \mapsto [\tau(\lambda \ell_y \circ h)](x, y), h \in \mathcal{H} \}.$$

Proof. With this corruption formulation, we can replicate the proof of Lemma S1 up to Eq. (S1) by simply plugging in λ instead of δ_Y . Therefore, we obtain the thesis.

We remark that in this case $\tilde{P} \neq \pi_Y \times \tilde{E}$ with $\tilde{E}_y(d\tilde{x}) := (E \circ_X \tau)_y(d\tilde{x})$, i.e., the corrupted experiment is not given by the sole action of τ , but also by the influence of λ . That is clarified further by corruption formula $\tilde{P} = \pi_y \circ [(E \circ_X \tau) \otimes \lambda]$. We conclude that, in this more general case, it does not make sense to distinguish the effect of corruption on E and π .

Lemma S2 (BR under Y corruption). Let A1 and A2 hold. Consider the learning problem (ℓ, \mathcal{H}, P) and $F : X \rightsquigarrow Y$ its associated posterior such that $P = \pi_X \times F$ for a suitable π_X . Let $\delta_X \otimes \lambda$ be a corruption acting on this problem, with $\lambda \in \mathcal{M}(X \times Y, Y)$. Then, we obtain

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\delta_X \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ (\delta_X \otimes (F \circ_Y \lambda))\right) \equiv_{BR} \left(\lambda \ell \circ \mathcal{H}, \pi_X \times F\right).$$

Moreover, if $\lambda \in \mathcal{M}(Y, Y)$ *, we have*

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\delta_X \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ (\delta_X \otimes (F \circ \lambda))\right) \equiv_{BR} \left(\lambda \ell \circ \mathcal{H}, \pi_X \times F\right).$$

Proof. Let $A \in \mathcal{X} \times \mathcal{Y}$. By definition of all the objects involved, the action of $\tau \otimes \delta_Y$ on *P* is

$$\begin{split} \tilde{P}(A) &= \int_{(\tilde{x},\tilde{y})\in A} \int_{(x,y)\in X\times Y} \delta_x(d\tilde{x})\,\lambda_x(y,d\tilde{y})\,P(dxdy) \\ &= \int_{(\tilde{x},\tilde{y})\in A} \left[\int_{x\in X} \left(\sum_{y\in Y} \lambda_x(y,d\tilde{y})\,F_x(dy) \right) \delta_x(d\tilde{x})\,\pi(dx) \right] \\ &= \int_{(\tilde{x},\tilde{y})\in A} \left[\int_{x\in X} (F\circ_Y\lambda)_x(d\tilde{y})\,\delta_x(d\tilde{x})\,\pi_x(dx) \right] \\ &= \left[\pi_x \circ \left((F\circ_Y\lambda) \otimes \delta_X \right) \right](A) \,. \end{split}$$

We can hence rewrite the risk w.r.t. \tilde{P} as

$$\begin{split} \mathbb{E}_{(\tilde{X},\tilde{Y})\sim\pi_{X}\circ[(F\circ_{Y}\lambda)\otimes\delta_{X}]}\left[\ell(h_{\tilde{X}},\tilde{Y}))\right] &= \int_{x\in X,\tilde{x}\in X} \left[\sum_{\tilde{y}\in Y}\ell(h_{\tilde{x}},\tilde{y})\left(\sum_{y\in Y}\lambda(x,y,d\tilde{y})F(x,dy)\right)\right]\delta(x,d\tilde{x})\,\pi(dx) \\ &= \int_{x\in X,\tilde{x}\in X} \left[\sum_{y\in Y}\left(\sum_{\tilde{y}\in Y}\ell(h_{\tilde{x}},\tilde{y})\,\lambda(x,y,d\tilde{y})\right)F(x,dy)\right]\delta(x,d\tilde{x})\,\pi(dx) \\ &= \int_{x\in X} \left[\sum_{y\in Y}\left(\int_{\tilde{x}\in X}(\lambda\ell)(h_{\tilde{x}},x,y)\delta(x,d\tilde{x})\right)F(x,dy)\right]\pi(dx) \\ &= \int_{x\in X} \left[\sum_{y\in Y}\left((\lambda\ell)(h_{x},x,y)\right)F(x,dy)\right]\pi(dx) \quad (S3) \\ &= \mathbb{E}_{(X,Y)\sim(\pi_{Y}\times E)}\left[(\lambda\ell)(h_{X},X,Y)\right] = \mathbb{E}_{(X,Y)\sim(\pi_{Y}\times E)}\left[(\lambda\ell_{(X,Y)}\circ h)(X)\right]. \end{split}$$

Similarly to the proof provided for Lemma S1, we can switch to BR and obtain

$$\mathbf{BR}_{\ell \circ \mathcal{H}}[\pi_X \circ ((F \circ_Y \lambda) \otimes \delta_X)] = \mathbf{BR}_{\lambda \ell \circ \mathcal{H}}(\pi_X \times F),$$

with functions $\lambda \ell(h_x, x, y) = (\lambda \ell_{(x,y)} \circ h)(x) \in \lambda \ell \circ \mathcal{H}$. If λ is simple, then Eq. (S3) leads to a simpler model class:

ъ.

r

$$BR_{\ell\circ\mathcal{H}}[\pi_X \circ \left((F \circ \lambda) \otimes \delta_X\right)] = \min_{h\in\mathcal{H}} \int_{x\in X} \left[\sum_{y\in Y} (\lambda\ell)(h_x, y)F(x, dy) \right] \pi(dx)$$
$$= \min_{f\in\lambda(\ell\circ\mathcal{H})} \int_{x\in X} \left[\sum_{y\in Y} f(x, y)F(x, dy) \right] \pi(dx) = BR_{\lambda(\ell\circ\mathcal{H})}(\pi_X \times F).$$

Theorem (BR under simple τ , 2-dependent λ , Theorem 15). Let A1 and A2 hold. Consider the learning problem (ℓ , \mathcal{H} , P) and F : X \rightsquigarrow Y its associated posterior such that $P = \pi_X \times F$ for a suitable π_X . Let ($\tau : X \rightsquigarrow X$) \otimes ($\lambda : X \times Y \rightsquigarrow Y$) be a corruption acting on this problem, then, we obtain

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ (\tau \otimes (F \circ_Y \lambda))\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_X \times F\right).$$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_{(x, y)} \circ h)](x), h \in \mathcal{H}\}.$$

Proof. With this corruption formulation, we can replicate the proof of Lemma S2 up to Eq. (S3) by simply plugging in τ instead of δ_x . Therefore, we obtain the thesis.

Theorem (BR under a 1-dependent and a 2-dependent, Theorem 16). Let A1 and A2 hold. Consider the clean learning problem (ℓ, \mathcal{H}, P) , $E : Y \rightsquigarrow X$ its associated experiment such that $P = \pi_Y \times E$ for a suitable π_Y , and $F : X \rightsquigarrow Y$ its associated posterior such that $P = \pi_X \times F$ for a suitable π_X . 1. Let $(\tau : Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$ be a corruption acting on the problem, then, we obtain $\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ (\tau \otimes (E \circ_X \lambda))\right) \equiv_{BR} (\tau(\lambda \ell \circ \mathcal{H}), \pi_Y \times E).$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H})\{(x, y) \mapsto \tau[\lambda \ell_{(x, y)} \circ h](y), h \in \mathcal{H}\}.$$

2. Let $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \rightsquigarrow Y)$ be a corruption acting on the problem, then, we obtain

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ \left((F \circ_Y \tau) \otimes \lambda\right)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_X \times F\right).$$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H})\{(x, y) \mapsto \tau[\lambda \ell_x \circ h](x, y), h \in \mathcal{H}\}.$$

Proof. Consider point 1 and let $A \in X \times \mathcal{Y}$. By definition of all the objects involved, the action of $\tau \otimes \lambda$ on *P* is

$$\begin{split} \tilde{P}(A) &= \int_{(\tilde{x}, \tilde{y}) \in A} \left[\sum_{y \in Y} \left(\int_{x \in X} \lambda_y(x, d\tilde{y}) E_y(dx) \right) \tau(y, d\tilde{x}) \pi_y \right] \\ &= \int_{(\tilde{x}, \tilde{y}) \in A} \left[\sum_{y \in Y} (E \circ_X \lambda)(y, d\tilde{y}) \tau(y, d\tilde{x}) \pi_y \right] \\ &= \int_{(\tilde{x}, \tilde{y}) \in A} \left[\sum_{y \in Y} \left(\tau \otimes (E \circ_X \lambda) \right)(y, d\tilde{x}, d\tilde{y}) \pi_y \right] = \left[\pi_Y \times \left(\tau \otimes (E \circ_X \lambda) \right) \right] (A) \,. \end{split}$$

We can then write the associated risk as

$$\begin{split} \mathbb{E}_{(\tilde{\mathsf{X}},\tilde{\mathsf{Y}})\sim\pi_{\mathsf{Y}}\times\left(\tau\otimes(E\circ_{\mathsf{X}}\lambda)\right)}[\ell(h_{\tilde{\mathsf{X}}},\tilde{\mathsf{Y}})] &= \sum_{y\in\mathsf{Y},\tilde{y}\in\mathsf{Y}} \left[\int_{\tilde{x}\in\mathsf{X}} \ell(h_{\tilde{x}},\tilde{y}) \left(\int_{x\in\mathsf{X}} \lambda(x,y,d\tilde{y}) E_{y}(dx) \right) \right] \tau(y,d\tilde{x}) \pi_{y} \\ &= \sum_{y\in\mathsf{Y}} \left[\int_{x\in\mathsf{X}} \left(\int_{\tilde{x}\in\mathsf{X}} \left(\sum_{\tilde{y}\in\mathsf{Y}} \lambda(x,y,d\tilde{y}) \ell(h_{\tilde{x}},\tilde{y}) \right) \tau(y,d\tilde{x}) \right) E_{y}(dx) \right] \pi_{y} \\ &= \sum_{y\in\mathsf{Y}} \left[\int_{x\in\mathsf{X}} \left(\int_{\tilde{x}\in\mathsf{X}} (\lambda\ell_{(x,y)}\circ h)(\tilde{x}) \tau(y,d\tilde{x}) \right) E_{y}(dx) \right] \pi_{y} \\ &= \sum_{y\in\mathsf{Y}} \left[\int_{x\in\mathsf{X}} \left[\tau(\lambda\ell_{(x,y)}\circ h)](y) E_{y}(dx) \right] \pi_{y} \\ &= \mathbb{E}_{(\mathsf{X},\mathsf{Y})\sim(\pi_{\mathsf{Y}}\times\mathsf{E})} \left[\left(\tau(\lambda\ell_{(\mathsf{X},\mathsf{Y})}\circ h))(\mathsf{Y}) \right] \,, \end{split}$$

which proves the thesis when minimizing over $h \in \mathcal{H}$. For proving point 2, we first rewrite the action of $\tau \otimes \lambda$ on *P* as

$$\begin{split} \tilde{P}(A) &= \int_{(\tilde{x}, \tilde{y}) \in A} \left[\int_{x \in X} \lambda(x, d\tilde{y}) \left(\sum_{y \in Y} \tau(x, y, d\tilde{x}) F(x, dy) \right) \pi(dx) \right] \\ &= \int_{(\tilde{x}, \tilde{y}) \in A} \left[\int_{x \in X} \lambda(x, d\tilde{y}) \left(F \circ_Y \tau \right) (x, d\tilde{x}) \pi(dx) \right] = \left[\pi_X \times \left(\lambda \otimes \left(F \circ_Y \tau \right) \right) \right] (A) \,, \end{split}$$

and repeat a similar argument but for the *F* kernel. We find a minimization space of functions $f(x, y) \coloneqq \tau[\lambda \ell_x \circ h](x, y)$. Thus, we obtain the thesis.

Corollary (BR under 1-dependent τ and λ , Corollary 17). Let A1 and A2 hold. Consider the clean learning problem (ℓ, \mathcal{H}, P) , $E : Y \rightsquigarrow X$ its associated experiment such that $P = \pi_Y \times E$ for a suitable π_Y , and $F : X \rightsquigarrow Y$ its associated posterior such that $P = \pi_X \times F$ for a suitable π_X . Let $(\tau : Y \rightsquigarrow X) \otimes (\lambda : X \rightsquigarrow Y)$ be a corruption acting on the problem, then, we obtain

$$\left(\ell \circ \mathcal{H}, (\pi_Y \times E) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_Y \circ (\tau \otimes (E \circ \lambda))\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_Y \times E\right).$$

or, equivalently,

$$\left(\ell \circ \mathcal{H}, (\pi_X \times F) \circ (\tau \otimes \lambda)\right) = \left(\ell \circ \mathcal{H}, \pi_X \circ ((F \circ \tau) \otimes \lambda)\right) \equiv_{BR} \left(\tau(\lambda \ell \circ \mathcal{H}), \pi_X \times F\right).$$

The functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_x \circ h)](y), h \in \mathcal{H}\}.$$

Proof. We can replicate the proof of Theorem 16 by simply substituting $\lambda(x, d\tilde{y})$ in place of $\lambda(x, y, d\tilde{y})$ in the first point, and $\tau(y, d\tilde{x})$ for $\tau(x, y, d\tilde{x})$ in the second point. We then in both cases obtain functions $f(x, y) \coloneqq \tau[(\lambda \ell)_x \circ h](y)$, i.e. comparing a point x with a kernel on $\mathcal{P}(X)$ parameterized by y. Therefore, we obtain the thesis.

Theorem (BR under 2-dependent κ and λ , Theorem 18). Let A1 and A2 hold. Consider the clean learning problem (ℓ, \mathcal{H}, P) , and let $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$ be a corruption acting on the problem. Then:

- 1. the action of such corruption on the joint probability P is equivalent to the one of the non-decomposed joint corruption;
- 2. the action on the minimization set $\ell \circ \mathcal{H}$ induces the following BR-equivalence

$$(\ell, \mathcal{H}, P \circ (\tau \otimes \lambda)) \equiv_{BR} (\tau(\lambda \ell \circ \mathcal{H}), P);$$

3. the functions contained in the new minimization set are defined as

$$\tau(\lambda \ell \circ \mathcal{H}) \coloneqq \{(x, y) \mapsto [\tau(\lambda \ell_{(x, y)} \circ h)](x, y), h \in \mathcal{H}\}.$$

Proof. Let $A \in X \times \mathcal{Y}$. By definition of all the objects involved, the action of $\tau \otimes \lambda$ on P is

$$\begin{split} \tilde{P}(A) &= \int_{(\tilde{x},\tilde{y})\in A} \left[\sum_{y\in Y} \left(\int_{x\in X} \tau_y(x,d\tilde{x}) \,\lambda_x(y,d\tilde{y}) \, E_y(dx) \right) \pi_y \right] \\ &= \int_{(\tilde{x},\tilde{y})\in A} \left[\int_{x\in X} \left(\sum_{y\in Y} \tau_y(x,d\tilde{x}) \,\lambda_x(y,d\tilde{y}) \, F_x(dy) \right) \pi(dx) \right] \end{split}$$

In both the formulations above, obtained by factorizing the joint probability *P* in two different ways, we cannot isolate the action of one between λ and τ on *F* or *E*. That is, because of the

dependence of λ and τ on the couple (x, y), and because the action of a kernel on a probability via a combination of P1, 2 and 4 requires sequential integration. This concludes point 1.

As for point 2, we now want to consider the action on functions. This uses integration w.r.t. the corrupted variables (\tilde{x}, \tilde{y}) , and therefore allows sequential integration. We have that the associate risk is equal to

$$\begin{split} \mathbb{E}_{(\tilde{\mathbf{X}},\tilde{\mathbf{Y}})\sim\tilde{P}}[\ell(h_{\tilde{\mathbf{X}}},\tilde{\mathbf{Y}})] &= \int_{\tilde{x}\in X,\tilde{y}\in Y} \ell(h_{\tilde{x}},\tilde{y}) \left[\int_{x\in X,y\in Y} \tau(x,y,d\tilde{x})\,\lambda(x,y,d\tilde{y})\,P(dxdy) \right] \quad (S4) \\ &= \int_{\tilde{x}\in X,\tilde{y}\in Y} \ell(h_{\tilde{x}},\tilde{y}) \left[\sum_{y\in Y} \left(\int_{x\in X} \tau(x,y,d\tilde{x})\,\lambda(x,y,d\tilde{y})\,E_{y}(dx) \right) \pi_{y} \right] \\ &= \sum_{y\in Y} \left[\int_{x\in X} \left(\int_{\tilde{x}\in X,\tilde{y}\in Y} \ell(h_{\tilde{x}},\tilde{y})\tau(x,y,d\tilde{x})\,\lambda(x,y,d\tilde{y})\,E_{y}(dx) \right) \right] \pi_{y} \\ &= \sum_{y\in Y} \left[\int_{x\in X} \left(\int_{\tilde{x}\in X} \left(\sum_{\tilde{y}\in Y} \ell(h_{\tilde{x}},\tilde{y})\,\lambda(x,y,d\tilde{y}) \right) \tau(x,y,d\tilde{x})\,E_{y}(dx) \right) \right] \pi_{y} \\ &= \sum_{y\in Y} \left[\int_{x\in X} \left(\int_{\tilde{x}\in X} \lambda\,\ell(h_{\tilde{x}},x,y)\,\tau(x,y,d\tilde{x})\,E_{y}(dx) \right) \right] \pi_{y} \\ &= \sum_{y\in Y} \left[\int_{x\in X} \tau[\lambda\ell_{(x,y)}\circ h](x,y)\,E_{y}(dx) \right] \pi_{y} \quad (S5) \\ &= \mathbb{E}_{(X,Y)\sim(\pi_{Y}\times E)} \left[\left(\tau(\lambda\ell_{(X,Y)}\circ h) \right) (X,Y) \right] . \end{split}$$

Following the same reasoning, we can also write

$$\mathbb{E}_{(\tilde{\mathsf{X}},\tilde{\mathsf{Y}})\sim\tilde{P}}[\ell(h_{\tilde{\mathsf{X}}},\tilde{\mathsf{Y}})] = \mathbb{E}_{(\mathsf{X},\mathsf{Y})\sim(\pi_{\mathsf{X}}\times F)}\left[\left(\tau(\lambda\ell_{(\mathsf{X},\mathsf{Y})}\circ h)\right)(\mathsf{X},\mathsf{Y})\right] \,.$$

We prove point 2 and 3 minimizing both the obtained risk equalities w.r.t. $h \in \mathcal{H}$.

S6 Proofs for CL and GCL

In this section, we give the proof of the results stated in § 5. In addition to the assumptions A1 and 2 stated for proving the BR theorems (§ S5), we assume here:

A3 There exist a loss function $\tilde{\ell}$ such that $f^* = \tilde{\ell} \circ h$ for some model of interest $h \in \mathcal{H}$, and that satisfies the equality $\kappa^{\dagger}(\ell \circ h) = \tilde{\ell} \circ h$.

Here **A3** is restated for a general model *h*; in the main, we directly assume it to be the corrupted minimum, since ultimately our goal is to apply the result to such model.

Restated for a general $h \in H$, we are finding the following representation of the corrupted minimization set:

$$\kappa^{\dagger}(\ell \circ \mathcal{H}) = \{\tilde{\ell}_h \circ h \mid h \in \mathcal{H}\},\$$

if assuming **A3** for every $\tilde{\ell}_h$.

Theorem. Let (ℓ, \mathcal{H}, P) be a clean learning problem and $(\kappa^{\dagger}(\ell \circ \mathcal{H}), P \circ \kappa)$ its associated corrupted one. Let $\kappa^{\dagger} = \tau \otimes \lambda$ be the joint cleaning kernel reversing κ , such that assumptions A1 and 2 hold for

the said problems. Hence, provided that ℓ_{ξ} is a function in $L^0(\mathcal{P}(Y), \tau \# \tilde{h}^*(\xi))$, with ξ being either \tilde{x} or \tilde{y} depending on the case, we have:

1. Let $\kappa^{\dagger} = \delta_X \otimes \lambda$. When $\lambda \in \mathcal{M}(Y, Y)$, we have

$$\tilde{\ell}(h(\tilde{x}), \tilde{y}) \coloneqq (\lambda \ell) (h(\tilde{x}), \tilde{y}) \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y,$$

while when $\mathcal{M}(X \times Y, Y)$ we have

$$\tilde{\ell}(h(\tilde{x}), \tilde{x}, \tilde{y}) \coloneqq (\lambda \ell) (h(\tilde{x}), \tilde{x}, \tilde{y}) \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y.$$

2. When A3 holds for κ^{\dagger} , and it is of the form $(\tau : X \rightsquigarrow X) \otimes (\lambda : Y \rightsquigarrow Y)$, or $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : Y \rightsquigarrow Y)$, or $(\tau : X \rtimes X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$, we have

$$\tilde{\ell}(h, \tilde{x}, \tilde{y}) \coloneqq \mathbb{E}_{\mathsf{u} \sim (\tau \# h)(\tilde{x})} [\lambda \ell(\mathsf{u}, \tilde{y})] \quad \forall (\tilde{x}, \tilde{y}) \in \mathbf{X} \times \mathbf{Y}.$$

For the cases that involve a 2-dependent corruption, for the former κ^{\dagger} factorization we have $\lambda(\ell) = \lambda_{\tilde{x}}(\ell) - inducing \ \lambda\ell(\mathbf{u}, \tilde{x}, \tilde{y})$, while we get $(\tau \# h)(\tilde{x}) = (\tau \# h)(\tilde{x}, \tilde{y})$ for the latter.

3. When A3 holds for κ^{\dagger} , and it is of the form $(\tau : \Upsilon \rightsquigarrow X) \otimes (\lambda : X \rightsquigarrow \Upsilon)$, we have

$$\hat{\ell}(h, \tilde{x}, \tilde{y}) \coloneqq \mathbb{E}_{\mathsf{u} \sim (\tau \# h)(\tilde{y})}[\lambda \ell(\mathsf{u}, \tilde{x})] \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y$$

4. When A3 holds for κ^{\dagger} , and it is of the form $(\tau : Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$, or $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \sim Y)$, we respectively have

$$\begin{split} \tilde{\ell}(h,\tilde{x},\tilde{y}) &\coloneqq \mathbb{E}_{\mathsf{u}\sim(\tau\#h)(\tilde{y})}[\lambda\ell(\mathsf{u},\tilde{x},\tilde{y})] \quad \forall (\tilde{x},\tilde{y}) \in X \times Y; \\ \tilde{\ell}(h,\tilde{x},\tilde{y}) &\coloneqq \mathbb{E}_{\mathsf{u}\sim(\tau\#h)(\tilde{x},\tilde{y})}[\lambda\ell(\mathsf{u},\tilde{x})] \quad \forall (\tilde{x},\tilde{y}) \in X \times Y. \end{split}$$

5. When A3 holds for κ^{\dagger} , and it is of the form $(\tau : X \times Y \rightsquigarrow X) \otimes (\lambda : X \times Y \rightsquigarrow Y)$, we have

$$\tilde{\ell}(h, \tilde{x}, \tilde{y}) \coloneqq \mathbb{E}_{\mathsf{u} \sim (\tau \# h)(\tilde{x}, \tilde{y})} [\lambda \ell(\mathsf{u}, \tilde{x}, \tilde{y})] \quad \forall (\tilde{x}, \tilde{y}) \in X \times Y.$$

Proof. Given assumption A3, we can write for a general model in the clean model class:

$$\tilde{\ell}(h(\tilde{x}),\tilde{y}) = \sum_{y \in Y} \int_{x \in X} \ell(h(x), y) \,\kappa^{\dagger}(\tilde{x}, \tilde{y}, dxdy) = \sum_{y \in Y} \int_{x \in X} \ell(h(x), y) \,(\tau \otimes \lambda)(\tilde{x}, \tilde{y}, dxdy) \;.$$

Consider the κ^{\dagger} from point 1. They act on $\ell \circ h$ as

$$\tilde{\ell}(h(\tilde{x}), \tilde{x}, \tilde{y}) = \sum_{y \in Y} \int_{x \in X} \ell(h(x), y) \,\delta(\tilde{x}, dx) \,\lambda(\tilde{x}, \tilde{y}, dy) = \int_{x \in X} (\lambda \ell)(h(x), \tilde{x}, \tilde{y}) \,\delta(\tilde{x}, dx) = (\lambda \ell)(h(\tilde{x}), \tilde{x}, \tilde{y}) \,.$$

Hence, the case $\lambda(\tilde{x}, \tilde{y}, dy) = \lambda_{\tilde{x}}(\tilde{y}, dy)$ and its subcase $\lambda(\tilde{y}, dy)$ combined with an identity kernel on X do not change the hypothesis function.

For the more complex cases in point 2, $\tau(\tilde{x}, dx) \neq \delta_x(dx)$, we have:

$$\begin{split} \tilde{\ell}(h,\tilde{x},\tilde{y}) &= \sum_{y \in Y} \int_{x \in X} \ell(h(x),y) \,\tau(\tilde{x},dx) \,\lambda(\tilde{x},\tilde{y},dy) \\ &= \sum_{y \in Y} \int_{x \in h(X)} \ell(u,y) \,\tau(\tilde{x},(h)^{-1}(du)) \,\lambda(\tilde{x},\tilde{y},dy) = \int_{x \in h(X)} (\lambda\ell)_{\tilde{x}}(u,\tilde{y}) \,\tau(\tilde{x},(h)^{-1}(du)) \;, \end{split}$$
(S6)

where $u = u(dy) \in \mathcal{P}(Y)$. The following equality for the expectation of u, the image measure of τ through h, and the kernel chain composition holds:

$$\mathbb{E}_{\mathsf{u}\sim\tau(\tilde{x},(h)^{-1}(\cdot))}[\mathsf{u}] = \int_{x\in\tilde{h}^*(X)} u \,\tau(\tilde{x},(h)^{-1}(du)) = (\tau \# h)(\tilde{x}) \in \mathcal{P}(Y) ,$$

that can be verified easily by recalling the alternative definition of \mathcal{H} as a subset of $\mathcal{M}(X, Y)$ and using the definition of $\tau #h$. We remark that $\tau(\tilde{x}, (h)^{-1}(du))$ is then a probability in $\mathcal{P}(\mathcal{P}(Y))$. Hence we can rewrite Eq. (S6) as

$$\tilde{\ell}(h,\tilde{x},\tilde{y}) = \int_{u\in\mathcal{P}(Y)} (\lambda\ell)_{\tilde{x}}(u,\tilde{y}) \,\tau(\tilde{x},(h)^{-1}(du)) = \mathbb{E}_{\mathsf{u}\sim\tau(\tilde{x},(h)^{-1}(\cdot))}[(\lambda\ell)(\mathsf{u},\tilde{x},\tilde{y})]$$

with τ having support included in $\hat{h}^*(X)$.

As for more dependent corruptions of *X*, i.e. $\tau(\tilde{x}, \tilde{y}, dx)$, the action on the hypothesis will be dependent from \tilde{y} . Therefore we obtain $\tilde{\ell}(h, \tilde{x}, \tilde{y}) = \mathbb{E}_{\tau(\tilde{x}, \tilde{y}, (h)^{-1}(\cdot))}[(\lambda \ell)(\mathsf{u}, \tilde{x}, \tilde{y})]$, where only the simple *Y* noise can be considered, given the missing result for the BR equality in the $D(\tau) = D(\lambda) = X \times Y$ case. As for points 3, 4 and 5, we follow the same procedure deployed in the above, using the action formula of dependent corruptions as described in the proof of Theorems 16 and 18, and obtain the thesis.

References

- [1] Mary Poovey. A history of the modern fact: Problems of knowledge in the sciences of wealth and society. University of Chicago Press, 1998.
- [2] Robert C Williamson. Process and Purpose, Not Thing and Technique: How to Pose Data Science Research Challenges. *Harvard Data Science Review*, 2(3), 2020.
- [3] World Economic Forum. How to prevent discriminatory outcomes in machine learning. In World Economic Forum Global Future Council on Human Rights 2016-18, REF, 2018.
- [4] Andrey Malinin, Neil Band, Yarin Gal, Mark Gales, Alexander Ganshin, German Chesnokov, Alexey Noskov, Andrey Ploskonosov, Liudmila Prokhorenkova, Ivan Provilkov, Vatsal Raina, Vyas Raina, Denis Roginskiy, Mariya Shmatova, Panagiotis Tigas, and Boris Yangel. Shifts: A dataset of real distributional shift across multiple large-scale tasks. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021.
- [5] Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, et al. Wilds: A benchmark of in-the-wild distribution shifts. In *International Conference on Machine Learning*, pages 5637–5664. PMLR, 2021.

- [6] Xiao-Li Meng. Enhancing (publications on) data quality: Deeper data minding and fuller data confession. *Journal of the Royal Statistical Society Series A: Statistics in Society*, 184(4): 1161–1175, 2021.
- [7] Negar Rostamzadeh, Ben Hutchinson, Christina Greer, and Vinodkumar Prabhakaran. Thinking beyond distributions in testing machine learned models. In *NeurIPS* 2021 Workshop on Distribution Shifts: Connecting Methods and Applications, 2021.
- [8] Facundo Mémoli, Brantley Vose, and Robert C Williamson. Geometry and stability of supervised learning problems. *arXiv preprint arXiv:2403.01660*, 2024.
- [9] Dana Angluin and Philip Laird. Learning from noisy examples. *Machine Learning*, 2: 343–370, 1988.
- [10] Kun Zhang, Bernhard Schölkopf, Krikamol Muandet, and Zhikun Wang. Domain adaptation under target and conditional shift. In *International conference on machine learning*, pages 819–827. PMLR, 2013.
- [11] Nagarajan Natarajan, Inderjit S Dhillon, Pradeep K Ravikumar, and Ambuj Tewari. Learning with noisy labels. *Advances in neural information processing systems*, 26, 2013.
- [12] Giorgio Patrini, Alessandro Rozza, Aditya Krishna Menon, Richard Nock, and Lizhen Qu. Making deep neural networks robust to label noise: A loss correction approach. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1944–1952, 2017.
- [13] Hidetoshi Shimodaira. Improving predictive inference under covariate shift by weighting the log-likelihood function. *Journal of statistical planning and inference*, 90(2):227–244, 2000.
- [14] Joaquin Quiñonero-Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D Lawrence. *Dataset shift in machine learning*. MIT Press, 2008.
- [15] Tianyi Zhang, Ikko Yamane, Nan Lu, and Masashi Sugiyama. A one-step approach to covariate shift adaptation. In *Asian Conference on Machine Learning*, pages 65–80. PMLR, 2020.
- [16] Jose G Moreno-Torres, Troy Raeder, Rocío Alaiz-Rodríguez, Nitesh V Chawla, and Francisco Herrera. A unifying view on dataset shift in classification. *Pattern recognition*, 45(1):521–530, 2012.
- [17] Meelis Kull and Peter Flach. Patterns of dataset shift. In *First International Workshop on Learning over Multiple Contexts (LMCE) at ECML-PKDD*, 2014.
- [18] José A. Sáez. Noise models in classification: Unified nomenclature, extended taxonomy and pragmatic categorization. *Mathematics*, 10(20), 2022.
- [19] Adarsh Subbaswamy, Bryant Chen, and Suchi Saria. A unifying causal framework for analyzing dataset shift-stable learning algorithms. *Journal of Causal Inference*, 10(1):64–89, 2022.
- [20] George Shackelford and Dennis Volper. Learning k-DNF with noise in the attributes. In Proceedings of the first annual workshop on Computational learning theory, pages 97–103, 1988.
- [21] Sally A. Goldman and Robert H. Sloan. Can PAC learning algorithms tolerate random attribute noise? *Algorithmica*, 14(1):70–84, 1995.

- [22] Xingquan Zhu and Xindong Wu. Class noise vs. attribute noise: A quantitative study. *The Artificial Intelligence Review*, 22(3):177, 2004.
- [23] Robert C. Williamson and Zac Cranko. Information processing equalities and the information–risk bridge. *Journal of machine learning research*, 25(103):1–53, 2024.
- [24] Avrim Blum and Tom Mitchell. Combining labeled and unlabeled data with co-training. In *Proceedings of the eleventh annual conference on Computational learning theory*, pages 92–100, 1998.
- [25] Brendan Van Rooyen, Aditya Menon, and Robert C Williamson. Learning with symmetric label noise: The importance of being unhinged. *Advances in neural information processing* systems, 28, 2015.
- [26] Brendan van Rooyen and Robert C. Williamson. A theory of learning with corrupted labels. *Journal of machine learning research*, 18(228):1–50, 2018.
- [27] Aditya Krishna Menon, Brendan Van Rooyen, and Nagarajan Natarajan. Learning from binary labels with instance-dependent noise. *Machine Learning*, 107(8):1561–1595, 2018.
- [28] Jiacheng Cheng, Tongliang Liu, Kotagiri Ramamohanarao, and Dacheng Tao. Learning with bounded instance and label-dependent label noise. In *International Conference on Machine Learning*, pages 1789–1799. PMLR, 2020.
- [29] Yu Yao, Tongliang Liu, Mingming Gong, Bo Han, Gang Niu, and Kun Zhang. Instancedependent label-noise learning under a structural causal model. *Advances in Neural Information Processing Systems*, 34:4409–4420, 2021.
- [30] Qizhou Wang, Bo Han, Tongliang Liu, Gang Niu, Jian Yang, and Chen Gong. Tackling instance-dependent label noise via a universal probabilistic model. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 10183–10191, 2021.
- [31] Gilles Blanchard and Clayton Scott. Decontamination of mutually contaminated models. In *Artificial Intelligence and Statistics*, pages 1–9. PMLR, 2014.
- [32] Aditya Menon, Brendan Van Rooyen, Cheng Soon Ong, and Robert C Williamson. Learning from corrupted binary labels via class-probability estimation. In *International conference on machine learning*, pages 125–134. PMLR, 2015.
- [33] Gilles Blanchard, Marek Flaska, Gregory Handy, Sara Pozzi, and Clayton Scott. Classification with asymmetric label noise: Consistency and maximal denoising. *Electronic Journal of Statistics*, 10(2):2780–2824, 2016.
- [34] Julian Katz-Samuels, Gilles Blanchard, and Clayton Scott. Decontamination of mutual contamination models. *Journal of machine learning research*, 20(41), 2019.
- [35] Nathalie Japkowicz and Shaju Stephen. The class imbalance problem: A systematic study. *Intelligent data analysis*, 6(5):429–449, 2002.
- [36] Haibo He and Edwardo A García. Learning from imbalanced data. *IEEE Transactions on knowledge and data engineering*, 21(9):1263–1284, 2009.
- [37] Mateusz Buda, Atsuto Maki, and Maciej A Mazurowski. A systematic study of the class imbalance problem in convolutional neural networks. *Neural networks*, 106:249–259, 2018.

- [38] Zachary Lipton, Yu-Xiang Wang, and Alexander Smola. Detecting and correcting for label shift with black box predictors. In *International conference on machine learning*, pages 3122–3130. PMLR, 2018.
- [39] Arthur Gretton, Alex Smola, Jiayuan Huang, Marcel Schmittfull, Karsten Borgwardt, and Bernhard Schölkopf. Covariate shift by kernel mean matching. *Dataset shift in machine learning*, 3(4):5, 2009.
- [40] Masashi Sugiyama and Motoaki Kawanabe. *Machine learning in non-stationary environments: Introduction to covariate shift adaptation.* MIT press, 2012.
- [41] Mingming Gong, Kun Zhang, Tongliang Liu, Dacheng Tao, Clark Glymour, and Bernhard Schölkopf. Domain adaptation with conditional transferable components. In *International conference on machine learning*, pages 2839–2848. PMLR, 2016.
- [42] Xiyu Yu, Tongliang Liu, Mingming Gong, Kun Zhang, Kayhan Batmanghelich, and Dacheng Tao. Label-noise robust domain adaptation. In *International conference on machine learning*, pages 10913–10924. PMLR, 2020.
- [43] Leon A Gatys, Alexander S Ecker, and Matthias Bethge. A neural algorithm of artistic style. arXiv preprint arXiv:1508.06576, 2015.
- [44] Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *European Conference on Computer Vision*, page 694, 2016.
- [45] Eric Grinstein, Ngoc QK Duong, Alexey Ozerov, and Patrick Pérez. Audio style transfer. In 2018 IEEE international conference on acoustics, speech and signal processing (ICASSP), pages 586–590. IEEE, 2018.
- [46] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.
- [47] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2015.
- [48] Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In 2016 IEEE European symposium on security and privacy (EuroS&P), pages 372–387. IEEE, 2016.
- [49] Alexey Kurakin, Ian J Goodfellow, and Samy Bengio. Adversarial examples in the physical world. In Artificial intelligence safety and security, pages 99–112. Chapman and Hall/CRC, 2018.
- [50] Dan Hendrycks, Kevin Zhao, Steven Basart, Jacob Steinhardt, and Dawn Song. Natural adversarial examples. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15262–15271, 2021.
- [51] Gerhard Widmer and Miroslav Kubat. Learning in the presence of concept drift and hidden contexts. *Machine learning*, 23:69–101, 1996.
- [52] João Gama, Indrė Žliobaitė, Albert Bifet, Mykola Pechenizkiy, and Abdelhamid Bouchachia. A survey on concept drift adaptation. ACM computing surveys (CSUR), 46(4): 1–37, 2014.

- [53] Jie Lu, Anjin Liu, Fan Dong, Feng Gu, Joao Gama, and Guangquan Zhang. Learning under concept drift: A review. *IEEE Transactions on Knowledge and Data Engineering*, pages 1–1, 2018.
- [54] Peter Vorburger and Abraham Bernstein. Entropy-based concept shift detection. In *Sixth International Conference on Data Mining (ICDM'06)*, pages 1113–1118. IEEE, 2006.
- [55] Gerhard Widmer and Miroslav Kubat. Effective learning in dynamic environments by explicit context tracking. In *European Conference on Machine Learning*, volume 6, pages 227–243, 1993.
- [56] Marcos Salganicoff. Tolerating concept and sampling shift in lazy learning using prediction error context switching. *Artificial Intelligence Review*, 11:133–155, 1997.
- [57] Alexey Tsymbal. The problem of concept drift: definitions and related work. *Computer Science Department, Trinity College Dublin,* 106(2):58, 2004.
- [58] Achim Klenke. Probability Theory: A Comprehensive Course. Springer, 2007.
- [59] Erhan Çinlar. Probability and Stochastics. Springer, 2011.
- [60] Olav Kallenberg. Random measures, theory and applications. Springer, 2017.
- [61] David Johnston. *Statistical Causal Modelling and Decision Theory*. PhD thesis, The Australian National University, 2023.
- [62] Arthur Parzygnat. Kleisli categories and probability 03 markov kernels. https: //youtu.be/psUDrasc210?si=we87QEeKiGOa0_eN, 2020.
- [63] Imre Csiszár. A class of measures of informativity of observation channels. *Periodica Mathematica Hungarica*, 2(1-4):191–213, 1972.
- [64] Erik Torgersen. Comparison of statistical experiments. Cambridge University Press, 1991.
- [65] Albert N Shiryaev and Vladimir G Spokoiny. *Statistical Experiments And Decision, Asymptotic Theory*. World Scientific, 2000.
- [66] Nithya Sambasivan, Shivani Kapania, Hannah Highfill, Diana Akrong, Praveen Paritosh, and Lora M Aroyo. "Everyone wants to do the model work, not the data work": Data Cascades in High-Stakes AI. In proceedings of the 2021 CHI Conference on Human Factors in Computing Systems, pages 1–15, 2021.
- [67] Peter L Bartlett, Michael I Jordan, and Jon D McAuliffe. Convexity, classification, and risk bounds. *Journal of the American Statistical Association*, 101(473):138–156, 2006.
- [68] Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Vaughan. A theory of learning from different domains. *Machine Learning*, 79: 151–175, 2010.
- [69] Riccardo Fogliato, Alexandra Chouldechova, and Max G'Sell. Fairness evaluation in presence of biased noisy labels. In *International conference on artificial intelligence and statistics*, pages 2325–2336. PMLR, 2020.
- [70] Jonathan Rothwell. How the war on drugs damages black social mobility. *The Brookings Institution, published Sept*, 30, 2014.

- [71] Charles Elkan and Keith Noto. Learning classifiers from only positive and unlabeled data. In Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining, pages 213–220, 2008.
- [72] Gill Ward, Trevor Hastie, Simon Barry, Jane Elith, and John R Leathwick. Presence-only data and the EM algorithm. *Biometrics*, 65(2):554–563, 2009.
- [73] Marthinus C Du Plessis, Gang Niu, and Masashi Sugiyama. Analysis of learning from positive and unlabeled data. *Advances in neural information processing systems*, 27, 2014.
- [74] Marthinus Du Plessis, Gang Niu, and Masashi Sugiyama. Convex formulation for learning from positive and unlabeled data. In *International conference on machine learning*, pages 1386–1394. PMLR, 2015.
- [75] Ryuichi Kiryo, Gang Niu, Marthinus C Du Plessis, and Masashi Sugiyama. Positiveunlabeled learning with non-negative risk estimator. *Advances in neural information* processing systems, 30, 2017.
- [76] Novi Quadrianto, Alex J Smola, Tiberio S Caetano, and Quoc V Le. Estimating labels from label proportions. In *Proceedings of the 25th International Conference on Machine learning*, pages 776–783, 2008.
- [77] Felix X Yu, Krzysztof Choromanski, Sanjiv Kumar, Tony Jebara, and Shih-Fu Chang. On learning from label proportions. *arXiv preprint arXiv:*1402.5902, 2014.
- [78] Jiabin Liu, Bo Wang, Zhiquan Qi, Yingjie Tian, and Yong Shi. Learning from label proportions with generative adversarial networks. *Advances in neural information processing systems*, 32, 2019.
- [79] Clayton Scott and Jianxin Zhang. Learning from label proportions: A mutual contamination framework. *Advances in neural information processing systems*, 33:22256–22267, 2020.
- [80] Yuting Tang, Nan Lu, Tianyi Zhang, and Masashi Sugiyama. Multi-class classification from multiple unlabeled datasets with partial risk regularization. In *Asian Conference on Machine Learning*, pages 990–1005. PMLR, 2023.
- [81] David Blackwell. Comparison of experiments. *Second Berkeley Symposium on Mathematical Statistics and Probability*, pages 93–102, 1951.
- [82] Brendan Van Rooyen. *Machine learning via transitions*. PhD thesis, The Australian National University, 2015.
- [83] Wikipedia contributors. Data corruption Wikipedia, the free encyclopedia. https: //en.wikipedia.org/w/index.php?title=Data_corruption&oldid=1176791517, 2023. [Online; accessed 13-October-2023].
- [84] Andreas Buja, Werner Stuetzle, and Yi Shen. Loss functions for binary class probability estimation and classification: Structure and applications. *Working draft, November*, 2005.
- [85] Robert Williamson, Elodie Vernet, and Mark Reid. Composite multiclass losses. *Journal of machine learning research*, 17(222):1–52, 2016.
- [86] Corinna Cortes, Yishay Mansour, and Mehryar Mohri. Learning bounds for importance weighting. In J. Lafferty, C. Williams, J. Shawe-Taylor, R. Zemel, and A. Culotta,

editors, Advances in Neural Information Processing Systems, volume 23. Curran Associates, Inc., 2010. URL https://proceedings.neurips.cc/paper_files/paper/2010/file/ 59c33016884a62116be975a9bb8257e3-Paper.pdf.

- [87] Tongliang Liu and Dacheng Tao. Classification with noisy labels by importance reweighting. *IEEE Transactions on pattern analysis and machine intelligence*, 38(3):447–461, 2015.
- [88] Tongtong Fang, Nan Lu, Gang Niu, and Masashi Sugiyama. Rethinking importance weighting for deep learning under distribution shift. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, pages 11996–12007. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/8b9e7ab295e87570551db122a04c6f7c-Paper.pdf.
- [89] Tongtong Fang, Nan Lu, Gang Niu, and Masashi Sugiyama. Generalizing importance weighting to a universal solver for distribution shift problems. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.
- [90] Clayton Scott. A rate of convergence for mixture proportion estimation, with application to learning from noisy labels. In *Artificial Intelligence and Statistics*, pages 838–846. PMLR, 2015.
- [91] Xiao-Li Meng. Comments on "statistical inference with non-probability survey samples"miniaturizing data defect correlation: A versatile strategy for handling non-probability samples, 2022.
- [92] Robin J Boyd, Gary D Powney, and Oliver L Pescott. We need to talk about nonprobability samples. *Trends in Ecology & Evolution*, 2023.
- [93] Donald B Rubin. Inference and missing data. *Biometrika*, 63(3):581–592, 1976.
- [94] Roderick JA Little and Donald B Rubin. *Statistical analysis with missing data*. John Wiley & Sons, 2019.
- [95] Takashi Ishida, Gang Niu, Weihua Hu, and Masashi Sugiyama. Learning from complementary labels. *Advances in neural information processing systems*, 30, 2017.
- [96] Takashi Ishida, Gang Niu, Aditya Menon, and Masashi Sugiyama. Complementary-label learning for arbitrary losses and models. In *International Conference on Machine Learning*, pages 2971–2980. PMLR, 2019.
- [97] Aritra Ghosh, Naresh Manwani, and PS Sastry. Making risk minimization tolerant to label noise. *Neurocomputing*, 160:93–107, 2015.
- [98] Jun Du and Zhihua Cai. Modelling class noise with symmetric and asymmetric distributions. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2015.
- [99] Kun Zhang, Mingming Gong, Petar Stojanov, Biwei Huang, Qingsong Liu, and Clark Glymour. Domain adaptation as a problem of inference on graphical models. *Advances in neural information processing systems*, 33:4965–4976, 2020.
- [100] Keisuke Yamazaki, Motoaki Kawanabe, Sumio Watanabe, Masashi Sugiyama, and Klaus-Robert Müller. Asymptotic bayesian generalization error when training and test distributions are different. In *Proceedings of the 24th international conference on Machine learning*, pages 1079–1086, 2007.

- [101] Rocío Alaiz-Rodríguez and Nathalie Japkowicz. Assessing the impact of changing environments on classifier performance. In Advances in Artificial Intelligence: 21st Conference of the Canadian Society for Computational Studies of Intelligence, Canadian AI 2008 Windsor, Canada, May 28-30, 2008 Proceedings 21, pages 13–24. Springer, 2008.
- [102] Kaihua Tang, Mingyuan Tao, Jiaxin Qi, Zhenguang Liu, and Hanwang Zhang. Invariant feature learning for generalized long-tailed classification. In *European Conference on Computer Vision*, pages 709–726. Springer, 2022.
- [103] Judea Pearl. Causality. Cambridge university press, 2009.
- [104] Fredrik Dahlqvist, Vincent Danos, Ilias Garnier, and Ohad Kammar. Bayesian inversion by *ω*-complete cone duality. In *27th International Conference on Concurrency Theory*, 2016.
- [105] Saunders Mac Lane. *Categories for the working mathematician*. Springer Science & Business Media, 2013.
- [106] Arnold M Faden. The existence of regular conditional probabilities: necessary and sufficient conditions. *The Annals of Probability*, pages 288–298, 1985.
- [107] Nicolo Cesa-Bianchi, Shai Shalev-Shwartz, and Ohad Shamir. Online learning of noisy data with kernels. arXiv preprint arXiv:1005.2296, 2010. Full version of the paper appearing in the 23rd International Conference on Learning Theory (COLT 2010).
- [108] Ievgen Redko, Emilie Morvant, Amaury Habrard, Marc Sebban, and Younès Bennani. A survey on domain adaptation theory: learning bounds and theoretical guarantees. arXiv preprint arXiv:2004.11829, 2022.