Almost Envy-Freeness under Weakly Lexicographic Preferences

Hadi Hosseini, Aghaheybat Mammadov, and Tomasz Was

Pennsylvania State University

{hadi, mammadovagha, twas}@psu.edu

Abstract

In fair division of indivisible items, domain restriction has played a key role in escaping from negative results and providing structural insights into the computational and axiomatic boundaries of fairness. One notable subdomain of additive preferences, the lexicographic domain, has yielded several positive results in dealing with goods, chores, and mixtures thereof. However, the majority of work within this domain primarily consider strict linear orders over items, which do not allow the modeling of more expressive preferences that contain indifferences (ties). We investigate the most prominent fairness notions of envy-freeness up to any (EFX) or some (EF1) item under weakly lexicographic preferences. For the goods-only setting, we develop an algorithm that can be customized to guarantee EF1, EFX, maximin share (MMS), or a combination thereof, along the efficiency notion of Pareto optimality (PO). From the conceptual perspective, we propose techniques such as preference graphs and potential envy that are independently of interest when dealing with ties. Finally, we demonstrate challenges in dealing with chores and highlight key algorithmic and axiomatic differences of finding EFX solutions with the goods-only setting. Nevertheless, we show that there is an algorithm that always returns an EF1 and PO allocation for the chores-only instances.

1 Introduction

The distribution of indivisible items is a fundamental problem in a wide array of societal, computational, and economic settings. Over the past few decades, the field of fair division has emerged to promote fairness in designing scalable algorithms for distributing resources and tasks. Arguably, one of the primary drivers behind recent advancements in algorithmic fairness was the focus on restricted domains (e.g., additive valuations) that enabled concise representation of preferences in complex resource allocation problems. Domain restriction has played a key role in escaping from negative results and providing structural insights into the computational and axiomatic boundaries in computational social choice [Lang et al., 2018, Hosseini and Larson, 2019, Nguyen, 2020, Fujita et al., 2018]. One notable subdomain of additive preferences, the lexicographic domain, has received much attention due to its succinct representation of complex preferences and its natural proxy for modeling consumer behavior [Gigerenzer and Goldstein, 1996, Fishburn, 1974].

Within fair division, the lexicographic domain has resulted in several positive results in dealing with goods [Hosseini et al., 2021], chores [Ebadian et al., 2022, Hosseini et al., 2022b], and mixtures thereof [Hosseini et al., 2023]. These results primarily consider strict linear orderings over the items, which do not allow for the modeling of more expressive preferences that contain ties (aka weak preferences). Yet, individuals are often indifferent between sets of items and tend

to group those into 'equivalence classes'. For example, in conference paper reviewing, one may strictly prefer papers from computational social choice to those from computer vision, but the same reviewer may be indifferent between papers that cover topics in fair division.

The introduction of weak preferences poses several intriguing algorithmic challenges, particularly when dealing with economic efficiency; as such ties have been in the center of attention in a large body of work, for example, in probabilistic assignments with ordinal or lexicographic preferences [Katta and Sethuraman, 2006, Saban and Sethuraman, 2014, Aziz et al., 2015], mechanism design for object allocation [Bogomolnaia et al., 2005, Krysta et al., 2014], assigning papers to reviewers [Garg et al., 2010], and Shapley-Scarf housing markets [Klaus and Meo, 2023, Saban and Sethuraman, 2013, Jaramillo and Manjunath, 2012, Aziz and De Keijzer, 2012].

Along this line, we focus on expanding the existing computational and axiomatic results in fair division to the more expressive preference class that allows for 'mild continuity' in preferences over items. We investigate the most prominent fairness notion, envy-freeness EF, and its relaxations envy-freeness up to *any* item (EFX) [Caragiannis et al., 2019] and envy-freeness up to *some* item (EF1) [Lipton et al., 2004, Budish, 2011], along with an efficiency requirement of Pareto optimality (PO). EFX requires that a pairwise envy between the two agents is eliminated by the removal of any good (or chore) from the envied (envious) agent's bundle, while EF1 relaxes this requirement to the removal of some single item from the bundle of one of the two agents. Furthermore, we consider fairness notion of *maximin share* (MMS) [Budish, 2011], which states that an agent should receive a bundle at least as preferable as the best possible bundle it can get in a partition from which it receives the worst bundle.

1.1 Contributions

We study fair and efficient allocations in goods-only and chores-only instances under weakly lexicographic preferences. We present computational and axiomatic results regarding well-established fairness notions of EF and its prominent relaxations, EFX and EF1, and MMS, as well as conceptual techniques which hold independent significance when dealing with ties.

Goods. Our first result shows that with the introduction of ties, deciding if an EF allocation of goods exists becomes NP-complete, even when agents have at most two indifference classes (Theorem 1). Given the nonexistence and computational hardness for EF, we develop a customizable algorithm that finds a PO allocation satisfying an EF relaxation of EF1, MMS, EFX, or a combination thereof, depending on the chosen parameters (Theorem 3).

This way, we are able to pinpoint to an exact place in our algorithm that is responsible for guaranteeing fairness.

Chores. Under additive preferences, there has been much less progress for chores, and as such, the existence of EF1 and PO is still open. We prove the existence and computation of such an allocation under weakly lexicographic preferences (Theorem 4) as the *largest* known subclass of additive valuations for which EF1 and PO can be guaranteed. Moreover, we illustrate the challenges involved in fairly allocating chores (Examples 2 and 3), and show that in the chores-only instances, EFX implies MMS (Proposition 3), which surprisingly stands in contrast to the case of goods (Appendix E).

Conceptual Techniques. From the technical perspective, we develop novel techniques such as preference graphs and potential envy (Definition 1 and Figure 1a) for handling indifferences when

the goal is to guarantee fairness along with efficiency in this setting.

2 Related Work

It is well-known that for goods-only instances with additive preferences an EF1 allocation can be efficiently computed [Lipton et al., 2004]. Moreover, an allocation satisfying EF1 and PO always exists [Caragiannis et al., 2019] and can be computed in pseudo-polynomial time [Barman et al., 2018]. Nevertheless, the existence of EFX allocations remains unresolved for this general setting. To gain insights into the problem, a wide variety of restricted domains have been considered. In particular, it has been shown that an EFX allocation always exists for instances with identical valuations [Plaut and Roughgarden, 2020], under submodular utilities with binary marginals [Babaioff et al., 2021], and for additive preferences with interval valuations or at most two distinct values [Amanatidis et al., 2021, Garg and Murhekar, 2021]. However, EFX is not compatible with PO under submodular valuations [Plaut and Roughgarden, 2020]. Nevertheless, under strict lexicographic preferences, an EFX and PO allocation always exists and can be computed in polynomial time [Hosseini et al., 2021].

In studying possible fairness, Aziz et al. [2023a] proposed an algorithm for finding an EFX, MMS, and PO allocation under weakly lexicographic preferences. Our algorithm achieving the same guarantees has been developed concurrently and independently. Moreover, there are significant differences between these algorithms, both in terms of their outputs (see Example 1) as well as construction. The main difference on the conceptual level is that our algorithm can be easily alternated to cover different notions of fairness, allowing for better understanding of where the particular fairness guarantee is invoked. For more detailed comparison see Appendix C.

Analogous problems for chores-only instances seem much more complex. EF1 allocations can still be efficiently computed [Bhaskar et al., 2021, Aziz et al., 2022], however the existence of EF1 and PO allocations remains an important open problem, except for a few restricted domains [Ebadian et al., 2022, Garg et al., 2022, Aziz et al., 2023b]. Despite much efforts, the progress for EFX is also limited. Recent works established its existence for ordered instances [Li et al., 2022], generalized binary preferences [Camacho et al., 2023], strictly lexicographic preferences [Hosseini et al., 2022b], and instances with two types of chores [Aziz et al., 2023b].

The next most studied fairness notion is arguably MMS. It may fail to exist for both goodsonly [Kurokawa et al., 2018] and chores-only [Aziz et al., 2017] instances under additive preferences. Therefore, both multiplicative approximations [Aziz et al., 2017, Ghodsi et al., 2021, Garg and Taki, 2021] and ordinal ones [Babaioff et al., 2019, Hosseini et al., 2022a] have been proposed and analyzed. [Ebadian et al., 2022] showed, among others, that an MMS and PO allocation can be efficiently computed in every goods-only or chores-only weakly lexicographic instance.

3 Preliminaries

For every $k \in \mathbb{N}$, let $[k] = \{1, \ldots, k\}$. A weakly lexicographic instance is defined as a triple (N, M, \triangleright) , in which N = [n] is a set of *agents*, M a set of *items*, and $\triangleright = (\triangleright_i)_{i \in N}$ a family of weak linear orders over M, based on which we will define the preferences of the agents. We will consider two types of instances: in a *goods-only* instance, we say that $M = \{g_1, \ldots, g_m\}$ is a set of *goods*, while in a *chores-only* instance, it is a set of *chores*, $M = \{c_1, \ldots, c_m\}$.

Indifference classes. For each agent $i \in N$, a weak linear order \triangleright_i partitions the set M into k_i indifference classes, $\triangleright_i(1), \ldots, \triangleright_i(k_i)$, for some integer $k_i \leq |M|$. Intuitively, the agent is indifferent between two items from the same class, but for every $k \in [k_i]$, a single element of the k-th class, i.e., $\triangleright_i(k)$ cannot be compensated by any number of items from the later classes, i.e., $\triangleright_i(k')$ for k' > k. In examples, we will define the weak linear orders by explicitly writing the indifference classes divided by a triangle sign, \triangleright , to denote relation between them, e.g.,

$$1: g_1 \triangleright \{g_2, g_3\} \triangleright g_4.$$
 (1)

Preferences. For every subset $X \subseteq M$, and indifference class $k \in [k_i]$, let $\triangleright_i(k, X) = \triangleright_i(k) \cap X$. Then, we will denote a *score* vector, $s_i(X) = (s_i(1, X), \dots, s_i(k_i, X))$, in which for each $k \in [k_i]$ its k-th coordinate is defined as $s_i(k, X) = |\triangleright_i(k, X)|$, for goods-only instances, and $s_i(k, X) = -|\triangleright_i(k, X)|$, for chores-only instances. For X = M, we will write simply $s_i(k)$ for brevity. For two sets of items, $X, Y \subseteq M$, agent *i strictly prefers* set X over Y, i.e., $X \succ_i Y$, if the score of X lexicographically dominates the score of Y, i.e., $s_i(X) >_{lex} s_i(Y)$. In other words, there exists $\overline{k} \in [k_i]$ such that $s_i(\overline{k}, X) > s_i(\overline{k}, Y)$, and $s_i(k, X) = s_i(k, Y)$, for every $k < \overline{k}$.

For example, agent 1 from (1) prefers $X = \{g_1, g_4\}$ over $Y = \{g_2, g_3, g_4\}$ as $s_i(X) = (1, 0, 1) >_{lex} (0, 2, 1) = s_i(Y)$. If $s_i(X) = s_i(Y)$, then agent *i* is *indifferent* between the sets, i.e., $X \sim_i Y$. Finally, agent *i* weakly prefers X over Y, denoted by $X \succeq_i Y$, if either $X \succ_i Y$ or $X \sim_i Y$. For singleton sets, we will skip the brackets in these relations, e.g., we will write $g_1 \succ_1 g_2 \sim_1 g_3$.

Allocations. An allocation $A = (A_1, \ldots, A_n)$ is an *n* partition of *M*, such that the *bundles* of agents are disjoint, i.e., $A_i \cap A_j = \emptyset$, for every $i, j \in N$. If all items are allocated, i.e., $\bigcup_{i \in N} A_i = M$, we say that *A* is *complete*. It is *partial* otherwise. The goal is to find a complete allocation that is fair and efficient.

Envy-freeness. An agent *j* envies *i* if $A_i \succ_j A_j$. An allocation *A* is said to be envy-free (EF) if no agent envies any other. It is envy-free up to one item (EF1), if for every pair of agents $i, j \in N$ such that *j* envies *i*, $A_j \succeq_j A_i \setminus \{g\}$ for some $g \in A_i$ in case of a goods-only instance, or $A_j \setminus \{c\} \succeq_j A_i$ for some $c \in A_j$ in case of a chores-only instance. Finally, allocation *A* is envy-free up to any item (EFX), if for every pair of agents $i, j \in N$, $A_j \succeq_j A_i \setminus \{g\}$ for every $g \in A_i$ in case of a goods-only instance, or $A_j \setminus \{c\} \succeq_j A_i$ for every pair of agents $i, j \in N$, $A_j \succeq_j A_i \setminus \{g\}$ for every $g \in A_i$ in case of a goods-only instance, or $A_j \setminus \{c\} \succeq_j A_i$ for every $c \in A_j$ in case of a chores-only instance.

Maximin share. A maximin share of an agent is the score vector of the most preferred bundle it can guarantee for itself by dividing the items into n bundles and receiving the worst one. Formally, $MMS_i = \max_{(A_1,...,A_n)\in\Pi^n} \min_{j\in[n]} s_i(A_j)$, where Π^n is a set of all possible n-partitions and max and min are determined based on lexicographic dominance. An allocation A satisfies maximin share (MMS) if for every agent $i \in N$, it holds that $s_i(A_i) \ge_{lex} MMS_i$.

Pareto optimality. An (possibly partial) allocation *A Pareto dominates* allocation *B* if *A* assigns the same set of goods as *B*, i.e., $\bigcup_{i \in N} A_i = \bigcup_{i \in N} B_i$, and $A_i \succeq_i B_i$ for every $i \in N$ and there exists $j \in N$ such that $A_j \succ_j B_j$. Allocation *A* is *Pareto optimal* (PO), if it is not Pareto dominated by any other allocation.

4 Goods

Let us start with weakly lexicographic goods-only instances.

[Hosseini et al., 2021] proved that we can decide if a strict lexicographic goods-only instance admits an EF allocation in polynomial time. However, we show that the same is no longer true for weakly lexicographic instances.

Theorem 1. Deciding whether an EF allocation exists for a given weakly lexicographic goods-only instance is NP-complete, even if every agent has at most two indifference classes.

The proof is relegated to Appendix A, where we also show NP-completeness of EF combined with PO. We build upon similar proofs by Aziz et al. [2015] and Hosseini et al. [2020] for binary preferences. However, under binary preferences a good may hold no additional value to an agent, which is not possible in our setting (i.e., an agent always strictly prefers to have a good rather than not). As a result, our construction is more intricate and requires additional steps in the proof.

Motivated by the non-existence and computational hardness for EF, we move to its most compelling relaxation: EFX. In what follows, we will provide an algorithm (Algorithm 1) that, depending on a given requirement, finds an allocation that satisfies PO as well as EF1, MMS, EFX, or MMS and EFX simultaneously (Theorem 3).

4.1 Preference Graph and Potential Envy

We begin by introducing additional constructions and definitions which our algorithm utilizes.

Preference graph. First, let us introduce a *preference graph*, which is a weighted complete bipartite graph, $G_{pref} = (N, M, E, \psi)$, in which both agents and goods are vertices, all agent-good pairs are edges $E = N \times M$, and the weights, $\psi : E \to \mathbb{N}$, denote in which indifference class is a given good for a given agent, i.e., for every $(i,g) \in E$, $\psi(i,g) = k$ such that $g \in \triangleright_i(k)$. An example of a preference graph can be found in Figure 1a. For every (possibly partial) allocation A, we will slightly abuse the notation and treat A both as a collection of subsets, (A_1, \ldots, A_n) , and as a subset of edges in a preference graph, $\bigcup_{i \in N} \{(i,g) : g \in A_i\}$, depending on the context. Given a preference graph $G_{pref} = (N, M, E, \psi)$ and an (possibly partial) allocation A, an *alternating path*, $p = (g_0, i_1, g_1, \ldots, i_s, g_s)$, is a path in G_{pref} (possibly of length zero) such that

- the goods in *p* are pairwise distinct,
- p alternates between edges that belong and do not belong to A, i.e., $(g_{r-1}, i_r) \in A$, for every $r \in [s]$, and $(i_r, g_r) \notin A$, for every $r \in [s]$, and
- for every $r \in [s]$, agent i_r weakly prefers good g_r over g_{r-1} , i.e., $\psi(g_{r-1}, i_r) \ge \psi(i_r, g_r)$.

Available goods. We say that a good g is *available* if there exists an alternating path from g to an unallocated good (or g is unallocated itself). Otherwise g is *unavailable*. If an alternating path $p = (g_0, i_1, g_1, \ldots, i_s, g_s)$ ends with an unallocated good, then allocation A can be *updated* along p, to obtain allocation A' such that $A' = A \setminus \{(g_{r-1}, i_r) : r \in [s]\} \cup \{(i_r, g_r) : r \in [s]\}$. Observe that every agent $i \in N$ weakly prefers its bundle in A' compared to A. Note also that for a given good g, we can find an alternating path starting in g and ending in an unallocated good (or conclude that there is none) using the BFS algorithm in time O(nm).

Moreover, a preference graph can be used to efficiently check whether an allocation is PO. Rewriting the result of Aziz et al. [2019] using a preference graph, we get that the allocation is PO,

if and only if, there is no alternating path, p, and agent, i, such that the last good in the path, g_s , belongs to agent i, but i strictly prefers the first good in the path over g_s .

Theorem 2. [Aziz et al., 2019, Theorem 5] Given a weakly lexicographic goods-only instance (N, M, \triangleright) , an (possibly partial) allocation A is PO, if and only if, there is no alternating path, $p = (g_0, i_1, g_1, \ldots, i_s, g_s)$ and agent i_0 such that $(g_s, i_0) \in A$ and $\psi(i_0, g_0) < \psi(g_s, i_0)$.

Next, we introduce a notion of *potential envy* in a partial allocation, which we will use to guarantee EFX. Intuitively, potential envy towards an agent exists, if giving all still available goods to this agent, would result in an (actual) envy.

Definition 1. (Potential envy) Given an instance (N, M, \triangleright) , a partial allocation A, and agents $i, j \in N$, agent j potentially envies agent i if $A_i \cup B \succ_j A_j$, where B denotes the set of all available goods.

Then, a *potential envy graph* is a directed graph, $G_{envy}(U, A) = (U, E)$, that given a subset of agents U and a partial allocation A, puts an edge (i, j) from agent $i \in U$ to $j \in U \setminus \{i\}$, if and only if, i potentially envies j (see Figure 1b for an illustration).

Finally, let us include a characterization of MMS allocations that will be useful in proving that our algorithm always outputs an MMS allocation. This characterization is based on the algorithm for establishing an MMS threshold for a given agent, i, which was developed by Ebadian et al. [2022]. The algorithm starts with a family of n empty bundles. Then, in each step, it assigns an unallocated good from the first indifference class of agent i with still unallocated goods to a bundle with lexicographically minimal score s_i . After all goods are allocated, the MMS threshold is then the lexicographically minimal score s_i among the n bundles. Based on the algorithm, we provide a numerical formula for the threshold.

Proposition 1. Given a weakly lexicographic goods-only instance (N, M, \triangleright) and agent $i \in N$, it holds that $MMS_i = (x_1, x_2, ..., x_k)$, where $x_l = \lfloor s_i(l)/r_l \rfloor$, for every $l \in [k]$, while $r_1 = n$, and $r_{l+1} = r_l - (s_i(l) - r_l x_l)$, for every $l \in [k-1]$.

4.2 The Algorithm

Now, let us move to the main result of this section which is Algorithm 1 that finds a fair (EF1, MMS, or EFX) allocation which satisfies PO in polynomial time for every weakly lexicographic goods-only instance.

Our algorithm allows for flexibility in regard to the fairness guarantees it obtains. Specifically, in each iteration of our algorithm, for each agent, our algorithm decides whether we want to stop giving goods to this agent or not, based on certain criteria, F. The choice of criteria affects the fairness guarantee for the outcome. In general, these criteria can be arbitrary, but we focus on three, which, with a slight abuse of terminology, we call based on the fairness notions they turn out to guarantee: EFX, MMS, and the conjunction of both EFX+MMS. We also analyze the baseline version of the algorithm which never differentiates agents (i.e., F = null), and show that such algorithm guarantees EF1 and PO allocations.

Description. Fix an ordering of agents, σ .

We initialize the algorithm with empty bundles. In U we keep the set of prioritized agents, for which we put U = N at the start. In each iteration of the main loop (lines 2–8), we take an agent i_0 from U that has the least number of goods (the earliest in ordering σ if there is a tie). In case $U = \emptyset$ (which is only possible if F = MMS), we take i_0 from N. Next, agent i_0 chooses the most preferred

Algorithm 1 Finding a fair and efficient allocation of goods

Input: A weakly lexicographic goods-only instance $\langle N, M, \rhd \rangle$, an ordering σ , and criteria F

- 1: $A \leftarrow (\emptyset, \dots, \emptyset), \quad G_{pref} \leftarrow (N, M, E, \psi), \quad U \leftarrow N$
- 2: while there is an unallocated good do
- 3: Take $i_0 \in U$ (or $i_0 \in N$, if $U = \emptyset$) s.t. $|A_{i_0}|$ is minimal (break ties by σ)
- 4: Find an alternating path $p = (g_0, i_1, g_1, \dots, i_s, g_s)$ in G_{pref} such that g_s is unallocated and $\psi(i_0, g_0)$ is smallest possible
- 5: $A \leftarrow A$ updated along p
- $6: \quad A_{i_0} \leftarrow A_{i_0} \cup \{g_0\}$
- 7: $U \leftarrow \{i \in U : CHECKCRITERIA(i, A, U, F) = True\}$ (Algorithm 2)
- 8: end while
- 9: return A

Algorithm 2 Checking fairness criteria

Input: An agent i, a partial alloc. A, a set U, and criteria F

- if F = null then return True
 if F = EFX or F = EFX + MMS then
 U_e ← a strongly connected component with no incoming edge in G_{envy}(A, U) (if there is more than one, take the one with the earliest agent according to σ)
 if i ∈ U_e then return True
 end if
 if F = MMS or F = EFX + MMS then
 if s_i(A_i) ≤_{lex} MMS_i then return True
- 8: end if
- 9: return False

available good, g_0 . We update the allocation along alternating path from g_0 to an unallocated good (if g_0 is allocated), and give g_0 to i_0 .

Then, we update set U using subroutine CHECKCRITERIA (Algorithm 2) to give the priority to agents satisfying given criteria F. If F = EFX, in potential envy graph $G_{envy}(A, U)$ we look for a strongly connected component without an incoming edge and remove from U agents outside it. Intuitively, since there are no edges to the strongly connected component, no agent outside of Uwill ever start envying an agent in U at the later steps of the algorithm. If F = MMS, we remove from U agents that crossed their MMS thresholds. Finally, if F = EFX + MMS, we remove from Uagents satisfying both conditions simultaneously, and if F = null, we never remove agents from U. After m iterations, all goods are allocated and we output the final allocation.

Let us illustrate the most restrictive version of Algorithm 1, i.e., when F = EFX + MMS, with an example. We provide an analogous example for the other criteria in Appendix D. For each variable used in the algorithm, we will write it with superscript t, to denote its value at the end of t-th iteration of the main loop of our algorithm (lines 2–8). We use superscript 0 to denote the initial values of variables.

Example 1. Consider a goods-only instance with three agents, four goods, and the following preferences (see Figure <u>1a</u> for an illustration of the respective preference graph).

$$1: \quad \{g_1, \underline{g_2}\} \rhd \{g_3, g_4\}$$
$$2: \quad \underline{g_1} \rhd \{g_2, g_3, g_4\}$$
$$3: \quad g_1 \rhd \{g_2, \underline{g_3}, \underline{g_4}\}$$

Let $\sigma = (1, 2, 3)$. In iteration 1, agent 1 receives g_1 (see the red highlight in Figure 1a). Observe that



(a) G_{pref} with A^1 highlighted in red.





good g_1 is still available since there exists an alternating path $(g_1, 1, g_2)$ ending in an unallocated good. Thus, in iteration 2, agent 1 exchanges g_1 for g_2 and agent 2 receives g_1 . Then, in the potential envy graph at the end of iteration 2, i.e., $G_{envy}(A^2, U^1)$, agent 3 is the only agent that forms a strongly connected component with no incoming edge, U_e^2 (see Figure 1b). Moreover, since for each of agents 1 and 2, its bundle is above the respective MMS threshold, we remove them from U, thus $U^2 = \{3\}$. Therefore, agent 3 receives goods g_3 and g_4 . The final allocation is underlined.

We note that the algorithm of [Aziz et al., 2023a] returns the allocation $(\{g_2, g_4\}, \{g_1\}, \{g_3\})$ in the above example. Observe that in this allocation, agent 3 is envious of agent 1, which is not the case in the allocation returned by Algorithm 1. See Appendix C for a detailed discussion.

Let us now sketch the proof of correctness of our algorithm (the full proof can be found in Appendix B).

Theorem 3. Given a weakly lexicographic goods-only instance (N, M, \triangleright) , Algorithm 1 always returns

- (A) if criteria F = null, an EF1 and PO allocation;
- (B) if criteria F = EFX, an EFX and PO allocation;
- (C) if criteria F = MMS, an MMS and PO allocation; and
- (D) if criteria F = EFX + MMS, an EFX, MMS and PO allocation.

Proof (Sketch). We begin with the series of observations that hold for all considered by us criteria F (Claim 1 to 3) or only those with either EFX or MMS (Claim 4 to 6). Using them, we will prove the fairness guarantees in each of the statements (A)–(D). Finally, PO can be easily proved using Theorem 2. In this sketch we will mainly focus on showing statement (D).

We first prove several basic observations, which we group in the following two claims. Let X^t be a set of unavailable goods at the end of iteration t.

Claim 1. For every agent $i \in N$, its indifference classes $k, k' \in [k_i]$, and iterations $t, t' \in [m]$, such that k' < k and t' < t, it holds that

- (a) an unavailable good stays unavailable, i.e., $X^{t'} \subseteq X^t$,
- (b) agents weakly prefer their goods over the available ones, i.e., if $s_i(k, A_i^t) > 0$, then $\triangleright_i(k') \subseteq X^{t-1}$,

- (c) score of the bundle of an agent is (weakly) monotonic, i.e., $s_i(k, A_i^t) \ge s_i(k, A_i^{t'})$
- (d) if an agent has an unavailable good, then the whole indifference class with this good is unavailable, i.e., if $\triangleright_i(k, A_i^t) \cap X^t \neq \emptyset$, then $\triangleright_i(k) \subseteq X^t$.

Claim 2. For arbitrary iterations $t', t \in [m]$ and agents $i, j \in N$ such that t' < t, it holds that

- (a) no agent becomes prioritized again, i.e., $U^t \subseteq U^{t'}$,
- (b) the sizes of bundles of agents in U are as equal as possible, i.e., $0 \le |A_i^t| |A_j^t| \le 1$, if $i, j \in U^t$ and $\sigma(i) < \sigma(j)$, and
- (c) an agent cannot start envying an agent that did not receive more goods, i.e., if $A_j^{t'} \succeq_j A_i^{t'}$ and $|A_i^{t'}| = |A_i^t|$, then $A_i^t \succeq_j A_i^t$.
- (d) an agent never envies agents that are later in the ordering, i.e., if $\sigma(i) < \sigma(j)$, then $A_i^t \succeq_i A_j^t$.

Next, we prove a quite technical result that if an agent has only unavailable goods and potentially envies other agent, then the envied agent has at least the same amount of unavailable goods.

Claim 3. For every iteration $t \in [m]$ and agents $i, j \in N$ such that $A_i^t \subseteq X^t$, if *i* potentially envies *j*, but not actually envies, then $|A_i^t| \leq |A_i^t \cap X^t|$.

Next, we focus on the case where EFX is a part of criteria F and show that in such a case, the set U is never empty.

Claim 4. If criteria F = EFX or F = EFX + MMS, then for every $t \in [m]$ it holds that $U^t \neq \emptyset$.

Using this and Claim 3, we show one of the key observation of the proof that allows us to guarantee EFX: if an agent, j, envies another agent, i, with at most the same number of goods, then there is no potential envy path from i to j. In consequence, in such cases, i can be eliminated from U.

Claim 5. If criteria F = EFX or F = EFX + MMS, then for every agents $i, j \in N$, and iteration $t \in [m]$ such that j envies i and $|A_i^t| \leq |A_j^t|$, there is no path $p = (i_1, \ldots, i_r)$ in $G_{envy}(A^{t-1}, N)$ such that $i = i_1$ and $j = i_r$.

Next, we inductively show the key result for the proof of MMS. For this claim, for an agent *i*, let us denote set $\triangleright_i(1:k) = \triangleright_i(1) \cup \cdots \cup \triangleright_i(k)$ and vectors $s_i(1:k, A_i^t) = (s_i(1, A_i^t), \dots, s_i(k, A_i^t))$ and MMS_i(1: k) = (MMS_i(1), ..., MMS_i(k)).

Claim 6. If fairness criterion F = MMS or F = EFX + MMS, then for every iteration $t \in [m]$, agent $i \in N$, and $k \in \mathbb{N}$ such that $\triangleright_i(1:k) \subseteq X^t$, it holds that:

- (a) $s_i(1:k, A_i^t) \ge_{lex} \text{MMS}_i(1:k)$,
- (b) if $s_i(k', A_i^t) = 0$ for every k' > k and there is an agent $j \in U^t$ such that $|A_j^t| < |A_i^t|$, then $A_i^t >_{lex} \text{MMS}_i$,
- (c) if $s_i(1:k, A_i^t) = \text{MMS}_i(1:k)$, then there is a subset of agents $L \subseteq N \setminus U^t$ such that $|L| = n r_{k+1}$ and

$$\sum_{j \in L} |A_j^t| = \sum_{u=1}^k s_i(u) - r_{k+1} \cdot \sum_{u=1}^k \text{MMS}_i(u)$$

where, as in Proposition 1, $r_1 = n$ and $r_{u+1} = s_i(u) - \text{MMS}_i(u) \cdot r_u$, for every $u \in [k_i - 1]$.

Observe that point (a) of Claim 6 directly implies MMS of the output allocation as at the end of the algorithm all goods are unavailable. Thus, let us show that if F = EFX + MMS, then the output allocation satisfies EFX as well. Assume otherwise, and take first $t \in [m]$ such that there exist $i, j \in N$ and $g \in A_i$ for which $A_i \setminus \{g\} \succ_j A_j$.

From Claim 2d we know that *i* is before *j* in ordering σ . Let us take the last iteration t' < t in which *i* had smaller number of goods, i.e., $|A_i^{t'}| < |A_i^t|$. By Claim 4, this means that $i \in U^{t'}$ and from Claim 1c we get that $|A_i^{t'}| = |A_j^{t'}|$. Based on this, using Claim 5, we deduce that *j* does not envy *i* at the end of iteration *t'* (otherwise it could not be that $i \in U^t$). Since between iteration *t'* and *t* agent *i* receives just one more good, we can show that this implies that *i* and *j* do not violate EFX in iteration *t*—a contradiction.

5 Chores

In many aspects, the situation for chores is more complex than that of goods. For example, we can decide if there exists an EF allocation for goods-only strict lexicographic instances in polynomial time, but the same problem is NP-complete for chores [Hosseini et al., 2022b]. For additive preferences, even the existence of an EF1 and PO allocation remains an open problem for the chores case.

In this section, we will show that Algorithm 1 can be adapted so that we obtain an EF1 and PO allocation for every weakly lexicographic chores-only instance. However, let us first discuss the differences and challenges of finding EFX allocations for chores in comparison with goods. We believe that this sheds some light on the nature of the general problem of dividing the chores.

5.1 EFX implies MMS

Let us start by noting that EFX implies MMS for weakly lexicographic instances, which is not the case for goods (see Appendix E). To this end, we first provide a compact formulation of an agent's MMS threshold analogous to the ones for goods in Proposition 1.

Proposition 2. For every weakly lexicographic chores-only instance (N, M, \triangleright) and agent $i \in N$, it holds that

$$\text{MMS}_i = (s_i(1)/n, s_i(2)/n, \dots, |s_i(k)/n|, 0, \dots, 0),$$

where k is the number of the first indifference class of i such that n does not divide $s_i(k)$. Note that since $s_i(k)$ is negative, the absolute value of $\lfloor s_i(k)/n \rfloor$ is the number of chores in the k-th indifference class of i divided by n and rounded up.

Using it let us show that EFX implies MMS.

Proposition 3. Given a weakly lexicographic chores-only instance (N, M, \triangleright) , every EFX allocation satisfies MMS.

Proof. Assume for a contradiction that there is an allocation A that is EFX but not MMS, i.e., there is agent $i \in N$ such that its $s_i(A_i) <_{lex} MMS_i$.

From Proposition 2 we know that

$$MMS_i = (s_i(1)/n, s_i(2)/n, \dots, |s_i(k)/n|, 0, \dots, 0),$$

where k is the number of the first indifference class of i such that n does not divide $s_i(k)$.

Given that for agent i, $s_i(A_i) <_{lex} \text{MMS}_i$, it is not possible to have that $s_i(A_j) \leq_{lex} \text{MMS}_i$, for every agent $j \in N \setminus \{i\}$ (otherwise, from one of the first k indifference classes of agent i, there would be more chores assigned to agents than there are in total). Hence, there exists $j \in N$ such that $s_i(A_j) >_{lex} \text{MMS}_i$. Let \bar{k} be an indifference class such that $s_i(\bar{k}, A_i) < \text{MMS}_i(\bar{k})$, and $c \in \triangleright_i(\bar{k}, A_i)$ be an arbitrary chore assigned to i from this class. Observe that $s_i(A_i \setminus \{c\}) \leq_{lex} \text{MMS}_i <_{lex} s_i(A_j)$. Hence, agent i envies agent j even after the removal of chore c from its bundle. This contradicts EFX.

Despite the fact that an EFX allocation implies MMS, we note that there is no implication from MMS (with or without PO) to EFX for chores-only instances even when each agent has at most two indifference classes (see Example 9 in Appendix E).

5.2 EFX and PO Challenges

Given a chores-only instance, a straightforward approach to obtain an EFX and PO allocation would be to directly copy the idea behind Algorithm 1: assign to agents their most preferred available items (using the alternating paths) in rounds, removing certain agents from the set of prioritized agents U on the way, to guarantee EFX. In the goods-only case, the agents start picking the items from their first indifference classes, which works well, as the same items are key to establishing envy relations. However, in the chores case, the order is reversed: the agents start picking the items from the last indifference classes, but still the envy relations depend predominantly on the first indifference classes. Hence, an initial fair allocation of chores in the last indifference classes, may turn out to be impossible to extend to an EFX allocation.

Example 2. Consider a chores-only instance with two agents, three chores and preferences as follows:

$$1: \quad c_1 \triangleright \{c_2, \underline{c_3}\}$$
$$2: \quad c_1 \triangleright \{\underline{c_2}, \underline{c_3}\}$$

If we allow agents to choose their chores, agent 1 can pick chore c_3 in iteration 1 and agent 2 chore c_2 in iteration 2. Observe that the resulting partial allocation is EFX (indeed, EF). However, if we assign c_1 to either of the agents, then the recipient would envy the other agent, and the envy will not be eliminated by the removal of the other chore. Hence, this allocation cannot be extended to an EFX allocation.

Given the above observation, another strategy would be to start assigning chores to the agents from their first indifference classes (worst chores). On the other hand, for the sake of PO, we need to allow agents to exchange the chores among themselves if it is beneficial for all sides. However, such exchanges can lead to a situation similar to that in Example 2.

Example 3. Consider a chores-only instance with four agents, five chores and preferences as follows:

 $\begin{array}{ll} 1: & \{c_1, c_2\} \rhd c_3 \rhd \{\underline{c_4}, c_5\} \\ 2: & \{c_1, c_2\} \rhd c_3 \rhd \{c_4, \underline{c_5}\} \\ 3: & \{c_4, c_5\} \rhd c_3 \rhd \{\underline{c_1}, c_2\} \\ 4: & \{c_4, c_5\} \rhd c_3 \rhd \{c_1, \underline{c_2}\} \end{array}$

Assume we start allocating chores from the first indifference classes of the agents: agent 1 receives chore c_1 , agent 2 chore c_2 , agent 3 c_4 and 4 c_5 .

Algorithm 3 Finding an EF1 and PO allocation of chores

Input: A weakly lexicographic chores-only instance $\langle N, M, \rhd \rangle$ and the ordering σ

Output: An EF1 and PO allocation *A*

- 1: $A \leftarrow (\emptyset, \dots, \emptyset), \quad G_{pref} \leftarrow (N, M, E, \psi)$
- 2: while there is an unallocated chore **do**
- 3: Take $i_0 \in N$ s.t. $|A_{i_0}|$ is minimal (break ties by σ)
- 4: Find an alternating path $p = (c_0, i_1, c_1, \dots, i_s, c_s)$ in G_{pref} such that c_s is unallocated and $\psi(i_0, c_0)$ is largest possible
- 5: $A \leftarrow A$ updated along p,
- $6: \quad A_{i_0} \leftarrow A_{i_0} \cup \{c_0\}$
- 7: end while
- 8: return A

Such partial allocation is not PO, thus agents have to exchange their chores.

As a result, each agent has one chore from its last indifference class. Such partial allocation is EFX and PO, and in fact it is the only EFX and PO allocation of this subset of chores (up to relabeling of the agents). However, assigning chore c_3 to any one agent will result in an allocation that violates EFX.

Finally, we note that we can overcome the above problems and find an EFX and PO allocation when we deal with two agents only. Indeed, Gafni et al. [2021] have shown that for each choresonly instance we can construct an equivalent goods-only instance with n - 1 goods for each chore of the original instance (the goods can be interpreted as "not doing a chore"). Then, each EFX and PO allocation in the chores-only instance correspond to an EFX and PO allocation in the goods-only instance, and vice-versa, assuming that no agent receives two goods that come from the same chore. For two agents, this condition is always satisfied, thus whenever we have an algorithm guaranteeing EFX and PO for goods (and here we have Algorithm 1), we have one for chores as well.

Remark 1. Given a weakly lexicographic chores-only instance (N, M, \triangleright) with two agents, we can always find an EFX and PO allocation in polynomial time.

5.3 EF1 and PO

In this section, we show that despite the challenges in obtaining EFX and PO shown in Examples 2 and 3, if we relax EFX to EF1, then we can always find an EF1 and PO allocation.

To this end, we need to adapt the definitions from Section 4 to chores-only setting. Most of them are symmetrically applicable. To point out the only difference, we explicitly define alternating paths for chores. Given a preference graph $G_{pref} = (N, M, E, \psi)$ and an (possibly partial) allocation A, an *alternating path*, $p = (c_0, i_1, c_1, \ldots, i_s, c_s)$, is a path in G_{pref} (possibly of length zero) such that

- the chores in *p* are pairwise distinct,
- p alternates between edges that belong and do not belong to A, i.e., $(c_{r-1}, i_r) \in A$, for every $r \in [s]$, and $(i_r, c_r) \notin A$, for every $r \in [s]$, and
- for every r ∈ [s], agent i_r weakly prefers chore c_r over c_{r-1}, i.e., ψ(c_{r-1}, i_r) ≤ ψ(i_r, c_r). Note that since items are chores, an agent prefers its higher indifference class, which is the difference with the goods.

The Algorithm. Algorithm 3 proceeds similarly to Algorithm 1 with criteria F = null. Fix an ordering of agents, σ . We initialize the algorithm with the empty allocation. Then, in each iteration of the main loop (lines 2–7), we take an agent *i* that has the least number of chores (the earliest in σ if there is a ties). Next, agent *i* chooses the most preferred (i.e., least important) available chore, c_0 . We update the allocation along alternating path from c_0 to an unallocated chore (if c_0 is allocated), and assign c_0 to *i*. After *m* iterations of the main loop, all chores are allocated and we return the final allocation.

We illustrate Algorithm 3 in the following example.

Example 4. Consider a chores-only instance with three agents, four chores and preferences as follows:

$$1: \quad \underline{c_1} \triangleright \{\underline{c_2}, c_3, c_4\} \\ 2: \quad \{c_1, c_2, c_3\} \triangleright \underline{c_4} \\ 3: \quad \{c_1, c_2\} \triangleright \{\underline{c_3}, c_4\}$$

Let $\sigma = (1, 2, 3)$. In iteration 1, agent 1 receives c_4 . However, c_4 is still available, so in iteration 2, agent 2 gets c_4 , while agent 1 exchanges c_4 for c_3 in an alternating path.

Next, agent 3 receives c_3 and we update the allocation along the alternating path, $p = (c_3, 1, c_2)$. Finally, agent 1 gets c_1 .

The proof of correctness of Algorithm 3 is similar to the proof of Theorem 3A and is relegated to Appendix F.

Theorem 4. Given a weakly lexicographic chores-only instance (N, M, \triangleright) , Algorithm 3 always returns an EF1 and PO allocation.

6 Concluding Remarks

We showed that when dealing with goods allowing agents to express indifferences immediately results in computational hardness for deciding the existence of an EF allocation. Yet, we developed an algorithm that always finds an EFX, MMS, and PO allocation in polynomial time; and more importantly, our algorithm is versatile as it enables a social planner to select a set of desired fairness criteria. An intriguing future direction is investigating whether our positive results can be extended beyond weak lexicographic orderings, possibly to allow for more complex (e.g. combinatorial) preferences.

We illustrated the challenges in dealing with chores when agents have weakly lexicographic preferences. While in this setting EFX implies MMS for chores—in contrast to the goods-only case—finding an algorithm for achieving EFX allocations (with or without PO) remains an interesting open problem. Nonetheless, we developed an algorithm for finding an EF1 and PO allocation in this domain.

Acknowledgments

Hadi Hosseini acknowledges support from NSF IIS grants #2144413 (CAREER) and #2107173. We thank the anonymous reviewers for their helpful comments.

References

- Georgios Amanatidis, Georgios Birmpas, Aris Filos-Ratsikas, Alexandros Hollender, and Alexandros A Voudouris. Maximum Nash welfare and other stories about EFX. *Theoretical Computer Science*, 863:69–85, 2021.
- Haris Aziz and Bart De Keijzer. Housing markets with indifferences: A tale of two mechanisms. In *Proceedings of the 26th AAAI conference on Artificial Intelligence*, pages 1249–1255, 2012.
- Haris Aziz, Serge Gaspers, Simon Mackenzie, and Toby Walsh. Fair assignment of indivisible objects under ordinal preferences. *Artificial Intelligence*, 227:71–92, 2015.
- Haris Aziz, Gerhard Rauchecker, Guido Schryen, and Toby Walsh. Algorithms for max-min share fair allocation of indivisible chores. In *Proceedings of the 31st AAAI Conference on Artificial Intelligence*, pages 335–341, 2017.
- Haris Aziz, Péter Biró, Jérôme Lang, Julien Lesca, and Jérôme Monnot. Efficient reallocation under additive and responsive preferences. *Theoretical Computer Science*, 790:1–15, oct 2019. doi: 10.1016/j.tcs.2019.05.011.
- Haris Aziz, Ioannis Caragiannis, Ayumi Igarashi, and Toby Walsh. Fair allocation of indivisible goods and chores. *Autonomous Agents and Multi-Agent Systems*, 36(1):1–21, 2022.
- Haris Aziz, Bo Li, Shiji Xing, and Yu Zhou. Possible fairness for allocating indivisible resources. In *Proceedings of the 22nd International Conference on Autonomous Agents and Multiagent Systems*, pages 197–205, 2023a.
- Haris Aziz, Jeremy Lindsay, Angus Ritossa, and Mashbat Suzuki. Fair allocation of two types of chores. In *Proceedings of the 22nd International Conference on Autonomous Agents and Multiagent Systems*, pages 143–151, 2023b.
- Moshe Babaioff, Noam Nisan, and Inbal Talgam-Cohen. Fair allocation through competitive equilibrium from generic incomes. In *Proceedings of the 2nd ACM Conference on Fairness, Accountability and Transparency*, pages 180–180, 2019.
- Moshe Babaioff, Tomer Ezra, and Uriel Feige. Fair and truthful mechanisms for dichotomous valuations. In *Proceedings of the 35th AAAI Conference on Artificial Intelligence*, volume 35, pages 5119–5126, 2021.
- Siddharth Barman, Sanath Kumar Krishnamurthy, and Rohit Vaish. Finding fair and efficient allocations. In *Proceedings of the 19th ACM Conference on Economics and Computation*, pages 557–574, 2018.
- Umang Bhaskar, AR Sricharan, and Rohit Vaish. On approximate envy-freeness for indivisible chores and mixed resources. *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques*, 2021.
- Anna Bogomolnaia, Rajat Deb, and Lars Ehlers. Strategy-proof assignment on the full preference domain. *Journal of Economic Theory*, 123(2):161–186, 2005.
- Eric Budish. The combinatorial assignment problem: Approximate competitive equilibrium from equal incomes. *Journal of Political Economy*, 119(6):1061–1103, 2011.

- Franklin Camacho, Rigoberto Fonseca-Delgado, Ramón Pino Pérez, and Guido Tapia. Generalized binary utility functions and fair allocations. *Mathematical Social Sciences*, 121:50–60, 2023.
- Ioannis Caragiannis, David Kurokawa, Hervé Moulin, Ariel D Procaccia, Nisarg Shah, and Junxing Wang. The unreasonable fairness of maximum Nash welfare. *ACM Transactions on Economics and Computation (TEAC)*, 7(3):1–32, 2019.
- Soroush Ebadian, Dominik Peters, and Nisarg Shah. How to fairly allocate easy and difficult chores. In *Proceedings of the 21st International Conference on Autonomous Agents and MultiAgent Systems*, pages 372–380, 2022.
- Peter C Fishburn. Lexicographic orders, utilities and decision rules: A survey. *Management science*, 20(11):1442–1471, 1974.
- Etsushi Fujita, Julien Lesca, Akihisa Sonoda, Taiki Todo, and Makoto Yokoo. A complexity approach for core-selecting exchange under conditionally lexicographic preferences. *Journal of Artificial Intelligence Research*, 63:515–555, 2018.
- Hanna Furmańczyk, K Kaliraj, Marek Kubale, and J Vernold Vivin. Equitable coloring of corona products of graphs. *Advances and Applications of Discrete Mathematics*, 11:103–120, 2013.
- Yotam Gafni, Xin Huang, Ron Lavi, and Inbal Talgam-Cohen. Unified fair allocation of goods and chores via copies. *arXiv preprint arXiv:2109.08671*, 2021.
- Jugal Garg and Aniket Murhekar. Computing fair and efficient allocations with few utility values. In *Proceedings of the 14th International Symposium on Algorithmic Game Theory*, pages 345–359. Springer, 2021.
- Jugal Garg and Setareh Taki. An improved approximation algorithm for maximin shares. *Artificial Intelligence*, 300:103547, 2021.
- Jugal Garg, Aniket Murhekar, and John Qin. Fair and efficient allocations of chores under bivalued preferences. *Proceedings of 36th the AAAI Conference on Artificial Intelligence*, pages 5043–5050, 2022.
- Naveen Garg, Telikepalli Kavitha, Amit Kumar, Kurt Mehlhorn, and Julián Mestre. Assigning papers to referees. *Algorithmica*, 58:119–136, 2010.
- Michael R Gary and David S Johnson. Computers and intractability: A guide to the theory of NP-completeness, 1979.
- Mohammad Ghodsi, Mohammad Taghi Hajiaghayi, Masoud Seddighin, Saeed Seddighin, and Hadi Yami. Fair allocation of indivisible goods: Improvement. *Mathematics of Operations Research*, 46 (3):1038–1053, 2021.
- Gerd Gigerenzer and Daniel G Goldstein. Reasoning the fast and frugal way: models of bounded rationality. *Psychological review*, 103(4):650, 1996.
- Hadi Hosseini and Kate Larson. Multiple Assignment Problems under Lexicographic Preferences. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, pages 837–845, 2019.

- Hadi Hosseini, Sujoy Sikdar, Rohit Vaish, Hejun Wang, and Lirong Xia. Fair division through information withholding. In *Proceedings of the 34th AAAI Conference on Artificial Intelligence*, pages 2014–2021, 2020.
- Hadi Hosseini, Sujoy Sikdar, Rohit Vaish, and Lirong Xia. Fair and efficient allocations under lexicographic preferences. In *Proceedings of the 35th AAAI Conference on Artificial Intelligence*, pages 5472–5480, 2021.
- Hadi Hosseini, Andrew Searns, and Erel Segal-Halevi. Ordinal maximin share approximation for goods. *Journal of Artificial Intelligence Research*, 74:353–391, 2022a.
- Hadi Hosseini, Sujoy Sikdar, Rohit Vaish, and Lirong Xia. Fairly dividing mixtures of goods and chores under lexicographic preferences. In *Proceedings of the 22nd International Conference on Autonomous Agents and MultiAgent Systems*, 2022b.
- Hadi Hosseini, Aghaheybat Mammadov, and Tomasz Wąs. Fairly allocating goods and (terrible) chores. In *Proceedings of the 32nd International Joint Conference on Artificial Intelligence*, pages 2738–2746, 2023.
- Paula Jaramillo and Vikram Manjunath. The difference indifference makes in strategy-proof allocation of objects. *Journal of Economic Theory*, 147(5):1913–1946, 2012.
- Akshay-Kumar Katta and Jay Sethuraman. A solution to the random assignment problem on the full preference domain. *Journal of Economic Theory*, 131(1):231–250, 2006.
- Bettina Klaus and Claudia Meo. The core for housing markets with limited externalities. *Economic Theory*, pages 1–33, 2023.
- Piotr Krysta, David Manlove, Baharak Rastegari, and Jinshan Zhang. Size versus truthfulness in the house allocation problem. In *Proceedings of the 15th ACM conference on Economics and Computation*, pages 453–470, 2014.
- David Kurokawa, Ariel D Procaccia, and Junxing Wang. Fair enough: Guaranteeing approximate maximin shares. *Journal of the ACM (JACM)*, 65(2):1–27, 2018.
- Jérôme Lang, Jérôme Mengin, and Lirong Xia. Voting on multi-issue domains with conditionally lexicographic preferences. *Artificial Intelligence*, 265:18–44, 2018.
- Bo Li, Yingkai Li, and Xiaowei Wu. Almost (weighted) proportional allocations for indivisible chores. In *Proceedings of the ACM Web Conference 2022*, pages 122–131, 2022.
- Richard J Lipton, Evangelos Markakis, Elchanan Mossel, and Amin Saberi. On approximately fair allocations of indivisible goods. In *Proceedings of the 5th ACM Conference on Electronic Commerce*, pages 125–131, 2004.
- Trung Thanh Nguyen. How to fairly allocate indivisible resources among agents having lexicographic subadditive utilities. In *Frontiers in Intelligent Computing: Theory and Applications*, pages 156–166. Springer, 2020.
- Benjamin Plaut and Tim Roughgarden. Almost envy-freeness with general valuations. *SIAM Journal on Discrete Mathematics*, 34(2):1039–1068, 2020.

- Daniela Saban and Jay Sethuraman. House allocation with indifferences: a generalization and a unified view. In *Proceedings of the 14th ACM conference on Electronic Commerce*, pages 803–820, 2013.
- Daniela Saban and Jay Sethuraman. A note on object allocation under lexicographic preferences. *Journal of Mathematical Economics*, 50:283–289, 2014.

Appendix

A Envy-Freeness for Goods

Theorem 1. Deciding whether an EF allocation exists for a given weakly lexicographic goods-only instance is NP-complete, even if every agent has at most two indifference classes.

Proof. Observe that given an allocation, we can check if it is EF in polynomial time. Thus, our problem is in NP. Hence, let us focus on showing the hardness of our problem.

We prove the hardness by a reduction from EQUITABLE COLORING (EC). The EC problem is defined as follows. For a fixed constant $l \in \mathbb{N}$, given a graph G, the task is to determine if there exists a proper l-coloring, i.e., an assignment of l colors to the vertices of the graph such that no two adjacent vertices are of the same color, with the property that the numbers of vertices in any two color classes differ by at most one. We further extend the EC problem by requiring that each color class has the same number of vertices. This problem is known to be NP-complete by a reduction from GRAPH k-COLORABILITY Gary and Johnson [1979], Hosseini et al. [2020]. Let G = (V, E), where |V| = n and |E| = m.¹ We assume that $l \ge 3$ and that in the graph G each vertex has a degree of at least two. Since EC was shown to be NP-hard for much more restricted classes of graphs Furmańczyk et al. [2013], we still retain NP-hardness in this more general version of the problem. The assumption that each vertex has at least two incident edges, implies that there are at least that many edges as vertices, i.e.,

$$m \ge n. \tag{2}$$

Finally, since for small number of vertices and fixed l the problem can be solved in polynomial time by a brute-force algorithm, without loss of generality, we assume that the number of vertices is at least three times greater than the number of colors, i.e., $n \ge 3l$.

For an EC instance, a graph G = (V, E), we construct its corresponding weakly lexicographic instance $\langle N, M, \rhd \rangle$. To this end, we take m + l agents, i.e., one agent, a_e , for each edge $e \in E$ and one agent, a_r , for each color $r \in [l]$. Furthermore, we take 2m + n goods, where we have two goods, e and e', for every edge $e \in E$ and one good, v, for every vertex $v \in V$. Thus, the set of goods is given by $M = E \cup E' \cup V$, where $E' = \{e' : e \in E\}$. Finally, the preferences are such that each agent has two indifference classes. More precisely, each edge agent a_e has all the edge goods and vertex goods which are incident to the edge e in the first indifference class and the rest of the goods in the second one. Meanwhile, each color agent a_r has all the vertex goods in the first indifference class, while all the edge goods are in the second class. Formally,

$$a_e: (E \cup E' \cup \{v, v'\}) \triangleright (V \setminus \{v, v'\}), \text{ for every } e = (v, v') \in E, \text{ and}$$

 $a_r: V \triangleright (E \cup E'), \text{ for every } r \in [l].$

In what follows, we will show that there exists an equitable l-coloring of G if and only if there is an EF allocation A in the corresponding allocation instance.

First, assume that the graph G admits an equitable l-coloring. Consider an allocation A such that for every $e \in E$, edge agent a_e receives two edge goods e and e', and for every $r \in [l]$, color agent a_r receives all vertex goods of color r. Since all the edge agents receive exactly two goods which are from their first indifference classes, there is no envy among them. Moreover, for every e = (v, v'), the edge agent a_e envies none of the color agents as due to the proper coloring of G, the vertex goods v and v', which are in the first indifference class of the agent a_e , are not allocated to

¹To maintain consistency with the standard graph notation, it should be noted that in this context, the variables n and m do not represent the number of agents and the number of goods as in the rest of the paper.

the same color agent. Each color class is of the same size and therefore, each color agent receives the same number of goods. Thus, there is no envy among the color agents. Each color agent envies none of the edge agents given that each color agent gets at least 3 vertex goods (by the assumption that $n \ge 3l$) and has all the edge goods in its second indifference set. Hence, the allocation A is EF.

Conversely, assume that there is an EF allocation denoted by A. We will show that this implies the existence of a proper *l*-coloring for the graph G. In order to establish this, we will prove a series of Claims 1 - 10 that pertain to the properties of the allocation A.

Claim 1. For each $e \in E$, edge agent a_e receives at most two edge goods under A.

Proof. Suppose, for a contradiction, that there is some edge agent a_e who receives three or more edge goods. For every edge agent, all the edge goods are in its first indifference class. Thus, all the edge agents should receive at least three or more goods that are in their first indifference classes (as otherwise they will envy a_e). Therefore, there should be at least 3m goods to be allocated among the edge agents. By Equation 2, the number of goods in the instance, 2m + n, is bounded by 3m. This implies that after allocating at least 3m goods to the edge agents, no good will be allocated to the color agents. Thus, the color agents will surely be envious—a contradiction.

Claim 2. For every $r \in [l]$, color agent a_r receives at least one vertex good under A.

Proof. Suppose, for a contradiction, that there is some color agent a_r who does not receive any vertex good. Since its first indifference class consists exactly of all vertex goods, it envies an agent that receives some vertex good—a contradiction.

Claim 3. For every $r \in [l]$, color agent a_r receives at most one edge good under A.

Proof. Suppose, for a contradiction, that there is some color agent a_r who receives two or more edge goods. By Claim 2, this agent also receives some vertex good v_0 . By the assumption that the graph G has minimum degree two, there exists some edge $e_0 = (v_0, v_1)$ incident to the vertex v_0 and also a cycle that contains e_0 , i.e., (e_0, e_1, \ldots, e_z) , in which $e_k = (v_k, v_{k+1})$ and $v_{z+1} = v_0$. Since the agent a_r receives three goods from the first indifference class of a_{e_0} , the latter agent has to receive three such goods as well. Thus, by Claim 1, two edge goods and the vertex good v_1 must be assigned to the agent a_{e_0} . Similarly, the agent a_{e_1} views the bundle of a_{e_0} as having the score vector of at least (3,0). Hence, it has to receive two edge goods and the vertex good v_2 . Continuing this way, we can show by induction that agent a_{e_k} for every $k \in [z]$ is given two edge goods and vertex goods and vertex good $v_{z+1} = v_0$ this leads to a contradiction.

Claim 4. There exists some $e \in E$ such that edge agent a_e receives two edge goods under A.

Proof. Observe that if none of the color agents receives an edge good, then by a pigeonhole principle some edge agent has to receive at least two edge goods. Therefore, let us assume that there is some color agent a_r who receives an edge good (by Claim 3, it can receive at most one edge good).

Suppose, for a contradiction, that none of the edge agents receive more than one edge good. By Claim 2, gent a_r also receives some vertex good v_0 . Now, consider a similar construction as in the proof of Claim 3. Take a cycle (e_0, e_1, \ldots, e_z) such that $e_k = (v_k, v_{k+1})$ and $v_{z+1} = v_0$. Since the agent a_{e_0} views the bundle of a_r as having the score vector of at least (2, 0), it must receive two goods from its first indifference class. Given that the agent a_{e_0} does not receive two edge goods (by the assumption), it has to receive the vertex good v_1 together with one edge good. Continuing this way, we can show by induction that agent a_{e_k} for every $k \in [z]$ is given one edge good and vertex good v_{k+1} . However, since $v_{z+1} = v_0$ this leads to a contradiction. **Claim 5.** For every $e \in E$, if edge agent a_e has two edge goods, then it does not receive a vertex good under A.

Proof. Suppose, for a contradiction, that there is some edge agent a_e who receives two edge goods and a vertex good. Then, every other edge agent views the bundle of the edge agent a_e as having the score vector of at least (2,1). Therefore, to guarantee envy-freeness of A, every other edge agent should receive at least three goods. Thus, at least 3m goods should be allocated among the edge agents. Then, there will be at most one good to be allocated to the color agents, which contradicts Claim 2.

Claim 6. For each $e \in E$, edge agent a_e receives exactly two goods under A.

Proof. Observe that if none of the color agents receives an edge good, then each edge agent has to receive two edge goods (and nothing more) by Claims 1 and 5. Therefore, let us assume that there is some color agent a_r who receives an edge good.

By Claim 4, there is at least one edge agent who receives two edge goods. Therefore, all edge agents should receive at least two goods. Suppose now, for a contradiction, that there is some edge agent $a_{\bar{e}}$ who receives more than two goods. By Claim 1, the edge agent $a_{\bar{e}}$ must receive at least one vertex good. Moreover, by Claim 5, this agent can not get two edge goods. Therefore, $a_{\bar{e}}$ receives at least two vertex goods.

Since all vertex goods are in the first indifference set of the agent a_r , it should receive at least two vertex goods as well. Let us denote one of these vertex goods by v_0 . Once again, consider a similar construction to those in the proofs of Claims 3 and 4. Take a cycle (e_0, e_1, \ldots, e_z) such that $e_k = (v_k, v_{k+1})$ and $v_{z+1} = v_0$. Since the agent a_{e_0} views the bundle of a_r as having the score vector of at least (2, 1), it must receive two goods from its first indifference class and one good from its second class. By Claim 5, the agent a_{e_0} has to receive one edge good and two vertex goods one of which is the vertex good v_1 . Continuing this way, we can show by induction that agent a_{e_k} for every $k \in [z]$ is given one edge good and two vertex goods one of which is vertex good v_{k+1} . However, since $v_{z+1} = v_0$ this leads to a contradiction.

Claim 7. There exists some $r \in [l]$, the color agent a_r receives at least $\frac{n}{l}$ goods under A.

Proof. The total number of goods in the instance is 2m + n. By Claim 6, edge agents receive 2m goods in total. Therefore, one of the color agents must receive at least $\frac{n}{l}$ goods from the pigeonhole principle.

Claim 8. For each $e \in E$, edge agent a_e receives exactly two edge goods and no vertex good under A.

Proof. Observe that if none of the color agents receives an edge good, then each edge agent should receive exactly two edge goods and nothing more by Claims 1 and 5. Therefore, assume now that there is some color agent a_r who receives at least one edge good.

By Claim 2, the agent a_r also receives vertex good v. By the assumption that the graph G has minimum degree two, there is an edge e = (v, v') which is incident to the vertex v. The agent a_e views the bundle of the agent a_r as having the score vector (2, 0) or better. Since the edge agent a_e receives exactly two goods (by Claim 6), the color agent a_r cannot receive any other good (otherwise, the agent a_e will envy the agent a_r). Thus, the color agent a_r also receives exactly two goods – one edge good and the vertex good v. By Claim 7, there is some color agent $a_{r'}$ who receives at least $\frac{n}{l}$ goods, which is at least 3 goods by the assumption that $n \ge 3l$. Since the agent $a_{r'}$ also receives one or more vertex goods (by Claim 2), the agent a_r views the bundle of the agent $a_{r'}$ as having the score vector (1,2) or better. Thus, the agent a_r will be envious of the agent $a_{r'}$ —a contradiction.

Claim 9. For each $r \in [l]$, color agent a_r receives exactly $\frac{n}{l}$ vertex goods and no edge good under A.

Proof. From Claim 8 all edge goods are distributed among edge agents, and all vertex goods are distributed among color agents. Since there is no envy among color agents and they have identical preferences, every color agent must receive exactly the same number of vertex goods, i.e., $\frac{n}{T}$.

Claim 10. For every $e \in E$ with e = (v, v'), there is no $r \in [l]$ such that the color agent a_r receives both the vertex goods v and v' under A.

Proof. Suppose, for a contradiction, that there is some color agent a_r who receives both of the vertex goods v and v' for some edge e = (v, v'). By Claim 8, edge agent a_e has two edge goods and nothing more. However, by Claim 9, agent r has $\frac{n}{l}$ goods, which by our initial assumptions that $n \ge 3l$ is at least 3. Since both v and v' are in the first indifference class of e that makes agent a_e envy agent a_r , which is a contradiction.

To conclude the proof, observe that we can identify the color of each vertex with the color agent that received the corresponding vertex good. By Claim 10 such coloring will be proper and by Claim 9 it will be equitable as well. \Box

Observe that the EF allocation constructed in the proof for the NP-completeness of the EFexistence problem satisfies PO as well. This is because every good is assigned to an agent who has it in its first indifference set. As a result, the problem of determining whether an EF and PO allocation is also NP-complete.

Corollary 1. Deciding whether an EF and PO allocation exists for a given weakly lexicographic goodsonly instance is NP-complete.

B Correctness of Algorithm 1

Theorem 3. Given a weakly lexicographic goods-only instance (N, M, \triangleright) , Algorithm 1 always returns

- (A) if criteria F = null, an EF1 and PO allocation;
- (B) if criteria F = EFX, an EFX and PO allocation;
- (C) if criteria F = MMS, an MMS and PO allocation; and
- (D) if criteria F = EFX + MMS, an EFX, MMS and PO allocation.

Proof. Throughout the proof, we will use t to denote the number of an iteration of the main loop (lines 2–8), and each variable used in the algorithm with superscript t, e.g., A^t or U^t , will denote the value of this variable at the end of iteration t. For convenience, by A^0 or U^0 , etc., we denote the initial values of these variables.

We start the proof by showing that Algorithm 1 is well defined and always returns a complete allocation for all statements (A), (B), (C) and (D) of Theorem 3. To this end, observe that in each iteration of the main loop (lines 2–8), we take one still unallocated good, g_s , and assign it to one of the agents identified by Algorithm 2 (possibly, changing the assignments of some of the already allocated goods on the way). Hence, after *m* iterations of the main loop, we allocate all items.

The remainder of the proof is organized into the three main parts as follows:

- 1. First, we will prove several basic properties regarding the concepts and notions used in the proof, which hold for all considered criteria F (Claim 1 to 3).
- 2. Next we will show several results that make some assumptions on the criteria we consider (Claim 4 to 6).
- 3. Then, for each statement, we will provide a separate proof for the fairness of the output allocation: EF1 for (A), EFX for (B), MMS for (C), and EFX and MMS for (D).
- 4. Finally, we will prove PO of the output allocation once for all statements.

Part 1: Basic common properties.

By X^t let us denote the set of all *unavailable* goods in iteration t, i.e., goods from which there is no alternating path to an unallocated good in G_{pref} . Let us prove the basic properties regarding unavailable goods and score vectors of agents.

Claim 1. For every agent $i \in N$, its indifference classes $k, k' \in [k_i]$, and iterations $t, t' \in [m]$, such that k' < k and t' < t, it holds that

- (a) an unavailable good stays unavailable, i.e., $X^{t'} \subseteq X^t$,
- (b) agents weakly prefer their goods over the available ones, i.e., if $s_i(k, A_i^t) > 0$, then $\triangleright_i(k') \subseteq X^{t-1}$,
- (c) the score of the own bundle of an agent is (weakly) monotonic, i.e., $s_i(k, A_i^t) \ge s_i(k, A_i^{t'})$,
- (d) if an agent has an unavailable good, then the whole indifference class with this good is unavailable, i.e., if $\triangleright_i(k, A_i^t) \cap X^t \neq \emptyset$, then $\triangleright_i(k) \subseteq X^t$.

Proof. For (*a*), we will show that for every good $g \in M$, if $g \in X^t$, then $g \in X^{t+1}$, which will imply the thesis by induction. If $g \in X^t$, then, for allocation A^t , there is no alternating path in G_{pref} that starts in g and ends in an unallocated good. Hence, the same is true for every good g', for which there exists an alternating path that starts in g and ends in g'. This means that in the next iteration, the allocation of every such good g' as well as good g has to remain the same (only the available goods can change ownership in lines 5 and 6 of the algorithm). Thus, again, for allocation A^{t+1} , there is no alternating path in G_{pref} starting in g and ending in an unallocated good. Thus, $g \in X^{t+1}$.

For (b), assume by contradiction that there exists an available good that is strictly preferred by agent *i* over one of its owned goods, i.e., there exist $g \in M \setminus X^{t-1}$ and $g' \in A_i^t$ such that $g \succ_i g'$. Let *k* be an indifference class of good g', i.e., $g' \in \triangleright_i(k)$, and *t'* be the first iteration in which $s_i(k', A_i^{t'}) > 0$ for some $k' \ge k$. Since by an exchange in an alternating path each agent always weakly prefers its new goods over the old ones, this means that in iteration *t'* agent *i* was chosen in line 3 of the algorithm and received a new good, $g'' \in \triangleright_i(k')$, in line 5. Observe also that $t' \le t$, which means, by (*a*), that *g* was available at the end of iteration t'-1. However, since $g \succ_i g' \succeq_i g''$, agent *i* should receive good *g* instead of g'' in iteration t'—a contradiction.

For (c), observe that the bundle of an agent can change only in line 5 and 6 of the algorithm. In line 5 an agent receives an additional good, thus the score $s_i(k, A_i^t)$ can only increase. Hence, let us prove that it is not possible for a score $s_i(k, A_i^t)$ to decrease as an effect of the exchange along the alternating path in line 6 of the algorithm. To the end, we will show that in the alternating paths an agent exchanges only goods it sees as indifferent. More formally, let $p = (g_0, i_1, g_1, \ldots, i_s, g_s)$ be an alternating path chosen in line 4 of the algorithm. We will prove that for every $j \in [s]$, it holds that $g_{j-1} \sim_{i_j} g_j$. Observe that $g_j \succeq_{i_j} g_{j-1}$ by the the definition of an alternating path. Observe also that g_j is available at the end of iteration t-1, as witnessed by alternating path $p' = (g_j, i_{j+1}, g_{j+1}, \ldots, i_s, g_s)$. Thus, from (b) we get that $g_{j-1} \succeq_{i_j} g_j$, which proves that $g_{j-1} \sim_{i_j} g_j$.

For (d), assume for a contradiction that there exists $g \in \triangleright_i(k, A_i^t) \cap X^t$ and $g' \in \triangleright_i(k) \setminus X^t$. This means that there exists an alternating path $p = (g_0, i_1, g_1, \ldots, i_r, g_r)$ in G_{pref} that starts in $g_0 = g'$ and ends in some unallocated good g_r . Thus, since *i* is indifferent between *g* and *g'*, we get that path $(g, i, g_0, i_1, g_1, \ldots, i_r, g_r)$ is also alternating. As a result, *g* is available—a contradiction.

Next, let us prove some basic observations regarding set U and envy in our algorithm.

Claim 2. For arbitrary iterations $t', t \in [m]$ and agents $i, j \in N$ such that t' < t, it holds that

- (a) no agent becomes prioritized again, i.e., $U^t \subseteq U^{t'}$,
- (b) the sizes of bundles of agents in U are as equal as possible, i.e., $0 \le |A_i^t| |A_j^t| \le 1$, if $i, j \in U^t$ and $\sigma(i) < \sigma(j)$, and
- (c) an agent cannot start envying an agent that did not receive more goods, i.e., if $A_j^{t'} \succeq_j A_i^{t'}$ and $|A_i^{t'}| = |A_i^t|$, then $A_j^t \succeq_j A_j^t$.
- (d) an agent never envies agents that are later in the ordering, i.e., if $\sigma(i) < \sigma(j)$, then $A_i^t \succeq_i A_j^t$.

Proof. We get (a) directly from the algorithm as U^t is always chosen as a subset of U^{t-1} in line 7 by checking criteria F (Algorithm 2).

For (b), since in line 3 of the algorithm we choose an agent from U (whenever it is nonempty) with the smallest number of goods and from (a) U never gets new agents, the difference in the number of goods of agents in U never increases above one. Since we break ties according to σ , if the number of goods is not equal, it is the earlier agent in σ that has one more good.

For (c), assume otherwise, i.e., $A_j^{t'} \succeq_j A_i^{t'}$ and $|A_i^{t'}| = |A_i^t|$, but $A_i^t \succ_j A_j^t$. From Claim 1c we have $A_i^t \succ_j A_j^t \succeq_j A_j^{t'} \succeq_j A_i^{t'}$. Thus, in order for the envy to appear, between iteration t' and t, agent i had to exchange one of its goods for a good, g, which is preferred by j over one of its goods, g', in $A_j^{t'}$. This implies that g was available in iteration t'. However, this and the fact that $g \succ_j g'$ contradicts Claim 1b.

Finally, for (d), assume by contradiction that there is an iteration t such that $A_j^t \succ_i A_i^t$ and let us take the first such t. Since $A_i^{t-1} \succeq_i A_j^{t-1}$, in iteration t, agent j obtains good g (either receives it in line 7 or exchanges for another good in the alternating path in line 6) that is preferred by agent i over one of i's goods. Since j received g in iteration t it must be that g was available at the end of iteration t - 1, i.e., $g \notin X^{t-1}$. However, this contradicts Claim 1b.

Finally, let us show a quite technical result that if an agent has only unavailable goods and potentially envies other agent, then the envied agent has at least the same amount of unavailable goods.

Claim 3. For every iteration $t \in [m]$ and agents $i, j \in N$ such that $A_i^t \subseteq X^t$, if *i* potentially envies *j*, but not actually envies, then $|A_i^t| \leq |A_j^t \cap X^t|$.

Proof. Let us denote the set of available goods in iteration t by $H^t = M \setminus X^t$. By definition, if i potentially envies j, then it strictly prefers bundle $A_j^t \cup H^t$ over its bundle. This means that there exists a position \bar{k} such that $s_i(\bar{k}, A_j^t \cup H^t) > s_i(\bar{k}, A_i^t)$ and $s_i(k, A_j^t \cup H^t) = s_i(k, A_i^t)$, for every $k < \bar{k}$. By k^* let us denote the last position for which $s_i(k^*, A_i^t) > 0$. From Claim 1b and Claim 1d we know that every good in the first k^* indifference classes of i is unavailable. Thus, for every $k \le k^*$, we

have $s_i(k, A_j^t) = s_i(k, A_j^t \cup H^t)$. Since *i* does not actually envy *j*, this means that $\bar{k} > k^*$ (otherwise, we would have $s_i(\bar{k}, A_j^t) = s_i(\bar{k}, A_j^t \cup H^t) > s_i(\bar{k}, A_i^t)$) Hence, we get the bound in question, i.e., $|A_j^t \cap X^t| \ge \sum_{k=1}^{k^*} s_i(k, A_j^t) = \sum_{k=1}^{k^*} s_i(k, A_i^t) = |A_i^t|$.

Part 2: Criteria specific properties.

We now move the second part of the proof in which we consider properties that rely on specific fairness criteria.

Claim 4. If criteria F = EFX or F = EFX + MMS, then for every $t \in [m]$ it holds that $U^t \neq \emptyset$.

Proof. Observe that in every directed graph, there exists a strongly connected component without any incoming edge. In particular, such a component exists in $G_{envy}(A^t, S)$ for every $S \subseteq N$ and $t \in [m]$. Hence, in each iteration $t \in [m]$, for some agent $i \in U^{t-1}$, Algorithm 2 will return *True* and keep it in U^t .

Now, let us show one of the key observation of the proof that allows us to guarantee EFX: if an agent, j, envies another agent, i, with at most the same number of goods, then there is no potential envy path from i to j in G_{envy} . We will use this result later on to prove that, in such cases, i can be eliminated from U.

Claim 5. If criteria F = EFX or F = EFX + MMS, then for every agents $i, j \in N$, and iteration $t \in [m]$ such that j envies i and $|A_i^t| \leq |A_j^t|$, there is no path $p = (i_1, \ldots, i_r)$ in $G_{envy}(A^{t-1}, N)$ such that $i = i_1$ and $j = i_r$.

Proof. We will prove that for every agents $i, j \in N$, if $t \in [m]$ is the first iteration in which j envies i and $|A_i^t| \leq |A_i^t|$, then in iteration t - 1, it holds that:

- (a) agent j envies i, i.e., $A_i^{t-1} \succ_j A_j^{t-1}$,
- (b) agent *i* has one more good than agent *j* in its bundle, i.e., $|A_i^{t-1}| = s$ and $|A_i^{t-1}| = s 1$
- (c) all goods of agent *i* are unavailable, i.e., $A_i^{t-1} \subseteq X^{t-1}$, and
- (d) there is no path $p = (i_1, \ldots, i_r)$ in $G_{envy}(A^{t-1}, N)$ such that $i = i_1$ and $j = i_r$.

Observe that point (d) will imply the thesis of the claim, as by Claim 1a and Claim 1c, it is not possible for the potential envy to reappear in our algorithm once it is gone. Thus, if there is no potential envy path from i to j in iteration t, then there is no such path in any later iteration.

Assume otherwise. Fix arbitrary agents $i, j \in N$, and take the first iteration $t \in [m]$ such that j envies i and $|A_i^t| \le |A_j^t|$. Observe that from Claim 2d we know that i is before j in the ordering σ . Denote $s = |A_i^t|$. Let us now prove each of the points (a)–(d) separately.

Point (a). Let us start by showing that actually $|A_j^t| = |A_i^t| = s$. Assume otherwise, i.e., $|A_j^t| > s$. Let t' be the last iteration in which $|A_j^{t'}| = s$. This means that in iteration t' + 1 agent j is chosen in line 3 of the algorithm, not agent i. Since $|A_j^{t'}| = s \ge |A_i^{t'}|$ and $\sigma(i) < \sigma(j)$, this implies that $i \notin U^{t'}$ and $j \in U^{t'}$. From the minimality of t, we know that j does not envy i in iteration t', i.e., $A_j^{t'} \succeq_j A_i^{t'}$. Hence, $|A_i^{t'}| \neq s$, as otherwise this would violate Claim 2c. Thus, $|A_i^{t'}| < s$. However, since $i \notin U^{t'}$ and the fact that, by Claim 4, set U is never empty, the number of goods of i cannot increase in later iterations. But this contradicts the fact that $|A_i^t| = s$.

Let us now show that agent j envies i in iteration t-1 as well. Assume otherwise, i.e., the envy appeared in iteration t. From Claim 2c this means that i received a new good in line 7 of iteration t, which means that $|A_i^{t-1}| = s - 1$ and $|A_j^{t-1}| = s$. Consequently, this implies that $i \in U^{t-1}$ from

the fact that U is never empty (Claim 4). Furthermore, from Claim 2b we get that $j \notin U^{t-1}$. Let t' be the last iteration in which $j \in U^{t'}$. By Claim 2b, $|A_j^{t'}| \leq |A_i^{t'}| \leq |A_i^{t-1}| = s - 1$. Observe that between iterations t' + 1 and t agent j cannot receive new goods in line 7 of the algorithm (as i should receive a good before j). Hence, $|A_j^{t'+1}| = |A_j^t|$ and the latter is equal to s as we have shown in the previous paragraph. Thus, in iteration t' we have $|A_j^{t'}| = |A_i^{t'}| = s - 1$. But then, it is agent i that should receive a new goods in line 7 of iteration t' + 1 not j—a contradiction.

Point (b). Since, by (a), agent j envies i in iteration t - 1, then by minimality of t, this means that $|A_i^{t-1}| > |A_j^{t-1}|$. Since in each single iteration, the number of goods increases by one for one agent and stays the same for all others, it must be that $|A_i^{t-1}| = s$ and $|A_i^{t-1}| = s - 1$.

agent and stays the same for all others, it must be that $|A_i^{t-1}| = s$ and $|A_j^{t-1}| = s - 1$. *Point (c).* Now let us show that at the end of iteration t - 1 all goods of agent i are unavailable. Assume for contradiction that $A_i^{t-1} \not\subseteq X^{t-1}$. By k^* let us denote the last position for which $s_j(k^*, A_j^{t-1}) > 0$. Since, by (a), j envies i there must be a position $\bar{k} \in \mathbb{N}$ such that $s_j(\bar{k}, A_i^{t-1}) > s_j(\bar{k}, A_j^{t-1})$ and $s_j(k, A_i^{t-1}) = s_j(k, A_j^{t-1})$, for every $k < \bar{k}$. Now, let us consider two cases based on relation between k^* and \bar{k} .

If $\bar{k} \geq k^*$, then since j has only one less good than i, \bar{k} is the only position on which score vectors $s_j(A_i^{t-1})$ and $s_j(A_j^{t-1})$ differ. Specifically, $s_j(\bar{k}, A_i^{t-1}) = s_j(\bar{k}, A_j^{t-1}) + 1$ and $s_j(k, A_i^{t-1}) = s_j(k, A_j^{t-1})$, for every $k < \bar{k}$. Take arbitrary i's available good, $g \in A_i^{t-1} \setminus X^{t-1}$. From Claim 1b we know that g must be in the \bar{k} -th or k^* -th indifference class of agent j. In line 7 of iteration t agent j receives the most preferred available good, which, since g is available, has to be in \bar{k} -th or earlier indifference class. Thus, $s_j(A_j^t) \ge_{lex} s_j(A_i^t)$, but this contradicts the fact that j envies i.

Now, consider the case in which $\bar{k} < k^*$. By Claim 1b, all *i*'s goods in \bar{k} -th and earlier indifference classes of j are unavailable. Thus, if we remove all available goods we still have $s_j(A_i^{t-1} \cap X^{t-1}) >_{lex} s_j(A_j^{t-1})$. Now, let t' < t - 1 be some iteration in which $|A_j^{t'}| = |A_i^{t'}| =$ $|A_i^{t-1} \cap X^{t-1}|$ (from Claim 2b and Claim 4 we know that there exists at least one). By Claim 1c, $A_j^{t-1} \succeq_j A_j^{t'}$, thus $A_i^{t-1} \cap X^{t-1} \succ_j A_j^{t'}$. On the other hand, from the minimality of t we know that j does not envy i in iteration t', i.e., $A_j^{t'} \succeq_j A_i^{t'}$. Since j weakly prefers $A_j^{t'}$ over $A_i^{t'}$ but not over $A_i^{t-1} \cap X^t$ and we know that $|A_i^{t'}| = |A_i^{t-1} \cap X^{t-1}|$, there must be a good in the latter but not former, $g \in (A_i^{t-1} \cap X^{t-1}) \setminus A_i^{t'}$, that j strictly prefers over one of its goods $g' \in A_j^{t'}$. However, since g is assigned to agent i in some iteration later than t', g is available in t'. But then the fact that $g \succ_j g'$ contradicts Claim 1b. Therefore, all of the goods in A_i^{t-1} are unavailable.

Point (d). In order to prove this point, let us take minimal iteration $t \in [m]$ for which there are agents $i, j \in N$ such that j envies $i, |A_j^t| \ge |A_i^t|$ and there is a path $p = (i_1, i_2, \ldots, i_r)$ in $G_{envy}(A^{t-1}, N)$ such that $i = i_1$ and $j = i_r$. We will show by induction that each agent in $\{i_1, i_2, \ldots, i_r\}$ has $|A_i^t| = s$ unavailable goods in iteration t - 1. This will lead to contradiction as from (b) we know that agent $j = i_r$ has s - 1 goods in total.

The basis of induction follows from (c). For the inductive step, assume that i_u has s unavailable goods for arbitrary $u \in [r-1]$. Observe that since in iteration t-1 we have that $j \in U^{t-1}$ and it has s-1 goods, then by Claim 2b, no agent has more than s goods. Thus, all of the goods of i_u are unavailable. Hence, by Claim 3, either i_u actually envies i_{u+1} or i_{u+1} also has s unavailable goods. In the former case, by minimality of t, we get that there is no potential envy path from i_{u+1} to i_u in $G_{envy}(A^{t-2}, N)$. Since j potentially envies i in t-2 (as otherwise it would not envy it in t-1), this means that there is no potential envy path from i_{u+1} to j in $G_{envy}(A^{t-1}, N)$, which contradicts our assumptions. Hence, i_{u+1} has s unavailable goods. Thus, by induction, we obtain that j also has sunavailable goods, but that contradicts the fact that $|A_i^{t-1}| = s - 1$, which concludes the proof. \Box

Next, we show the key result for the proof of MMS. Specifically, we consider an arbitrary agent

i and iteration *t* such that all goods in the first *k* indifference classes of agent *i* are unavailable. We show that in such a case the score vector of *i*'s bundle is lexicographically as large as its MMS vector up to first *k* coordinates (a). Moreover, if all of *i*'s goods are from its first *k* classes and there is an agent with less goods than *i*, then *i* strictly prefers its bundle to its MMS (b). Finally, if the first *k* positions of the score of *i*'s bundle are exactly the same as the first *k* positions of *i*'s MMS, then we can identify a certain subset of agents that are not in *U* with a specific number of goods in total (c). To this end, let us introduce some additional notation. For an agent *i*, let us denote set $\triangleright_i(1: k) = \triangleright_i(1) \cup \cdots \cup \triangleright_i(k)$ and vectors $s_i(1: k, A_i^t) = (s_i(1, A_i^t), \dots, s_i(k, A_i^t))$ and MMS_i(1: k) = (MMS_i(1), ..., MMS)_i(k)).

Claim 6. If fairness criterion F = MMS or F = EFX + MMS, then for every iteration $t \in [m]$, agent $i \in N$, and $k \in \mathbb{N}$ such that $\triangleright_i(1:k) \subseteq X^t$, it holds that:

- (a) $s_i(1:k, A_i^t) \ge_{lex} \text{MMS}_i(1:k)$,
- (b) if $s_i(k', A_i^t) = 0$ for every k' > k and there is an agent $j \in U^t$ such that $|A_j^t| < |A_i^t|$, then $A_i^t >_{lex} MMS_i$,
- (c) if $s_i(1:k, A_i^t) = \text{MMS}_i(1:k)$ and $i \in U^t$, then there is a subset of agents $L \subseteq N \setminus U^t$ such that $|L| = n r_{k+1}$ and

$$\sum_{j \in L} |A_j^t| = \sum_{u=1}^k s_i(u) - r_{k+1} \cdot \sum_{u=1}^k \text{MMS}_i(u),$$

where, as in Proposition 1, $r_1 = n$ and $r_{u+1} = r_u - (s_i(u) - \text{MMS}_i(u) \cdot r_u)$, for every $u \in [k_i - 1]$.

Proof. We will prove the claim by induction on the iteration number t. Observe that for t = 0, for every agent i we have $\triangleright_i(1) \not\subseteq X^0$. Hence, the thesis holds vacuously. Thus, let us take t > 0 and assume that for every $t' \in [t - 1]$ the thesis holds. In what follows, we will show that each point (a)–(c) also holds in iteration t.

Point (a). Assume otherwise, i.e., there is $k \in \mathbb{N}$ such that $\triangleright_i(k') \subseteq X^t$ for every $k' \leq k$, but $s_i(k', A_i^t) =_{lex} \text{MMS}_i(k')$, for every $k' \in [k-1]$, and $s_i(k, A_i^t) < \text{MMS}_i(k)$. Observe that since the point (a) was satisfied in iteration t-1, it must be that there is $k^* \in [k]$ such that $\triangleright_i(k^*) \not\subseteq X^{t-1}$. Since $s_i(A_i^t) <_{lex} \text{MMS}_i$, we know that $i \in U^t$ and, by Claim 2a, $i \in U^{t-1}$. Thus, from (c) for iteration t-1 we get that there is a set $L \subseteq N \setminus U^{t-1}$ such that $|L| = n - r_{k^*}$ and

$$\sum_{j \in L} |A_j^t| = \sum_{u=1}^{k^*-1} s_i(u) - r_{k^*} \cdot \sum_{u=1}^{k^*-1} \text{MMS}_i(u).$$
(3)

Let us denote $s = |A_i^t|$. Since $i \in U^t$, by Claim 2b, no agent has more than s + 1 goods. Now, let us consider two cases, based on whether $k^* = k$ (1) or $k^* < k$ (2).

Case (a.1) Assume $k^* = k$. Then, since by Claim 2b $s_i(k, A_i^t) = 0$ for every $k' \ge k$, we have

$$|A_i^t| = \sum_{u=1}^k s_i(u, A_i^t) < \sum_{u=1}^k \text{MMS}_i(u),$$
(4)

while for every $j \in N \setminus L \setminus \{i\}$, we have

$$|A_j^t| \le |A_i^t| + 1 \le \sum_{u=1}^k \text{MMS}_i(u).$$
 (5)

Adding inequalities (3), (4), and (5) sidewise together, we get $\sum_{j \in N} |A_j^t| < \sum_{u=1}^{k-1} s_i(u) - r_k \cdot \sum_{u=1}^{k-1} MMS_i(u) + r_k \cdot \sum_{u=1}^{k} MMS_i(u)$, which gives

$$\sum_{j \in N} |A_j^t| < \sum_{u=1}^{k-1} s_i(u) + r_k \cdot \mathsf{MMS}_i(k) \le \sum_{u=1}^k s_i(u),$$

where the last inequality comes from the definition of the sequence r_1, \ldots, r_{k_j} . However, this stands in a contradiction to the fact that all items from $\triangleright_i(1), \ldots, \triangleright_i(k)$ are unavailable, hence allocated.

Case (a.2). If $k^* < k$, then by Claim 1b, it must be that $s_i(k', A_i^{t-1}) = 0$, for every $k' > k^*$. Also, since some goods from $\triangleright_i(k^*)$ are still available after iteration t - 1, if it is agent *i* that is chosen in line 3 of iteration *t*, it will receive a good from this class. Thus, also $s_i(k', A_i^t) = 0$, for every $k' > k^*$.

Thus, we have,

$$|A_i^t| = \sum_{u=1}^{k^*} s_i(u, A_i^t) = \sum_{u=1}^{k^*} \text{MMS}_i(u),$$
(6)

while for every $j \in N \setminus L \setminus \{i\}$, we have

$$|A_j^t| \le |A_i^t| + 1 = 1 + \sum_{u=1}^{k^*} \text{MMS}_i(u).$$
(7)

Adding equation (3) and inequalities (6) and (7) sidewise together, we get

$$\sum_{j \in N} |A_j^t| \le \sum_{u=1}^{k^*-1} s_i(u) + r_{k^*} \cdot \text{MMS}_i(k^*) + (r_{k^*} - 1).$$
(8)

From the definition of the sequence r_1, \ldots, r_{k_i} we have that

$$\sum_{u=k^*}^k s_i(u) = \sum_{u=k^*}^k (r_u - r_{u+1} + r_u \cdot \text{MMS}_i(u))$$

$$\geq r_{k^*} \cdot \text{MMS}_i(k^*) + r_k \cdot \text{MMS}_i(k) + \sum_{u=k^*}^k (r_u - r_{u+1})$$

$$\geq r_{k^*} \cdot \text{MMS}_i(k^*) + r_k \cdot \text{MMS}_i(k) + r_{k^*} - r_k$$

$$\geq r_{k^*} \cdot \text{MMS}_i(k^*) + r_{k^*},$$

where the last inequality comes from the fact that $s_i(k, A_i^t) < \text{MMS}_i(k)$, thus $\text{MMS}_i(k) \ge 1$. Combining this with inequality (8), yields $\sum_{j \in N} |A_j^t| < \sum_{u=1}^k s_i(k)$, which contradicts the assumption that $\triangleright_i(k')$ is unavailable, thus also allocated, for every $k' \in [k]$.

Point (b). Assume otherwise, i.e., there is $k \in \mathbb{N}$ such that $\triangleright_i(1:k) \subseteq X^t$, agent $j \in U^t$ such that $|A_j^t| < |A_i^t|$, and it holds that $s_i(A_i^t) \leq \text{MMS}_i$ and $s_i(k', A_i^t) = 0$, for every k' > k. From (a) we know that this means that $s_i(1:k, A_i^t) = \text{MMS}_i(1:k)$.

Observe that since the point (b) was satisfied in iteration t-1, it must be that there is $k^* \in [k]$ such that $\triangleright_i(k^*) \not\subseteq X^{t-1}$. Since, by Claim 1c, $s_i(A_i^{t-1}) \leq s_i(A_i^t) \leq \text{MMS}_i$, this means that $i \in U^{t-1}$. Thus, from (c) for iteration t-1, we know that there is $L \subseteq N \setminus U^{t-1}$ such that $|L| = n - r_{k^*}$ and

$$\sum_{h \in L} |A_h^t| = \sum_{u=1}^{k^*-1} s_i(u) - r_{k^*} \cdot \sum_{u=1}^{k^*-1} \text{MMS}_i(u).$$
(9)

Let us denote $s = |A_i^t|$. Then, $|A_j^t| < s$. Since $j \in U^t$, from Claim 2b we know that $|A_j^t| = s - 1$ and no agent has more than s goods. If $k^* < k$, then from Claim 1b it must be that $s_i(k', A_i^{t-1}) = 0$, for every $k' > k^*$. Hence, no matter the relation between k^* and k, it holds that

$$s = \sum_{u=1}^{k} s_i(u, A_i^t) = \sum_{u=1}^{k^*} s_i(u, A_i^t) = \sum_{u=1}^{k^*} \text{MMS}_i(u).$$

Therefore,

$$|A_j^t| = s - 1 = \sum_{u=1}^{k^*} \text{MMS}_i(u) - 1,$$
(10)

while for every $h \in N \setminus L \setminus \{j\}$, we have

$$|A_h^t| \le s = \sum_{u=1}^{k^*} \text{MMS}_i(u).$$
 (11)

Adding inequalities (9), (10), and (11) sidewise together, we get $\sum_{h \in N} |A_h^t| \leq \sum_{u=1}^{k^*-1} s_i(u) - r_{k^*} \cdot \sum_{u=1}^{k^*-1} \text{MMS}_i(u) + r_{k^*} \cdot \sum_{u=1}^{k^*} \text{MMS}_i(u) - 1$, which gives

$$\sum_{h \in N} |A_h^t| < \sum_{u=1}^{k^*-1} s_i(u) + r_{k^*} \cdot \text{MMS}_i(k^*)$$
$$\leq \sum_{u=1}^{k^*} s_i(u).$$

However, this stands in a contradiction to the fact that all items from $\triangleright_i(1), \ldots, \triangleright_i(k^*)$ are unavailable, hence allocated.

Point (c). Take iteration $t \in [m]$, agent $i \in U^t$, and class $k \in [k_i]$ such that $\triangleright_i(1:k) \subseteq X^t$ and $s_i(1:k, A_i^t) = \text{MMS}_i(1:k)$. First, let us consider the case in which the first k classes of i are unavailable also in iteration t - 1, i.e., $\triangleright_i(1:k) \subseteq X^{t-1}$. Observe that U does not increase (Claim 2a) and the agents in U do not receive more goods if U is not empty (and since $i \in U^t$, it is not empty). Thus, since (c) holds for iteration t - 1, we get that it holds also for t. Therefore, for the remainder of the proof, we will assume that there is $k^* \in [k]$ such that $\triangleright_i(k^*) \not\subseteq X^{t-1}$.

From Claim 2a and the assumption that $i \in U^t$ we get that $i \in U^{t-1}$. Thus, from (c) for iteration t-1 we know that $|U^{t-1}| \leq r_{k^*}$ and there is $L \subseteq N \setminus U^{t-1}$ such that $|L| = n - r_{k^*}$ and

$$\sum_{j \in L} |A_j^t| = \sum_{u=1}^{k^*-1} s_i(u) - r_{k^*} \cdot \sum_{u=1}^{k^*-1} \text{MMS}_i(u).$$
(12)

The fact that $\triangleright_i(1:k) \subseteq X^t$, implies that $\sum_{j\in N} |A_j^t \cap \triangleright_i(1:k)| = \sum_{u=1}^k s_i(u)$. Combining this with equation (12) implies that among agents in $N \setminus L$ there are $\sum_{u=k^*}^k s_i(u) + r_{k^*} \cdot \sum_{u=1}^{k^*-1} \text{MMS}_i(u)$ goods from $\triangleright_i(1:k)$. From the definition of the sequence r_1, \ldots, r_{k_i} , we have that

$$\sum_{u=k^*}^k s_i(u) = \sum_{u=k^*}^k (r_u - r_{u+1} + r_u \cdot \text{MMS}_i(u))$$
$$= \sum_{u=k^*}^k r_u \cdot \text{MMS}_i(u) + r_{k^*} - r_{k+1}.$$

Thus,

$$\sum_{j \in N \setminus L} |A_j^t \cap \rhd_i(1:k)| = r_{k^*} - r_{k+1} + r_{k^*} \cdot \sum_{u=1}^{k^*} \mathrm{MMS}_i(u) + \sum_{u=k^*+1}^k r_u \cdot \mathrm{MMS}_i(u).$$

Since $\triangleright_i(k^*) \notin X^{t-1}$, then by Claim 1b, we know that $s_i(u, A_i^t) = 0$ for every $u > k^*$. Hence, by the assumption that $s_i(1:k, A_i^t) = MMS_i(1:k)$, we get that $MMS_i(u) = 0$ for every $u \in \{k^*, k^* + 1, \dots, k\}$. Therefore,

$$\sum_{j \in N \setminus L} |A_j^t \cap \rhd_i(1:k)| = r_{k^*} - r_{k+1} + r_{k^*} \cdot \sum_{u=1}^{k^*} \text{MMS}_i(u).$$
(13)

Now, let us denote $s = |A_i^t| = \sum_{u=1}^{k_i} s_i(u, A_i^t) = \sum_{u=1}^{k^*} \text{MMS}_i(u)$. By Claim 2b, no agent has more than $s + 1 = 1 + \sum_{u=1}^{k^*} \text{MMS}_i(u)$ goods. By equation (13), the fact that $|N \setminus L| = r_{k^*}$, and a pigeonhole principle kind of argument, this means that there are at least $r_{k^*} - r_{k+1}$ agents with s + 1 goods from $\triangleright_i(1:k)$.

Let j be an arbitrary agent with s + 1 goods from $\triangleright_i(1:k)$ at the end of iteration t. We will show that necessarily $j \notin U^t$. Observe that all goods of agent j belong to $\triangleright_i(1:k)$, hence they are unavailable. In particular, if l is the last indifference class such that $s_j(l, A_j^t) > 0$, then by Claim 1d we know that $\triangleright_j(l) \subseteq X^t$. Also, from Claim 1b we know that this is the case for every indifference class of j before l. Thus, since i has less goods than j, from (b) we have that $s_j(A_j^t) >_{lex} MMS_j$. Hence, if fairness criterion F = MMS, then $j \notin U^t$.

Now, let us show that the same holds if fairness criterion F = EFX + MMS. We can show that $s_i(A_i^t) >_{lex} MMS_j$ in the same way, hence let us focus on showing that there is no path from j to i in graph $G_{envy}(A^t, U^{t-1})$. Assume otherwise, i.e., there exists a path (i_0, i_1, \ldots, i_r) in $G_{envy}(A^t, U^{t-1})$ such that $j = i_0$ and $i = i_r$. Similarly to the proof of Claim 5c, we will inductively show that this would imply that every agent in the path has s + 1 unavailable goods, which would contradict the fact that $|A_i^j| = s$. The basis of induction we have already established, i.e., agent j has s + 1 goods and all of them are unavailable. For the inductive step, assume that for some $u \in [r-1]$ agent i_u has s + 1 unavailable goods. Since no agent has more than s + 1, this means that all i_u 's goods are unavailable. Hence, if agent i_u does not actually envy i_{u+1} , but only potentially, then i_{u+1} has s+1unavailable goods from Claim 3. Thus, assume that i_u actually envy agent i_{u+1} . Observe that i_{u+1} has to be in U^t if there is a potential envy path from i_{u+1} to i_r in $G_{envy}(A^t, U^{t-1})$. Moreover, since i_u envies i_{u+1} , from Claim 2d we know that i_{u+1} is before i_u in the ordering σ . Hence, by Claim 2b, agent i_{u+1} also has s+1 goods. But then, from Claim 5c we get that all of the goods of i_{u+1} are unavailable. Thus, by induction, we get that i has s + 1 unavailable goods, which is a contradiction. Hence, also in this case, $j \notin U^t$. Let us denote by L' the union of L and the set of such agents in set $N \setminus L$. Observe that $|L'| = (n - r_{k^*}) + (r_{k^*} - r_{k+1}) = n - r_{k+1}$. Moreover, from the definition of the sequence r_1, \ldots, r_{k_i} and the fact that $MMS_i(u) = 0$ for every $u \in \{k^* + 1, k^* + 2, \ldots, k\}$ we get that

$$\sum_{j \in L' \setminus L} |A_j^t| = (r_{k^*} - r_{k+1}) \cdot (s+1)$$

= $(r_{k^*} - r_{k+1}) \cdot (1 + \sum_{u=1}^k \text{MMS}_i(u))$
= $(r_{k^*} - r_{k+1})(1 + \text{MMS}_i(k^*) + \sum_{u=1}^{k^*-1} \text{MMS}_i(u))$
= $\sum_{u=k^*}^k s_i(u) - r_{k+1} \cdot \text{MMS}_i(k^*) + (r_{k^*} - r_{k+1}) \cdot \sum_{u=1}^{k^*-1} \text{MMS}_i(u).$

Hence, from equation (12), we get

$$\sum_{j \in L'} |A_j^t| = \sum_{j \in L' \setminus L} |A_j^t| + \sum_{j \in L} |A_j^t|$$
$$= \sum_{u=1}^k s_i(u) - r_{k+1} \cdot \sum_{u=1}^{k^*} \text{MMS}_i(u)$$
$$= \sum_{u=1}^k s_i(u) - r_{k+1} \cdot \sum_{u=1}^k \text{MMS}_i(u).$$

Therefore, L' is a desired set of agents.

Part 3: Fairness guarantees.

In this part of the proof, we will show how Claim 1 to 6 imply the fairness guarantees in the statements (A)–(D). Let us consider each of the statements separately.

(A): EF1. Let us show that if there is no criteria, i.e., F = null, then the output allocation is EF1. To this end, observe that at the end of every iteration, U contains all agents, i.e., for every $t \in [m], U^t = N$.

For iteration t and two agents i, j let $e_{i,j}^t$ be a vector such that

$$e_{i,j}^t(k) = \begin{cases} 1, & \text{if } k \text{ is minimal s. t. } s_j(k, A_i^t) > 0, \\ 0, & \text{otherwise.} \end{cases}$$

Observe that an allocation A^t is EF1, if and only if, for every agents $i, j \in N$ it holds that $s_j(A_j^t) \ge_{lex} s_j(A_i^t) - e_{i,j}^t$. Let us show that indeed, for every $t \in [m]$, allocation A^t is EF1. For a contradiction, let us assume that there is $t \in [m]$ such that $s_j(A_i^t) - e_{i,j}^t >_{lex} s_j(A_j^t)$ for some $i, j \in N$ and let us take the first such t.

Let t' < t be the last iteration in which agent j has less goods than in iteration t, i.e., $|A_j^t| < |A_j^t|$. This means that in iteration t' + 1 agent j is chosen in line 3 of the algorithm and receives a good, g, in line 5. Let $k \in [k_j]$ be such that $g \in \triangleright_j(k)$ and let e_k be a vector with 1 on k-th position and 0 otherwise. Then, by Claim 1c,

$$s_j(A_j^t) = s_j(A_j^{t'}) + e_k.$$
 (14)

Now, let us compare vectors $\mathbf{x} = (x(1), \dots, x(k_j)) = s_j(A_i^{t'}) + e_k - e_{i,j}^{t'}$ and $\mathbf{y} = (y(1), \dots, y(k_j)) = s_j(A_i^t) - e_{i,j}^t$. Observe that:

- (a) $|A_j^t| \ge \sum_{u=1}^{k_j} y(u)$ by Claim 2b;
- (b) $x(u) \ge y(u)$ for every u < k, since, by Claim 1b, all goods from the first k 1 classes of j are unavailable $\triangleright_j(1:k-1) \subseteq X^t$, which means that between iteration t' and t, agent i can only gain new goods from the k-th and further indifference classes of j;
- (c) $s_j(u, A_j^t) = 0$ for every $u \in [k]$, by Claim 1b and the fact that $g \in \triangleright_j(k)$ is available in iteration t-1; and finally
- (d) $s_j(A_j^t) \ge_{lex} \mathbf{x}$. This holds since from minimality of t, we have $s_j(A_j^{t'}) \ge s_j(A_i^{t'}) e_{i,j}^{t'}$. Combining this with equation (14), yields $s_j(A_j^t) \ge_{lex} s_j(A_i^{t'}) + e_k - e_{i,j}^{t'} = \mathbf{x}$.

Finally, let us show that $s_j(A_j^t) \ge_{lex} \mathbf{y}$. If there is $u \in [k-1]$ such that either x(u) > y(u) or $s_j(u, A_j^t) > x(u)$, then by (b) and (d) we get that $s_j(A_j^t) >_{lex} \mathbf{y}$. Hence, assume otherwise, i.e., $s_j(u, A_j^t) = x(u) = y(u)$ for every $u \in [k-1]$. Then, from (c) and (a) we get that

$$s_j(k, A_j^t) = |A_j^t| - \sum_{u=1}^{k-1} s_j(u, A_j^t) \ge \sum_{u=1}^{k_j} y(u) - \sum_{u=1}^{k-1} y(u) \ge y(k),$$

where the equality is only possible if y(u) = 0 for every u > k. Thus, $s_j(A_j^t) \ge_{lex} y$, which contradicts the assumption that *i* and *j* violate EF1 at the end of iteration *t*.

(B): EFX. Let us show that if criteria F = EFX, then the output allocation satisfies EFX.

Assume by contradiction that for some iteration $t \in \{0, ..., m\}$ allocation A^t is not EFX and let us take the first such t. Since for t = 0, empty allocation A^0 is EFX, we know that t > 0. This means that there exist agents $i, j \in N$ and good $g \in A_i^t$ such that j prefers $A_i^t \setminus \{g\}$ over its bundle. From Claim 2d we know that i is before j in ordering σ .

Let t' < t be the last iteration in which agent *i* had smaller number of goods, i.e., $|A_i^{t'}| < |A_i^t|$. This means that in iteration t' + 1 agent *i* was chosen in line 4 of the algorithm. Thus, by Claim 4, $i \in U^{t'}$ and $|A_i^{t'}| = |A_i^{t'+1}| - 1 = |A_i^t| - 1$. Observe that $j \in U^t$ as otherwise there would be some iteration t' < t in which *j* did not potentially envy *i*, so, by Claim 1c, *j* could not envy *i* in iteration *t*. Hence, since *i* is before *j* in ordering σ , from Claim 2b we get that in iteration *t'* agents *i* and *j* had equal number of goods, i.e., $|A_i^{t'}| = |A_j^{t'}|$. Let us show that necessarily $t' + 1 \neq t$. Assume otherwise. By Claim 5 and the fact that $i \in U^{t'}$ this means that *j* does not envy *i* in iteration *t'*. Let $k^* \in \mathbb{N}$ be the last position for which there is a positive number in *j*'s bundle score, i.e., $s_j(k^*, A_j^{t'}) > 0$. By Claim 1c, $s_j(k^*, A_j^{t'+1}) > 0$ as well. Then, a good, *g'*, that agent *i* receives in iteration t' + 1 has to be in a *k*-th indifference class of *j* for some $k < k^*$ (otherwise removing any good from $A_i^{t'+1}$ would eliminate the envy). However, since *g'* was available in iteration *t'*, this contradicts Claim 1b.

Therefore, t' + 1 < t and j and i do not violate EFX in iteration t' + 1. Since $|A_i^t| = |A_i^{t'+1}|$ and, by Claim 1c, $A_j^t \succeq_j A_j^{t'+1}$, this means that between iteration t and t' + 1 agent i exchanged one of its goods for a good g that is preferred by j over one of goods from $A_j^{t'+1}$. However, this means that g was available at iteration t' + 1, which contradicts Claim 1b. Thus, A^t is EFX for every $t \in [m]$.

<u>(C): MMS.</u> Observe that if criteria F = MMS, then the fact that the output allocation satisfies MMS follows directly from Claim 6a: at the end of the algorithm all goods are unavailable, thus $s_i(A_i) \ge_{lex} \text{MMS}_i$, for every agent $i \in N$.

(D): EFX+MMS. Let us show that if criteria F = EFX+MMS, then the output allocation satisfies EFX and MMS. Observe that MMS follows directly from Claim 6a: at the end of the algorithm all goods are unavailable, thus $s_i(A_i) \ge_{lex} MMS_i$, for every agent $i \in N$.

Therefore, let us focus on proving EFX. Assume by contradiction that for some iteration $t \in$ $\{0, \ldots, m\}$ allocation A^t is not EFX and let us take the first such t. Since for t = 0, empty allocation A^0 is EFX, we know that t > 0. This means that there exist agents $i, j \in N$ and good $g \in A_i^t$ such that j prefers $A_i^t \setminus \{g\}$ over its bundle. From Claim 2d we know that i is before j in ordering σ .

Let t' < t be the last iteration in which agent *i* had smaller number of goods, i.e., $|A_i^{t'}| < |A_i^t|$. This means that in iteration t' + 1 agent i was chosen in line 3 of the algorithm. Thus, by Claim 4, $i \in U^{t'}$ and $|A_i^{t'}| = |A_i^{t'+1}| - 1 = |A_i^t| - 1$. Observe that $j \in U^t$ as otherwise there would be some iteration t'' < t in which j did not potentially envy i, so, by Claim 1c, j could not envy i in iteration t. Hence, since i is before j in ordering σ , from Claim 2b we get that in iteration t' agents i and j had equal number of goods, i.e., $|A_i^{t'}| = |A_i^{t'}|$.

Let us prove that j does not envy i in iteration t'. Assume otherwise and observe that, by Claim 5c, all goods of j are unavailable in iteration t' - 1. Hence, by Claim 1d, also all indifference classes of j containing these goods are unavailable. Therefore, from Claim 6b, $A_i^{t'-1} >_{lex} MMS_i$. However, combining this with Claim 5d yields $j \notin U^{t'-1}$, which is a contradiction.

Now, we will show that necessarily $t' + 1 \neq t$. Let us denote the good that agent *i* receives in line 6 of iteration t' + 1 as g'. Also, let $k^* \in \mathbb{N}$ be the last position for which there is a positive number in j's bundle score, i.e., $s_j(k^*, A_j^{t'}) > 0$. By Claim 1b, $g' \in \triangleright_j(k^* : k_j)$. Since by Claim 1c $s_j(A_j^{t'}) = s_j(A_j^{t'+1})$, this means that removing any good from $A_i^{t'+1}$ would eliminate the envy. Thus, i and j do not violate EFX in iteration t' + 1, hence $t' + 1 \neq t$. Therefore, t' + 1 < t and j and i do not violate EFX in iteration t' + 1. Since $|A_i^t| = |A_i^{t'+1}|$ and, by Claim 1c, $A_j^t \succeq_j A_j^{t'+1}$, this means that between iteration t and t' + 1 agent i exchanged one of

its goods for a good g that is preferred by j over one of goods from $A_j^{t'+1}$. However, this means that g was available at iteration t' + 1, which contradicts Claim 1b. Thus, A^t is EFX for every $t \in [m]$.

Part 4: Pareto optimality.

Finally, let us prove that the output of our algorithm is always a PO allocation.

To this end, we will show that for each iteration $t \in \{0, \ldots, m\}$, partial allocation A^t is PO. Assume otherwise. Let us take the first iteration t such that A^t is not PO. From Theorem 2 we know that there is an alternating path, $p = (g_0, i_1, g_1, \ldots, i_s, g_s)$ and agent i_0 such that $(g_s, i_0) \in A^t$ and $\psi(i_0, g_0) < \psi(g_s, i_0)$. Since allocation A^{t-1} is PO, either $(g_s, i_0) \notin A^{t-1}$ or path p is not alternating for A^{t-1} . Either way, this means that at least one of the goods on path p changed the owner in iteration t. Let us take the one such good g_u with the smallest $u \in [s]$. As g_u changed the owner, it has to be available in t-1, i.e., $g_u \notin X^{t-1}$. Since u is the smallest, the part of the original path, $(g_0, i_1, g_1, \ldots, i_u, g_u)$, is still an alternating path in A^{t-1} . Thus, g_0 is available in t-1 as well. By Claim 1b, this means that agent i_0 weakly prefers each of its goods in A^t over g_0 . However, this stands in contradiction to the fact that $(g_s, i_0) \in A^t$ and $\psi(i_0, g_0) < \psi(g_s, i_0)$.

Comparison with Aziz et al. [2023a] С

In this appendix, we compare Algorithm 1 and the algorithm developed by Aziz et al. [2023a] for the purpose of studying possible fairness that also achieves EFX, MMS and PO for every weakly lexicographic goods-only instance. We note that both algorithms were developed independently and there are important differences between them both in terms of the techniques they utilize and the final outcomes they produce (see Example 5).

Our algorithm (in contrast to Aziz et al. [2023a]'s) directly checks a predefined fairness requirement for the bundle of each agent in each round of the runtime. Then, the agents with an unfair advantage stop receiving more goods and the priority is given to the worse-off agents. Such construction has several benefits.

Firstly, the working mechanism behind our algorithm is well-structured and easy to understand, which is in a sharp contrast with the more black-box approach of Aziz et al. [2023a]. Thus, we believe that our formulation of the algorithm holds an educational value as it allows for explanation of where the fairness comes from.

Secondly, our algorithm is customizable in the sense that a set of imposed fairness requirements can be modified, which will directly affect the outcome of the algorithm. This in turn allows for easy modification of the algorithm to different notions of fairness (including and beyond the notions studied in this paper).

Finally, the construction of our algorithm introduces the techniques of potential envy and preference graph, which can be found useful on their own.

In contrast, the algorithm of Aziz et al. [2023a] uses an exchange graph, which is a directed graph whose vertices are goods and there is an edge (g,g') for $g,g' \in M$ if there is an agent $i \in N$ such that $g \in A_i$ and $g' \succeq_i g$. The algorithm starts by initializing an empty bundle for each agent. The agents that can still receive goods are kept in set N, which is updated over the run of the algorithm. In each round, each agent in N (in an arbitrary order) receives its most preferred good out of the unallocated ones or the ones that can be freed if other agents exchange their goods in along the edges of the exchange graph. After the goods are allocated, the set N is updated. To this end, the algorithm looks at the set of goods distributed in this round. If some agent, i, strictly prefers the good received by another agent, j, over its own, then agent j is removed. Moreover, whenever an agent is removed, all agents with whom it can exchange goods are allocated.

In addition to the differences in the construction, the outcomes of the two algorithms can also be significantly different. Let us consider the following example to illustrate this.

Example 5. Consider the instance given in Example 1.

 $1: \quad \{g_1, \underline{g_2}\} \triangleright \{g_3, \underline{g_4}\}$ $2: \quad \underline{g_1} \triangleright \{g_2, g_3, g_4\}$ $3: \quad g_1 \triangleright \{g_2, \underline{g_3}, \underline{g_4}\}$

The outcome of Algorithm 1 with F = EFX + MMS:

In iteration 1, agent 1 receives g_1 (see the red highlight in Figure 1a). Observe that good g_1 is still available since there exists an alternating path $(g_1, 1, g_2)$ ending in an unallocated good. Thus, in iteration 2, agent 1 exchanges g_1 for g_2 and agent 2 receives g_1 . Then, in the potential envy graph at the end of iteration 2, i.e., $G_{envy}(A^2, U^1)$, agent 3 is the only agent that forms a strongly connected component with no incoming edge, U_e^2 . Moreover, since for each of agents 1 and 2, its bundle is above the respective MMS threshold, we remove them from U, thus $U^2 = \{3\}$. Therefore, agent 3 receives goods g_3 and g_4 . The final allocation is underlined.

The outcome of the algorithm of Aziz et al. [2023a]:

In the first round, the algorithm begins by giving agent 1 good g_1 . Next, in the same round, since agent 1 can exchange good g_1 for g_2 , agent 2 gets good g_1 and agent 1, g_2 . The first round ends, with agent 3 receiving good g_3 . Observe that agent 3 strictly prefers good g_1 over g_3 , thus agent 2 is removed from set N, i.e., $N = \{1, 3\}$. In the second round, agent 1 receives good g_4 . The final allocation is circled with red.

Observe that although the allocation produced by the algorithm of Aziz et al. [2023a] is EFX, agent 3 envies agent 1. In our Algorithm 1, since agent 1 received a good from its first indifference class, we

know that it will never envy agent 3, thus we do not give any more goods to agent 1. As a result, agent 3 does not envy agent 1 and the total number of envy relations between the agents is smaller in the output of our algorithm.

Examples of Running Algorithm 1 D

In this section, we analyze several examples for the goods-only setting.

In Examples 6 to 8, we illustrate how Algorithm 1 runs with different fairness criteria F in its input on the same instance.

Example 6. Consider a goods-only instance with three agents, seven goods and preferences as follows. Each agent partitions the goods into two indifference classes.

> 1: $\{g_1, g_2, g_3\} \triangleright \{g_4, g_5, g_6, g_7\}$ 2: $\{g_1, g_2, g_3\} \triangleright \{g_4, g_5, g_6, g_7\}$ 3: $\{g_1, g_2, g_3, g_4, g_5\} \triangleright \{g_6, g_7\}$

Algorithm 1 with F = null (EF1 and PO): First, agents 1, 2 and 3 receive goods g_1 , g_2 and g_3 , respectively. Then, agent 1 points to g_3 , and we update the allocation along the alternating path $p = (g_3, 3, g_4)$ and assign g_3 to agent 1. In the following iterations, agents 2 and 3 receive goods g_6 and g_5 in order. Finally, agent 1 receives good g_7 . The final allocation is underlined.

Example 7. Consider the instance given in Example 6.

1: $\{g_1, g_2, g_3\} \triangleright \{g_4, g_5, g_6, g_7\}$ 2: $\{g_1, g_2, g_3\} \triangleright \{g_4, g_5, g_6, g_7\}$ $3: \{g_1, g_2, g_3, g_4, g_5\} \triangleright \{g_6, g_7\}$

Algorithm 1 with F = EFX (EFX, PO, but not MMS):

First, agents 1, 2 and 3 receive goods g_1 , g_2 and g_3 , respectively. Observe that every agent potentially envies every other agent at the current allocation. Thus, agent 1 points to g_3 , and we update the allocation along the alternating path $p = (g_3, 3, g_4)$ and assign g_3 to agent 1. Then, agent 3 is the only agent that is not potentially envied. Therefore, 3 receives the rest of the goods. The final allocation is underlined. Observe that this allocation is EFX. However, agent 2's MMS threshold is not met, as it receives no good from its second indifference class.

Example 8. Consider the instance given in Example 6.

1: $\{g_1, g_2, g_3\} \triangleright \{g_4, g_5, g_6, g_7\}$ 2: $\{g_1, g_2, g_3\} \triangleright \{g_4, g_5, g_6, g_7\}$ $3: \{g_1, g_2, g_3, g_4, g_5\} \triangleright \{g_6, g_7\}$

Algorithm 1 with F = MMS (MMS and PO):

First, agents 1, 2 and 3 receive goods g_1 , g_2 and g_3 , respectively. Then, agent 1 points to g_3 , and we update the allocation along the alternating path $p = (g_3, 3, g_4)$ and assign g_3 to agent 1. Agent 1 prefers its bundle to its MMS threshold. However, agents 2 and 3 have not yet met their MMS. Thus, agent 2 receives goods g_6 and g_7 , while agent 3 gets g_5 . The final allocation is underlined.

E EFX and MMS Relation

In the current section, we present examples for the relation between EFX and MMS under both goods-only and chores-only settings.

The fact that EFX (even with PO) does not necessarily imply MMS in the goods-only setting is visible in Example 7. In contrast, as shown in Section 5.1, EFX implies MMS for chores-only instances. However, Example 9 illustrates that MMS coupled with PO does not imply EFX for this setting, even when agents have at most two indifference classes.

Example 9. Consider a chores-only instance with three agents, three chores and preferences as follows. Agent 3 has all chores as one class while the others partition the chores into two indifference classes.

$$1: \quad c_1 \triangleright \{\underline{c_2}, \underline{c_3}\} \\ 2: \quad c_1 \triangleright \{c_2, c_3\} \\ 3: \quad \{\underline{c_1}, c_2, c_3\}$$

Observe that the underlined allocation is MMS and PO. But agent 1 envies agent 2 more than EFX.

F Correctness of Algorithm 3

In this appendix, we show that our Algorithm 3 indeed always finds an EF1 and PO allocation.

Helpful for that will be the observation made by [Ebadian et al., 2022, Lemma 4.14] that the PO characterization in Theorem 2 can be also adapted to chores-only instances. For completeness, we provide its proof in Appendix G.

Theorem 5. Given a weakly lexicographic chores-only instance (N, M, \triangleright) , an (possibly partial) allocation A is PO, if and only if, there is no alternating path, $p = (c_0, i_1, c_1, \ldots, i_s, c_s)$ and agent i_0 such that $(c_s, i_0) \in A$ and $\psi(i_0, c_0) > \psi(c_s, i_0)$.

Let us now move to the proof of the correctness of Algorithm 3.

Theorem 4. Given a weakly lexicographic chores-only instance (N, M, \triangleright) , Algorithm 3 always returns an EF1 and PO allocation.

Proof. For every $t \in [m]$, by A^t , we will denote the allocation we have at the end of the *t*-th iteration of the main loop of the algorithm (lines 2–7). By A^0 , we denote the initial empty allocation.

The proof is split in two parts in which we focus on showing that the output allocation is EF1 (part 1) and PO (part 2).

Part 1: The output allocation is EF1.

Let e_k denote a vector with all zeros except for 1 in the *k*-th position. Also, let X^t be the set of all unavailable chores at the end of iteration *t*, i.e., allocated chores from which there is no alternating path ending in an unallocated chore. Let us show two claims that correspond to Claim 1a and Claim 1b from the proof of Theorem 3. First, let us show that unavailable chores do not become available.

Claim 1. For every iterations $t, t' \in [m]$ such that t < t', it holds that $X^t \subseteq X^{t'}$.

Proof. The proof is almost identical to that of Claim 1a in the proof of Theorem 3. It suffices to show that $X^{t-1} \subseteq X^t$, for every $t \in [m]$. Take an arbitrary chore $c \in X^{t-1}$. Observe that every chore c' such that there is an alternating path starting in c and ending in c' has to be unavailable. Thus, all of these chores will not change the ownership in iteration t. Thus, they will remain unavailable, i.e., $c \in X^t$.

The second claim ensures that agents weakly prefer their chores over the available ones.

Claim 2. For every agent $i \in N$, iteration $t \in [m]$, and chore $c \in A_i^t$, it holds that $c \succeq_i c'$, for every $c' \in M \setminus X^{t-1}$.

Proof. The proof is similar to that of Claim 1b in the proof of Theorem 3. Assume by contradiction that there exists $c \in M \setminus X^{t-1}$ such that $c \succ_i c'$ for some $c' \in A_i^t$. Let k be such that $c' \in \triangleright_i(k)$ and let $t' \in [m]$ be the first iteration in which i received a chore, c'', from its k-th or earlier indifference class. Thus, $t' \leq t$. Since all chores in $A_i^{t'-1}$ are preferred over chore c'', agent i could not obtain it in line 5 of the algorithm, by the definition of the alternating path. Hence, i received it in line 6. However, by Claim 1, chore c was also available at the end of iteration t' - 1. Therefore, since $c \succ_i c' \succeq_i c''$, agent i should receive c instead of c''—a contradiction.

Next, let us show how the score vectors of agents are changing as the algorithm progresses.

Claim 3. For every agent $i \in N$ and iteration $t \in [m]$ it holds that

$$s_i(A_i^t) = \begin{cases} s_i(A_i^{t-1}), & \text{if } i \text{ is not chosen in line 3 of iteration t} \\ s_i(A_i^{t-1}) - e_k, & \text{otherwise} \end{cases}$$

where $k \in [k_i]$ is the number of the last indifference class of i with available chores, i.e., $s_i(k, M \setminus X^t) > 0$.

Proof. First, consider iteration $t \in [m]$ such that i is not chosen in line 3. Then, the bundle of i can change only due to an alternating path. By definition of an alternating path agent i cannot get worse off, i.e., $s_i(A_i^t) \ge_{lex} s_i(A_i^{t-1})$. Assume by contradiction that $s_i(A_i^t) >_{lex} s_i(A_i^{t-1})$. This means that there is a chore $c \in A_i^{t-1} \setminus A_i^t$ that got exchanged for $c' \in A_i^t \setminus A_i^{t-1}$ such that $c' \succ_i c$. This means that c' was available at the end of iteration t - 1, so, by Claim 1 also t - 2. However, this contradicts Claim 2. Hence, $s_i(A_i^t) = s_i(A_i^{t-1})$.

Now, if in iteration $t \in [m]$ agent *i* is chosen in line 3, then in line 6 it receives an available chore from its last possible indifference class. The thesis follows.

Now, let us move to the main observation of the proof that is Claim 4. Intuitively, the following claim guarantees that an agent that is just about to pick a chore, i, does not envy any other agent. However, it is even a bit stronger than that. Denote by k the first indifference class of agent i from which i has some chores, i.e., $s_i(k, A_i^t) > 0$. Then, the claim guarantees that agent i would not envy other agents, even if we move all allocated chores from the first k indifference classes of i to the k-th class of i. For this purpose, some additional notation will be helpful. For every agent $i \in N$, indifference class $k \in [k_i]$, and a subset of chores $X \subseteq M$, let us denote the score vector of i with the first k-th positions merged as $s_i^k(X) = (\sum_{u \in [k]} s_i(u), s_i(k+1), \ldots, s_i(k_i - k + 1))$.

Claim 4. For every agent $i \in N$, iteration $t \in [m]$, and $k \in [k_i]$ such that agent i is chosen in line 3 of the algorithm in iteration t+1 and k is the first indifference class of i such that $s_i(k, A_i^t) > 0$ or $k = k_i$ if $s_i(A_i^t) = (0, \ldots, 0)$, it holds that $s_i^k(A_i^t) \ge_{lex} s_i^k(A_i^t)$, for every agent $j \in N$.

Proof. Assume otherwise and take the first iteration t for which there exist agents $i, j \in N$ such that i is chosen in line 3 of the algorithm in iteration t + 1, and $s_i^k(A_i^t) >_{lex} s_i^k(A_i^t)$.

Observe that t > n (otherwise, agent *i* has no chores at the end of iteration *t*). Let t' = t - n. Note that agent *i* is chosen in line 3 of the algorithm in iteration t' + 1 and, by Claim 3, receives a chore from its *k*-th indifference class in line 6. Thus, from the minimality of *t*, we get that $s_i^{k'}(A_i^{t'}) \ge_{lex} s_i^{k'}(A_j^{t'})$, where k' is the first indifference class such that $s_i(k', A_i^{t'}) > 0$. Since $k' \ge k$, this implies that

$$s_i^k(A_i^{t'}) \ge_{lex} s_i^k(A_j^{t'}). \tag{15}$$

Since in iteration t' + 1 agent *i* gets a chore from its *k*-th class, all of the chores from its later classes are no longer available. Thus, the chores from these classes cannot change owners between iteration t' and t. In particular, agent *j* has the same chores from these classes in t' and t. Since in line 3 of some iteration between t' + 1 and t agent *j* receives an additional chore, which has to be in the first *k* indifference classes of *i*, we get that $s_i^k(A_j^t) = s_i^k(A_j^{t'}) - e_1$. Therefore, by Claim 3 and equation (15),

$$s_i^k(A_i^t) = s_i^k(A_i^{t'}) - e_1 \ge_{lex} s_i^k(A_j^{t'}) - e_1 = s_i^k(A_j^t),$$

which is a contradiction.

Now, let us prove the main theorem. Fix arbitrary $i, j \in N$. We will show by induction that for every iteration $t \in [m]$ it holds that $s_i(A_i^t) + e_k \ge_{lex} s_i(A_j^t)$, where k is the first indifference class of i such that $s_i(k, A_i^t) > 0$, or $k = k_i$, if $s_i(A_i^t) = (0, ..., 0)$. Since there exists a chore $c \in A_i^t$ such that $s_i(A_i^t \setminus \{c\}) = s_i(A_i^t) + e_k$, this will imply that A^t is EF1. Clearly, for t = 0 the thesis holds. Assume that the thesis holds for some $t \in [m]$ and consider iteration t + 1. Let k be the first indifference class such that $s_i(k, A_i^{t+1}) > 0$ or let $k = k_i$ if i does not have chores. By Claim 2, the chores from the later than k-th indifference classes of agent i are not available. Hence, agent j has the same chores from these classes in t and t + 1. Thus,

$$s_i^k(A_i^{t+1}) + e_k = s_i^k(A_j^t) \ge_{lex} s_i^k(A_j^{t+1})$$
(16)

(the inequality is only possible if *j* received an additional chore in line 6 of the iteration t + 1).

If *i* was chosen in line 3 of iteration t + 1, then, by Claim 4, we have $s_i^k(A_i^t) \ge_{lex} s_i^k(A_j^t)$. Let *c* be a chore that *i* received in line 6 of iteration *t*. Then, by Claim 3 and Equation (16),

$$s_{i}^{k}(A_{i}^{t+1} \setminus \{c\}) = s_{i}^{k}(A_{i}^{t}) \geq_{lex} s_{i}^{k}(A_{j}^{t}) \geq_{lex} s_{i}^{k}(A_{j}^{t+1}).$$

Since $s_i(k', A_i^{t+1} \setminus \{c\}) = 0$ for every k' < k, this implies the inductive thesis.

Thus, let us assume that i was not chosen in line 3 in iteration t + 1. Then, by Claim 3, Equation (16), and the inductive assumption,

$$s_i^k(A_i^{t+1}) + e_k = s_i^k(A_i^t) + e_k \ge_{lex} s_i^k(A_j^t) \ge_{lex} s_i^k(A_j^{t+1}).$$

Again, the fact that $s_i(k', A_i^{t+1} \setminus \{c\}) = 0$ for every k' < k, implies the inductive thesis.

Part 2: The output allocation is PO.

The proof of PO is similar to the respective part in the proof of Theorem 3. We will prove that for every $t \in \{0, \ldots, m\}$, allocation A^t is PO. Assume otherwise and take the first t such that A^t is not PO. By Theorem 5, this means that there is an alternating path, $p = (c_0, i_1, c_1, \ldots, i_s, c_s)$ and agent i_0 such that $(c_s, i_0) \in A^t$ and $\psi(i_0, c_0) > \psi(c_s, i_0)$. Since A^{t-1} is PO, either $(c_s, i_0) \notin A^{t-1}$ or p is not an alternating path for A^{t-1} . In both cases, at least one chore on path p belongs to different agents in A^t and A^{t-1} . Let us take the first on the path such chore c_u , i.e., such that $u \in [s]$ is the smallest. Observe that c_u is available in t - 1. Also, the part of path p that is $(c_0, i_1, c_1, \ldots, i_u, c_u)$ is still an alternating path in A^{t-1} as chores c_0, \ldots, c_{u-1} belong to the same agents in A^t and A^{t-1} . Both facts imply, that c_0 is available in t - 1. Hence, by Claim 2, agent i_0 weakly prefers each of its chores in A^t over c_0 . However, this contradicts the fact that $\psi(i_0, c_0) > \psi(c_s, i_0)$ and $(c_s, i_0) \in A^t$.

G PO Characterization for Chores

In this appendix, we present the proof of the PO characterization for weakly lexicographic chores only instances.

Theorem 5. Given a weakly lexicographic chores-only instance (N, M, \triangleright) , an (possibly partial) allocation A is PO, if and only if, there is no alternating path, $p = (c_0, i_1, c_1, \ldots, i_s, c_s)$ and agent i_0 such that $(c_s, i_0) \in A$ and $\psi(i_0, c_0) > \psi(c_s, i_0)$.

Proof. If there exists such alternating path and agent i_0 , then let us obtain A' from A by updating it along this path, i.e., $A' = A \setminus \{(c_s, i_0)\} \setminus \{(c_{r-1}, i_r) : r \in [s]\} \cup \{(i_r, c_r) : r \in \{0, \ldots, s\}\}$. From the definition of alternating path, for every $r \in [s]$, agent i_r weakly prefers its bundle in A' over its bundle in A. Moreover, i_0 strictly prefers its bundle in A'. Thus, we get that A' Pareto dominates A.

Thus, it remains to show that if A is not PO, then there exists an alternating path and agent i_0 in question. Take an arbitrary A' that Pareto dominates A and for which the number of reallocated chores, i.e., $\sum_{i \in N} |A_i \setminus A'_i|$, is minimal. By $N' = \{i \in N : A'_i \neq A_i\}$ let us denote the set of agents with different bundles in A' and A.

For every agent $i \in N'$, by x_i let us denote the first position such that $s_i(x_i, A_i \setminus A'_i) > 0$ (observe that there always exists such x_i since i cannot just receive chores without giving away any). For every chore $c \in M$ and agent $i \in N'$ such that $c \in A_i \setminus A'_i$, let us use $b_c(i)$ to denote agent j that has c in A', i.e., $c \in A'_i \setminus A_j$.

Next, let us consider a directed multigraph, G = (N', E) in which the set of vertices is N' and for every agent $i \in N'$ and chore $c \in \triangleright(x_i, A_i \setminus A'_i)$ we put an edge $(i, b_c(i))$. Intuitively, graph G denotes who has to give the chores to whom to convert A to A' (where we take into account only the most important chores from the perspective of the giver).

Observe that every vertex in G has an outgoing edge. Hence, there has to be a cycle, $C = (i_0, i_1, i_2, \ldots, i_s)$. For every $r \in [s]$, let c_{r-1} be a chore that is "given" by i_r to i_{r-1} and c_s by i_0 to i_s , i.e., $b_{c_{r-1}}(i_r) = i_{r-1}$ and $b_{c_s}(i_0) = i_s$. Fix $r \in [s]$. Since c_{r-1} is in the x_{i_r} -th indifference class of agent i_r chore c_r has to be in the class x_{i_r} or further otherwise agent i_r would strictly prefer its bundle in A over A'. Similarly, chore c_s has to be in the class, i.e., not higher, then consider i_0 . If for every $r \in \{0, \ldots, s\}$ it would be in exactly x_{i_r} -th class, i.e., not higher, then consider A'' obtained from A', i.e., $A'' = A' \setminus \{(c_{r-1}, i_r) : r \in [s]\} \setminus \{(c_s, i_0)\} \cup \{(c_r, i_r) : r \in \{0, \ldots, s\}\}$. Observe that every agent is indifferent between the bundles in A'' and A'. Hence, A'' also Pareto dominates A. However, $\sum_{i \in N} |A_i \setminus A''_i| < \sum_{i \in N} |A_i \setminus A''_i|$, which is a contradiction. Thus, there exists an agent i_r in the cycle C that strictly prefers the new chore to the old one. Without loss of generality, let us assume that r = 0, i.e., c_0 is in the later indifference class of i_0 than x_{i_0} . Then, observe that $(c_0, i_1, c_1, \ldots, i_s, c_s)$ is an alternating path for allocation A such that $(c_s, i_0) \in A$ and $\psi(i_0, c_0) > \psi(c_s, i_0)$, which concludes the proof.