German Beams The Story of Particle Accelerators in Germany

Volker Ziemann, Uppsala University, Uppsala, Sweden

May 7, 2024

Abstract

Even though many of the experiments leading to the standard model of particle physics were done at large accelerator laboratories in the US and at CERN, many exciting developments happened in smaller national facilities all over the world. In this report we highlight the history of accelerator facilities in Germany.

In *Beams*¹ I describe the co-evolution of particle accelerators and the standard model of elementary particles. The majority of these experiments were done at the large laboratories in the US and at CERN. There are, however, so many other accelerators doing important experiments that it would be a shame not to briefly talk about them as well. In the coming sections I will tell the story of accelerators in Germany.

Prehistory

The first particle accelerator in Germany was the linear accelerator that Wideroe built for his PhD thesis (Chapter 4)² in 1927. Around 1936, rather than a linear accelerator, Gentner and Bothe³ constructed a van de Graaff accelerator (Figure 4.1) at the Kaiser-Wilhelm Institute of Medical Science in Heidelberg. Once completed they used it for experiments in nuclear physics. Assembling the machine had progressed very quickly and encouraged them to think about a bigger accelerator—a cyclotron (Figure 4.4). Already in 1938 Wolfgang Gentner traveled to Berkeley and established contact with the group of Lawrence, the inventor of the cyclotron. As a result he obtained blueprints for many parts needed to

¹V. Ziemann, *Beams—the Story of Particle Accelerators and the Science they Discover*, Copernicus Books, Springer 2024.

 $^{^{2}}$ All references to chapters, sections, and figures refer to "Beams" mentioned in footnote 1.

³Walther Bothe (1891-1957) received the Nobel Prize in Physics in 1954 "for the coincidence method and his discoveries made therewith." See also https://www.nobelprize.org/prizes/physics/1954/.

construct his cyclotron. By 1941—the Second World War had already broken out—Gentner and Bothe had secured funding. Immediately they started designing the new cyclotron and ordered the main components. During the spring of 1943 the 70-ton magnet arrived and by the end of the year the cyclotron produced deuterons with an energy of 12 MeV. It operated into the 1970s.

The cyclotron in Heidelberg was not the only one. Several others were planned in Berlin, Leipzig, and Bonn.

Bonn

In Bonn, a smaller 1.5 MeV cyclotron was constructed at about the same time as Gentner's machine in Heidelberg. Sadly it was destroyed during an allied bomb raid in October 1944.

It took until 1952, after having learned about alternating-gradient focusing (Chapter 6), that Wolfgang Paul⁴ applied for funds to build a 100 MeV electron synchrotron (Chapter 8) in Bonn. Remarkably, the funding agency suggested to increase the energy to 500 MeV. After suitably adapting the application, the project was approved and resulted in the first alternating-gradient synchrotron in Europe⁵. After designing the machine with its 16 m circumference throughout the following years, often with the help of young students, construction commenced in 1955. It took three years until all components were delivered and installed. But then a crisis struck because it was realized that the magnetic field was unsuitable for stable operation. The problem was eventually solved by sandwiching plywood sheets between magnets which sufficiently changed the fields to allow stable operation. By the spring of 1958, first beams were available and even synchrotron radiation was observed. In the following years the beams were directed onto tungsten targets in order to produce "bremsstrahlung" which are just highly energetic gamma rays. By directing these gamma rays onto protons or deuterons and observing the scattering products (Chapter 2) much was learned about the structure of atomic nuclei. The experimental program continued until 1984, when the 500 MeV synchrotron was dismantled to make space for ELSA, discussed below.

Already a few years after the 500 MeV synchrotron produced beams, the need for a larger electron synchrotron, reaching 2500 MeV, became apparent. Towards the end of 1963, the state government provided funds, such that design of the accelerator could start⁶. With a circumference of almost 70 m it became substantially larger than its smaller brethren. Four years later the first electrons were

⁴Wolfgang Paul (1913-1993) received the Nobel Prize in Physics in 1989 "for the development of the ion trap technique." See also https://www.nobelprize.org/prizes/physics/1989/.

⁵For the history of this machine see: B. Mecking, *Das Bonner 500 MeV Elektronensynchrotron*, Bonn-IR-85-02 (in German).

⁶K. Althoff et al., *The 2.5 GeV Electron Synchrotron of the University of Bonn*, Nuclear Instruments and Methods 61 (1968) 1.

injected from a 25 MeV linear accelerator into the new synchrotron and accelerated up to the design energy. After a while the beams could even be extracted and directed towards a number of experimental stations, where they impinged on a variety of targets, often containing protons or deuterons. The machine operated in this mode until 1984, at which point the ELectron-Stretcher-Accelerator ELSA was constructed adjacent to the larger synchrotron.

Synchrotrons provide a short burst of beams, typically 50 times per second, but many experiments desire a continuous stream of electrons. One solution is to inject the short burst into a larger so-called stretcher ring. In this ring one or several pulses from the synchrotron are collected before the stored electrons are slowly extracted and guided to experiments. The project already went under way in the early 1980s, but it took until 1989 to complete the construction of ELSA⁷ with its circumference of 164 m and to connect it to the larger synchrotron that was used as an injector. Once the electrons were inside ELSA, they could be slowly extracted, just as was initially planned. Even accelerating the beams and extracting them at higher energies became possible. Finally, beams could be accumulated in ELSA and stored for several hours to provide synchrotron radiation. In this way, ELSA doubled up as a synchrotron light source (Section 13.1).

Much expertise was generated by constructing the smaller synchrotron, being the first of its kind. And that competence came handy when a larger synchrotron was planned in Hamburg.

DESY

By 1955 Germany had regained part of its sovereignty and was permitted to create a ministry for nuclear energy. Moreover, this new ministry was willing to fund an institute for research in particle physics; the creation of CERN in Geneva the previous year served as a inspiration. Incidentally, at that time Hamburg University offered a professorship to the US-based Austrian scientist Willibald Jentschke, who accepted after being granted substantial funds to create a new department, which served as the nucleus for what would later become DESY⁸.

The type of accelerator was settled at a conference in Geneva the following year. Instead of a proton synchrotron, which would be in direct competition with the accelerator at CERN (Chapter 6), Jentschke decided to build an electron synchrotron (Chapter 8) with the unprecedented energy of 6 GeV, more than ten times the energy of the first synchrotron in Bonn. During the following years negotiations between federal and state agencies led to the constitution of the "Deutsches Elektronen SYnchrotron" DESY in December 1959. An abandoned

⁷For an account of the history leading to construction of ELSA, see: W. Hillert, *The Bonn Electron Stretcher Accelerator ELSA: Past and future*, Eur. Phys. J. A 28, s01 (2006) 139.

⁸For a comprehensive account of DESY's first fifty years, see: E. Lohrmann, P. Söding, *Von schellen Teilchen und hellem Licht*, Wiley-VCH Weinheim, 2009 (in German). The second edition from 2013 is available online from https://bib-pubdb1.desy.de/record/374686.



Sketch of the accelerators at DESY.

airfield in the suburb of Bahrenfeld was selected as the site to house a 40 MeV linear accelerator, used as injector, and the 300 m long synchrotron. It took until 1964 for the first beams to be accelerated. Fifty times per second a new batch reached top energy, was ejected from the synchrotron, and directed towards experimental stations.

The first experiments pointed the electrons onto hydrogen-rich targets and analyzed the scattering products in spectrometers, conceptually similar to Hofstadter's experiments discussed in Chapter 7. A second group of experiments directed the electrons onto a target where they produce gamma-ray photons that are then impinged onto protons. Subsequently the photon-induced reactions and scattering products are analyzed. A third group of experiments directed the electrons into a bubble chamber (Figure 5.5), photographing the tracks, and analyzing the reactions that show up. Right after beams became available, the copious synchrotron radiation emitted by the 6 GeV electrons was characterized and used for first experiments.

Already a few years after the synchrotron started to operate, ideas were discussed to build a second accelerator in which electrons and positrons would circulate in opposite directions and collide head-on (Figure 8.1). In this way much more energy would become available for new particles to emerge from the fireball at the collision points. There detectors stood by to record the escaping particles. At the time it was deemed advantageous to store electrons and positrons in separate rings, mounted on top of each other. This new storage ring was given the name DORIS (derived from the German "DOppel-RIng Speicher"). It had a circumference of 288 m and initially stored electrons and positrons with energies of up to 3 GeV.

Towards the end of 1974, the two detectors PLUTO and DASP were placed in their respective collision points. At just this time SLAC and Brookhaven discovered the very sharp resonance made of charm and anticharm quark (Chapter 8), an event later referred to as the "November revolution." DORIS verified these discoveries within a very short time and then successfully searched for mesons consisting of one charm and one other quark. Later it engaged in the detailed analysis of many bound states, an activity that was dubbed "charmonium spectroscopy." Just as upgrading DORIS to higher energies was under way, the Upsilon as a bound state of two bottom quarks was discovered at Fermilab in 1977 (Chapter 9). Luckily the magnets were already somewhat over-designed from the beginning and could handle the higher energies. Nevertheless, additional components and smart ideas were asked for to eventually reach close to 5 GeV per beam which made the production of Upsilons possible. Observing their decay into muon and electron pairs were important ingredients to determine the charge of the bottom quark. DORIS then embarked on a campaign to determine other properties of the quarks and the strong interaction.

In order to consolidate operating at higher energies DORIS was upgraded in 1982 to reemerge as DORIS II. It now stored electrons and positrons in a single ring, rather than the "Doppel-ring" that gave DORIS its name. The higher energies of 5.6 GeV per beam allowed the two new detectors, ARGUS and Crystal Ball, to investigate pairs of *B*-mesons and their antiparticles \bar{B} , each containing a bottom quark and one other quark. This led to the first observation of $B-\bar{B}$ mixing, a process closely linked to the prevalence of matter over antimatter in our universe that is referred to as CP-violation (Chapter 10).

All the time, the number of synchrotron-radiation users increased. A large laboratory building housing their experiments was completed by 1982 and was dubbed "Hasylab," derived from "HAmburger SYnchrotron LABoratory." Increasing demands led to yet another upgrade to DORIS III in 1991, now equipped with an outward-bulging no-longer-straight section. There five wigglers and undulators (Section 13.1) were installed to increase the flux and the quality of the emitted synchrotron radiation. By that time most particle physics activities concentrated on the next-generation colliders PETRA and HERA such that from 1993 until 2012 DORIS operated solely to produce synchrotron radiation. Research highlights include Ada Yonath's studies⁹ of ribosomes, the engines that produce proteins in cells.

Already by the time DORIS was starting up, discussions about the next generation of accelerators were picking up speed and converged towards the electron-

⁹Ada Yonath (b. 1939) received the Nobel prize in Chemistry "for studies of the structure and function of the ribosome." See also https://www.nobelprize.org/prizes/chemistry/2009/.

positron collider PETRA (from the German "Positron-Electron Tandem RingbeschleunigerAnlage"). With a circumference of 2.3 km it was the largest ring that would fit onto the DESY site. It should reach more than 20 GeV per beam and provide four collision points for experiments housing the detectors TASSO, MARK J, JADE, and PLUTO; the latter was later replaced by CELLO. Approval came in 1975 and less than three years later the beams were colliding. The hope to find the sixth quark, called top, remained unfulfilled. It turned out to be much too heavy for PETRA and other rings of similar size. Instead, the highlight of research on PETRA was the discovery of gluons through the observation of three-jet events (Figure 8.7), already mentioned towards the end of Chapter 8. Many careful measurements revealed intricate details of subatomic interactions and contributed to establishing quantum chromodynamics as a valid theory of the strong interaction (Chapter 7). Moreover, many aspects of the electroweak interaction (Chapter 6) were explored. The experimental program continued until the end of 1986. At that time PETRA was needed as injector for an even larger ring, the "Hadron-Electron Ring Accelerator" HERA.

After plans to add a proton ring inside the PETRA tunnel were abandoned, a proposal to build a new 6.3 km long underground tunnel was put forward. This tunnel would house HERA comprising a 820 GeV proton and a 30 GeV electron ring. Head-on collisions of electrons and protons at these energies would allow the experimenters to probe the inside of the proton much more accurately than was possible in the deep-inelastic scattering experiments at SLAC (Chapter 8). After a period of negotiations the project was approved in 1984 and construction could start. A large tunnel-boring machine, similar to the one that dug the tunnel of LEP (Chapter 10) drilled the 6.3 km long tunnel 10 m to 20 m below the surface. The DESY synchrotron, rebuilt and called DESY II, as well as PETRA were used to accelerate the electrons. Accelerating protons, on the other hand, was new for DESY and a second synchrotron for protons, called DESY III, was installed alongside the venerable electron synchrotron. Additional components were added to PETRA, now called PETRA II, that allowed it to accelerate protons. The electron ring of HERA is fairly conventional, but the magnets for the proton ring had to be superconducting in order to fit the high-energy beams into the tunnel, just as the Tevatron needed superconducting magnets at Fermilab (Chapter 9). After meticulous development work at DESY the manufacture of the 750 up to 9 m long magnets was transferred to industry, half in Germany, the other half in Italy. The magnets were cooled to low temperatures by the, at the time, largest Helium liquefaction plant in Europe. After installing and testing many more components, HERA was inaugurated towards the end of 1990. Commissioning all subsystems, including the detectors H1 and ZEUS, took more time but by 1992 first collisions were observed. Later even two additional detectors, HERA-B and HERMES, were installed.

The detectors extended the deep-inelastic scattering results, pioneered at the SLAC linac, to much smaller distances inside the proton, thereby validating the

standard model. In particular, the momentum distribution of the quarks inside protons was measured with unprecedented accuracy. Moreover, there appeared to be additional quark-antiquark pairs bouncing around inside protons. Even previously unseen reactions that have their origin in the weak interaction were found; only a single shower of hadrons appeared besides an unobservable neutrino. Its existence was inferred by balancing the energy and the momentum of the observed ejectiles. Experiments in HERA continued until 2007, when the accelerator was turned off, because DESY started to build the European XFEL, a large free-electron laser (Section 13.2) to produce X-rays. With HERA turned off, PETRA was no longer needed as injector and one octant was be refurbished to house undulators that generate copious amounts of high-quality synchrotron radiation. The rebuilt machine was called PETRA III. As of 2024, even a further upgrade, called PETRA IV, to improve the amount and quality of the emitted radiation, is actively discussed.

The work towards the XFEL started from designing a linear electron-positron collider (Chapter 12) called TESLA, that would use superconducting accelerating structures (Chapter 10). In order to broaden the number of users beyond the particle physics community, an X-ray free-electron laser was added to the proposal; it would serve the community of synchrotron radiation users. In order to test the concept—both the accelerating structures and the free-electron laser—a $100 \,\mathrm{m}$ long superconducting linac accelerated beams to about $250 \,\mathrm{MeV}$ and passed them through a 13 m long undulator magnet. With all parameters tuned just right, the machine would emit a high-intensity free-electron laser pulse (Section 13.2). This Tesla-Test Facility (TTF) was constructed on the DESY site and produced very short-wavelength light pulses in 2000. Shortly afterwards the machine, renamed FLASH¹⁰ (for "Free-Electron LASer in Hamburg"), was rebuilt to increase the energy to 1000 MeV. Moreover, a new undulator, now 30 m long, led to first lasing at much shorter wavelengths by 2004. Continued upgrades and an additional undulator have vastly enhanced the capabilities of FLASH. In one of the many experimental highlights the scattered light from a microscopic sample was processed to reconstruct the sample with high fidelity; a precursor to determine the structure of many otherwise inaccessible biomolecules.

But originally TTF was constructed to develop the superconducting accelerating structures that were successfully used in TTF and FLASH. Despite this success the application to build TESLA was turned down. Instead, based on the success of the free-electron laser program, the funding agencies supported the construction of a much larger version of FLASH, the European XFEL. About two thirds of this 3.2 km long machine is filled with superconducting structures to reach beam energies close to 20 GeV. The last third is filled with several-hundred-

¹⁰For a comprehensive review see: J. Rossbach, J. Schneider, and W. Wurth, 10 years of pioneering X-ray science at the Free-Electron Laser FLASH at DESY, Physics Reports 808 (2019) 1.

meter-long undulator magnets that produce ultra-short and super-intense pulses of X-rays. Since the completion of the facility in 2017, this radiation permits experimenters to investigate the structure of proteins, make time-resolved measurements ("movies") of chemical reactions, and explore matter under extreme conditions.

At DESY, a particle physics lab was slowly converted to one that pursues synchrotron radiation research. In Berlin, on the other hand, a facility dedicated to the generation of this radiation right from the start was constructed.

BESSY in Berlin

By 1975, both the accelerators in Bonn and Hamburg were producing synchrotron radiation, quasi on the side, but the demand was growing. As a consequence a review was conducted and found that two storage rings, dedicated to the production of synchrotron radiation, were needed. A larger one for the production of X-rays that turned out to be DORIS and a smaller machine to generate radiation with lower energies. The formal decision to build the latter came in 1979 and construction of BESSY (derived from "Berliner ElektronenSpeicherring Gesellschaft für SYnchrotronstrahlung") soon commenced¹¹. Less than three years later, beams, accelerated in a small pre-accelerator, and an injector synchrotron to 800 MeV, were injected into the BESSY storage ring having a circumference of $62 \,\mathrm{m}$. Throughout the 1980s and 1990s the beam quality and intensity were improved and with it the quality of the synchrotron radiation that escaped the beam pipe through 35 windows. Highlights of the instrumental developments are new types of undulator magnets¹² (Section 13.1) and methods to ensure the quality of optical components that guide and focus the synchrotron light on its way to the experimental stations.

Highlights of the experimental program are Peter Grünberg's experiments on what was later called giant magnetoresistance. This effect led the way to vastly increased storage capacities of hard drives in our computers and was honored with a Nobel Prize in Physics¹³. Surface physics and catalysis are other fields of endeavor that were pursued at BESSY. These phenomena are tremendously important to facilitate difficult chemical reactions, such as converting toxic gases in car exhausts to more benign chemicals. The high impact of this research contributed to Gerhard Ertl's Nobel Prize in Chemistry¹⁴.

¹¹D. Einfeld, G. Mühlhaupt, *Choice of the Principal Parameters and Lattice of BESSY, an* 800 MeV Dedicated Light Source, Nuclear Instruments and Methods 172 (1980) 55.

¹²Of particular interest are so-called Apple undulators that allow to adjust the polarization of the emitted radiation. Today they are used in practically every synchrotron light source.

¹³Peter Grünberg (1939-2018) received the Nobel Prize in Physics in 2007 "for the discovery of giant magnetoresistance." See also https://www.nobelprize.org/prizes/physics/2007/.

¹⁴Gerhard Ertl (b.1936) received the Nobel Prize in Chemistry in 2007 "for his studies of chemical processes on solid surfaces." See also https://www.nobelprize.org/prizes/

The distribution of wavelengths—the spectrum—and the intensity of the emitted radiation can be calculated from first principles and only depends on very few beam parameters. Since those quantities can be very accurately measured, the emitted radiation is known with high confidence and can be used to calibrate other measurement devices, such as spectrometers. These activities were driven under the auspices of the German authority for measurements, abbreviated PTB¹⁵. In particular, they were responsible for the calibration of instruments for two spacetelescopes, SOHO and Chandra. The accelerator operated until 1999 and was then packed up and shipped to Jordan, where it was reassembled and now serves as injector for SESAME, the first synchrotron light source in the middle-east.

A few years after the first BESSY storage ring started to produce light in the early 1980s, proposals for several so-called third-generation light sources with vastly improved quality and intensities were discussed world-wide. Such an accelerator would be several times larger than BESSY and would not fit within the limits of the original site in West-Berlin. With the fall of the Berlin wall in 1989, however, new options appeared and a site in former East-Berlin was chosen to become the home of BESSY-II¹⁶. Construction started in 1993 and five years later an injector synchrotron filled the new BESSY-II storage ring, having a circumference of 240 m and operating at 1.7 GeV for the first time. A year later first photons, produced in special undulator magnets but also in the magnets that keep the beam on its circular path, were served to users. The photons follow a straight path and escape from the beam pipe to travel via more than forty so-called synchrotron beam lines towards the experimental stations.

With higher beam energies, radiation in the X-ray region could be produced. It was used to analyze the structure of materials and of proteins. Even the structure of proteins of the Covid virus were determined at BESSY-II. A further very active field of research addresses materials for new batteries and for high-temperature superconductors. Both aspects are particularly relevant to improve the efficiency of energy utilization. Even the PTB continues to calibrate instruments with the help of BESSY-II, especially at higher photon energies. The reduced availability of lower-energy photons caused the PTB to construct a second smaller ring, the "Metrology Light Source" (MLS) adjacent to the BESSY-II site.

Construction of the MLS¹⁷ started in 2004 and first beams became available in 2008, predominantly for metrology applications, such as calibrating spectrom-

chemistry/2007/.

¹⁵PTB is a acronym, derived from "Physikalisch Technische Bundesanstalt."

¹⁶For more background on BESSY-II, see the brochure: 25 Years of BESSY-II: A Success Story in Berlin-Adlershof, special edition of "Lichtblick" from September 2023; online available from the following web page https://www.helmholtz.de/en/newsroom/article/ 25-years-of-bessy-ii-light-source-for-the-good-of-society/.

¹⁷G. Brandt et al., The Metrology Light Source – The new dedicated electron storage ring of PTB, Nuclear Instruments and Methods B258 (2007) 445.

eters but also other sources of light used in industrial processes or in scientific applications. The MLS has a circumference of 48 m and stores electron beams with energies between 105 MeV and 630 MeV. Remarkably, the MLS reproducibly stores beam intensities ranging from a single electron to several ten billions of electrons, with the intensity of the emitted radiation covering the corresponding range. Moreover, the synchrotron radiation covers the far infrared to the extreme ultraviolet. It thus extends from far below the visible spectrum to significantly above. Since the properties of the emitted radiation can be calculated from first principles, the MLS serves as a "standard candle" to calibrate other sources or spectrometers.

Bessy and DESY were not the only laboratories producing synchrotron radiation. Towards the end of the millennium, mid-size electron accelerators appeared in several other places, among them Dortmund.

Dortmund

Following the decision on the European level to locate the European Synchrotron Radiation Facility in Grenoble instead of Dortmund, negotiations on the regional level succeeded to secure funds for building a smaller accelerator, the "Dortmund ELectron Test Accelerator" DELTA¹⁸. Construction started in 1990 and and by the second half of the 1990s first beams were accelerated in a linac and a synchrotron to 1.5 GeV before they were stored in the DELTA storage ring with a circumference of 115 m. The declared purpose of DELTA was developing and testing of components for larger facilities, preparing experiments with synchrotron radiation, educating a new generation of accelerator builders¹⁹, and a first free-electron laser experiment called FELICITA²⁰.

After the free-electron laser experiment was successfully completed the demand for synchrotron radiation from the user community increased. As a consequence the originally foreseen program was ramped down while the production of photons to serve users was ramped up. The increased demand was then satisfied by installing additional wigglers and undulators to increase the experimental capabilities to provide an increasing number of users with synchrotron radiation.

¹⁸D. Nölle et al., *DELTA a new storage-ring-fel facility at the University of Dortmund*, Nuclear Instruments and Methods A296 (1990) 263.

¹⁹I am one of the substantial number of graduates that emerged from DELTA and populate accelerator labs all over Europe.

²⁰D. Nölle et al., *First lasing of the FELICITA I FEL at DELTA*, Nuclear Instruments and Methods A445 (2000) 128. FELICITA is an acronym for "Free-Electron Laser In a Circular Test Accelerator." It also happens to be the middle name of my wife; what a coincidence.

Karlsruhe

Before building the first linear accelerator (Chapter 4), Rolf Wideroe had already conceived the betatron (Chapter 4) while he was a student in Karlsruhe, though he was advised not to pursue the idea further. Much later, in the 1980s, ideas of building a much larger accelerator emerged and a storage ring for industrial applications of synchrotron radiation was proposed. This proposal was refined throughout the 1990s and led to the construction of ANKA (from "ÅNgströmquelle KArlsruhe"), an electron storage ring with a circumference of 110 m and a beam energy of $2.5 \,\text{GeV}^{21}$. It stored the first beams in 1999. The high beam energy and the large stored currents cause the emission of very intense X-rays that are directed to multiple experimental stations. Moreover, industry could simply purchase beam time from ANKA. This differs remarkably from the way how beam time is allocated in accelerators that operate for pure science. There it is assigned in a beauty contest—the scientifically most attractive experiments get beam time.

One of the prime uses of the radiation from ANKA and of particular interest for the semiconductor industry is the creation of microscopic mechanical structures—precursors of the accelerometers and gyroscopes found in modern phones—in a process called LIGA²², which is a type of X-ray lithography. The irradiation transfers the geometrical pattern of a microscopic mask onto a substrate that is covered by a protective film. In a second step the irradiated sections of the film are removed, and in a third step an acid etches the pattern into the substrate, for example, silicon. In another type of experiment the X-rays determine the structure of samples, including proteins, on atomic scales. The wavelength of the radiation that is transmitted to the samples can be adjusted in so-called monochromators to excite deep-lying energy levels of atoms. Since these levels are specific to the type of atom, very low concentrations of impurities in materials can be identified.

Following a restructuring of the laboratory in 2015, access to external users was limited and this was reflected by changing the name from ANKA to KARA (for "KArlsruhe Research Accelerator") and mainly using it for in-house developments²³. After the reorganization KARA was increasingly used to develop advanced beam diagnostic equipment such as ultra-fast cameras to explore the dynamics of charged particle beams on previously inaccessible time scales. Apart from developing other super-fast electronics components, new technologies, among them superconductivity, were used to construct undulators (Section 13.1)

²¹G. Buth et al., *Status of the 2.5 GeV Light Source ANKA*, Proceedings of EPAC 1998 in Stockholm, p. 635.

 $^{^{22}\}mathrm{LIGA}$ is the acronym derived from the German phrase "Lithographie, Galvanoforming, und Abformung."

²³A. Papash et al., *Different operation regimes at the KIT Storage Ring KARA*, Proceedings of IPAC 2021 in Campinas, p. 163.

and other very compact magnets, important for future accelerators.

In order to complement the very short-wavelength radiation from KARA, in 2017 the 12 m long linear accelerator $FLUTE^{24}$ (derived from the German "Ferninfrarot Linac Und Test Experiment") started to operate. It produces radiation with much longer wavelengths than KARA. FLUTE accelerates electron beams to 50 MeV, compresses them to a very short length, and then passes them through a thin foil, where ultra-short pulses of so-called THz radiation are produced. This radiation is immensely useful to study the dynamics of chemical bonds that bind atoms into molecules, a process of great importance in biology, as well as material and life sciences.

Dresden

Already in 1995 ideas were discussed to build a linear accelerator dubbed $ELBE^{25}$ in Rossendorf near Dresden that would deliver a continuous stream of electrons for experiments in nuclear and radiation physics²⁶. To keep operating costs for this linac reasonable the accelerator had to be superconducting. Moreover, high demands on the beam quality stimulated the development of high-performing electron sources. By 2001 the first 6 m long accelerator stage delivered beams up to 20 MeV, later a second stage was added and brought the energy to 40 MeV. A system of beam transport lines directs the electrons to several experimental areas²⁷.

There the electrons are used to drive two free-electron lasers producing farinfrared radiation that is used to probe material-science samples. The radiation is often used in so-called pump-probe experiments. First a sample is excited with a pulse from the free-electron laser and then a delayed second pulse from a conventional laser probes the sample. In this way, the temporal evolution of very fast processes can be investigated.

A specially developed electron source produces electron bunches that are shorter than the wavelength of the radiation emitted in a short undulator magnet. This causes a dramatically increased emission, because all electrons radiate in phase. The enhanced radiation level makes it possible to explore the properties of graphene, among other things.

The electrons are used for many other purposes. They are crashed into targets and produce very high-energy bremsstrahlung to probe the energy levels of nuclei.

 $^{^{24}\}mathrm{M.}$ Nasse et al., FLUTE: A versatile linac-based THz source, Rev. Sci. Instrum. 84 (2013) 022705.

²⁵ELBE is an acronym derived from "Electron Linear accelerator with high Brilliance and low Emittance," certainly inspired by the river Elbe that flows through Dresden.

 $^{^{26}\}mathrm{A.}$ Büchner et al., The ELBE-Project at Dresden-Rossendorf, Proceeedings of EPAC 2000 in Vienna, p. 732.

²⁷M. Helm et al., *The ELBE infrared and THz facility at Helmholtz-Zentrum Dresden-Rossendorf*, Eur. Phys. J. Plus (2023) 138.

Moreover, they are used to produce neutrons by crashing the beam into a liquidlead target. Even positrons can be produced. They are used to probe material defects in metals and in semiconductors.

Darmstadt

Inspired by Hofstadter's electron-scattering experiments in Stanford (Chapter 7), the nuclear physics department in Darmstadt purchased a 60 MeV linac from Varian Associates (Chapter 7). By 1962 the 10 m long linac, called DALINAC, started to produce beams that impinged on a variety of targets²⁸. The escaping particles were analyzed in spectrometers not unlike the one shown on Figure 7.4. In particular, details of the nuclear structure were determined by inelastically scattering electrons (middle image in Figure 7.3) from a large variety of nuclei, all the way up to uranium. The linac operated well into the 1980s at which time a more powerful linac with better beam quality was discussed.

The new accelerator was called S-DALINAC and consisted of a 16 m long linac based on superconducting radio-frequency structures (Chapter 10). Two recirculation arcs that allowed reusing the same linac three times, at which point the electrons reached 130 MeV and were directed to experimental areas. Instead of a pulsed beam, the new linac provided a continuous stream of electrons. First beams were accelerated in 1987 and henceforth used in nuclear physics experiments. Early on it was realized that the new linac could be used for a freeelectron laser (Section 13.2) as well²⁹. After installing additional hardware, the laser started to produce the first photons in 1996. These photons are routed to a separate room, dedicated to optical experiments.

Apart from experiments for nuclear physics and with the photons from the free-electron laser, S-DALINAC serves as a test facility to explore advanced manipulations with the beams themselves. In one of these experiments, the energy of the beam is recovered inside the structures that were used to accelerate it in the first place. The original beam is discarded, but its energy is reused to accelerate new beams, thus the machine becomes a so-called energy-recovery linac.

Not only electrons can be used in nuclear physics experiments, also accelerated beams of heavy ions provide suitable projectiles to explore the inner workings of nuclear matter. Close to Darmstadt, in a nearby village, a new lab appeared in the late 1960s.

 $^{^{28}{\}rm F.}$ Gudden et al., Eine Anordnung für Experimente zur Elektronenstreuung unterhalb 60 MeV, Zitschrift für Physik 181 (1964) 453 (in German).

²⁹V. Aab et al., *The Darmstadt near-infrared free-electron laser project*, Nuclear Instruments and Methods A272 (1988) 53.

GSI and FAIR

During the 1960s accelerators for heavy ions were discussed³⁰ as tools to analyze nuclear matter with methods that were complementary to those of high-energy proton or electron accelerators that were used to look inside protons and other sub-nuclear particles at the time. Instead, the new facility would focus on the collective behavior of large numbers of protons and neutrons inside heavier nuclei. As a consequence of these discussions, the "Gesellschaft für SchwerIonenforschung" (GSI) was founded in 1969 and the construction of the approximately 120 m long linear accelerator, called UNILAC, soon started. It was based on drift tubes developed by Wideroe (Figure 4.2) and Alvarez (Figure 5.3). However, with a diameter of 1.2 m the vacuum vessel is much larger. By 1975 it accelerated beams up to energies of 11 MeV per nucleon. The total energy of uranium with 238 nucleons (92 protons and 146 neutrons) is therefore in the GeV range. At these energies the speed of the uranium ions is about 16% of the speed of light. Soon experiments in two experimental areas commenced by impinging the heavy-ion beams onto targets. Detectors then analyze whatever scattering products escape from the point of impact.

Of particular interest is the distribution of fragments with different numbers of protons and neutrons (isotopes) that are created in the collision, because it shows how the nucleons are organized inside the nucleus. Thereby it probes the organization of nucleons into shells³¹. These experiments help us to better understand the stability of nuclei, especially in extreme situations as they occur in very heavy nuclei. Some of the lighter isotopes feature in the creation of heavier elements inside stars and supernovae, a process called "nucleosynthesis". In particular, measuring their masses and lifetimes helps us understand the relative abundance of different elements in our universe.

The heaviest naturally occurring element on the periodic table is uranium with atomic number 92. Since the 1940s heavier elements, so-called transuranium elements, were created in nuclear reactors and in accelerators. Once the UNILAC was up and running, it joined the search for previously unseen heavier elements. And indeed, between 1981 and 1984, the three elements with atomic numbers 107, 108, and 109³² were discovered at GSI. Bohrium with atomic number 107, for example, was created by slamming chromium ions into a bismuth target and then filtering the debris to select particles with a specific mass using an elaborate

³⁰For an early account see: K. Blasche, H Prange, *Die GSI in Darmstadt (I)*, Physikalische Blätter 33 (1977) 249 (in German). Online available from https://doi.org/10.1002/phbl. 19770330602. The GSI website at https://www.gsi.de/en/about_us/ provides a wealth of more up-to-date information.

³¹Maria Goeppert-Mayer (1906-1975) and Hans Jensen (1907-1973) received the Nobel Prize for Physics in 1963 "for their discoveries concerning nuclear shell structure." See also https://www.nobelprize.org/prizes/physics/1963/.

 $^{^{32}\}mathrm{The}$ transuranium elements 107 to 109 are now adays called bohrium, has sium, and meitnerium, respectively.



Sketch of GSI and the FAIR facility.

setup of magnetic and electric fields, called SHIP, short for "Separator for Heavy Ion Products." Other combinations of beams and targets were used to create the other new elements. And about ten years later, between 1994 and 1996, the team at GSI repeated their success and found elements 110, 111, and 112³³. In the decade between the element discoveries, many other experiments were performed and, most importantly, the facility was upgraded by adding a synchrotron and a storage ring.

Already in the early 1980s, different options to increase the energy of the beams were discussed and finally converged on a synchrotron (Chapter 5), for technical reasons called SIS18, and the ESR, short for "Experimentier Speicher-Ring." SIS18 has a circumference of 216 m and increases the energy of beams by large factors. At the same time their speed increases from 16% to 90% of the speed of light. The accelerated beams are then directed onto a target and the debris is filtered by a special beam line consisting of magnets and thin absorbers, called FRS, short for "FRagment Separator." Only one specific nucleus containing a particular number of protons and neutrons (a specific isotope) emerges at the exit of FRS and is injected into the ESR with half the circumference of SIS18. In the ESR a stochastic cooling system (Figure 9.4) improves the beam quality of the injected ions. Additionally, an electron cooler superimposes a high-quality electron beam with the stored ion beam. This allows the ions to bounce off the electrons and thereby lose some of their random motion. This process then slowly "cools" the ions and makes it possible to measure their revolution frequency with very high precision from which the mass of the injected isotope can be derived. This method was used to analyze a wide variety of isotopes thus improving our

³³The transuranium elements 110 to 112 are nowadays called darmstadtium, roentgenium, and copernicium, respectively.

understanding of nuclear matter.

Since the early 1990s, GSI explored the use of ion beams to treat cancer. Especially carbon ions showed a distinct advantage over conventional therapy with X-rays or electrons, because the carbon ions cause much more damage in deep-seated tumors while causing less harm in surrounding healthy tissue. The depth of the tumor-damage can be adjusted by adjusting the energy of the SIS18 synchrotron. The extension of the tumor in the sideways directions is covered by raster-scanning the ion beam with the help of magnets. During the process that destroys a tumor, positrons are created that annihilate with nearby electrons and give rise to two characteristic X-ray photons that reveal their point of origin. In this positron-emission tomographic (PET) process the deposited dose is verified while the patient is treated. The pilot project at GSI was such a success that a similar facility comprising synchrotron and raster-scanning target system was built in Heidelberg and treats patients from 2009 onwards. A few years later similar systems started operating in Marburg, Shanghai (China), Pavia (Italy), and Vienna (Austria).

Once SIS18 and the ESR were in operation in the mid-1990s, discussions started about the future needs of the nuclear physics community. It came up with a proposal for the "Facility for Antiproton and Ion Research" (FAIR)³⁴. The funding agencies recommended to jointly construct the facility with international partners. By 2010, all partners signed an agreement and FAIR was officially founded. It still took several years until construction began. Unfortunately it was delayed further due to massive increases in the cost, the covid pandemic, and the Russian war in Ukraine. By the time of writing construction, albeit on a reduced scope, is ongoing.

For FAIR, all the existing accelerators at GSI are upgraded and will become part of the injector complex for the large synchrotron SIS100. With a circumference of 1100 m it is about five times larger than SIS18 and reaches about five times higher energies. Beams extracted from SIS100 are guided to several experimental areas; one of them is the Super-FRS, a large fragment separator to isolate exotic isotopes. The "Collector Ring" CR collects these isotopes and makes detailed studies of their properties possible, just as the ESR was used to analyze isotopes produced in the FRS. In parallel to the Super-FRS, proton beams from SIS100 can be directed to an antiproton-production (\bar{p}) target. Also the antiprotons are collected in the CR. Once their beam quality is increased, they are directed to the "High-Energy Storage Ring" (HESR) where they are stored for hours and collide with a hydrogen target inside the PANDA detector.

The physics program of FAIR comprises four topics, labeled NUSTAR, PAN-DA, CBM, and APPA³⁵. NUSTAR is focused on exploiting the Super-FRS and

 $^{^{34}}$ See the online presentation at https://fair-center.eu/ for more information.

³⁵These names are acronyms. NUSTAR stands for "Nuclear Structure, Astrophysics and Reactions," PANDA stands for " antiProton ANnihilation at DArmstadt," CBM stands for "Compressed Baryonic Matter," and APPA stands for "Atomic, Plasma Physics and Applica-

determines the masses and lifetimes of rare isotopes that play an important role for the creation of heavier elements in stars and during supernova explosions. PANDA explores the spectrum of hadrons that include a charm quark and tries to find bound states of gluons, so-called glueballs. Since the mass of the quarks alone does not account for the mass of, for example, protons, PANDA tries to find explanations based on quantum chromodynamics. CBM will crash the full-energy beam coming from SIS100 into a target inside a dedicated cave. There conditions are recreated that resemble those immediately after the Big Bang when the primordial quark-gluon plasma condensed into the first hadrons. APPA explores how high-energy particles affect matter relevant to life sciences and material sciences. For example the impinging particles can form nanopores that serve as filters to separate smaller from larger compounds.

Not far from the FAIR site, in Frankfurt and in Mainz, two institutes pursue development work that directly contributes to GSI and FAIR. The "Institute for Applied Physics" at Frankfurt University develops accelerating structures, especially for the new linear accelerator HELIAC. It will take over the super-heavy element production from the venerable UNILAC, once the latter is dedicated to FAIR. The "Helmholtz Institute" in Mainz integrates the structures into HELIAC and works on a new electron cooler for the HESR to produce high-quality beams for PANDA.

Mainz

Long before the work towards FAIR, already since 1963, the university in Mainz operated a 300 MeV electron linear accelerator for experiments in nuclear physics. This machine, however, did not work quite as well as was hoped for and, tongue in cheek, was named MUELL (for "Mainzer Universitäts ELectron Linac"). About a decade later, an ingenious add-on, dubbed MALAISE (for "MAinz Linear Accelerator Improving SystEm")³⁶, improved the beam quality significantly, which is essential when probing nuclear matter with electrons. Experimental highlights comprise a precise measurement of the mixing of Z^0 -bosons and photons at low energies. This is a crucial parameter for the standard model, commonly referred to as Weinberg angle.

But in the mid 1970s the experimenters demanded higher energies and better beam quality, which would allow them to increase the precision of their experiments. But most of all, they asked for a continuous stream of electrons. The accelerator to provide these beams was dubbed MAMI³⁷, derived from "MAinz

tions."

³⁶The German word "Muell", if spelled "Müll," translates to the English word "garbage." Malaise, French for "misery," is actually a misnomer, because performance of the linac improved substantially.

³⁷H. Herminghaus et al., *The Design of a Cascaded 800 MeV Normal Conducting C.W. Race Track Microtron*, Nuclear Instruments and Methods 138 (1976) 1.



Sketch of a microtron.

MIcrotron." In microtrons a short linear accelerator is reused multiple times by recirculating the electron beam with magnets. This provides a much more compact way of reaching higher energies than would be possible by traversing a longer linac only once. Nevertheless, accelerating electrons from very low energies all the way to the full energy in only one microtron would be technically impossible; therefore MAMI had to be constructed as a cascade of three microtrons. The first one brought the energy up to 14 MeV and by 1983 the second microtron produced electrons with 213 MeV. Constructing the much larger third stage took more time, but by 1990 a continuous stream of electrons with energies up to 855 MeV was available. Most experiments used these electrons to probe the structure of nuclei. And the continuously available beam made it possible to probe very rare events. One just had to accumulate data for a long time. Other experiments first crashed the electrons into a heavy target to produce so-called bremsstrahlung composed of high-energy photons and then using the photons to probe various nuclei.

After running the facility for about a decade the experimentalists once again requested higher beam energies. That stimulated the construction of a fourth accelerator stage. Since the magnets for this large microtron would be too massive, the accelerator builders came up with an ingenious proposal³⁸. They proposed to split the large magnets into smaller ones and adjust ancillary components such as the acceleration system appropriately. By 2006 the fourth stage was up and running and produces 1500 MeV beams ever since.

Already the four MAMI stages could produce electrons with a well-defined

³⁸A. Jankowiak, *The Mainz Microtron MAMI—Past and Future*, Eur. Phys. J A 28, s01 (2006) 149.

orientation of their spin, but certain measurements require much higher beam intensities to achieve results in a reasonable time. To accommodate this type of experiment a new accelerator, called MESA³⁹, was proposed. In a second mode of operation, the accelerated electrons would be passed through the same structures that accelerated them, thereby recovering the energy of the beam and reusing it to accelerate a fresh beam of electrons with better quality. This mode of operation makes much higher beam intensities possible and thereby enables the experimenters to probe much rarer processes than previously possible. In particular, searches for the hypothetical dark matter (Chapter 14) are planned once MESA becomes operational in 2024.

Heidelberg

Even before the previously mentioned cancer therapy center was built in Heidelberg, an ion storage ring was constructed at the Max-Planck Institute for Nuclear Physics in close collaboration with GSI. By 1988 the "Test Storage Ring" TSR⁴⁰ with a circumference of 55 m stored beams of ionized atoms and molecules. An electron cooler, similar to the one installed in the ESR at GSI, was used to reduce the beam sizes and allowed the experimenters to analyze the behavior of beams with very high charge densities. Moreover, the cooler was used as an electron target to investigate atomic and molecular recombination processes. In these processes an atom picks up an additional electron from the cooler. They are important to understand the creation of complex molecules in outer space. Moreover, the accelerated and cooled ion beams were used for high-resolution experiments in nuclear physics. The ring was operated until 2012 when construction of a new storage ring in Heidelberg started.

Rather than using magnetic fields to guide the beams, the new ring with a circumference of 35 m uses electric fields, which is advantageous for slow and very heavy particles or molecules. Moreover, in order to permit very delicate measurements, the ring is cooled down to extremely low temperatures and is therefore dubbed CSR⁴¹, an acronym derived from "Cryogenic Storage Ring." Like in the earlier ring, an electron cooler serves as an electron target for high-resolution recombination reactions.

³⁹MESA is an acronym derived from "Mainz Energy recovering Superconducting Accelerator." See also https://www.mesa.uni-mainz.de/eng/.

⁴⁰P. Baumann et al., *The Heidelberg Heavy Ion Test Storage Ring TSR*, Nuclear Instruments and Methods A268 (1988) 531.

⁴¹R. von Hahn et al., *The cryogenic storage ring CSR*, Rev. Sci. Instrum. 87, (2016) 063115.

Jülich

Already 1968 the JULIC⁴² cyclotron in Jülich accelerated protons and other light ions with energies up to 45 MeV that were mostly used for nuclear physics experiments. A number of transfer lines brought these beams to several different target stations, among them a large detector called BIG KARL. Other stations were used to produce radioactive isotopes for medical applications.

Already in the early 1980s, ideas appeared to add a synchrotron to the facility that would increase the energy of the protons substantially. In order to produce high-quality beams, an electron cooler was planned, which gave the synchrotron the name COSY⁴³, for "COoler SYnchrotron." It has a circumference of 184 m and accelerates protons, which could be prepared with their spins aligned, to energies of up to 2300 MeV. Besides the electron cooler, elaborate stochastic cooling systems (Figure 9.4) improve the quality of beams that are delivered to the experiments. Three of them are part of the ring where the beam continuously interacts with a target such as a gas jet or a very thin carbon filament. Later a stream of frozen hydrogen spheres, so-called pellets, served as a target to explore nuclear interactions. Apart from using these internal targets, the beam was extracted from the ring and directed to external detectors, among them the venerable BIG KARL.

The nuclear physics program continued until 2014, at which time the focus switched to precision experiments to understand various aspects of CP-violation (Chapter 10). In the "Time Reversal Invariance at COSY" (TRIC) experiment, a specially prepared proton beam with spins aligned collided with a likewise prepared deuteron target. A second experimental program, called EDM, aims at measuring the "Electric Dipole Moment" of protons and deuterons by observing the precession of the spin of beam particles in the presence of strong electric fields. Any non-zero value would give strong indications about "new physics" beyond the standard model. At the same time, COSY was used to develop the nextgeneration accelerator technology needed for the FAIR facility in Darmstadt, in particular the electron coolers and stochastic cooling systems.

And there is more

Besides the larger accelerators covered in this report, there are many smaller ones. Many hospitals operate small cyclotrons to produce radioactive isotopes that are used for diagnostic purposes, such as positron-emission tomography (Section 13.4). They also operate small, often less than one meter long electron linear accelerators to irradiate tumors.

Several universities operate electrostatic accelerators of the type devised by

⁴²L. Aldea et al., *Status of JULIC*, Proceedings of Cyclotrons 1981 in Caen, p. 103.

⁴³U. Bechstedt et al., *The cooler synchrotron COSY in Jülich*, Nuclear Instruments and Methods B113 (1996) 26.

van der Graaff (Figure 4.1). They are used for dating artefacts using the carbon-14 method (Section 13.5) and to analyze specimen by impinging the beams onto the sample. Subsequently observing the emitted X-rays, specific to the material composition of the specimen, allows the experimenters to identify even minute quantities of constituents.

Accelerating very heavy ions to a few hundred of kV implants the ions inside the irradiated substrate, which is used in industry and academia. These machines are up-to-date versions of Cockroft and Walton's accelerator (Figure 4.1) used to split Lithium atoms in 1930.

Acknowledgements

I benefitted greatly from helpful discussions with Christian Jung, Roger Ruber, Detlev Schirmer, Wolfgang Hillert, Daniel Elsner, Andreas Lehrach, Kurt Aulenbacher, and Jörg Rossbach.