Pseudoentanglement Ain't Cheap

Sabee Grewal^{*}

Vishnu Iyer[†]

William Kretschmer[‡]

Daniel Liang[§]

Abstract

We show that any pseudoentangled state ensemble with a gap of t bits of entropy requires $\Omega(t)$ non-Clifford gates to prepare. This bound is tight up to polylogarithmic factors if lineartime quantum-secure pseudorandom functions exist. Our result follows from a polynomial-time algorithm to estimate the entanglement entropy of a quantum state across any cut of qubits. When run on an n-qubit state that is stabilized by at least 2^{n-t} Pauli operators, our algorithm produces an estimate that is within an additive factor of $\frac{t}{2}$ bits of the true entanglement entropy.

1 Introduction

Recent work [ABF⁺24] introduced the notion of *pseudoentangled* quantum states, in analogy with pseudorandomness in classical computation. An ensemble of quantum states is said to be pseudoentangled if states in the ensemble have low entanglement across every bipartition, but they are difficult to distinguish from states with much larger entanglement. A more formal definition is the following:

Definition 1.1. A pseudoentangled ensemble with gap f(n) vs. g(n) (where f(n) > g(n)) consists of two ensembles of *n*-qubit states $\{|\Psi_k\rangle, |\Phi_k\rangle\}_k$ indexed by a key $k \in \{0, 1\}^{\text{poly}(n)}$ such that

- $|\Psi_k\rangle$ and $|\Phi_k\rangle$ are preparable in quantum polynomial time.
- With probability at least 1 poly(n) over the choice of k, the entanglement entropy across every cut of size $\Omega(f(n))$ of $|\Psi_k\rangle$ (respectively, $|\Phi_k\rangle$) is $\Theta(f(n))$ (respectively, $\Theta(g(n))$).
- For any polynomial p(n), no polynomial-time quantum adversary can distinguish

$$\rho \coloneqq \mathbf{E}_{k} \left[|\Psi_{k}\rangle\!\langle\Psi_{k}|^{\otimes p(n)} \right] \quad \text{and} \quad \sigma = \mathbf{E}_{k} \left[|\Phi_{k}\rangle\!\langle\Phi_{k}|^{\otimes p(n)} \right]$$

with better than negligible success probability.

 $[ABF^+24]$ showed that pseudoentangled states can be instantiated in polynomial time and logarithmic depth, assuming the existence of quantum-secure one-way functions. So, under a standard cryptographic assumption, there exists an efficient construction of pseudoentanglement. Nevertheless, in applications, we sometimes need constructions that are even simpler and more efficient, due to constraints beyond total gate complexity. For example, $[ABF^+24]$ suggested that a construction of "holographic" pseudoentangled states might imply that the AdS/CFT dictionary

^{*}sabee@cs.utexas.edu. The University of Texas at Austin.

[†]vishnu.iyer@utexas.edu. The University of Texas at Austin.

[‡]kretsch@berkeley.edu. Simons Institute for the Theory of Computing, UC Berkeley.

[§]dl88@rice.edu. Rice University.

is hard to compute. However, it remains open to build such pseudoentangled states that are compatible with the laws of AdS/CFT. There are also various other measures of quantum state complexity, beyond circuit depth. For example, a counting argument shows that stabilizer states and free-fermionic states can require super-logarithmic depth, but these states are also "easy" in the sense that their evolutions are efficiently classically simulable [AG04, Val02] and they are efficiently learnable [AG08, Mon17, AG23].

In this work, we study the relationship between pseudoentanglement and non-Clifford complexity. The Clifford group is a remarkably useful object in quantum information that consists of all quantum circuits generated by Hadamard, Phase, and CNOT gates. Clifford gates are almost universal for quantum computing: the addition of any single-qubit non-Clifford gate gives rise to a universal gate set, as shown by Shi [Shi02]. Generally speaking, Clifford gates are "cheaper" than non-Clifford gates, in a sense that can be formalized in a variety of applications. Examples where the cost of a quantum operation is dominated by non-Clifford gates include quantum fault tolerance based on magic state distillation [BK05], near-Clifford classical simulation algorithms [AG04, BG16, RLCK19, BBC⁺19], and quantum learning algorithms based on the stabilizer formalism [LC22, GIKL23a, GIKL23b, GIKL23c, GIKL23d, LOLH22, LOH23, HG23, CLL23].

A related work by Grewal, Iyer, Kretschmer, and Liang [GIKL23d, GIKL23c] investigated the stabilizer complexity of a different cryptographic object called *pseudorandom* quantum states. These are ensembles of quantum states that cannot be distinguished from Haar-random by any polynomial-time adversary. The main result of [GIKL23c], improving upon earlier work by the same authors, shows that *n*-qubit pseudorandom states require at least $\Omega(n)$ non-Clifford gates. The present work asks whether a similar lower bound on non-Clifford resources holds for quantum pseudoentanglement.

As it happens, several of the known pseudoentangled state ensembles are *also* pseudorandom states ensembles, including the only known instantiations of pseudoentanglement that achieve an optimal gap of $\Theta(n)$ vs. $\omega(\log n)$ [ABF⁺24, GTB23]. However, [ABF⁺24] further observed that a pseudoentangled ensemble need not be pseudorandom, nor vice-versa. Hence, it is not clear that the computational resources needed to construct pseudoentangled states mirror those for pseudorandom states.

On the other hand, existing work has made clear that that *some* amount of non-Cliffordness is needed to generate pseudoentangled states. Fattal, Cubitt, Yamamoto, Bravyi, and Chuang [FCY+04] gave an efficient algorithm for computing the entanglement entropy across any bipartition of a *stabilizer state* (i.e., a state preparable using Clifford gates only). Combined with Montanaro's algorithm for learning an unknown stabilizer state [Mon17], this implies that any ensemble $\{|\Psi_k\rangle, |\Phi_k\rangle\}_k$ of stabilizer states cannot be pseudoentangled.

Our main result is an algorithm with a much stronger guarantee than the combination of $[FCY^+04, Mon17]$. In short, our algorithm estimates the entanglement entropy of an unknown quantum state across any cut of qubits, where the accuracy of the estimate scales with the number of Pauli operators that stabilize the state (i.e., the number of Pauli operators for which the state is a +1-eigenvector).

Theorem 1.2 (Informal version of Corollary 4.4). There is a polynomial-time quantum algorithm that takes as input

- 1. $O(n^3)$ copies of an n-qubit quantum state $|\psi\rangle$ that is stabilized by at least 2^{n-t} Pauli operators, and
- 2. A bipartition $A \sqcup B = [n]$ of qubits,

and outputs an estimate of the entanglement entropy of $|\psi\rangle$ across the partition. The estimate is within an additive factor of $\frac{t}{2}$ bits of the true entanglement entropy, with high probability.

We remark that the set of states for which this is applicable is rather large and includes states prepared by a Clifford circuit with up to $\lfloor \frac{t}{2} \rfloor$ auxiliary single-qubit non-Clifford gates (such as the *T*-gate). When the algorithm is run on a stabilizer state (i.e., when t = 0), then our algorithm outputs the entanglement entropy across any cut of qubits *exactly*, recovering the aforementioned result of [FCY⁺04, Mon17]. On the other hand, the bounds degrade as t becomes too close to n.

As a straightforward consequence, we show that pseudoentangled state ensembles require a number of non-Clifford gates that scales linearly in the pseudoentanglement gap.

Theorem 1.3 (Restatement of Corollary 4.5). Any family of Clifford circuits that produces a pseudoentangled ensemble $\{|\Psi_k\rangle, |\Phi_k\rangle\}_k$ with entropy gap f(n) vs. g(n) satisfying $f(n) - g(n) \ge t$ must use $\Omega(t)$ auxiliary non-Clifford single-qubit gates.

So, pseudoentangled ensembles with the optimal $\Theta(n)$ vs. $\omega(\log n)$ gap require a linear number of non-Clifford gates. Interestingly, this matches the lower bound on non-Clifford gates needed for pseudorandom states [GIKL23c].

Corollary 4.5 is optimal up to polylogarithmic factors under plausible computational assumptions. In particular, Ma [Ma24] constructs pseudoentangled state ensembles in O(n polylog(n)) time under the assumption that linear-time quantum-secure pseudorandom functions exist.¹ This is to say that under this assumption, pseudoentangled state ensembles on n qubits require at most O(n polylog(n)) non-Clifford gates in total. It is widely conjectured that linear-time *classically*-secure pseudorandom functions exist [IKOS08, FLY22], and it is plausible that these (or other) constructions are also secure against quantum adversaries.

Prior to this work, it was unknown if even O(1) non-Clifford gates sufficed to construct pseudoentangled states. While one can efficiently learn states prepared by $O(\log n)$ non-Clifford gates [GIKL23a, GIKL23b], it is unclear how to leverage those algorithms to estimate entanglement entropy. Following intuition from simulation algorithms for near-Clifford circuits, whose running times scale exponentially in the number of non-Clifford gates, it was also conceivable that a super-logarithmic number of non-Clifford gates would be sufficient to construct pseudoentangled states.

Concurrent Work While finalizing this work, we became aware of independent and concurrent work by Gu, Oliveiro, and Leone [GOL24]. Their [GOL24, Lemma 7] resembles our Theorem 3.1. However, we only prove bounds for the von Neumann entropy, whereas [GOL24] prove similar bounds for any α -Rényi entanglement entropy, which captures the von Neumann entropy as a special case.

1.1 Main Ideas

For an *n*-qubit quantum state $|\psi\rangle$, let Weyl($|\psi\rangle$) denote the Pauli operators *P* for which $P |\psi\rangle = 1.^2$ Let $A \sqcup B = [n]$ be a bipartition of qubits. Denote Weyl($|\psi\rangle$)_A as the subset of Pauli operators in Weyl($|\psi\rangle$) that act only the qubits indexed by *A*, and define Weyl($|\psi\rangle$)_B analogously. We use dim(*G*) to refer to the minimum number of generators of a group *G*. It is easy to verify that Weyl($|\psi\rangle$), Weyl($|\psi\rangle$)_A, and Weyl($|\psi\rangle$)_B are abelian subgroups of the Pauli group. We prove the following bounds on the entanglement entropy across (*A*, *B*), which hold for any quantum state.

¹The details will be included in a forthcoming work due to Ma [Ma24].

²See Definition 2.10 for a formal definition. We find it convenient to work with Weyl operators, a subset of Pauli operators that form a basis of $\mathbb{C}^{2^n \times 2^n}$. One can think of Weyl($|\psi\rangle$) as the stabilizer group of $|\psi\rangle$ with all of the phase information removed. For example, for any computational basis state $|x\rangle$, Weyl($|x\rangle$) $\equiv \{I, Z\}^{\otimes n}$.

Theorem 1.4 (Restatement of Theorem 3.1). Let $\rho = |\psi\rangle\langle\psi|$ be an *n*-qubit quantum state and let $A \sqcup B = [n]$ be a partition of qubits. Then

 $\dim \left(\operatorname{Weyl}(|\psi\rangle) \right) - \dim \left(\operatorname{Weyl}(|\psi\rangle)_B \right) - |A| \le \mathsf{S}(\rho_A) \le |A| - \dim \left(\operatorname{Weyl}(|\psi\rangle)_A \right),$

where $\rho_A = \operatorname{tr}_B(\rho)$ is the reduced density matrix of ρ after tracing out the qubits in B and $\mathsf{S}(\rho_A)$ is the entanglement entropy across (A, B).

Crucially, the quantities in Theorem 1.4 can be (approximately) computed efficiently, given a polynomial number of copies of $|\psi\rangle$. First, we learn generators for Weyl($|\psi\rangle$) with Bell difference sampling, a quantum measurement that consumes four copies of a state and produces a Pauli operator (see the end of Section 2.1 for further detail). Bell difference sampling many times, along with some classical post-processing, suffices to (approximately) learn generators of Weyl($|\psi\rangle$), as proven in prior work [GIKL23c, GIKL23a]. Then, using these generators of Weyl($|\psi\rangle$), we can compute (approximations of) Weyl($|\psi\rangle$)_A and Weyl($|\psi\rangle$)_B in polynomial time by solving a system of linear constraints. We note that these approximations suffice, due to a result of Audenaert [Aud07, Theorem 1], which relates the entanglement entropy of states that are close in trace distance.

Let us now explain how the upper and lower bounds in Theorem 1.4 are proved, and then explain some applications. At a high level, we argue that there exist Clifford circuits acting locally on either A or B that exhibit entanglement (or the lack thereof) in the system. Because the Clifford circuits are local, we conclude that the original state must have the same entanglement (or lack thereof). The formal proofs are given in Section 3.

We begin with the upper bound. Trivially, the entanglement entropy is at most |A|. To simplify the presentation, define $a := \dim(\operatorname{Weyl}(|\psi\rangle)_A)$. By known techniques, one can construct a Clifford circuit acting only on A that maps $\operatorname{Weyl}(|\psi\rangle)_A$ to Pauli-Z strings on a subset of a qubits.³ This has the effect of mapping the state $|\psi\rangle$ to a *product state* where a subset of a qubits in A are in a computational basis state and the remaining qubits are in some arbitrary state. The a qubits cannot be entangled with the rest of the system, and our upper bound follows.

For the lower bound, we argue that there exist Clifford circuits acting locally on A and B, respectively, that distill EPR pairs across qubits of A and B. Observe that the EPR state is stabilized by the Pauli operators generated by $X \otimes X$ and $Z \otimes Z$. While these two Pauli operators commute with one another, they locally anticommute (i.e., X and Z do not commute). Clifford circuits acting locally on A (or B, respectively) do not affect the global or local commutation relations. As such, any pair of locally anticommuting Pauli operators in Weyl(ψ) can be mapped, via local Clifford circuits on A and B, respectively, to $X \otimes X$ and $Z \otimes Z$, creating an EPR pair on one qubit of A and B each. Our lower bound follows from counting the number of EPR pairs we can produce in this way.

For both the upper and lower bounds, the Clifford circuits can be found efficiently. Indeed, a similar approach played a crucial role in the tomography algorithms given in [GIKL23a, GIKL23b]. Additionally, one can view our lower bound as an efficient algorithm for entanglement distillation of quantum states with large stabilizer dimension (Definition 2.11), which may be of independent interest.

We conclude by explaining how to apply Theorem 1.4 to get our entanglement estimation algorithm (Theorem 1.2) and the pseudoentanglement lower bound (Theorem 1.3). Our algorithm outputs upper and lower bounds (u, ℓ) , essentially by computing the quantities appearing in Theorem 1.4. When run on a quantum state $|\psi\rangle$ that is stabilized by least 2^{n-k} Pauli operators, we prove that $u - \ell \leq k$. Therefore, $\frac{u+\ell}{2}$ will always be within an additive factor of $\frac{k}{2}$ bits of the

³It is well known that Clifford unitaries map Pauli operators to Pauli operators, see Section 2.1 for more detail.

true entanglement entropy. As a corollary, we obtain a lower bound on preparing pseudoentangled states. Suppose we have two state ensembles $\{|\Psi_k\rangle\}_k$ and $\{|\Phi_k\rangle\}_k$ that are prepared with at most t non-Clifford gates. If we run our entropy estimation algorithm on copies drawn from either ensemble, we will recover upper and lower bounds (u, ℓ) such that $u - \ell \leq 2t$. Therefore, the pseudoentanglment gap between these ensembles is at most 2t.

2 Preliminaries

For a positive integer n, $[n] \coloneqq \{1, 2, ..., n\}$. For $x = (a, b) \in \mathbb{F}_2^{2n}$, a and b always denote the first and last n coordinates of x, respectively. For vectors v_1, \ldots, v_k , $\langle v_1, \ldots, v_k \rangle$ denotes their span. For matrix $X \in \mathbb{C}^{d \times d}$, $||X||_1$ denotes the sum of the absolute values of its singular values (known as the trace norm, nuclear norm, or Schatten 1-norm). For quantum mixed states ρ, σ , dist_{tr} := $\frac{1}{2} ||\rho - \sigma||_1$ is the trace distance. For us, log denotes the logarithm with base 2, and ln is the logarithm with base $e \approx 2.718$.

Let $A \sqcup B$ be a partition of [n]. We refer to (A, B) as a *cut* of *n* qubits. Let ρ be an *n*-qubit quantum state. The entanglement entropy across (A, B) is defined as

$$\mathsf{S}(\rho_A) \coloneqq -\operatorname{tr}(\rho_A \log \rho_A) = -\operatorname{tr}(\rho_B \log \rho_B),$$

where $\rho_A = \operatorname{tr}_B(\rho)$ and $\rho_B = \operatorname{tr}_A(\rho)$ are the states obtained by tracing out B and A, respectively.

Define the binary entropy function H(p) by

$$H(p) = -p\log(p) - (1-p)\log(1-p).$$

The following is a well-known upper bound on H(p).

Fact 2.1.

$$\mathsf{H}(p) \le (4p(1-p))^{1/\ln 4} \le e \cdot p^{1/\ln 4} \le e \cdot p^{0.72}.$$

If two states are close in trace distance, then so is their entanglement entropy.

Lemma 2.2 (Fannes-Audenaert inequality [Aud07, Theorem 1]). Let $\rho = |\psi\rangle\langle\psi|$ and $\sigma = |\phi\rangle\langle\phi|$ be *n*-qubit states satisfying dist_{tr}($|\psi\rangle$, $|\phi\rangle) \leq \varepsilon$, and let $A \sqcup B = [n]$ be a partition. Then

$$|\mathsf{S}(\rho_A) - \mathsf{S}(\sigma_A)| \le \varepsilon n + \mathsf{H}(\varepsilon)$$

2.1 Symplectic Vector Spaces and Weyl Operators

There is a deep connection between quantum information and symplectic vector spaces over \mathbb{F}_2 that we leverage throughout this work. Many in the quantum information and theoretical computer science communities may not be familiar with this connection, so we take care to review these notions here.

To obtain a symplectic vector space, one must equip a vector space with a symplectic form.

Definition 2.3 (Symplectic form). Let V be a vector space over a field \mathbb{F} . A symplectic form is a mapping $\omega : V \times V \to \mathbb{F}$ that satisfies the following conditions.

- 1. Bilinear: ω is linear in each argument separately.
- 2. Alternating: For all $v \in V$, $\omega(v, v) = 0$.
- 3. Non-degenerate: If for all $v \in V$, $\omega(u, v) = 0$, then u = 0.

A symplectic vector space is a pair (V, ω) , where V is a vector space and ω is a symplectic form. We will equip \mathbb{F}_2^{2n} with the standard symplectic form, which we refer to as the symplectic product.

Definition 2.4 (Symplectic product). For $x, y \in \mathbb{F}_2^{2n}$, we define the symplectic product as $[x, y] = x_1 \cdot y_{n+1} + x_2 \cdot y_{n+2} + \cdots + x_n \cdot y_{2n} + x_{n+1} \cdot y_1 + x_{n+2} \cdot y_2 + \cdots + x_{2n} \cdot y_n$.

In this work, one should always view \mathbb{F}_2^{2n} as a symplectic vector space equipped with the symplectic product.

The symplectic product allows us to define the symplectic complement.

Definition 2.5 (Symplectic complement). Let $T \subseteq F_2^{2n}$ be a subspace. The symplectic complement of T, denoted by T^{\perp} , is defined by

$$T^{\perp} \coloneqq \{ a \in \mathbb{F}_2^{2n} : \forall x \in T, [x, a] = 0 \}.$$

We will also need the notion of isotropic and symplectic subspaces.

Definition 2.6 (Isotropic subspace). A subspace $W \subseteq \mathbb{F}_2^{2n}$ is isotropic when $W \subseteq W^{\perp}$. Equivalently, W is isotropic if and only if $[w_1, w_2] = 0$ for all $w_1, w_2 \in W$.

Definition 2.7 (Symplectic subspace). A subspace $W \subseteq \mathbb{F}_2^{2n}$ is symplectic when $W \cap W^{\perp} = \{0\}$.

Every symplectic space has a standard basis, which we refer to as the symplectic basis.

Fact 2.8. Any 2*d*-dimensional symplectic space over \mathbb{F}_2 has a basis $\{x_1, \ldots, x_d, z_1, \ldots, z_d\}$ such that

$$[x_i, z_j] = \delta_{ij} \qquad and \qquad [x_i, x_j] = [z_i, z_j] = 0.$$

Any basis with the above form is referred to as a symplectic basis.

The direct sum of two symplectic vector spaces is also symplectic. This is a basic fact, but we include a proof for completeness.

Fact 2.9. If V, W are symplectic vector spaces over \mathbb{F}_2 , so is their direct sum.

Proof. Denote the symplectic forms on V and W by ω_V and ω_W , respectively. Let $A \coloneqq V \oplus W$, where $V \oplus W = \{(v, w) : v \in V, w \in W\}$. Define the form ω_A on A by $\omega_A(a_1, a_2) = \omega_V(v_1, v_2) + \omega_W(w_1, w_2)$ where $a_i = v_i + w_i$. We will prove that (A, ω_A) is symplectic.

It is obvious that A is a vector space, so it remains to prove that ω_A is a symplectic form. Recall from Definition 2.3 that we must show that ω_A is bilinear, alternating, and non-degenerate. It is clear that ω_A is bilinear because it is the sum of two bilinear forms. For $a = (v, w) \in A$, we have $\omega_A(a, a) = \omega_V(v, v) + \omega_W(w, w) = 0$, so ω_A is alternating.

Finally, we prove that ω_A is non-degenerate. Suppose we have an element a = (v, w) such that for all $a' \in A$ we have $\omega_A(a, a') = \omega_V(v, v') + \omega_W(w, w') = 0$. Now choose a $v' \in V$ such that [v, v'] = 0 (one must exist since V is symplectic). $\omega_A(a, a') = \omega_V(v, v') + \omega_W(w, w') = 0$ by assumption, and, because $\omega_V(v, v') = 0$, it follows that $\omega_W(w, w') = 0$ for all $w' \in W$. Since ω_W is non-degenerate, w = 0. A similar argument shows that v = 0. Therefore, ω_A is non-degenerate. \Box

Each element of \mathbb{F}_2^{2n} can be identified with a Weyl operator. For $x = (a, b) \in \mathbb{F}_2^{2n}$, let a', b' be the embeddings of a, b into \mathbb{Z}^n , respectively. Then the Weyl operator W_x is defined as

$$W_x \coloneqq i^{a' \cdot b'} (X^{a_1} Z^{a_1}) \otimes \cdots \otimes (X^{a_n} Z^{b_n}).$$

The symplectic structure of \mathbb{F}_2^{2n} respects the commutation relations of the Weyl operators. Specifically, for $x, y \in \mathbb{F}_2^{2n}$, [x, y] = 0 iff $W_x W_y = W_y W_x$. Therefore, working with symplectic vector spaces lets us discard cruft while retaining relevant algebraic structure. We also note that Weyl operators form an orthogonal basis of $\mathbb{C}^{2^n \times 2^n}$ with respect to the Hilbert-Schmidt inner product, so every quantum state and unitary transformation can be written as a linear combination of Weyl operators.

We define $\mathcal{Z} := 0^n \times \mathbb{F}_2^n$ as the subset of \mathbb{F}_2^{2n} corresponding to Pauli-Z strings. We define the unsigned stabilizer group of a quantum state as the subspace of \mathbb{F}_2^{2n} that stabilizes or anti-stabilizes the state.

Definition 2.10 (Unsigned stabilizer group). Given an *n*-qubit quantum state $|\psi\rangle$, Weyl $(|\psi\rangle) := \{x \in \mathbb{F}_2^{2n} : W_x |\psi\rangle = \pm |\psi\rangle\}$ is the unsigned stabilizer group of $|\psi\rangle$.

It is easy to verify that $Weyl(|\psi\rangle)$ is an isotropic subspace. We define the stabilizer dimension, which quantifies the size of the Pauli group stabilizing a given state.

Definition 2.11 (Stabilizer dimension). Let $|\psi\rangle$ be a *n*-qubit pure state. The *stabilizer dimension* of $|\psi\rangle$ is the dimension of Weyl($|\psi\rangle$) as a subspace of \mathbb{F}_2^{2n} .

The stabilizer dimension of a state is closely related to the number of non-Clifford gates required to prepare it.

Fact 2.12 ([GIKL23c, Lemma 4.2]). Let $|\psi\rangle$ be an n-qubit state which is the output of a Clifford circuit with at most t single-qubit non-Clifford gates. Then $|\psi\rangle$ has stabilizer dimension at least n-2t.

For a Clifford circuit C and any $x \in \mathbb{F}_2^{2n}$, we define C(x) to be the $y \in \mathbb{F}_2^{2n}$ such that $W_y = \pm CW_x C^{\dagger}$. We can extend this notation to subsets S of \mathbb{F}_2^{2n} by writing $C(S) = \{C(x) : x \in S\}$. Conjugation by any Clifford circuit is an automorphism of the Pauli group. Furthermore, C(x) preserves the symplectic form.

Fact 2.13. For any Clifford circuit C and $x, y \in \mathbb{F}_2^{2n}$, [C(x), C(y)] = [x, y].

Proof. Recall that $W_{C(x)}W_{C(y)} = (-1)^{[C(x),C(y)]}W_{C(y)}W_{C(x)}$. Suppose that $W_{C(x)} = (-1)^{c_1}CW_xC^{\dagger}$ and $W_{C(y)} = (-1)^{c_2}CW_yC^{\dagger}$. We have

$$W_{C(x)}W_{C(y)} = (-1)^{c_1+c_2}CW_xC^{\dagger}CW_yC^{\dagger}$$

= $(-1)^{c_1+c_2}CW_xW_yC^{\dagger}$
= $(-1)^{[x,y]}(-1)^{c_1+c_2}CW_yW_xC^{\dagger}$
= $(-1)^{[x,y]}(-1)^{c_1+c_2}CW_yC^{\dagger}CW_xC^{\dagger}$
= $(-1)^{[x,y]}W_{C(y)}W_{C(x)}.$

Thus [C(x), C(y)] = [x, y].

Since the inverse of any Clifford circuit is itself a Clifford circuit, we have the following as a simple corollary:

Corollary 2.14. Given a subspace $H \subseteq \mathbb{F}_2^{2n}$ and a Clifford circuit C, H is isotropic (resp. symplectic) if and only if C(H) is isotropic (resp. symplectic).

Finally, we remark on Bell difference sampling [Mon17, GNW21], an algorithmic primitive used in this work. Define $p_{\psi}(x) \coloneqq 2^{-n} \langle \psi | W_x | \psi \rangle^2$. Bell difference sampling is a quantum measurement that takes four copies of a state $|\psi\rangle$, and produces a sample $x \in \mathbb{F}_2^{2n}$ drawn from the distribution q_{ψ} which is defined as

$$q_{\psi}(x) \coloneqq \sum_{a \in \mathbb{F}_2^{2n}} p_{\psi}(a) p_{\psi}(x+a).$$

This process takes O(n) time. We refer readers to [GIKL23c, Section 2] for further detail.

3 Entanglement Entropy Bounds

We prove upper and lower bounds on the entanglement entropy across any cut of qubits for any *n*-qubit quantum state $|\psi\rangle$. The quality of our bounds depends on Weyl($|\psi\rangle$). For example, if dim(Weyl($|\psi\rangle$)) = 0, our bounds become trivial, and, if dim(Weyl($|\psi\rangle$)) = n (i.e., $|\psi\rangle$ is a stabilizer state), our bounds are tight, recovering the main result of [FCY⁺04].

To state our bounds, we must introduce some notation. Let $A \subseteq [n]$ be a subset of qubits, and let S be a subspace of \mathbb{F}_2^{2n} . We denote by S_A the intersection of S with operators that act only on qubits indexed by A. In symbols, we can express this as follows:

$$S_A \coloneqq \{(x, z) \in S : \forall i \in [n] \setminus A, x_i = z_i = 0\}.$$

So, for example,

$$\mathcal{Z}_A \coloneqq \{ (0^n, z) \in \mathbb{F}_2^{2n} : \forall i \in [n] \setminus A, z_i = 0 \}$$

are essentially the Pauli-Z strings that act on the qubits indexed by A.

Computationally speaking, one can compute S_A efficiently, given a basis of S, by solving a system of linear constraints to zero all coordinates corresponding to $i \in [n] \setminus A$.

In the remainder of this section, we prove the following theorem.

Theorem 3.1. Let $\rho = |\psi\rangle\langle\psi|$ be an *n*-qubit quantum state and let $A \sqcup B = [n]$ be a partition of qubits. Then

 $\dim (\operatorname{Weyl}(|\psi\rangle)) - \dim (\operatorname{Weyl}(|\psi\rangle)_B) - |A| \leq \mathsf{S}(\rho_A) \leq |A| - \dim (\operatorname{Weyl}(|\psi\rangle)_A).$

3.1 Proof of Upper Bound

Lemma 3.2. Let $\rho = |\psi\rangle\langle\psi|$ be an *n*-qubit quantum state and let $A \subseteq [n]$ be a partition of qubits. Then

$$\mathsf{S}(\rho_A) \leq |A| - \dim (\operatorname{Weyl}(|\psi\rangle)_A).$$

Proof. Let $A' \subseteq A$ be any set of size $\dim(\operatorname{Weyl}(|\psi\rangle)_A)$. By known techniques, one can find a Clifford circuit C acting only on A that maps the Paulis in $\operatorname{Weyl}(|\psi\rangle)_A$ to $\mathcal{Z}_{A'}$.⁴ As a consequence, this C behaves as $C |\psi\rangle = |x\rangle_{A'} |\phi\rangle_{[n]\setminus A'}$, where $|x\rangle_{A'}$ is a computational basis state on A' and $|\phi\rangle_{[n]\setminus A'}$ is an arbitrary state on the remaining qubits. Because C is local to A, it does not affect the entanglement entropy across the partition. Furthermore, it is clear that the qubits $|x\rangle_{A'}$ are unentangled from the rest of the system. As such, only the qubits in $A \setminus A'$ can exhibit entanglement across the partition, and there are $|A| - |A'| = |A| - \dim(\operatorname{Weyl}(|\psi\rangle)_A)$ many such qubits. So, the entanglement entropy across the partition is bounded above by $|A| - \dim(\operatorname{Weyl}(|\psi\rangle)_A)$.

⁴An explicit algorithm for computing this C can be found in [GIKL23a, Section 3].

3.2 Proof of Lower Bound

Lemma 3.3. Let $V \subseteq \mathbb{F}_2^{2n}$ be a symplectic subspace of dimension 2v and have $S \subseteq V$ be a subspace of dimension v + k. There exists a symplectic subspace $T \subseteq S$ with dimension at least 2k.

Proof. Take any nonzero $e_1 \in S$. Because $\dim(S) > v$, there exists some $f_1 \in S$ such that $[e_1, f_1] = 1$. Let W_1 be the span of e_1 and f_1 . We will prove that $S = W_1 \oplus (W_1^{\perp} \cap S)$ is a direct sum. First, we argue that $W_1 \cap (W_1^{\perp} \cap S) = \{0\}$.⁵ Take $z \in W_1$. Since W is the span of e_1 and f_1 , we can write $z = \alpha e_1 + \beta f_1$. If z is also in $W^{\perp} \cap S \subseteq W^{\perp}$, then $0 = [x, z] = \beta$ and $0 = [y, z] = \alpha$, so z = 0. Next, we prove that any $v \in S$ can be written as a sum of $w_1 \in W_1$ and $w_1^c \in W_1^{\perp} \cap S$. Clearly $w_1 \coloneqq [v, e_1]f_1 + [v, f_1]e_1 \in W_1$, and define $w_1^c \coloneqq v + [v, e_1]f_1 + [v, f_1]e_1$. It is easy to check $[e_1, w_1^c] = [f_1, w_1^c] = 0$, so $w_1^c \in W_1^{\perp}$. Furthermore, if since $e_1, f_1 \in W_1 \subset S$, $w_1^c \in S$ as well. It is clear that $v = w_1 + w_1^c$.

Repeat this process to collect pairs $(e_1, f_1), \ldots, (e_r, f_r)$ until we have that $S \cap_{j=1}^r W_j^{\perp}$ doesn't contain an e_{r+1} and f_{r+1} such that $[e_{r+1}, f_{r+1}] = 1$. Observe by linearity that any object in $x \in \bigcap_{j=1}^r W_j^{\perp}$ must have [x, y] = 0 for all $y \in \bigoplus_{i=1}^r W_i$. Consequently, $S \cap_{j=1}^r W_j^{\perp} \oplus \langle e_1, \ldots, e_r \rangle$ is an isotropic subspace of dimension v + k - r. Since all isotropic subspaces within V must have dimension at most v,

$$v + k - r \le v \implies r \ge k.$$

Hence, $\bigoplus_{i=1}^{r} W_i$ has dimension at least 2k. Since each W_i is symplectic, their direct sum is symplectic by Fact 2.9.

Lemma 3.4. Let $\rho = |\psi\rangle\langle\psi|$ be an n-qubit quantum state and let $A \sqcup B = [n]$ be a partition of qubits. Then

$$\mathsf{S}(\rho_A) \ge \dim (\operatorname{Weyl}(|\psi\rangle)) - \dim (\operatorname{Weyl}(|\psi\rangle)_B) - |A|.$$

Proof. Let $\{b_i\}_i$ be a basis for $\operatorname{Weyl}(|\psi\rangle)_B$, and let $\{e_i\}_i$ be an extension such that, together, they span $\operatorname{Weyl}(|\psi\rangle)$. Define the subspace $S \coloneqq \langle \{e_i\}_i \rangle$. Clearly $\dim(S) = \dim(\operatorname{Weyl}(|\psi\rangle)) - \dim(\operatorname{Weyl}(|\psi\rangle)_B)$ and $S \cap (\mathbb{F}_2^{2n})_B = \{0\}$. Define $e_i^A \in (\mathbb{F}_2^{2n})_A$ to be e_i except with the coordinates not in A set to 0.

Define $S^A \coloneqq \langle \{e_i^A\}_i \rangle$.

Claim 3.5. $\dim(S^A) = \dim(S) = \dim(\operatorname{Weyl}(|\psi\rangle)) - \dim(\operatorname{Weyl}(|\psi\rangle)_B)$

Proof. dim(S) ≥ dim(S^A) is trivial, so we just need to argue that the vectors $\{e_i^A\}_i$ are linearly independent. For the sake of contradiction, assume they're not, i.e., that there exists some set of indices $I \subseteq [\dim(S)]$ such that $\sum_{i \in I} e_i^A = 0$. Note that $\sum_{i \in I} e_i \neq 0$ because is $\{e_i\}_i$ is a basis by construction. Therefore, $\sum_{i \in I} e_i$ will be zero on the coordinates of A, but not B. That is, $\sum_{i \in I} e_i \in \operatorname{Weyl}(|\psi\rangle)_B$, a contradiction. We conclude that dim $(S^A) = \dim(\operatorname{Weyl}(|\psi\rangle)) - \dim(\operatorname{Weyl}(|\psi\rangle)_B)$.

 $(\mathbb{F}_2^{2n})_A$ is a symplectic subspace, and each $e_i^A \in (\mathbb{F}_2^{2n})_A$. Therefore, S^A is a subspace of a 2|A|-dimensional symplectic subspace. By Lemma 3.3, there must exist some symplectic subspace $T^A \subseteq S^A$ of dimension at least $2(\dim(S^A) - |A|) = 2(\dim(\operatorname{Weyl}(|\psi\rangle)) - \dim(\operatorname{Weyl}(|\psi\rangle)_B) - |A|)$. Let $\{t_i^A\}_i$ be a symplectic basis of T^A . We can express each basis element as $t_i^A = \sum_j \alpha_j e_j^A$ for some setting of $\alpha_j \in \{0, 1\}$. Define $t_i \coloneqq \sum_j \alpha_j e_j$, and observe that their span defines a subspace $T \subseteq \mathbb{F}_2^{2n}$ that shares the same dimension as T'. We can then similarly define $t_i^B \in (\mathbb{F}_2^{2n})_B$ to be t_i

⁵In fact, because W_1 is symplectic, even $W_1 \cap W_1^{\perp} = \{0\}$.

except with the coordinates not in B set to 0. Observe that $t_i = t_i^A + t_i^B$. By the linearity of the symplectic product and the fact that Weyl($|\psi\rangle$) is isotropic,

$$0 = [t_i, t_j] = [t_i^A, t_j^A] + [t_i^B, t_j^B] \implies [t_i^A, t_j^A] = [t_i^B, t_j^B].$$

Therefore, $\{t_i^B\}$ is also a symplectic basis for a symplectic subspace of $(\mathbb{F}_2^{2n})_B$.

Using a Clifford circuit C^A acting locally on the qubits in A, we can perform the symplectic map that takes $\{t_i^A\}$ to the symplectic basis of $(\mathbb{F}_2^{2n})_{A'}$ where $A' \subset A$ and $|A'| = \dim(T)$.⁶ Note that $C^A(t_i^B) = t_i^B$. Using a second Clifford circuit C^B acting locally on the qubits in B, we can take $\{t_i^B\}$ to the symplectic basis of $(\mathbb{F}_2^{2n})_{B'}$ where $B' \subset B$ and $|B'| = |A'| = \dim(T)$. Note $C^B(C^A(t_i^A)) = C^A(t_i^A)$.

Claim 3.6. $C^B(C^A(T))$ is a Lagrangian subspace of $(\mathbb{F}_2^{2n})_{A' \sqcup B'}$.

Proof. It is clear from the actions of C^A and C^B that each $C^B(C^A(t_i))$ is a member of $(\mathbb{F}_2^{2n})_{A'\sqcup B'}$. Furthermore, dim $(C^B(C^A(T))) = \dim(T)$, which is half the dimension of $(\mathbb{F}_2^{2n})_{A'\sqcup B'}$. Finally, since $C^B(C^A(\operatorname{Weyl}(|\psi\rangle)))$ is isotropic, so too must $C^B(C^A(T))$ as a subset of $C^B(C^A(\operatorname{Weyl}(|\psi\rangle)))$.

We conclude that the state of the qubits indexed by $A' \sqcup B'$ is a stabilizer state $|\phi\rangle$ of $2 \dim(T)$ qubits that is unentangled from the rest of the system.

Our last step is to prove that $C^B(C^A(T))_{B'} = \{0\}$, which will imply that the entanglement across (A', B') is $\dim(T)/2$ by $[FCY^+04$, Eq. 1]. First recall that $S \cap (\mathbb{F}_2^{2n})_B = \{0\}$ by construction, which implies $T \cap (\mathbb{F}_2^{2n})_B = \{0\}$ because $T \subseteq S$. Next, we note that C^A has no effect on $(\mathbb{F}_2^{2n})_B$ since its action is local to A. Furthermore, C^B simply permutes $(\mathbb{F}_2^{2n})_B$ (and cannot map elements into $(\mathbb{F}_2^{2n})_B$). Hence,

$$C^{B}(C^{A}(T)) \cap \left(\mathbb{F}_{2}^{2n}\right)_{B} = C^{B}(C^{A}(T)) \cap C^{B}(C^{A}(\left(\mathbb{F}_{2}^{2n}\right)_{B}) = T \cap \left(\mathbb{F}_{2}^{2n}\right)_{B} = \{0\}.$$

Finally, since $(\mathbb{F}_2^{2n})_{B'} \subseteq (\mathbb{F}_2^{2n})_B$,

$$C^{B}(C^{A}(T))_{B'} = C^{B}(C^{A}(T)) \cap (\mathbb{F}_{2}^{2n})_{B'} = \{0\}.$$

Because C^A and C^B act locally on A and B respectively, they do not change the entanglement between A and B, thus completing the proof.

4 The Algorithm

We present and analyze our algorithm for estimating the entanglement entropy across any bipartition of qubits. At a high level, our algorithm computes the upper and lower bounds given in Theorem 3.1. The details are presented below in Algorithm 1.

⁶Again, this mapping is described in detail in [GIKL23a, Section 3].

Algorithm 1: Estimating Entanglement Entropy

Input: $\frac{8\ln(1/\delta)+16n}{\varepsilon^2} \text{ copies of } \rho = |\psi\rangle\langle\psi|, A \sqcup B = [n], \varepsilon \in (0, 3/8), \text{ and } \delta \in (0, 1]$ Promise: $|\psi\rangle$ has stabilizer dimension at least n - kOutput: $\ell, u \in \mathbb{R}$ such that $\ell \leq \mathsf{S}(\rho_A) \leq u$ and $0 \leq u - \ell \leq k + \max\{0, 2(\varepsilon n + \mathsf{H}(\varepsilon)) - 1\},$ with probability at least $1 - \delta$ 1 Perform Bell difference sampling to draw $\frac{2\ln(1/\delta)+4n}{\varepsilon^2}$ samples from q_{ψ} .
2 Let S be the symplectic complement of the subspace spanned by the samples.
3 Let $r \coloneqq \begin{cases} 0 & \dim(S) = n - k, \\ \varepsilon n + \mathsf{H}(\varepsilon) & \dim(S) > n - k. \end{cases}$ 4 Let $u \coloneqq \min\{|A| - \dim S_A, |B| - \dim S_B\} + r.$ 5 Let $\ell \coloneqq \max\{\dim S - \dim S_B - |A|, \dim S - \dim S_A - |B|\} - r.$

6 return (ℓ, u)

Let us make a few remarks on Algorithm 1. Note that the bounds (u, ℓ) produced by our algorithm are within a range of $k + \max\{0, 2(\varepsilon n + \mathsf{H}(\varepsilon)) - 1\}$ rather than $k + 2(\varepsilon n + \mathsf{H}(\varepsilon))$ as one might naïvely expect. This comes from a subtle case in our analysis, the details of which are contained in the proof of Theorem 4.3. We observe that in the case where our sampling procedure happens to find the exact subspace $\operatorname{Weyl}(|\psi\rangle)$, we no longer need to apply Lemma 2.2. Conversely, when our sampling procedure fails to find $\operatorname{Weyl}(|\psi\rangle)$ exactly, the distance between the bounds in Lemmas 3.2 and 3.4 decreases by at least 1.

We also note that the Bell difference sampling procedure only needs to be performed once. After that, one can compute entanglement entropy bounds across any cut of qubits with only classical post-processing.

To prove the correctness of Algorithm 1, we use the following two statements. The first is about the time complexity of computing symplectic complements. The second says that Bell difference sampling suffices to approximately recover Weyl($|\psi\rangle$).

Fact 4.1 ([GIKL23a, Lemma 3.1]). Given a set of m vectors whose span is a subspace $H \subseteq \mathbb{F}_2^{2n}$, there is an algorithm that outputs a basis for H^{\perp} in $O(mn \cdot \min(m, n))$ time.

Lemma 4.2 ([GIKL23a, Proof of Theorem 5.1]). Let $|\psi\rangle$ have stabilizer dimension at least n - k, and let S be the symplectic complement of the space spanned by $\frac{2\ln(1/\delta)+4n}{\varepsilon}$ samples from q_{ψ} , for some $\varepsilon \in (0,3/8)$. Then with probability at least $1 - \delta$, there exists a state $|\phi\rangle$ such that S =Weyl($|\phi\rangle$) \supseteq Weyl($|\psi\rangle$) and $|\langle\psi|\phi\rangle|^2 \ge 1 - \varepsilon$.

We now show our main result, namely that Algorithm 1 is correct as specified.

Theorem 4.3. Algorithm 1 is correct and runs in time $O\left(\frac{n^3+n^2\log(1/\delta)}{\varepsilon^2}\right)$.

Proof. Let S be the symplectic complement of the subspace spanned by our $\frac{2\ln(1/\delta)+4n}{\varepsilon^2}$ samples from q_{ψ} . We note that these samples take 4 copies of ρ and O(n) time each, and that S can be computed in time $O\left(\frac{n^3+n^2\log(1/\delta)}{\varepsilon^2}\right)$ by Fact 4.1. By Lemma 4.2, with probability at least $1-\delta$, there exists a state $|\phi\rangle$ such that $S = \text{Weyl}(|\phi\rangle) \supseteq$

By Lemma 4.2, with probability at least $1-\delta$, there exists a state $|\phi\rangle$ such that $S = \text{Weyl}(|\phi\rangle) \supseteq$ Weyl $(|\psi\rangle)$ and $|\langle \psi | \phi \rangle|^2 \ge 1 - \varepsilon^2$, and therefore $\text{dist}_{\text{tr}}(|\psi\rangle, |\phi\rangle) \le \varepsilon$. Assume henceforth that S and $|\phi\rangle$ satisfy these criteria. In fact, we can further assume $\text{dist}_{\text{tr}}(|\psi\rangle, |\phi\rangle) \le d$, where

$$d := \begin{cases} 0 & \dim(S) = n - k, \\ \varepsilon & \dim(S) > n - k, \end{cases}$$

because if dim(S) = n - k, we must have $S = \text{Weyl}(|\psi\rangle)$, and hence we can choose $|\phi\rangle = |\psi\rangle$. Let $\sigma = |\phi\rangle\langle\phi|$. By Lemma 3.2, we have

$$u' \coloneqq \min\{|A| - \dim S_A, |B| - \dim S_B\} \ge \mathsf{S}(\sigma_A).$$

Similarly, Lemma 3.4 implies

$$\ell' \coloneqq \max\{\dim S - \dim S_B - |A|, \dim S - \dim S_A - |B|\} \le \mathsf{S}(\sigma_A).$$

Note that r = dn + H(d), $\ell = \ell' - r$, and u = u' + r. Recalling that $\operatorname{dist}_{\operatorname{tr}}(|\psi\rangle, |\phi\rangle) \leq d$, Lemma 2.2 implies that $\ell \leq S(\rho_A) \leq u$. So, this establishes that u and ℓ are upper and lower bounds, respectively, on the entanglement entropy.

It remains to bound the difference between u and ℓ . Observe that

$$u - \ell = (u' + r) - (\ell' - r)$$

$$\leq (|A| - \dim S_A) - (\dim S - \dim S_A - |B|) + 2r$$

$$= |A| + |B| - \dim S + 2r$$

$$= n - \dim S + 2r.$$

In the case where dim S = n - k, we have $u - \ell \leq k$. Otherwise, when dim(S) > n - k, we have

$$n - \dim S + 2r \le n - (n - k + 1) + 2r$$
$$= k + 2r - 1$$
$$= k + 2(\varepsilon n + \mathsf{H}(\varepsilon)) - 1.$$

In both cases, for all $S \supseteq \text{Weyl}(|\psi\rangle)$, we have

$$u - \ell \le k + \max\{0, 2r - 1\},\$$

which completes the proof.

If we take ε to be sufficiently small, we can disregard the additional additive error 2r-1.

Corollary 4.4. By setting $\varepsilon = \frac{1}{8n}$, Algorithm 1 outputs upper and lower bounds on the entanglement entropy (u, ℓ) such that $u - \ell \leq k$ with probability at least $1 - \delta$. It now uses $1024n^3 + 512n^2 \ln(1/\delta)$ samples of $|\psi\rangle$ and runs in time $O(n^5 + n^4 \log(1/\delta))$.

Proof. Assume $n \ge 2$, because we don't need to compute the entanglement of a single qubit state. Fact 2.1 tells us that $H(\varepsilon) < 0.37$, and therefore $2(\varepsilon n + H(\varepsilon)) - 1 < 2(1/8 + 0.37) - 1 < 0$. So, $\max\{0, 2(\varepsilon n + H(\varepsilon)) - 1\} = 0$. We then appeal to Theorem 4.3.

As a corollary, we can show a lower bound on the number of non-Clifford gates necessary to prepare pseudoentangled states.

Corollary 4.5. Any family of Clifford circuits that produces a pseudoentangled ensemble $\{|\Psi_k\rangle, |\Phi_k\rangle\}_k$ with entropy gap f(n) vs. g(n) satisfying $f(n) - g(n) \ge t$ must use $\Omega(t)$ auxiliary non-Clifford single-qubit gates.

 -	

Proof. Suppose t' non-Clifford gates are used to construct $\{|\Psi_k\rangle\}_k$ and $\{|\Phi_k\rangle\}_k$. We argue that if 2t' < t, these state ensembles can be distinguished with non-negligible advantage in polynomial time.

All such states $|\Psi_k\rangle$ and $|\Phi_k\rangle$ have stabilizer dimension at least n - 2t', by Fact 2.12. The distinguisher, then, is the following: given copies of an unknown $|\psi\rangle$ belonging to one of the two ensembles, run Algorithm 1 according to Corollary 4.4, assuming stabilizer dimension at least n-2t' and $\delta = 1/3$. This produces bounds (u, ℓ) on the entanglement entropy of $|\psi\rangle$ across some fixed cut (A, B) of size n/2. Then, output that $|\psi\rangle \in \{|\Psi_k\rangle\}_k$ if $\ell \leq f(n) \leq u$, and output $|\psi\rangle \in \{|\Phi_k\rangle\}_k$ otherwise. The algorithm guesses correctly with probability at least 2/3, because $u - \ell \leq 2t'$, so at most one of f(n) and g(n) can lie between u and ℓ .

Acknowledgments

We thank Tony Metger for suggesting this problem to us, and Fermi Ma for helpful conversations.

SG is supported (via Scott Aaronson) by a Vannevar Bush Fellowship from the US Department of Defense, the Berkeley NSF-QLCI CIQC Center, a Simons Investigator Award, and the Simons "It from Qubit" collaboration. VI is supported by an NSF Graduate Research Fellowship. WK acknowledges support from the U.S. Department of Energy, Office of Science, National Quantum Information Science Research Centers, Quantum Systems Accelerator. DL is supported by NSF award FET-2243659.

This work was done in part while SG, VI, and DL were visiting the Simons Institute for the Theory of Computing.

References

- [ABF⁺24] Scott Aaronson, Adam Bouland, Bill Fefferman, Soumik Ghosh, Umesh Vazirani, Chenyi Zhang, and Zixin Zhou. Quantum Pseudoentanglement. In 15th Innovations in Theoretical Computer Science Conference (ITCS 2024), volume 287 of Leibniz International Proceedings in Informatics (LIPIcs), pages 2:1–2:21, 2024. doi:10.4230/LIPIcs.ITCS.2024.2. [pp. 1, 2]
- [AG04] Scott Aaronson and Daniel Gottesman. Improved Simulation of Stabilizer Circuits. Physical Review A, 70(5), 2004. doi:10.1103/physreva.70.052328. [p. 2]
- [AG08] Scott Aaronson and Daniel Gottesman. Identifying Stabilizer States, 2008. https://pirsa.org/08080052. [p. 2]
- [AG23] Scott Aaronson and Sabee Grewal. Efficient Tomography of Non-Interacting-Fermion States. In 18th Conference on the Theory of Quantum Computation, Communication and Cryptography (TQC 2023), volume 266 of Leibniz International Proceedings in Informatics (LIPIcs), pages 12:1–12:18, 2023. doi:10.4230/LIPIcs.TQC.2023.12. [p. 2]
- [Aud07] Koenraad M. R. Audenaert. A sharp continuity estimate for the von Neumann entropy. Journal of Physics A: Mathematical and Theoretical, 40(28):8127, 2007.
 doi:10.1088/1751-8113/40/28/S18. [pp. 4, 5]

- [BBC⁺19] Sergey Bravyi, Dan Browne, Padraic Calpin, Earl Campbell, David Gosset, and Mark Howard. Simulation of quantum circuits by low-rank stabilizer decompositions. *Quan*tum, 3:181, 2019. doi:10.22331/q-2019-09-02-181. [p. 2]
- [BG16] Sergey Bravyi and David Gosset. Improved Classical Simulation of Quantum Circuits Dominated by Clifford Gates. *Phys. Rev. Lett.*, 116:250501, 2016. doi:10.1103/PhysRevLett.116.250501. [p. 2]
- [BK05] Sergey Bravyi and Alexei Kitaev. Universal quantum computation with ideal Clifford gates and noisy ancillas. *Phys. Rev. A*, 71:022316, 2005. doi:10.1103/PhysRevA.71.022316. [p. 2]
- [CLL23] Nai-Hui Chia, Ching-Yi Lai, and Han-Hsuan Lin. Efficient learning of *t*-doped stabilizer states with single-copy measurements, 2023. arXiv:2308.07014. [p. 2]
- [FCY⁺04] David Fattal, Toby S. Cubitt, Yoshihisa Yamamoto, Sergey Bravyi, and Isaac L. Chuang. Entanglement in the stabilizer formalism, 2004. arXiv:quant-ph/0406168. [pp. 2, 3, 8, 10]
- [FLY22] Zhiyuan Fan, Jiatu Li, and Tianqi Yang. The Exact Complexity of Pseudorandom Functions and the Black-Box Natural Proof Barrier for Bootstrapping Results in Computational Complexity. In Proceedings of the 54th Annual ACM SIGACT Symposium on Theory of Computing, STOC 2022, page 962–975, 2022. doi:10.1145/3519935.3520010. [p. 3]
- [GIKL23a] Sabee Grewal, Vishnu Iyer, William Kretschmer, and Daniel Liang. Efficient Learning of Quantum States Prepared With Few Non-Clifford Gates, 2023. arXiv:2305.13409. [pp. 2, 3, 4, 8, 10, 11]
- [GIKL23b] Sabee Grewal, Vishnu Iyer, William Kretschmer, and Daniel Liang. Efficient Learning of Quantum States Prepared With Few Non-Clifford Gates II: Single-Copy Measurements, 2023. arXiv:2308.07175. [pp. 2, 3, 4]
- [GIKL23c] Sabee Grewal, Vishnu Iyer, William Kretschmer, and Daniel Liang. Improved Stabilizer Estimation via Bell Difference Sampling, 2023. arXiv:2304.13915. [pp. 2, 3, 4, 7, 8]
- [GIKL23d] Sabee Grewal, Vishnu Iyer, William Kretschmer, and Daniel Liang. Low-Stabilizer-Complexity Quantum States Are Not Pseudorandom. In 14th Innovations in Theoretical Computer Science Conference (ITCS 2023), volume 251 of Leibniz International Proceedings in Informatics (LIPIcs), pages 64:1-64:20, 2023. doi:10.4230/LIPIcs.ITCS.2023.64. [p. 2]
- [GNW21] David Gross, Sepehr Nezami, and Michael Walter. Schur-Weyl duality for the Clifford group with applications: Property testing, a robust Hudson theorem, and de Finetti representations. *Communications in Mathematical Physics*, 385(3):1325–1393, 2021. doi:10.1007/s00220-021-04118-7. [p. 8]
- [GOL24] Andi Gu, Salvatore F. E. Oliviero, and Lorenzo Leone. Magic-induced computational separation in entanglement theory, 2024. arXiv:2403.19610. [p. 3]
- [GTB23] Tudor Giurgica-Tiron and Adam Bouland. Pseudorandomness from subset states, 2023. arXiv:2312.09206. [p. 2]

- [HG23] Dominik Hangleiter and Michael J. Gullans. Bell sampling from quantum circuits, 2023. arXiv:2306.00083v1. [p. 2]
- [IKOS08] Yuval Ishai, Eyal Kushilevitz, Rafail Ostrovsky, and Amit Sahai. Cryptography with Constant Computational Overhead. In Proceedings of the Fortieth Annual ACM Symposium on Theory of Computing, STOC '08, page 433–442, 2008. doi:10.1145/1374376.1374438. [p. 3]
- [LC22] Ching-Yi Lai and Hao-Chung Cheng. Learning Quantum Circuits of Some T Gates. IEEE Transactions on Information Theory, 68(6):3951–3964, 2022.
 doi:10.1109/TIT.2022.3151760. [p. 2]
- [LOH23] Lorenzo Leone, Salvatore F. E. Oliviero, and Alioscia Hamma. Learning t-doped stabilizer states, 2023. arXiv:2305.15398v1. [p. 2]
- [LOLH22] Lorenzo Leone, Salvatore F. E. Oliviero, Seth Lloyd, and Alioscia Hamma. Learning efficient decoders for quasi-chaotic quantum scramblers, 2022. arXiv:2212.11338. [p. 2]
- [Ma24] Fermi Ma. Personal communication, 2024. [p. 3]
- [Mon17] Ashley Montanaro. Learning stabilizer states by Bell sampling, 2017. arXiv:1707.04012. [pp. 2, 3, 8]
- [RLCK19] Patrick Rall, Daniel Liang, Jeremy Cook, and William Kretschmer. Simulation of qubit quantum circuits via Pauli propagation. *Phys. Rev. A*, 99:062337, 2019. doi:10.1103/PhysRevA.99.062337. [p. 2]
- [Shi02] Yaoyun Shi. Both Toffoli and Controlled-NOT need little help to do universal quantum computation, 2002. arXiv:quant-ph/0205115. [p. 2]
- [Val02] Leslie G. Valiant. Quantum Circuits That Can Be Simulated Classically in Polynomial Time. SIAM Journal on Computing, 31(4):1229–1254, 2002. doi:10.1137/S0097539700377025. [p. 2]