MER 2024: Semi-Supervised Learning, Noise Robustness, and Open-Vocabulary Multimodal Emotion Recognition

Zheng Lian Institute of Automation, Chinese Academy of Sciences (CAS) Beijing, China

Zhuofan Wen Institute of Automation, CAS Beijing, China

Hao Gu Institute of Automation, CAS Beijing, China

Xie Chen Shanghai Jiao Tong University Shanghai, China

Kele Xu National University of Defense Technology Beijing, China

> Guoying Zhao University of Oulu Oulu, Finland

ABSTRACT

Multimodal emotion recognition is an important research topic in artificial intelligence. Over the past few decades, researchers have made remarkable progress by increasing dataset size and building more effective architectures. However, due to various reasons (such as complex environments and inaccurate labels), current systems still cannot meet the demands of practical applications. Therefore, we plan to organize a series of challenges around emotion recognition to further promote the development of this field. Last year, we launched MER2023¹, focusing on three topics: multi-label learning, noise robustness, and semi-supervised learning. This year, we continue to organize MER2024². In addition to expanding the dataset size, we introduce a new track around open-vocabulary emotion recognition. The main consideration for this track is that existing

² https://zeroqiaoba.github.io/MER2024-website

MM '24, October 28-November 1, 2024, Melbourne, Australia

© 2024 Copyright held by the owner/author(s).

ACM ISBN 978-x-xxxx-x/YY/MM.

https://doi.org/XXXXXXXXXXXXXXX

Haiyang Sun Institute of Automation, CAS Beijing, China

Siyuan Zhang Institute of Automation, CAS Beijing, China

Jinming Zhao Renmin University of China Beijing, China

Jiangyan Yi Institute of Automation, CAS Beijing, China

Bin Liu Institute of Automation, CAS Beijing, China

Björn W. Schuller Imperial College London London, United Kingdom Licai Sun Institute of Automation, CAS Beijing, China

Shun Chen Institute of Automation, CAS Beijing, China

Ziyang Ma Shanghai Jiao Tong University Shanghai, China

Rui Liu Inner Mongolia University Inner Mongolia, China

Erik Cambria Nanyang Technological University Singapore

> Jianhua Tao Tsinghua University Beijing, China

datasets often fix the label space and use majority voting to enhance annotator consistency, but this process may limit the model's ability to describe subtle emotions. In this track, we encourage participants to generate any number of labels in any category, aiming to describe the emotional state as accurately as possible. Our baseline is based on MERTools³ and the code is available at: https://github.com/zeroQiaoba/MERTools/tree/master/MER2024.

CCS CONCEPTS

• Computing methodologies → Neural networks; Artifcial intelligence; Computer vision; Natural language processing.

KEYWORDS

MER 2024, multimodal emotion recognition, semi-supervised learning, noise robustness, open-vocabulary emotion recognition

ACM Reference Format:

Zheng Lian, Haiyang Sun, Licai Sun, Zhuofan Wen, Siyuan Zhang, Shun Chen, Hao Gu, Jinming Zhao, Ziyang Ma, Xie Chen, Jiangyan Yi, Rui Liu, Kele Xu, Bin Liu, Erik Cambria, Guoying Zhao, Björn W. Schuller, and Jianhua Tao. 2024. MER 2024: Semi-Supervised Learning, Noise Robustness, and Open-Vocabulary Multimodal Emotion Recognition. In *Proceedings of the 32st ACM International Conference on Multimedia (MM '24), October 28-November 1, 2024, Melbourne, Australia.* ACM, New York, NY, USA, 9 pages. https://doi.org/XXXXXXXXXXXXXX

¹ http://merchallenge.cn/mer2023

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

³ https://github.com/zeroQiaoba/MERTools

1 INTRODUCTION

Multimodal emotion recognition plays an important role in humancomputer interaction. With the development of deep learning, researchers have made significant progress in this task. However, it still cannot be well addressed, and the emotion recognition performance still cannot meet the requirements of practical applications [1]. To promote the development of this field, last year, we launched MER2023 [2], focusing on three interesting topics: multi-label learning, noise robustness, and semi-supervised learning. This year, we continue the latter two tracks and add a new track around openvocabulary emotion recognition, aiming to describe the emotional state as accurately as possible.

First, it is difficult to collect large amounts of samples with emotion labels. On the one hand, the collected samples usually have no emotion (i.e. *neutral*) [3]. On the other hand, emotions have inherent subjectivity. To increase annotation consistency, researchers often hire multiple annotators and adopt majority voting [4], significantly increasing labor costs. To address the problem of data sparseness, researchers revolve around unsupervised or semi-supervised learning and use unlabeled data during training. Furthermore, MERBench [1] points out the necessity of using unlabeled data from the same domain as labeled data. Therefore, we provide a large number of human-centric unlabeled videos in MER2024 and encourage participants to explore more effective unsupervised or semi-supervised learning strategies for better performance.

Meanwhile, noise generally exists in the video. It is hard to guarantee that every video is free of any audio noise and each frame is in high-resolution. To improve noise robustness, researchers have carried out a series of works on emotion recognition under noise conditions [5]. However, there lacks a benchmark dataset to fairly compare different strategies. Therefore, we organize a track around noise robustness. Although there are many types of noise, we consider the two most common ones: audio additive noise and image blur noise. We encourage participants to exploit data augmentation [6] or other effective techniques [7, 8] to improve the noise robustness of emotion recognition systems.

Furthermore, emotions are subjective and ambiguous. To increase annotation consistency, existing datasets typically limit the label space to a few discrete labels. Then, they employ multiple annotators and use majority voting to select the most likely label. However, this process may cause some correct but non-candidate or non-majority labels to be ignored, resulting in inaccurate annotations. To this end, we introduce a new track around openvocabulary emotion recognition. We encourage participants to generate any number of labels in any category, trying to describe emotions accurately.

To sum up, MER2024 contains three tracks: MER-SEMI, MER-NOISE, and MER-OV. In MER-SEMI, we encourage participants to use unlabeled data for better performance; in MER-NOISE, we focus on the systems' noise robustness; in MER-OV, we ask participants to describe the emotional state as accurately as possible. This challenge provides participants with a platform to fairly compare the performance of different methods. In the remainder of this paper, we introduce the dataset, baseline systems, evaluation metrics, and experimental results for each track.



Figure 1: Dataset construction pipeline for MER2024.

2 CHALLENGE DATASET

MER2024 is an extended version of MER2023 [2]. Figure 1 shows the dataset construction pipeline. Specifically, MER2023 contains four subsets: Train&Val, MER-MULTI, MER-NOISE, and MER-SEMI. In the last subset, besides labeled samples, it also contains a large amount of unlabeled data. In MER2024, we merge all labeled samples and get the updated Train&Val. Meanwhile, we collect more unlabeled data and select some unlabeled samples for annotation, getting MER-SEMI and MER-NOISE. For MER-OV, we select 332 samples from Train&Val and rely on LLMs to extract open-vocabulary labels from emotion-related descriptions (see Section 2.3 for more details). Table 1 provides statistics for MER2023 and MER2024.

2.1 Data Collection

As shown in Figure 1, MER2024 increases the number of unlabeled samples. The data collection process is borrowed from MER2023 and includes two key steps: video cutting and video filtering.

Video Cutting. To simulate real scenarios, we collect raw video from movies and TV series. However, the raw video is often long and have multiple characters. It is impossible to assign an emotion label to the entire video. Therefore, we need to split the raw video into video clips. In this process, we require that the video clips should contain relatively complete content from the same character. Considering that the timestamps in subtitles are generally accurate, for videos with subtitles, we directly use these timestamps for video segmentation. For videos without subtitles, we use the voice activity detection toolkit, Silero VAD⁴, to segment the video and the speaker identification toolkit, Deep Speaker⁵, to merge the consecutive clips if they are likely to be from the same speaker.

Video Filtering. In the previous step, we aim to generate video clips containing relatively complete content from the same speaker. However, it only guarantees that the audio is from the same character, not that there is one character in the visual frames. Therefore, we further filter these video clips. Specifically, we use the face detection toolkit, YuNet⁶, to ensure that most frames contain only

Lian et al.

 $^{^{4}} https://github.com/snakers4/silero-vad$

⁵ https://github.com/philipperemy/deep-speaker

⁶ https://github.com/ShiqiYu/libfacedetection

MER 2024: Semi-Supervised Learning, Noise Robustness, and Open-Vocabulary Multimodal Emotion Recognition MM '24, October 28-November 1, 2024, Melbourne, Australia

Table 1: Statistics for MER2023 and MER2024. Here, "A/B" means that there are B samples in the subset and we only annotate A samples for performance evaluation.

MER2023	# of samples (labeled/whole)	MER2024	# of samples (labeled/whole)
Train&Val	3373	Train&Val	5030
MER-MULTI	411	MER-SEMI	1169/115595
MER-NOISE	412	MER-NOISE	1170/115595
MER-SEMI	834/73982	MER-OV	322

one face. Then, we use the face recognition toolkit, face.evoLVe⁷, to ensure that these faces belong to the same person. Additionally, the length of video clips is also important. Video clips that are too short generally cannot express the complete meaning; video clips that are too long may contain emotional changes, making it difficult to accurately describe the emotional state with one label. Therefore, we perform an additional filtering operation, only selecting video clips between $2\sim16$ seconds.

2.2 MER-SEMI and MER-NOISE

Annotating all unlabeled data requires significant labor costs. To reduce the cost, we only select samples with a high probability of explicit emotions for labeling. Specifically, we use the top-16 prediction results in last year's challenge and calculate the proportion of primary labels as the basis for selection. For example, if a sample is predicted as *happy* 10 times and *neutral* 6 times, its score is v = 10/16. Then, taking into account the score and class balance, we select a total of 6,000 samples for labeling. During the annotation process, we hire 5 annotators and only select samples in which at least 4 annotators assign the same label, resulting in 2,339 labeled samples. All these samples are equally divided into two parts, one for MER-SEMI and the other for MER-NOISE.

In MER-NOISE, we need to add noise to the video. This paper considers two types of noise: audio additive noise and image blur noise. For the audio modality, we select noise from the MUSAN dataset [9], which contains three subsets: *music, noise,* and *speech.* The noise in the first two subsets may convey emotions, thus affecting the emotion of the raw audio. For example, rain and thunder may lead to a negative sentiment, while a pleasant breeze may generate a positive sentiment. Therefore, we only use the noise in the last subset. In this process, we randomly select a speech-to-noise ratio (SNR) between 5dB~10dB and randomly select noise from the *speech* subset. For the visual modality, image blur is a common noise. To generate blurry images, we downsample the image to lose some details, and then upsample the low-resolution image to keep the size unchanged. In this process, we randomly select a downsampling factor from $r = \{1, 2, 4\}$.

2.3 MER-OV

MER-OV focuses on open-vocabulary emotion recognition. Unlike MER-SEMI and MER-NOISE which only predict the most likely emotion within a fixed label space, MER-OV needs to predict any number of emotions in any category, trying to describe the emotional state as accurately as possible. Previously, we made an initial attempt on this task [10]. Specifically, we first annotate emotionrelated acoustic and visual clues. Then, we rely on the LLMs' reasoning ability and use these clues to disambiguate video subtitles. This process can generate descriptions containing more subtle emotional labels. Finally, we use ChatGPT to extract all labels using the following prompt:

Please assume the role of an expert in the field of emotions. We provide clues that may be related to the emotions of the characters. Based on the provided clues, please identify the emotional states of the main characters. Please separate different emotional categories with commas and output only the clearly identifiable emotional categories in list format. If none are identified, please output an empty list.

Due to the high annotation cost, we only select 332 samples for annotation [10]. Through this process, we can generate an average of 2.92 labels per sample. We encourage participants to use MLLMs directly or to further conduct instruction fine-tuning with our annotated samples to solve this task.

2.4 Challenge Protocol

To download the dataset, participants should fill out an End User License Agreement (EULA)⁸. It requires participants to use this dataset only for academic research and not to edit or upload it to the Internet. For MER-SEMI and MER-NOISE, each team should submit the most likely discrete label among the 6 candidate labels (i.e., worried, happy, neutral, angry, surprised, and sad). For MER-OV, each team can submit any number of labels in any category. For all tracks, participants should predict results for all 115,595 unlabeled data, although we only evaluate a small subset. This requires participants to focus on the generalization ability and develop systems that do not require a large amount of inference time. Additionally, it is worth noting that participants cannot manually annotate the samples in MER2024. We will ask them to submit their code for further checking. Finally, each team should submit a paper describing their method, otherwise, the submitted results will not be included in the final leaderboard.

3 BASELINES AND EVALUATION METRICS

We first introduce the baselines of these tracks. For MER-SEMI and MER-NOISE, we establish the baseline based on MERTools⁹. For MER-OV, we use MLLMs as the baselines since these models can solve various multimodal tasks. Then, we illustrate implementation details and evaluation metrics for each track.

3.1 MER-SEMI and MER-NOISE

Feature selection and fusion are crucial to building an effective emotion recognition system. Regarding feature selection, we adopt the recommendations of MERBench [1]. Language compatibility is important for both lexical and acoustic features. Therefore, we mainly choose encoders trained in Chinese corpora. For visual features, domain compatibility is also important. Therefore, in addition to encoders trained on action or caption datasets, we also select

⁷ https://github.com/ZhaoJ9014/face.evoLVe

⁸ https://drive.google.com/file/d/1cXNfKHyJzVXg_7kWSf_nVKtsxIZVa517/view?usp=sharing ⁹ https://github.com/zeroQiaoba/MERTools

		· · · · · · · · · · · · · · · · · · ·	/1 C	• 11	401
Table 2: Prompt for generatin	g emotion-related descr	inflong using MILLMS	drawn from our	previous work l	101).
Tuble It I tompt for Senerating		perone aong maanie			

Models	Prompt
Audio LLM	Subtitle content of the audio: {subtitle}; As an expert in the field of emotions, please focus on the
	acoustic information and subtitle content in the audio to discern clues related to the emotions of the
	individual. Please provide a detailed description and ultimately predict the emotional state of the
	individual in the audio.
	Subtitle content of the video: {subtitle}; As an expert in the field of emotions, please focus on the facial
Video LLM	expressions, body movements, environment, subtitle content, etc., in the video to discern clues related
VIGEO LLIVI	to the emotions of the individual. Please provide a detailed description and ultimately predict the
	emotional state of the individual in the video.
	Subtitle content of the video: {subtitle} As an expert in the field of emotions, please focus on the facial
Audio-Video LLM	expressions, body movements, environment, acoustic information, subtitle content, etc., in the video
	to discern clues related to the emotions of the individual. Please provide a detailed description and
	ultimately predict the emotional state of the individual in the video.

encoders trained on human-centric videos. Table 6 lists model cards for some representative unimodal encoders.

Regarding fusion strategies, MERBench points out that the attention mechanism can achieve relatively good performance among all algorithms [1]. The reason lies in that the labeled samples are limited in emotion recognition. A complex architecture can easily lead to the overfitting problem, affecting the model's generalization ability on unseen data. Specifically, assume that acoustic, lexical, and visual features are $f_a \in \mathbb{R}^{d_a}$, $f_l \in \mathbb{R}^{d_l}$, $f_v \in \mathbb{R}^{d_v}$, respectively. During the fusion process, we first map these features to a fixed dimension d:

$$h_m = \operatorname{ReLU}\left(f_m W_m + b_m\right), m \in \{a, l, v\},\tag{1}$$

where $W_m \in \mathbb{R}^{d_m \times d}$ and $b_m \in \mathbb{R}^d$ are trainable parameters. Then, we calculate the attention score for each modality:

$$h = \text{Concat}(h_a, h_l, h_v), \qquad (2)$$

$$\alpha = \operatorname{softmax}\left(h^T W_{\alpha} + b_{\alpha}\right), \qquad (3)$$

where $W_{\alpha} \in \mathbb{R}^{d \times 1}$ and $b_{\alpha} \in \mathbb{R}^{1}$ are trainable parameters. Here, $h \in \mathbb{R}^{d \times 3}$ and $\alpha \in \mathbb{R}^{3 \times 1}$. The fused multimodal feature $z = h\alpha \in \mathbb{R}^{d}$ is used for subsequent emotion recognition.

3.2 MER-OV

Open-vocabulary emotion recognition is a new task that lacks largescale training data. Considering that MLLMs can handle various multimodal tasks, we choose MLLMs as the baselines. Meanwhile, temporal information is important for understanding the emotions. Therefore, we select MLLMs that support at least audio or video input, including video LLMs (such as VideoChat [11]), audio LLMs (such as SALMONN [12]), and audio-video LLMs (such as PandaGPT [13]). In practice, we first use the prompt in Table 2 to generate emotion-relevant descriptions that contain multi-faceted and multimodal clues. During inference, we add subtitles as additional input. Then, we use the prompt in Section 2.3 to extract all emotion labels in an open-vocabulary manner.

3.3 Implementation Details

For MER-OV, we directly use pretrained MLLMs. We rely on GPT-3.5 ("gpt-3.5-turbo-16k-0613") to generate emotions in an openvocabulary manner. For MER-SEMI and MER-NOISE, we use the attention mechanism for multimodal fusion. This process involves one hyper-parameter, i.e., the dimension of hidden representation *d*, and we choose *d* from {64, 128, 256}. During training, we use the Adam optimizer and choose the learning rate from $\{10^{-3}, 10^{-4}\}$. To alleviate the overfitting problem, we also use Dropout and select the rate from $\{0.2, 0.3, 0.4, 0.5\}$. Therefore, a total of 3 hyper-parameters need to be adjusted. To find the optimal hyper-parameters, we randomly select 50 parameter combinations and choose the model that performed best in five-fold cross-validation. Then, we report its average result and standard deviation.

3.4 Evaluation Metrics

For MER-SEMI and MER-NOISE, we choose two widely used metrics in emotion recognition: accuracy and weighted average F-score (WAF) [38]. Considering the inherent class imbalance, we choose WAF as the final ranking. For MER-OV, we draw on our previous work [10], in which we extend traditional classification metrics (i.e., accuracy and recall) and define set-level metrics. Specifically, assume that the true label set is $\{y_i\}_{i=1}^M$ and the predicted label set is $\{\hat{y}_i\}_{i=1}^N$, where *M* and *N* are the number of labels. Considering that there may be labels with different expressions but the same meaning, we first use ChatGPT to group all labels:

Please assume the role of an expert in the field of emotions. We provide a set of emotions. Please group the emotions, with each group containing synonyms or consistent emotional terms. Directly output the results, with each group in list format.

Following that, we map these labels to their group IDs, where the mapping function is defined as $G(\cdot)$:

$$Y = \{G(x) | x \in \{y_i\}_{i=1}^M\},\tag{4}$$

$$\hat{Y} = \{G(x) | x \in \{\hat{y}_i\}_{i=1}^N \}.$$
(5)

The set-level accuracy and recall are defined as follows:

$$Accuracy_s = \frac{|Y \cap Y|}{|\hat{Y}|},\tag{6}$$

MER 2024: Semi-Supervised Learning, Noise Robustness, and Open-Vocabulary Multimodal Emotion Recognition MM '24, October 28-November 1, 2024, Melbourne, Australia

Table 3: Unimodal results (%). In addition to five-fold cross-validation results on Train&Val, we also report results on MER-SEMI and MER-NOISE. These features are ordered by the average WAF score on Train&Val, MER-SEMI, and MER-NOISE. The values in gray columns are used as the final ranking metric for these tracks.

	Train&Val		MER-SEMI		MER-NOISE		Average	
Feature	WAF (↑)	ACC (↑)	WAF (\uparrow)	ACC (↑)	WAF (\uparrow)	ACC (↑)	WAF (\uparrow)	ACC (↑)
Visual Modality								
VideoMAE-base [14]	52.86 ± 0.23	53.27 ± 0.21	47.37±0.41	52.04 ± 0.16	48.53±0.39	51.81 ± 0.26	49.59	52.37
EmoNet [15]	51.76 ± 0.31	53.18 ± 0.10	52.45 ± 0.18	54.94 ± 0.15	51.22 ± 0.21	53.56 ± 0.43	51.81	53.90
VideoMAE-large [14]	57.04±0.25	57.49 ± 0.30	51.05 ± 0.39	55.73 ± 0.41	50.81 ± 0.28	55.22 ± 0.62	52.97	56.15
DINOv2-large [16]	58.44±0.12	59.57 ± 0.15	53.41 ± 0.26	57.47 ± 0.22	52.37 ± 0.31	56.10 ± 0.14	54.74	57.71
SENet-FER2013 [17]	57.67±0.10	58.79 ± 0.16	54.62 ± 0.16	56.36 ± 0.24	52.31 ± 0.24	54.79 ± 0.16	54.87	56.65
ResNet-FER2013 [18]	58.73±0.30	59.66 ± 0.16	53.07 ± 0.20	55.13 ± 0.27	53.26 ± 0.29	55.54 ± 0.20	55.02	56.78
MANet-RAFDB [19]	59.91±0.12	$61.10 {\pm} 0.11$	56.59 ± 0.31	58.87 ± 0.43	55.15 ± 0.30	57.49 ± 0.23	57.22	59.15
EVA-02-base [20]	61.41±0.20	62.28 ± 0.22	55.25 ± 0.21	$58.80 {\pm} 0.24$	55.36 ± 0.14	58.14 ± 0.15	57.34	59.74
CLIP-base [21]	61.74±0.18	62.56 ± 0.20	57.16 ± 0.14	60.69 ± 0.24	57.43 ± 0.16	61.25 ± 0.19	58.78	61.50
VideoMAE-base (VoxCeleb2) [22]	63.33±0.13	$63.84 {\pm} 0.14$	57.98 ± 0.20	61.56 ± 0.23	57.18 ± 0.28	60.06 ± 0.19	59.50	61.82
VideoMAE-base (MER2023) [2]	64.50 ± 0.17	$64.93 {\pm} 0.19$	58.34 ± 0.32	$62.10 {\pm} 0.35$	57.32 ± 0.20	61.07 ± 0.31	60.05	62.70
CLIP-large [21]	66.66±0.12	$67.17{\pm}0.12$	63.27±0.29	$65.45{\pm}0.30$	60.04±0.19	$62.78{\pm}0.13$	63.32	65.13
		Ac	oustic Modali	ty				
eGeMAPS [23]	39.68±0.53	42.88 ± 0.38	30.27 ± 0.58	33.85 ± 0.79	28.92 ± 0.39	32.05 ± 0.43	32.96	36.26
VGGish [24]	48.60 ± 0.10	50.20 ± 0.09	45.44 ± 0.37	48.52 ± 0.23	40.70 ± 0.31	43.69 ± 0.23	44.91	47.47
Whisper-base [25]	56.65 ± 0.13	57.08 ± 0.24	59.70 ± 0.16	$60.60 {\pm} 0.12$	41.26 ± 0.41	42.52 ± 0.23	52.54	53.40
emotion2vec [26]	56.08 ± 0.09	56.48 ± 0.03	58.98 ± 0.33	59.68 ± 0.26	45.66 ± 0.31	46.97 ± 0.31	53.57	54.38
Whisper-large [25]	63.23±0.20	63.27 ± 0.20	69.24 ± 0.87	70.62 ± 0.62	53.26 ± 0.86	55.34 ± 0.57	61.91	63.08
wav2vec 2.0-base [27]	64.89±0.26	$65.14 {\pm} 0.30$	68.12 ± 0.34	69.29 ± 0.25	53.91 ± 0.14	56.87 ± 0.29	62.31	63.76
wav2vec 2.0-large [27]	65.50 ± 0.29	65.83 ± 0.27	68.12 ± 0.30	70.06 ± 0.22	56.41 ± 0.73	59.12 ± 0.63	63.35	65.00
HUBERT-base [28]	69.26±0.13	$69.43 {\pm} 0.15$	78.70 ± 0.20	$79.28 {\pm} 0.20$	59.55 ± 0.70	59.76 ± 0.82	69.17	69.49
HUBERT-large [28]	$73.02{\pm}0.13$	$73.10{\pm}0.15$	$83.42{\pm}0.37$	$84.00{\pm}0.32$	73.21±0.36	$74.03{\pm}0.31$	76.55	77.05
Lexical Modality								
XLNet-base [29]	48.59 ± 0.30	48.95 ± 0.29	49.13 ± 0.07	$48.64 {\pm} 0.04$	46.14 ± 0.16	$46.44 {\pm} 0.10$	47.96	48.01
ELECTRA-large [30]	50.45 ± 0.15	$50.83 {\pm} 0.09$	52.07 ± 0.16	$51.81 {\pm} 0.12$	47.34 ± 0.18	47.14 ± 0.12	49.95	49.93
MOSS-7B	51.25 ± 0.23	51.64 ± 0.19	51.62 ± 0.22	$51.64 {\pm} 0.14$	47.87 ± 0.19	48.42 ± 0.29	50.25	50.57
PERT-large [31]	50.36 ± 0.23	$50.69 {\pm} 0.10$	53.47 ± 0.17	53.26 ± 0.13	48.76 ± 0.23	48.83 ± 0.22	50.86	50.93
PERT-base [31]	50.26 ± 0.08	50.62 ± 0.12	53.64 ± 0.21	$53.50 {\pm} 0.18$	49.29 ± 0.18	$49.44 {\pm} 0.18$	51.06	51.19
LERT-large [32]	52.22 ± 0.18	52.38 ± 0.19	52.40 ± 0.20	52.18 ± 0.28	49.17 ± 0.44	$49.14 {\pm} 0.49$	51.26	51.24
ELECTRA-base [30]	50.98 ± 0.07	$51.30 {\pm} 0.07$	54.50 ± 0.33	54.35 ± 0.30	49.35 ± 0.15	49.32 ± 0.16	51.61	51.65
LERT-base [32]	52.37 ± 0.13	52.72 ± 0.10	54.84 ± 0.21	54.62 ± 0.20	47.98 ± 0.07	48.15 ± 0.15	51.73	51.83
RoBERTa-base [33]	51.84 ± 0.22	52.24 ± 0.18	54.37 ± 0.24	53.99 ± 0.34	49.49 ± 0.51	49.56 ± 0.41	51.90	51.93
MacBERT-base [34]	51.40 ± 0.13	51.75 ± 0.13	55.11 ± 0.29	54.74 ± 0.37	49.68 ± 0.24	49.74 ± 0.25	52.06	52.08
RoBERTa-large [33]	52.66 ± 0.18	52.92 ± 0.13	55.14 ± 0.31	$54.88 {\pm} 0.31$	49.06 ± 0.21	49.23 ± 0.28	52.29	52.34
ChatGLM2-6B [35]	53.04±0.23	53.28 ± 0.22	55.52 ± 0.56	55.06 ± 0.63	50.39 ± 0.43	$50.40 {\pm} 0.40$	52.98	52.91
MacBERT-large [34]	52.19 ± 0.14	52.47 ± 0.12	56.99±0.20	$56.81{\pm}0.31$	50.24 ± 0.20	50.34 ± 0.23	53.14	53.21
BLOOM-7B [36]	53.13±0.24	$53.30 {\pm} 0.24$	56.01 ± 0.36	$55.99 {\pm} 0.40$	50.38 ± 0.21	$50.58 {\pm} 0.13$	53.18	53.29
Baichuan-13B [37]	54.86±0.12	55.11±0.06	56.63 ± 0.18	56.17 ± 0.34	52.01±0.30	$51.90{\pm}0.21$	54.50	54.39

$$\operatorname{Recall}_{s} = \frac{|Y \cap \hat{Y}|}{|Y|}.$$
(7)

labels with the predictions submitted by participants. Finally, we manually check all labels to obtain the final ground truth.

For MER-OV, we choose the average between Accuracy $_s$ and Recall $_s$ as the final ranking:

$$Avg = \frac{Accuracy_s + Recall_s}{2}.$$
 (8)

To obtain more accurate open-vocabulary labels, we first extract labels using the approach in Section 2.3. Then, we merge these

4 RESULTS AND DISCUSSION

In this section, we report baseline results for three tracks. For MER-SEMI and MER-NOISE, we report both unimodal and multimodal results. For MER-OV, we report the results of various MLLMs.

Table 4: Multimodal results (%). We report both bimodal and trimodal results. Here, "A", "V", "T" represent acoustic, visual, and textual modalities, respectively. "TopN" means that we select the top-N features for each modality. Their ranking is based on the average WAF in Table 3.

# Ton	Train&Val		MER-	SEMI	MER-	NOISE	Average	
# Top	$\begin{array}{c c} WAF(\uparrow) & ACC(\uparrow) & WAF \end{array}$		WAF (\uparrow)	ACC (↑)	WAF (\uparrow)	ACC (↑)	WAF (\uparrow)	ACC (\uparrow)
				A+V				
Top1	78.86 ± 0.17	78.98 ± 0.13	84.07 ± 0.17	84.60 ± 0.16	78.14±0.31	$79.43 {\pm} 0.22$	80.36	81.00
Top2	78.92 ± 0.04	$78.97 {\pm} 0.11$	84.20 ± 0.15	84.73 ± 0.13	77.33 ± 0.14	78.55 ± 0.18	80.15	80.75
Top3	79.16 ± 0.11	$79.18 {\pm} 0.16$	84.09 ± 0.15	84.67 ± 0.15	77.26 ± 0.38	78.70 ± 0.33	80.17	80.85
Top4	79.11 ± 0.08	79.23 ± 0.09	84.12 ± 0.11	84.72 ± 0.11	77.16 ± 0.15	78.55 ± 0.15	80.13	80.83
Top5	79.17±0.07	79.25 ± 0.10	84.38±0.23	$84.92{\pm}0.22$	77.05 ± 0.17	78.46 ± 0.32	80.20	80.88
Top6	79.12 ± 0.09	$79.25{\pm}0.12$	84.14 ± 0.20	84.72 ± 0.19	77.54 ± 0.34	78.78 ± 0.22	80.27	80.91
				A+T				
Top1	73.67 ± 0.13	73.82 ± 0.09	84.06 ± 0.35	84.57 ± 0.32	$74.74{\pm}0.26$	75.61±0.23	77.49	7 8.00
Top2	73.75 ± 0.19	$73.84 {\pm} 0.17$	84.50 ± 0.36	85.01 ± 0.35	73.38 ± 0.46	74.25 ± 0.59	77.21	77.70
Top3	73.97±0.11	$73.97{\pm}0.05$	84.64±0.16	$\textbf{85.10{\pm}0.17}$	73.67 ± 0.39	74.32 ± 0.39	77.42	77.80
Top4	73.82 ± 0.22	73.87 ± 0.22	84.37 ± 0.57	84.85 ± 0.54	73.90 ± 0.30	74.36 ± 0.29	77.36	77.69
Top5	73.73±0.19	$73.80 {\pm} 0.18$	84.08 ± 0.30	84.64 ± 0.27	73.53 ± 0.14	74.20 ± 0.15	77.11	77.55
Top6	73.68 ± 0.12	$73.70 {\pm} 0.11$	84.31 ± 0.36	84.80 ± 0.31	73.99 ± 0.49	74.62 ± 0.40	77.32	77.71
V+T								
Top1	72.28 ± 0.16	72.47 ± 0.11	77.34 ± 0.30	77.74 ± 0.28	71.98 ± 0.42	73.38 ± 0.31	73.87	74.53
Top2	73.88 ± 0.08	$74.03 {\pm} 0.07$	77.17 ± 0.43	77.89 ± 0.39	71.99 ± 0.21	73.72 ± 0.11	74.34	75.21
Top3	74.29 ± 0.09	$74.35 {\pm} 0.10$	77.98 ± 0.37	78.60 ± 0.39	72.61 ± 0.34	74.26 ± 0.35	74.96	75.74
Top4	74.06 ± 0.12	74.22 ± 0.09	78.31±0.34	$79.08{\pm}0.33$	72.51 ± 0.18	74.26 ± 0.13	74.96	75.85
Top5	74.04 ± 0.10	$74.20 {\pm} 0.10$	77.78 ± 0.23	78.50 ± 0.25	$73.12{\pm}0.41$	$74.81{\pm}0.33$	74.98	75.84
Top6	$74.33{\pm}0.17$	$74.48{\pm}0.21$	77.83 ± 0.26	78.53 ± 0.26	73.03 ± 0.36	74.70 ± 0.27	7 5.0 7	7 5.90
A+V+T								
Top1	79.31 ± 0.03	$79.40 {\pm} 0.04$	86.73±0.13	87.09±0.16	79.47 ± 0.29	80.67 ± 0.19	81.84	82.39
Top2	80.05 ± 0.06	80.07 ± 0.09	85.94 ± 0.25	86.44 ± 0.24	79.11±0.33	80.33 ± 0.29	81.70	82.28
Top3	80.28 ± 0.16	80.33 ± 0.12	86.27±0.22	86.74 ± 0.18	78.75 ± 0.20	80.17 ± 0.19	81.77	82.41
Top4	80.02 ± 0.11	$80.10 {\pm} 0.11$	86.19 ± 0.14	86.67 ± 0.16	79.62±0.27	$80.82{\pm}0.28$	81.94	82.53
Top5	80.17 ± 0.13	80.21 ± 0.12	85.93 ± 0.15	86.45 ± 0.17	78.91 ± 0.28	80.36 ± 0.22	81.67	82.34
Top6	80.34±0.10	80.43±0.12	86.32 ± 0.22	86.86 ± 0.19	79.24 ± 0.40	80.33 ± 0.28	81.97	82.54

4.1 MER-SEMI and MER-NOISE

Table 3 presents the unimodal results. From this table, we observe that the model that performs well on Train&Val generally performs well on MER-SEMI and MER-NOISE. These results indicate that the model trained on our dataset has a good generalization ability. Among all modalities, the acoustic encoder can achieve the best unimodal result, suggesting that the samples in MER2024 mainly rely on the acoustic modality to express emotions.

For the visual modality, unsupervised or semi-supervised models generally perform better than supervised models (e.g., CLIP-large performs better than SENet-FER2013). This phenomenon shows that unsupervised or semi-supervised models can capture universal representations, which are beneficial for downstream tasks. Meanwhile, previous works point out that domain compatibility is important for the visual encoder [1]. Therefore, we further train VideoMAE-based on in-domain corpora (such as VoxCeleb2 and MER2023). We observe that this process leads to significant performance improvements compared to the raw VideoMAE-based. Therefore, we recommend that participants try to train other visual encoders on in-domain corpora. For acoustic and lexical modalities, based on the recommendations of MERBench [1], we mainly select the models trained on the Chinese corpus. From Table 3, we observe that unsupervised or semi-supervised acoustic encoders (e.g., HUBERT-large) generally perform better than traditional acoustic encoders (e.g., eGeMAPS), which is consistent with findings in the visual modality. Furthermore, LLMs often perform better than pretrained language models (PLMs). These results show that by increasing training data and model size, we can build more powerful lexical encoders and achieve better performance on emotion recognition.

Table 4 reports multimodal results. In this table, we choose "TopN" features and use the attention mechanism for multimodal fusion. "TopN" means that we select the top-N features for each modality, and their ranking is based on the average WAF in Table 3. Experimental results show that different modality combinations prefer distinct N. Therefore, we should adjust this parameter carefully. Meanwhile, we can achieve the best result when considering trimodal information, reflecting the effectiveness of multimodal fusion. In terms of WAF scores, our baseline system can reach 86.73% in MER-SEMI and 79.62% in MER-NOISE.

Table 5: Performance of different methods on MER-OV (%). These results are drawn from our previous work [10]. The values in the gray column are used for the final ranking. Here, "L", "V", and "A" indicate whether lexical, visual, and acoustic information is used in the emotion recognition process.

Model	L	V	А	Avg	Accuracy _s	Recalls
Empty	×	Х	Х	0.0	0.0	0.0
Random	×	Х	Х	19.0	24.1	13.8
Valley [39]		\checkmark	Х	11.1	12.7	9.6
Otter [40]		\checkmark	Х	24.5	27.6	21.4
PandaGPT [13]		\checkmark	\checkmark	25.3	26.5	24.2
Video-LLaMA [41]		\checkmark	Х	28.4	27.3	29.4
VideoChat2 [42]		\checkmark	Х	32.9	36.8	28.9
Video-ChatGPT [43]		\checkmark	Х	35.3	39.0	31.7
VideoChat [11]		\checkmark	Х	35.9	34.3	37.5
SALMONN [12]		Х	\checkmark	36.0	34.3	37.8
mPLUG-Owl [44]		\checkmark	Х	39.8	38.8	40.7
Qwen-Audio [45]		×	\checkmark	46.0	54.0	38.0
GPT-4V [46]	\checkmark	\checkmark	×	56.0	53.2	58.9

4.2 MER-OV

In this section, we report the performance of different methods on this track. Besides MLLMs, we introduce two heuristic baselines: *Empty* and *Random*. For the former, we do not assign any label. For the latter, we randomly select a label from six candidate categories (i.e., *worried, happy, neutral, angry, surprised,* and *sad*). Considering that the emotion labels extracted in Section 2.3 are relatively accurate, we use them as the ground truth. Table 5 shows the performance of different methods. Experimental results demonstrate that MLLMs generally outperform heuristic baselines, showcasing that MLLMs can handle this task to some extent. However, these models still cannot address this task perfectly. Meanwhile, audio LLMs generally perform better than video LLMs. The reason is that the samples in our dataset mainly convey emotions through the acoustic modality, which is consistent with the findings in Table 3.

5 CONCLUSIONS

This paper introduces a multimodal emotion recognition challenge, MER2024, which consists of three tracks: MER-SEMI, MER-NOISE, and MER-OV. This challenge is an extended version of MER2023 with more labeled and unlabeled samples. Meanwhile, it introduces a new task called open-vocabulary emotion recognition, which aims to generate any number of labels in any category to describe the emotional state as accurately as possible. In this paper, we introduce the datasets, establish the baselines, define the evaluation metrics, and report the baseline results for three tracks. Meanwhile, we open-source the code to ensure reproducibility. We hope that the MER series of challenges can provide researchers with a platform to evaluate their emotion recognition systems and prompt the application of this technology in real-life scenarios.

6 ACKNOWLEDGEMENTS

We would like to thank the members of data chairs Bin Liu (Institute of Automation, CAS), Rui Liu (Inner Mongolia University), and Kele Xu (National University of Defense Technology). Meanwhile, we appreciate the program committee for their valuable support: Xiaobai Li (Zhejiang University), Zixing Zhang (Hunan University), Jianfei Yu (Nanjing University) of Science and Technology), Ya Li (Beijing University of Posts and Telecommunications), Mengyue Wu (Shanghai Jiao Tong University), Jing Han (University of Cambridge), Jinming Zhao (Renmin University of China), Mingyue Niu (Yanshan University), Yongwei Li (Institute of Automation, CAS), and Licai Sun (University of Chinese Academy of Sciences). This work is supported by the National Natural Science Foundation of China (No. 62201572, No. 62276259, No. U21B2010, No. 62271083, No. 62306316, No. 62322120).

REFERENCES

- Zheng Lian, Licai Sun, Yong Ren, Hao Gu, Haiyang Sun, Lan Chen, Bin Liu, and Jianhua Tao. Merbench: A unified evaluation benchmark for multimodal emotion recognition. arXiv preprint arXiv:2401.03429, 2024.
- [2] Zheng Lian, Haiyang Sun, Licai Sun, Kang Chen, Mngyu Xu, Kexin Wang, Ke Xu, Yu He, Ying Li, Jinming Zhao, et al. Mer 2023: Multi-label learning, modality robustness, and semi-supervised learning. In Proceedings of the 31st ACM International Conference on Multimedia, pages 9610–9614, 2023.
- [3] Soujanya Poria, Devamanyu Hazarika, Navonil Majumder, Gautam Naik, Erik Cambria, and Rada Mihalcea. Meld: A multimodal multi-party dataset for emotion recognition in conversations. In *Proceedings of the 57th Conference of the Association for Computational Linguistics*, pages 527–536, 2019.
- [4] Shan Li, Weihong Deng, and JunPing Du. Reliable crowdsourcing and deep locality-preserving learning for expression recognition in the wild. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 2852–2861, 2017.
- [5] Jinming Zhao, Ruichen Li, and Qin Jin. Missing modality imagination network for emotion recognition with uncertain missing modalities. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 2608–2618, 2021.
- [6] Devamanyu Hazarika, Yingting Li, Bo Cheng, Shuai Zhao, Roger Zimmermann, and Soujanya Poria. Analyzing modality robustness in multimodal sentiment analysis. In Proceedings of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 685–696, 2022.
- [7] Licai Sun, Zheng Lian, Bin Liu, and Jianhua Tao. Efficient multimodal transformer with dual-level feature restoration for robust multimodal sentiment analysis. *IEEE Transactions on Affective Computing*, 2023.
- [8] Zheng Lian, Lan Chen, Licai Sun, Bin Liu, and Jianhua Tao. Gcnet: Graph completion network for incomplete multimodal learning in conversation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(07):8419–8432, 2023.
- [9] David Snyder, Guoguo Chen, and Daniel Povey. Musan: A music, speech, and noise corpus. arXiv preprint arXiv:1510.08484, 2015.
- [10] Zheng Lian, Licai Sun, Mingyu Xu, Haiyang Sun, Ke Xu, Zhuofan Wen, Shun Chen, Bin Liu, and Jianhua Tao. Explainable multimodal emotion reasoning. arXiv preprint arXiv:2306.15401, 2023.
- [11] KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. arXiv preprint arXiv:2305.06355, 2023.
- [12] Changli Tang, Wenyi Yu, Guangzhi Sun, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, MA Zejun, and Chao Zhang. Salmonn: Towards generic hearing abilities for large language models. In *The Twelfth International Conference on Learning Representations*, 2023.
- [13] Yixuan Su, Tian Lan, Huayang Li, Jialu Xu, Yan Wang, and Deng Cai. Pandagpt: One model to instruction-follow them all. In Proceedings of the 1st Workshop on Taming Large Language Models: Controllability in the era of Interactive Assistants, pages 11–23, 2023.
- [14] Zhan Tong, Yibing Song, Jue Wang, and Limin Wang. Videomae: Masked autoencoders are data-efficient learners for self-supervised video pre-training. In Proceedings of the Advances in Neural Information Processing Systems, pages 10078–10093, 2022.
- [15] Samira Ebrahimi Kahou, Xavier Bouthillier, Pascal Lamblin, Caglar Gulcehre, Vincent Michalski, Kishore Konda, Sébastien Jean, Pierre Froumenty, Yann Dauphin, Nicolas Boulanger-Lewandowski, et al. Emonets: Multimodal deep learning approaches for emotion recognition in video. *Journal on Multimodal User Interfaces*, 10:99–111, 2016.
- [16] Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. Dinov2: Learning robust visual features without supervision. arXiv

MM '24, October 28-November 1, 2024, Melbourne, Australia

Lian et al.

preprint arXiv:2304.07193, 2023.

- [17] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 7132–7141, 2018.
- [18] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 770–778, 2016.
- [19] Zengqun Zhao, Qingshan Liu, and Shanmin Wang. Learning deep global multiscale and local attention features for facial expression recognition in the wild. *IEEE Transactions on Image Processing*, 30:6544–6556, 2021.
- [20] Yuxin Fang, Quan Sun, Xinggang Wang, Tiejun Huang, Xinlong Wang, and Yue Cao. Eva-02: A visual representation for neon genesis. arXiv preprint arXiv:2303.11331, 2023.
- [21] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In Proceedings of the International Conference on Machine Learning, pages 8748–8763. PMLR, 2021.
- [22] Joon Son Chung, Arsha Nagrani, and Andrew Zisserman. Voxceleb2: Deep speaker recognition. In Proceedings of the Interspeech, pages 1086–1090, 2018.
- [23] Florian Eyben, Klaus R Scherer, Björn W Schuller, Johan Sundberg, Elisabeth André, Carlos Busso, Laurence Y Devillers, Julien Epps, Petri Laukka, Shrikanth S Narayanan, et al. The geneva minimalistic acoustic parameter set (gemaps) for voice research and affective computing. *IEEE Transactions on Affective Computing*, 7(2):190–202, 2016.
- [24] Shawn Hershey, Sourish Chaudhuri, Daniel PW Ellis, Jort F Gemmeke, Aren Jansen, R Channing Moore, Manoj Plakal, Devin Platt, Rif A Saurous, Bryan Seybold, et al. Cnn architectures for large-scale audio classification. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 131–135. IEEE, 2017.
- [25] Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. In Proceedings of the International Conference on Machine Learning, pages 28492– 28518. PMLR, 2023.
- [26] Ziyang Ma, Zhisheng Zheng, Jiaxin Ye, Jinchao Li, Zhifu Gao, Shiliang Zhang, and Xie Chen. emotion2vec: Self-supervised pre-training for speech emotion representation. arXiv preprint arXiv:2312.15185, 2023.
- [27] Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. wav2vec 2.0: A framework for self-supervised learning of speech representations. In Proceedings of the Advances in Neural Information Processing Systems, pages 12449–12460, 2020.
- [28] Wei-Ning Hsu, Benjamin Bolte, Yao-Hung Hubert Tsai, Kushal Lakhotia, Ruslan Salakhutdinov, and Abdelrahman Mohamed. Hubert: Self-supervised speech representation learning by masked prediction of hidden units. *IEEE/ACM Trans*actions on Audio, Speech, and Language Processing, 29:3451–3460, 2021.
- [29] Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *Proceedings of the Advances in Neural Information Processing* Systems, pages 5754–5764, 2019.
- [30] Kevin Clark, Minh-Thang Luong, Quoc V Le, and Christopher D Manning. Electra: Pre-training text encoders as discriminators rather than generators. In Proceedings of the International Conference on Learning Representations, pages 1–18, 2020.
- [31] Yiming Cui, Ziqing Yang, and Ting Liu. Pert: pre-training bert with permuted language model. arXiv preprint arXiv:2203.06906, 2022.
- [32] Yiming Cui, Wanxiang Che, Shijin Wang, and Ting Liu. Lert: A linguisticallymotivated pre-trained language model. arXiv preprint arXiv:2211.05344, 2022.
- [33] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692, 2019.
- [34] Yiming Cui, Wanxiang Che, Ting Liu, Bing Qin, Shijin Wang, and Guoping Hu. Revisiting pre-trained models for chinese natural language processing. In Findings of the Association for Computational Linguistics: EMNLP 2020, pages 657–668, 2020.
- [35] Zhengxiao Du, Yujie Qian, Xiao Liu, Ming Ding, Jiezhong Qiu, Zhilin Yang, and Jie Tang. Glm: General language model pretraining with autoregressive blank infilling. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 320–335, 2022.
- [36] BigScience Workshop, Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, et al. Bloom: A 176b-parameter open-access multilingual language model. arXiv preprint arXiv:2211.05100, 2022.
- [37] Aiyuan Yang, Bin Xiao, Bingning Wang, Borong Zhang, Ce Bian, Chao Yin, Chenxu Lv, Da Pan, Dian Wang, Dong Yan, et al. Baichuan 2: Open large-scale language models. arXiv preprint arXiv:2309.10305, 2023.
- [38] Zheng Lian, Bin Liu, and Jianhua Tao. Ctnet: Conversational transformer network for emotion recognition. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 29:985–1000, 2021.

- [39] Ruipu Luo, Ziwang Zhao, Min Yang, Junwei Dong, Minghui Qiu, Pengcheng Lu, Tao Wang, and Zhongyu Wei. Valley: Video assistant with large language model enhanced ability. arXiv preprint arXiv:2306.07207, 2023.
- [40] Bo Li, Yuanhan Zhang, Liangyu Chen, Jinghao Wang, Jingkang Yang, and Ziwei Liu. Otter: A multi-modal model with in-context instruction tuning. arXiv preprint arXiv:2305.03726, 2023.
- [41] Hang Zhang, Xin Li, and Lidong Bing. Video-llama: An instruction-tuned audiovisual language model for video understanding. arXiv preprint arXiv:2306.02858, 2023.
- [42] Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, Limin Wang, and Yu Qiao. Mvbench: A comprehensive multi-modal video understanding benchmark. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2024.
- [43] Muhammad Maaz, Hanoona Rasheed, Salman Khan, and Fahad Shahbaz Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models. arXiv preprint arXiv:2306.05424, 2023.
- [44] Qinghao Ye, Haiyang Xu, Guohai Xu, Jiabo Ye, Ming Yan, Yiyang Zhou, Junyang Wang, Anwen Hu, Pengcheng Shi, Yaya Shi, Chaoya Jiang, Chenliang Li, Yuanhong Xu, Hehong Chen, Junfeng Tian, Qian Qi, Ji Zhang, and Fei Huang. mplug-owl: Modularization empowers large language models with multimodality, 2023.
- [45] Yunfei Chu, Jin Xu, Xiaohuan Zhou, Qian Yang, Shiliang Zhang, Zhijie Yan, Chang Zhou, and Jingren Zhou. Qwen-audio: Advancing universal audio understanding via unified large-scale audio-language models. arXiv preprint arXiv:2311.07919, 2023.
- [46] OpenAI. Gpt-4v(ision) system card, 2023.

A MODEL CARDS

MERBench [1] provides some guidelines for feature selection. For the lexical and acoustic modalities, language matching is important. Therefore, we mainly choose encoders trained in Chinese corpora. For the visual modality, domain matching is important. Therefore, we provide two visual encoders trained on human-centric videos (i.e., MER2023-SEMI and VoxCeleb2). Table 6 provides model cards for some feature extractors. MER 2024: Semi-Supervised Learning, Noise Robustness, and Open-Vocabulary Multimodal Emotion Recognition MM '24, October 28-November 1, 2024, Melbourne, Australia

Table 6: Model cards for some feature extractors. Here, "CH", "EN", and "MULTI" are the abbreviations of Chinese, English, and multilingualism, respectively.

Feature	Training Data (Language)	Link				
Visual Modality						
VideoMAE-base	Kinetics-400	huggingface.co/MCG-NJU/videomae-base				
VideoMAE-large	Kinetics-400	huggingface.co/MCG-NJU/videomae-large				
CLIP-base	WIT	huggingface.co/openai/clip-vit-base-patch32				
CLIP-large	WIT	huggingface.co/openai/clip-vit-large-patch14				
EVA-02-base	ImageNet-22k	huggingface.co/timm/eva02_base_patch14_224.mim_in22k				
DINOv2-large	LVD-142M	huggingface.co/facebook/dinov2-large				
VideoMAE-base (VoxCeleb2)	VoxCeleb2	github.com/zeroQiaoba/MERTools				
VideoMAE-base (MER2023)	MER2023	github.com/zeroQiaoba/MERTools				
	Acoustic M	odality				
emotion2vec	Mix (EN)	github.com/ddlBoJack/emotion2vec				
Whisper-base	Internet (MULTI, mainly EN)	huggingface.co/openai/whisper-base				
Whisper-large	Internet (MULTI, mainly EN)	huggingface.co/openai/whisper-large-v2				
wav2vec 2.0-base	WenetSpeech (CH)	huggingface.co/TencentGameMate/chinese-wav2vec2-base				
wav2vec 2.0-large	WenetSpeech (CH)	huggingface.co/TencentGameMate/chinese-wav2vec2-large				
HUBERT-base	WenetSpeech (CH)	huggingface.co/TencentGameMate/chinese-hubert-base				
HUBERT-large	WenetSpeech (CH)	huggingface.co/TencentGameMate/chinese-hubert-large				
Lexical Modality						
PERT-base	EXT Data (CH)	huggingface.co/hfl/chinese-pert-base				
PERT-large	EXT Data (CH)	huggingface.co/hfl/chinese-pert-large				
LERT-base	EXT Data (CH)	huggingface.co/hfl/chinese-lert-base				
LERT-large	EXT Data (CH)	huggingface.co/hfl/chinese-lert-large				
XLNet-base	EXT Data (CH)	huggingface.co/hfl/chinese-xlnet-base				
MacBERT-base	EXT Data (CH)	huggingface.co/hfl/chinese-macbert-base				
MacBERT-large	EXT Data (CH)	huggingface.co/hfl/chinese-macbert-large				
RoBERTa-base	EXT Data (CH)	huggingface.co/hfl/chinese-roberta-wwm-ext				
RoBERTa-large	EXT Data (CH)	huggingface.co/hfl/chinese-roberta-wwm-ext-large				
ELECTRA-base	EXT Data (CH)	huggingface.co/hfl/chinese-electra-180g-base-discriminator				
ELECTRA-large	EXT Data (CH)	huggingface.co/hfl/chinese-electra-180g-large-discriminator				
BLOOM-7B	ROOTS (MULTI)	huggingface.co/bigscience/bloom-7b1				
MOSS-7B	Mix (MULTI, mainly EN and CH)	huggingface.co/fnlp/moss-base-7b				
ChatGLM2-6B	Mix (MULTI, mainly EN and CH)	huggingface.co/THUDM/chatglm2-6b				
Baichuan-13B	Mix (MULTI, mainly EN and CH)	huggingface.co/baichuan-inc/Baichuan-13B-Base				