An RNN-policy gradient approach for quantum architecture search

Gang Wang ¹, Bang-Hai Wang ^{1*†}, Shao-Ming Fei ^{2,3†}

^{1*}School of Computer Science and Technology, Guangdong University of Technology, GuangZhou, 510006, GuangDong, China.

²School of Mathematical Sciences, Capital Normal University, Beijing, 100048, China.

³Max-Planck-Institute for Mathematics in the Sciences, 04103, Leipzig, Germany.

*Corresponding author(s). E-mail(s): bhwang@gdut.edu.cn; †These authors contributed equally to this work.

Abstract

Variational quantum circuits are one of the promising ways to exploit the advantages of quantum computing in the noisy intermediate-scale quantum technology era. The design of the quantum circuit architecture might greatly affect the performance capability of the quantum algorithms. The quantum architecture search is the process of automatically designing quantum circuit architecture, aiming at finding the optimal quantum circuit composition architecture by the algorithm for a given task, so that the algorithm can learn to design the circuit architecture. Compared to manual design, quantum architecture search algorithms are more effective in finding quantum circuits with better performance capabilities. In this paper, based on the deep reinforcement learning, we propose an approach for quantum circuit architecture search. The sampling of the circuit architecture is learnt through reinforcement learning based controller. Layer-based search is also used to accelerate the computational efficiency of the search algorithm. Applying to data classification tasks we show that the method can search for quantum circuit architectures with better accuracies. Moreover, the circuit has a smaller number of quantum gates and parameters.

Keywords: Quantum architecture search, Reinforcement learning , Quantum computing $% \mathcal{A}(\mathcal{A})$

1 Introduction

The development of quantum computing and quantum information theory has revolutionized the implementation of computing. Quantum computing can theoretically break the RSA algorithm in a few hours [1], which would take billions of years in a traditional computational environment. Meanwhile, machine learning has achieved great success in the last two decades, with major breakthroughs in applications such as image processing [2], language processing [3] and games [4]. Integrating quantum computing and machine learning has become a popular research topic. On the one hand, machine learning methods are used to solve quantum physics problems such as quantum many-body states [5], nonlocality detection [6], quantum error correction [7, 8] and quantum control [9]. On the other hand, quantum computing is expected to bring new developments to traditional machine learning, e.g., quantum support vector machines [10, 11], quantum reinforcement learning[12], etc.

One of the most promising ways to exploit the advantages of quantum computing on the noisy intermediate-scale quantum devices [13] is currently the hybrid quantum classical models which use classical computing methods to optimize the parameters of the parameterized quantum circuits, called variational quantum circuits [14]. This kind of hybrid quantum models includes quantum neural networks [15] and quantum eigen-solvers [16] etc.. In recent years, typical applications are given to quantum eigensolvers for ground state estimation of quantum systems [17], quantum approximate optimization algorithms for better approximation of NP-hard combination optimization problems [18] and solving machine learning tasks in classical settings by quantum machine learning [19]. Although good performances have been experimentally verified in tasks such as small-scale energy estimation [20] and data classification [21, 22], it is still a big problem to design the architecture of quantum circuits. As the number of quantum gates and the depth of the circuit increase, the noise of the circuit also increases. As a result, this leads to the barren plateau [23] and affects the performance of the variational circuit. Thus, efficient designs to discover the optimal representation for quantum circuit architectures with restricted scale are critical research challenges.

Similarly, the design of neural networks in deep learning depends significantly on the researchers' previous knowledge and experience, which may limit the design of neural network architectures. Therefore, neural architecture search (NAS) [24] has been proposed aimed to design neural network structures automatically with restricted computational resources and the least manual intervention, and to achieve optimal performance as good as possible. Typical approaches include reinforcement learning [25–27], evaluation algorithms [28] and differentiable search [29]. The problems and objectives faced by neural architecture search and quantum architecture search are rather similar. Inspired by neural architecture search, the related quantum circuit architecture search based on reinforcement learning [30], evaluation algorithm [31] and differentiable search [32, 33] have been proposed as well. In contrast, related algorithms based on reinforcement learning are currently mostly used for quantum control [9] and quantum compiling [34, 35]. Architecture search has not been directly applied for a given computational task.

In this paper, we propose a reinforcement learning based quantum circuit architecture search method for searching optimal ansatz in quantum circuits. We use a

recurrent neural network(RNN) to fit the policy function and optimize it with Monte Carlo policy gradient[36] as the strategy for architecture search. The computational efficiency of the search is also improved by using layer-based search. To verify the efficiency of the method, we use the MNIST dataset [37] for classification. It outperforms manual-based designs and employs fewer quantum gates and variable parameters.

2 PRELIMINARY

2.1 Neural architecture search

NAS is an emerging research area in AutoML aimed to automatically find the optimal performance neural network architecture for a given task. The use of reinforcement learning to search for neural network architecture in image classification beyond the previously manual design of neural networks in 2017 [25] is a significant event in the field of NAS. The original NAS approach requires a large amount of computational resources. A more efficient neural architecture search (ENAS) was subsequently proposed to address the problems for which previous NAS methods require large computational resources [26]. This method denotes the search space as a directed acyclic graph, where any subgraph represents a network architecture, replacing the global search space with a cell-based search space. At the same time, different network architectures share the parameters on the whole directed acvclic graph nodes, i.e., weight sharing. ENAS reduces significantly the expense and improves the computational efficiency compared to the previous NAS. The modular search space and weight sharing effectively reduce the expenses of neural architecture search. Later FPNAS [27] also considered the diversity of the cell stacking, and demonstrated that stacking different cells is effective in improving the performance of the neural architecture. In addition to reinforcement learning-based strategies, there are also search methods based on evaluation algorithms [28], Bayesian optimization [38], SMBO (Sequential Model-Based Global Optimization) [39] and Monte Carlo tree search [40]. These methods treat neural architecture search as a black-box optimization problem in discrete search strategies. By converting discrete spaces into continuous differentiable formats, the DARTS method was proposed in [41]. As with ENAS, the network space is represented as a directed acyclic graph. The node connections and activation functions are combined into a matrix, where each element represents the weight of the connection and activation function, and the Softmax function is used in the search to convert the search space into a continuous space and the objective function into a differentiable function. The DARTS search neural network architecture performs well under classical computational tasks and enhances computational efficiency compared to previous reinforcement learning approaches. Subsequently, many variants based on DARST were proposed[42, 43]. With the success of the attention mechanism and Transformer in the field of natural language processing, researchers use the attention mechanism in other application areas. A Transformer-based approach to encoding computational awareness architecture was used in [44], which results in neural network architectures with dense computational resource consumption in the hidden space. The results indicate that this encoding approach can enhance downscale tasks.

2.2 Quantum architecture search

Inspired by the research on neural architecture search, researchers have also proposed a series of algorithms for quantum circuit architecture search. For the quantum circuit in image classification, Hur et al. [22] considered the effect of different QCNN's circuit ansatz architecture on the classification performance, through different structures are still designed manually. Du et al. [32] used an approach of differentiable search for quantum circuit architecture with decent resources and runtime efficiency, in addition to excellent performance on classification tasks and hydrogen molecule ground state estimation tasks. Similarly, Zhang et al. [33] proposed the differentiable quantum architecture search (DQAS) that was experimentally demonstrated to be superior to the traditional QAOA circuit on the MaxCut problem. Ostaszewski et al. [30] proposed a reinforcement learning algorithm that can automatically explore the space of possible architectures and recognize economic loops that still generate accurate ground state energy estimation. The algorithm uses a feedback-driven learning approach that adapts the complexity of the learning problem to the current performance of the learning algorithm and progressively improves the accuracy of the results while reducing the circuit depth to a minimum at the same time. Lu et al. [31] proposed the use of neuroevolutionary algorithms for quantum circuit architecture search for different machine learning tasks, establishing a one-to-one mapping between quantum circuits and directed graphs, and reducing the problem of searching for proper gate sequences to the task of searching for proper paths in the corresponding graphs as a Markov process.

In addition to the applied circuit architecture search in problems of quantum machine learning, similar circuit search methods can be applied in quantum compilers as well to generate specific quantum gate sequences. Kuo et al. [45] used A2C (Advantage actor-critic) and PPO (Proximal policy optimization) algorithms for quantum architecture search to demonstrate the successful generation of quantum gate sequences with multi-GHZ states without encoding any knowledge of quantum physics in the agent. Zhang et al. [34] propose a deep reinforcement learning-based algorithm which is designed to compile an arbitrary single quantum bit gate from a finite common set into a sequence of fundamental gates, which is applied to the topological compilation of Fibonacci arbitrators to obtain an approximate optimal sequence of arbitrary single qubits of unitary. Subsequently, PPO is further used to compile arbitrary quantum channels [35]. The current research for the field of quantum artificial intelligence including quantum circuit architecture search is still far from being satisfied. How to design or optimize quantum algorithms to solve quantum computing problems is an important challenging problem. The extension of classical computing algorithms is also in the preliminary stage. Quantum architecture search using reinforcement learning is currently mostly evolved in quantum compilation. This paper aims to investigate a reinforcement learning quantum circuit architecture design based approach for a given task.

2.3 Variational quantum circuits

Variational quantum circuits (or parametric quantum circuits) are based on hybrid quantum and classical computational methods. A set of quantum gates with parameters θ_i are carried out on a quantum computer, while the θ_i is optimized on a classical computer, as shown in Fig. 1. Where the parameters θ_i are different for each quantum gate. Usually it includes three steps: encoding, variational and readout. To be processed on quantum devices, classical data need to be encoded into quantum states. The encoding layer encodes n dimensional data onto m qubits by such as direct encoding, angular encoding, amplitude encoding etc.. The direct encoding represents the classical data in binary form and directly maps them onto quantum computational bases. This method takes n qubits to load the binary representation of a classical data point $x = (x_1, x_2, ..., x_n)$ and encodes it as $|\Psi_x\rangle = \bigotimes_i^n |x_i\rangle$. The angular encoding loads the classical data as the radians of rotation gates acting on qubits. A classical data $x = (x_1, x_2, ..., x_n)$ is encoded as $|\Psi_x\rangle = \bigotimes_i^n \cos(x_i)|0\rangle + \sin(x_i)|1\rangle$. The encoding method used in this paper is the amplitude encoding, which embeds classical data into the amplitudes of a quantum state. An n-dimensional normalized classical vector x is encoded to the amplitudes of quantum state by $|\Psi_x\rangle = \sum_{i=1}^n x_i |i\rangle$, where $|i\rangle$ is the *i*-th computational basis state and $\sum |x_i|^2 = 1$

The step variational layer operates on qubits by rotating parametric quantum gates denoted by $U(\theta) = \prod_{l=1}^{L} U_l(\theta)$, where $U_l(\theta)$ consists of a sequence of parameterized quantum gates including single-qubit and two-qubit quantum gates, $\theta = \{\theta_1, \theta_2, ..., \theta_n\}$ denotes the parameters of all quantum gates in this layer. The performance of the circuit can be improved by increasing the number of variational layers and quantum gates.

After the variational operation of the L layer, the quantum data are read out by measurement. The measurement output is $\langle \Psi_x | U(\theta) M U^{\dagger}(\theta) | \Psi_x \rangle$, where $| \Psi_x \rangle$ is the input quantum state and M are measurement operators on read out qubits. Then, the classical computer calculates the loss function J to optimize the circuit parameter θ . In this way, the circuit can fit arbitrary functions like traditional neural networks[46]. Hence, QVC is also called quantum neural network and is widely used in quantum machine learning. A series of derivative structures such as QCNN [47] and QRNN [48] have been proposed.



Fig. 1 The general form of variational quantum circuits

2.4 Reinforcement learning

Reinforcement learning emphasizes that the intelligence learns by interacting with the environment and does not require imitable supervised signals or complete modeling of the environment. During the continuous interaction between the agent and the environment, the agent selects an action, while the environment responds to this action and moves to a new state. At the same time, the environment generates a reward. During the interaction the agent needs to maximize the cumulative rewards obtained. Reinforcement learning can be modeled as a partially observable Markov decision process defined as a tuple (S, A, T, R, Ω, O) , where S is the state set, A is the action set, T is the transfer function that maps the state-action to the probability distribution of the next state, $R: S \times A \to R$ is the reward function, O is the observation set and Ω is the probability distribution function that maps observations to states. The agent obtains observations o as partial information about the environment state s. After the agent selects an action, the environment transfers to the next state s_1 according to T, while giving back new observations o and reward r to the agent. The agent's goal is to obtain the maximum cumulative expected reward during the interaction, defined as $G = \sum_{t=0}^{T} \gamma^t R_t$, where γ is the discount factor. In this paper, we model quantum architecture search as a process of reinforcement learning, as shown in Fig. 2. The state is the current circuit architecture. The action is the next layer that will be added to the circuit. The reward is the performance of the current circuit.



Fig. 2 Workflow

3 Method

The method consists of two parts training process. According to a given task and the existing circuit architecture, a controller samples the quantum circuit architecture of each layer based on reinforcement learning and recurrent neural network(RNN). The training controller is aimed to find the required gates for the quantum circuit for the given task. The next is the process of training circuit. The circuit is composed based on the architecture of the single layer sampled from the controller for the given task. The training objective is to optimize the parameters of the circuit. At the end of one epoch of training for the circuit, the accuracy performance of the circuit on the validation set is feedback to the controller as a reward signal for parameter optimization of the controller network. The training of the circuit and the training of the controller constitute a complete epoch of training. We show the details below.

3.1 Training process

The training process shown in Fig. 2 consists of two parts. At the beginning of an epoch, the quantum circuit is initialized to empty. The controller selects a quantum gate sequence of a layer to join the circuit based on the initial state of the circuit. The quantum circuit adds that sequence to the existing architecture to construct the quantum circuit. Subsequently, Adam is used to optimize the parameters of the circuit.



The mean squared error loss is chosen as the loss function J for the training circuit,

$$J = \frac{1}{N} \sum_{i=1}^{N} \left(y_i - y_{\text{prediction}} \right)^2.$$
(1)

Where y_i is the target label of input, $y_{prediction}$ is the circuit prediction. The training algorithm is shown in Algorithm 1.

Algorithm 1 Train Circuit

while $epoch < max \ epoch$ do Sample a random batch B from train set Input circuit to get prediction $y_{prediction}$ Compute loss by MSE: $J = \frac{1}{N} \sum_{i=1}^{N} (y_i - y_{prediction})^2$ Upgrade parameters: $m_t = \beta_1 m_{t-1} + (1 - \beta_1) \nabla_{\theta} J$ $n_t = \beta_2 n_{t-1} + (1 - \beta_2) \nabla_{\theta} J$ $\hat{m}_t = \frac{m_t}{1 - \beta_1^t}$ $\hat{n}_t = \frac{n_t}{1 - \beta_2^t}$ $\theta_t = \theta_{t-1} - \frac{\alpha}{\sqrt{\hat{n}_t + \varepsilon}} \hat{m}_t$ end

After the training of the quantum circuit is finished, we compute the accuracy on the validation set as a reward in order to have better generality of our controller. The controller parameters are then optimized, with the training of the controller given in the next section. Finally, the performance of the circuit representation is verified on the test set. The complete training procedure of our method is shown in Algorithm 2.

Algorithm 2 Train procedure initialized arch to empty

for $epoch <$	$max \ epoch \ \mathbf{do}$
for <i>layer</i>	$< max \ layer \ do$
Sample	e a layer L architecture by the controller
Add L	to arch
Genera	ate circuit by arch
Train	circuit
Calcul	ate reward by circuit train loss
Upgra	de the controller parameters
end	
end	



Fig. 3 Training process

The controller uses a policy gradient approach to optimize the parameters. To find the optimal architecture, the accuracy performance of the circuit on the validation set is feedback to the controller as a reward. The goal of controller learning is to maximize the total expected reward, i.e:

$$\max J(\theta_c) = \max E_{P(a_t,\theta_c)}[R], \qquad (2)$$

where a_t denotes the circuit architecture at time t, θ_c is the circuit parameter, and R denotes the reward calculated based on the performance of the circuit on the validation set. For optimization, we use the Monte Carlo policy gradient [36]

$$\nabla_{\theta_c} J(\theta_c) = \sum_{t=1}^{T} E_{P(a_t,\theta_c)} \left[\nabla_{\theta_c} \log P(a_t \mid a_{t-1},\theta_c) R \right].$$
(3)

The complete training process is shown in the Fig. 4. At the beginning of an epoch, the controller samples a random batch from valid set of input circuits to compute the loss. Then reward is computed by loss and feeded back to the controller. At last, the controller upgrades the policy function. The complete algorithm for controller training is shown in Algorithm 3.

Algorithm 3 Train Controller

Sample a random batch *B* from valid set Input circuit to compute loss *L* calculate reward *r* by *L* calculate return: $R = \sum_{t=0}^{T} \gamma^{t} r_{t}$ $J(\theta_{c}) = E_{(a_{t},\theta_{c})}[R]$ calculate gradient: $\nabla_{\theta_{c}} J(\theta_{c}) = \sum_{t=1}^{T} E_{(a_{t},\theta_{c})} [\nabla_{\theta_{c}} \log P(a_{t} \mid a_{t-1}, \theta_{c}) R]$ Upgrade parameters: $m_{t} = \beta_{1} m_{t-1} + (1 - \beta_{1}) \nabla_{\theta} J$ $n_{t} = \beta_{2} n_{t-1} + (1 - \beta_{2}) \nabla_{\theta} J$ $\hat{m}_{t} = \frac{m_{t}}{1 - \beta_{1}^{t}}$ $\hat{n}_{t} = \frac{n_{t}}{1 - \beta_{1}^{t}}$ $\theta_{t} = \theta_{t-1} - \frac{\alpha}{\sqrt{\hat{n}_{t} + \varepsilon}} \hat{m}_{t}$

3.2 Controller

We use a reinforcement learning algorithm for policy gradients to design a controller for searching circuit architecture. First, the circuit architecture search process is modelled as a Markov decision process. The observation O_t acquired by the controller at moment t is the structure $arch_t$ of the quantum variational circuit at that moment in time. $arch_t$ consists of the quantum gates in a given set of quantum gates R. The quantum gates in the set of available quantum gates $R = \{R_x, R_y, R_z, CNOT\}$, where R_x, R_y, R_z are rotational gates and the CNOT is the controlled-NOT operator, denoted as.

$$R_x(\phi) = \begin{bmatrix} \cos(\phi/2) & -i\sin(\phi/2) \\ -i\sin(\phi/2) & \cos(\phi/2) \end{bmatrix},\tag{4}$$

$$R_y(\phi) = \begin{bmatrix} \cos(\phi/2) & -\sin(\phi/2) \\ \sin(\phi/2) & \cos(\phi/2) \end{bmatrix},$$
(5)

$$R_{z}(\phi) = \begin{bmatrix} e^{-i\phi/2} & 0\\ 0 & e^{i\phi/2} \end{bmatrix},$$
(6)

$$CNOT = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{bmatrix}.$$
 (7)

The controller chooses the action a_{t+1} , i.e., the next moment as a layer to join the quantum circuit of l quantum gates according to the policy π , denoted as $a_{t+1} = \pi(arch_t)$. For each quantum gate G in the circuit can be denoted by $\{B, E, T\}$, where B(E) is the first (second) qubit in a double quantum operation, and T denotes the type of the quantum gate $T \in R$. When B is equal to E, the quantum gate is a single quantum operation. There are 4q + q(q-1) quantum gates of different types in the circuit, where q is the number of qubits in the circuit. Essentially, 4q represents

the number of single-qubit gates, and q * (q - 1) refers to the number of CNOT gates utilized. Each quantum gate is numbered using a unique index in that space to facilitate input to the neural network for processing. Each time l quantum gates are added to the circuit, their parameters are optimized according to the given task. The controller network is optimized based on the circuit's accuracy performance on the validation set after parameter optimization as a reward signal.



Fig. 4 The controller's network architecture

The controller uses the LSTM[49] network to fit the policy function, which is structured as shown in Fig. 4. First to the input architecture sequence through the embedding layer to extract the embedded vector. Then a simple coding layer is input to extract a hidden layer feature with the following expression:

$$out_{hidden} = ReLU(linear(BN(Embed_{input})))$$
(8)

Where BN is the regularization, *linear* is the linear layer and ReLU is the activation function. The hidden layer features are fed into the lstm network to get the sequence output, and then the number of quantum gates can be used by transforming the vectors into action dimensions through the decoding layer which has the same structure as the coding layer. Finally, the probability of the policy network for each action is obtained using the softmax function, and the sequence of quantum gates to be added to the circuit is sampled according to this probability.

model	input size	encode	qubits num	gates num	parameters num	accuracy
manual QCNN[22] Neuroevolution[31] Our	$256 \\ 256 \\ 256$	amplitude amplitude amplitude	8 9 8	30 50 37	$45 \\ 106 \\ 11$	98.3% 97% 99.6%

Table 1 MNIST dataset classification accuracy

4 Experiments and result

We use the pytorch [50] and pennylane [51] for model development. We verify the performance of the model on the data classification task on the classical dataset MNIST, a handwritten image dataset, which is a typical entry-level machine learning task for testing various learning methods. The dataset consists of grayscale images of handwritten data from 0 to 9, with each image containing 28×28 pixels. We choose 0 and 1 for testing the binary classification task. The images are preprocessed and compressed to 16×16 . The size of the original dataset is 60,000 for the training set, 10,000 for the test set, and 12665 and 2115 for the subsets containing only 0 and 1. We divide the validation set on the original training set with size 2115. Then the final training, validation, and test set sizes are 10,550, 2115 and 2115, respectively. For the 16×16 pixel image, 8 quantum bits are needed to encode the input. We use amplitude encoding to encode the image data into qubits in the following form

$$|\psi_x\rangle = \sum_{i=1}^N x_i |i\rangle.$$
(9)

By amplitude encoding, the data is encoded into the amplitude of the quantum state. The data in 2^n dimensions can be encoded into n qubits. We set the maximum number of quantum gates per layer to be 8, and the maximum number of layers to be 5. The learning rate of both circuit and controller is 0.001. The epoch of the search algorithm is 50, and the epoch of the training circuit to optimize the parameter subprocess is 300. The size of the randomly sampled batch of the training data is 25. The discount factor of the controller reward is 0.8. A simple linear layer is used for the encoding and decoding layers of the controller network respectively. The RNN part uses an lstm with 100 hidden units. The Adam optimizer is used to optimize the quantum circuit and the controller. The final architecture obtained can reach 99.6% accuracy on the test set, and just use 37 quantum gates and 11 parameters in 8 qubits. This paper is compared with two other researches using quantum circuits for image classification, designing the circuit architecture by manual^[22] and searching the circuit architecture by evolutionary algorithms [31], and the comparison of the experimental results is shown in Table 1. In QCNN, 8 qubits with 30 quantum gates and 45 parameters are used. 9 qubits with 50 quantum gates and 106 parameters are used in Neuroevolution. In comparison, our proposed method searches the quantum circuit architecture using fewer qubits, while achieving good performance.

5 Conclusion and discussions

We have proposed a reinforcement learning based approach in dealing with the quantum circuit structure search problem. Different from the previous reinforcement learning methods applied to quantum compiling, our model applies to quantum circuit architecture search for a given computational task. The use of layer-based search and weight sharing improves the computational efficiency of the search for reinforcement learning. The binary classification experiments on MNIST dataset show that our model can search for quantum circuits with excellent classification performance. Moreover, it has fewer quantum gates and variational parameters than the manually designed circuits. In addition to classical image classification tasks, our model can also be applied to search for circuit architectures for other computational tasks in quantum data processing. An interesting problem is the balance between the performance capability of the searched circuit architecture and the circuit complexity, namely, to make the quantum architecture search adaptively to balance the model of reinforcement learning by reward design, so that the controller learns to design quantum circuits. This is also an important issue and a possible direction for future research.

Acknowledgments

Thanks to Dr. Situ Haozhen from South China Agricultural University and Dr. Huang YiMing from Beijing University for their comments on this work. This work is supported by the National Natural Science Foundation of China under Grant Nos. 62072119, National Natural Science Foundation of China under grant Nos. 12075159 and 12171044, and the specific research fund of the Innovation Platform for Academicians of Hainan Province under Grant No. YSPTZX202215

Declarations

Data availability. The datasets generated during and/or analysed during the current study are available from the corresponding author on reasonable request.

Conflict of interest. The authors have declared that they do not have any conflicts of interest.

References

- Shor, P.W.: Polynomial-time algorithms for prime factorization and discrete logarithms on a quantum computer. SIAM review 41(2), 303–332 (1999)
- [2] LeCun, Y., Bottou, L., Bengio, Y., Haffner, P.: Gradient-based learning applied to document recognition. Proceedings of the IEEE 86(11), 2278–2324 (1998)
- [3] Sutskever, I., Vinyals, O., Le, Q.V.: Sequence to sequence learning with neural networks. Advances in neural information processing systems **27** (2014)

- [4] Silver, D., Huang, A., Maddison, C.J., Guez, A., Sifre, L., Van Den Driessche, G., Schrittwieser, J., Antonoglou, I., Panneershelvam, V., Lanctot, M., *et al.*: Mastering the game of go with deep neural networks and tree search. nature 529(7587), 484–489 (2016)
- [5] Carleo, G., Troyer, M.: Solving the quantum many-body problem with artificial neural networks. Science 355(6325), 602–606 (2017)
- [6] Deng, D.-L.: Machine learning detection of bell nonlocality in quantum manybody systems. Physical review letters 120(24), 240402 (2018)
- [7] Baireuther, P., O'Brien, T.E., Tarasinski, B., Beenakker, C.W.: Machine-learningassisted correction of correlated qubit errors in a topological code. Quantum 2, 48 (2018)
- [8] Andreasson, P., Johansson, J., Liljestrand, S., Granath, M.: Quantum error correction for the toric code using deep reinforcement learning. Quantum 3, 183 (2019)
- [9] An, Z., Zhou, D.: Deep reinforcement learning for quantum gate control. EPL (Europhysics Letters) 126(6), 60002 (2019)
- [10] Rebentrost, P., Mohseni, M., Lloyd, S.: Quantum support vector machine for big data classification. Physical review letters 113(13), 130503 (2014)
- [11] Li, Z., Liu, X., Xu, N., Du, J.: Experimental realization of a quantum support vector machine. Physical review letters 114(14), 140504 (2015)
- [12] Jerbi, S., Gyurik, C., Marshall, S., Briegel, H., Dunjko, V.: Parametrized quantum policies for reinforcement learning. Advances in Neural Information Processing Systems 34, 28362–28375 (2021)
- [13] Preskill, J.: Quantum computing in the nisq era and beyond. Quantum 2, 79 (2018)
- [14] Bharti, K., Cervera-Lierta, A., Kyaw, T.H., Haug, T., Alperin-Lea, S., Anand, A., Degroote, M., Heimonen, H., Kottmann, J.S., Menke, T., et al.: Noisy intermediate-scale quantum algorithms. Reviews of Modern Physics 94(1), 015004 (2022)
- [15] Beer, K., Bondarenko, D., Farrelly, T., Osborne, T.J., Salzmann, R., Scheiermann, D., Wolf, R.: Training deep quantum neural networks. Nature communications 11(1), 1–6 (2020)
- [16] Peruzzo, A., McClean, J., Shadbolt, P., Yung, M.-H., Zhou, X.-Q., Love, P.J., Aspuru-Guzik, A., O'brien, J.L.: A variational eigenvalue solver on a photonic quantum processor. Nature communications 5(1), 1–7 (2014)

- [17] Liu, J.-G., Zhang, Y.-H., Wan, Y., Wang, L.: Variational quantum eigensolver with fewer qubits. Physical Review Research 1(2), 023025 (2019)
- [18] Farhi, E., Goldstone, J., Gutmann, S.: A quantum approximate optimization algorithm. arXiv preprint arXiv:1411.4028 (2014)
- [19] Farhi, E., Neven, H.: Classification with quantum neural networks on near term processors. arXiv preprint arXiv:1802.06002 (2018)
- [20] Havlíček, V., Córcoles, A.D., Temme, K., Harrow, A.W., Kandala, A., Chow, J.M., Gambetta, J.M.: Supervised learning with quantum-enhanced feature spaces. Nature 567(7747), 209–212 (2019)
- [21] Huang, H.-L., Du, Y., Gong, M., Zhao, Y., Wu, Y., Wang, C., Li, S., Liang, F., Lin, J., Xu, Y., et al.: Experimental quantum generative adversarial networks for image generation. Physical Review Applied 16(2), 024051 (2021)
- [22] Hur, T., Kim, L., Park, D.K.: Quantum convolutional neural network for classical data classification. Quantum Machine Intelligence 4(1), 1–18 (2022)
- [23] McClean, J.R., Boixo, S., Smelyanskiy, V.N., Babbush, R., Neven, H.: Barren plateaus in quantum neural network training landscapes. Nature communications 9(1), 1–6 (2018)
- [24] Ren, P., Xiao, Y., Chang, X., Huang, P.-Y., Li, Z., Chen, X., Wang, X.: A comprehensive survey of neural architecture search: Challenges and solutions. ACM Computing Surveys (CSUR) 54(4), 1–34 (2021)
- [25] Zoph, B., Le, Q.V.: Neural architecture search with reinforcement learning. arXiv preprint arXiv:1611.01578 (2016)
- [26] Pham, H., Guan, M., Zoph, B., Le, Q., Dean, J.: Efficient neural architecture search via parameters sharing. In: International Conference on Machine Learning, pp. 4095–4104 (2018). PMLR
- [27] Cui, J., Chen, P., Li, R., Liu, S., Shen, X., Jia, J.: Fast and practical neural architecture search. In: Proceedings of the IEEE/CVF International Conference on Computer Vision, pp. 6509–6518 (2019)
- [28] Real, E., Moore, S., Selle, A., Saxena, S., Suematsu, Y.L., Tan, J., Le, Q.V., Kurakin, A.: Large-scale evolution of image classifiers. In: International Conference on Machine Learning, pp. 2902–2911 (2017). PMLR
- [29] Liu, H., Simonyan, K., Yang, Y.: Darts: Differentiable architecture search. arXiv preprint arXiv:1806.09055 (2018)
- [30] Ostaszewski, M., Trenkwalder, L.M., Masarczyk, W., Scerri, E., Dunjko, V.: Reinforcement learning for optimization of variational quantum circuit architectures.

Advances in Neural Information Processing Systems 34, 18182–18194 (2021)

- [31] Lu, Z., Shen, P.-X., Deng, D.-L.: Markovian quantum neuroevolution for machine learning. Physical Review Applied 16(4), 044039 (2021)
- [32] Du, Y., Huang, T., You, S., Hsieh, M.-H., Tao, D.: Quantum circuit architecture search for variational quantum algorithms. npj Quantum Information 8(1), 1–8 (2022)
- [33] Zhang, S.-X., Hsieh, C.-Y., Zhang, S., Yao, H.: Differentiable quantum architecture search. arXiv preprint arXiv:2010.08561 (2020)
- [34] Zhang, Y.-H., Zheng, P.-L., Zhang, Y., Deng, D.-L.: Topological quantum compiling with reinforcement learning. Physical Review Letters 125(17), 170501 (2020)
- [35] Gong, W., Jiang, S., Deng, D.-L.: Weighted quantum channel compiling through proximal policy optimization. arXiv preprint arXiv:2111.02426 (2021)
- [36] Williams, R.J.: Simple statistical gradient-following algorithms for connectionist reinforcement learning. Machine learning 8(3), 229–256 (1992)
- [37] Y. LeCun, C.C., Burges, C.: Mnist handwritten digit database (1998)
- [38] Kandasamy, K., Neiswanger, W., Schneider, J., Poczos, B., Xing, E.P.: Neural architecture search with bayesian optimisation and optimal transport. Advances in neural information processing systems **31** (2018)
- [39] Liu, C., Zoph, B., Neumann, M., Shlens, J., Hua, W., Li, L.-J., Fei-Fei, L., Yuille, A., Huang, J., Murphy, K.: Progressive neural architecture search. In: Proceedings of the European Conference on Computer Vision (ECCV), pp. 19–34 (2018)
- [40] Negrinho, R., Gordon, G.: Deeparchitect: Automatically designing and training deep architectures. arXiv preprint arXiv:1704.08792 (2017)
- [41] Shin, R., Packer, C., Song, D.: Differentiable neural network architecture search (2018)
- [42] Liang, H., Zhang, S., Sun, J., He, X., Huang, W., Zhuang, K., Li, Z.: Darts+: Improved differentiable architecture search with early stopping. arXiv preprint arXiv:1909.06035 (2019)
- [43] Chu, X., Wang, X., Zhang, B., Lu, S., Wei, X., Yan, J.: Darts-: robustly stepping out of performance collapse without indicators. arXiv preprint arXiv:2009.01027 (2020)
- [44] Yan, S., Song, K., Liu, F., Zhang, M.: Cate: Computation-aware neural architecture encoding with transformers. In: International Conference on Machine

Learning, pp. 11670–11681 (2021). PMLR

- [45] Kuo, E.-J., Fang, Y.-L.L., Chen, S.Y.-C.: Quantum architecture search via deep reinforcement learning. arXiv preprint arXiv:2104.07715 (2021)
- [46] Oh, S., Choi, J., Kim, J.: A tutorial on quantum convolutional neural networks (qcnn). In: 2020 International Conference on Information and Communication Technology Convergence (ICTC), pp. 236–239 (2020). IEEE
- [47] Cong, I., Choi, S., Lukin, M.D.: Quantum convolutional neural networks. Nature Physics 15(12), 1273–1278 (2019)
- [48] Bausch, J.: Recurrent quantum neural networks. Advances in neural information processing systems 33, 1368–1379 (2020)
- [49] Hochreiter, S., Schmidhuber, J.: Long short-term memory. Neural computation 9(8), 1735–1780 (1997)
- [50] Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., et al.: Pytorch: An imperative style, highperformance deep learning library. Advances in neural information processing systems **32** (2019)
- [51] Bergholm, V., Izaac, J., Schuld, M., Gogolin, C., Alam, M.S., Ahmed, S., Arrazola, J.M., Blank, C., Delgado, A., Jahangiri, S., et al.: Pennylane: Automatic differentiation of hybrid quantum-classical computations. arXiv preprint arXiv:1811.04968 (2018)