Design of a Multi-User RIS-Aided System with Statistical Channel Knowledge

Sadaf Syed ¹⁰, Graduate Student Member, IEEE, Dominik Semmler ¹⁰, Graduate Student Member, IEEE,

Donia Ben Amor 🙆, Graduate Student Member, IEEE, Michael Joham 🙆, Member, IEEE,

and Wolfgang Utschick ^(D), *Fellow*, *IEEE*

School of Computation, Information and Technology, Technical University of Munich, Germany Emails: {sadaf.syed, dominik.semmler, donia.ben-amor, joham, utschick}@tum.de

arXiv:2405.08585v1 [eess.SP] 14 May 2024

Abstract-Reconfigurable intelligent surface (RIS) is a promising technology to enhance the spectral and energy efficiency in a wireless communication system. The design of the phase shifts of an RIS in every channel coherence interval demands a huge training overhead, making its deployment practically infeasible. The design complexity can be significantly reduced by exploiting the second-order statistics of the channels. This paper is the extension of our previous work to the design of an RIS for the multi-user setup, where we employ maximisation of the lower bound of the achievable sum-rate of the users. Unlike for the single-user case, obtaining a closed-form expression for the update of the filters and phase shifts is more challenging in the multi-user case. We resort to the fractional programming (FP) approach and the non-convex block coordinate descent (BCD) method to solve the optimisation problem. As the phase shifts of the RIS obtained by the proposed algorithms are based on the statistical channel knowledge, they do not need to be updated in every channel coherence interval.

Index Terms—MISO, Downlink, RIS, CSI, statistical knowledge, bilinear precoders, Gaussian, fractional programming

I. INTRODUCTION

ASSIVE multiple-input multiple-output (MaMIMO) systems, wherein the base station (BS) is equipped with a huge number of antennas, have the capacity to fulfill the growing need for high data throughput and reduced energy consumption in the wireless communication systems [1]. Nevertheless, deploying a large number of antennas would increase the circuit energy consumption and the hardware expenditures. The recently proposed technology of reconfigurable intelligent surface (RIS) has emerged as an alternative cost-effective solution to enhance the spectral efficiency [2]-[4]. Since the advent of wireless communication systems, the propagation medium between the transmitter and the receiver has been perceived as an uncontrollable entity. The RIS has been proposed as a solution to overcome the ill effects of the propagation medium by manipulating the direction of the transmitted signal to the user in a controlled fashion. It is composed of a large number of passive reflecting elements and offers the flexibility to configure these passive elements in order to achieve the desired performance objectives. Moreover, the passive nature of the RIS elements eliminates the need for an active transmit radio frequency (RF) chain, thereby resulting in a significantly reduced energy consumption and hardware cost compared to

the traditional active antennas at the BS. Thus, they can be scaled economically compared to the scaling of active antennas at the BS.

In this paper, we investigate an RIS-aided multi-user multiple-input single-output (MISO) downlink (DL) communication system and try to exploit the second-order channel statistics in order to reduce the system's design complexity.

A. Related Works

The design of the RIS for various system models has been extensively investigated in the literature, and it offers a considerable performance gain in comparison to the systems without an RIS [5]-[17]. For example, the transmit power of the BS is minimised by employing an RIS in [5], [8], where an alternating optimisation approach is proposed, which relies on the semi-definite relaxation (SDR) technique. Although this algorithm provides a good performance, its complexity is very high, especially for a large-sized RIS. The algorithm proposed in [6] aims to maximise the weighted sum-rate of the users by employing an iterative approach, which utilises the fractional programming (FP) technique [18], [19]. [9] also considers maximisation of the weighted sum-rate of the users by employing the Majorisation-Minimisation algorithm [20] and the Complex Circle Manifold method [21]. However, in order to fully exploit the potential of the RIS, the algorithms in [5]-[10] require perfect knowledge of the RIS-associated links in every channel coherence interval. The passive architecture of the RIS intricates the channel estimation of its links to the BS and the users, and the requirement to estimate these channels perfectly in every channel coherence interval would lead to a huge training overhead, e.g., [22]. Moreover, these algorithms demand the joint optimisation of the phase shifts and the transmit filters to be performed in every channel coherence interval, which is computationally very expensive for an RIS-aided system with a large number of passive elements, and also practically infeasible to be implemented for the fast-fading channels.

In order to combat this problem, many algorithms have been proposed that exploit the statistical knowledge of the channels to design the phase shifts of the RIS [11]–[17]. Since the structure of the channels varies slowly, the channel statistics remain constant for many channel coherence intervals, and hence, it is relatively easier to obtain accurate information of the second-order statistics of the channels through longterm observation. The phase shifts designed on the basis of the channel covariance matrices do not need to be updated regularly, i.e., there is no need to perform the joint optimisation in every channel coherence interval. Moreover, the RIS-associated channels do not need to be estimated frequently as in the case of the algorithms in [5]–[10]. This significantly reduces the channel training overhead and the design complexity of the RIS.

The algorithms in [11], [12], [14] propose low complexity methods for a single-user RIS-aided system based on the long-term channel statistics, but these algorithms cannot be readily extended to the multi-user case. The algorithms in [15], [16] consider a multi-user system, but they assume specific channel models for analytical simplicity. For example, [15] considers a Rician fading model for the RIS-associated channels, which assumes a deterministic line-of-sight (LoS) component and the non-line-of-sight (NLoS) component to have independent and identically distributed (i.i.d.) entries following complex Gaussian distribution with zero mean and unit variance. Similarly, [16] assumes a system model with no direct path and the Kronecker channel model [23] with zero mean for all the channels. In these algorithms, the phase shifts of the RIS and the transmit filters at the BS are only optimised in the coherence interval of the covariance matrices. The algorithms in [13], [17] and [24] propose a two-timescale (TTS) approach with hybrid offline and online optimisation phases. In the offline phase, the phase shifts of the RIS are designed considering the long-term statistics of the channels, which are then kept fixed in the coherence interval of the covariance matrices. On the other hand, in the online step, the optimal filters are computed in every channel coherence interval using the perfect knowledge of the instantaneous channel state information (CSI). This leads to a better performance than the algorithms in [15], [16] but at the cost of a higher computational complexity.

B. Contributions

Motivated by the above challenges, we propose algorithms for designing a multi-user RIS-aided system considering a more general channel model, where the computational complexity is reduced by exploiting the statistical knowledge of the channels. The main contributions of this paper can be summarised as follows.

• We consider a general channel model where the direct channel between the BS and the user and the channel between the RIS and the user are considered to be zero mean with perfectly known covariance matrices. Since the RIS is expected to be deployed at a favourable position, we assume a deterministic LoS path between the BS and the RIS in addition to a NLoS component. This system model is different from the one considered in [15] and [17], where a deterministic LoS path for all the channels is assumed. The proposed algorithms are based on the maximisation of the sum-rate of the users by employing the information-theoretic lower bound on the achievable rate [25] as the figure of merit.

- The Gaussian assumption of the effective channel in an RIS-aided system holds only asymptotically for an infinite number of reflecting elements [26]. Unlike our previous work [11], where we considered the asymptotic Gaussian behaviour to derive the closed-form expression of the lower bound on the sum-rate [25], we derive the lower bound for the non-Gaussian channel model.
- We first propose an algorithm where both the transmit filter at the BS and the phase shifts of the RIS need to be optimised only in the coherence interval of the covariance matrices. A generalised matched filter (GMF) or the bilinear precoder [27], [28] is used as the transmit filter at the BS.
- The algorithm based on the GMF is observed to have a saturation of the sum-rate of the users in the high transmit power regime for the multi-user setup. In order to combat this problem, we also propose another algorithm that employs the TTS approach of [13], where the phase shifts of the RIS are optimised in the coherence interval of the channel statistics, whereas the optimal filters are designed in every channel coherence interval. Both the algorithms require the channel to be estimated in every channel coherence interval, however, we only need to estimate the effective channel of the system and not the RIS-associated links separately. We compare our TTS algorithm to the one in [13], which is based on the stochastic successive convex approximation (SSCA) method [29] employing the maximisation of a concave surrogate function during the offline step.

C. Organisation of the Paper and Mathematical Notation

The paper is organised as follows. In Section II, we present the system model and formulate the optimisation problem. In Section III, we present a simplification of the problem to a tractable form. Section IV deals with the optimisation procedure and the simulation results are presented in Section V. Finally, we conclude the work in Section VI.

Notation: Scalars, vectors and matrices are respectively denoted by lower/upper case, boldface lower case and boldface upper case letters. For an arbitrary matrix A, A^{T} and A^{H} represent its transpose and conjugate transpose respectively. $[\mathbf{A}]_{i,i}$ signifies the element in the *i*-th row and the *j*-th column of the matrix A. The expectation and the variance of a random variable are defined by $\mathbb{E}[.]$ and var(.) respectively, while tr(.) denotes the trace of a square matrix. The Hadamard product of two matrices of the same dimensions is represented by \odot operator, whereas \otimes symbolises the Kronecker product of two matrices of arbitrary dimensions. The real and the imaginary parts of a complex number are defined by Re{.} and $Im\{.\}$ respectively. The operators $(.)^*$, |.| and ||.|| stand for the complex conjugation, scalar magnitude and \mathcal{L} -2 norm respectively, whereas vec(.) denotes vectorisation of the input matrix by stacking its columns into a vector.

The DL of an RIS-aided multi-user MISO communication system is investigated. The system is equipped with one BS having M antennas and serving K single-antenna users. The RIS consists of N passive reflecting elements. The phase-shift matrix is defined by the diagonal matrix $\boldsymbol{\Phi} =$ diag (ϕ_1, \dots, ϕ_N) , where $\phi_1 \dots \phi_N$ are the phase shifts of the N elements of the RIS and $\boldsymbol{\phi} = [\phi_1, \dots, \phi_N]^T$ denotes the phase-shift vector. The channel from the BS to the k-th user is denoted by $\boldsymbol{h}_{d,k} \in \mathbb{C}^M$ and it is circularly symmetric, complex Gaussian distributed, with zero mean and covariance matrix $\boldsymbol{C}_{d,k}$, i.e., $\boldsymbol{h}_{d,k} \sim \mathcal{N}_{\mathbb{C}}(\boldsymbol{0}, \boldsymbol{C}_{d,k})$. The channel from the RIS to the user is denoted by $\boldsymbol{r}_k \in \mathbb{C}^N$ with $\boldsymbol{r}_k \sim \mathcal{N}_{\mathbb{C}}(\boldsymbol{0}, \boldsymbol{C}_{r,k})$. The channel from the BS to the RIS is assumed to have a deterministic LoS component in addition to the random part, which is modelled as

$$\boldsymbol{T} = \underbrace{\left(\sqrt{1-\beta}\right)\boldsymbol{T}'}_{\boldsymbol{\bar{T}}} + \sqrt{\beta}\boldsymbol{R}_{\mathrm{RIS}}^{1/2}\boldsymbol{W}\boldsymbol{R}_{\mathrm{Tx}}^{1/2,\mathrm{H}}$$
(1)

where $(\sqrt{1-\beta}) \mathbf{T}' = \bar{\mathbf{T}}$ denotes the LoS component between the BS and the RIS. The entries in $\mathbf{W} \in \mathbb{C}^{N \times M}$ are i.i.d. with unit variance and zero mean, following circularly symmetric complex Gaussian distributions. \mathbf{R}_{RIS} and \mathbf{R}_{Tx} denote the channel correlation matrices on the side of the RIS and the BS respectively, and $\beta \in [0, 1]$ is the factor controlling the strength of the LoS component. Note that the extreme case of $\beta = 1$ corresponds to the case of zero-mean \mathbf{T} , similar to that in [11]. The effective channel for the k-th user is given by

$$\boldsymbol{h}_{k} = \boldsymbol{h}_{\mathrm{d},k} + \boldsymbol{T}^{\mathrm{H}} \boldsymbol{\varPhi} \boldsymbol{r}_{k}$$
(2)

where $h_{d,k}$, T and r_k are mutually independent. Note that h_k is zero-mean, and its covariance matrix is given by C_k . Moreover, it is assumed that the channels of different users are mutually independent, i.e., $\mathbb{E}[h_i h_j^{\mathrm{H}}] = \mathbf{0} \forall i \neq j$. It is clear from (2) that h_k is non-Gaussian since T and r_k follow Gaussian distributions. The signal received by the k-th user is

$$y_k = \boldsymbol{h}_k^{\mathrm{H}} \boldsymbol{p}_k \, s_k + \sum_{i \neq k} \boldsymbol{h}_k^{\mathrm{H}} \boldsymbol{p}_i \, s_i + v_k \tag{3}$$

where $p_k \in \mathbb{C}^{M \times 1}$ is the transmit beamforming vector for the k-th user, $s_k \sim \mathcal{N}_{\mathbb{C}}(0, 1)$ is the transmitted data symbol to user k and $v_k \sim \mathcal{N}_{\mathbb{C}}(0, 1)$ denotes the additive white Gaussian noise (AWGN) at the k-th user's side. The objective is to reduce the training complexity, and hence, to update the phase shifts of the RIS only in each coherence interval of the covariance matrices, which is much longer than the channel coherence interval. The sum-rate optimisation problem with respect to the transmit filters and the phase shifts of the RIS reads as

$$\max_{\boldsymbol{p}_{1},\cdots,\boldsymbol{p}_{K},\boldsymbol{\phi}} \qquad \mathbb{E}\left[\sum_{k=1}^{K} \log_{2}\left(1+\gamma_{k}\right)\right]$$
s.t.
$$\gamma_{k} = \frac{\left|\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{p}_{k}\right|^{2}}{\sum_{\substack{j=1\\ j\neq k}}^{K} \left|\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{p}_{j}\right|^{2}+1} \qquad (P1)$$

$$\sum_{k=1}^{K} \mathbb{E}[\|\boldsymbol{p}_{k}\|^{2}] \leq P$$

$$|\phi_{n}| = 1 \forall n = 1, \cdots, N.$$

Here γ_k denotes the *k*-th user's signal-to-interference-plusnoise-ratio (SINR) and *P* denotes the total transmit power budget of the BS. It is very difficult to obtain a closed-form expression of the expected sum-rate of the users, and hence, we employ a lower bound on the sum-rate based on the worstcase noise, which is extensively used in the massive MIMO literature [25]. The lower bound of the users' sum-rate is given by $\sum_{k=1}^{K} \log_2(1+\gamma_k^{\text{lb}})$, where γ_k^{lb} is the lower bound of the actual SINR of the *k*-th user, expressed as

$$\gamma_{k}^{\text{lb}} = \frac{\left|\mathbb{E}\left[\boldsymbol{h}_{k}^{\text{H}}\boldsymbol{p}_{k}\right]\right|^{2}}{\operatorname{var}(\boldsymbol{h}_{k}^{\text{H}}\boldsymbol{p}_{k}) + \sum_{\substack{j=1\\j\neq k}}^{K} \mathbb{E}\left[\left|\boldsymbol{h}_{k}^{\text{H}}\boldsymbol{p}_{j}\right|^{2}\right] + 1}.$$
(4)

In order to obtain the closed-form expressions of the expectation and the variance terms in the lower bound, we choose p_k to be a GMF, also known as the bilinear precoder [27], [30], given by

$$\boldsymbol{p}_k = \boldsymbol{A}_k \boldsymbol{h}_k \tag{5}$$

where $A_k \in \mathbb{C}^{M \times M}$ is a deterministic transformation matrix, which only depends on the higher-order statistical knowledge of the channels. As such, the optimisation problem in (P1) is modified to the maximisation of the lower bound, given by

$$\max_{\boldsymbol{A}_{1},\cdots,\boldsymbol{A}_{K},\boldsymbol{\phi}} \sum_{k=1}^{K} \log_{2} \left(1+\gamma_{k}^{\text{lb}}\right)$$
(P2)
s.t.
$$\sum_{k=1}^{K} \mathbb{E}[\|\boldsymbol{p}_{k}\|^{2}] = \sum_{k=1}^{K} \operatorname{tr}\left(\boldsymbol{A}_{k}\boldsymbol{C}_{k}\boldsymbol{A}_{k}^{H}\right) \leq P$$
$$|\phi_{n}| = 1 \forall n = 1, \cdots, N.$$

III. SIMPLIFICATION OF THE OPTIMISATION PROBLEM

In order to solve (P2), we need to express the optimisation problem in a closed-form. Since h_k is not Gaussian distributed, the variance term in (4) is no longer similar to the one derived in [27], [30]. **Theorem 1:** For $\boldsymbol{p}_k = \boldsymbol{A}_k \boldsymbol{h}_k$ and \boldsymbol{h}_k given by (2), $\operatorname{var}(\boldsymbol{h}_k^{\mathrm{H}} \boldsymbol{p}_k) = \boldsymbol{a}_k^{\mathrm{H}} \boldsymbol{J}_k \boldsymbol{a}_k + \operatorname{tr}(\boldsymbol{A}_k \boldsymbol{C}_k \boldsymbol{A}_k^{\mathrm{H}} \boldsymbol{C}_k)$, where

$$\begin{split} \boldsymbol{J}_{k} &= \beta^{2} \operatorname{tr} \left(\boldsymbol{Q} \boldsymbol{R}_{\text{RIS}} \right) \left(\operatorname{vec}(\boldsymbol{R}_{\text{Tx}}) \operatorname{vec}^{\text{H}}(\boldsymbol{R}_{\text{Tx}}) + \left(\boldsymbol{R}_{\text{Tx}}^{\text{T}} \otimes \boldsymbol{R}_{\text{Tx}} \right) \right) \\ &+ 2\beta \operatorname{Re} \Big\{ \operatorname{vec}(\boldsymbol{R}_{\text{Tx}}) \operatorname{vec}^{\text{H}}(\bar{\boldsymbol{T}}^{\text{H}} \boldsymbol{Q} \bar{\boldsymbol{T}}) \Big\} + \beta \boldsymbol{R}_{\text{Tx}}^{\text{T}} \otimes \left(\bar{\boldsymbol{T}}^{\text{H}} \boldsymbol{Q} \bar{\boldsymbol{T}} \right) \\ &+ \beta \left(\bar{\boldsymbol{T}}^{\text{H}} \boldsymbol{Q} \bar{\boldsymbol{T}} \right)^{\text{T}} \otimes \boldsymbol{R}_{\text{Tx}} \\ \boldsymbol{Q} &= \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\text{H}} \boldsymbol{R}_{\text{RIS}} \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\text{H}}. \end{split}$$

Proof. Please refer to Appendix B.

Using (5), we get $\mathbb{E}\left[\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{p}_{k}\right] = \operatorname{tr}(\boldsymbol{C}_{k}\boldsymbol{A}_{k})$ and $\mathbb{E}\left[\left|\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{p}_{j}\right|^{2}\right] = \operatorname{tr}\left(\boldsymbol{C}_{k}\boldsymbol{A}_{j}\boldsymbol{C}_{j}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$. Thus, the lower bound of the SINR in (4) can be expressed in a closed-form as

$$\gamma_k^{\rm lb} = \frac{\left|\boldsymbol{c}_k^{\rm H} \boldsymbol{a}_k\right|^2}{\sum\limits_{j=1}^{K} \boldsymbol{a}_j^{\rm H} \left(\boldsymbol{C}_j^{\rm T} \otimes \boldsymbol{C}_k\right) \boldsymbol{a}_j + \boldsymbol{a}_k^{\rm H} \boldsymbol{J}_k \boldsymbol{a}_k + 1} \tag{6}$$

where $a_k = \operatorname{vec}(A_k)$ and $c_k = \operatorname{vec}(C_k)$. The covariance matrix C_k depends on the phase shifts of the RIS, and hence, C_k must be expressed as a function of ϕ for the phase shift optimisation.

A. Computation of the Channel Covariance Matrix

The channel covariance matrix of the effective channel for the k-th user can be computed as

$$\begin{split} \boldsymbol{C}_{k} &= \mathbb{E}\left[\boldsymbol{h}_{k}\boldsymbol{h}_{k}^{\mathrm{H}}\right] = \boldsymbol{C}_{\mathrm{d},k} + \mathbb{E}_{\boldsymbol{r}_{k},\boldsymbol{T}}\left[\boldsymbol{T}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{r}_{k}\boldsymbol{r}_{k}^{\mathrm{H}}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}\right] \\ &\stackrel{(a)}{=} \boldsymbol{C}_{\mathrm{d},k} + \overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\overline{\boldsymbol{T}} \\ &+ \beta \mathbb{E}_{\boldsymbol{W}}\left[\boldsymbol{R}_{\mathrm{Tx}}^{1/2}\boldsymbol{W}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}^{1/2,\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}^{1/2}\boldsymbol{W}\boldsymbol{R}_{\mathrm{Tx}}^{1/2,\mathrm{H}}\right] \end{split}$$

where (a) follows from (1) and using the fact that $h_{d,k}$, r_k and W are mutually independent random variables. Since the entries of W are i.i.d. with zero mean and unit variance, and $\Phi = \text{diag}(\phi)$, the above expression can be simplified as

$$C_{k} = C_{d,k} + \overline{T}^{H} \boldsymbol{\Phi} C_{\boldsymbol{r},k} \boldsymbol{\Phi}^{H} \overline{T} + \beta \operatorname{tr}(\boldsymbol{R}_{\text{RIS}} \boldsymbol{\Phi} C_{\boldsymbol{r},k} \boldsymbol{\Phi}^{H}) \boldsymbol{R}_{\text{Tx}}$$

$$= C_{d,k} + \overline{T}^{H} \boldsymbol{\Phi} C_{\boldsymbol{r},k} \boldsymbol{\Phi}^{H} \overline{T} + \beta \operatorname{tr}\left(\boldsymbol{R}_{\text{RIS}}(\boldsymbol{C}_{\boldsymbol{r},k} \odot \boldsymbol{\phi} \boldsymbol{\phi}^{H})\right) \boldsymbol{R}_{\text{Tx}}$$

$$\stackrel{(b)}{=} C_{d,k} + \overline{T}^{H} \boldsymbol{\Phi} C_{\boldsymbol{r},k} \boldsymbol{\Phi}^{H} \overline{T} + \beta \boldsymbol{\phi}^{H} \left(\boldsymbol{R}_{\text{RIS}} \odot \boldsymbol{C}_{\boldsymbol{r},k}^{T}\right) \boldsymbol{\phi} \boldsymbol{R}_{\text{Tx}}$$

$$(7)$$

where (b) uses Lemma 1 of [11].

B. Reformulation of the Objective Function

With the expression of γ_k^{lb} in (6), the objective function in (P2) becomes very involved. (P2) can be simplified by the FP approach [18], [19] in a more tractable form. Introducing the auxiliary variables λ_k , the objective function in (P2) can be reformulated as

$$\sum_{k=1}^{K} \log(1+\gamma_k^{\mathrm{lb}}) = \max_{\lambda_k \ge 0} \sum_{k=1}^{K} \log(1+\lambda_k) - \lambda_k + \frac{(1+\lambda_k)\gamma_k^{\mathrm{lb}}}{1+\gamma_k^{\mathrm{lb}}}$$
(8)

The last fractional term in (8) is given by

$$\frac{(1+\lambda_k)\gamma_k^{\text{lb}}}{1+\gamma_k^{\text{lb}}}
= \frac{(1+\lambda_k) \left| \boldsymbol{c}_k^{\text{H}} \boldsymbol{a}_k \right|^2}{\left| \boldsymbol{c}_k^{\text{H}} \boldsymbol{a}_k \right|^2 + \sum_{j=1}^K \boldsymbol{a}_j^{\text{H}} \left(\boldsymbol{C}_j^{\text{T}} \otimes \boldsymbol{C}_k \right) \boldsymbol{a}_j + \boldsymbol{a}_k^{\text{H}} \boldsymbol{J}_k \boldsymbol{a}_k + 1}.$$
(9)

Using the quadratic transform step of the FP approach, the numerator and the denominator of the above fraction can be decoupled with the auxiliary variables χ_k as

$$\frac{(1+\lambda_k)\gamma_k^{\text{lb}}}{1+\gamma_k^{\text{lb}}} = 2\text{Re}\left\{\chi_k^*\left(\sqrt{1+\lambda_k}\right)\boldsymbol{c}_k^{\text{H}}\boldsymbol{a}_k\right\} \\ - |\chi_k|^2 \left(\left|\boldsymbol{c}_k^{\text{H}}\boldsymbol{a}_k\right|^2 + \sum_{j=1}^K \boldsymbol{a}_j^{\text{H}}\left(\boldsymbol{C}_j^{\text{T}} \otimes \boldsymbol{C}_k\right)\boldsymbol{a}_j + \boldsymbol{a}_k^{\text{H}}\boldsymbol{J}_k\boldsymbol{a}_k + 1\right)$$

Let $\boldsymbol{a} = [\boldsymbol{a}_1, \cdots, \boldsymbol{a}_K]^{\mathrm{T}}$, $\boldsymbol{\lambda} = [\lambda_1, \cdots, \lambda_K]^{\mathrm{T}}$ and $\boldsymbol{\chi} = [\chi_1, \cdots, \chi_k]^{\mathrm{T}}$, the objective problem can now be expressed in a more tractable form as

$$\max_{\boldsymbol{a},\boldsymbol{\phi},\boldsymbol{\lambda},\boldsymbol{\chi}} f(\boldsymbol{a},\boldsymbol{\phi},\boldsymbol{\lambda},\boldsymbol{\chi}), \text{ where}$$

$$f(\boldsymbol{a},\boldsymbol{\phi},\boldsymbol{\lambda},\boldsymbol{\chi}) = \sum_{k=1}^{K} \left(\log\left(1+\lambda_{k}\right)-\lambda_{k} \right)$$

$$+ \sum_{k=1}^{K} 2\left(\sqrt{1+\lambda_{k}}\right) \operatorname{Re}\left\{\chi_{k}^{*}\boldsymbol{c}_{k}^{\mathrm{H}}\boldsymbol{a}_{k}\right\}$$

$$- \sum_{k=1}^{K} |\chi_{k}|^{2} \left(\left|\boldsymbol{c}_{k}^{\mathrm{H}}\boldsymbol{a}_{k}\right|^{2} + \sum_{j=1}^{K} \boldsymbol{a}_{j}^{\mathrm{H}}\left(\boldsymbol{C}_{j}^{\mathrm{T}}\otimes\boldsymbol{C}_{k}\right)\boldsymbol{a}_{j} + \boldsymbol{a}_{k}^{\mathrm{H}}\boldsymbol{J}_{k}\boldsymbol{a}_{k} + 1 \right)$$

s.t.
$$\sum_{k=1}^{K} \mathbb{E}[\|\boldsymbol{p}_{k}\|^{2}] = \sum_{k=1}^{K} \mathbb{E}[\|\boldsymbol{A}_{k}\boldsymbol{h}_{k}\|^{2}] \leq P$$
$$|\phi_{n}| = 1 \forall n = 1, \cdots, N$$
$$\lambda_{k} \geq 0 \forall k = 1, \cdots, K.$$
(P3)

The optimisation problem (P3) is non-convex and one can adopt the iterative non-convex BCD method [31], [32] to decompose the problem into four disjoint blocks, containing one of the four variables as the optimisation parameter in each block, as done in [6]. The solution to (P3) with the non-convex BCD method is discussed in the next section.

IV. OPTIMISATION STEPS

The objective problem in (P3) can be solved by updating the variables a, ϕ, λ and χ iteratively using the BCD method. Denoting the optimisation results from the previous iteration by $\bar{a}, \bar{\phi}, \bar{\lambda}$ and $\bar{\chi}$, the update rule of the variables is described next.

A. Update of the auxiliary variables

It can be observed from (8) that the optimal λ_k for a fixed γ_k^{lb} is given by

$$\lambda_k = \gamma_k^{\rm lb}.\tag{10}$$

For the update of χ , $f(a, \phi, \lambda, \chi)$ has to be maximised w.r.t. χ , keeping the other variables fixed. Ignoring the constant terms, the optimisation problem now becomes

$$\max_{\boldsymbol{\chi}} \sum_{k=1}^{K} 2\left(\sqrt{1+\bar{\lambda}_{k}}\right) \operatorname{Re}\left\{\chi_{k}^{*}\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\bar{\boldsymbol{a}}_{k}\right\} -\sum_{k=1}^{K} |\chi_{k}|^{2} \left(\left|\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\bar{\boldsymbol{a}}_{k}\right|^{2} + \sum_{j=1}^{K} \bar{\boldsymbol{a}}_{j}^{\mathrm{H}}\left(\bar{\boldsymbol{C}}_{j}^{\mathrm{T}}\otimes\bar{\boldsymbol{C}}_{k}\right)\bar{\boldsymbol{a}}_{j} + \boldsymbol{a}_{k}^{\mathrm{H}}\boldsymbol{J}_{k}\boldsymbol{a}_{k} + 1\right).$$
(11)

The closed-form solution to the above problem is

$$\chi_{k} = \frac{\left(\sqrt{1+\bar{\lambda}_{k}}\right)\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\bar{\boldsymbol{a}}_{k}}{\left|\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\bar{\boldsymbol{a}}_{k}\right|^{2} + \sum_{j=1}^{K}\bar{\boldsymbol{a}}_{j}^{\mathrm{H}}\left(\bar{\boldsymbol{C}}_{j}^{\mathrm{T}}\otimes\bar{\boldsymbol{C}}_{k}\right)\bar{\boldsymbol{a}}_{j} + \boldsymbol{a}_{k}^{\mathrm{H}}\boldsymbol{J}_{k}\boldsymbol{a}_{k} + 1}.$$
(12)

B. Update of the transformation matrix

The optimisation problem for this block reads as

$$\max_{\boldsymbol{a}_{1},\cdots,\boldsymbol{a}_{K}} \sum_{k=1}^{K} 2\left(\sqrt{1+\bar{\lambda}_{k}}\right) \operatorname{Re}\left\{\bar{\chi}_{k}^{*}\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\boldsymbol{a}_{k}\right\} -\sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \left(\left|\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\boldsymbol{a}_{k}\right|^{2} + \sum_{j=1}^{K} \boldsymbol{a}_{j}^{\mathrm{H}}\left(\bar{\boldsymbol{C}}_{j}^{\mathrm{T}}\otimes\bar{\boldsymbol{C}}_{k}\right)\boldsymbol{a}_{j} + \boldsymbol{a}_{k}^{\mathrm{H}}\boldsymbol{J}_{k}\boldsymbol{a}_{k} + 1\right)$$
(13)

s.t.
$$\sum_{k=1}^{K} \mathbb{E}[\|\boldsymbol{A}_{k}\boldsymbol{h}_{k}\|^{2}] = \sum_{k=1}^{K} \operatorname{tr}\left(\boldsymbol{A}_{k}\bar{\boldsymbol{C}}_{k}\boldsymbol{A}_{k}^{\mathrm{H}}\right) \leq P. \quad (14)$$

The constraint in (14) can be equivalently represented in the vectorised form as

$$\sum_{k=1}^{K} \operatorname{tr} \left(\boldsymbol{A}_{k} \bar{\boldsymbol{C}}_{k} \boldsymbol{A}_{k}^{\mathrm{H}} \right) = \sum_{k=1}^{K} \boldsymbol{a}_{k}^{\mathrm{H}} \left(\bar{\boldsymbol{C}}_{k}^{\mathrm{T}} \otimes \mathbf{I} \right) \boldsymbol{a}_{k} \leq P. \quad (15)$$

The optimal solution to the above optimisation problem is given by

$$\boldsymbol{a}_{k} = \bar{\chi}_{k} \left(\sqrt{1 + \bar{\lambda}_{k}} \right) \left(\left| \bar{\chi}_{k} \right|^{2} \bar{\boldsymbol{c}}_{k} \bar{\boldsymbol{c}}_{k}^{\mathrm{H}} + \left| \bar{\chi}_{k} \right|^{2} \boldsymbol{J}_{k} + \sum_{j=1}^{K} \left| \bar{\chi}_{j} \right|^{2} \left(\bar{\boldsymbol{C}}_{k}^{\mathrm{T}} \otimes \bar{\boldsymbol{C}}_{j} \right) + \mu \left(\bar{\boldsymbol{C}}_{k}^{\mathrm{T}} \otimes \mathbf{I} \right) \right)^{-1} \bar{\boldsymbol{c}}_{k} \quad (16)$$

where $\mu \ge 0$ is the optimal Lagrangian multiplier corresponding to the DL power constraint in (15), which can be obtained using one-dimensional search techniques, e.g., the bisection method. However, the matrix inversion is expensive and one needs to perform a large number of iterations to obtain an accurate value of μ by the bisection method. It can become computationally very expensive if M is large. This problem can be averted by applying the trick mentioned in [33]–[35]. The idea is to convert the constrained optimisation problem in (14) to an equivalent unconstrained problem by introducing the constraint into the objective function itself. The inequality constraint in (15) will be satisfied with equality for the optimal precoding filters, and hence, (14) can be written as

$$\max_{\boldsymbol{a}_{1},\cdots,\boldsymbol{a}_{K}} \sum_{k=1}^{K} 2\left(\sqrt{1+\bar{\lambda}_{k}}\right) \operatorname{Re}\left\{\bar{\chi}_{k}^{*}\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\boldsymbol{a}_{k}\right\} -\sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \left(\left|\bar{\boldsymbol{c}}_{k}^{\mathrm{H}}\boldsymbol{a}_{k}\right|^{2} + \sum_{j=1}^{K} \boldsymbol{a}_{j}^{\mathrm{H}}\left(\bar{\boldsymbol{C}}_{j}^{\mathrm{T}}\otimes\bar{\boldsymbol{C}}_{k}\right)\boldsymbol{a}_{j} + \boldsymbol{a}_{k}^{\mathrm{H}}\boldsymbol{J}_{k}\boldsymbol{a}_{k} + \frac{\sum_{j=1}^{K} \boldsymbol{a}_{j}^{\mathrm{H}}\left(\bar{\boldsymbol{C}}_{j}^{\mathrm{T}}\otimes\mathbf{I}\right)\boldsymbol{a}_{j}}{P}\right).$$
(17)

The optimal solution of (17) is given by

$$\boldsymbol{a}_{k} = \bar{\chi}_{k} \left(\sqrt{1 + \bar{\lambda}_{k}} \right) \left(\left| \bar{\chi}_{k} \right|^{2} \bar{\boldsymbol{c}}_{k} \bar{\boldsymbol{c}}_{k}^{\mathrm{H}} + \left| \bar{\chi}_{k} \right|^{2} \boldsymbol{J}_{k} + \sum_{j=1}^{K} \left| \bar{\chi}_{j} \right|^{2} \left(\bar{\boldsymbol{C}}_{k}^{\mathrm{T}} \otimes \bar{\boldsymbol{C}}_{j} \right) + \sum_{j=1}^{K} \frac{\left| \bar{\chi}_{j} \right|^{2}}{P} \left(\bar{\boldsymbol{C}}_{k}^{\mathrm{T}} \otimes \mathbf{I} \right) \right)^{-1} \bar{\boldsymbol{c}}_{k}.$$
(18)

Hence, we obtain a closed-form solution for the optimal precoders without the need to compute μ by the iterative onedimensional search methods. However, it is to be noted that the optimal a_k from (18) might not necessarily satisfy the downlink power constraint of (15). Hence, a_k from (18) must be scaled in the end to fulfill the power budget.

C. Update of the phase-shift vector

Ignoring the constant terms, the optimisation problem for this block is given by

$$\max_{\boldsymbol{\phi}} \sum_{k=1}^{K} 2\left(\sqrt{1+\bar{\lambda}_{k}}\right) \operatorname{Re}\left\{\bar{\chi}_{k}^{*}\boldsymbol{c}_{k}^{\mathrm{H}}\bar{\boldsymbol{a}}_{k}\right\} - \sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \left(\left|\boldsymbol{c}_{k}^{\mathrm{H}}\bar{\boldsymbol{a}}_{k}\right|^{2} + \sum_{j=1}^{K} \bar{\boldsymbol{a}}_{j}^{\mathrm{H}}\left(\boldsymbol{C}_{j}^{\mathrm{T}}\otimes\boldsymbol{C}_{k}\right)\bar{\boldsymbol{a}}_{j} + \boldsymbol{a}_{k}^{\mathrm{H}}\boldsymbol{J}_{k}\boldsymbol{a}_{k}\right)$$

$$(19)$$

s.t. $|\phi_n| = 1 \,\forall \, n = 1, \cdots, N.$ (20)

 C_k from (7) is inserted in (19), and ϕ is replaced by $e^{j\varphi}$, where $\phi_n = e^{j\varphi_n} \forall n$ and $\varphi \in \mathbb{R}^{N \times 1}$ denotes the vector containing the corresponding angles in radians. We would then employ the iterative gradient ascent method to find the optimal φ . The gradient of (19) w.r.t. φ is given by $2 \operatorname{Re} \{ -j \overline{\phi^*} \odot \Delta \}$, where the expression of Δ is provided in Appendix C. Hence, the update rule for φ can be written as

$$\boldsymbol{\varphi} \leftarrow \bar{\boldsymbol{\varphi}} + 2 \kappa \operatorname{Re} \left\{ -j \bar{\boldsymbol{\phi}}^* \odot \boldsymbol{\Delta} \right\}$$
 (21)

where κ is the optimal step size, which can be computed by the Armijo rule [36].

The iterative BCD method results in the improvement of the objective function in each sub iteration and its convergence has been established in [31], [32]. Once the optimal phase shift vector ϕ and the transformation matrices A_k are obtained, they are kept fixed in the coherence interval of the covariance matrices. The filters are then updated in each channel coherence interval by (5), i.e., the filter update in each channel coherence interval only requires multiplication of the precomputed matrices A_k with the perfectly estimated channel h_k . The proposed algorithm is summarised in Algorithm 1.

Algorithm 1 Bilinear Precoders based Design of RIS using the Statistical Channel Knowledge

- Initialise the phase-shift vector φ and the auxiliary variables λ and χ with feasible values;
- 2: Initialise a according to (18);
- 3: Repeat
- 4: Update λ , χ and a according to (10), (12), and (18) respectively;
- 5: Find the optimal step size κ by the Armijo rule and update φ according to (21);
- 6: **Until** The value of the objective function in (P3) converges.
- 7: Obtain the precoding vectors by (5).

It will be later shown in the simulation results that the proposed algorithm offers a performance gain with low complexity. However, it is also observed that the GMFs cannot suppress the inter-user interference, which results in a saturation of the sum-rate at high power levels [27], [30], [37]. This leads to a considerable performance loss compared to the algorithms requiring instantaneous CSI for the phase shift update [6] at high transmit power. This saturation problem can be resolved by employing a hybrid online and offline optimisation algorithm as adopted in [13], [17], [24]. The key idea here is to design the phase shifts based on the channels' statistical knowledge so that we do not need to compute the phases in every channel coherence interval. The phase shift optimisation is again performed by maximising the lower bound of the users' sum rate given in (P3). Once the optimised phase shifts are obtained, they are kept fixed in the coherence interval of the covariance matrices. The design of the phase shifts belongs to the offline optimisation part, which relies only on the long-term statistics of the channels. After performing the offline optimisation, the transmit filters are now designed in the online optimisation step, i.e., the filter optimisation (for fixed phase shifts) is now performed in every channel coherence interval using the BCD or zeroforcing (ZF) methods, instead of multiplying the perfectly estimated channel vector with the precomputed matrices as in Algorithm 1. After estimating the effective channel vectors for the users, the filter update step in Algorithm 1 has the complexity of $\mathcal{O}(M^2)$, but this hybrid method computing the optimal filters in every channel coherence interval has the complexity of $\mathcal{O}(M^3)$. However, the filter design in every channel coherence interval still does not require the knowledge of the RIS-associated links separately. Instead, the BS only requires the knowledge of the effective channels, thereby reducing the channel training overhead as compared to the algorithms only based on the instantaneous CSI, e.g., [6]. The overall hybrid algorithm is summarised in Algorithm 2.

Algorithm 2 Hybrid Online and Offline Design of RIS using the Statistical Channel Knowledge

- 1: Perform the offline optimisation with the statistical knowledge of the channels:
 - Initialise the phase-shift vector φ and the auxiliary variables λ and χ with feasible values;
 - Initialise *a* according to (18);
 - Repeat
 - Update λ , χ and a according to (10), (12), and (18) respectively;
 - Find the optimal step size κ by the Armijo rule and update φ according to (21);
 - Until The value of the objective function in (P3) converges.
- 2: The phase-shift vector obtained from the offline optimisation step is kept fixed and the online optimisation step is performed in each channel coherence interval:
 - Apply either the iterative BCD algorithm or the zeroforcing method with the optimal power allocation (waterfilling solution [38]) to obtain the precoding vectors p_1, \dots, p_K .

D. Convergence and Complexity

The convergence of the BCD algorithm is discussed in [32]. Since the value of the objective function improves in each subproblem, the convergence to a local minimum is guaranteed. The reduction in the complexity by the proposed algorithms is achieved due to the fact that the phase shifts of the RIS only need to be updated in the coherence interval of the covariance matrices. Both of the algorithms employ the same update step for the phase shifts of the RIS. The complexity for updating the phase shifts by the proposed algorithms is $\mathcal{O}(I_a(KN^2 + KNM^2))$, where I_a is the number of iterations required by the algorithms for convergence. We next compare the complexity of the proposed algorithms with the TTS algorithm in [13], which uses the SSCA method in which several random channel samples are generated from their known distributions in each iteration. For each of the generated samples, the optimal filters are computed by employing the iterative weighted minimum mean-square error (IWMMSE) method [39] and this process needs to be repeated several times till the convergence is reached. The optimisation of the phase shifts with the SSCA based TTS method [13] has the complexity of $\mathcal{O}(I_b(KNM + T_HJKM^3))$, where I_b denotes the number of iterations required for convergence, J denotes the number of IWMMSE iterations, and T_H denotes



Figure 1: Convergence Plot for IWMMSE method for K = 3, M = 8

the number of random channel samples required for the SSCA method. Even though the complexity of our proposed algorithms grows with N^2 , whereas the SSCA method has a linear growth with N, using Algorithms 1 and 2 results in a reduced computational time for the practical systems. This is due to the fact that the complexity of the SSCA method is dominated by the requirement to perform IWMMSE iterations several times. From the convergence plot of the IWMMSE method in Fig. 1, it can be seen that its convergence is very slow for high power levels, and it takes more than 100 iterations to converge for P = 30 dB. Each IWMMSE iteration in Fig. 1 needs several iterations to compute the optimal Lagrangian parameter, which is needed for the update of the transmit filters in [39] (discussed in [40]). However, the proposed algorithms bypass this requirement because of the closed-form solution given by (18). Moreover, the IWMMSE method needs to be applied for each of the T_H random samples, which is generally around 50 to 100 in number. This increases the computational time of the TTS approach in [13] and its run-time is observed to be approximately 10 times higher than that of the propsoed algorithms.

V. SIMULATION RESULTS

In this section, numerical results are provided to validate the effectiveness of the proposed algorithms. The system comprises of one BS equipped with M = 16 antennas, serving K single-antenna users. The RIS is equipped with N = 100passive reflecting elements. The setup is illustrated in Fig. 2. The users are placed inside a circle of radius 50 m with the centre of the circle at a distance D m from the BS. Each of the channels is generated according to its distribution described in Section II. The covariance matrix of each channel is generated according to the 3GPP specifications [41]. The BS, users and the RIS are equipped with a uniform linear array (ULA). To model each of the channels, a spatial channel propagation model is considered similar to [42], where the channels are obtained by the superposition of multiple-path components resulting from the scatterers in the surrounding propagation



Figure 2: Simulation Setup



Figure 3: Convergence Plot of the Proposed Algorithms (a) and with the Normalised Objective (b) for K = 1

environment. Assuming $N_{\text{path}} = 6$ main clusters and $N_{\text{ray}} = 20$ rays in each cluster, each covariance matrix is given by

$$oldsymbol{C}_{i,k} = lpha_{i,k} \sum_{n=1}^{N_{\text{path}}} rac{
u_n}{N_{\text{ray}}} \sum_{m=1}^{N_{\text{ray}}} oldsymbol{x}_{i,k}(heta_{n,m}) oldsymbol{x}_{i,k}^{ ext{H}}(heta_{n,m})$$

where $\theta_{n,m}$ corresponds to the incident angle of the received signal from the scatterer of the *m*-th ray in the *n*-th cluster, and the index *i* is used to differentiate the different components of the effective channel, i.e., $h_{d,k}$, r_k and T. $x_{i,k}(\theta_{n,m})$ denotes the array steering vector of the *i*-th channel component of the *k*-th user at an angle $\theta_{n,m}$ and is given by

$$\boldsymbol{x}_{i,k}(\theta_{n,m}) = \left[1, \mathrm{e}^{j\pi \sin(\theta_{n,m})}, \cdots, \mathrm{e}^{j\pi(M_i-1)\sin(\theta_{n,m})}\right]^{\mathrm{T}}$$

where M_i denotes the number of antennas. ν_n signifies the power of the *n*-th cluster and $\alpha_{i,k}$ corresponds to the slowfading coefficient which depends on the distance. According to the 3GPP model, $\alpha_{i,k}$ is equal to the signal to noise ratio (SNR) at distance $\delta_{i,k}$ and is given by [43]

$$10 \log_{10}(\alpha_{i,k}) = 78.7 - 37.6 \log_{10}(\delta_{i,k}) \,\mathrm{dB}.$$

The deterministic LoS component T' is considered to have rank one, and it is generated by taking the outer product of two array-steering vectors of lengths N and M respectively, and β is set to 0.2. The achievable sum-rate of the users is taken as the performance metric, which is averaged over 1000 channel realisations for 100 different covariance matrices $C_{i,k}$, generated by varying the position of the users and the path powers ν_n .

A. Single-User Case

We first consider the single-user case where the user is placed at (D m, 0 m). In order to compare the proposed algorithms for the single-user case with the single-user algorithms in [11] exploiting the statistical channel knowledge, we consider T' = 0 similar to [11]. At first, the convergence plot of the long-term optimisation part of the proposed algorithms is presented in Fig. 3a for a single scenario of covariance matrices with $D = 30 \,\mathrm{m}$ and the transmit power levels of P = 0 dB and P =30 dB. Both Algorithm 1 and Algorithm 2 have the same long-term optimisation method. The convergence analysis reveals that the proposed algorithms converge in approximately 20 iterations for both lower and higher power levels, i.e., the convergence behaviour is independent of the transmit power level. We also compare the convergence of our algorithms to the SSCA based TTS method of [13] in Fig. 3b. Since the algorithms have different metrics for optimisation, we normalise the objective values between 0 and 1, where 0 denotes the minimum objective value and 1 denotes the maximum value over the iterations. It is clear from Fig. 3b that the proposed algorithms have a faster rate of convergence than the TTS method of [13], which takes more than 50 iterations to converge.

The user's rate is next plotted in Fig. 4, which is computed with the different algorithms and compared over the transmit power levels P with D varying in between 15 m to 60 m. The performance of the proposed algorithms is compared with the algorithms in [11], [13] exploiting the statistical channel knowledge, and also with [6] employing the instantaneous CSI for both the filter and the phase shift optimisation. Fig. 4 shows that the algorithm in [6] serves as an upper bound to the algorithms using only the statistical information for the phase shift design. Both of the proposed algorithms have a similar performance at low P, however, Algorithm 1, employing the bilinear precoder, is not optimal at the higher power levels [27]. Hence, Algorithm 2 with the optimal filters computed using the BCD method outperforms Algorithm 1 at high P and at the price of higher complexity. The proposed algorithms clearly offer a considerable performance gain when compared to a system without RIS [27] or to the one employing RIS with random phase shifts. Fig. 4 also shows that Algorithm 2 slightly outperforms the TTS approach in [13] based on the SSCA method, which also uses the optimal precoding filters computed via the IWMMSE method [39] in every channel coherence interval. Moreover, Algorithm 2 employing the hybrid design with the optimal BCD filters also slightly outperforms the hybrid algorithms with the optimal filters in [11] at high transmit power levels.

B. Multi-User Case

We next consider a multi-user system with K = 3 users, randomly placed inside a circle of radius 50 m at a distance D = 30 m from the BS. At first, the convergence plot of the proposed algorithms for the multi-user case is shown in Fig. 5a. Similar to the single-user case, the convergence of the algorithms is independent of the transmit power level and they converge in approximately 25 iterations. We again compare the rate of convergence of our algorithms to the SSCA based TTS method of [13] in Fig. 5b. The objective values of the algorithms are normalised between 0 and 1 for comparison.



Figure 4: User's Rate vs Transmit Power P in dB for K = 1



Figure 5: Convergence Plot of the Proposed Algorithms (a) and with the Normalised Objective (b) for K = 3

The proposed algorithms have a faster rate of convergence than the TTS method of [13], which takes more than 100 iterations to converge, and the difference in rate is even larger here than the single-user case in Fig. 3b.

The sum-rate of the users is plotted in Fig. 6. The algorithm in [6] performing the optimisation of both the filters and the phase shifts in every channel coherence interval acts as the upper bound to the algorithms involving only the statistical channel knowledge for the optimisation of the phase shifts. It can be seen that Algorithm 1 using the bilinear precoders offers a good performance only for low P and the sum-rate starts to saturate gradually when the transmit power is higher than 10 dB. This sum-rate saturation in the multi-user scenario



Figure 6: Sum-Rate vs Transmit Power P in dB for K = 3



Figure 7: Sum-Rate vs N at P = 10 dB

is owing to the fact that the GMF cannot mitigate the interuser interference. It can also be seen that Algorithm 2 is able to solve this saturation problem as it computes the optimal precoding filters in every channel coherence interval with the BCD method or the zero-forcing solution (optimal at high P). It can be observed in Fig. 6 that the hybrid algorithm using the zero-forcing filters performs almost similar to the algorithm using the BCD method at high power levels, but there is some performance gap at lower power levels since the zero-forcing solution is not optimal when the noise level is high. Moreover, Algorithm 2 performs slightly better than the SSCA-based hybrid algorithm of [13] on an average with the BCD filter and at high P with the zero-forcing filter. All the algorithms are compared with systems having no RIS or having an RIS with random phase shifts. For these two baseline systems, the chosen filters are either the low-complexity bilinear precoders or those computed by the BCD method. Algorithm 2 with the optimal filters performs better than the baseline algorithms at all transmit power levels. The bilinear precoders based Algorithm 1 offers a performance gain when compared to the baseline algorithms employing the bilinear precoders [27]. However, it is only better than the baseline cases with the BCD filters at low P. This behaviour is expected and the difference in performance is attributed to the suboptimality of the low complexity bilinear precoders at high P in comparison to the BCD filters. We also compare the simulation run-time of the long-term optimisation method of the proposed algorithms and SSCA-based TTS approach of [13] for P = 20 dB in Fig. 6. Since the run-time also depends on the processor, we only plot the ratio of run-time of [13] to the proposed algorithms for comparison. From the histogram plot, it is observed that the ratio is always greater than 10, i.e. the proposed algorithms are an order of magnitude faster than the SSCA-based method even in the worst-case trials.

Finally, Fig. 7 shows the impact of the number of passive reflecting elements N on the performance of the different algorithms at a fixed power P = 10 dB. It is observed that the sum-rate computed with the algorithm performing the

optimisation of the phase shifts in every channel coherence interval [6] grows at a faster rate with N than the other lower complexity algorithms in Fig. 7. The performance of the proposed algorithms improves with an increase in N at a similar rate. This behaviour is expected as both the algorithms employ the same optimisation procedure for the update of the phase shifts. Also, it is observed that the sum-rate does not improve with increasing N, if the phase shifts of the RIS are not optimised.

VI. CONCLUSION

This work has addressed the problem of the existing algorithms for an RIS-aided system relying on the knowledge of the instantaneous CSI for all the channels in every channel coherence interval. The information-theoretic lower bound of the users' sum-rate based on the worst-case noise is used as the figure of merit. This lower bound is then maximised to design the transmit filters at the BS and the phase shifts of the RIS. Our proposed algorithms, utilising the second-order channel statistics, significantly reduce the training overhead as the coherence interval of the covariance matrices consists of many channel coherence intervals. It is seen from the simulation results that there is a decline in the performance gain as compared to the algorithms optimising both the phase shifts and the transmit filters in every channel coherence interval, however, the proposed algorithms still bring a considerable improvement in the sum-rate of the users in comparison to the systems with no RIS or with random phase shifts. The first proposed algorithm uses the bilinear precoder and it performs all the optimisation processes only in the coherence interval of the channel statistics. However, it is observed to saturate in the high power regime for the multi-user case. The second algorithm employs the hybrid online/offline optimisation step and performs the transmit filter optimisation in every channel coherence interval, thereby having a higher complexity than the first algorithm. Nevertheless, it is seen to combat the observed saturation effect with the bilinear precoder. We have considered the covariance matrices to be perfectly known in this work. As a possible future work, one can focus on the effect of the imperfect covariance information on the performance of the RIS-aided communication systems.

APPENDIX

A. Lemma 1

For any $\boldsymbol{u} \sim \mathcal{N}_{\mathbb{C}}(\boldsymbol{0}, \boldsymbol{C})$, it holds that

$$\mathbb{E} \left[\boldsymbol{u}^{\mathrm{H}} \boldsymbol{M}_{1} \boldsymbol{u} \boldsymbol{u}^{\mathrm{H}} \boldsymbol{M}_{2} \boldsymbol{u} \right] = \operatorname{tr} (\boldsymbol{C} \boldsymbol{M}_{1} \boldsymbol{C} \boldsymbol{M}_{2}) \\ + \operatorname{tr} (\boldsymbol{C} \boldsymbol{M}_{1}) \operatorname{tr} (\boldsymbol{C} \boldsymbol{M}_{2})$$

Proof. The lemma is a straightforward extension of Lemma 2 in [44]. \Box

B. Proof of Theorem 1

Proof.

$$egin{aligned} ext{var}(oldsymbol{h}_k^{ ext{H}}oldsymbol{p}_k) &= \mathbb{E}[|oldsymbol{h}_k^{ ext{H}}oldsymbol{p}_k - \mathbb{E}[oldsymbol{h}_k^{ ext{H}}oldsymbol{p}_k]]^2] \ &= \mathbb{E}\left[oldsymbol{h}_k^{ ext{H}}oldsymbol{A}_koldsymbol{h}_k - oldsymbol{h}_k^{ ext{H}}oldsymbol{h}_k^{ ext{H}}oldsymbol{p}_k]]^2
ight] \ &= \mathbb{E}\left[oldsymbol{h}_k^{ ext{H}}oldsymbol{A}_koldsymbol{h}_k + oldsymbol{A}_koldsymbol{h}_k^{ ext{H}}oldsymbol{h}_k^{ ext{H}}oldsymbol{h}_k
ight] - \left| ext{tr}oldsymbol{(oldsymbol{C}_koldsymbol{A}_k)}
ight|^2 \end{aligned}$$

Since $h_{d,k}$, T and r_k are mutually independent, and denoting $\sqrt{\beta} R_{\text{RIS}}^{1/2} W R_{\text{Tx}}^{1/2,\text{H}}$ by T_r , we have

$$\mathbb{E}\left[\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{h}_{k}\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{h}_{k}\right] = \mathbb{E}\left[|\boldsymbol{h}_{\mathrm{d},k}^{\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{h}_{\mathrm{d},k}|^{2}\right] \\ + \mathbb{E}\left[\boldsymbol{h}_{\mathrm{d},k}^{\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{h}_{\mathrm{d},k}\boldsymbol{r}_{k}^{\mathrm{H}}\boldsymbol{\Phi}^{\mathrm{H}}\boldsymbol{T}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{T}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{r}_{k}\right] \\ + \mathbb{E}[|\boldsymbol{h}_{\mathrm{d},k}^{\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{T}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{r}_{k}|^{2}] \\ + \mathbb{E}[|\boldsymbol{r}_{k}^{\mathrm{H}}\boldsymbol{\Phi}^{\mathrm{H}}\boldsymbol{T}\boldsymbol{A}_{k}\boldsymbol{h}_{\mathrm{d},k}|^{2}] \\ + \mathbb{E}[\boldsymbol{r}_{k}^{\mathrm{H}}\boldsymbol{\Phi}^{\mathrm{H}}\boldsymbol{T}\boldsymbol{A}_{k}\boldsymbol{T}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{r}_{k}\boldsymbol{h}_{\mathrm{d},k}^{\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{h}_{\mathrm{d},k}] \\ + \mathbb{E}[|\boldsymbol{r}_{k}^{\mathrm{H}}\boldsymbol{\Phi}^{\mathrm{H}}\boldsymbol{T}\boldsymbol{A}_{k}\boldsymbol{T}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{r}_{k}\boldsymbol{h}_{\mathrm{d},k}^{\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{h}_{\mathrm{d},k}] \\ + \mathbb{E}[|\boldsymbol{r}_{k}^{\mathrm{H}}\boldsymbol{\Phi}^{\mathrm{H}}\boldsymbol{T}\boldsymbol{A}_{k}\boldsymbol{T}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{r}_{k}|^{2}]. \quad (22)$$

For the computation of the terms in (22), we need some additional results.

$$\mathbb{E}\left[\boldsymbol{T}_{r}\boldsymbol{A}_{k}\boldsymbol{T}_{r}^{\mathrm{H}}\right] = \beta \mathbb{E}\left[\boldsymbol{R}_{\mathrm{RIS}}^{1/2}\boldsymbol{W}\boldsymbol{R}_{\mathrm{Tx}}^{1/2,\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{R}_{\mathrm{Tx}}^{1/2}\boldsymbol{W}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}^{1/2,\mathrm{H}}\right]$$
$$= \beta \operatorname{tr}(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k})\boldsymbol{R}_{\mathrm{RIS}}.$$
(23)

Using Lemma 2 of [44], we get

$$\mathbb{E}\left[|\boldsymbol{r}_{k}^{\mathrm{H}}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{r}\boldsymbol{A}_{k}\boldsymbol{T}_{r}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{r}_{k}|^{2}\right]$$

$$=\mathbb{E}_{\boldsymbol{T}_{r}}\left[\left|\operatorname{tr}\left(\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{r}\boldsymbol{A}_{k}\boldsymbol{T}_{r}^{\mathrm{H}}\boldsymbol{\varPhi}\right)\right|^{2}\right]$$

$$+\mathbb{E}_{\boldsymbol{T}_{r}}\left[\operatorname{tr}\left(\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{r}\boldsymbol{A}_{k}\boldsymbol{T}_{r}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{r}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{T}_{r}^{\mathrm{H}}\boldsymbol{\varPhi}\right)\right].$$
(24)

The first term in (24) can be written as

$$\mathbb{E}_{\boldsymbol{T}_{r}}\left[\left|\operatorname{tr}\left(\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{\boldsymbol{r}}\boldsymbol{A}_{k}\boldsymbol{T}_{\boldsymbol{r}}^{\mathrm{H}}\boldsymbol{\varPhi}\right)\right|^{2}\right]$$
$$=\mathbb{E}_{\boldsymbol{w}}\left[\left|\boldsymbol{w}^{\mathrm{H}}\left(\boldsymbol{\mathcal{Y}}_{1,k}^{\mathrm{T}}\otimes\left(\boldsymbol{R}_{\mathrm{RIS}}^{1/2,\mathrm{H}}\boldsymbol{\mathcal{Y}}_{2,k}\boldsymbol{R}_{\mathrm{RIS}}^{1/2}\right)\right)\boldsymbol{w}\right|^{2}\right] \quad (25)$$

where $\mathcal{Y}_{1,k} = \mathbf{R}_{T_x}^{1/2,H} \mathbf{A}_k \mathbf{R}_{T_x}^{1/2}$, $\mathcal{Y}_{2,k} = \beta^2 \boldsymbol{\Phi} \mathbf{C}_{r,k} \boldsymbol{\Phi}^H$ and $\boldsymbol{w} = \text{vec}(\boldsymbol{W})$, and since the entries of \boldsymbol{W} are i.i.d. with zero mean and unit variance, it follows that $\boldsymbol{w} \sim \mathcal{N}_{\mathbb{C}}(\mathbf{0}, \mathbf{I})$. The above expression can hence be computed as follows

$$\begin{split} & \mathbb{E}_{\boldsymbol{T}_{r}}\left[\left|\operatorname{tr}\left(\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{r}\boldsymbol{A}_{k}\boldsymbol{T}_{r}^{\mathrm{H}}\boldsymbol{\varPhi}\right)\right|^{2}\right] \\ &=\beta^{2}\left(\left|\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}\right)\right|^{2}\left|\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{RIS}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\right)\right|^{2} \right. \\ &\left.+\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}\right)\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{RIS}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\right)\right)^{2} \end{split}$$

where we have used the property that for all square matrices P, Q, R and S, we have $\operatorname{tr}(P \otimes Q) = \operatorname{tr}(P) \operatorname{tr}(Q)$, and $(P \otimes Q)(R \otimes S) = (PR) \otimes (QS)$ [45].

$$\mathbb{E}_{\boldsymbol{T}_{r}}\left[\operatorname{tr}\left(\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{r}\boldsymbol{A}_{k}\boldsymbol{T}_{r}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{T}_{r}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{T}_{r}^{\mathrm{H}}\boldsymbol{\varPhi}\right)\right]$$

$$=\beta^{2}\mathbb{E}_{\boldsymbol{W}}\left[\operatorname{tr}\left(\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}^{1/2}\boldsymbol{W}\boldsymbol{R}_{\mathrm{Tx}}^{1/2,\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{R}_{\mathrm{Tx}}^{1/2}\boldsymbol{W}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}^{1/2,\mathrm{H}}\right)$$

$$\times\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\varPhi}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}^{1/2}\boldsymbol{W}\boldsymbol{R}_{\mathrm{Tx}}^{1/2,\mathrm{H}}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{Tx}}^{1/2}\boldsymbol{W}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}^{1/2,\mathrm{H}}\boldsymbol{\varPhi}\right)\right].$$

Let the matrix $C_{r,k}^{1/2,\mathrm{H}} \Phi^{\mathrm{H}} R_{\mathrm{RIS}}^{1/2}$ be decomposed by its SVD as $U\Lambda V^{\mathrm{H}}$, where U and V contain the singular vectors and Λ is a diagonal matrix containing the singular values. Using the fact that $V^{\mathrm{H}}W = Z$ has the same distribution as W, since V is a unitary matrix, the above expression can be written as

$$eta^2 \mathbb{E}_{\boldsymbol{Z}} \left[\operatorname{tr} \left(\boldsymbol{\Lambda}^2 \boldsymbol{Z} \boldsymbol{\mathcal{Y}}_{1,k} \boldsymbol{Z}^{\mathrm{H}} \boldsymbol{\Lambda}^2 \boldsymbol{Z} \boldsymbol{\mathcal{Y}}_{1,k}^{\mathrm{H}} \boldsymbol{Z}^{\mathrm{H}}
ight)
ight].$$

Denoting the eigen values of $C_{r,k}^{1/2,\mathrm{H}} \Phi^{\mathrm{H}} R_{\mathrm{RIS}} \Phi C_{r,k}^{1/2}$ by λ_i s, the diagonal matrix Λ can be written as $\sum_i \lambda_i e_i e_i^{\mathrm{T}}$. Hence, the above expression is equivalent to

$$eta^2 \sum_{i,j} \lambda_i \lambda_j \mathbb{E} \left[\operatorname{tr} \left(\boldsymbol{z}_i \boldsymbol{z}_i^{\mathrm{H}} \boldsymbol{\mathcal{Y}}_{1,k} \boldsymbol{z}_j \boldsymbol{z}_j^{\mathrm{H}} \boldsymbol{\mathcal{Y}}_{1,k}^{\mathrm{H}}
ight)
ight]$$

where the matrix Z^{H} is denoted by $[z_1, \cdots, z_{\text{N}}]$. Since z_i s have the same distribution as w_i s, $z_i \sim \mathcal{N}_{\mathbb{C}}(\mathbf{0}, \mathbf{I})$, and the expectation can be computed as

$$\beta^{2} \sum_{\substack{i,j \\ i \neq j}} \lambda_{i} \lambda_{j} \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}}^{1/2,\mathsf{H}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathsf{Tx}}^{1/2} \boldsymbol{R}_{\mathsf{Tx}}^{1/2,\mathsf{H}} \boldsymbol{A}_{k}^{\mathsf{H}} \boldsymbol{R}_{\mathsf{Tx}}^{1/2} \right) + \beta^{2} \sum_{i} \lambda_{i}^{2} \mathbb{E}_{\boldsymbol{z}_{i}} \left[\left| \boldsymbol{z}_{i}^{\mathsf{H}} \boldsymbol{R}_{\mathsf{Tx}}^{1/2,\mathsf{H}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathsf{Tx}}^{1/2} \boldsymbol{z}_{i} \right|^{2} \right] \overset{(a)}{=} \beta^{2} \sum_{\substack{i,j \\ i \neq j}} \lambda_{i} \lambda_{j} \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}}^{1/2,\mathsf{H}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathsf{Tx}}^{1/2,\mathsf{H}} \boldsymbol{A}_{k}^{\mathsf{H}} \boldsymbol{R}_{\mathsf{Tx}}^{1/2} \right) + \beta^{2} \sum_{i} \lambda_{i} \lambda_{j} \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k} \right) \right|^{2} + \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k}^{\mathsf{H}} \right) = \beta^{2} \sum_{i,j} \lambda_{i} \lambda_{j} \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k}^{\mathsf{H}} \right) + \beta^{2} \sum_{i} \lambda_{i}^{2} \left| \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k} \right) \right|^{2} = \beta^{2} \left(\operatorname{tr}^{2} \left(\boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\mathsf{H}} \boldsymbol{R}_{\mathsf{RIS}} \boldsymbol{\Phi} \right) \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k}^{\mathsf{H}} \right) + \operatorname{tr} \left(\boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\mathsf{H}} \boldsymbol{R}_{\mathsf{RIS}} \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\mathsf{H}} \boldsymbol{R}_{\mathsf{RIS}} \boldsymbol{\Phi} \right) \left| \operatorname{tr} \left(\boldsymbol{R}_{\mathsf{Tx}} \boldsymbol{A}_{k} \right) \right|^{2} \right)$$
(26)

where (*a*) again uses Lemma 2 of [44]. Now using (23)-(26), Lemma 1 and Lemma 2 of [44], all the terms in (22) can be calculated in closed-form.

Using the expression of C_k from (7) and with some calculations, we get

$$\mathbb{E}\left[\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{A}_{k}\boldsymbol{h}_{k}\boldsymbol{h}_{k}^{\mathrm{H}}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{h}_{k}\right] = \operatorname{tr}\left(\boldsymbol{C}_{k}\boldsymbol{A}_{k}\boldsymbol{C}_{k}\boldsymbol{A}_{k}^{\mathrm{H}}\right) + \left|\operatorname{tr}(\boldsymbol{C}_{k}\boldsymbol{A}_{k})\right|^{2} + \beta^{2}\operatorname{tr}\left(\boldsymbol{Q}\boldsymbol{R}_{\mathrm{RIS}}\right) \times \left(\left|\operatorname{tr}(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k})\right|^{2} + \operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}^{\mathrm{H}}\right)\right) + 2\beta\operatorname{Re}\left\{\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}^{\mathrm{H}}\right)\operatorname{tr}\left(\boldsymbol{Q}\bar{\boldsymbol{T}}\boldsymbol{A}_{k}\bar{\boldsymbol{T}}^{\mathrm{H}}\right)\right\} + \beta\operatorname{tr}\left(\boldsymbol{Q}\bar{\boldsymbol{T}}\boldsymbol{A}_{k}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}\bar{\boldsymbol{T}}^{\mathrm{H}}\right) + \beta\operatorname{tr}\left(\boldsymbol{Q}\bar{\boldsymbol{T}}\boldsymbol{A}_{k}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}\bar{\boldsymbol{T}}^{\mathrm{H}}\right)$$

$$(27)$$

where $\boldsymbol{Q} = \boldsymbol{\varPhi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\varPhi}^{\mathrm{H}} \boldsymbol{R}_{\mathrm{RIS}} \boldsymbol{\varPhi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\varPhi}^{\mathrm{H}}.$

C. Computation of the gradient

From (7), we get

$$\boldsymbol{c}_{k}^{\mathrm{H}}\boldsymbol{a}_{k} = \mathrm{tr}\left(\boldsymbol{C}_{k}\boldsymbol{A}_{k}\right) = \mathrm{tr}(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{k}) + \mathrm{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\,\mathrm{tr}(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}) + \mathrm{tr}\left(\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},k}\,\boldsymbol{\varPhi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{k}\right)$$
(28)

where $\Gamma_k = \beta \left(\mathbf{R}_{\text{RIS}} \odot \mathbf{C}_{\mathbf{r},k}^{\text{T}} \right)$ and $\mathbf{V} = \phi \phi^{\text{H}}$. Both Γ_k and \mathbf{V} Denoting the constant terms which are independent of ϕ as are Hermitian matrices. The above expression can be further ℓ_1 , we get simplified as

$$\boldsymbol{c}_{k}^{\mathrm{H}}\boldsymbol{a}_{k} = \operatorname{tr}(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{k}) + \operatorname{tr}\left(\boldsymbol{\overline{T}}\boldsymbol{A}_{k}\boldsymbol{\overline{T}}^{\mathrm{H}}\left(\boldsymbol{C}_{\boldsymbol{r},k}\odot\boldsymbol{\phi}\boldsymbol{\phi}^{\mathrm{H}}\right)\right) \\ + \operatorname{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\operatorname{tr}(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}) \\ \stackrel{(a)}{=}\operatorname{tr}(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{k}) + \operatorname{tr}\left(\left(\left(\boldsymbol{\overline{T}}\boldsymbol{A}_{k}\boldsymbol{\overline{T}}^{\mathrm{H}}\right)\odot\boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}}\right)\boldsymbol{V}\right) \\ + \operatorname{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\operatorname{tr}(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{k}) \\ = \operatorname{tr}(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{k}) + \operatorname{tr}(\boldsymbol{\mathcal{D}}_{k}\boldsymbol{V})$$
(29)

where (a) follows from Lemma 1 in [11] and \mathcal{D}_k is given by

$$\boldsymbol{\mathcal{D}}_{k} = \left(\overline{\boldsymbol{T}} \boldsymbol{A}_{k} \overline{\boldsymbol{T}}^{\mathrm{H}} \right) \odot \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}} + \operatorname{tr}(\boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k}) \boldsymbol{\Gamma}_{k}.$$
(30)

Similarly, we get

$$|\boldsymbol{c}_{k}^{\mathrm{H}}\boldsymbol{a}_{k}|^{2} = |\mathrm{tr}(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{k})|^{2} + \mathrm{tr}(\boldsymbol{\mathcal{D}}_{k}\boldsymbol{V}) \operatorname{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{k}^{\mathrm{H}}\right) + |\mathrm{tr}(\boldsymbol{\mathcal{D}}_{k}\boldsymbol{V})|^{2} + \mathrm{tr}\left(\boldsymbol{\mathcal{D}}_{k}^{\mathrm{H}}\boldsymbol{V}\right) \operatorname{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{k}\right)$$
(31)

$$\boldsymbol{a}_{j}^{\mathrm{H}}\left(\boldsymbol{C}_{j}^{\mathrm{T}}\otimes\boldsymbol{C}_{k}\right)\boldsymbol{a}_{j}=\mathrm{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\boldsymbol{C}_{j}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$
$$+\mathrm{tr}\left(\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\boldsymbol{\Phi}}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\boldsymbol{\Phi}}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}\boldsymbol{C}_{j}\boldsymbol{A}_{j}^{\mathrm{H}}\right) \quad (32)$$
$$+\mathrm{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\mathrm{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\boldsymbol{C}_{j}\boldsymbol{A}_{j}^{\mathrm{H}}\right).$$

Further expanding the terms,

$$\operatorname{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\boldsymbol{C}_{j}\boldsymbol{A}_{j}^{\mathrm{H}}\right) = \operatorname{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\boldsymbol{C}_{\mathrm{d},j}\boldsymbol{A}_{j}^{\mathrm{H}}\right) \\ + \operatorname{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\varPhi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\right) \\ + \operatorname{tr}(\boldsymbol{\Gamma}_{j}\boldsymbol{V})\operatorname{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$
(33)

$$\operatorname{tr}(\overline{T}^{\mathrm{H}} \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\mathrm{H}} \overline{\boldsymbol{T}} \boldsymbol{A}_{j} \boldsymbol{C}_{j} \boldsymbol{A}_{j}^{\mathrm{H}}) = \operatorname{tr}\left(\overline{T}^{\mathrm{H}} \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\mathrm{H}} \overline{\boldsymbol{T}} \boldsymbol{A}_{j} \boldsymbol{C}_{\mathrm{d},j} \boldsymbol{A}_{j}^{\mathrm{H}}\right) + \operatorname{tr}\left(\overline{T}^{\mathrm{H}} \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\mathrm{H}} \overline{\boldsymbol{T}} \boldsymbol{A}_{j} \overline{T}^{\mathrm{H}} \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},j} \boldsymbol{\Phi}^{\mathrm{H}} \overline{\boldsymbol{T}} \boldsymbol{A}_{j}^{\mathrm{H}}\right) + \operatorname{tr}(\boldsymbol{\Gamma}_{j} \boldsymbol{V}) \operatorname{tr}\left(\overline{T}^{\mathrm{H}} \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\Phi}^{\mathrm{H}} \overline{\boldsymbol{T}} \boldsymbol{A}_{j} \boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{j}^{\mathrm{H}}\right)$$
(34)

$$\operatorname{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\operatorname{tr}(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\boldsymbol{C}_{j}\boldsymbol{A}_{j}^{\mathrm{H}}) = \operatorname{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\boldsymbol{C}_{\mathrm{d},j}\boldsymbol{A}_{j}^{\mathrm{H}}\right) + \operatorname{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\varPhi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\right) + \operatorname{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\operatorname{tr}(\boldsymbol{\Gamma}_{j}\boldsymbol{V})\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}^{\mathrm{H}}\right).$$
(35)

$$a_{j}^{\mathrm{H}}\left(\boldsymbol{C}_{j}^{\mathrm{T}}\otimes\boldsymbol{C}_{k}\right)a_{j}=\mathrm{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\Phi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$+\mathrm{tr}(\boldsymbol{\Gamma}_{j}\boldsymbol{V})\mathrm{tr}\left(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$+\mathrm{tr}\left(\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\Phi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}\boldsymbol{C}_{\mathrm{d},j}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$+\mathrm{tr}\left(\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\Phi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\Phi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$+\mathrm{tr}(\boldsymbol{\Gamma}_{j}\boldsymbol{V})\mathrm{tr}\left(\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\Phi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$+\mathrm{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\mathrm{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\boldsymbol{C}_{\mathrm{d},j}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$+\mathrm{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\mathrm{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\Phi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$+\mathrm{tr}(\boldsymbol{\Gamma}_{k}\boldsymbol{V})\mathrm{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\Phi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$(36)$$

where ℓ_1 consists of the terms which are independent of ϕ . The terms can be further simplified as

$$\operatorname{tr}(\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\varPhi}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\varPhi}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}) = \operatorname{tr}\left(\left(\left(\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\boldsymbol{C}_{\mathrm{d},k}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\right)\odot\boldsymbol{C}_{\boldsymbol{r},j}^{\mathrm{T}}\right)\boldsymbol{\phi}\boldsymbol{\phi}^{\mathrm{H}}\right).$$
(37)

Similarly, we have

$$\operatorname{tr}\left(\overline{T}^{\mathrm{H}} \boldsymbol{\varPhi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\varPhi}^{\mathrm{H}} \overline{T} \boldsymbol{A}_{j} \boldsymbol{C}_{\mathrm{d},j} \boldsymbol{A}_{j}^{\mathrm{H}}\right)$$
$$= \operatorname{tr}\left(\left(\left(\overline{T} \boldsymbol{A}_{j} \boldsymbol{C}_{\mathrm{d},j} \boldsymbol{A}_{j}^{\mathrm{H}} \overline{T}^{\mathrm{H}}\right) \odot \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}}\right) \boldsymbol{\phi} \boldsymbol{\phi}^{\mathrm{H}}\right) \quad (38)$$
$$\operatorname{tr}\left(\overline{T}^{\mathrm{H}} \boldsymbol{\varPhi} \boldsymbol{C}_{\boldsymbol{r},k} \boldsymbol{\varPhi}^{\mathrm{H}} \overline{T} \boldsymbol{A}_{j} \boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{j}^{\mathrm{H}}\right)$$

$$= \operatorname{tr} \left(\left(\left(\overline{T} A_j R_{\mathrm{Tx}} A_j^{\mathrm{H}} \overline{T}^{\mathrm{H}} \right) \odot C_{r,k}^{\mathrm{T}} \right) \phi \phi^{\mathrm{H}} \right) \quad (39)$$

$$\operatorname{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\boldsymbol{\boldsymbol{\Phi}}\boldsymbol{C}_{\boldsymbol{r},j}\boldsymbol{\boldsymbol{\Phi}}^{\mathrm{H}}\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\right) = \operatorname{tr}\left(\left(\left(\overline{\boldsymbol{T}}\boldsymbol{A}_{j}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{Tx}}\boldsymbol{A}_{j}\overline{\boldsymbol{T}}^{\mathrm{H}}\right)\odot\boldsymbol{C}_{\boldsymbol{r},j}^{\mathrm{T}}\right)\boldsymbol{\phi}\boldsymbol{\phi}^{\mathrm{H}}\right). \quad (40)$$

Now, the first term in (19) can be simplified using (29) as follows

$$\sum_{k=1}^{K} 2\left(\sqrt{1+\bar{\lambda}_{k}}\right) \operatorname{Re}\left\{\bar{\chi}_{k}^{*}\boldsymbol{c}_{k}^{\mathrm{H}}\bar{\boldsymbol{a}}_{k}\right\}$$
$$= \sum_{k=1}^{K} 2\left(\sqrt{1+\bar{\lambda}_{k}}\right) \operatorname{Re}\left\{\bar{\chi}_{k}^{*}\operatorname{tr}\left(\bar{\boldsymbol{\mathcal{D}}}_{k}\boldsymbol{V}\right)\right\} + \ell_{2}$$
$$= \boldsymbol{\phi}^{\mathrm{H}}\boldsymbol{\mathcal{X}}_{1}\boldsymbol{\phi} + \ell_{2}$$
(41)

where ℓ_2 consists of the terms which are independent of ϕ , and $\bar{\mathcal{D}}_k$ and \mathcal{X}_1 are given by

$$\bar{\boldsymbol{\mathcal{D}}}_{k} = \left(\overline{\boldsymbol{T}}\bar{\boldsymbol{A}}_{k}\overline{\boldsymbol{T}}^{\mathrm{H}}\right) \odot \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}} + \mathrm{tr}\left(\boldsymbol{R}_{\mathrm{Tx}}\bar{\boldsymbol{A}}_{k}\right)\boldsymbol{\Gamma}_{k} \qquad (42)$$

$$\boldsymbol{\mathcal{X}}_{1} = \sum_{k=1}^{K} \left(\sqrt{1 + \bar{\lambda}_{k}} \right) \left(\bar{\chi}_{k}^{*} \bar{\boldsymbol{\mathcal{D}}}_{k} + \bar{\chi}_{k} \bar{\boldsymbol{\mathcal{D}}}_{k}^{\mathrm{H}} \right).$$
(43)

The second term in (19) can be simplified using (31).

$$\sum_{k=1}^{K} \left| \bar{\chi}_{k} \right|^{2} \left| \boldsymbol{c}_{k}^{\mathrm{H}} \bar{\boldsymbol{a}}_{k} \right|^{2} = \sum_{k=1}^{K} \left| \boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{2,k} \boldsymbol{\phi} \right|^{2} + \boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{3} \boldsymbol{\phi} + \ell_{3} \quad (44)$$

where ℓ_3 denotes the constant terms which are irrelevant for the optimisation, and

$$\begin{aligned} \boldsymbol{\mathcal{X}}_{2,k} &= |\bar{\chi}_{k}| \, \bar{\boldsymbol{\mathcal{D}}}_{k} \end{aligned} \tag{45} \\ \boldsymbol{\mathcal{X}}_{3} &= \sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \left(\operatorname{tr} \left(\boldsymbol{C}_{\mathrm{d},k} \bar{\boldsymbol{A}}_{k}^{\mathrm{H}} \right) \bar{\boldsymbol{\mathcal{D}}}_{k} + \operatorname{tr} \left(\boldsymbol{C}_{\mathrm{d},k} \bar{\boldsymbol{A}}_{k} \right) \bar{\boldsymbol{\mathcal{D}}}_{k}^{\mathrm{H}} \right). \end{aligned}$$

The third term in (19) can be simplified using (36) - (40).

$$\sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \sum_{j=1}^{K} \bar{a}_{j}^{\mathrm{H}} \left(\boldsymbol{C}_{j}^{\mathrm{T}} \otimes \boldsymbol{C}_{k} \right) \bar{a}_{j}$$

$$= \sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{4,k} \boldsymbol{\phi} + \sum_{k=1}^{K} \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\Gamma}_{k} \boldsymbol{\phi} \right) \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{5,k} \boldsymbol{\phi} \right)$$

$$+ \left(\boldsymbol{\phi}^{\mathrm{H}} \left(\sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \boldsymbol{\Gamma}_{k} \right) \boldsymbol{\phi} \right) \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{6} \boldsymbol{\phi} \right)$$

$$+ \sum_{j=1}^{K} \operatorname{tr} \left(\boldsymbol{S}_{j}^{\mathrm{H}} \boldsymbol{\varPhi} \left(\sum_{k=1}^{K} |\bar{\chi}_{k}|^{2} \boldsymbol{C}_{\boldsymbol{r},k} \right) \boldsymbol{\varPhi}^{\mathrm{H}} \boldsymbol{S}_{j} \boldsymbol{\varPhi} \boldsymbol{C}_{\boldsymbol{r},j} \boldsymbol{\varPhi}^{\mathrm{H}} \right) + \ell_{4}$$

$$(47)$$

where ℓ_4 denotes the constant terms, which are independent of ϕ , and

$$\begin{aligned} \boldsymbol{\mathcal{X}}_{4,k} &= \sum_{j=1}^{K} \left(\overline{\boldsymbol{T}} \bar{\boldsymbol{A}}_{j}^{\mathrm{H}} \boldsymbol{C}_{\mathrm{d},k} \bar{\boldsymbol{A}}_{j} \overline{\boldsymbol{T}}^{\mathrm{H}} \right) \odot \boldsymbol{C}_{\boldsymbol{r},j}^{\mathrm{T}} \\ &+ \sum_{j=1}^{K} \operatorname{tr} \left(\boldsymbol{C}_{\mathrm{d},k} \bar{\boldsymbol{A}}_{j} \boldsymbol{R}_{\mathrm{Tx}} \bar{\boldsymbol{A}}_{j}^{\mathrm{H}} \right) \boldsymbol{\Gamma}_{j} \\ &+ \sum_{j=1}^{K} \left(\overline{\boldsymbol{T}} \bar{\boldsymbol{A}}_{j} \boldsymbol{C}_{\mathrm{d},j} \bar{\boldsymbol{A}}_{j}^{\mathrm{H}} \overline{\boldsymbol{T}}^{\mathrm{H}} \right) \odot \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}} \\ &+ \sum_{j=1}^{K} \operatorname{tr} \left(\boldsymbol{R}_{\mathrm{Tx}} \bar{\boldsymbol{A}}_{j} \boldsymbol{C}_{\mathrm{d},j} \bar{\boldsymbol{A}}_{j}^{\mathrm{H}} \right) \boldsymbol{\Gamma}_{k} \end{aligned}$$
(48)

$$\boldsymbol{\mathcal{X}}_{5,j} = \left(\overline{\boldsymbol{T}} \bar{\boldsymbol{A}}_{j} \boldsymbol{R}_{\mathrm{Tx}} \bar{\boldsymbol{A}}_{j}^{\mathrm{H}} \overline{\boldsymbol{T}}^{\mathrm{H}} \right) \odot \left(\sum_{k=1}^{K} \left| \bar{\boldsymbol{\chi}}_{k} \right|^{2} \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}} \right)$$
(49)

$$\mathcal{X}_{6} = \sum_{j=1}^{K} \left(\overline{T} \overline{A}_{j}^{\mathrm{H}} R_{\mathrm{Tx}} \overline{A}_{j} \overline{T}^{\mathrm{H}} \right) \odot \boldsymbol{C}_{\boldsymbol{r},j}^{\mathrm{T}} + \sum_{j=1}^{K} \operatorname{tr} \left(\boldsymbol{R}_{\mathrm{Tx}} \overline{A}_{j} \boldsymbol{R}_{\mathrm{Tx}} \overline{A}_{j}^{\mathrm{H}} \right) \boldsymbol{\Gamma}_{j}$$
(50)

$$\boldsymbol{S}_{j} = \overline{\boldsymbol{T}} \boldsymbol{A}_{j} \overline{\boldsymbol{T}}^{\mathrm{H}}.$$
 (51)

Next, $\boldsymbol{a}_{k}^{\mathrm{H}} \boldsymbol{J}_{k} \boldsymbol{a}_{k}$ can be written as

$$\boldsymbol{a}_{k}^{\mathrm{H}}\boldsymbol{J}_{k}\boldsymbol{a}_{k} = \mathrm{tr}\left(\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\Phi}^{\mathrm{H}}\boldsymbol{M}_{k}\boldsymbol{\Phi}\boldsymbol{C}_{\boldsymbol{r},k}\boldsymbol{\Phi}^{\mathrm{H}}\boldsymbol{R}_{\mathrm{RIS}}\boldsymbol{\Phi}\right)$$
 (52)

where

$$\begin{split} \boldsymbol{M}_{k} &= \beta^{2} \left(\left| \operatorname{tr}(\boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k}) \right|^{2} + \operatorname{tr} \left(\boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k}^{\mathrm{H}} \right) \right) \boldsymbol{R}_{\mathrm{RIS}} \\ &+ \beta \operatorname{tr} \left(\boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k}^{\mathrm{H}} \right) \bar{\boldsymbol{T}} \boldsymbol{A}_{k} \bar{\boldsymbol{T}}^{\mathrm{H}} + \beta \operatorname{tr} (\boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k}) \bar{\boldsymbol{T}} \boldsymbol{A}_{k}^{\mathrm{H}} \bar{\boldsymbol{T}}^{\mathrm{H}} \\ &+ \beta \bar{\boldsymbol{T}} \boldsymbol{A}_{k} \boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k}^{\mathrm{H}} \bar{\boldsymbol{T}}^{\mathrm{H}} + \beta \bar{\boldsymbol{T}} \boldsymbol{A}_{k}^{\mathrm{H}} \boldsymbol{R}_{\mathrm{Tx}} \boldsymbol{A}_{k} \bar{\boldsymbol{T}}^{\mathrm{H}}. \end{split}$$

Finally, ignoring all the constant terms, (19) can be written as a function of ϕ as

$$f(\boldsymbol{\phi}) = \boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{G}} \boldsymbol{\phi} - \sum_{k=1}^{K} \left| \boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{2,k} \boldsymbol{\phi} \right|^{2} - \sum_{k=1}^{K} \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\Gamma}_{k} \boldsymbol{\phi} \right) \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{5,k} \boldsymbol{\phi} \right)$$
$$- \left(\boldsymbol{\phi}^{\mathrm{H}} \left(\sum_{k=1}^{K} \left| \bar{\chi}_{k} \right|^{2} \boldsymbol{\Gamma}_{k} \right) \boldsymbol{\phi} \right) \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{6} \boldsymbol{\phi} \right)$$
$$- \sum_{j=1}^{K} \operatorname{tr} \left(\boldsymbol{S}_{j}^{\mathrm{H}} \boldsymbol{\Phi} \left(\sum_{k=1}^{K} \left| \bar{\chi}_{k} \right|^{2} \boldsymbol{C}_{r,k} \right) \boldsymbol{\Phi}^{\mathrm{H}} \boldsymbol{S}_{j} \boldsymbol{\Phi} \boldsymbol{C}_{r,j} \boldsymbol{\Phi}^{\mathrm{H}} \right)$$
$$- \sum_{k=1}^{K} \left| \bar{\chi}_{k} \right|^{2} \operatorname{tr} \left(\boldsymbol{C}_{r,k} \boldsymbol{\Phi}^{\mathrm{H}} \boldsymbol{M}_{k} \boldsymbol{\Phi} \boldsymbol{C}_{r,k} \boldsymbol{\Phi}^{\mathrm{H}} \boldsymbol{R}_{\mathrm{RIS}} \boldsymbol{\Phi} \right)$$
(53)

where \mathcal{G} is given by

$$\boldsymbol{\mathcal{G}} = \boldsymbol{\mathcal{X}}_1 - \boldsymbol{\mathcal{X}}_3 - \sum_{k=1}^K |\bar{\boldsymbol{\chi}}_k|^2 \, \boldsymbol{\mathcal{X}}_{4,k}. \tag{54}$$

The gradient of $f(\phi)$ in (53) w.r.t. ϕ^* is given by Δ , which can be expressed as follows

$$\begin{split} \boldsymbol{\Delta} &= \boldsymbol{\mathcal{G}}\boldsymbol{\phi} - \sum_{k=1}^{K} \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{2,k} \boldsymbol{\phi} \right) \boldsymbol{\mathcal{X}}_{2,k}^{\mathrm{H}} \boldsymbol{\phi} - \sum_{k=1}^{K} \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{2,k}^{\mathrm{H}} \boldsymbol{\phi} \right) \boldsymbol{\mathcal{X}}_{2,k} \boldsymbol{\phi} \\ &- \sum_{k=1}^{K} \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\Gamma}_{k} \boldsymbol{\phi} \right) \boldsymbol{\mathcal{X}}_{5,k} \boldsymbol{\phi} - \sum_{k=1}^{K} \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{5,k} \boldsymbol{\phi} \right) \boldsymbol{\Gamma}_{k} \boldsymbol{\phi} \\ &- \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{Y}_{1} \boldsymbol{\phi} \right) \boldsymbol{\mathcal{X}}_{6} \boldsymbol{\phi} - \left(\boldsymbol{\phi}^{\mathrm{H}} \boldsymbol{\mathcal{X}}_{6} \boldsymbol{\phi} \right) \boldsymbol{Y}_{1} \boldsymbol{\phi} \\ &- \sum_{k=1}^{K} \left(\boldsymbol{Y}_{3,k} \odot \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}} \right) \boldsymbol{\phi} - \sum_{k=1}^{K} \left(\boldsymbol{Y}_{4,k} \odot \boldsymbol{Y}_{2}^{\mathrm{T}} \right) \boldsymbol{\phi} \\ &- \sum_{k=1}^{K} \left| \bar{\boldsymbol{\chi}}_{k} \right|^{2} \left(\boldsymbol{Y}_{5,k} \odot \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}} \right) \boldsymbol{\phi} - \sum_{k=1}^{K} \left| \bar{\boldsymbol{\chi}}_{k} \right|^{2} \left(\boldsymbol{Y}_{5,k}^{\mathrm{H}} \odot \boldsymbol{C}_{\boldsymbol{r},k}^{\mathrm{T}} \right) \boldsymbol{\phi} \end{split}$$
(55)

where

$$\begin{split} \boldsymbol{Y}_1 &= \sum_{k=1}^K |\bar{\chi}_k|^2 \, \boldsymbol{\Gamma}_k, \boldsymbol{Y}_2 = \sum_{k=1}^K |\bar{\chi}_k|^2 \, \boldsymbol{C}_{\boldsymbol{r},k}, \\ \boldsymbol{Y}_{3,k} &= \boldsymbol{S}_k^{\mathrm{H}} \boldsymbol{\Phi} \boldsymbol{Y}_2 \, \boldsymbol{\Phi}^{\mathrm{H}} \boldsymbol{S}_k, \boldsymbol{Y}_{4,k} = \boldsymbol{S}_k \, \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \, \boldsymbol{\Phi}^{\mathrm{H}} \boldsymbol{S}_k^{\mathrm{H}}, \\ \boldsymbol{Y}_{5,k} &= \boldsymbol{R}_{\mathrm{RIS}} \, \boldsymbol{\Phi} \boldsymbol{C}_{\boldsymbol{r},k} \, \boldsymbol{\Phi}^{\mathrm{H}} \boldsymbol{M}_k. \end{split}$$

References

- L. Lu, G. Y. Li, A. L. Swindlehurst, A. Ashikhmin, and R. Zhang, "An overview of massive MIMO: Benefits and challenges," *IEEE journal of selected topics in signal processing*, vol. 8, no. 5, pp. 742–758, 2014.
- [2] Q. Wu and R. Zhang, "Towards smart and reconfigurable environment: Intelligent reflecting surface aided wireless network," *IEEE Communications Magazine*, vol. 58, no. 1, pp. 106–112, 2019.

- [3] C. Huang, A. Zappone, G. C. Alexandropoulos, M. Debbah, and C. Yuen, "Reconfigurable intelligent surfaces for energy efficiency in wireless communication," *IEEE Transactions on Wireless Communications*, vol. 18, no. 8, pp. 4157–4170, 2019.
- [4] M. D. Renzo, M. Debbah, D.-T. Phan-Huy, A. Zappone, M.-S. Alouini, C. Yuen, V. Sciancalepore, G. C. Alexandropoulos, J. Hoydis, H. Gacanin *et al.*, "Smart radio environments empowered by reconfigurable AI meta-surfaces: An idea whose time has come," *EURASIP Journal on Wireless Communications and Networking*, vol. 2019, no. 1, pp. 1–20, 2019.
- [5] Q. Wu and R. Zhang, "Intelligent reflecting surface enhanced wireless network via joint active and passive beamforming," *IEEE Transactions* on Wireless Communications, vol. 18, no. 11, pp. 5394–5409, 2019.
- [6] H. Guo, Y.-C. Liang, J. Chen, and E. G. Larsson, "Weighted sumrate maximization for reconfigurable intelligent surface aided wireless networks," *IEEE Transactions on Wireless Communications*, vol. 19, no. 5, pp. 3064–3076, 2020.
- [7] S. Zhang and R. Zhang, "Capacity characterization for intelligent reflecting surface aided MIMO communication," *IEEE Journal on Selected Areas in Communications*, vol. 38, no. 8, pp. 1823–1838, 2020.
- [8] Q. Wu and R. Zhang, "Intelligent reflecting surface enhanced wireless network: Joint active and passive beamforming design," in 2018 IEEE Global Communications Conference (GLOBECOM). IEEE, 2018, pp. 1–6.
- [9] C. Pan, H. Ren, K. Wang, W. Xu, M. Elkashlan, A. Nallanathan, and L. Hanzo, "Multicell MIMO communications relying on intelligent reflecting surfaces," *IEEE Transactions on Wireless Communications*, vol. 19, no. 8, pp. 5218–5233, 2020.
- [10] D. Semmler, M. Joham, and W. Utschick, "Linear precoding in the intelligent reflecting surface assisted MIMO broadcast channel," in 2022 IEEE 23rd International Workshop on Signal Processing Advances in Wireless Communication (SPAWC). IEEE, 2022, pp. 1–5.
- [11] S. Syed, D. Semmler, D. B. Amor, M. Joham, and W. Utschick, "Design of a single-user RIS-aided MISO system based on statistical channel knowledge," 2023.
- [12] X. Hu, J. Wang, and C. Zhong, "Statistical CSI based design for intelligent reflecting surface assisted MISO systems," *Science China Information Sciences*, vol. 63, no. 12, pp. 1–10, 2020.
- [13] M.-M. Zhao, Q. Wu, M.-J. Zhao, and R. Zhang, "Intelligent reflecting surface enhanced wireless networks: Two-timescale beamforming optimization," *IEEE Transactions on Wireless Communications*, vol. 20, no. 1, pp. 2–17, 2020.
- [14] J. Dang, Z. Zhang, and L. Wu, "Joint beamforming for intelligent reflecting surface aided wireless communication using statistical CSI," *China Communications*, vol. 17, no. 8, pp. 147–157, 2020.
- [15] X. Gan, C. Zhong, C. Huang, and Z. Zhang, "RIS-assisted multi-user MISO communications exploiting statistical CSI," *IEEE Transactions* on Communications, vol. 69, no. 10, pp. 6781–6792, 2021.
- [16] H. Zhang, S. Ma, Z. Shi, X. Zhao, and G. Yang, "Sum-rate maximization of RIS-aided multi-user MIMO systems with statistical CSI," *IEEE Transactions on Wireless Communications*, 2022.
- [17] T. Noh and J. Choi, "Cell-free MIMO systems powered by intelligent reflecting surfaces," *IEEE Communications Letters*, vol. 26, no. 5, pp. 1076–1080, 2022.
- [18] K. Shen and W. Yu, "Fractional programming for communication systems—part I: Power control and beamforming," *IEEE Transactions* on Signal Processing, vol. 66, no. 10, pp. 2616–2630, 2018.
- [19] —, "Fractional programming for communication systems—part II: Uplink scheduling via matching," *IEEE Transactions on Signal Processing*, vol. 66, no. 10, pp. 2631–2644, 2018.
- [20] Y. Sun, P. Babu, and D. P. Palomar, "Majorization-minimization algorithms in signal processing, communications, and machine learning," *IEEE Transactions on Signal Processing*, vol. 65, no. 3, pp. 794–816, 2016.
- [21] K. Alhujaili, V. Monga, and M. Rangaswamy, "Transmit MIMO radar beampattern design via optimization on the complex circle manifold," *IEEE Transactions on Signal Processing*, vol. 67, no. 13, pp. 3561–3575, 2019.
- [22] M. Joham, H. Gao, and W. Utschick, "Estimation of channels in systems with intelligent reflecting surfaces," in *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing* (ICASSP). IEEE, 2022, pp. 5368–5372.
- [23] J.-P. Kermoal, L. Schumacher, K. I. Pedersen, P. E. Mogensen, and F. Frederiksen, "A stochastic MIMO radio channel model with experi-

mental validation," *IEEE Journal on selected areas in Communications*, vol. 20, no. 6, pp. 1211–1226, 2002.

- [24] A. Abrardo, D. Dardari, and M. Di Renzo, "Intelligent reflecting surfaces: Sum-rate optimization based on statistical CSI," arXiv preprint arXiv:2012.10679, 2020.
- [25] M. Medard, "The effect upon channel capacity in wireless communications of perfect and imperfect knowledge of the channel," *IEEE Transactions on Information Theory*, vol. 46, no. 3, pp. 933–946, 2000.
- [26] Z. Wang, L. Liu, S. Zhang, and S. Cui, "Massive mimo communication with intelligent reflecting surface," *IEEE Transactions on Wireless Communications*, vol. 22, no. 4, pp. 2566–2582, 2022.
- [27] D. B. Amor, M. Joham, and W. Utschick, "Bilinear precoding for FDD massive MIMO system with imperfect covariance matrices," WSA 2020; 24th International ITG Workshop on Smart Antennas, pp. 1–6, 2020.
- [28] D. Neumann, T. Wiese, M. Joham, and W. Utschick, "A generalized matched filter framework for massive MIMO systems," *ArXiv E-Print*, 2017.
- [29] A. Liu, V. K. Lau, and M.-J. Zhao, "Online successive convex approximation for two-stage stochastic nonconvex optimization," *IEEE Transactions on Signal Processing*, vol. 66, no. 22, pp. 5941–5955, 2018.
- [30] D. Neumann, T. Wiese, M. Joham, and W. Utschick, "A generalized matched filter framework for massive MIMO systems," *ArXiv E-Print*, 2017.
- [31] Y. Xu and W. Yin, "A block coordinate descent method for regularized multiconvex optimization with applications to nonnegative tensor factorization and completion," *SIAM Journal on imaging sciences*, vol. 6, no. 3, pp. 1758–1789, 2013.
- [32] M. Razaviyayn, M. Hong, and Z.-Q. Luo, "A unified convergence analysis of block successive minimization methods for nonsmooth optimization," *SIAM Journal on Optimization*, vol. 23, no. 2, pp. 1126– 1153, 2013.
- [33] M. Joham, K. Kusume, M. H. Gzara, W. Utschick, and J. A. Nossek, "Transmit wiener filter for the downlink of TDDDS-CDMA systems," in *IEEE Seventh International Symposium on Spread Spectrum Techniques* and Applications,, vol. 1. IEEE, 2002, pp. 9–13.
- [34] S. S. Christensen, R. Agarwal, E. De Carvalho, and J. M. Cioffi, "Weighted sum-rate maximization using weighted mmse for mimo-bc beamforming design," *IEEE Transactions on Wireless Communications*, vol. 7, no. 12, pp. 4792–4799, 2008.
- [35] X. Zhao, S. Lu, Q. Shi, and Z.-Q. Luo, "Rethinking WMMSE: Can its complexity scale linearly with the number of BS antennas?" *IEEE Transactions on Signal Processing*, vol. 71, pp. 433–446, 2023.
- [36] D. P. Bertsekas, "Nonlinear programming," Journal of the Operational Research Society, vol. 48, no. 3, pp. 334–334, 1997.
- [37] D. Neumann, T. Wiese, M. Joham, and W. Utschick, "A bilinear equalizer for massive MIMO systems," *IEEE Transactions on Signal Processing*, vol. 66, no. 14, pp. 3740–3751, 2018.
- [38] E. Telatar, "Capacity of multi-antenna gaussian channels," *European transactions on telecommunications*, vol. 10, no. 6, pp. 585–595, 1999.
- [39] Q. Shi, M. Razaviyayn, Z.-Q. Luo, and C. He, "An iteratively weighted MMSE approach to distributed sum-utility maximization for a MIMO interfering broadcast channel," *IEEE Transactions on Signal Processing*, vol. 59, no. 9, pp. 4331–4340, 2011.
- [40] Z. Zhang, Z. Zhao, K. Shen, D. P. Palomar, and W. Yu, "Discerning and Enhancing the Weighted Sum-Rate Maximization Algorithms in Communications," arXiv preprint arXiv:2311.04546, 2023.
- [41] T. ETSI, "Study on channel model for frequencies from 0.5 to 100 GHz," 138 901 v16.1.0, 5G, 2020.
- [42] D. B. Amor, M. Joham, and W. Utschick, "Rate splitting in fdd massive mimo systems based on the second order statistics of transmission channels," *IEEE Journal on Selected Areas in Communications*, vol. 41, no. 5, pp. 1351–1365, 2023.
- [43] E. Björnson, L. Sanguinetti, and M. Debbah, "Massive mimo with imperfect channel covariance information," in 2016 50th Asilomar Conference on Signals, Systems and Computers. IEEE, 2016, pp. 974– 978.
- [44] E. Björnson, M. Matthaiou, and M. Debbah, "Massive MIMO with nonideal arbitrary arrays: Hardware scaling laws and circuit-aware design," *IEEE Transactions on Wireless Communications*, vol. 14, no. 8, pp. 4353–4368, 2015.
- [45] J. Brewer, "Kronecker products and matrix calculus in system theory," *IEEE Transactions on circuits and systems*, vol. 25, no. 9, pp. 772–781, 1978.