

Global controllability with a single local actuator

S. G. Schirmer,^{1,*} I. C. H. Pullen,¹ and P. J. Pemberton-Ross¹

¹*Dept of Applied Maths and Theoretical Physics,
University of Cambridge, Wilberforce Rd, Cambridge, CB3 0WA, UK.*

(Dated: June 21, 2024)

We show that an N -dimensional bilinear Hamiltonian control system is generally globally (density operator) controllable with a *single* actuator whose influence is local and limited to modulating a single transition, for instance, provided only that there are fixed (uncontrollable) couplings so that the system is not decomposable into non-interacting subsystems and there are no dynamical symmetries restricting the dynamics of a system to a subgroup of the unitary group $\mathfrak{SU}(N)$. The results are applied to spin chains and examples of constructive control with a single binary switch actuator are given.

I. INTRODUCTION

The ability to control the dynamics of quantum systems is a long established objective in areas as diverse as molecular chemistry and quantum computing among others. Control in practice comprises various related tasks such as transforming a system from a given initial state to a desired target state, implementing a desired unitary operator, or optimising the expectation value of selected variable. The manner in which control is effected is also variable depending on the system but a common approach for quantum systems is the application of external electromagnetic fields. In the diabatic control regime these can drive transitions between different states of the system, and control can be achieved by adjusting the amplitude and phase of the field(s) as a function of time in a way that maximizes constructive interference of various excitation pathways that lead to a desired outcome while maximizing destructive interference for all others.

Although the ultimate goal of control is usually to find a control field that steers the system in the manner required to achieve the objective, the question of what tasks can be accomplished for a given system with a given set of actuators, is of fundamental interest. A key concept in this regard is that of controllability. A substantial number of papers have been devoted to studying this issue for both classical and quantum systems, establishing various notions of controllability and general algebraic criteria for them and showing that particular types of systems are controllable [1, 2, 3, 4, 5, 6, 7, 8]. On the latter front, it has been shown, for instance, that any system with distinct transition frequencies and a connected transition graph is controllable [9, 10]. For an n -level system this requires at least $n - 1$ transitions with non-zero probabilities. It has also been shown that these requirements can be relaxed in many cases [11], and more recently indirect controllability has been studied [12].

One remaining area of interest is global controllability with a small number of local actuators. A motivation for

this type of scenario could be a chain or array of quantum dots with control electrodes to manipulate the local dynamics of one or a few quantum dots. In the ideal case, one might consider separate control electrodes for each quantum dot, as well as separate electrodes to modulate the interactions between pairs of adjacent quantum dots, as proposed by Kane in [13] and many other quantum computing architectures since. Leaving aside the often considerable challenges of finding optimal control schemes and fighting decoherence, with enough local actuators almost any (Hamiltonian) quantum system is controllable, at least in principle. However, in many cases it is impractical or even impossible to have a large number of individual local actuators such as control electrodes. Rather, one would like to make do with as few local actuators as possible to simplify the engineering design and reduce deleterious effects such as decoherence and crosstalk, for example.

Motivated by this problem we investigate the question of controllability of a finite-dimensional model system with the smallest number of local actuators. We show that provided the system is not decomposable into non-interacting parts, a *single* local actuator is sufficient for controllability of the *entire* system, except in a few cases where the system possesses dynamical symmetries that restrict its evolution to a subgroup of the unitary group, thus ensuring non-controllability. Many systems with some form of fixed interactions connecting its parts such as chains of quantum dots etc with fixed non-zero couplings between adjacent dots satisfy this connectedness requirement, and the disorder present in most realistic systems will all but ensure that there are no special dynamical symmetries to worry about. For these types of systems our controllability analysis suggests that the entire system can be controlled by modulating a single transition with a local actuator. Although the explicit controllability proofs given apply to specific model systems, the same arguments are applicable to many other model systems, suggesting that a large class of systems with fixed couplings may be controllable by modulating only a single transition or some local couplings. We conclude with an explicit example of constructive control with a single binary switch actuator.

*Electronic address: sgs29@cam.ac.uk

II. DEFINITION OF CONTROL PROBLEM

We restrict ourselves here to control problems that can be classified as open-loop Hamiltonian engineering problems and systems subject to Hamiltonian dynamics. Open-loop control engineering means that we aim to design control fields relying only on (presumed) knowledge of the initial state of the system and the dynamic laws governing its evolution in the presence of the control fields, without feedback from measurements. We will furthermore assume the system is finite-dimensional with Hilbert space $\mathcal{H} \simeq \mathbb{C}^N$. The state of the system in this case can be represented by a density operator $\hat{\rho}$, i.e., a positive unit-trace operator acting on \mathcal{H} , and its evolution is governed by the quantum Liouville equation

$$i\hbar \frac{d}{dt} \hat{\rho}(t) = \left[\hat{H}[\mathbf{f}(t)], \hat{\rho}(t) \right] + i\hbar \mathcal{L}_D[\hat{\rho}(t)], \quad (1)$$

where $[A, B] = AB - BA$ is the usual matrix commutator and $\mathcal{L}_D = 0$ for a Hamiltonian control system. The operator $\hat{H}[\mathbf{f}(t)]$ is the total Hamiltonian of the system subject to the control fields $\mathbf{f}(t)$. For control-linear systems we have the perturbative expansion

$$\hat{H}[\mathbf{f}(t)] = \hat{H}_0 + \sum_{m=1}^M f_m(t) \hat{H}_m, \quad (2)$$

where \hat{H}_0 is the internal Hamiltonian of the system and \hat{H}_m , $m > 0$, are the interaction terms. This assumption is generally reasonable as long as the control fields are sufficiently weak compared to, e.g., the relevant intratomic or molecular forces.

Hamiltonian dynamics constrains the evolution of density operators $\rho(t)$ to isospectral flows

$$\hat{\rho}(t) = \hat{U}(t, t_0) \hat{\rho}_0 \hat{U}(t, t_0)^\dagger, \quad (3)$$

since the evolution operator $\hat{U}(t, t_0)$ must satisfy the related Schrodinger equation

$$i\hbar \frac{d}{dt} \hat{U}(t, t_0) = \hat{H}[\mathbf{f}(t)] \hat{U}(t, t_0) \quad (4)$$

and is hence restricted to the unitary group $\mathfrak{U}(N)$. Due to this fundamental restriction it is clear that the maximum degree of state control we can achieve for this system is the ability to interconvert density operators with the same spectrum, which is achieved if we can implement any unitary operator in the special unitary group $\mathfrak{SU}(N)$ of unitary operators with determinant 1 as abelian factors do not affect the isospectral flow. It is also not difficult to show that any proper subgroup of $\mathfrak{SU}(N)$ is not sufficient to interconvert any two generic density operators with the same spectrum.

To properly define the notion of controllability we need some concepts from Lie group / algebra theory. A *Lie algebra* is a vector space over a field endowed with a bilinear composition $[x, y]$ that satisfies the Jacobi identity

$$[[x, y], z] + [[y, z], x] + [[z, x], y] = 0.$$

It is easy to see that the anti-Hermitian matrices iH_0 and iH_1 generate a Lie algebra \mathfrak{L} which must be a subalgebra of the Lie algebra of skew-hermitian matrices $\mathfrak{u}(N)$, and if iH_0 and iH_1 have zero trace, \mathfrak{L} will be a subalgebra of the trace-zero, anti-Hermitian matrices $\mathfrak{su}(N)$, which can be regarded as the tangent space to the Lie group $\mathfrak{SU}(N)$ at the identity via the exponential map $x \in \mathfrak{su}(N) \mapsto \exp(x) \in \mathfrak{SU}(N)$. Therefore, we can argue that if the $i\hat{H}_0$ and $i\hat{H}_1$ —or their trace-zero counterparts $\hat{H}_m = \hat{H}_m - N^{-1} \text{Tr}(\hat{H}_m) I_N$ —generate the entire Lie algebra $\mathfrak{su}(N)$ then we can in principle dynamically generate any matrix $U \in \mathfrak{SU}(N)$. Hence, a system is said to be density matrix controllable or simply *controllable* if the Lie algebra generated by $i\hat{H}_0$ and $i\hat{H}_1$ is $\mathfrak{su}(N)$.

III. CONTROLLABILITY FOR SINGLE LOCAL ACTUATOR

We consider an N -level system with energy levels E_n , $n = 1, \dots, N$, and transition frequencies $\omega_n = E_{n+1} - E_n$ for $n = 1, \dots, N - 1$. Choose a basis such that H_0 is diagonal and let H_1 be an interaction Hamiltonian. In this paper we focus on systems with couplings between adjacent basis states of H_0 only, so that H_1 is tridiagonal with zeros on the diagonal, and we have

$$H_0 = \sum_{n=1}^N E_n |n\rangle\langle n|, \quad (5a)$$

$$H_1 = \sum_{n=1}^{N-1} d_n [|n\rangle\langle n+1| + |n+1\rangle\langle n|]. \quad (5b)$$

It is well known that a system of this type is controllable if $d_n \neq 0$ and H_0 and H_1 have no symplectic or orthogonal symmetries [14]. This model is quite realistic for a control field that simultaneously drives all transitions with certain transition probabilities d_n , as might be expected for an atom or molecule driven by a laser field.

For other systems such as spin chains or arrays of quantum dots, however, it is more realistic to assume fixed couplings between adjacent spins or quantum dots that we can manipulate to some extent, e.g., by applying potentials to local control electrodes. In this case our drift Hamiltonian is more realistically modelled as

$$A_0 = H_0 + H_1 \quad (6)$$

with H_0 and H_1 as in Eq. (5), and a local actuator modulating the coupling between states $|r\rangle$ and $|r+1\rangle$,

$$A_r = |r\rangle\langle r+1| + |r+1\rangle\langle r|. \quad (7)$$

Thus, for a single local actuator positioned between r and $r+1$ we have

$$H[f(t)] = A_0 + f(t)A_r. \quad (8)$$

Example 1. *The Hamiltonian of the first excitation subspace of a spin chain of length N with nearest neighbour coupling of isotropic Heisenberg form given by the coupling constants $d_n > 0$ for $n = 1, \dots, N-1$ is*

$$A_0 = \sum_{n=1}^N E_n |n\rangle\langle n| + \sum_{n=1}^{N-1} d_n [|n\rangle\langle n+1| + |n+1\rangle\langle n|], \quad (9)$$

where the energy levels are explicitly

$$E_n = \frac{1}{2} \sum_{\ell \neq n-1, n} d_\ell - \frac{1}{2}(d_{n-1} + d_n) \quad (10)$$

and we set $d_0 = d_N = 0$. Assuming we have a local actuator that allows us to modulate the coupling between spins r and $r+1$, the total Hamiltonian is of the form Eq. (8) with A_r of the form Eq. (7). The first excitation subspace Hamiltonian for spin chains with dipole-dipole interactions is also of form (9) but with different energy levels. Similar results hold for any spin chain decomposable into excitation subspaces.

Again, it is quite obvious that $N-1$ independent local actuators of this type, controlling the coupling between spins n and $n+1$ in the chain, will suffice for the system to be controllable, but in fact, a single such actuator suffices in most cases.

Theorem 1. *A quantum system with Hamiltonian $H[f(t)] = A_0 + f(t)A_r$ with A_0 and A_r as above is controllable if $\omega_r \neq 0$, $d_n \neq 0$ and $d_{r+1}^2 \neq d_{r-1}^2$.*

Proof. We show that the trace-zero anti-Hermitian matrices iV_0 and iV_r defined by

$$V_0 = A_0 - \frac{\text{Tr}(A_0)}{N} I_N, \quad V_1 = A_r - \frac{\text{Tr}(A_r)}{N} I_N$$

generate the Lie algebra $\mathfrak{L} = \mathfrak{su}(N)$. To this end it suffices to show that the Lie algebra \mathfrak{L} contains the $2(n-1)$ generators $x_n \equiv x_{n,n+1}$ and $y_n \equiv y_{n,n+1}$ of $\mathfrak{su}(N)$, where the basis elements of $\mathfrak{su}(N)$ are defined as usual,

$$\begin{aligned} x_{mn} &= |n\rangle\langle m| - |m\rangle\langle n|, \\ y_{mn} &= i(|n\rangle\langle m| + |m\rangle\langle n|), \\ h_n &= |n\rangle\langle n| - |n+1\rangle\langle n+1|, \end{aligned}$$

for $1 \leq m < n \leq N$. Let $V_0^{(0)} = i(V_0 - d_r V_1)$. We have $iV_1 = y_r \in \mathfrak{L}$ and

$$\begin{aligned} X_0 &\equiv [y_r, V_0^{(0)}] = d_{r-1}x_{r-1,r+1} - d_{r+1}x_{r,r+2} - \omega_r x_r \\ Y_0 &\equiv [X_0, y_r] = d_{r-1}y_{r-1} + d_{r+1}y_{r+1} - 2\omega_r h_r \\ X'_0 &\equiv [Y_0, y_r] = -d_{r-1}x_{r-1,r+1} + d_{r+1}x_{r,r+2} + 4\omega_r x_r \\ Y'_0 &\equiv [X'_0, y_r] = -d_{r-1}y_{r-1} - d_{r+1}y_{r+1} + 8\omega_r h_r \end{aligned}$$

yields $x_r = (3\omega_r)^{-1}(X_0 + X'_0) \in \mathfrak{L}$ and $h_r = 2^{-1}[x_r, y_r] \in$

\mathfrak{L} as $\omega_r \neq 0$. Next setting

$$\begin{aligned} Y_1 &\equiv 3^{-1}(4Y_0 + Y'_0) = d_{r-1}y_{r-1} + d_{r+1}y_{r+1} \\ X_1 &\equiv [[x_r, Y_1], y_r] = d_{r-1}x_{r-1} + d_{r+1}x_{r+1} \\ Z_1 &\equiv 2^{-1}[X_1, Y_1] = d_{r-1}^2 h_{r-1} + d_{r+1}^2 h_{r+1} \\ Y'_1 &\equiv 2^{-1}[Z_1, X_1] = d_{r-1}^3 y_{r-1} + d_{r+1}^3 y_{r+1} \\ X'_1 &\equiv 2^{-1}[Y_1, Z_1] = d_{r-1}^3 x_{r-1} + d_{r+1}^3 x_{r+1}, \end{aligned}$$

and $c_1 = d_{r-1}^2 - d_{r+1}^2$ leads to

$$\begin{aligned} Y'_1 - d_{r+1}^2 Y_1 &= d_{r-1} c_1 y_{r-1}, \\ X'_1 - d_{r+1}^2 X_1 &= d_{r-1} c_1 x_{r-1}, \\ Y'_1 - d_{r-1}^2 Y_1 &= -d_{r+1} c_1 y_{r+1}, \\ X'_1 - d_{r-1}^2 X_1 &= -d_{r+1} c_1 x_{r+1}. \end{aligned}$$

Since $d_{r\pm 1} \neq 0$, $c_1 \neq 0$ by hypothesis, we have $y_{r\pm 1}$, $x_{r\pm 1}$, and $h_{r\pm 1} = 2^{-1}[x_{r\pm 1}, y_{r\pm 1}]$ in \mathfrak{L} . Next note that

$$V_0^{(1)} \equiv V_0^{(0)} - Y_1 = iH_0 + \sum_{n \in I^{(1)}} d_n y_n$$

where $I^{(1)}$ is the index set $\{1, \dots, N-1\}$ minus the subset $\{r-1, r, r+1\}$ and we have

$$\begin{aligned} Y'_2 &\equiv [[Z_1, V_0^{(1)}], Z_1] = d_{r-2} d_{r-1}^4 y_{r-2} + d_{r+1}^4 d_{r+2} y_{r+2} \\ V_0^{(2)} &\equiv V_0^{(1)} - d_{r-1}^4 Y'_2 = iH_0 + \sum_{n \in I^{(2)}} d_n y_n + c_{r+2} y_{r+2}, \end{aligned}$$

with $I^{(2)}$ the index set $I^{(1)}$ minus $\{r-2, r+2\}$ and $c_{r+2} = d_{r+2}(1 - d_{r+1}^4/d_{r-1}^4)$. Hence

$$\begin{aligned} X_2 &\equiv [Z_1, V_0^{(2)}] = d_{r+1}^2 c_{r+2} x_{r+2}, \\ Y_2 &\equiv [X_2, Z_1] = d_{r+1}^4 c_{r+2} y_{r+2} \end{aligned}$$

shows x_{r+2} , y_{r+2} and $h_{r+2} = 2^{-1}[x_{r+2}, y_{r+2}]$ in \mathfrak{L} . Setting $V_0^{(3)} = V_0^{(2)} - d_{r+2} y_{r+2}$ now shows that

$$\begin{aligned} x_{r+3} &= d_{r+3}^{-1} [h_{r+2}, V_0^{(3)}] \in \mathfrak{L}, \\ y_{r+3} &= [x_{r+3}, h_{r+2}] \in \mathfrak{L}, \\ h_{r+3} &= 2^{-1} [x_{r+3}, y_{r+3}] \in \mathfrak{L}. \end{aligned}$$

Repeating this procedure with $V_0^{(k+1)} = V_0^{(k)} - d_{r+k} y_{r+k}$ we obtain

$$\begin{aligned} x_{r+k+1} &= d_{r+k+1}^{-1} [h_{r+k}, V_0^{(k+1)}] \in \mathfrak{L} \\ y_{r+k+1} &= [x_{r+k+1}, h_{r+k}] \in \mathfrak{L} \\ h_{r+k+1} &= 2^{-1} [x_{r+k+1}, y_{r+k+1}] \in \mathfrak{L} \end{aligned}$$

for $3 \leq k \leq N-r-2$. To show that the elements x_{r-k} , y_{r-k} for $2 \leq k \leq r-1$ are in \mathfrak{L} , we note that

$$\begin{aligned} y_{r-2} &= d_{r-2}^{-1} d_{r-1}^{-4} (Y'_1 - d_{r+1}^4 d_{r+2} y_{r+2}) \in \mathfrak{L} \\ x_{r-2} &= [h_{r-1}, y_{r-2}] \in \mathfrak{L} \\ h_{r-2} &= 2^{-1} [x_{r-2}, y_{r-2}] \in \mathfrak{L} \end{aligned}$$

and setting $W_0^{(2)} = V_0^{(N-r-1)}$ and $W_0^{(k+1)} = W_0^{(k)} - d_{r-k-1}y_{r-k-1}$ shows

$$\begin{aligned} x_{r-k-1} &= d_{r-k-1}^{-1}[h_{r-k}, W_0^{(k)}] \in \mathcal{L} \\ y_{r-k-1} &= [x_{r-k-1}, h_{r-k}] \in \mathcal{L} \\ h_{r-k-1} &= 2^{-1}[x_{r-k-1}, y_{r-k-1}] \in \mathcal{L} \end{aligned}$$

for $2 \leq k \leq r-2$, as desired. \square

For a Heisenberg spin chain $d_n > 0$ for $n = 1, \dots, N-1$ and Eq. (10) show that $\omega_n = d_{n-1} - d_{n+1}$. Thus $\omega_r \neq 0$ is equivalent to $d_{r+1} \neq d_{r-1}$ and we have the following

Corollary 1. *The first excitation subspace of a Heisenberg spin chain of length N with coupling constants d_n is controllable with single local actuator between spins r and $r+1$ if $d_{r+1} \neq d_{r-1}$.*

A Heisenberg spin chain with non-uniform couplings almost certainly satisfies $d_{r-1}^2 \neq d_{r+1}^2$ for any r between 1 and $N-1$. A chain with uniform coupling $d_n = d$, $n = 1, \dots, N-1$, $d_0 = d_N = 0$, satisfies this condition only if the actuator is placed near the end of the chain, i.e., $r = 1$ or $r = N-1$. However, we can generalize the previous theorem.

Theorem 2. *A quantum system with Hamiltonian $H[f(t)] = A_0 + f(t)A_r$ with A_0 and A_r as above is controllable if $\omega_r \neq 0$, $d_n \neq 0$ and $d_{r-k-1}^2 \neq d_{r+k+1}^2$ for some $k \in \mathbb{N}_0$.*

Proof. For $k = 0$, i.e., if $d_{r-1}^2 \neq d_{r+1}^2$, the result follows from Thm 1. If $d_{r-1}^2 = d_{r+1}^2$ we begin as in the proof of Thm 1 to conclude that $y_r \in \mathcal{L}$, $x_r = (3\omega_r)^{-1}(X_0 + X'_0) \in \mathcal{L}$ and $h_r = 2^{-1}[x_r, y_r] \in \mathcal{L}$, and set

$$\begin{aligned} V_0^{(0)} &\equiv iV_0 - d_r y_r \\ Y_1^{(0)} &\equiv 3^{-1}(4Y_0 + Y'_0) = d_{r-1}y_{r-1} + d_{r+1}y_{r+1} \\ X_1^{(0)} &\equiv [[x_r, Y_1^{(0)}], y_r] = d_{r-1}x_{r-1} + d_{r+1}x_{r+1} \\ Z_1^{(0)} &\equiv 2^{-1}[X_1^{(0)}, Y_1^{(0)}] = d_{r-1}^2 h_{r-1} + d_{r+1}^2 h_{r+1} \\ V_0^{(1)} &\equiv V_0^{(0)} - Y_1^{(0)} = iH_0 - \sum_{n \in I^{(1)}} d_n y_n \end{aligned}$$

where $I^{(1)}$ is the index set $\{1, \dots, N-1\}$ minus the subset $\{r-1, r, r+1\}$.

Setting $d_{r+j}^2 = d_{r-j}^2$ for $j = 1 \dots k-1$ and observing that we cannot separate the $r+1$ to $r+k$ and $r-1$ to $r-k$ terms, respectively, at this stage we continue along similar lines by iterating the following set of recurrence

relations for $j = 1, \dots, k-1$

$$\begin{aligned} Z_j^{(1)} &\equiv d_{r-j}^{-2} Z_1^{(0)} \\ &= h_{r-j} + h_{r+j} \text{ as } d_{r+j}^2 = d_{r-j}^2 \neq 0 \\ X_j^{(1)} &\equiv [Y_j^{(0)}, V_0^{(j)}] \\ &= d_{r-j} d_{r-j-1} x_{r-j-1, r-j+1} - d_{r-j} \omega_{r-j} h_{r-j} \\ &\quad - d_{r+j} d_{r+j+1} x_{r+j, r+j+2} - d_{r+j} \omega_{r+j} h_{r+j} \\ Y_j^{(1)} &\equiv [X_j^{(1)}, Y_j^{(0)}] \\ &= d_{r-j}^2 d_{r-j-1} y_{r-j-1} - 2d_{r-j}^2 \omega_{r-j} h_{r-j} \\ &\quad + d_{r+j}^2 d_{r+j+1} y_{r+j+1} - 2d_{r+j}^2 \omega_{r+j} h_{r+j} \\ Y_j^{(2)} &\equiv d_{r-j}^{-2} Y_j^{(1)} \\ &= d_{r-j-1} y_{r-j-1} - 2\omega_{r-j} h_{r-j} \\ &\quad + d_{r+j+1} y_{r+j+1} - 2\omega_{r+j} h_{r+j} \\ X_{j+1}^{(0)} &\equiv [Z_j^{(1)}, Y_j^{(2)}] \\ &= d_{r-j-1} x_{r-j-1} + d_{r+j+1} x_{r+j+1} \\ Y_{j+1}^{(0)} &\equiv [X_{j+1}^{(0)}, Z_j^{(1)}] \\ &= d_{r-j-1} y_{r-j-1} + d_{r+j+1} y_{r+j+1} \\ Z_{j+1}^{(0)} &\equiv 2^{-1}[X_{j+1}^{(0)}, Y_{j+1}^{(0)}] \\ &= d_{r-j-1}^2 h_{r-j-1} + d_{r+j+1}^2 h_{r+j+1} \\ V_0^{(j+1)} &\equiv V_0^{(j)} - Y_{j+1}^{(0)} \\ &= iH_0 - \sum_{n \in I^{(j+1)}} d_n y_n \end{aligned}$$

where $I^{(j+1)}$ is the index set $I^{(j)}$ with the subset $\{r-j-1, r+j+1\}$ removed. Since $d_{r-k-1}^2 \neq d_{r+k+1}^2$ and

$$\begin{aligned} X_k^{(0)} &= d_{r-k} x_{r-k} + d_{r+k} x_{r+k} \\ Y_k^{(0)} &= d_{r-k} y_{r-k} + d_{r+k} y_{r+k} \\ Z_k^{(0)} &= d_{r-k}^2 h_{r-k} + d_{r+k}^2 h_{r+k} \\ V_0^{(k)} &= iH_0 - \sum_{n \in I^{(k)}} d_n y_n \end{aligned}$$

where $I^{(k)}$ is the index set $\{1, \dots, r-k, r+k, \dots, N\}$.

To complete the proof by showing that $y_{r \pm (k+1)}$, $x_{r \pm (k+1)}$ and $h_{r \pm (k+1)}$ are in \mathcal{L} , we calculate the commutators

$$\begin{aligned} X_k^{(1)} &\equiv [Y_k^{(0)}, V_0^{(k)}] \\ &= d_{r-k} d_{r-k-1} x_{r-k-1, r-k+1} - d_{r-k} \omega_{r-k} h_{r-k} \\ &\quad - d_{r+k} d_{r+k+1} x_{r+k, r+k+2} - d_{r+k} \omega_{r+k} h_{r+k} \\ Y_k^{(1)} &\equiv [X_k^{(1)}, Y_k^{(0)}] \\ &= d_{r-k}^2 d_{r-k-1} y_{r-k-1} - 2d_{r-k}^2 \omega_{r-k} h_{r-k} \\ &\quad + d_{r+k}^2 d_{r+k+1} y_{r+k+1} - 2d_{r+k}^2 \omega_{r+k} h_{r+k} \\ Z_k^{(1)} &\equiv d_{r-k}^{-2} Z_k^{(0)} \\ &= h_{r-k} + h_{r+k} \text{ as } d_{r-k}^2 = d_{r+k}^2 \end{aligned}$$

$$\begin{aligned}
X_k^{(2)} &\equiv [Z_k^{(1)}, Y_k^{(1)}] \\
&= d_{r-k}^{-2} d_{r-k-1} x_{r-k-1} + d_{r+k}^{-2} d_{r+k+1} x_{r+k+1} \\
X_k^{(3)} &\equiv d_{r-k}^{-2} X_k^{(2)} \\
&= d_{r-k-1} x_{r-k-1} + d_{r+k+1} x_{r+k+1} \\
Y_k^{(2)} &\equiv [X_k^{(3)}, Z_k^{(1)}] \\
&= d_{r-k-1} y_{r-k-1} + d_{r+k+1} y_{r+k+1} \\
Z_k^{(2)} &\equiv 2^{-1} [X_k^{(3)}, Y_k^{(2)}] \\
&= d_{r-k-1}^2 h_{r-k-1} + d_{r+k+1}^2 h_{r+k+1} \\
Y_k^{(3)} &\equiv 2^{-1} [Z_k^{(2)}, X_k^{(3)}] \\
&= d_{r-k-1}^3 y_{r-k-1} + d_{r+k+1}^3 y_{r+k+1}
\end{aligned}$$

which gives

$$\begin{aligned}
y_{r\pm(k+1)} &= \frac{Y_k^{(3)} - d_{r\mp(k+1)} Y_k^{(2)}}{d_{r\pm(k+1)} (d_{r\pm(k+1)}^2 - d_{r\mp(k+1)}^2)} \\
x_{r\pm(k+1)} &\equiv [y_{r\pm(k+1)}, Z_k^{(2)}] / (2d_{r\pm(k+1)}^2) \\
h_{r\pm(k+1)} &\equiv [x_{r\pm(k+1)}, y_{r\pm(k+1)}] / 2
\end{aligned}$$

showing that these generators are in \mathcal{L} . To show that the generators $x_{r\pm j}$, $y_{r\pm j}$, and $h_{r\pm j}$ are in \mathcal{L} for $j = 1, \dots, k$ we set

$$\begin{aligned}
V_0^{(k+1)} &= V_0^{(k)} - d_{r-k-1} y_{r-k-1} - d_{r+k+1} y_{r+k+1} \\
&= iH_0 - \sum_{n \in I^{(k+1)}} d_n y_n,
\end{aligned}$$

where $I^{(k+1)}$ is the index set $I^{(k)}$ with the subset $\{r - k - 1, r + k + 1\}$ removed, and note that

$$\begin{aligned}
x_{r\pm j} &\equiv d_{r\pm j}^{-1} [[y_{r\pm(j+1)}, X_j^{(0)}], y_{r\pm(j+1)}] \\
y_{r\pm j} &\equiv [x_{r\pm(j+1)}, [x_{r\pm j}, y_{r\pm(j+1)}]] \\
h_{r\pm j} &\equiv 2^{-1} [x_{r\pm j}, y_{r\pm j}]
\end{aligned}$$

Finally, we show that the generators x_{r+k+j} , y_{r+k+j} and h_{r+k+j} are in \mathcal{L} for $j = 2 \dots N - r - k - 1$, by iterating the following set of recurrence relations for $j = 2 \dots N - r - k - 1$:

$$\begin{aligned}
x_{r+k+j} &= d_{r+k+j}^{-1} [h_{r+k+j-1}, V_0^{(k+j-1)}] \\
y_{r+k+j} &= [x_{r+k+j}, h_{r+k+j-1}] \\
h_{r+k+j} &= 2^{-1} [x_{r+k+j}, y_{r+k+j}] \\
V_0^{(k+j)} &= V_0^{(k+j-1)} - d_{r+k+j} y_{r+k+j}
\end{aligned}$$

Similarly, we show that the elements x_{r-k-j} , y_{r-k-j} and h_{r-k-j} are in \mathcal{L} for $j = 2, \dots, r - k - 1$, by setting $W_0^{(k-1)} = V_0^{(k-1)}$ and iterating the following recurrence relations for $j = 2 \dots r - k - 1$:

$$\begin{aligned}
x_{r-k-j} &= d_{r-k-j}^{-1} [h_{r-k-j+1}, W_0^{(k-j+1)}] \\
y_{r-k-j} &= [x_{r-k-j}, h_{r-k-j+1}] \\
h_{r-k-j} &= 2^{-1} [x_{r-k-j}, y_{r-k-j}] \\
W_0^{(k-j)} &= W_0^{(k-j+1)} - d_{r-k-j} y_{r-k-j}
\end{aligned}$$

We have now shown that $x_j, y_j \in \mathcal{L}$ for $j = 1 \dots N - 1$ as desired, completing the proof. \square

We note that $d_{r-k-1}^2 \neq d_{r+k+1}^2$ for some integer k is always satisfied if the system dimension is odd, $N = 2\ell + 1$, no matter where we place the actuator. If $N = 2\ell$ then $d_{r-k-1}^2 = d_{r+k+1}^2$ for all k is possible only if $r = \ell$, i.e., if the actuator is placed in the middle, and the coupling constants are symmetric around the centre, $d_{\ell-k}^2 = d_{\ell+k}^2$ for all k . For a spin chain with strictly isotropic Heisenberg interaction the requirement $\omega_r \neq 0$ would still be a problem if $d_{r-1} = d_{r+1}$, although control simulations suggest that even in this case effective control may be possible, and controllability could be restored by engineering a local perturbation of the energy levels in the vicinity of the actuator, which may even be achieved by the actuator itself.

IV. CONSTRUCTIVE CONTROL WITH SINGLE BINARY SWITCH ACTUATOR

The results of the previous section suggest that a single actuator is often sufficient to achieve the same degree of controllability that is achievable with many local actuators, a rather surprising result. However, is it ever possible to control such a system constructively, i.e., to explicitly find the correct switching times to accomplish a desired task? Although analytical expressions for the optimal switching times are generally very difficult to obtain, conventional optimization techniques can be used to find suitable controls, and we have found them to be surprisingly effective in many cases.

The type of control functions that are permissible generally depends on the specifics of the system and controller. For instance, for an optically controlled quantum dot, the availability of optical pulse shaping technology and the demonstrated superiority of shaped pulses over simple pulses in certain settings, suggests optimization routines designed to find an optimal time-dependent pulse shape $f(t)$, which can be implemented with the available pulse shaping equipment. Various such algorithms based on gradients and variational techniques exists (see e.g. [15, 16, 17]).

For other systems, especially voltage gate controlled systems, however, complicated time-varying potentials $f(t)$ are generally difficult to implement. In this case, the controls should ideally be simple, piecewise constant functions, if possible perhaps taking only two values f_0 and f_1 . The latter type of actuator corresponds to a binary switch that simply switches the voltage between two possible values, corresponding to two fixed Hamiltonians

$$H^{(1)} = A_0 + f_0 A_1 \quad (11a)$$

$$H^{(2)} = A_0 + f_1 A_1. \quad (11b)$$

Given a sequence of switching times $\mathbf{t} = (t_1, \dots, t_K)$ the corresponding evolution of the system is given by

$$U(\mathbf{t}) = U^{(1)}(t_1) U^{(2)}(t_2) \dots U^{(1)}(t_{K-1}) U^{(2)}(t_K) \quad (12)$$

where $U^{(m)}(t_k) = \exp(-it_k H^{(m)})$ for $m = 1, 2$.

As a specific example, we consider the first excitation subspace of a spin chain of length four with a single binary switch actuator placed between spins one and two, i.e., $r = 1$. This system is controllable with a single actuator at $r = 1$ according to Theorem 1. To show that we can constructively control this system with a single binary switch actuator, we find switching time sequences for a complete set of generators of $\mathfrak{SU}(4)$. Interpreting the first excitation subspace of the chain as a two-qubit system by setting

$$|0\rangle = |00\rangle, |1\rangle = |01\rangle, |2\rangle = |10\rangle, |3\rangle = |11\rangle,$$

we show that it is possible to find vectors $\mathbf{t}^{(s)}$ such that

$$\|U_T^{(s)} - U(\mathbf{t}^{(s)})\| \leq 10^{-4} \quad (13)$$

for the following set of six target operators

$$U_T^{(s)} \in \{I \otimes I, \text{Had} \otimes I, T \otimes I, I \otimes \text{Had}, I \otimes T, \text{CNOT}\}, \quad (14)$$

where I is identity operator on a single two-level subspace (qubit), $T = \exp(-i\pi/8\sigma_z)$ is a $\pi/8$ phase gate, and Had and CNOT are the Hadamard and CNOT gate, respectively,

$$\text{Had} = \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & -1 \\ 1 & 1 \end{pmatrix}, \quad \text{CNOT} = e^{-i\pi/4} \begin{pmatrix} I_2 & 0 \\ 0 & \sigma_x \end{pmatrix},$$

with σ_x and σ_z being the usual Pauli matrices

$$\sigma_x = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \quad \sigma_z = \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}.$$

The set of target operators (14) was chosen because it is a universal set of elementary gates in that any other $\mathfrak{SU}(4)$ operator can be constructed from these elementary gates, and the ability to implement a universal set of gates for $\mathfrak{SU}(4)$ is equivalent to (density operator) controllability of the system.

Table I shows the time vectors $\mathbf{t}^{(s)}$, as well as the gate operation times $T = \sum_{k=1}^K t_k$ and gate errors as defined above for a system with uniform isotropic Heisenberg coupling. The optimization was performed using a Nelder-Mead downhill simplex algorithm [18] with multiple initial simplices. The table shows that it is possible to implement all of the six elementary gates with a fidelity $\geq 99.99\%$ with no more than 20 switches of a single on-off switch actuator in approximately 40 time units each, a surprisingly good result considering the minimal nature of the available control. Since solutions are obviously not unique, and the minimum control time or number of switches required to achieve the control objective are unknown, even better solutions probably exist. The non-uniqueness of the solutions can be exploited to satisfy additional constraints such as minimum pulse lengths (switching cannot be arbitrarily fast) etc.

V. CONCLUSION

We have shown that a certain class of systems of Hilbert space dimension N is controllable with a single local actuator as opposed to $N - 1$ or more independent local actuators, or global actuators acting on the entire system. The results are of interest as they establish theoretical minimum requirements for controllability for a class of systems that includes many types of spin chains and other systems with non-trivial fixed couplings between adjacent elements. In particular, the results show that it is not necessary to be able control all transitions, and a single local actuator in fact suffices in most cases to achieve controllability. Considering that systems with fixed interactions are generally much easier to engineer than systems with individually tunable transitions, this is a promising result.

Although the controllability proof is an existence proof, we have further demonstrated that it is possible to constructively control a system with a local actuator, even if the actuator is limited to a binary switch, for a four-level system, where we have shown that it is possible to implement a complete set of generators of $\mathfrak{SU}(4)$ with fidelities $\geq 99.99\%$ using a single binary switch actuator, with no more than 20 switches per gate required. Although it would be desirable to have analytic expressions for the switching times, it appears that numerical optimization techniques are quite effective in finding suitable controls.

Numerical simulations for systems with non-tridiagonal Hamiltonians (e.g., as a result of non-nearest neighbour couplings) suggest that constructive control is generally still possible, and similar strong controllability results can almost certainly be obtained using very similar arguments for these systems. Beyond the extension of generic controllability results to other classes of Hamiltonians, interesting questions for future work—the answers to which could point the way to achieving effective control with much simpler control system designs—include what type of systems can be effectively controlled with a single local actuator, whether the placement of the actuator matters, and how additional constraints (e.g., binary switch versus continuous modulation) affect the control outcomes in practice.

Acknowledgments

SGS acknowledges support from an EPSRC Advanced Research Fellowship, the EPSRC QIP IRC and Hitachi. PJP is supported by an EPSRC Project Studentship.

	$I \otimes I$	Had $\otimes I$	$T \otimes I$	$I \otimes$ Had	$I \otimes T$	CNOT
error	6.02407e-05	9.93462e-06	9.41944e-10	8.86637e-07	1.10773e-06	1.31773e-06
duration	40.5351	37.9537	41.166	41.1328	42.5368	39.3569
t_1	0.731996	3.94518	1.79446	3.08601	1.30764	3.34576
t_2	2.03884	2.20021	1.79932	3.13305	1.1069	0.0179813
t_3	3.52727	0.0384191	0.0730935	0.701478	0.518925	2.59171
t_4	1.38628	1.07432e-07	1.71885	3.62498	5.85085	3.23448
t_5	3.39919	0.680856	2.07051	2.45712	0.396729	1.46693
t_6	0.951534	3.04816	0.747468	0.68558	7.37392	0.212212
t_7	1.35113	1.292	1.84047	1.3746	1.13031	5.0851
t_8	0.575672	1.86256	2.53341	1.12801	1.16712	3.07975
t_9	3.38307	4.14879	4.73792	3.50997	0.802765	2.75667
t_{10}	0.0365974	0.356856	1.3432	1.92944	4.08279	0.439889
t_{11}	3.62131	1.02202	1.39084	5.57909	1.27132	3.25423
t_{12}	0.93505	0.0453206	0.320722	0.298252	2.70023	2.41685
t_{13}	1.75377	2.13701	4.15595	0.987279	4.67647	1.04768
t_{14}	5.19515	1.24291	0.533115	0.26934	0.705919	1.31426
t_{15}	4.5099	0.101593	1.03574	1.7998	1.01477	2.6859
t_{16}	1.01899	4.40131	7.58673	4.66334	1.78438	0.732592
t_{17}	4.01314	1.07241	4.77061	0.135612	1.02283	0.16703
t_{18}	0.991019	5.83516	0.857316	1.31499	1.02426	0.770284
t_{19}	0.705316	1.6229	1.7735	3.38444	2.16687	2.32287
t_{20}	0.409887	2.89999	0.082803	1.07044	2.43177	2.41471

TABLE I: Gate errors (1–gate fidelity), total time T required to implement respective gates, and vector of switching times t_k to implement a universal set of elementary gates with 20 switches for (the first excitation subspace of) a uniform isotropic Heisenberg spin chain of length four.

-
- [1] V. Jurdjevic and H. J. Sussmann, *J. Diff. Eq.* **12**, 313 (1972).
- [2] G. M. Huang, T. J. Tarn, and J. W. Clark, *J. Math. Phys.* **24**, 2608 (1983).
- [3] V. Ramakrishna, M. V. Salapaka, M. Dahleh, H. Rabitz, and A. Peirce, *Phys. Rev. A* **51**, 960 (1995).
- [4] F. Albertini and D. D’Alessandro, <http://arxiv.org/abs/quant-ph/0106128> (2001).
- [5] S. G. Schirmer, H. Fu, and A. I. Solomon, *Phys. Rev. A* **63**, 063410 (2001).
- [6] S. G. Schirmer, J. V. Leahy, and A. I. Solomon, *J. Phys. A* **35**, 4125 (2002).
- [7] S. G. Schirmer, I. C. H. Pullen, and A. I. Solomon, in *Hamiltonian and Lagrangian Methods in Nonlinear Control*, edited by Astolfi, Gordillo, and van der Schaft (Elsevier Science Ltd, 2003), pp. 311–316.
- [8] S. G. Schirmer, I. C. H. Pullen, and A. I. Solomon, *J. Optics B* **7**, S293 (2005).
- [9] G. Turinici and H. Rabitz, *Chem. Phys.* **267**, 1 (2001).
- [10] C. Altafini, *J. Math. Phys.* **43**, 2051 (2002).
- [11] H. Fu, S. G. Schirmer, and A. I. Solomon, *J. Phys. A* **34**, 1679 (2001).
- [12] H. C. Fu, H. Dong, X. F. Liu, and C. P. Sun, *Physical Review A (Atomic, Molecular, and Optical Physics)* **75**, 052317 (2007).
- [13] B. E. Kane, *Nature* **393**, 133 (1998).
- [14] S. G. Schirmer, I. C. H. Pullen, and A. I. Solomon, *J. Phys. A* **35**, 2327 (2002).
- [15] Y. Ohtsuki, G. Turinici, and H. Rabitz, *J. Chem. Phys.* **120**, 5509 (2004).
- [16] S. G. Schirmer, M. D. Girardeau, and J. V. Leahy, *Phys. Rev. A* **61**, 012101 (2000).
- [17] N. Khaneja, T. Reiss, C. Kehlet, T. Schulte-Herbruggen, and S. J. Glaser, *J. Mag. Resonance* **172**, 296 (2005).
- [18] J. C. Lagarias, J. A. Reeds, M. H. Wright, and P. E. Wright, *SIAM Journal of Optimization* **9**, 112 (1998).