High-fidelity quantum operations on superconducting qubits in the presence of noise

Andrew J. Kerman and William D. Oliver

Lincoln Laboratory, Massachusetts Institute of Technology, Lexington, MA, 02420

(Dated: October 31, 2018)

We present a scheme for implementing quantum operations with superconducting qubits. Our approach uses a "coupler" qubit to mediate a controllable, secular interaction between "data" qubits, pulse sequences which strongly mitigate the effects of 1/f flux noise, and a high-Q resonator-based local memory. We develop a Monte-Carlo simulation technique capable of describing arbitrary noiseinduced dephasing and decay, and demonstrate in this system a set of universal gate operations with $\mathcal{O}(10^{-5})$ error probabilities in the presence of experimentally measured levels of 1/f noise. We then add relaxation and quantify the decay times required to maintain this error level.

PACS numbers: 02.70.Ss, 03.65.Yz, 03.67.Ac, 03.67.Lx, 03.67.Pp, 85.25.Am, 85.25.Cp

Superconducting qubits are promising building blocks for quantum computers [\[1\]](#page-3-0). Realizing this promise requires a qubit coupling scheme and associated control pulse sequences capable of realizing gate operations with error probabilities low enough to achieve faulttolerance [\[2\]](#page-3-1). Such a control scheme should ideally permit a practical, time-efficient implementation of universal single- and two-qubit operations; incorporate switchable coupling between qubits; and be insensitive both to decoherence and fabrication variations of the qubits.

Although several proposed [\[3](#page-3-2), [4,](#page-3-3) [5,](#page-3-4) [6](#page-3-5)] and experimental [\[7](#page-3-6)] qubit coupling schemes already exist, none yet combine all of the above features. In this Letter, we present a scheme which aims to do this. Our approach utilizes a "coupler" qubit to mediate interaction between "data" qubits [\[4\]](#page-3-3), pulse sequences incorporating spinechoes to suppress the effects of 1/f flux noise [\[8](#page-3-7), [9](#page-3-8)], and local memory in the form of high-Q resonators [\[10\]](#page-3-9). We introduce a Monte-Carlo technique capable of simulating gate operations in the presence of noise and spontaneous decay, which we then use to show that $\mathcal{O}(10^{-5})$ error probabilities (comparable to certain predicted thresholds for fault-tolerance [\[2](#page-3-1)]) can be achieved in the presence of experimentally measured levels of flux noise. Finally, we quantify the qubit excited-state lifetimes and control signal requirements necessary to achieve this.

We focus here on the flux qubit [\[11\]](#page-3-10), although much of what follows is more generally applicable. In most work to date, this consists of a single superconducting loop interrupted by several Josephson junctions [Fig. [1\(](#page-0-0)b)]. In this work, however, we consider the double-loop four-junction version [Fig. [1\(](#page-0-0)c)]. When $\Phi_1, \Phi_2 \approx \frac{\Phi_0}{2}$, 0 $(\Phi_0 = h/2e$ is the flux quantum), the qubit can be described by the approximate two-level Hamiltonian $\hat{H}_{\text{qb}} =$ $\frac{1}{2}[\epsilon \hat{\sigma}^z + \Delta \hat{\sigma}^x]$. The eigenstates of $\hat{\sigma}^z$ are "persistent current" (PC) states with energies $\pm \epsilon/2 = \pm I_p(\Phi_1 - \frac{\Phi_0}{2}),$ where currents $\pm I_{\rm p}$ circulate around the Φ_1 loop. The parameters ϵ and Δ are tunable by the fluxes $\Phi_{\epsilon} \equiv \Phi_1 + \frac{\Phi_2}{2}$ and $\Phi_{\Delta} \equiv \Phi_2$ [Figs. [1\(](#page-0-0)c),(f)]. Point A in Fig. 1(a), where the PC states are mixed to produce an avoided crossing with $\hat{\sigma}^x$ -like energy eigenstates, is known as the "degeneracy point". It has the desirable feature that

f) a) b) αA^J ε *M* 2 Φ_1 Aj $\,$ x—O $_1\,$ xyAj ∆ $+\Phi_1$ $\overline{2}$ c) *M* + Φ ₂ - Φ_{2} βA, Φ ₂ Energy [GHz] Energy [GHz] -Φ₁ A X A_J \bigstar β A_J Aj**≭** βAj ∦XAj C B Φ_1 ↑↑ d) e) $|_{\uparrow\uparrow}$ *J* C ↓↑ ↓↑ 4 ↑↓ ↑↓ Φ_{Δ} 0.2 Φ_{ϵ} $|\downarrow \downarrow \rangle$ ↓↓

FIG. 1: (color online) Flux qubits and secular vs. nonsecular coupling. (a) Lowest-two energy levels for a flux qubit. Schematic of (b) single-loop 3-JJ and (c) double-loop 4-JJ flux qubits. Relative junction areas have ratios α and β [\[11\]](#page-3-10). Single-loop qubits have only one control flux Φ_{ϵ} and are restricted to the line AC in (a). Double-loop qubits have two control fluxes: $\Phi_{\epsilon} \equiv \Phi_1 + \frac{\Phi_2}{2}$ and $\Phi_{\Delta} \equiv \Phi_2$. (d) Energy levels for two flux qubits at degeneracy, with nonsecular coupling. Level shifts result from second-order mixing of twoqubit eigenstates (dashed arrows). (e) Energy levels for secular coupling. A conditional level shift allows CNOT to be implemented with a single microwave transition (solid arrow), and SWAP with a stimulated Raman transition (by driving a 2π pulse on each qubit, corresponding to a π pulse on the Raman transition). (f) possible layout of a gradiometric 4-JJ qubit, for which Φ_1 and Φ_2 can be accessed independently. The Δ control-loop orientation induces Φ_1 and Φ_2 in the -0.5:1 ratio required to adjust Δ without affecting ϵ .

 $dE/d\Phi_{\epsilon} = dE/d\Phi_{\Delta} = 0$ (where the qubit energy splitting $E = \sqrt{\epsilon^2 + \Delta^2}$ so that decoherence due to flux noise is minimized [\[8](#page-3-7)]. Existing qubit coupling schemes which are insensitive to decoherence rely on biasing at this point [\[3](#page-3-2), [4](#page-3-3), [5](#page-3-4)].

There are, however, two disadvantages to working at degeneracy: first, E is then fixed by fabrication and may vary significantly between qubits, requiring individually tuned microwaves; second, the degenerate qubit is firstorder insensitive to flux from other qubits, so that induc-

FIG. 2: (color online) Possible scheme for universal two-qubit operations. (a) A 4-JJ coupler qubit mediates the interaction between two 4-JJ data qubits (Q1, Q2). Coupling is switched off by tuning $\epsilon_{\text{C}} \gg \Delta_{\text{C}}$. (b) An inductive interaction mixes the coupler levels (dashed arrows), resulting in a conditional frequency shift $\delta \nu$ c in the computational subspace \mathcal{C}_2 [see Fig. [1\(](#page-0-0)e)] [\[15](#page-3-11)]. (c) Increasing the qubit Δ adiabatically through the avoided crossing transfers the qubit state to the resonator [\[10](#page-3-9)].

tively coupling Φ_1 -loops, as in previous works [\[3,](#page-3-2) [4,](#page-3-3) [5\]](#page-3-4), has no effect on the system to first order. This "nonsecular" coupling can be written in the form $\hat{H}_{\text{C}}^{zz} \equiv J_{\text{C}}^{zz} \hat{\sigma}_1^z \hat{\sigma}_2^z$ (the subscripts indicate qubits 1 and 2), and its leadingorder effect at degeneracy is a second-order mixing [Fig. [1\(](#page-0-0)d)]. This mixing can be exploited using double resonance [\[3\]](#page-3-2) or parametric driving [\[4,](#page-3-3) [5\]](#page-3-4) to enable, for example, the two-qubit $\sqrt{\text{SWAP}}$ gate, even if the qubits have different splittings [\[3](#page-3-2), [4](#page-3-3), [5](#page-3-4)]; however, these schemes require different microwave frequencies for each qubit or qubit pair. Furthermore, the Controlled-NOT (CNOT) gate used ubiquitously in quantum circuits must then $\frac{1}{\sqrt{S}WAP}$ and single-qubit gates [\[12](#page-3-12)].

Far from degeneracy ($\epsilon \gg \Delta$), however, the energy eigenstates are approximately PC states, and $\hat{H}^{\rm zz}_{\rm C}$ commutes with \hat{H}_{qb} , giving a first-order level shift [Fig. [1\(](#page-0-0)e)] which lifts the degeneracy between the $|\downarrow \downarrow \rangle \leftrightarrow |\uparrow \downarrow \rangle$ and $|\downarrow\uparrow\rangle \leftrightarrow |\uparrow\uparrow\rangle$ transitions by the conditional frequency shift $\hbar \delta \nu_C = J_C^{zz}$. This "secular" coupling allows CNOT to be driven with a single microwave pulse (Fig. [1\(](#page-0-0)e), solid arrow), and SWAP with a stimulated Raman transition (dashed arrows). However, the qubits are now sensitive to flux noise due to the large slope $dE/d\Phi_{\epsilon} = 2I_{p}$.

Based on these observations, we consider the system shown in Fig. [2\(](#page-1-0)a) consisting of two two-loop "data" qubits, whose coupling is mediated by a third "coupler" qubit in a manner similar to that used in Ref. [4](#page-3-3) for singleloop qubits. Here, however, we inductively couple to Φ_{Δ} of each data qubit rather than Φ_1 (as in previous works), with the Hamiltonian: $\hat{H}_C = J_C \hat{\sigma}_C^z (\hat{\sigma}_1^x + \hat{\sigma}_2^x)$, where $J_C \approx$ $M_{\rm iC}I_{\rm p}d\Delta_{\rm i}/d\Phi_S$ and $M_{\rm iC}$ is the mutual inductance be-tween data and coupler qubits [\[13](#page-3-13)]. When $\epsilon_1 = \epsilon_2 = \epsilon_C$ = 0, this configuration produces the level structure shown in Fig. [2\(](#page-1-0)b) [\[14\]](#page-3-14). The lower four of these eight eigenstates (hereafter the two-qubit "computational subspace" or C_2)

exhibit an effective two-qubit conditional frequency shift $\hbar \delta \nu_{\rm C} = \Delta_C \{1 - \sqrt{1 + (2J_{\rm C}/\Delta_{\rm C})^2}\}\;$ equivalent to that shown in Fig. $1(e)$ [\[15](#page-3-11)]. In addition, this shift can be turned off by tuning $\epsilon_{\text{C}}/\Delta_{\text{C}} \gg 1$, so that the coupler eigenstates become approximately PC states (and eigenstates of \hat{H}_{C}); this suppresses the mixing shown in Fig. [2\(](#page-1-0)b), and with it $\delta \nu_C$ by the factor ~ (Δ_C/ϵ_C)³. The speed of this switching is limited only by nonadiabatic excitation of the coupler qubit [\[16](#page-4-0)]. Finally, the sensitivity of each data qubit to flux noise in this configuration is given by $d\Delta/d\Phi_{\Delta} = J_{\rm C}/M I_{\rm p}^{\rm C}$ ($I_{\rm p}^{\rm C}$ is the coupler persistent current), which can be reduced substantially by using larger junctions in the coupler qubit to increase I_{p}^{C} .

The final ingredient shown in Fig. [2\(](#page-1-0)a) are the transmission-line resonators coupled to the Φ_{ϵ} -loop of each qubit so that its state can be adiabatically trans-ferred into a resonator state [\[10\]](#page-3-9) [Fig. $2(c)$]. These resonators provide a potentially long-lived memory in which qubit states can be stored between manipulations.

To simulate our system, we integrate the timedependent Schrödinger equation with the Hamiltonian:

$$
\hat{H} = \frac{1}{2} \sum \left\{ [\epsilon_i(t) + \hbar \Omega_{\mu i}(t) \cos(\omega_i t)] \hat{\sigma}_i^z + \Delta_i(t) \hat{\sigma}_i^x \right\} \n+ \sum \left[h f_{rj} \hat{a}_{rj}^\dagger \hat{a}_{rj} + J_{\text{res}} (\hat{a}_{rj}^\dagger + \hat{a}_{rj}) \hat{\sigma}_j^z \right] + \hat{H}_{\text{C}} \quad (1)
$$

where $i \in \{1, 2, C\}, j \in \{1, 2\},\$ and we have added microwave fields illuminating the Φ_{ϵ} loop of each qubit. We treat the qubits as two-level systems and truncate the ladder of resonator photon states at $n = 1$ [\[16\]](#page-4-0). As fixed input parameters, we assume resonator frequencies $f_{r1,r2} = 9,11$ GHz (they may be identical in general), qubit-resonator coupling $J_{\text{res}}/h = 0.75$ GHz, and qubitqubit coupling $J_{\rm C}/h = 0.3$ GHz [\[18\]](#page-4-1).

We have simulated Hadamard (H), CNOT, and SWAP gates. As an example, the CNOT pulse sequence is shown in Fig. $3(a)$. Both qubits begin with states stored in their respective resonators $(\Delta_{1,2}$ high), and with the coupler "off" ($\epsilon_{\rm C}/\Delta_{\rm C} \gg 1$). A downward ramp is applied to both Δ_i to retrieve the qubits' states (only one Δ_i would be ramped for H). These ramps are optimized to maintain a constant non-adiabaticity as the avoided crossing in Fig. $2(c)$ is traversed. Next, the qubits are manipulated with single-qubit microwave rotations and conditional phase (CΦ) gates produced by transiently pulsing the coupler "on" ($\epsilon_{\rm C}/\Delta_{\rm C} = 0$) using linear flux ramps [\[16\]](#page-4-0). The CNOT pulse sequence (with bit 1 the target qubit) shown in Fig. $3(a)$ is: $R_{1,2}(\pi)R_1^x(\frac{\pi}{2})C^e(\frac{\pi}{2})R_1^y(\frac{\pi}{2})C^e(\frac{\pi}{2})R_{1,2}(\pi)$, where $R_{p,q}^{v'}(\theta)$ is a rotation of angle $\hat{\theta}$ around axis ν on the Bloch sphere for qubits p and q, $C^e(\frac{\pi}{2}) \equiv C(\frac{\pi}{4})R_{1,2}(\pi)C(\frac{\pi}{4}),$ and we have suppressed the free evolution intervals for clarity. The π -pulses induce spin-echoes at the center of each $\pi/2$ -pulse and at the end of the operation. H and SWAP can be constructed similarly: $H = R_1(\pi) R_i^x(\frac{\pi}{2}) R_1(\pi)$, and SWAP = $R_{1,2}(\pi) R_{1,2}^x(\frac{\pi}{2}) C^e(\frac{\pi}{2}) R_{1,2}^y(\frac{\pi}{2}) C^e(\frac{\pi}{2}) R_{1,2}^x(\frac{\pi}{2}) C^e(\frac{\pi}{2}) R_{1,2}(\pi)$

FIG. 3: (color online) Simulation of gate operations in the presence of noise. (a) CNOT pulse sequence. Data qubits are ramped to $\Delta_{1,2}$ =5,6 GHz during operations, e.g., point X [Fig. [1\(](#page-0-0)a)] ($\Delta_{1,2}$ are chosen to be different here only for clarity); the coupler has $(\epsilon_{\rm C}, \Delta_{\rm C}) = (17, 0.2)$ GHz and $(0, 4)$ GHz in the decoupled and coupled states, respectively [\[18\]](#page-4-1). Pulsed microwaves generate $π$ and $π/2$ rotations; $Cπ/4$ operations are generated by coupling for a controlled duration. Spin-echoes are generated at times indicated by dashed lines using π -pulses. (b) Simulation of a single qubit including $1/f$ noise and spontaneous decay (see text). (c) Decay rates as a function of ϵ/Δ . Solid symbols show the fitted exponential decay rate Γ_e of ρ_{22} (constant by construction). Open symbols show the decay rate $\Gamma_{\rm g}$, extracted by fitting $|\rho_{12}|$ to the approximate expression: $\exp[-\Gamma_{\rm e}t - (\Gamma_{\rm g}t)^2]$ with $\Gamma_{\rm e}$ fixed at the fitted value. The solid red line is based on the theory in Ref. [\[21\]](#page-4-2) with no free parameters. (d) maximum gate error $\mathcal E$ for H (triangles) and CNOT (circles) gates with $T_1 \to \infty$ and noise spectral density $S(\omega) = A_\omega/\omega$, vs. A_ω . Open symbols: same operations without spin-echo compensation. Vertical dashed line: experimentally measured noise level of $1 \mu \Phi_0 / \sqrt{\text{Hz}}$ at 1 Hz [\[8\]](#page-3-7). (e) Maximum error probabilities at that noise level versus the qubits' excited state lifetime. In both (d) and (e), (+) and (\times) show $\mathcal E$ for CNOT and H, respectively, with noise and decay on the coupler qubit only.

Finally, the qubit states are transferred back into the resonators, and the final relative phase of each qubit is adjusted by varying the time at which this occurs.

All microwave pulses have a fixed amplitude (with 100 ps rise/fall times), so that pulse area is controlled solely by their duration. This is crucial for producing effective spin-echoes with short, intense pulses at a fixed frequency, due to the Bloch-Siegert shift [\[17\]](#page-4-3). This frequency shift is amplitude dependent, so the microwave amplitude must be kept fixed in order to compensate for it with a fixed frequency offset (here, ∼5 MHz).

The use of single-qubit rotations and CΦ gates instead of the frequency-resolved pulses shown in Fig. [1\(](#page-0-0)e) has several advantages: first, it requires only a single microwave frequency for all operations (assuming all qubits are tuned to the same frequency using Φ_{Δ}); second, it does not require accurately resolving two frequencies spaced by $\delta \nu_{\rm C}$ using long microwave pulses. Finally, all gate parameters can be adjusted solely by varying the timing of the microwave and flux pulse edges. These characteristics may also be of interest for other types of qubits.

We simulate the effect of decoherence due to flux noise using a Monte-Carlo technique. Noise is added to each Δ_i and ϵ_i in eq. [1](#page-1-1) by superposing an independent, discrete set of random two-level "telegraph" signals [\[19\]](#page-4-4), which produce a 1/f average spectral density. For each Monte-carlo iteration (all of which can be run in parallel), a new set of noise functions is generated (one for each ϵ, Δ). From these we obtain a sequence of N time intervals $\{\delta\tau_i\}$ (typically $N \sim$ several hundred) whose union is the full gate time, and over each of which all fluctuators are *constant*. We then integrate the 32 coupled Schrödinger equations sequentially over these intervals. The final states for all iterations are converted to density matrices and then averaged, corresponding to a statistical mixture of the different noise realizations.

Spontaneous decay is added as follows. At the end of each $\delta \tau_i \equiv t_i - t_{i-1}$, we construct the density matrix ρ_i and apply amplitude damping to the qubits: $\rho_i^{\gamma} = S^1(\gamma_i) \overline{S^2(\gamma_i)} S^C(\gamma_i) \rho_i$ where $\overline{S^j(\gamma)} \rho =$ $\sum_{k} U_k^j(\gamma) \rho U_k^j(\gamma)^\dagger$, and:

$$
U_{1,2}^j(\gamma) = M_{\rm d}^j \left\{ \left(\begin{array}{cc} 1 & 0 \\ 0 & \sqrt{1-\gamma} \end{array} \right), \left(\begin{array}{cc} 0 & 0 \\ \sqrt{\gamma} & 0 \end{array} \right) \right\} (M_{\rm d}^j)^\dagger. (2)
$$

Here, $\gamma_i = 1 - \exp[-\delta \tau_i/T_1^j]$ is the probability of decay for qubit j during $\delta \tau_i$, T_1^j is the excited-state decay time for qubit j, and M_d^j transforms from the instantaneous energy eigenbasis of the *isolated* qubit j at time t_i (decay is assumed to occur in this basis) to the fixed basis of the simulation [\[20](#page-4-5)]. To return to state-vector space at the end of each $\delta \tau_i$, we first write $\rho_i = \sum_k \lambda_i^k |\psi_i^k\rangle \langle \psi_i^k|$. In principle, we could then pick one normalized $|\psi_i^k\rangle$ at random according to the probabilities λ_i^k ; however, since $\lambda_i^k \leq \mathcal{O}(\gamma_i)$ for $k \neq 1$ (with λ_i^k in decreasing order for given i), convergence of the Monte-Carlo sum would require many iterations to sample any of these unlikely events. Instead, we use an expansion procedure. For each noise realization, we run two simulations; for the first, we choose $|\psi_i^1\rangle$ at every time $t_i \in \{t_1 \cdots t_N\}.$ This corresponds to the leading term in a weighted average, having probability $\mathcal{P}_0 \equiv \prod_i \lambda_i^1 \sim \mathcal{O}(1 - t_N/T_1)$. Next, we use the $\{\lambda_i^k\}$ obtained from simulation of the first term to obtain approximate relative probabilities $\mathcal{P}(m, n)$ for the next order terms, sequences of eigenvectors of the form $\{\psi_1^1, \dots, \psi_{n-1}^1, \psi_n^m, \psi_{n+1}^1, \dots, \psi_N^1\}$ with $m \neq 1$ (exactly one unlikely event), as: $\mathcal{P}(m,n) \approx$ $\lambda_1^1 \cdots \lambda_{n-1}^1 \lambda_n^m$ (we neglect the possibility of two or more unlikely events); we then randomly pick one of these terms according to normalized probability distribution: $\mathcal{P}(m,n)/\sum_{m,n}\mathcal{P}(m,n)$, and simulate it. Finally, we combine the density matrices for these two simulations with the relative weights P_0 and $\sum_{m,n} P(m,n) \approx 1 - P_0$.

Figures [3\(](#page-2-0)b) and (c) show a test of this method on a single qubit initially in the state $(| \uparrow \rangle + | \downarrow \rangle)/\sqrt{2}$, under the influence of both 1/f noise and decay. As expected, the excited state decays exponentially, while the coherence does not [Fig. [3\(](#page-2-0)b)]. Decay rates can be extracted from these data, and are shown in Fig. $3(c)$ as a function of ϵ/Δ . The solid line is a prediction, with no free parameters, using the theory from Ref. [21](#page-4-2).

To characterize a gate operation, we run the simulation (in parallel) for each of a set of chosen initial states $|\phi^\nu_0\rangle$ spanning C_2 . From these outputs we can reconstruct the superoperator \mathcal{S}_{op} for the gate (acting on density matrices in C_2), which can be represented as a 16 x 16 matrix acting on "vectors" obtained by stacking the columns of the 4 x 4 density matrix [\[22](#page-4-6)]. For decoherence only (no decay), each iteration is a linear operation, and only four $|\phi_0^{\nu}\rangle$ are required. With decay, however, this is no longer true due to the projection and renormalization,

4

and *sixteen* $|\phi_0^{\nu}\rangle$ are required.

We calculate the maximum error probability: $\mathcal{E} =$ $1 - \min \left[\langle \Psi | S_0^{-1} S_{\text{op}} \rho | \Psi \rangle \right],$ where S_0 is the superoperator corresponding to the desired operation, and maximization is over normalized state vectors $|\Psi\rangle$ in C_2 . Fig-ure [3\(](#page-2-0)d) shows $\mathcal E$ for the CNOT (circles) and Hadamard (triangles) gates, both with spin-echo compensation [fig. [3\(](#page-2-0)a)] (filled symbols) and without it (open symbols), as a function of 1/f-noise amplitude A_{ω} , for $T_1 \rightarrow \infty$ [\[23,](#page-4-7) [24\]](#page-4-8). The spin-echo compensation strongly suppresses errors due to 1/f noise, keeping $\mathcal E$ at or below $\mathcal O(10^{-5})$ up to the noise level observed in Ref. [8](#page-3-7), indicated by the verti-cal dashed line. Figure [3\(](#page-2-0)e) shows $\mathcal E$ for this same noise level as a function of the qubits' excited state lifetime, which would evidently have to be \sim ms for $\mathcal{E} \sim 10^{-5}$. Finally, $(+)$ and (\times) show $\mathcal E$ with noise and decay added only to the coupler qubit, illustrating that although the extra qubit does in principle expose the system to more noise, the present configuration is insensitive to it.

Although $\mathcal E$ can be used to set bounds on faulttolerance thresholds for quantum circuits, the $S_{\rm op}$ generated by these simulations give much more: a full statistical description of the errors that occur for an arbitrary input state. This may provide a means to compute more accurate thresholds for real quantum circuits (assuming that noise correlations between successive operations can be neglected). Furthermore, it may enable the design of optimized error-correction schemes and/or gate operation protocols which target a particular noise source, enabling higher thresholds for fault-tolerance.

This work is sponsored by the United States Air Force under Air Force Contract #FA8721-05-C-0002. Opinions, interpretations, recommendations and conclusions are those of the authors and are not necessarily endorsed by the United States Government.

- [1] Y. Makhlin, G. Schön, A. Shnirman, Rev. Mod. Phys. 73, 357 (2001).
- [2] See, e.g.: A.M. Steane, Phys. Rev. A 68, 42322 (2003); P. Aliferis, D. Gottesman, and J. Preskill, Quant. Inf. Comput. 6, 97 (2006); K.M. Svore, D.P. DiVincenzo, and B.M. Terhal, Quant. Inf. Comput. 7, 297 (2007).
- [3] C. Rigetti, A. Blais, and M. Devoret, Phys. Rev. Lett. 94, 240502 (2005); S. Ashhab, S. Matsuo, N. Hatakenaka, and F. Nori Phys. Rev. B 74, 184504 (2006).
- [4] A.O. Niskanen, Y. Nakamura, and J.-S. Tsai, Phys. Rev. B 73, 094506 (2006)
- [5] P. Bertet, C.J.P.M. Harmans, and J.E. Mooij, Phys. Rev. B 73, 064512 (2006).
- [6] B.L.T. Plourde, *et al.*, Phys. Rev. B **70**, $140501(R)$ (2004); A. Maassen van den Brink, A.J. Berkley, and M. Yalowsky, New J. Phys. 7, 230 (2005); A. Blais, et al., Phys. Rev. A 75, 032329 (2007); Y.X. Liu, L.F. Wei, J.S. Tsai, and F. Nori, Phys. Rev. Lett 96, 067003 (2006).
- [7] T. Hime, et al., Science 314 1427 (2006); S.H.W. van der Ploeg, et al., Phys. Rev. Lett. 98, 057004 (2007); A.O. Niskanen, et al., Science 316, 723 (2007).
- [8] F. Yoshihara, K. Harrabi, A.O. Niskanen, Y. Nakamura, and J.S. Tsai, Phys. Rev. Lett. 97, 167001 (2006).
- [9] K. Kakuyanagi, et al., Phys. Rev. Lett. 98, 047004 (2007).
- [10] R.H. Koch, et al., Phys. Rev. Lett. **96** 127001 (2006).
- [11] T.P. Orlando, *et al.*, Phys. Rev. B **60**, 15398 (1999).
- [12] N. Schuch and J. Siewert, Phys. Rev. A 67, 032301 (2003); M.J. Bremner, et al., Phys. Rev. Lett. 89, 247902 (2002).
- [13] Note that a deviation δ_M^i from the -0.5:1 ratio in Fig. [1\(](#page-0-0)f) gives a term $\delta \hat{H}_{\rm C} = \delta_M^i J_{\rm C} \hat{\sigma}_{\rm C}^z \hat{\sigma}_{i}^z$, whose leading effect arises in the qubit-resonator state transfer. Our simulations show that $\delta_M^i < 0.5\%$ maintains errors of $\mathcal{O}(10^{-5})$. Slowing down the transfer or removing the memory entirely leaves the next order effect from the $C\Phi$ gates, where \sim ten times larger δ_M^i gives $\mathcal{O}(10^{-5})$ errors.
- [14] The same structure could also be obtained by coupling split cooper-pair box qubits with a flux qubit.
- [15] The level structure in Fig. [2\(](#page-1-0)b) also has the property that the parity of the two-qubit state in \mathcal{C}_2 can be directly measured using the coupler energy splitting, which could

be useful for error-correction.

- [16] We simulated the full single-qubit dynamics $(\pm 16 \text{ charge})$ states) under the action of flux and microwave pulses; pulse parameters were chosen to keep nonadiabatic and off-resonant microwave excitation out of the lowest two states below 10⁻⁵. We checked the $n_{ph} = 1$ truncation of resonator photon states by simulating up to $n_{ph} = 3$.
- [17] See, e.g., C. Wei, A.S.M. Windsor, and N.B. Manson, J. Phys. B 30, 4877 (1997).
- [18] We assumed the following physical values: Data qubits: $E_\mathrm{J}/h=175$ GHz, $I_\mathrm{p}=250$ nA, $E_\mathrm{J}/E_\mathrm{C}=40, \beta=0.925,$ and $\Phi_{\Delta} = 371 \text{ m}\Phi_0$; Coupler qubit: $E_J/h = 350 \text{ GHz}$, $I_{\rm p} = 500 \text{ nA}, E_{\rm J}/E_{\rm C} = 160, \beta = 0.375; (\Phi_{\epsilon}, \Phi_{\Delta}) =$ $(0, 179)$ and $(5.44, 0)$ m Φ_0 for the coupled and uncoupled states. Then, $M_{\rm iC} = 10$ pH gives $J_{\rm C}/h \approx 0.3$ GHz.
- [19] For each ϵ and Δ we used 40 independent fluctuators, with average switching rates spaced logarithmically from $\nu_{ir} = 1$ Hz to $\nu_{uv} = 0.2$ GHz, and relative amplitudes chosen to maximize convergence to a 1/f spectrum. Net amplitudes are determined by the slopes $d\epsilon/d\Phi_{\epsilon}$ and

 $d\Delta_i/d\Phi_{\Delta}$. Error rates do depend on ν_{ir} as expected [\[21\]](#page-4-2), but are independent of ν_{uv} for $\nu_{uv} \geq 0.2$ GHz.

- [20] We explicitly neglect any cooperative effects in decay.
- [21] G. Ithier, et al., Phys. Rev. B 72 , 134519 (2005).
- [22] I.L. Chuang and M.A. Nielsen, J. Mod. Opt. 44, 2455 (1997); J.F. Poyatos, J.I. Cirac, and P. Zoller, Phys. Rev. Lett. 78, 390 (1997); T.F.Havel, J. Math. Phys. 44, 534 (2003).
- [23] Our simulations also allow us to determine the controlpulse requirements for $\mathcal{E} \sim 10^{-5}$. For $\Omega_{\mu}(t)$, $\epsilon_{\rm C}(t)$, and Δ _C(t): 8 bit vertical accuracy, 1 ps edge timing; for $\Delta_1(t)$ and $\Delta_2(t)$, 14 bit, 0.2 ps. The latter pair can be relaxed by reducing the qubit-resonator detuning; however, this would also increase off-resonant mixing between them and reduce the resonator lifetime. Removing the resonators entirely is also possible, and will be considered in a future publication.
- [24] The error "floor" for $A_{\omega} \to 0$ is caused by residual nonadiabaticity in the qubit-resonator state transfer.