Designing optimal 2N qubit entangled channels for quantum communication protocols

Sreraman Muralidharan*

Loyola College, Nungambakkam, Chennai - 600 034, India

Siddharth Karumanchi

Birla Institute of Technology and Science, Pilani, Rajasthan- 333031, India

Prasanta K. Panigrahi[†]

Indian Institute of Science Education and Research (IISER) Kolkata, Salt Lake, Kolkata - 700106, India and Physical Research Laboratory, Navrangpura, Ahmedabad - 380 009, India

We introduce a genuinely entangled 2N qubit state which is well suited for teleportation of an arbitrary N qubit state. It can optimally implement algorithms for the quantum information

an arbitrary N qubit state. It can optimally implement algorithms for the quantum information splitting, often in more than one way. With regard to superdense coding, one can send 2N classical bits by sending only N qubits and consuming N ebits of entanglement.

I. INTRODUCTION

Entanglement, arising from non-separability of quantum many-particle states, has been effectively used to perform a range of tasks like teleportation, remote state preparation, dense coding and quantum state splitting between multiple parties [1]. These communication protocols require the participating qubits to be appropriately entangled, which need not be maximal. Quantification of entanglement in multipartite systems is still not well understood [2], which leads to difficulties in making judicious use of this resource for effecting quantum algorithms. As is well known, quantum teleportation is the transfer of information between parties with the help of a distributed entangled state and classical communicational channel. It has been achieved experimentally in many quantum systems [3, 4, 5, 6], as well as over long distances in realistic conditions [7, 8]. The first teleportation scheme was demonstrated by Bennett *et al.* [9], using an Einstein-Podolsky-Rosen (EPR) pair as an entangled resource. The scheme utilizes two entangled bits and two classical bits for communication. In the case of three particles, it has been shown that the GHZ [10] and the asymmetric W state [11, 12] are well suited for teleportation of a single qubit state. The purpose of a proper choice of entangled channel can be appreciated from the fact that the symetric W-state is not useful for teleportation [11].

Teleportation of an arbitrary two qubit state,

$$|\psi\rangle = \alpha|00\rangle + \mu|10\rangle + \gamma|01\rangle + \beta|11\rangle, \tag{1}$$

has been carried out using pairs of entangled Bell states [13, 14], genuinely entangled four qubit channels [15, 16] and the five qubit Brown state [17, 18]. Entanglement is also crucial to quantum information splitting (QIS),

which is the technique of sharing of quantum information among two or more parties, such that none of them can obtain the unknown information by local operations on their own particles. QIS of an unknown single qubit information was first carried out by Hillery *et al.* [19], using the three and four particle GHZ states which was later shown in an asymetric W state [20]. QIS of an arbitrary two qubit state has been demonstrated through the five particle Brown [17] and cluster states [21]. Another topic that is of significant interest, is superdense coding. It is a way of encoding classical information in quantum bits and is closely related with teleportation [22, 27]. Suppose Alice and Bob share an entangled state, namely $|\psi\rangle_{AB}$, then Alice can convert her state into different orthogonal states by applying suitable unitary transforms on her particles. Bob then does appropriate measurements on his gubits to retrieve the encoded information after receiving communication from Alice. It is known that two classical bits per qubit can be exchanged by sending information through a Bell state [27]. One can send four classical bits, by two qubits using two ebits of entanglement or send five classical bits, by three quantum bits, utilizing two ebits of entanglement [17].

Owing to the complexity of multiparticle entangled states, scaling up of algorithms from few particles to many particle scenarios poses significant challenge. Furthermore, decoherence needs to be tackled in maintaining entangled channels over distributed networks. Hence, designing suitable channels, which need not be maximally entangled, but effective in implementing a number of communication protocols is an attractive proposition. In this context, the entangled states accessible for experimental implementation are obviously of significant interest. Varieties of entangled states can be created, by the application of different types of unitary operators on product states. Each entangling unitary operation transforms a product basis into a specific type of entangled state, which may find optimal use in implementing one or more number of protocols. Recently, genuinely entangled 2N [23] and (2N+1) [24] qubit states have been introduced for teleportation. However, one may not need

 $^{{}^*}Electronic \ address: \ sreraman@loyolacollege.edu$

[†]Electronic address: prasanta@prl.res.in

such highly entangled states to carry out specific tasks as entanglement involves cost and is prone to decoherence. In this paper, we demonstrate that appropriate SWAPoperations, make a state well suited for specific quantum communicational purposes like teleportation, information splitting and dense coding. For designing the desired 2N qubit state, one starts with N Bell pairs,

$$|\psi_{+}\rangle_{\otimes N} = \frac{1}{\sqrt{2}} (|00\rangle + |11\rangle)_{\otimes N}.$$
 (2)

Keeping in mind, the implimentation of quantum communication protocols between the last two entities, we perform a SWAP operation between the second and the last qubits:

$$|\psi_{+}\rangle_{\otimes N} \xrightarrow{SWAP(2,2N)} |\zeta_{2N}\rangle,$$
 (3)

which entangles the first and the last pairs. This makes the state usable for quantum communicational purposes, by creating N ebits of entanglement between the first Nand the last N qubits. One can also perform, a SWAPgate on a product of Bell and GHZ state, leading to varieties of entanglement which can be handy for other quantum communicational purposes. As is well known, SWAP gate can be further decomposed into UCNOT gates, making the above scheme amenable to experimental realization.

The state is genuinely entangled according to many measures of entanglement. The von-Neumann entropy between the subsystems $E(\rho_{1,2...,k}|\rho_{k,...,2N}) = k$; hence, for teleporting an arbitrary $k \ (k \leq N)$ qubit state, Alice can have the first k particles and Bob the last (2N-k) particles in $|\zeta_{2N}\rangle$. The monogamy inequality for entanglement is given by [25],

$$\sum_{i=2}^{n} \tau_{A_1 A_i}^2 \le \tau_{A_1 | A_2 \dots A_n}^2; \tag{4}$$

equality holds for the present state and hence there is no residual entanglement. This is the characteristic of a state belonging to the W-state category. The above state is also genuinely entangled according to the recently proposed multiple entropy measures (MEMS) [26]. For N = 3, it has MEMS of $S_1 = 1$, $S_2 = 1.741$ and $S_3 =$ 2.303 respectively, which is more than the entanglement shown by GHZ, W and cluster states. This 2N qubit state can be used for the purpose of teleportation of an unknown N qubit state and for the information splitting of an unknown (N - k) state (k < N). An arbitrary N qubit state that needs to be teleported is of the general form :

$$|\psi_N\rangle = \sum_{i=1}^{2^N} \alpha_i |\psi_i\rangle,\tag{5}$$

where α_i 's are any set of complex numbers satisfying $\Sigma |\alpha_i|^2 = 1$ and $|\psi_i\rangle$'s form the computational basis. The

way in which a given shared multiparticle channel is entangled, plays a pivotal role in deciding the suitability of the channel for teleportation. The general condition for an entangled channel $|\psi\rangle_{AB}$, where A and B refer to the subsystems of Alice and Bob respectively, to be used for teleportation of an arbitrary k qubit state, is that there has to be atleast k ebits of entanglement between them. For instance, in the four particle cluster state, Yeo-Chua state, and the five particle Brown state, there is two ebits of entanglement between A and B. Hence, these states could be used for the perfect teleportation of an arbitrary two qubit state. On the other hand, there is only one ebit of entanglement between A and B, in a symmetrical four particle W state, making it unsuitable for the teleportation of an arbitrary two qubit state. It is interesting to note that, the proposed 2N qubit state to teleport the state in Eq. (5), has the form:

$$\zeta_{2N}\rangle = \sum_{i=1}^{2^N} R(|\psi_i\rangle)|\psi_i\rangle.$$
(6)

Here R is the unitary "Reflection operator", which gives the "mirror image" of a state, through the following transformations,

$$|i_1 i_2 \dots i_N\rangle \stackrel{R}{\to} |i_N i_{N-1} \dots i_1\rangle. \tag{7}$$

For $N = 1, |\zeta_2\rangle$ is a Bell state, the state for N = 2 belongs to the cluster class of states. As is well known, these states are well suited for teleportation of an arbitrary single and two qubit information. For N > 2, the state differs from the cluster class of states.

II. TELEPORTATION OF AN ARBITRARY N QUBIT STATE

In $|\zeta_{2N}\rangle$, there are k $(k \leq N)$ ebits of entanglement between subsystems A and B, in which A comprises of first k particles and B, the last (2N - k) particles, owing to the fact that after we trace out (2N - k) particles, the resulting density matrix is completely mixed. Hence, it can be used for the perfect teleportation of an arbitrary k qubit state. We let Alice possess, particles 1 to Nand Bob, the last N particles. Alice can combine the unknown N qubit state with her particles and prepare the combined state to perform a 2N partite measurement on her particles as,

$$|\psi_C\rangle = \sum_{i=1}^{2^N} \alpha_i |\psi_i\rangle \otimes \sum_{i=1}^{2^N} \xi(|\psi_i\rangle) |\psi_i\rangle = \frac{1}{2^{N/2}} \sum |\phi_{x_i}\rangle U_x(\Sigma \alpha_i |\psi_i\rangle), \tag{8}$$

where $|\phi_x\rangle' s$ form an orthogonal basis of measurement. A general basis can be written in the convienient form,

$$\sum_{l} \sum_{k} (|\psi_l\rangle R |\psi_k\rangle) \ (k \neq l), \ \sum_{i} (|\psi_i\rangle R |\psi_i\rangle) \ (k = l = i).$$
(9)

Alice can convey the outcome of her measurement to Bob via 2N cbits of information. The state of Bob is given by :

$$\sum_{k} \sum_{l} (\alpha_{k} |\psi_{l}\rangle + \alpha_{l} |\psi_{k}\rangle) (k \neq l),$$
$$\sum_{i} \alpha_{i} |\psi_{i}\rangle (k = l = i).$$
(10)

Bob can obtain $|\psi_N\rangle$, by performing an appropriate unitary operation on his particles.

We now explicitly show how this protocol works for the teleportation of an arbitrary three qubit state using $|\zeta_6\rangle$ as a shared entangled channel. The unknown three qubit state that is to be teleported has the form:

$$\begin{aligned} |\psi_3\rangle &= \alpha_1 |000\rangle + \alpha_2 |001\rangle + \alpha_3 |011\rangle + \alpha_4 |111\rangle + \\ \alpha_5 |110\rangle + \alpha_6 |101\rangle + \alpha_7 |100\rangle + \alpha_8 |010\rangle. \end{aligned}$$
(11)

The corresponding entangled channel reads:

$$\begin{aligned} |\zeta_6\rangle &= \frac{1}{2\sqrt{2}} (|000000\rangle + |001100\rangle + |011110\rangle + |111111\rangle \\ &+ |110011\rangle + |100001\rangle + |101101\rangle + |010010\rangle) \end{aligned}$$

Now, Alice can perform a six partite measurement and classically communicate the outcome of her measurement to Bob via six cbits of information. For instance, if Alice measures in the basis

$$\begin{aligned} |\phi_x\rangle_1 &= \frac{1}{2\sqrt{2}} (|000100\rangle + |001000\rangle + |011111\rangle + |11110\rangle \\ &+ |100001\rangle + |100011\rangle + |101010\rangle + |010101\rangle)(13) \end{aligned}$$

the corresponding state obtained by Bob is :

$$\begin{aligned} |\phi_{x_1}\rangle &= \alpha_1 |001\rangle + \alpha_2 |000\rangle + \alpha_3 |111\rangle + \alpha_4 |011\rangle \\ &+ \alpha_5 |100\rangle + \alpha_6 |110\rangle + \alpha_7 |010\rangle + \alpha_8 |100\rangle. \end{aligned}$$
(14)

Bob can perform an unitary transformation and obtain the state in Eq. (11). This completes the teleportation protocol of an arbitrary three qubit state using $|\zeta_6\rangle$.

III. QUANTUM INFORMATION SPLITTING

QIS of a multiparticle system has been a subject of intense investigation. Recently, it has been conjectured [21] that, through a genuinely entangled channel of Nqubits, a maximum of (N - 2n) protocols can be devised for the QIS of an arbitrary n qubit state among two people. According to this, one can devise a maximum of k protocols for QIS of an arbitrary (N - k)state (k < N) using $|\zeta_{2N}\rangle$. A protocol can be considered successful only if, after Alice performs the desired measurement, Bob-Charlie system collapses into a partially entangled state. Hence, protocols in which the Bob-Charlie system becomes a product state is considered a failure. It turns out that some protocols succeed

while others fail using $|\zeta_{2N}\rangle$, as an entangled channel. Let us consider the example of $|\zeta_6\rangle$, for the information splitting of an arbitrary two qubit system. We let Alice, Bob and Charlie possess two particles each. Alice can combine the arbitrary two qubit state with her state and perform a four particle measurement. The Bob-Charlie system collapses into a product state. This protocol fails irrespective of the fact that, Charlie gets the final state. This happens because, there is not enough entanglement between the Bob-Charlie system. On the other hand, we consider a scenario in which Alice possess particles 1,2,3, Bob possesses particle 4 and Charlie possesses 5,6. Alice can combine the arbitrary two qubit state with her particles, perform a five particle measurement and convey the outcome of her measurement to Charlie. Then, the Bob-Charlie system collapses to the entangled state, on which Bob can perform a measurement, in the basis $\frac{1}{\sqrt{2}}(|0\rangle + |1\rangle)$, and communicate the outcome of his measurement to Charlie. Having known the outcomes of both their measurements, Charlie can obtain the state by performing an appropriate unitary operation. Hence, this protocol succeeds. Table 8 summarizes the results of our exhaustive calculations with regard to the sutability of $|\zeta_6\rangle$ and $|\zeta_8\rangle$ for QIS. It is worth mentioning that, for

TABLE I: The protocols that work for QIS

Channel	Information	Protocols
6	1	2
6	2	1
8	1	5
8	2	3
8	3	2

a given N, more number of protocols can be made to succeed, by performing more SWAP operations on the product of Bell states. Moreover, it can be noticed that, for any N, for the information splitting of an arbitrary (N-k) qubit state, the protocol in which Bob possesses a single particle always succeeds. Hence, atleast one protocol succeeds for the QIS of an arbitrary (N-k) qubit state using $|\zeta_{2N}\rangle$ as an entangled channel, making $|\zeta_{2N}\rangle$ as an important resource for QIS.

IV. SUPERDENSE CODING

In the original superdense coding scenario, Alice and Bob share a Bell state. Alice performs a set of unitary operations on his particles and converts their combined state into a set of four orthogonal states and sends it to Bob. Bob can perform a Bell-measurement and recover the unknown information. Let us discuss the general condition for an entangled channel to be used for superdense coding. Let, Alice and Bob share a genuinely entangled channel $|\psi_{AB}\rangle$, where A and B refer to the subsystems of Alice and Bob respectively. If this channel is to be used for sending 2k cbits $(k \leq N)$ by sending k qubits, then there has to be atleast k ebits of entanglement between A and B. The protocol is said to reach the "Holevo bound", when k = N.

We shall now discuss the usefulness of $|\zeta_{2N}\rangle$, for superdense coding. Let, Alice have first k particles in $|\zeta_{2N}\rangle$, and Bob, the remaining (2N - k) particles. Alice can perform unitary operations on her particles and convert it into a set of orthogonal states. For instance, if Alice has first N particles and Bob the remaining N particles, then Alice can apply a set of unitary transforms from the set $(1, \sigma_1, i\sigma_2, \sigma_3)$ on each of her particles and generate 4^N orthogonal states. After performing the unitary operations, Alice can send her particles to Bob. Bob can then perform a measurement and retrieve the classical information. The capacity of superdense coding for $|\zeta_{2N}\rangle$ is given by, $X(\rho^{AB}) = N + N - 0 = 2N$. The Holevo bound of a multipartite 2N qubit quantum state, which the maximum amount of classical information can be encoded [28] is equal to 2N. Thus, the super dense coding reaches the "Holevo bound" allowing 2N classical bits to be transmitted through N quantum bits consuming only N ebits of entanglement. The given entangled channel can also send 2k cbits by sending k qubits while consuming k ebits of entanglement. Thus, this state can also be used instead of the Bell or the cluster states.

V. CONCLUSION

In conclusion, we have introduced a new entangled state for quantum communication purposes like tele-

- M. A. Nielsen and I. L. Chuang, *Quantum Computation and Quantum Information* Cambridge Univ. Press, 2002.
- [2] M. B. Plenio and S. Virmani, eprint quant-ph/0504163.
 [3] D. Bouwmeester, J. W. Pan, K. Mattle, M. Eibl, H. We-
- infurter, and A. Zeilinger, Nature **390**, 575 (1997). [4] M. Riebe, H. Hffner, C. F. Roos, W. Hnsel, J. Benhelm,
- G. P. T. Lancaster, T. W. Krber, C. Becher, F. S. Kaler,
 D. F. V. James, and R. Blatt, Nature 429, 734 (2004).
- [5] M. D. Barrett, J. Chiaverini, T. Schaetz, J. Britton, W. M. Itano, J. D. Jost, E. Knill, C. Langer, D. Leibfried, R. Ozeri, and D. J. Wineland, Nature **429**, 737 (2004).
- [6] I. Marcikic, H. de Riedmatten, W. Tittel, H. Zbinden, and N. Gisin, Nature 421, 509 (2003).
- [7] R. Ursin, F. Tiefenbacher, T. S. Manderbach, H. Weier, T. Scheidl, M. Lindenthal, B. Blauensteiner, T. Jennewein, J. Perdigues, P. Trojek, B. mer, M. Frst, M. Meyenburg, J. Rarity, Z. Sodnik, C. Barbieri, H. Weinfurter, and A. Zeilinger Nature 3, 481 (2007).
- [8] R. Ursin, T. Jennewein, M. Aspelmeyer, R. Kaltenbaek, M. Lindenthal, P. Walther, and A. Zeilinger, Nature 430, 849 (2004).
- [9] C. H. Bennett, G. Brassard, C. Crepeau, R. Jozsa, A. Peres, and W. K. Wootters, Phys. Rev. Lett. 70, 1895 (1993).
- [10] A. Karlsson and M. Bourennane, Phys. Rev. A 58, 4394 (1998).
- [11] V. N. Gorbachev, A. I. Trubilko, and A. A. Rodichkina,

portation, information splitting and superdense coding. These protocols need quantum information to be shared by limited number of parties. Hence, one can have the advantage, by entangling the desired parts, appropriately through a SWAP operator for accomplishing the task. The quantum channel is not maximally entangled which makes them suitable for realistic networks. It is shown that, the proposed state can be used for the teleportation of an arbitrary N qubit state: the protocol works well for the information splitting of an arbitrary (N-k) qubit state. The state is also found to be an excellent resource for superdense coding. The given entangled channel can be used to send 2k chits by sending k qubits while utilizing k ebits of entanglement ($k \leq N$). Considering the simplicity of the quantum operations involved in creating this state, we hope that this state will find experimental realization. We intend to investigate the usefulness of these states for quantum error correction and one way quantum computing. The decoherence properties of this state, also needs a careful investigation.

Phys. Lett. A **314**, 267 (2003).

- [12] P. Agrawal and A. Pati, Phys. Rev. A 74, 062320 (2006).
- [13] J. Lee, H. Min, and S. D. Oh, Phys. Rev. A 66, 052318 (2002).
- [14] G. Rigolin, Phys. Rev. A **71**, 032303 (2005).
- [15] Y. Yeo and W. K. Chua, Phys. Rev. Lett. 96, 060502 (2006).
- [16] Pradhan, P. Agrawal, and A. K. Pati, eprint quantph/0705.1917v1.
- [17] S. Muralidharan and P. K. Panigrahi, Phys. Rev. A 77, 032321 (2008).
- [18] I. D. K. Brown, S. Stepney, A. Sudbery, and S. L. Braunstein, J. Phys. A: Math. Gen. 38, 1119 (2005).
- [19] Mark Hillery, V. Buzek, and A. Berthiaume, Phys. Rev. A 59, 1829 (1999).
- [20] S. B. Zheng, Phys. Rev. A 74, , (054303) 2006.
- [21] S. Muralidharan and P. K. Panigrahi, eprint quantph/0802.0781v1.
- [22] R. F. Werner, J. Phys. A: Math. Gen. 34, 7081 (2001).
- [23] P. X. Chen, S. Y. Zhu, and G. C. Guo, Phys. Rev. A 74, 032324 (2006).
- [24] Z. X. Man, Y. J. Xia, and N. B. An, Phys. Rev. A 75, 052306 (2007).
- [25] V. Coffman, J. Kundu and W.K. Wootters, Phys. Rev. A 61, 052306 (2000).
- [26] D. Liu, X. Zhao, G. L. Long, eprint quantph/0705.3904v4.

- [27] C. H. Bennett and S. J. Wiesner, Phys. Rev. Lett. 69, 2881 (1992).
- [28] D. Bruss, G. M. D'Ariano, M. Lewenstein, C. Macchi-

avello, A. Sen
De, and U. Sen, Phys. Rev. Lett. ${\bf 93},$ 210501 (2004).