

# Universal entangler with photon pairs in arbitrary states

Bing He,<sup>1,\*</sup> János A. Bergou,<sup>1</sup> and Yuhang Ren<sup>1</sup>

<sup>1</sup>*Department of Physics and Astronomy, Hunter College of the City University of New York, 695 Park Avenue, New York, NY 10065, USA*

(Dated: April 24, 2019)

We present a practical setup that transforms a single photon pair in arbitrary state to an approximate Bell state. The setup involves linear optical circuits processing the individual photons and quantum non-demolition (QND) measurements working with weak Kerr nonlinearity. The success probability in the performance is linearly proportional to the fidelity of the input photon pair.

## I. INTRODUCTION

Bell states or the maximally entangled qubits shared by two distant parties, say Alice and Bob, are important resources in quantum communication and quantum cryptography [1]. Since photons are relatively convenient to manipulate with the current technologies, Alice opts for a pair of photons in a polarization Bell state to teleport a qubit to Bob in the distance. She pumps a piece of properly arranged  $\beta$ -barium borate (BBO) crystal with a beam of laser and generates a non-maximally entangled state  $a|HH\rangle + b|VV\rangle$  (H and V respectively stand for horizontal and vertical polarization) in a spontaneous parametric down-conversion (SPDC) process. Although the photon pair can be locally transformed to a Bell state with a certain probability, Alice has to send half of it through an unknown noisy channel to Bob. The photon pair thus evolves in a decoherence process described by a completely positive map [2]. After the process, the correlation between the polarization of the photons will be damaged or even completely destroyed, and Alice and Bob will be left with a photon pair in unknown mixed state, which is disentangled if the photon went through an entanglement-breaking channel [3].

The main approach to restoring the entanglement is to apply entanglement purification protocols [4]. A simple method of purification is to filter a lowly entangled pair to higher fidelity by local operations [5], and has been experimentally investigated with various types of polarization photon pairs [6]. However, the success probability of the procedure will decrease as one improves on the fidelity of the output, since the fidelity of a single copy of a full rank state can not be generally increased by any local operation [7]. All proposed purification protocols beyond local filtering are, therefore, the procedures of extracting entangled pairs with higher fidelity out of a larger number of less-entangled pairs through local operations and classical communications (LOCC). Like an original proposal of Bennett, *et al.* [8], the experiments of entanglement purification or concentration thus far [9] require two identical input photon pairs in one operation step. Moreover, the complete information about the raw

input state should be available and, only then, could one determine if its remnant entanglement or initial fidelity is above the distillation lower bound specified by a particular purification protocol. Under these restrictions, it is impossible to purify a single photon pair in unknown mixed state with all previously proposed methods.

To overcome the above limitation of entanglement purification protocols, we apply a method involving nonlinear Kerr effect to restore the lost entanglement of a decohered photon pair by establishing the quantum correlation between its individual photons. Such quantum correlation is carried from one photon to another by laser beams in coherent states (similar to the approach proposed in Ref. [10]). Coherent states, a type of continuous variable (CV) states, undergo different decoherence processes from single photons in a noisy channel [11]. In their transmission, the dominant decoherence effect is the amplitude damping due to photon losses (see, e.g., [12]). We realize the transformation from any mixed-state photon pair to an approximate Bell state by comparing two coherent beams transmitted through an amplitude damping channel (e.g., lossy optical fiber), together with processing the individual photons by two linear optical circuits.

## II. NOTATION

In what follows, we adopt a notation of operator-vector duality [13] for a bipartite quantum state. This notation provides a natural correspondence between a bipartite pure state  $|\Lambda\rangle$  and its coefficient matrix  $\Lambda$ . One example of such correspondence is in the following expression for the Bell states in a which-path space (the indexes 1 and 2 represent two paths on both Alice and Bob's sides):

$$|B_{ij}\rangle = (\hat{a}_{A,1}^\dagger, \hat{a}_{A,2}^\dagger) B_{ij} \begin{pmatrix} \hat{a}_{B,1}^\dagger \\ \hat{a}_{B,2}^\dagger \end{pmatrix} |0\rangle, \quad (1)$$

with their coefficient matrices  $B_{ij}$  defined as

$$\begin{aligned} B_{00} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}, & B_{01} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}, \\ B_{10} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, & B_{11} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix}. \end{aligned} \quad (2)$$

---

\*Electronic address: bhe98@earthlink.net

We divide them into the even parity set with  $\Lambda_+ = B_{00}$  or  $B_{01}$  and the odd parity set with  $\Lambda_- = B_{10}$  or  $B_{11}$ . The states corresponding to  $\Lambda_+$  and  $\Lambda_-$  are transformed from the polarization Bell states  $|\Phi^\pm\rangle = 1/\sqrt{2}(|HH\rangle \pm |VV\rangle)$  and  $|\Psi^\pm\rangle = 1/\sqrt{2}(|HV\rangle \pm |VH\rangle)$ , respectively. With the notation, the action of two local operations  $A$  and  $B$  from Alice and Bob, respectively, is given as follows ( $T$  represents the matrix transpose):

$$A \otimes B|\Lambda\rangle = |AAB^T\rangle. \quad (3)$$

### III. UNITARY TRANSFORMATIONS

To restore the entanglement of a polarization photon pair mixed with noise, we first convert it to a which-path space by polarization beam splitters (PBS). Then the input photon pair in arbitrary mixed state takes the form

$$\begin{aligned} \rho_{in} = & \sigma_1|\Lambda_1\rangle\langle\Lambda_1| + \sigma_2|\Lambda_2\rangle\langle\Lambda_2| + \sigma_3|\Lambda_3\rangle\langle\Lambda_3| \\ & + \sigma_4|\Lambda_4\rangle\langle\Lambda_4|, \end{aligned} \quad (4)$$

where the pure state components  $|\Lambda_k\rangle = \sum_{i,j} \kappa_{k,ij} |B_{ij}\rangle$  and the non-negative coefficients  $\sigma_k$  ( $k$  ranges from 1 to 4, and  $i, j$  are 0 and 1) could be unknown to the sharing parties Alice and Bob. Any pure state component  $|\Lambda\rangle$  (a linear combination of Bell states) in a general input can be embedded in a larger space with the local operations performed in the extended space [14]. For example, if Alice and Bob respectively perform the identical rotation

$$U_1 = \frac{1}{\sqrt{2}} \begin{pmatrix} I & I \\ -I & I \end{pmatrix} \quad (5)$$

in the extended spaces, they will obtain a  $4 \times 4$  bipartite state  $|\Sigma\rangle$  with the coefficient matrix

$$\Sigma = U_1 \begin{pmatrix} \Lambda & 0 \\ 0 & 0 \end{pmatrix} U_1^T = \frac{1}{2} \begin{pmatrix} \Lambda & -\Lambda \\ -\Lambda & \Lambda \end{pmatrix}. \quad (6)$$

Fig. 1 illustrates how to implement the above transformation with linear optical circuit. All components of the processed photons could be first transformed to, e.g., horizontal polarization  $H$  with half wave plates (HWP or  $\lambda/2$  in Fig. 1). In the later steps, we will only show the necessary transformations on the coefficient matrix  $\Lambda$ , since any unitary transformation on a single photon in which-path space corresponds to a linear optical circuit [15].

The second local unitary transformation to apply is

$$U_2 = \begin{pmatrix} 0 & iV \\ I & 0 \end{pmatrix} = \begin{pmatrix} iV & 0 \\ 0 & I \end{pmatrix} \begin{pmatrix} 0 & I \\ I & 0 \end{pmatrix}, \quad (7)$$

in which

$$V = \begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix}. \quad (8)$$

Under the joint operation  $U_2$  of Alice and Bob, the bipartite state  $|\Sigma\rangle$  is transformed to another state  $|\Xi\rangle$  with the coefficient matrix

$$\Xi = U_2 \Sigma U_2^T = \frac{1}{2} \begin{pmatrix} -V\Lambda V^T & -iV\Lambda \\ -i\Lambda V^T & \Lambda \end{pmatrix}. \quad (9)$$

For the Bell states of different parity, three of the submatrices in Eq. (9) (up to the coefficients) are calculated as follows:

$$\begin{aligned} V\Lambda_+V^T &= \begin{pmatrix} \lambda_2 & 0 \\ 0 & \lambda_1 \end{pmatrix}, & V\Lambda_+ &= \begin{pmatrix} 0 & \lambda_2 \\ -\lambda_1 & 0 \end{pmatrix}, \\ \Lambda_+V^T &= \begin{pmatrix} 0 & -\lambda_1 \\ \lambda_2 & 0 \end{pmatrix}; \\ V\Lambda_-V^T &= \begin{pmatrix} 0 & -\lambda_2 \\ -\lambda_1 & 0 \end{pmatrix}, & V\Lambda_- &= \begin{pmatrix} \lambda_2 & 0 \\ 0 & -\lambda_1 \end{pmatrix}, \\ \Lambda_-V^T &= \begin{pmatrix} \lambda_1 & 0 \\ 0 & -\lambda_2 \end{pmatrix}. \end{aligned} \quad (10)$$

$\Lambda_+$  here are diagonal with the entries  $\lambda_1 = 1/\sqrt{2}$  and  $\lambda_2 = \pm 1/\sqrt{2}$ , while  $\Lambda_-$  off-diagonal with the entries  $\lambda_1 = 1/\sqrt{2}$  and  $\lambda_2 = \pm 1/\sqrt{2}$ .

### IV. NON-UNITARY TRANSFORMATION

Next, we will project a general input  $\rho_{in}$  onto a subspace spanned by only two of the Bell states. One more local operation performed by Alice and Bob is

$$K = \frac{1}{\sqrt{2}} \begin{pmatrix} 0 & 0 \\ I & I \end{pmatrix} = \begin{pmatrix} 0 & 0 \\ 0 & I \end{pmatrix} \begin{pmatrix} \frac{1}{\sqrt{2}}I & -\frac{1}{\sqrt{2}}I \\ \frac{1}{\sqrt{2}}I & \frac{1}{\sqrt{2}}I \end{pmatrix}, \quad (11)$$

which is the product of a projection and a rotation.  $K$  can be realized by a unitary operation in a further extended space of 8 dimension [16]. Only two 50/50 beam splitters, two totally reflecting mirrors and the proper phase shifters are required to construct its circuit. The transitional bipartite state  $|\Xi\rangle$  is transformed by the non-unitary map to  $|\Lambda'\rangle$ , with its coefficient matrix being

$$\Lambda' = K\Xi K^T = \frac{1}{4} \begin{pmatrix} 0 & 0 \\ 0 & \Lambda - V\Lambda V^T - iV\Lambda - i\Lambda V^T \end{pmatrix}. \quad (12)$$

Substituting the results of Eq. (10) into the non-zero block of  $\Lambda'$ , we see that those corresponding to the input of  $\Lambda = B_{00}$  and  $B_{11}$  will vanish. The output,  $|\Lambda'\rangle = (\hat{a}_{A,1'}^\dagger, \hat{a}_{A,2'}^\dagger)\Lambda'(\hat{a}_{B,1'}^\dagger, \hat{a}_{B,2'}^\dagger)^T|0\rangle$ , is on the tracks  $1'$  and  $2'$  shown in Fig. 2. If  $|\Lambda\rangle = |B_{ij}\rangle$ , we will realize the following non-unitary transformations for the Bell states

$$\begin{aligned} |\Phi^+\rangle &\rightarrow 0, & |\Phi^-\rangle &\rightarrow \frac{1}{2}(|\Phi^-\rangle + i|\Psi^+\rangle), \\ |\Psi^-\rangle &\rightarrow 0, & |\Psi^+\rangle &\rightarrow \frac{1}{2}(|\Psi^+\rangle - i|\Phi^-\rangle), \end{aligned} \quad (13)$$

after we convert such outputs back to the polarization space by using HWP and PBS again. Each pure state component of a general input  $\rho_{in}$  is therefore transformed to the subspace spanned by  $\{|\Phi^-\rangle, |\Psi^+\rangle\}$ .

## V. COHERENT STATES COMPARISON

Now we use an example of the even parity Bell states mixture,  $\chi_1|\Phi^+\rangle\langle\Phi^+| + \chi_2|\Phi^-\rangle\langle\Phi^-|$ , to illustrate the general result. After being processed by circuit A and B shown in Fig. 2, the total output from the mixture will be

$$\begin{aligned} \rho_{out} &= \chi_1|\Omega_1\rangle\langle\Omega_1| + \chi_2 \left( \frac{1}{2}(|\Phi^-\rangle + i|\Psi^+\rangle) + |\Omega_2\rangle \right) \\ &\times \left( \frac{1}{2}(|\Phi^-\rangle - i|\Psi^+\rangle) + |\Omega_2\rangle \right), \end{aligned} \quad (14)$$

where  $|\Omega_1\rangle$  is the cross terms between the ports  $R_A$ ,  $R_B$  and  $K_A$ ,  $K_B$ , and  $|\Omega_2\rangle$  the output components from the ports  $R_A$  and  $R_B$ . The desired components are projected out of  $\rho_{out}$  by comparing the coherent beams of two quantum non-demolition measurement (QND) modules in Fig. 3, which are coupled to track  $K_A$  or  $K_B$ . Under the action of a 50/50 beam splitter in each module, the unnormalized state involving the components on tracks  $K_A$ ,  $K_B$  and the coherent beams in both modules of Alice and Bob will be

$$\begin{aligned} |\psi_{out}\rangle_{K_A, K_B} &= (|\Phi^-\rangle + i|\Psi^+\rangle) \\ &\otimes \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} - 1) \right\rangle_{A,1} \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} + 1) \right\rangle_{A,2} \\ &\otimes \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} - 1) \right\rangle_{B,1} \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} + 1) \right\rangle_{B,2}. \end{aligned} \quad (15)$$

The first coherent beam (with the index 1 in the above equation) in each module is detected by a photodiode, and a response indicates the presence of a photon on track  $K_A$  or  $K_B$ . The success probability of the coherent states comparison is  $P_{succ} = 1 - \exp(-\frac{1}{2}|\alpha - \alpha e^{i\theta}|^2)$  [17]. With a small phase shift  $\theta \sim 10^{-5}$ , for example, it is sufficient to use a coherent light with the amplitude  $|\alpha| \sim 2\sqrt{5} \times 10^5$  ( $\alpha\theta \sim 2\sqrt{5}$ ) for achieving a close to unit success probability.

After that, we continue to couple the photonic components detected by Bob to two more coherent beams  $|\alpha\rangle$  as shown in Fig. 2, evolving the state of the total system to

$$\begin{aligned} |\psi_1\rangle &= (|H\rangle_A + i|V\rangle_A) \\ &\otimes (|H\rangle_B|\alpha e^{i\theta}\rangle_1|\alpha\rangle_2 + i|V\rangle_B|\alpha\rangle_1|\alpha e^{i\theta}\rangle_2). \end{aligned} \quad (16)$$

The two coherent beams are transmitted to Alice, while the state of the processed single photon of Bob could be stored in a kind of quantum memory. Alice also interacts the received coherent beams with her processed photon as shown in Fig. 2, and then transforms the total state with two phase shifters to (we neglect the unwanted pure state components due to decoherence, which can be reduced to vanishing percentage by choosing the proper parameters  $\alpha$  and  $\theta$ )

$$\begin{aligned} |\psi_2\rangle &= (|HH\rangle - |VV\rangle)|\alpha'\rangle_1|\alpha'\rangle_2 + i|VH\rangle|\alpha'e^{i\theta}\rangle_1|\alpha'e^{-i\theta}\rangle_2 \\ &+ i|HV\rangle|\alpha'e^{-i\theta}\rangle_1|\alpha'e^{i\theta}\rangle_2, \end{aligned} \quad (17)$$

where  $|\alpha'\rangle$  is with a reduced amplitude of  $|\alpha\rangle$  due to the loss in transmission. We should amplify the two being transmitted coherent beams by applying a displacement  $D(\beta)$ , where  $\beta = |\beta|e^{i(\frac{\theta}{2} + \pi)}$ , to compensate for the losses if the distance between Alice and Bob is too large. The displacement of a coherent beam can be realized by injection-locked nonlinear amplifier (see, e.g., [18]). The linear optical implementation of this displacement operation can be found in, e.g., [19]. Then, the phase shift  $\theta$  at Alice's location could become a different value. Finally, the total state is transformed by a 50/50 beam splitter to the following:

$$\begin{aligned} |\psi_2\rangle &\rightarrow (|HH\rangle - |VV\rangle)|0\rangle_1|\sqrt{2}\alpha'\rangle_2 \\ &+ i|VH\rangle\left|\frac{1}{\sqrt{2}}\alpha'(e^{i\theta} - e^{-i\theta})\right\rangle_1\left|\frac{1}{\sqrt{2}}\alpha'(e^{i\theta} + e^{-i\theta})\right\rangle_2 \\ &+ i|HV\rangle\left|\frac{1}{\sqrt{2}}\alpha'(e^{-i\theta} - e^{i\theta})\right\rangle_1\left|\frac{1}{\sqrt{2}}\alpha'(e^{i\theta} + e^{-i\theta})\right\rangle_2. \end{aligned} \quad (18)$$

We use only simple photodiodes that are unable to resolve photon numbers to separate the even and the odd parity sectors of the above state. The second coherent state here could be compared with another state  $|\frac{1}{\sqrt{2}}\alpha'(e^{i\theta} + e^{-i\theta})\rangle_3$  prepared by Alice. Under the action of one more 50/50 beam splitter, it will be transformed to  $|\frac{1}{2}\alpha'(1 - e^{i\theta}) + \frac{1}{2}\alpha'(1 - e^{-i\theta})\rangle_2$  in the even parity sector, but the vacuum state  $|0\rangle_2$  in the odd parity sector. Therefore, we have such detection pattern for the resulting state: if a photodiode responds to the first coherent beam, we will obtain a mixture of the odd parity Bell states  $|\Psi^+\rangle$  and  $|\Psi^-\rangle$ ; and if the second coherent beam is detected, any input will be purified to  $|\Phi^-\rangle$ .

## VI. EXAMPLES

Given an input photon pair in any bipartite state, the setup will transform it to an exact Bell state by the corresponding probability, if the photon absorption losses of the being transmitted coherent beams are negligible. As a typical example, a Werner state,  $F|\Phi^-\rangle\langle\Phi^-| + \frac{1-F}{4}I_4$ , can be transformed to  $|\Phi^-\rangle$  with a success probability  $(F + 1)/8$ . The setup works for the whole range of its initial fidelity  $0 \leq F < 1$ .

Another interesting case is the mixture of an even and an odd parity Bell states. A photon pair in the state  $F|\Phi^+\rangle\langle\Phi^+| + (1-F)|\Psi^+\rangle\langle\Psi^+|$ , which could be asymptotically purified with linear optics only under the condition  $F > 1/2$  [20], can be directly separated to  $|\Phi^+\rangle$  with a success probability  $F$  if we use a simplified setup (without the photon pairs being processed by the circuit A and B in Fig. 2).

## VII. ERROR ELIMINATION

The photon absorption loss is the dominant decoherence effect for the transmitted coherent beams. It will lead the final output to a mixture of Bell states [10]. Such loss over a segment of optical fiber is modeled by a beam splitter of reflectivity  $\eta$  which discards a portion of the beam to the environment [12]. Under this decoherence effect, the state involving Bob's photon and two coherent beams in Eq. (16) will evolve to

$$\rho_{B,1,2} = \frac{1 + |\chi|^2}{2} |\Phi^1\rangle_{B,1,2} \langle \Phi^1| + \frac{1 - |\chi|^2}{2} |\Phi^2\rangle_{B,1,2} \langle \Phi^2|, \quad (19)$$

where

$$\begin{aligned} |\Phi^1\rangle_{B,1,2} &= |H\rangle_B |\sqrt{1-\eta}\alpha\rangle_1 |\sqrt{1-\eta}\alpha e^{i\theta}\rangle_2 \\ &\quad + i|V\rangle_B |\sqrt{1-\eta}\alpha e^{i\theta}\rangle_1 |\sqrt{1-\eta}\alpha\rangle_2, \\ |\Phi^2\rangle_{B,1,2} &= |H\rangle_B |\sqrt{1-\eta}\alpha\rangle_1 |\sqrt{1-\eta}\alpha e^{i\theta}\rangle_2 \\ &\quad - i|V\rangle_B |\sqrt{1-\eta}\alpha e^{i\theta}\rangle_1 |\sqrt{1-\eta}\alpha\rangle_2 \end{aligned} \quad (20)$$

and  $|\chi| = |\langle \sqrt{\eta}\alpha e^{i\theta} | \sqrt{\eta}\alpha \rangle|$ . We can effectively eliminate the undesired component  $|\Phi^2\rangle_{B,1,2}$  by choosing the proper parameters of the transmitted coherent beams such that  $|\chi|^2 \sim 1$ . For example,  $|\alpha|$  can be set in the order of  $10^3$  if the phase  $\theta$  induced by the weak Kerr media is in the order  $10^{-5}$ . Then, the fidelity of the state in Eq. (20) will be larger than  $1 - 10^{-4}$  upon the first necessary amplification in transmission channel. After the transmission, the two coherent beams should be amplified to the amplitude satisfying  $\alpha'\theta \sim 2\sqrt{5}$ , so that their comparison can be realized in a near deterministic way.

To guarantee the perfect coherent states comparison at the final step, we can also transmit the two coherent beams through the same channel. Then the possible extra phase  $\phi$  gained by the two coherent beams in transmission (the effect of an unknown phase shifter) will be

identical. If the coherent beams are in pulse mode, for instance, we will fulfill such requirement by sending them within a very short period of time in optical fiber [21]. On the other hand, if the amplification enroute is necessary, we should determine the phase  $\phi$  by measuring the quadratures of the test beams prepared in the states  $|\alpha\rangle$  and  $|\alpha e^{i\theta}\rangle$ .

## VIII. CONCLUSION

We have illustrated a simple setup that transforms a photon pair mixed with noise to an approximate Bell state, even if the entanglement of the pair is totally lost in an unknown noisy channel. The system entangles an arbitrary photon pair as fast as one-way classical communication. A close to ideal fidelity and a much higher success probability than those of the entanglement purification protocols can be achieved by the setup. Since the input photon pair is never damaged throughout the process, it will be directly sent back to the linear optical circuits for the second round operation in case that a failure event is indicated by the photodiodes response pattern. Through the interaction between coherent light and matter qubits [22], it is possible to realize the purification of entangled spin-half particles in the mixtures of different parity Bell states by a corresponding extension of the setup. The setup could be found various applications in quantum communication and quantum computation.

## Acknowledgments

This work is supported in part by the Petroleum Research Fund and PSC-CUNY award.

- 
- [1] A. K. Ekert, Phys. Rev. Lett. **67**, 661 (1991); C. H. Bennett and S. J. Wiesner, Phys. Rev. Lett. **69**, 2881 (1992); C. H. Bennett, *et al.*, Phys. Rev. Lett. **70**, 1895 (1993).  
[2] W. Dür *et al.*, Phys. Rev. A **72**, 052326 (2005).  
[3] M. Horodecki, P. W. Shor and M. B. Ruskai, Rev. Math. Phys. **15**, 629 (2003).  
[4] W. Dür and H. J. Briegel, Rep. Prog. Phys. **70**, 1381 (2007).  
[5] N. Gisin, Phys. Lett. A **210**, 151 (1996); F. Verstraete, *et al.*, Phys. Rev. A **64**, 010101(R) (2001).  
[6] P. G. Kwiat, *et al.*, Nature **409**, 1014 (2001); N. A. Peters, *et al.*, Phys. Rev. Lett. **92**, 133601 (2004); Z.-W. Wang, *et al.*, Phys. Rev. Lett. **96**, 220505 (2006).  
[7] N. Linden, *et al.*, Phys. Rev. Lett. **81**, 3279 (1998); A. Kent, Phys. Rev. Lett. **81**, 2839 (1998).  
[8] C. H. Bennett, *et al.*, Phys. Rev. Lett. **76**, 722 (1996).  
[9] J.-W. Pan, *et al.*, Nature **423**, 417 (2003); T. Yamamoto, *et al.*, Nature **421**, 343 (2003); Z. Zhao, *et al.*, Phys. Rev. Lett. **90**, 207901 (2003); P. Walther, *et al.*, Phys. Rev. Lett. **94**, 040504 (2005).  
[10] W. J. Munro, *et al.*, New J. Phys. **7**, 137 (2005).  
[11] A. Serafini, *et al.*, J. Opt. B: Quantum Semiclass. Opt. **7**, R19 (2005).  
[12] J. K. Asbóth, *et al.*, Eur. Phys. J. D **30**, 403 (2004); S. J. van Enk, Phys. Rev. A **72**, 022308 (2005).  
[13] G. M. D'Ariano, *et al.*, Phys. Lett. A **272**, 32 (2000); J. Calsamiglia, Phys. Rev. A **65**, 030301(R) (2002); C. Li, *et al.*, Phys. Lett. A **297**, 121 (2002).  
[14] B. He and J. A. Bergou, Arxiv: 0708.4184 (2007).  
[15] M. Reck, *et al.*, Phys. Rev. Lett. **73**, 58 (1994).  
[16] B. He, *et al.*, Phys. Rev. A **76**, 042326 (2007).  
[17] E. Andersson, *et al.*, Phys. Rev. A **74**, 022304 (2006).  
[18] G. J. Kweon, J. Korean Phys. Soc. **41**, 617 (2002).  
[19] M. Takeoka and M. Sasaki, arXiv: 0706.1038 (2007).  
[20] J.-W. Pan, *et al.*, Nature **410**, 1067 (2001).  
[21] T. Yamamoto, *et al.*, arXiv: 0806.2896 (2008).

[22] P. van Loock, *et al.*, Phys. Rev. Lett. **96**, 240501 (2006).

Caption of Fig.1: Linear optical implementation of the local unitary operation  $U_1$ . As a part of the linear optical circuits A or B in Fig. 2, two 50/50 beam splitters transform the input  $2 \times 2$  bipartite state to a  $4 \times 4$  bipartite state. Then the output on the tracks from 1 to 4 will be processed further.

Caption of Fig.2: Two linear optical circuits A and B process the input photon pair from the ports  $A1$  and  $B1$ . Out of the ports  $K_A$  and  $K_B$ , any output will be the linear combination of only  $|\Phi^-\rangle$  and  $|\Psi^+\rangle$ . At Bob's location, the first coherent beam interacts with the  $H$  component of his photon in Kerr medium, while the second with the  $V$  component. Transmitted to Alice, the beams are coupled to her photon in the opposite way, and are transformed by two phase shifters to different

forms in the even parity and the odd parity sector of the photon pair state as in Eq. (17). The comparison of the two beams by a 50/50 beam splitter and a photodiode D will discriminate the difference, and a purified photon pair will be obtained over the ports  $A2$  and  $B2$ . The unmeasured coherent state C can be compared with another locally prepared state to confirm the generation of the state  $|\Phi^-\rangle$ .

Caption of Fig.3: One of the probe coherent beams  $|\alpha\rangle$  of the QND module is coupled to the photonic components on  $K_A$  or  $K_B$  through Kerr medium, picking up a phase shift  $\theta$  if the photon is present. The 50/50 beam splitter transforms two coherent states  $|\alpha\rangle_1|\beta\rangle_2$  to  $|\frac{\alpha-\beta}{\sqrt{2}}\rangle_1|\frac{\alpha+\beta}{\sqrt{2}}\rangle_2$  (with the proper phase shifters). A response of the photodiode D indicates that the two beams  $|\alpha\rangle_1$  and  $|\beta\rangle_2$  are different with  $|\frac{\alpha-\beta}{\sqrt{2}}\rangle_1 \neq |0\rangle_1$ .





