

Creation of perfect long-distance quantum communication channel

Bing He,^{1,*} Yuhang Ren,¹ and János A. Bergou¹

¹*Department of Physics and Astronomy, Hunter College of the City University of New York, 695 Park Avenue, New York, NY 10065*

The generation of entangled states of high fidelity over long distances is an extremely difficult task in quantum communications. All previously proposed approaches to distributing long-distance entanglement, for example, the quantum repeater protocols, are beyond the technologies in the near future. We present a realizable system that directly sets up an entangled pair of close to unit fidelity with Bell state between the remote locations. Only one photon pair in arbitrary state is used as the resource. The setup achieves a high success probability of 50% per try in the realistic situation. The time for realizing the entanglement is reduced to that of one-way classical communication between two distant locations. The method we propose significantly simplifies the implementation of long-distance quantum communications.

The realization of quantum communication and quantum cryptography relies on setting up entanglement of high fidelity between two far-away physical systems. In practice, photons are primarily used for the carrier of entanglement [1]. If one tries to establish entanglement by sending photons directly to a remote place, however, the range of communication will be limited by their absorption losses in the transmission channel. The previous solutions, including the quantum repeaters [2, 3, 4] and the quantum networks with percolation strategies [5, 6], require the resources (qubits or other quantum states connected in numerous entangled pairs over short distances) increasing with the communication distance to build up a communication channel. For example, in the quantum repeater realization of Duan, *et al.* [7], which has dominated the direction of developmental research in recent years [8, 9, 10, 11, 12, 13] and also has its ingredients experimentally demonstrated [14, 15, 16], a large number of entanglement generation and swapping procedures are performed through the coupling of photons and collective atomic excitation modes. The errors and inefficiencies in all these operations cause the memory time for the processed quantum states to grow polynomially with the communication distance. A recent theoretical analysis [13] shows that the minimum average time for distributing an entangled pair over 1200 km is about a half minute, far beyond the capacity of quantum memory in the near future. The other type of implementation for quantum repeaters, hybrid or qubus repeaters [17, 18, 19], improve on operation efficiency but generate entangled pairs with the lower fidelity, which necessitate much more time to purify.

In this work we propose a completely new conception that directly sets up entanglement approaching the exact Bell state between two far-away locations. We reduce the quantum memory time to that of one-way classical communication from one place to another (e.g. the time is only a few milliseconds for the distance of 1200 km). This linearly increasing generation time with the distance has

reached the limit of the causality between two spatially separated events, i.e., there will be no further improvement on the time of creating an entangled pair directly between two points. Moreover, the constant resources required by the scheme are minimal and flexible. Only one photon pair (two qubits) in arbitrary state is used to generate a close to Bell state between two distant locations.

We start with the purification of the photon sources used in our scheme. The output of a realistic single-photon source in a certain mode is a mixture of single photon Fock state $|1\rangle$ and vacuum $|0\rangle$, $\rho = p|1\rangle\langle 1| + (1-p)|0\rangle\langle 0|$, where p is the efficiency of the source (see, e.g., [20]). To sift the vacuum component out of the mixture, we apply a quantum non-demolition (QND) measurement module illustrated in Fig. 1. In the module, one of the laser beams in coherent state $|\alpha_0\rangle$ interacts with ρ through a weak Kerr nonlinear medium, picking up a small phase shift $\theta \ll 1$ to $|\alpha_0 e^{i\theta}\rangle$ if the single photon is present. The two coherent states after the interaction are compared with a 50/50 beam splitter and a simple photodiode. Any response of the photodiode indicates that the coherent states are different as $|\alpha_0\rangle$ and $|\alpha_0 e^{i\theta}\rangle$, projecting the mixture ρ to a pure state of single photon. The success probability of the coherent states comparison is $P_{succ} = 1 - \exp(-\frac{1}{2}|\alpha_0 - \alpha_0 e^{i\theta}|^2)$ [21]. It will be ideal to achieve the deterministic purification of the photon sources if $\alpha_0 \theta \gg 1$. Although it is possible to realize a considerably large phase shift with electromagnetically induced transparency (EIT) Kerr nonlinearity [22], for all coherent states comparison procedures in our scheme, we relax the requirement for the nonlinearity to that of generating the smallest phase shift ($\theta \sim 10^{-7}$) to be resolved by the present technology. For the phase shift of this order we will apply the coherent beams with $|\alpha_0| \sim 10^8$ to obtain a near deterministic result.

Next, we respectively process two purified single photons at two different locations A and B with a linear optical circuit. The purpose of the procedure is to transform a photon pair in arbitrary bipartite state ρ_{in} (much more general than the product of those for two single photon sources with the vacuum components removed) to a

*Electronic address: bhe98@earthlink.net

subspace spanned by only two Bell states. Here we represent the state of input photon pair in the Bell state basis $\{|\Phi^\pm\rangle = 1/\sqrt{2}(|HH\rangle \pm |VV\rangle), |\Psi^\pm\rangle = 1/\sqrt{2}(|HV\rangle \pm |VH\rangle)\}$, with H and V respectively representing horizontal and vertical polarizations. The states $|\Phi^\pm\rangle$ are called even parity and $|\Psi^\pm\rangle$ odd parity, respectively. A simple case of the input is $|HH\rangle = 1/\sqrt{2}(|\Phi^+\rangle + |\Phi^-\rangle)$, i.e., we horizontally polarize both of the purified photons, which are input from the terminals A1 and B1 in Fig. 2. Then, with two polarization beam splitters (PBS), we convert any input to a which-path space with the following transformed basis:

$$\begin{aligned} |\Phi^\pm\rangle &\rightarrow \frac{1}{\sqrt{2}}(\hat{a}_{A,1}^\dagger \hat{a}_{B,1}^\dagger \pm \hat{a}_{A,2}^\dagger \hat{a}_{B,2}^\dagger)|0\rangle, \\ |\Psi^\pm\rangle &\rightarrow \frac{1}{\sqrt{2}}(\hat{a}_{A,1}^\dagger \hat{a}_{B,2}^\dagger \pm \hat{a}_{A,2}^\dagger \hat{a}_{B,1}^\dagger)|0\rangle. \end{aligned} \quad (1)$$

The polarization of the photon components on both path 1 and 2 can be transformed to H with half wave plates (HWP or $\lambda/2$ in Fig. 2) for the time being. An input state in the which-path space is then embedded in a larger space with the local operations performed in the extended space (see Appendix A).

There is a symmetry in the entangled states of Eq. (1): in each class transformed from $|\Phi^\pm\rangle$ and $|\Psi^\pm\rangle$, respectively, one of the states is invariant under the permutation of the index 1 and 2 while the other changes the sign. With this symmetry, we design the linear optical circuits A and B in Fig. 2 (see Appendix A). Under the processing of the two circuits, any pure state component in a general input ρ_{in} will be mapped to the superposition of four bipartite states over the pairs of tracks $\{K_A, K_B\}$, $\{R_A, R_B\}$, $\{K_A, R_B\}$ and $\{R_A, K_B\}$, respectively. Over the tracks K_A and K_B (or R_A and R_B), the output is the linear combination of only $|\Phi^-\rangle$ and $|\Psi^+\rangle$; over the other two groups of tracks $\{K_A, R_B\}$ and $\{R_A, K_B\}$, on the other hand, it is spanned by the other fixed set of Bell states $\{|\Phi^+\rangle, |\Psi^-\rangle\}$. Only 50/50 beam splitters, totally reflecting mirrors and the proper phase shifters are required to construct the circuit A and B, which implement the necessary maps of single photon states [23, 24]. If we project any of the four pieces of bipartite states out of the total output, the resulting state from a general ρ_{in} will be in a subspace spanned by only two Bell states, one even parity but the other odd parity. Such projection can be done by four QND modules shown in Fig. 1 (see Appendix B). For example, by detecting the components on K_A and K_B merged from the tracks 1' and 2' (at both locations) with HWP and PBS, we will realize the following non-unitary maps of the basis vectors:

$$\begin{aligned} |\Phi^+\rangle &\rightarrow 0, & |\Phi^-\rangle &\rightarrow \frac{1}{2}(|\Phi^-\rangle + i|\Psi^+\rangle), \\ |\Psi^-\rangle &\rightarrow 0, & |\Psi^+\rangle &\rightarrow \frac{1}{2}(|\Psi^+\rangle - i|\Phi^-\rangle). \end{aligned} \quad (2)$$

The input $|HH\rangle$, e.g., will be correspondingly transformed to $1/(2\sqrt{2})(|\Phi^-\rangle + i|\Psi^+\rangle)$, which is separable as

$(|H\rangle_A + i|V\rangle_A)(|H\rangle_B + i|V\rangle_B)$ with the common constant neglected.

With this example, we demonstrate how to extract a Bell state by separating the even and the odd parity sectors of the output from any of the pure state components in an input ρ_{in} . As illustrated in Fig. 2, we continue to interact two identical coherent beams $|\alpha\rangle$ with the detected photon on track K_B (in Fig. 2 we draw the interaction points before the second PBS to save the space for two more PBS decomposing and merging the polarization components again) through two weak Kerr nonlinearities, evolving the state of the total system to

$$\begin{aligned} |\Psi_1\rangle_{tot} &= (|H\rangle_A + i|V\rangle_A)(|H\rangle_B |\alpha e^{i\theta_1}\rangle_1 |\alpha\rangle_2 \\ &\quad + i|V\rangle_B |\alpha\rangle_1 |\alpha e^{i\theta_1}\rangle_2). \end{aligned} \quad (3)$$

Due to the losses and the amplifications of the coherent beams in transmission we will discuss later, the parameters α and θ_1 could become α' and θ_n after their arrival at location A. There we use Kerr nonlinearities inducing θ_n to couple them with the detected photon as also shown in Fig. 2. Then two phase shifters of $-\theta_n$ are applied to adjust the state to (we neglect the undesired component from decoherence that can be reduced to vanishing percentage and the indexes A, B)

$$\begin{aligned} |\Psi_2\rangle_{tot} &= (|HH\rangle - |VV\rangle)|\alpha'\rangle_1 |\alpha'\rangle_2 \\ &\quad + i|VH\rangle|\alpha' e^{i\theta_n}\rangle_1 |\alpha' e^{-i\theta_n}\rangle_2 \\ &\quad + i|HV\rangle|\alpha' e^{-i\theta_n}\rangle_1 |\alpha' e^{i\theta_n}\rangle_2. \end{aligned} \quad (4)$$

The comparison of the transmitted coherent states is performed by a 50/50 beam splitter and a photon detector D as illustrated in Fig. 2. In the even parity sector of $|\Psi_2\rangle_{tot}$, the first coherent state is transformed by the 50/50 beam splitter to a vacuum state $|0\rangle_1$; and in the odd parity sector, two states of the coherent light will be possible: $|1/\sqrt{2}(\alpha' e^{i\theta_n} - \alpha' e^{-i\theta_n})\rangle_1$ with $|VH\rangle$ and $|1/\sqrt{2}(\alpha' e^{-i\theta_n} - \alpha' e^{i\theta_n})\rangle_1$ with $|HV\rangle$ (see Appendix C).

Ideally, the target state could be projected out by measuring the photon number of this coherent beam. If the photon number $n = 0$, the resulting state will be $|\Phi^-\rangle$; if the photon number $n \neq 0$, we will obtain $1/\sqrt{2}(e^{-i\frac{\pi}{2}n}|HV\rangle + e^{i\frac{\pi}{2}n}|VH\rangle)$, which can be transformed to $|\Psi^+\rangle$ with two phase shifters. In a realistic situation, however, one should only use simple photodiodes that are unable to resolve photon numbers but respond to any coherent beam with a sufficient brightness. Then we will realize $|\Phi^-\rangle$ with a success probability 25% over the tracks $\{K_A, K_B\}$ or $\{R_A, R_B\}$, and achieve another 25% success probability of creating $|\Phi^+\rangle$ over $\{K_A, R_B\}$ or $\{R_A, K_B\}$. We could also compare the second coherent state, which is $|\sqrt{2}\alpha'\rangle_2$ in the even parity sector and $|1/\sqrt{2}(\alpha' e^{i\theta_n} + \alpha' e^{-i\theta_n})\rangle_2$ in the odd parity sector, with a prepared state $|1/\sqrt{2}(\alpha' e^{i\theta_n} + \alpha' e^{-i\theta_n})\rangle_3$ at location A, and their difference indicated by a response of photodiode confirms the generation of an even parity Bell state. If the first coherent beam is responded by photodiode, on the other hand, what we obtain will be a mixture of

the odd parity Bell states $|\Psi^+\rangle$ and $|\Psi^-\rangle$ by the other 50% probability. A generated photon pair in this mixed state can be directly sent back to the circuit A and B for the second run, since an input in any state can be used for our raw material. The detection of sufficiently bright coherent beams also avoids the inefficiency and the dark-count error in detecting single photons. The time spent for setting up a Bell state is only the period of coherent beams' transmission from location B to A, since that of the local operations is negligible.

If the coherent beams are transmitted through lossy optical fiber, we need to compensate their photon absorption losses on the way. Over a segment of fiber with the loss rate γ_L , the dissipative evolution of a being transmitted optical field in Gaussian state ρ is described by the master equation

$$\frac{d\rho}{dt} = \frac{\gamma}{2}(2\hat{a}\rho\hat{a}^\dagger - \hat{a}^\dagger\hat{a}\rho - \rho\hat{a}^\dagger\hat{a}), \quad (5)$$

where \hat{a} corresponds to the transmitted mode and $\gamma = c\gamma_L$. The process is equivalent to a beam splitter of reflectivity $\eta = 1 - e^{-\gamma L}$ (see, e.g., [25]; L is the transmission distance), which discards the beam to environment with the distance. A simple way to overcome such loss is to displace the being transmitted coherent state $|\alpha_1\rangle = |\sqrt{1-\eta}\alpha\rangle$ by another coherent state $|\beta\rangle$ with a large $|\beta|$ (the star represents the complex conjugate):

$$D(\beta)|\alpha_1\rangle = \exp\left(\frac{\alpha_1^*\beta - \alpha_1\beta^*}{2}\right)|\alpha_1 + \beta\rangle. \quad (6)$$

Such addition of coherent states is implementable with injection-locked nonlinear amplifier (see, e.g., Ref. [26] for an overview covering the topic). The linear optical implementation of this displacement operation can be found in, e.g., [27]. In the case that the Kerr nonlinearities at location B induce a phase shift θ_1 for the coherent beams, we apply $D(\beta_1)$ with $\beta_1 = |\beta_1|e^{i(\frac{\theta_1}{2} + \pi)}$ to the being transmitted $|\alpha_1\rangle$ and $|\alpha_1e^{i\theta_1}\rangle$. The coherent beams thus keep the equal amplitudes after the operation. With two symmetric terms of coherent states in Eq. (3), the extra phases as indicated in Eq. (6) are factorized out. After each amplification in the same fashion, the relative phases θ_i ($i = 1, \dots, n$) can be determined by measuring the averages of the quadratures $X_\varphi = (\hat{a}e^{-i\varphi} + \hat{a}^\dagger e^{i\varphi})/2$ of the test beams initially prepared in the states $|\alpha\rangle$ and $|\alpha e^{i\theta_1}\rangle$ at location B. Given the sufficient phase shifts $\theta_i \geq 10^{-7}$, the pump beams $|\beta_i\rangle$ of the amplifiers can be precisely adjusted with linear optical technology to guarantee the exact displacements $D(\beta_i)$. Finally, we only need to match the phase θ_n with those induced by the Kerr media and the phase shifters at location A.

The photon absorption losses also give rise to the primary decoherence effect in transmitting the coherent beams. Under the effect the initial state involving photon B and the coherent beams in Eq. (3) will be decohered to [28]

$$\rho_{B,1,2} = \frac{1 + |\chi|^2}{2} |\Phi^1\rangle_{B,1,2} \langle\Phi^1| + \frac{1 - |\chi|^2}{2} |\Phi^2\rangle_{B,1,2} \langle\Phi^2|, \quad (7)$$

where

$$\begin{aligned} |\Phi^1\rangle_{B,1,2} &= |H\rangle_B |\sqrt{1-\eta}\alpha, \sqrt{1-\eta}\alpha e^{i\theta_1}\rangle_{1,2} \\ &\quad + i|V\rangle_B |\sqrt{1-\eta}\alpha e^{i\theta_1}, \sqrt{1-\eta}\alpha\rangle_{1,2}, \\ |\Phi^2\rangle_{B,1,2} &= |H\rangle_B |\sqrt{1-\eta}\alpha, \sqrt{1-\eta}\alpha e^{i\theta_1}\rangle_{1,2} \\ &\quad - i|V\rangle_B |\sqrt{1-\eta}\alpha e^{i\theta_1}, \sqrt{1-\eta}\alpha\rangle_{1,2} \end{aligned} \quad (8)$$

and $|\chi| = |\langle\sqrt{\eta}\alpha e^{i\theta_1}|\sqrt{\eta}\alpha\rangle|$. The relative phase shift θ_i relayed by this mixed state will lead to a mixture of the even or the odd parity Bell states in the end. To eliminate the undesired component $|\Phi^2\rangle_{B,1,2}$ effectively, we set the proper parameters such that $|\chi|^2 = \exp(-\eta|\alpha_i - \alpha_i e^{i\theta_i}|^2) \sim 1$. With $\theta_i \sim 10^{-7}$, for instance, we choose the coherent beams carrying the average photon number 10^8 ($|\alpha_i| \sim 10^4$), and then $|\chi|^2$ will be larger than $1 - 10^{-6}$. Using 10^3 times of amplification enroute for this case realizes the fidelity 99.9% with Bell state. After the beams are sent to location A, we should amplify them to the intensity $|\alpha_n| \sim 10^8$ before their comparison. Moreover, we can eliminate the possible deviation of θ_i in two beams, which could arise from their picking up the different extra phases in transmission, by transmitting them together as shown in Fig. 2. We let two initially identical beams respectively undergo the same physical processes throughout running the setup. With the symmetric structure in the design, all causal effects on the phases of two coherent beams, as well as on those of the different single photon components, will be identical if we also adopt a multi-mode approach (see, e.g., [29]) for these signals. This fact guarantees the ideal fidelity of the generated entanglement.

During the transmission of the coherent beams, we could store the states of single photons in atomic ensembles by local teleportation with an effective entangled pair of photonic and atomic qubits [15], $1/\sqrt{2}(|HL\rangle + |VR\rangle)$, where L and R are the collective excitation modes of atoms. Fig. 3 demonstrates the creation of the entanglement between the distant atomic ensembles through a Bell-state measurement (BSM) on midway. Unlike the quantum repeater protocols [7, 8, 9, 10, 11, 12, 13] which connect the entanglements of atomic ensembles with their emitted single photons being transmitted over a distance, the entanglement swapping in our scheme is realized with the measurement on a locally generated photon pair, so the interference instability is greatly reduced.

If we properly handle two coherent beams in running this kind of setup, a single photon will be entangled to a far-away system in a close to exact Bell state as we compare the transmitted coherent states. This process, which lasts for the time of one-way classical communication between distant locations, will be repeated until a successful event is heralded by a specific response pattern of the photodiodes. All operations involved are within the available technologies demonstrated in other applications. As the setups of this type become practical, the requirement to long-distance quantum communications will be only a quantum memory with a storage time for

quantum states in the order of the time for one-way classical communication.

This work is supported in part by the Petroleum Research Fund and PSC-CUNY award. B.H. thanks C. F. Wildfeuer and J. P. Dowling for material about Kerr non-linearity.

Appendix

A. Processing arbitrary input photon pair in extended spaces

In what follows, we demonstrate how to transform the state ρ_{in} of a photon pair (represented in the Bell state basis $\{|\Phi^+\rangle, |\Phi^-\rangle, |\Psi^+\rangle, |\Psi^-\rangle\}$) to a subspace spanned by a subset $\{|\Phi^-\rangle, |\Psi^+\rangle\}$ or $\{|\Phi^+\rangle, |\Psi^-\rangle\}$ of the four Bell states. This procedure establishes the fact that an input photon pair in any state ρ_{in} (pure or mixed) can be used as the raw material in our scheme. First we use two polarization beam splitters (PBS) to convert the input state in polarization space to a which-path space of two different tracks 1 and 2. The four basis vectors are therefore transformed as follows:

$$\begin{aligned} |\Phi^+\rangle &\rightarrow |B_{00}\rangle = (\hat{a}_{A,1}^\dagger, \hat{a}_{A,2}^\dagger) B_{00} \begin{pmatrix} \hat{a}_{B,1}^\dagger \\ \hat{a}_{B,2}^\dagger \end{pmatrix} |0\rangle, \\ |\Phi^-\rangle &\rightarrow |B_{01}\rangle = (\hat{a}_{A,1}^\dagger, \hat{a}_{A,2}^\dagger) B_{01} \begin{pmatrix} \hat{a}_{B,1}^\dagger \\ \hat{a}_{B,2}^\dagger \end{pmatrix} |0\rangle, \\ |\Psi^+\rangle &\rightarrow |B_{10}\rangle = (\hat{a}_{A,1}^\dagger, \hat{a}_{A,2}^\dagger) B_{10} \begin{pmatrix} \hat{a}_{B,1}^\dagger \\ \hat{a}_{B,2}^\dagger \end{pmatrix} |0\rangle, \\ |\Psi^-\rangle &\rightarrow |B_{11}\rangle = (\hat{a}_{A,1}^\dagger, \hat{a}_{A,2}^\dagger) B_{11} \begin{pmatrix} \hat{a}_{B,1}^\dagger \\ \hat{a}_{B,2}^\dagger \end{pmatrix} |0\rangle, \end{aligned} \quad (1)$$

where the four Bell matrices are defined as

$$\begin{aligned} B_{00} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}, & B_{01} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}, \\ B_{10} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, & B_{11} &= \frac{1}{\sqrt{2}} \begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix}. \end{aligned} \quad (2)$$

We divide these four which-path entangled states into two groups: the states of B_{00} and B_{01} belong to the even parity set, while those of B_{10} and B_{11} to the odd parity set. A general input state with these Bell states as the basis is a rank-four matrix

$$\begin{aligned} \rho_{in} &= \sigma_1 |\Lambda_1\rangle \langle \Lambda_1| + \sigma_2 |\Lambda_2\rangle \langle \Lambda_2| + \sigma_3 |\Lambda_3\rangle \langle \Lambda_3| \\ &+ \sigma_4 |\Lambda_4\rangle \langle \Lambda_4|, \end{aligned} \quad (3)$$

where the normalized pure state components $|\Lambda_k\rangle = \sum_{i,j} \kappa_{k,ij} |B_{ij}\rangle$ are the eigenvectors of ρ_{in} , and σ_k the eigenvalues of ρ_{in} .

For the further transformations on the input states, we adopt a notation of operator-vector duality [30]. This notation provides a natural correspondence between a pure

state component $|\Lambda\rangle$ in the general input state ρ_{in} and its coefficient matrix Λ , just as the relation between $|B_{ij}\rangle$ and B_{ij} in Eq. (1). With this notation, two local operations A and B from the sharing parties of the bipartite state $|\Lambda\rangle$ are expressed as follows (T represents the matrix transpose):

$$A \otimes B |\Lambda\rangle = |A\Lambda B^T\rangle. \quad (4)$$

The unitary and the non-unitary transformations of A and B can be realized following the procedures in [23] and [24], respectively.

The coefficient matrix Λ can be embedded in a larger space with the local operations performed in the extended space [31]. If we apply two identical local rotations

$$U_1 = \frac{1}{\sqrt{2}} \begin{pmatrix} I & I \\ -I & I \end{pmatrix} \quad (5)$$

in the extended space at both locations A and B, for example, there will be a bipartite state $|\Sigma\rangle$ with the following coefficient matrix obtained in the extended space of double dimension (we represent a zero submatrix with 0):

$$\Sigma = U_1 \begin{pmatrix} \Lambda & 0 \\ 0 & 0 \end{pmatrix} U_1^T = \frac{1}{2} \begin{pmatrix} \Lambda & -\Lambda \\ -\Lambda & \Lambda \end{pmatrix}. \quad (6)$$

As an example of $\Lambda = B_{00}$ in Eq. (2), we will thus obtain a 4×4 bipartite state:

$$\begin{aligned} |\Sigma\rangle &= \frac{1}{2\sqrt{2}} (\hat{a}_{A,1}^\dagger \hat{a}_{B,1}^\dagger + \hat{a}_{A,2}^\dagger \hat{a}_{B,2}^\dagger) |0\rangle \\ &- \frac{1}{2\sqrt{2}} (\hat{a}_{A,1}^\dagger \hat{a}_{B,3}^\dagger + \hat{a}_{A,2}^\dagger \hat{a}_{B,4}^\dagger) |0\rangle \\ &- \frac{1}{2\sqrt{2}} (\hat{a}_{A,3}^\dagger \hat{a}_{B,1}^\dagger + \hat{a}_{A,4}^\dagger \hat{a}_{B,2}^\dagger) |0\rangle \\ &+ \frac{1}{2\sqrt{2}} (\hat{a}_{A,3}^\dagger \hat{a}_{B,3}^\dagger + \hat{a}_{A,4}^\dagger \hat{a}_{B,4}^\dagger) |0\rangle, \end{aligned} \quad (7)$$

where the indexes ranging from 1 to 4 represent four different tracks. The linear optical implementation of U_1 is illustrated in Fig. 4. Since any unitary transformation operating on a single photon in which-path space corresponds to a linear optical circuit [23], in the later steps, we will only show the necessary transformations on the coefficient matrix Λ of a pure state component in an input without demonstrating their corresponding circuits.

The second pair of local unitary transformations we apply is

$$U_2 = \begin{pmatrix} 0 & iV \\ I & 0 \end{pmatrix} = \begin{pmatrix} iV & 0 \\ 0 & I \end{pmatrix} \begin{pmatrix} 0 & I \\ I & 0 \end{pmatrix}, \quad (8)$$

in which

$$V = \begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix}. \quad (9)$$

The operation U_2 can be implemented by three totally reflecting mirrors and the appropriate phase shifters. Under the joint local action of U_2 , a bipartite state of the following coefficient matrix will be obtained from $|\Sigma\rangle$:

$$\Xi = U_2 \Sigma U_2^T = \frac{1}{2} \begin{pmatrix} A & B \\ C & D \end{pmatrix}, \quad (10)$$

where $A = -V\Lambda V^T$, $B = -iV\Lambda$, $C = -i\Lambda V^T$ and $D = \Lambda$. If $\Lambda = B_{ij}$, we will obtain the submatrices for the different parity sets as follows:

$$\begin{aligned} A &= - \begin{pmatrix} \lambda_2 & 0 \\ 0 & \lambda_1 \end{pmatrix}, & B &= -i \begin{pmatrix} 0 & \lambda_2 \\ -\lambda_1 & 0 \end{pmatrix}, \\ C &= -i \begin{pmatrix} 0 & -\lambda_1 \\ \lambda_2 & 0 \end{pmatrix}, \end{aligned} \quad (11)$$

where Λ of the even parity set are diagonal with the entries $\lambda_1 = 1/\sqrt{2}$ and $\lambda_2 = \pm 1/\sqrt{2}$;

$$A = \begin{pmatrix} 0 & \lambda_2 \\ \lambda_1 & 0 \end{pmatrix}, \quad B = -i \begin{pmatrix} \lambda_2 & 0 \\ 0 & -\lambda_1 \end{pmatrix},$$

$$C = -i \begin{pmatrix} \lambda_1 & 0 \\ 0 & -\lambda_2 \end{pmatrix}, \quad (12)$$

where Λ of the odd parity set are off-diagonal with the entries $\lambda_1 = 1/\sqrt{2}$ and $\lambda_2 = \pm 1/\sqrt{2}$.

Now, we continue to apply the third pair of local unitary operations U_1^T to obtain a bipartite state $|\Lambda'\rangle$ with $\Lambda' = U_1^T \Xi U_1$. We embed the state $|\Lambda'\rangle$ into a further extended space of 8×8 dimension, and perform one more pair of local unitary operations K constructed with the projection operators,

$$P_1 = \begin{pmatrix} 0 & 0 \\ 0 & I \end{pmatrix}, \quad P_2 = \begin{pmatrix} I & 0 \\ 0 & 0 \end{pmatrix}, \quad (13)$$

where $P_1 + P_2 = I_4$, the identity in four dimensional space. Such unitary operations K are realized in the extended space as follows:

$$\begin{aligned} \Omega &= K \begin{pmatrix} \Lambda' & 0 \\ 0 & 0 \end{pmatrix} K^T = \begin{pmatrix} P_1 & P_2 \\ P_2 & -P_1 \end{pmatrix} \begin{pmatrix} \Lambda' & 0 \\ 0 & 0 \end{pmatrix} \begin{pmatrix} P_1 & P_2 \\ P_2 & -P_1 \end{pmatrix} = \frac{1}{4} \begin{pmatrix} P_1 \Lambda' P_1 & P_1 \Lambda' P_2 \\ P_2 \Lambda' P_1 & P_2 \Lambda' P_2 \end{pmatrix} \\ &= \frac{1}{4} \begin{pmatrix} 0 & 0 & 0 & 0 \\ 0 & A+B+C+D & A+C-B-D & 0 \\ 0 & A-C+B-D & A-B-C+D & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix}. \end{aligned} \quad (14)$$

If we substitute the results in Eqs. (11) and (12) into the non-zero block $A + B + C + D$, we will obtain the following transformations for the coefficient matrices of the Bell states:

$$\begin{aligned} \Lambda = B_{00} &\rightarrow 0, & \Lambda = B_{01} &\rightarrow 1/2(B_{01} + iB_{10}), \\ \Lambda = B_{11} &\rightarrow 0, & \Lambda = B_{10} &\rightarrow 1/2(B_{10} - iB_{01}). \end{aligned} \quad (15)$$

Only two Bell states survive in the transformations. Similar relations will be obtained from the other three non-zero blocks. We find that, in the non-zero parts of $P_1 \Lambda' P_1$ and $P_2 \Lambda' P_2$ blocks, the pure state components of an input ρ_{in} are mapped to a subspace spanned by $\{|B_{01}\rangle, |B_{10}\rangle\}$ or $\{|\Phi^-\rangle, |\Psi^+\rangle\}$ but, in the non-zero submatrices of other two blocks, they will be mapped to that spanned by $\{|B_{00}\rangle, |B_{11}\rangle\}$ or $\{|\Phi^+\rangle, |\Psi^-\rangle\}$ instead. These non-zero matrix blocks respectively correspond to the output components on tracks $\{K_A, K_B\}$, $\{R_A, R_B\}$, $\{K_A, R_B\}$ and $\{R_A, K_B\}$ in Fig. 2. Therefore, if one projects out the components only corresponding to one of the blocks, the resulting state from a general input ρ_{in} will be in a subspace with only two Bell states (one even parity but the other odd parity) as the basis vectors.

B. Projecting out desired photonic components with QND modules

The comparison of coherent states can be realized in a near deterministic way [21], so we apply coherent states comparison to project out the desired components in the processed photon pairs and separate the even and the odd parity sectors in them. Here we illustrate the general result with an example of input photon pair in the state $|HH\rangle = 1/\sqrt{2}(|\Phi^+\rangle + |\Phi^-\rangle)$. After a sequence of unitary transformations in the extended space, which have been discussed in the last section, the total output will be an 8×8 bipartite state in a which-path space. To project out the output on tracks K_A and K_B , for example, we use two quantum non-demolition (QND) shown in Fig. 1. The first coherent beam $|\alpha\rangle_{K_A,1}$ of QND module A and $|\alpha\rangle_{K_B,1}$ of module B are coupled only to the components on K_A or K_B through a Kerr medium inducing a phase shift θ . Before the interactions, the normalized state of the total system including the output photon pair and the coherent beams is

$$\begin{aligned} |\Psi\rangle_{tot} &= (|\Omega\rangle_{K_A, K_B} + |\Omega\rangle_{R_A, R_B} + |\Omega\rangle_{R_A, K_B} + |\Omega\rangle_{K_A, R_B}) \\ &\quad \times |\alpha\rangle_{K_A,1} |\alpha\rangle_{K_A,2} |\alpha\rangle_{K_B,1} |\alpha\rangle_{K_B,2}, \end{aligned} \quad (16)$$

where $|\Omega\rangle_{K_A, K_B} = 1/4(|H\rangle_A + i|V\rangle_A)(|H\rangle_B + i|V\rangle_B)$ is the output we intend to realize. Under the action of the Kerr nonlinearities and a 50/50 beam splitter in both

QND modules, the total state will evolve in the following way:

$$\begin{aligned}
|\Psi\rangle_{tot} &\rightarrow \frac{1}{4}(|H\rangle_A + i|V\rangle_A) \otimes \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} - 1) \right\rangle_{K_{A,1}} \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} + 1) \right\rangle_{K_{A,2}} \otimes (|H\rangle_B + i|V\rangle_B) \\
&\otimes \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} - 1) \right\rangle_{K_{B,1}} \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} + 1) \right\rangle_{K_{B,2}} \\
&+ |\Omega\rangle_{R_A, R_B} \otimes |0\rangle_{K_{A,1}} |\sqrt{2}\alpha\rangle_{K_{A,2}} |0\rangle_{K_{B,1}} |\sqrt{2}\alpha\rangle_{K_{B,2}} + |\Omega\rangle_{R_A, K_B} \otimes |0\rangle_{K_{A,1}} |\sqrt{2}\alpha\rangle_{K_{A,2}} \\
&\otimes \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} - 1) \right\rangle_{K_{B,1}} \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} + 1) \right\rangle_{K_{B,2}} \\
&+ |\Omega\rangle_{K_A, R_B} \otimes \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} - 1) \right\rangle_{K_{A,1}} \left| \frac{1}{\sqrt{2}}\alpha(e^{i\theta} + 1) \right\rangle_{K_{A,2}} |0\rangle_{K_{B,1}} |\sqrt{2}\alpha\rangle_{K_{B,2}}. \tag{17}
\end{aligned}$$

If one detects the first coherent beam of the QND modules at both location A and B with a simple photodiode, the desired output will be immediately projected out with

the responses of the two photodiodes together. This operation is equivalent to applying the projection P'_1 ,

$$\Omega_{K_A, K_B} = \frac{1}{4} \begin{pmatrix} I & 0 \\ 0 & 0 \end{pmatrix} \begin{pmatrix} A+B+C+D & A+C-B-D \\ A-C+B-D & A-B-C+D \end{pmatrix} \begin{pmatrix} I & 0 \\ 0 & 0 \end{pmatrix} = \frac{1}{4} \begin{pmatrix} A+B+C+D & 0 \\ 0 & 0 \end{pmatrix}, \tag{18}$$

at both location A and B on the total output corresponding to Eq. (14). Since $P'_1 + P'_2 = I_4$ and $[P'_1, P'_2] = 0$, P'_1 can be simultaneously implemented with another projection P'_2 realized with two more QND modules at both locations, with one of them having the measurement result 1. Therefore, two QND modules responding to either K_A or R_A at location A, together with the other two QND modules responding to either K_B or R_B at location B, will be used to project out the outputs over four groups of ports $\{K_A, K_B\}$, $\{R_A, R_B\}$, $\{K_A, R_B\}$ and $\{R_A, K_B\}$, respectively. In the actual operations, we send the result of which QND module responds at one location to another, where it is matched to another QND measurement result to determine the pair of output ports for setting up an entangled state.

C. Separation of different parity sectors with coherent states comparison

The projected-out photonic components at location B are coupled to two more coherent beams $|\alpha\rangle$ as shown in Fig. 2. Now we denote the induced phase shift as θ_1 to distinguish it from those after further processing. Due to the losses of photons, the amplitudes of the coherent beams will shrink with the distance as they are being

transmitted in lossy optical fiber. At a certain point, we need to amplify them by implementing a displacement $D(\beta_1)$, forwarding the state vector involving photon B and the coherent beams to (the common coefficient is neglected)

$$\begin{aligned}
|\Psi\rangle_B &= |H\rangle_B D(\beta_1) |\alpha_1 e^{i\theta_1}\rangle_1 \otimes D(\beta_1) |\alpha_1\rangle_2 \\
&+ i|V\rangle_B D(\beta_1) |\alpha_1\rangle_1 \otimes D(\beta_1) |\alpha_1 e^{i\theta_1}\rangle_2 \\
&= |H\rangle_B |\alpha_2\rangle_1 |\alpha_2 e^{i\theta_2}\rangle_2 + i|V\rangle_B |\alpha_2 e^{i\theta_2}\rangle_1 |\alpha_2\rangle_2, \tag{19}
\end{aligned}$$

where α_1 is proportional to α with a reduced modulus, and $\beta_1 = |\beta_1| e^{i(\frac{\theta_1}{2} + \pi)}$. The parameters of the coherent states after the displacement are, respectively, $\alpha_2 = \beta_1 + \alpha_1 e^{i\theta_1}$ and $\alpha_2 e^{i\theta_2} = \beta_1 + \alpha_1$, keeping the same modulus. Through n times of amplification in this way until the beams are transmitted to location A, the state of the total system will be (we neglect the unwanted pure state component arising from the decoherence in transmission, which can be effectively eliminated by choosing the proper parameters α_i and θ_i)

$$\begin{aligned}
|\Psi_1\rangle_{tot} &= (|H\rangle_A + i|V\rangle_A) (|H\rangle_B |\alpha' e^{i\theta_n}\rangle_1 |\alpha'\rangle_2 \\
&+ i|V\rangle_B |\alpha'\rangle_1 |\alpha' e^{i\theta_n}\rangle_2), \tag{20}
\end{aligned}$$

where α' and θ_n can be the appropriate values determined by the whole process.

The beams at location A will be coupled with photon A through Kerr media inducing a phase shift θ_n . After being adjusted by two phase shifters of $-\theta_n$, the resulting

state $|\Psi_2\rangle_{tot}$ will be transformed by a 50/50 beam splitter as follows:

$$\begin{aligned}
|\Psi_2\rangle_{tot} &= (|HH\rangle - |VV\rangle)|\alpha'\rangle_1|\alpha'\rangle_2 + i|VH\rangle|\alpha'e^{i\theta_n}\rangle_1|\alpha'e^{-i\theta_n}\rangle_2 + i|HV\rangle|\alpha'e^{-i\theta_n}\rangle_1|\alpha'e^{i\theta_n}\rangle_2 \\
&\rightarrow (|HH\rangle - |VV\rangle)|0\rangle_1|\sqrt{2}\alpha'\rangle_2 \\
&+ i|VH\rangle|\frac{1}{\sqrt{2}}(\alpha'e^{i\theta_n} - \alpha'e^{-i\theta_n})\rangle_1|\frac{1}{\sqrt{2}}(\alpha'e^{i\theta_n} + \alpha'e^{-i\theta_n})\rangle_2 \\
&+ i|HV\rangle|\frac{1}{\sqrt{2}}(\alpha'e^{-i\theta_n} - \alpha'e^{i\theta_n})\rangle_1|\frac{1}{\sqrt{2}}(\alpha'e^{i\theta_n} + \alpha'e^{-i\theta_n})\rangle_2.
\end{aligned} \tag{21}$$

The photon number measurement on the first coherent state could determine which Bell state is created by our setup. The second coherent state can be compared with another state $|\frac{1}{\sqrt{2}}(\alpha'e^{i\theta_n} + \alpha'e^{-i\theta_n})\rangle_3$ prepared at location A for a confirmation of the generation of an even parity Bell state. Under the action of another 50/50 beam splitter, the second coherent state in the even parity sector will be transformed to $|\frac{1}{2}\alpha'(1 - e^{i\theta_n}) + \frac{1}{2}\alpha'(1 - e^{-i\theta_n})\rangle_2$, while it is mapped to the vacuum state $|0\rangle_2$ in the odd parity sector. With a sufficient brightness of the beams, we can discriminate the different coherent states by a close to unit probability.

D. Generation of graph states

As an extension of the scheme, we can also generate graph states or cluster states from a group of independent photons at various locations. This type of multi-party

entangled states are important in quantum computation [32], and the entanglements of up to six particles have been experimentally realized so far [33, 34, 35]. By our method, all entangled edges in a graph state should be connected simultaneously, because the separate photons at each vertex can be processed by a linear circuit only once. Under any further operation by circuit, the connected graph could be damaged. One exception is the Greenberger-Horne-Zeilinger (GHZ) states, which can gradually grow to large size by means of coherent states comparison. For example, after we generate a two-photon state $1/\sqrt{2}(|HH\rangle + |VV\rangle)$, we let two identical coherent beams $|\alpha\rangle$ be coupled with any one of the photons as in Fig. 2. Then we send the beams to interact with another photon in the state $1/\sqrt{2}(|H\rangle + |V\rangle)$ and finally compared their states. A GHZ state $1/\sqrt{2}(|HHH\rangle + |VVV\rangle)$ will be thus created with a 50% success probability. The overall efficiency of generating a graph state of n edges is $(1/2)^n$ per try.

-
- [1] J.-W. Pan, *et al.*, arXiv: 0805.2853 (2008).
 - [2] H.-J. Briegel, W. Dür, J. I. Cirac & P. Zoller, *Phys. Rev. Lett.* **81**, 5932 (1998).
 - [3] W. Dür, H.-J. Briegel, J. I. Cirac & P. Zoller, *Phys. Rev. A* **59**, 169 (1999).
 - [4] L. Childress, J. M. Taylor, A. S. Sørensen & M. D. Lukin, *Phys. Rev. Lett.* **96**, 070504 (2006).
 - [5] A. Acín, J. I. Cirac & M. Lewenstein, *Nature Physics* **3**, 256 (2007).
 - [6] S. Perseguers, *et al.*, *Phys. Rev. A* **77**, 022308 (2008).
 - [7] L.-M. Duan, M. D. Lukin, J. I. Cirac & P. Zoller, *Nature* **414**, 413 (2001).
 - [8] C. Simon, *et al.*, *Phys. Rev. Lett.* **98**, 190503 (2007).
 - [9] B. Zhao, *et al.* *Phys. Rev. Lett.* **98**, 240502 (2007).
 - [10] L. Jiang, J. M. Taylor & M. D. Lukin, *Phys. Rev. A* **76**, 012301 (2007).
 - [11] Z.-B. Chen, *et al.*, *Phys. Rev. A* **76**, 022329 (2007).
 - [12] N. Sangouard, *et al.*, *Phys. Rev. A* **76**, R050304 (2007).
 - [13] N. Sangouard, *et al.*, *Phys. Rev. A* **77**, 062301 (2008).
 - [14] C. W. Chou, *et al.*, *Science* **316**, 1316 (2007).
 - [15] Y.-A. Chen, *et al.*, *Nature Physics* **4**, 103 (2008).
 - [16] Z.-S. Yuan, *et al.*, arXiv: 0803.1810 (2008).
 - [17] P. van Loock, *et al.*, *Phys. Rev. Lett.* **96**, 240501 (2006).
 - [18] T. D. Ladd, *et al.*, *New J. Phys.* **8**, 184 (2006).
 - [19] P. van Loock, N. Lütkenhaus, W. J. Munro & K. Nemoto, arXiv: 0806.1153 (2008).
 - [20] T. Konrad, A. Scherer, M. Nock & J. Audretsch, *Phys. Rev. A* **73**, 032327 (2006).
 - [21] E. Andersson, M. Curty & I. Jex, *Phys. Rev. A* **74**, 022304 (2006).
 - [22] M. Fleischhauer, A. Imamoglu & J. P. Marangos, *Rev. Mod. Phys.* **77**, 633 (2005).
 - [23] M. Reck, A. Zeilinger, H. J. Bernstein & P. Bertani, *Phys. Rev. Lett.* **73**, 58 (1994).
 - [24] B. He, J. Bergou & Z.-Y. Wang, *Phys. Rev. A* **76**, 042326 (2007).
 - [25] J. K. Asbóth, P. Adam, M. Koniorczyk & J. Janszky, *Eur. Phys. J. D* **30**, 403 (2004).
 - [26] G. Kweon, *J. Korean Phys. Soc.* **41**, 617 (2002).
 - [27] M. Takeoka & M. Sasaki, *Phys. Rev. A*, to be published;

arXiv: 0706.1038.

- [28] S. J. van Enk & O. Hirota, *Phys. Rev. A* **64**, 022313 (2001).
- [29] J. H. Shapiro & M. Razavi, *New. J. Phys.* **9**, 16 (2007).
- [30] G. M. D'Ariano, P. Lo Presti & M. F. Sacchi, *Phys. Lett. A* **272**, 32 (2000).
- [31] B. He & J. Bergou, Arxiv: 0708.4184 (2007).
- [32] R. Raussendorf & H. J. Briegel, *Phys. Rev. Lett.* **86**, 5188 (2001).
- [33] P. Walther, *et al.*, *Nature* **434**, 169 (2005).
- [34] D. Leibfried, *et al.*, *Nature* **438**, 639 (2005).
- [35] C.-Y. Lu, *et al.*, *Nature Physics* **3**, 91 (2007).

Caption of Fig.1: **Configuration of QND module.** (a) The interaction of one of the coherent beams $|\alpha_0\rangle$ (red line) with a signal photon state (blue line) in Kerr medium generates an extra phase θ on the coherent beam. The 50/50 beam splitter transforms two coherent states $|\alpha_0\rangle_1|\beta_0\rangle_2$, where $|\beta_0\rangle_2$ could be either $|\alpha_0\rangle_2$ or $|\alpha_0 e^{i\theta}\rangle_2$, to $|\frac{\alpha_0-\beta_0}{\sqrt{2}}\rangle_1|\frac{\alpha_0+\beta_0}{\sqrt{2}}\rangle_2$ (together with the proper phase shifters). A response of the photodiode D indicates that the two beams $|\alpha_0\rangle_1$ and $|\beta_0\rangle_2$ are different with $|\frac{\alpha_0-\beta_0}{\sqrt{2}}\rangle_1 \neq |0\rangle_1$. (b) Inside the Kerr medium, the single photon and the coherent beam with the different polarizations are transmitted together. Their interaction time can be adjusted so that we will obtain a designed θ value.

Caption of Fig.2: **Layout of setup.** The pairs of input photons are converted to a which-path space by two PBS, and the circuit A and B generate the outputs over four groups of tracks, $\{K_A, K_B\}$, $\{R_A, R_B\}$, $\{K_A, R_B\}$ and $\{R_A, K_B\}$, each pure state component of which, in turn, is the linear combination of only two fixed Bell states. The detection result of the QND modules at location B (we only show the one coupled to K_B) is sent to location A. If the two beams having interacted with the photon at location B are in pulse modes, we can send them within a very short time (controlled by optical switch) through the same channel to eliminate the deviation of their possible extra phases gained in transmission. For the beams in CW modes, we can simply let them have the different polarizations while transmitting them together, so that they will be separated at the destinations. The beams are amplified from $D(\beta_1)$ to $D(\beta_n)$ along the channel. At location B, the first coherent beams interacts with the H component of the processed photon while the second is coupled to the V component. After they are transmitted to location A, the beams will be coupled to the processed photon in the opposite way. The comparison of the two coherent beams, which is implemented by a 50/50 beam splitter and the photodiode D , determines the creation of a close to Bell state over the terminals $A2$ and $B2$.

Caption of Fig.3: **Entangling distant atomic ensembles through BSM.** Here the coherent beams are assumed to be transmitted through free space without losses. At location A and B, the state of the processed photon is teleported to atomic ensembles (only one as the representation is shown) for longer storage time. The coherent beams from both location A and B are transmitted to the location C, where they respectively entangle a locally processed photon with the atomic ensembles at location A or B. The photon pair at location C is then measured in the Bell basis $\{|\Phi^+\rangle, |\Phi^-\rangle, |\Psi^+\rangle, |\Psi^-\rangle\}$, and the atomic ensembles at location A and B will thus be connected to an entangled pair through entanglement swapping.

Caption of Fig.4: **Transformation of input bipartite state to larger space.** As a detailed part of the linear optical circuits A or B in Fig. 2, two 50/50

beam splitters (BS) transform the input 2×2 bipartite state to a 4×4 bipartite state. The polarization of all photon components are converted to H by an HWP or $\lambda/2$. Then the output on the tracks from 1 to 4 will be processed in the other part of circuit A or B. During the

later processing, the photonic components on all tracks keep the H polarization until two of them are converted to V polarization before being merged by PBS (shown in Fig. 2).





