

Universally-composable privacy amplification from causality constraints

Lluís Masanes

ICFO-Institut de Ciències Fòniques, 08860 Castelldefels (Barcelona), Spain

June 21, 2024

Abstract

The impossibility of arbitrarily-fast signaling implies that uniform randomness can be extracted from correlations which sufficiently violate a Bell inequality. In our scheme, Bell inequalities play the role usually played by entropies, and the randomness is obtained by processing outcomes of Bell-violating measurements with a constant hash function. This contrasts with previous schemes in classical/quantum information theory (e.g. two-universal hashing, extractors), where the hash function is necessarily random. Our results imply the security of privacy amplification and secret key distribution, with the sole assumption of no signaling—even according to the strongest notion of security, the so called universally-composable security. In the low-noise regime, the efficiency rate of our scheme tends to the one obtained by assuming that the eavesdropper is quantum-mechanical, although our assumption is weaker.

1 Introduction

The violation of Bell inequalities [1] implies that local physical properties do not determine the outcomes of local measurements. This fundamental piece of our understanding of physical reality can be exploited for implementing information-theoretic tasks. For instance, a key generated from the outcomes of Bell-violating measurements cannot exist beforehand, and hence, cannot be known by a distant adversary. This reasoning is independent of quantum mechanics, the only key assumption is the impossibility of arbitrarily-fast signaling between distant locations.

The first scheme for generating secret key from Bell-violating correlations was presented and shown to be secure in [2]. This scheme is inefficient, but in subsequent publications [3, 4, 5], new efficient schemes were introduced, although without security proofs. This is what we provide here. Our results, complemented with the ones in [6], provide a general security proof without assumptions

(apart from no signaling). Our security criterion is the strongest one, the so-called universally-composable security [7], which warrants that key distribution is secure in any context. Our methods are very general, and can be adapted to other Bell inequality-based key-distribution protocols.

2 Notation and main result

Upper-case A denotes random variables, and the corresponding lower-case a one particular outcome; bold symbols denote strings of variables $\mathbf{a} = (a_1, \dots, a_N)$ or random variables $\mathbf{A} = (A_1, \dots, A_N)$, whose length is clear by the context; the probability of obtaining one particular outcome is denoted by $P_a = \text{Prob}\{A = a\}$, and the whole vector of probabilities $P_A = |P_A\rangle = (P_{a_1}, P_{a_2}, \dots)$.

Consider two parties, Alice and Bob, each having a physical system which can be measured with different observables. Let $A \in \{0, 1\}$ be the outcome when Alice's system is measured with one of the observables parametrized by $X \in \{0, 1\}$. Let B and Y be the analogous thing for Bob, and $P_{A,B|X,Y}$ the joint conditional probability distribution. We say that $P_{A,B|X,Y}$ is a nonsignaling distribution if the marginals depend only on their corresponding observables, that is $P_{A|x,y} = P_{A|x}$ and $P_{B|x,y} = P_{B|y}$ [8]. It is clear that if one of these conditions is not satisfied, then arbitrarily-fast signaling is possible. In the binary case ($A, B, X, Y \in \{0, 1\}$) all Bell inequalities are equivalent to the CHSH inequality [9]. For what follows, it is convenient to express the CHSH inequality as $\langle \text{CHSH} | P_{A,B|X,Y} \rangle \geq 2$, with

$$|\text{CHSH}\rangle = \frac{1}{4} \left[\begin{array}{cc|cc} 1 & 5 & 1 & 5 \\ 5 & 1 & 5 & 1 \\ \hline 1 & 5 & 5 & 1 \\ 5 & 1 & 1 & 5 \end{array} \right], \quad (1)$$

$$|P_{A,B|X,Y}\rangle = \left[\begin{array}{cc|cc} P_{0,0|0,0} & P_{0,1|0,0} & P_{0,0|0,1} & P_{0,1|0,1} \\ P_{1,0|0,0} & P_{1,1|0,0} & P_{1,0|0,1} & P_{1,1|0,1} \\ \hline P_{0,0|1,0} & P_{0,1|1,0} & P_{0,0|1,1} & P_{0,1|1,1} \\ P_{1,0|1,0} & P_{1,1|1,0} & P_{1,0|1,1} & P_{1,1|1,1} \end{array} \right]. \quad (2)$$

Notice that in this form, the larger the violation the lower the number $\langle \text{CHSH} | P_{A,B|X,Y} \rangle$. The distribution attaining maximum violation ($\langle \text{CHSH} | P_{A,B|X,Y} \rangle = 1/2$) is the so-called PR-box [10].

Privacy amplification (PA) is the procedure by which a partially secret N_r -bit string \mathbf{A} (the *raw key*) is transformed into a highly-secret N_s -bit string \mathbf{K} (the *secret key*) [11]. Usually, the secret key is shorter than the raw key ($N_s < N_r$), which is the price for the gain in privacy. This transformation is implemented by a *hash function* $h(\mathbf{A}) = \mathbf{K}$. An *ideal secret key* is a uniformly-distributed random variable \mathbf{K} which is uncorrelated with the rest of the universe (or the eavesdropper). The information held by Eve (the eavesdropper) is encoded in the

state of a physical system, which can be measured with one of many different observables, parametrized by Z . If $P_{E|z}$ is the distribution for the outcomes when this system is measured with the observable z , then the distribution of an *ideal secret key* is $P_{\mathbf{k},e|z} = 2^{-N_s} P_{e|z}$. Usually, the *real secret key* generated by PA is not warranted to be an *ideal secret key*, $P_{\mathbf{k},e|z} \neq 2^{-N_s} P_{e|z}$.

In general, PA constitutes a sub-routine within cryptographic protocols, which use secret key as an ingredient (an example being the encryption of messages). It is desirable that the result obtained when any of these protocols is fed with the *real secret key*, is the same as if fed with an *ideal secret key*, with arbitrarily high probability. If this is the case, then we say that PA is universally composable, because it is secure in any context. Clearly, this happens if the *real* and *ideal* secret keys are indistinguishable.

The most general strategy for distinguishing the bipartite states $P_{\mathbf{k},e|z}$ (the real key) and $2^{-N_s} P_{e|z}$ (the ideal key) consists of performing joint measurements on the key and Eve's system. The no signaling formalism alone does not say anything about joint measurements. However, the key is a classical system which can be observed without disturbing the global state (it is a number written on a paper). Therefore, the most general strategy is to read \mathbf{K} and chose an observable \mathbf{Z} depending on its value. It is known that the optimal strategy has success probability

$$\text{Prob}\{\text{"success"}\} = \frac{1}{2} + \frac{1}{4} \sum_{\mathbf{k}} \max_z \|P_{\mathbf{k},E|z} - 2^{-N_s} P_{E|z}\| , \quad (3)$$

where $\|P_A\| = \sum_a |P_a|$ is the L_1 -norm [12]. Notice that the maximization on z depends on \mathbf{k} . When (3) is close to 1/2, the optimal strategy for distinguishing the real from the ideal key is as good as a random guess; this is the security condition that we consider.

In the scenario of key distribution from Bell-violating correlations, Alice has N systems, Bob has N systems and, without loss of generality, Eve has one "big" system, jointly distributed according to an arbitrary (unknown) $P_{\mathbf{A},\mathbf{B},E|\mathbf{X},\mathbf{Y},Z}$. It is usually assumed that this is an $(2N + 1)$ -partite nonsignaling distribution [6] (*i.e.* the marginals only depend on their corresponding observables), however, we are able to proceed with a weaker assumption. If Alice holds the raw key \mathbf{A} , then Bob's N systems can be considered as a single "big" system, that is, no-signaling within Bob's systems is not required in our proof. We refer to this assumption as " $(N + 2)$ -partite no signaling". According to [13], the even weaker assumption of 3-partite no signaling (where Alice's N systems are also considered a single one) is insufficient to warrant security. Hence, our assumption cannot be relaxed in the obvious way.

Main result: For almost all functions $h : \{0, 1\}^{N_r} \rightarrow \{0, 1\}^{N_s}$ and any $(N_r + 2)$ -partite nonsignaling distribution $P_{\mathbf{A}, \mathbf{B}, E | \mathbf{X}, \mathbf{Y}, Z}$, the random variable $\mathbf{K} = h(\mathbf{A})$ satisfies

$$\sum_{\mathbf{k}} \max_z \left\| P_{\mathbf{k}, E | \mathbf{X}=\mathbf{0}, z} - 2^{-N_s} P_{E|z} \right\| \leq \sqrt{2}^{N_s - N_r + \sqrt{N_r}} \langle \text{CHSH} |^{\otimes N_r} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle, \quad (4)$$

where $\mathbf{0}$ is the zero vector.

The ‘‘almost all’’ in the above statement means that, if we pick a random function h with uniform distribution over all functions, then the probability that h does not satisfy (4) is of order $e^{-2\sqrt{N_r}}$.

3 Proof

We begin by stating two lemmas that are proven at the end of this section.

Lemma 1. For any $(N_r + 1)$ -partite nonsignaling distribution $P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}}$ we have $P_{\mathbf{a} | \mathbf{x}=\mathbf{0}} = \langle \Gamma_{\mathbf{a}} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle$, where $|\Gamma_{\mathbf{a}}\rangle = |\gamma_{a_1}\rangle \otimes \cdots \otimes |\gamma_{a_{N_r}}\rangle$ and

$$|\gamma_0\rangle = \frac{1}{8} \left[\begin{array}{cc|cc} 1 & -3 & 1 & 5 \\ 5 & 1 & -3 & 1 \\ \hline 1 & -3 & 5 & 1 \\ 5 & 1 & 1 & -3 \end{array} \right], \quad |\gamma_1\rangle = \frac{1}{8} \left[\begin{array}{cc|cc} 1 & 5 & 1 & -3 \\ -3 & 1 & 5 & 1 \\ \hline 1 & 5 & -3 & 1 \\ -3 & 1 & 1 & 5 \end{array} \right]. \quad (5)$$

(Recall that $(N_r + 1)$ -partite nonsignaling means that \mathbf{B} and \mathbf{X} correspond to the outcome and observable of a single system.)

Any function h is characterized by specifying for each $\mathbf{k} \in \{0, 1\}^{N_s}$ the set of strings $\mathcal{A}_{\mathbf{k}} \subseteq \{0, 1\}^{N_r}$ which are mapped to \mathbf{k} , or in other words $\mathcal{A}_{\mathbf{k}} = h^{-1}(\mathbf{k})$. Let us use the notation $|\Gamma_{\mathcal{A}_{\mathbf{k}}}\rangle = \sum_{\mathbf{a} \in \mathcal{A}_{\mathbf{k}}} |\Gamma_{\mathbf{a}}\rangle$ which allows to write $P_{\mathbf{k} | \mathbf{x}=\mathbf{0}} = \langle \Gamma_{\mathcal{A}_{\mathbf{k}}} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle$ for all \mathbf{k} .

Lemma 2. Almost all functions $h : \{0, 1\}^{N_r} \rightarrow \{0, 1\}^{N_s}$ satisfy

$$\left| 2^{N_s} |\Gamma_{\mathcal{A}_{\mathbf{k}}}\rangle - 4^{-N_r} |1s\rangle \right| \preceq \sqrt{2}^{N_s - N_r + \sqrt{N_r}} |\text{CHSH}\rangle^{\otimes N_r}, \quad (6)$$

for all \mathbf{k} , where the symbol $|\cdot|$ denotes entry-wise absolute value, the symbol \preceq denotes entry-wise less or equal than, and $|1s\rangle \in \mathbb{R}^{16^{N_r}}$ is the vector with all entries equal to one.

In the next, we only consider functions h which satisfy inequality (6). In the following chain of equalities and inequalities we respectively use: the definition of

marginal distribution plus no signaling; the definition of $|\Gamma_{\mathcal{A}_k}\rangle$; the convexity of the absolute-value function; Lemma 2; and the definition of marginal:

$$\begin{aligned}
& \sum_{\mathbf{k}} \max_z \|P_{\mathbf{k},E|\mathbf{x}=\mathbf{0},z} - 2^{-N_s} P_{E|z}\| \\
&= \sum_{\mathbf{k}} \max_z \sum_e P_{e|z} |P_{\mathbf{k}|\mathbf{x}=\mathbf{0},e,z} - 2^{-N_s}| \\
&= \sum_{\mathbf{k}} \max_z \sum_e P_{e|z} \left| \left(\langle \Gamma_{\mathcal{A}_k} | - 2^{-N_s-2N_r} \langle 1s | \right) |P_{\mathbf{A},\mathbf{B}|\mathbf{X},\mathbf{Y},e,z}\rangle \right| \\
&\leq \sum_{\mathbf{k}} \max_z \sum_e P_{e|z} \left| \langle \Gamma_{\mathcal{A}_k} | - 2^{-N_s-2N_r} \langle 1s | \right| |P_{\mathbf{A},\mathbf{B}|\mathbf{X},\mathbf{Y},e,z}\rangle \\
&\leq \sum_{\mathbf{k}} 2^{-N_s} \sum_e P_{e|z} \sqrt{2^{N_s-N_r+\sqrt{N_r}}} \langle \text{CHSH} |^{\otimes N_r} |P_{\mathbf{A},\mathbf{B}|\mathbf{X},\mathbf{Y},e,z}\rangle \\
&= \sqrt{2^{N_s-N_r+\sqrt{N_r}}} \langle \text{CHSH} |^{\otimes N_r} |P_{\mathbf{A},\mathbf{B}|\mathbf{X},\mathbf{Y}}\rangle .
\end{aligned} \tag{7}$$

This is precisely the statement of the main result (4).

Proof of Lemma 1. Here we use the same tools as in the proof of Lemma 16 from [6]. By definition we can write $P_{\mathbf{a}|\mathbf{x}=\mathbf{0}} = \langle \Gamma'_{\mathbf{a}} | P_{\mathbf{A},\mathbf{B}|\mathbf{X},\mathbf{Y}} \rangle$, where $|\Gamma'_{\mathbf{a}}\rangle = |\gamma'_{a_1}\rangle \otimes \cdots \otimes |\gamma'_{a_{N_r}}\rangle$ and

$$|\gamma'_0\rangle = \left[\begin{array}{cc|cc} 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ \hline 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{array} \right], \quad |\gamma'_1\rangle = \left[\begin{array}{cc|cc} 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ \hline 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{array} \right]. \tag{8}$$

The fact that Bob (when considered as a single system) cannot signal to Alice can be expressed as $P_{\mathbf{A}|\mathbf{X},\mathbf{y}} = P_{\mathbf{A}|\mathbf{X},\mathbf{y}'}$ for any \mathbf{y}, \mathbf{y}' . This implies that $P_{\mathbf{a}|\mathbf{x}=\mathbf{0}} = \langle \Gamma''_{\mathbf{a}} | P_{\mathbf{A},\mathbf{B}|\mathbf{X},\mathbf{Y}} \rangle$ where $|\Gamma''_{\mathbf{a}}\rangle = |\gamma''_{a_1}\rangle \otimes \cdots \otimes |\gamma''_{a_{N_r}}\rangle$ and

$$|\gamma''_0\rangle = \frac{1}{4} \left[\begin{array}{cc|cc} 2 & 0 & -1 & 1 \\ 2 & 0 & -1 & 1 \\ \hline 2 & 0 & 1 & -1 \\ 2 & 0 & 1 & -1 \end{array} \right], \quad |\gamma''_1\rangle = \frac{1}{4} \left[\begin{array}{cc|cc} 0 & 2 & 1 & -1 \\ 0 & 2 & 1 & -1 \\ \hline 0 & 2 & -1 & 1 \\ 0 & 2 & -1 & 1 \end{array} \right]. \tag{9}$$

The fact that each of the N_r Alice's systems cannot signal to the rest, together with Bob's systems, implies the statement of the lemma. \square

Proof of Lemma 2. Within this proof, the entries of any vector $|\Phi\rangle \in \mathbb{R}^{16^{N_r}}$ are labeled as $\Phi(\mathbf{a}, \mathbf{b}, \mathbf{x}, \mathbf{y})$. Also, for any pair of bit-strings \mathbf{x}, \mathbf{y} : (i) the string $\mathbf{x} \cdot \mathbf{y}$ is the bit-wise product, (ii) the string $\mathbf{x} \oplus \mathbf{y}$ is the bit-wise xor, and (iii) the integer $\|\mathbf{x}\|$ is the number of ones in \mathbf{x} (or equivalently, the L_1 -norm of \mathbf{x}). Using this notation we can write the entries of the vector $|\text{CHSH}\rangle^{\otimes N_r}$ as $\text{CHSH}^{\otimes N_r}(\mathbf{a}, \mathbf{b}, \mathbf{x}, \mathbf{y}) = 4^{-N_r} 5^{\|\mathbf{a} \oplus \mathbf{b} \oplus \mathbf{x} \cdot \mathbf{y}\|}$.

Next we prove inequality (6) for a given \mathbf{k} and a given entry $(\mathbf{a}_0, \mathbf{b}_0, \mathbf{x}_0, \mathbf{y}_0)$. Let $V_{\mathbf{a}} = 1$ if the string \mathbf{a} belongs to $\mathcal{A}_{\mathbf{k}}$, and $V_{\mathbf{a}} = 0$ otherwise. If the random function h has uniform distribution over the set of all functions, then the random variables $V_{\mathbf{a}}$ (for all \mathbf{a}) are independent and distributed according to $\text{Prob}\{V_{\mathbf{a}} = 1\} = 2^{-N_s}$. Let $\mu_{\mathbf{a}} = \Gamma_{\mathbf{a}}(\mathbf{a}_0, \mathbf{b}_0, \mathbf{x}_0, \mathbf{y}_0)$, $M = \|\mathbf{a}_0 \oplus \mathbf{b}_0 \oplus \mathbf{x}_0 \cdot \mathbf{y}_0\|$, and note that $|\mu_{\mathbf{a}}| \leq 5^M 8^{-N_r}$ for all \mathbf{a} . For any J and $\beta \geq 0$ the exponential Chebichev inequality gives a bound for the probability of large deviations in terms of an expected value $\langle \cdot \rangle$:

$$\begin{aligned} & \text{Prob}\{\sum_{\mathbf{a}} \mu_{\mathbf{a}} V_{\mathbf{a}} \geq J\} \\ & \leq \langle \exp[\beta \sum_{\mathbf{a}} \mu_{\mathbf{a}} V_{\mathbf{a}} - \beta J] \rangle \\ & \leq \exp[2^{-N_s} \sum_{\mathbf{a}} (\beta \mu_{\mathbf{a}} + \beta^2 \mu_{\mathbf{a}}^2) - \beta J] , \end{aligned} \quad (10)$$

where the second inequality holds if $|\beta 5^M 8^{-N_r}| \leq 1$. Using $\sum_{\mathbf{a}} \mu_{\mathbf{a}} = 4^{-N_r}$, $\sum_{\mathbf{a}} \mu_{\mathbf{a}}^2 \leq 2^{-5N_r} 5^{2M}$, and substituting $J = 2^{-N_s - 2N_r} + 2^{(\sqrt{N_r} - N_r - N_s)/2} 4^{-N_r} 5^M$, $\beta = 2^{(\sqrt{N_r} + N_r + N_s)/2} 4^{N_r} 5^{-M}$ we obtain

$$\text{Prob}\{\sum_{\mathbf{a}} \mu_{\mathbf{a}} V_{\mathbf{a}} \geq 2^{-N_s - 2N_r} + 2^{(\sqrt{N_r} - N_r - N_s)/2} 4^{-N_r} 5^M\} \leq e^{-2\sqrt{N_r}/4} . \quad (11)$$

This, together with an upper bound obtained in a similar way gives

$$|2^{N_s} \Gamma_{\mathcal{A}_{\mathbf{k}}}(\mathbf{a}_0, \mathbf{b}_0, \mathbf{x}_0, \mathbf{y}_0) - 4^{-N_r}| \leq \sqrt{2^{N_s - N_r + \sqrt{N_r}}} \text{CHSH}^{\otimes N_r}(\mathbf{a}_0, \mathbf{b}_0, \mathbf{x}_0, \mathbf{y}_0) , \quad (12)$$

with high probability. However, we want this to hold for all \mathbf{k} and all entries $(\mathbf{a}, \mathbf{b}, \mathbf{x}, \mathbf{y})$. There is an exponential number of \mathbf{k} -values (2^{N_s}) and entries (16^{N_r}), but the super-exponential bound for the probability (11) keeps the probability of a function h not satisfying (6) small. \square

4 Key distribution

In this section we explain how to apply our result on PA to a general key distribution protocol.

4.1 Error correction and public communication

It is usually the case that the given distribution $P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}}$ does not provide perfect correlations between \mathbf{A} and \mathbf{B} . Hence, if \mathbf{A} is the raw key, Bob has to correct the errors in \mathbf{B} before applying the hash function h . This can be done by Alice publishing some information about \mathbf{A} , and Bob using it for correcting his errors.

Other procedures within the key distribution protocol may also require public communication. Let the N_c -bit string \mathbf{C} be all information published by Alice, so \mathbf{C} is a function of \mathbf{A} . We can still use the main result (4) in this new setting if we let both, \mathbf{K} and \mathbf{C} , to be the outcomes of the function $h : \{0, 1\}^{N_r} \rightarrow \{0, 1\}^{N_c} \times \{0, 1\}^{N_s}$. However, \mathbf{K} and \mathbf{C} play different roles: \mathbf{K} is the secret key

and \mathbf{C} is part of the information owned by Eve. Therefore, the extension of the security condition (4) to the present setting is

$$\begin{aligned}
& \sum_{\mathbf{k}, \mathbf{c}} \max_z \|P_{\mathbf{k}, \mathbf{c}, E|z} - 2^{-N_s} P_{\mathbf{c}, E|z}\| \\
\leq & \sum_{\mathbf{k}, \mathbf{c}} \max_z \left(\|P_{\mathbf{k}, \mathbf{c}, E|z} - 2^{-N_c - N_s} P_{E|z}\| + 2^{-N_s} \|P_{\mathbf{c}, E|z} - 2^{-N_c} P_{E|z}\| \right) \\
\leq & 2\sqrt{2}^{N_c + N_s - N_r + \sqrt{N_r}} \langle \text{CHSH} |^{\otimes N_r} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle, \tag{13}
\end{aligned}$$

where here and in the rest of the section, the conditioning on the event $\mathbf{x} = \mathbf{0}$ is implicit. The first inequality follows from the triangular inequality, and the second one from (4). The secret key is secure if the right-hand side of (13) can be made arbitrarily small (as N_r grows). This happens when the length of the final key is

$$N_s \approx N_r - N_c - 2 \log_2 \langle \text{CHSH} |^{\otimes N_r} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle, \tag{14}$$

up to sub-linear terms. This rate formula can be improved by modifying $|\text{CHSH}\rangle$ in the following way: take the expression (1) and substitute 5 by $\sqrt{17}$. The security of this rate will be proven somewhere else.

4.2 Parameter estimation

In the unconditional-security scenario, the honest parties are given N pairs of systems in a completely unknown global distribution. However, to perform a key distribution protocol, and in particular to set the numbers N_s and N_c , they need to bound some quantities, like for instance $\langle \text{CHSH} |^{\otimes N} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle$. In order to do so, they invest some of the given pairs to obtain information about the distribution $P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}}$ of the N_r remaining pairs. More precisely, they compute the bounds for N_s, N_c for another distribution $P'_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}}$, which is warranted to be close to the real (unknown) one $\|P'_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} - P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}}\| \leq \epsilon$. This is explained with full detail in [6].

Now one has to show that when the honest parties estimate N_s, N_c with the primed distribution (instead of the actual one) the protocol is still secure. Let $P_{\mathbf{A}, \mathbf{B}, E | \mathbf{X}, \mathbf{Y}, Z}$ be the global distribution for the N_r pairs constituting the two versions of the raw key, together with Eve's system. If we define its primed version as $P'_{\mathbf{a}, \mathbf{b}, e | \mathbf{x}, \mathbf{y}, z} = P_{e|z, \mathbf{a}, \mathbf{b}, \mathbf{x}, \mathbf{y}} P'_{\mathbf{a}, \mathbf{b} | \mathbf{x}, \mathbf{y}}$, then

$$\begin{aligned}
& \sum_{\mathbf{k}} \max_z \|P'_{\mathbf{k}, E|z} - P_{\mathbf{k}, E|z}\| \\
= & \sum_{\mathbf{k}} \max_z \left\| \sum_{\mathbf{a} \in \mathcal{A}_{\mathbf{k}}} (P'_{\mathbf{a}} - P_{\mathbf{a}}) P_{E|z, \mathbf{a}} \right\| \\
\leq & \sum_{\mathbf{k}} \max_z \sum_{\mathbf{a} \in \mathcal{A}_{\mathbf{k}}} \|(P'_{\mathbf{a}} - P_{\mathbf{a}}) P_{E|z, \mathbf{a}}\| \\
= & \|P'_{\mathbf{A}} - P_{\mathbf{A}}\| \leq \epsilon. \tag{15}
\end{aligned}$$

Recall that $\mathbf{x} = \mathbf{0}$ is still implicit. If we use the triangular inequality, and the bounds (13) and (15) we achieve our goal:

$$\begin{aligned}
& \sum_{\mathbf{k}, \mathbf{c}} \max_z \|P_{\mathbf{k}, \mathbf{c}, E|z} - 2^{-N_s} P_{E, \mathbf{c}|z}\| \\
& \leq \sum_{\mathbf{k}, \mathbf{c}} \max_z \left(\|P'_{\mathbf{k}, \mathbf{c}, E|z} - 2^{-N_s} P'_{E, \mathbf{c}|z}\| + \|P'_{\mathbf{k}, \mathbf{c}, E|z} - P_{\mathbf{k}, \mathbf{c}, E|z}\| + 2^{-N_s} \|P'_{\mathbf{c}, E|z} - P_{\mathbf{c}, E|z}\| \right) \\
& \leq 2\sqrt{2}^{N_s + N_c - N_r + \sqrt{N_r}} \langle \text{CHSH} |^{\otimes N_r} | P'_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle + 2\epsilon .
\end{aligned} \tag{16}$$

This provides the security bound for the real (unknown) distribution in terms of properties of any primed distribution.

5 The unit-rate protocol

The above PA scheme has zero rate when the given correlations are generated by measuring quantum systems —even maximally-entangled states. In this section we analyze a different scheme which yields similar rates as if assuming that the adversary is limited by quantum mechanics, instead of only no signaling. This method was first introduced in [2] and further developed in [5]. The essential novelty is to measure each system with one among $m \geq 2$ observables. The above scheme is precisely the $m = 2$ case.

Instead of the CHSH, we use the Braunstein-Caves Bell inequality [15], which can be expressed as $\langle \text{BC} | P_{A, B | X, Y} \rangle \geq 2$, with

$$|\text{BC}\rangle = \frac{1}{2m} \left[\begin{array}{cc|cc|} 1 & \alpha & 1 & \alpha & & & \\ \alpha & 1 & \alpha & 1 & & & \\ \hline & & 1 & \alpha & 1 & \alpha & \\ & & \alpha & 1 & \alpha & 1 & \\ \hline & & & & \ddots & \ddots & \\ & & & & & \ddots & 1 \ \alpha \\ & & & & & & \alpha \ 1 \\ \hline \alpha & 1 & & & & & 1 \ \alpha \\ 1 & \alpha & & & & & \alpha \ 1 \end{array} \right] , \tag{17}$$

where $\alpha = 2m + 1$, and the empty entries represent zeroes. Notice that for $m = 2$ this is equivalent to the CHSH inequality (1). Following the same methods as above, one can prove analogous results (4, 13, 16) and obtain the key rate

$$N_s \approx N_r - N_c - 2 \log_2 \langle \text{BC} |^{\otimes N_r} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle . \tag{18}$$

This rate formula can be improved by modifying $|\text{BC}\rangle$ in the following way: take the expression (17) and substitute α by $\sqrt{1 + 4m^2}$. The security of this rate will be proven somewhere else.

If Alice and Bob share singlets $|00\rangle + |11\rangle$, or something close to it, and measure them with all the observables corresponding to points in the equator of the block sphere (see [2, 5, 6] for details), the generated correlations satisfy $\langle \text{BC} |^{\otimes N_r} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle \approx 1$, for large m . If properly measured, singlets provide perfect correlations between \mathbf{A} and \mathbf{B} , hence $N_c \approx 0$. Using formula (18), the secret key rate is *one secret bit per singlet*: $N_s \approx N_r$. This rate cannot be improved because it is the maximum rate achievable against a much weaker (quantum) adversary.

6 Conclusions

We establish, for the first time, that key distribution from Bell-violating correlations is secure and efficient. Even according to the strongest notion of security, the so called universally-composable security. A key point is that randomness extraction, or equivalently privacy amplification, can be performed with a constant hash function. If one assumes only no signaling, random hashing seems to be useless; given that Eve can choose Z and the global distribution $P_{\mathbf{A}, \mathbf{B}, E | \mathbf{X}, \mathbf{Y}, Z}$ depending on the instance of the hash function, potentially canceling the average over hash functions.

This novelty contrasts with previous methods for extracting randomness (two-universal hash [11], extractors, etc.), which need random functions. We believe that this is a consequence of exchanging entropies by Bell inequalities, because knowing $H_\infty(\mathbf{A} | E)$ is not as informative as knowing $-\log \langle \text{CHSH} |^{\otimes N} | P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}} \rangle$. A high value of the last quantity necessarily implies that $P_{\mathbf{A}, \mathbf{B} | \mathbf{X}, \mathbf{Y}}$ is close to a product (of PR-boxes [10]) distribution, from which randomness can be extracted by a constant function.

But, which constant function? We know that almost all functions do the job, but we lack an explicit construction. Another open question is whether the rates (14) and (18) can be improved. Perhaps, some functions hash better than others.

7 Acknowledgements

The author is grateful to Renato Renner and Andreas Winter for valuable comments. This work is supported by Caixa Manresa and the spanish MEC (FIS2005-04627, FIS2007-60182, Consolider QOIT).

References

- [1] J. S. Bell; Physics **1**(3), 195 (1964).
- [2] J. Barrett, L. Hardy, A. Kent; Phys. Rev. Lett. **95**, 010503 (2005).
- [3] A. Acin, N. Gisin, Ll. Masanes; Phys. Rev. Lett. **97**, 120405 (2006).

- [4] V. Scarani, N. Gisin, N. Brunner, Ll. Masanes, S. Pino, A. Acin; Phys. Rev. A **74**, 042339 (2006).
- [5] A. Acin, S. Massar, S. Pironio; New J. Phys. **8**, 126 (2006).
- [6] Ll. Masanes, R. Renner, A. Winter, J. Barrett, M. Christandl; arXiv:quant-ph/0606049
- [7] R. Canetti; Proc. 42nd IEEE Symposium on Foundations of Computer Science (FOCS), 136 (2001).
- [8] Ll. Masanes, A. Acín, N. Gisin; Phys. Rev. A **73**, 012112 (2006).
- [9] J. F. Clauser, M. A. Horne, A. Shimony, R. A. Holt; Phys. Rev. Lett. **23**, 880 (1969).
- [10] S. Popescu, D. Rohrlich; Found. Phys. **24**, 379 (1994).
- [11] C. H. Bennett, G. Brassard, C. Crépeau, U. M. Maurer; IEEE Trans. Inf. Theory, vol. 41, no. 6 (1995).
- [12] T. M. Cover, J. A. Thomas; *Elements on Information Thoery*, John Wiley & Sons, Inc. (2006).
- [13] S. Wolf, R. Renner; *in preparation*.
- [14] R. Renner; *Security of Quantum Key Distribution*, PhD thesis, quant-ph/0512258.
- [15] S. Braunstein, C. Caves; Ann. Phys. **202**, p. 22 (1990).