

Universal quantum computation in a hidden basis

L. M. Ioannou^{1,*} and M. Mosca^{2,3,†}

¹*Centre for Quantum Computation, University of Cambridge,
Wilberforce Road, Cambridge, CB3 0WA, UK*

²*Institute for Quantum Computing, University of Waterloo,
200 University Avenue, Waterloo, Ontario, N2L 3G1, Canada*

³*Perimeter Institute for Theoretical Physics
31 Caroline Street North, Waterloo, Ontario, N2L 2Y5, Canada*

Let $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ be two states that are promised to come from known subsets of orthogonal subspaces, but are otherwise unknown. We consider computing with respect to the hidden computational basis $\{|\mathbf{0}\rangle, e^{i\theta}|\mathbf{1}\rangle\}^{\otimes n}$ of n logical qubits, for some phase angle θ . We investigate the number of physical copies of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ that are required to perform unitary operations and to prepare quantum states defined with respect to this basis, in the cases where θ is known and unknown. For the former case, we show that phase-invariant unitary operators can be implemented exactly with no copies and that phase-invariant states can be prepared exactly with at most n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$; we give an explicit algorithm for state preparation that is efficient for some classes of states (e.g. symmetric states). For the latter case, the same algorithm can be applied for exact state preparation; for universal computation, we give an efficient approximation algorithm, for which we introduce an analogue of a coherent state of light, which serves as a bounded quantum phase reference frame. We apply our results to quantum-public-key authentication protocols, by showing that a natural class of digital signature schemes for classical messages is insecure and by giving a (potentially secure) protocol for identification.

1 Introduction

We consider a new quantum-information-theoretic problem. Let S_0 and S_1 be two orthogonal subspaces that are *known* in that we can perform universal quantum computation with respect to the computational bases spanning S_0 and S_1 . For $b = 0, 1$, let $A_b \subset S_b$ be a set of pure state vectors, whose classical description is known, such that no two elements in A_b are equal up to global phase. Let $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ denote two states that are unknown but for the fact that $|\mathbf{0}\rangle \in A_0$ and $|\mathbf{1}\rangle \in A_1$. These states define a *hidden (computational) basis* $\{|\mathbf{0}\rangle, e^{i\theta}|\mathbf{1}\rangle\}^{\otimes n}$ of n logical qubits, for some phase angle θ . We investigate the number of physical copies of $|\mathbf{0}\rangle$

*lmi22@cam.ac.uk

†mmosca@iqc.ca

and $|\mathbf{1}\rangle$ that are required to perform unitary operations and to prepare quantum states defined with respect to $\{|\mathbf{0}\rangle, e^{i\theta}|\mathbf{1}\rangle\}^{\otimes n}$ in the following two cases:

- θ is known
- θ is unknown (and uniformly random in $[0, 2\pi)$).

We note that the first case is well defined by virtue of the known classical descriptions of A_0 and A_1 , which disambiguate the global phases of the states $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$.

In Section 2, we look at the case where θ is known and show that any phase-invariant (see Definition 1) unitary operator is exactly implementable without requiring any copies of the states $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$. We then show that any phase-invariant density operator is exactly preparable from at most n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$. We then give an explicit, efficient algorithm for creating symmetric states, based on Ref. [1], which easily generalizes to creating any phase-invariant state. For non-phase-invariant operators, we conjecture that a large number of copies of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ are needed; we give a precise conjecture, in a simplified framework, in the Appendix.

In Section 3, we consider the natural problem of quantum computing with respect to $\{|\mathbf{0}\rangle, e^{i\theta}|\mathbf{1}\rangle\}^{\otimes n}$ for unknown $\theta \in [0, 2\pi)$. First, we show that the associated state-preparation problem is exactly solvable with at most n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$, because such states are always phase invariant. Second, we give an algorithm for efficiently approximating universal quantum computation, using copies of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ as a phase-reference state that mimics a coherent light state.

Our motivation for considering such problems is rooted in quantum-public-key cryptography, a framework introduced in Ref. [2], in which the public keys are identical quantum systems, each of whose state encodes a classical private key. A major open problem in this area is to find an efficient and reusable digital signature scheme (or prove none exists). In Section 4, we show how our state preparation result (for unknown θ) is a cryptanalytic tool, rendering a class of digital signature schemes for classical messages insecure. We also show how our hidden basis framework might be used to build secure quantum-public-key authentication schemes, by giving a (potentially secure) protocol for identification.

2 The case of known θ

Assume $\theta = 0$; we show later that this results in no loss of generality.

2.1 Exact implementation or preparation of phase-invariant operators

For any bit-string $y = y_1 y_2 \cdots y_n \in \{0, 1\}^n$, let

$$|\mathbf{y}\rangle := |y_1\rangle |y_2\rangle \cdots |y_n\rangle. \quad (1)$$

For any $\theta' \in [0, 2\pi]$, let $U(\theta')$ be the *phase-shift* operator on \mathcal{H}^n such that

$$U(\theta') : |\mathbf{y}\rangle \mapsto e^{iH(\mathbf{y})\theta'} |\mathbf{y}\rangle, \quad (2)$$

where $H(\mathbf{y}) := \sum_j y_j$ is the Hamming weight of \mathbf{y} .

Definition 1 (Phase invariant). Let T be any operator on \mathcal{H}^n . Then T is *phase(-shift) invariant* if and only if

$$U(\theta') T U(\theta')^\dagger = T \quad (3)$$

for all $\theta' \in [0, 2\pi]$.

Define the *weight* of $|\mathbf{y}\rangle$ to be $H(\mathbf{y})$, and define the weight- w subspace of \mathcal{H}^n as

$$\mathcal{H}_w^n := \text{span}(\{|\mathbf{x}\rangle : H(\mathbf{x}) = w\}). \quad (4)$$

It is straightforward to show that T is phase invariant if and only if it is block diagonal with respect to the decomposition $\mathcal{H}^n = \bigoplus_{w=0}^n \mathcal{H}_w^n$.

Proposition 1. *If V is a phase invariant unitary operator on $\mathcal{H}^n = \text{span}(\{|\mathbf{0}\rangle, |\mathbf{1}\rangle\}^{\otimes n})$, then V can be implemented exactly (on arbitrary input on \mathcal{H}^n), knowing only that $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ come from known orthogonal subspaces.*

Proof. Fix n . Since V is phase invariant, it is block diagonal with respect to $\bigoplus_{w=0}^n \mathcal{H}_w^n$. Let $\{|w, j\rangle : j = 1, 2, \dots, \binom{n}{w}\}$ be the natural ordered basis for \mathcal{H}_w^n , that is, $|w, j\rangle \in \{|\mathbf{0}\rangle, |\mathbf{1}\rangle\}^{\otimes n}$ for all (w, j) . Without loss of generality, the operator V is specified by 2^n equations of the form

$$|w, j\rangle \mapsto \sum_{k=1}^{\binom{n}{w}} c_{k,j}^w |w, k\rangle. \quad (5)$$

If we fix π_j^w to be any permutation on n objects such that

$$|\pi_j^w(\mathbf{0}^{n-w} \mathbf{1}^w)\rangle = |w, j\rangle, \quad (6)$$

we can rewrite Eq. (5) as

$$|\pi_j^w(\mathbf{0}^{n-w}\mathbf{1}^w)\rangle \mapsto \sum_{k=1}^{\binom{n}{w}} c_{k,j}^w |\pi_k^w(\mathbf{0}^{n-w}\mathbf{1}^w)\rangle. \quad (7)$$

If we assume that the two known subspaces are of dimension d_0 and d_1 , and we substitute into Eq. (7) the two equations

$$|\mathbf{0}\rangle := \sum_{i=1}^{d_0} \alpha_i |a_i\rangle, \quad |\mathbf{1}\rangle := \sum_{j=1}^{d_1} \beta_j |b_j\rangle, \quad (8)$$

where $\{|a_i\rangle\}_i$ and $\{|b_j\rangle\}_j$ are known orthonormal bases of the two known subspaces, we get, after changing the order of summations,

$$\sum_{i_1, \dots, i_{n-w}} \sum_{j_1, \dots, j_w} \alpha_{i_1} \cdots \alpha_{i_{n-w}} \beta_{j_1} \cdots \beta_{j_w} |\pi_j^w(a_{i_1}, \dots, a_{i_{n-w}}, b_{j_1}, \dots, b_{j_w})\rangle \quad (9)$$

$$\mapsto \sum_{i_1, \dots, i_{n-w}} \sum_{j_1, \dots, j_w} \alpha_{i_1} \cdots \alpha_{i_{n-w}} \beta_{j_1} \cdots \beta_{j_w} \left(\sum_{k=1}^{\binom{n}{w}} c_{k,j}^w |\pi_k^w(a_{i_1}, \dots, a_{i_{n-w}}, b_{j_1}, \dots, b_{j_w})\rangle \right). \quad (10)$$

Thus, to achieve the mapping specified in the hidden basis $\{|\mathbf{0}\rangle, |\mathbf{1}\rangle\}^{\otimes n}$ by Eq. (7) for all (w, j) , it suffices that we implement the mapping defined in the known basis $(\{|a_i\rangle\}_i \cup \{|b_j\rangle\}_j)^{\otimes n}$ by the $d_0^{n-w} d_1^w$ equations

$$|\pi_j^w(a_{i_1}, \dots, a_{i_{n-w}}, b_{j_1}, \dots, b_{j_w})\rangle \mapsto \sum_{k=1}^{\binom{n}{w}} c_{k,j}^w |\pi_k^w(a_{i_1}, \dots, a_{i_{n-w}}, b_{j_1}, \dots, b_{j_w})\rangle \quad (11)$$

for all $|a_{i_l}\rangle \in \{|a_i\rangle\}_i$ (for all $l = 1, 2, \dots, n-w$) and for all $|b_{j_{l'}}\rangle \in \{|b_j\rangle\}_j$ (for all $l' = 1, 2, \dots, w$). The total number of equations is $\sum_{w=0}^n \binom{n}{w} d_0^{n-w} d_1^w = (d_0 + d_1)^n$, which is the dimension of the total space; thus, these equations well-define a unitary operator that we can implement, which effects V on \mathcal{H}^n .

Proposition 2. *If ρ is a phase-invariant density operator on $\mathcal{H}^n = \text{span}(\{|\mathbf{0}\rangle, |\mathbf{1}\rangle\}^{\otimes n})$, then ρ can be prepared exactly, using at most n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$, knowing only that $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ come from known orthogonal subspaces.*

Proof. Proposition 1 implies that, in order to prepare any phase-invariant pure state $|\phi\rangle \in \mathcal{H}_w^n$, it suffices to have $(n - w)$ copies of $|\mathbf{0}\rangle$ and w copies of $|\mathbf{1}\rangle$. To see this, note that there exists a unitary operator U_w on \mathcal{H}_w^n mapping

$$|\mathbf{0}\rangle^{\otimes(n-w)}|\mathbf{1}\rangle^{\otimes w} \mapsto |\phi\rangle, \quad (12)$$

and that U_w is (trivially) phase invariant. Since ρ is just a probabilistic distribution of phase-invariant pure states (because it is block diagonal), it follows that ρ is exactly preparable using at most n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ (assuming one can exactly sample from this probability distribution).

Note that Proposition 1 implies that we can exactly implement $U(\theta)$ for any $\theta \in [0, 2\pi)$, from which it follows easily that our assumption that $\theta = 0$ results in no loss of generality.

2.2 Algorithm for exact state preparation of phase-invariant states

Proposition 2 does not address the question of efficiency. Indeed, in some cases, the required unitary operation (denoted U_w in the proof) is efficient, as demonstrated by the following example.

Let $|S_w^n\rangle$ be the normalized symmetric sum of all $\binom{n}{w}$ states in $\{|\mathbf{0}\rangle, |\mathbf{1}\rangle\}^{\otimes n}$ that have weight w . The algorithm for state generation in Ref. [1] can be adapted to transform

$$|\mathbf{0}\rangle^{\otimes(n-w)}|\mathbf{1}\rangle^{\otimes w} \mapsto |S_w^n\rangle. \quad (13)$$

Fix n and assume $0 < w < n$. Hypothetically, suppose we had a copy of $|S_w^n\rangle$ and we measured the leftmost j registers in the basis $\{|\mathbf{0}\rangle, |\mathbf{1}\rangle\}^{\otimes j}$, $j = 2, 3, \dots, n$. Denote the binary outcome of measuring a register by 0 (if the register was in state $|\mathbf{0}\rangle$) or 1 (if the register was in state $|\mathbf{1}\rangle$). Let X_i , for $i = 1, 2, \dots, n$, denote the random variable representing the outcome of measuring register i (registers are enumerated from left to right). For any $x \in \{0, 1\}^{j-1}$ and $x_j \in \{0, 1\}$, define the probabilities

$$p_x := P(X_1 \cdots X_{j-1} = x) \quad (14)$$

$$p_{x_j|x} := P(X_j = x_j | X_1 \cdots X_{j-1} = x), \quad (15)$$

where adjacent bit-values denote string-concatenation and we note that the definition of p_x holds also for $j = n + 1$. Then we have

$$p_{x_j|x} = p_{xx_j}/p_x \quad (16)$$

$$p_{1|x} = (w - H(x))/(l - j + 1) \quad (17)$$

$$= 1 - p_{0|x}. \quad (18)$$

Define the shorthand notation, for nonnegative integers d and $c \geq d$,

$$|d^c\rangle := |\mathbf{0}\rangle^{\otimes(c-d)}|\mathbf{1}\rangle^{\otimes d}. \quad (19)$$

We can prepare $|S_w^n\rangle$ by starting with $|w^n\rangle$, and then applying a sequence of phase invariant unitary operators. For each $j = 2, 3, \dots, n$ and for any $x = x_1x_2 \cdots x_{j-1} \in \{0, 1\}^{j-1}$, we define the operators, for any $d \in \{1, 2, \dots, r\}$,

$$U_j : |\mathbf{x}\rangle|d^{n-(j-1)}\rangle \mapsto |\mathbf{x}\rangle \left(\sqrt{p_{0|x}}|\mathbf{0}\rangle|d^{n-j}\rangle + \sqrt{p_{1|x}}|\mathbf{1}\rangle|(d-1)^{n-j}\rangle \right). \quad (20)$$

Each U_j performs an operation similar to a root-SWAP operator³, controlled on registers 1 through $(j-1)$, swapping register j with the next closest register to the right whose state is orthogonal to the subspace containing $|\mathbf{0}\rangle$. Our U_j also has built into it a final phase-clean-up operation, controlled on registers 1 through j , which removes the imaginary factor of i arising from the root-SWAP operation. Finally, define

$$U_1 : |w^n\rangle \mapsto \sqrt{p_0}|\mathbf{0}\rangle|w^{n-1}\rangle + \sqrt{p_1}|\mathbf{1}\rangle|(w-1)^{n-1}\rangle, \quad (21)$$

where $p_1 = w/n = 1 - p_0$. We can now show that $|S_w^n\rangle = U_n \cdots U_2 U_1 |w^n\rangle$. A straightforward induction (similar to that in Ref. [1]) shows that, after U_j is applied, the state of the n registers is

$$\sum_{x \in \{0,1\}^j} \sqrt{p_x} |\mathbf{x}\rangle |(w - H(x))^{n-j}\rangle \quad (22)$$

so that, after U_n is applied, the state is $\sum_{x \in \{0,1\}^n} \sqrt{p_x} |\mathbf{x}\rangle = |S_w^n\rangle$.

The above algorithm for creating $|S_w^n\rangle$ can be generalized to create any $|\eta\rangle \in \mathcal{H}_w^n$ (and hence any phase-invariant density operator): it is clear that it can be generalized to create any state in \mathcal{H}_w^n that has real coefficients; we refer to Ref. [1] for how to create the correct phases of any complex coefficients of $|\eta\rangle$ efficiently. The general algorithm is efficient as long as the conditional probabilities $p_{x_j|x}$ are efficiently computable, as in the case of the symmetric states $|S_w^n\rangle$.

³For $0 < \alpha < 1$, we can define a *root-SWAP-like* operator, which maps $|\mathbf{0}\rangle|\mathbf{0}\rangle \mapsto |\mathbf{0}\rangle|\mathbf{0}\rangle$, $|\mathbf{0}\rangle|\mathbf{1}\rangle \mapsto \alpha|\mathbf{0}\rangle|\mathbf{1}\rangle + i\sqrt{1-\alpha^2}|\mathbf{1}\rangle|\mathbf{0}\rangle$, $|\mathbf{1}\rangle|\mathbf{0}\rangle \mapsto i\sqrt{1-\alpha^2}|\mathbf{0}\rangle|\mathbf{1}\rangle + \alpha|\mathbf{1}\rangle|\mathbf{0}\rangle$, and $|\mathbf{1}\rangle|\mathbf{1}\rangle \mapsto |\mathbf{1}\rangle|\mathbf{1}\rangle$. When $\alpha = 1/\sqrt{2}$, this is the root-SWAP operator.

2.3 Beyond phase invariance?

One may of course ask about unitary operators and quantum states that are not phase invariant. Regarding the former, recall the finite universal set $\{H, S, T, c\text{-}Z\}$ of gates [3], where

$$H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}, \quad S = \begin{bmatrix} 1 & 0 \\ 0 & i \end{bmatrix}, \quad T = \begin{bmatrix} 1 & 0 \\ 0 & e^{i\pi/4} \end{bmatrix}, \quad c\text{-}Z = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & -1 \end{bmatrix}, \quad (23)$$

and the matrices are defined with respect to $\{|0\rangle, |1\rangle\}$ (in the case of the one-qubit gates) and $\{|0\rangle, |1\rangle\}^{\otimes 2}$ (in the case of the $c\text{-}Z$ gate). Since S , T , and $c\text{-}Z$ are phase invariant, we see that it is the presumed inability to implement the Hadamard gate H exactly that prevents us from performing exact universal quantum computation in the hidden basis $\{|0\rangle, |1\rangle\}^{\otimes n}$. Indeed, we conjecture that, for worst-case A_0 and A_1 (see Section 1), a large number of copies of $|0\rangle \in A_0$ and $|1\rangle \in A_1$ are necessary to implement one Hadamard gate or to prepare one copy of $(|0\rangle + |1\rangle)/\sqrt{2}$, if the implementation/preparation is well approximated for every $|0\rangle \in A_0$ and every $|1\rangle \in A_1$; see Remark 5 and the Appendix for a precise conjecture in a simplified framework.

In the next section, we show that by allowing θ to be unknown, the Hadamard gate becomes something we can approximate with few copies of $|0\rangle$ and $|1\rangle$.

3 The case of unknown θ

In practice, performing a quantum computation in the basis $\{|0\rangle, |1\rangle\}^{\otimes n}$, for the known qubit-states $|0\rangle$ and $|1\rangle$, is actually equivalent to performing a computation in the basis $\{|0\rangle, e^{i\phi}|1\rangle\}^{\otimes n}$, where one replaces $|1\rangle$ with $e^{i\phi}|1\rangle$ in all the operations. For example, in optics, one typically assumes that a laser outputs coherent states $\sum_{w=0}^{\infty} (\gamma^w/\sqrt{w!})|w\rangle$ with a random, unknown, but consistent, phase parameter $\phi = \arg(\gamma)$ (see, e.g., Ref. [4]). When using these coherent states to drive transformations in the qubits, this is equivalent to performing the entire computation in the basis $\{|0\rangle, e^{i\phi}|1\rangle\}^{\otimes n}$. It is essential that the experimentalist maintains a consistent phase reference for the duration of the computation, but the actual value of ϕ is unimportant.

Thus, we now allow θ to be unknown and uniformly random in $[0, 2\pi)$, and consider the problems of state preparation and universal computation with respect to $\{|0\rangle, e^{i\theta}|1\rangle\}^{\otimes n}$.

3.1 Exact state preparation

Theorem 3. *Let $\rho(\theta)$ be any density operator on the span of $\{|0\rangle, e^{i\theta}|1\rangle\}^{\otimes n}$ such that the elements of the matrix with respect to $\{|0\rangle, e^{i\theta}|1\rangle\}^{\otimes n}$ that represents $\rho(\theta)$ are known. Then the*

uniform mixture over $\theta \in [0, 2\pi)$ of $\rho(\theta)$ can be prepared exactly, using at most n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$, knowing only that $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ come from known orthogonal subspaces.

Proof. This follows immediately from Proposition 2, by noting that

$$\frac{1}{2\pi} \int_0^{2\pi} \rho(\theta) d\theta \quad (24)$$

is phase invariant.

Example 1. Consider the state $\rho(\theta) = |\varphi(\theta)\rangle\langle\varphi(\theta)|$, where

$$|\varphi(\theta)\rangle = \left(\frac{|\mathbf{0}\rangle + e^{i\theta}|\mathbf{1}\rangle}{\sqrt{2}} \right)^{\otimes n} = \frac{1}{2^{n/2}} \sum_{w=0}^n \sqrt{\binom{n}{w}} e^{iw\theta} |S_w^n\rangle. \quad (25)$$

After averaging this state over θ , we get the mixture

$$\sum_{w=0}^n \binom{n}{w} 2^{-n} |S_w^n\rangle\langle S_w^n|. \quad (26)$$

We showed in Section 2.2 how to create the states $|S_w^n\rangle$ efficiently, using at most n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$.

3.2 Approximate universal computation with a phase reference frame

Let us consider a general quantum computation in the hidden n -logical-qubit computational basis $\{|\mathbf{0}\rangle, e^{i\theta}|\mathbf{1}\rangle\}^{\otimes n}$ for unknown θ , uniformly random in $[0, 2\pi)$. If we began such a computation with the goal of preparing a certain state in the span of $\{|\mathbf{0}\rangle, e^{i\theta}|\mathbf{1}\rangle\}^{\otimes n}$, we could prepare any state we like using Theorem 3, as long as we have n copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$. But what if, more generally, we would like to carry out an arbitrary quantum computation? We now show how we can achieve this approximately, by using copies of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ as a phase reference frame. It follows from Section 2.3 that it suffices for us to show how to approximately implement the Hadamard gate

$$H_\theta := \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & e^{-i\theta} \\ e^{i\theta} & -1 \end{bmatrix} \quad (27)$$

on an arbitrary input. Suppose we have been given t copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$.

We can actually implement, for any $\alpha \in [0, 1]$, the generalized Hadamard gate

$$H_\theta(\alpha) : \quad |\mathbf{0}\rangle \mapsto \alpha|\mathbf{0}\rangle + \sqrt{1-\alpha^2}e^{i\theta}|\mathbf{1}\rangle \quad (28)$$

$$e^{i\theta}|\mathbf{1}\rangle \mapsto \sqrt{1-\alpha^2}|\mathbf{0}\rangle - \alpha e^{i\theta}|\mathbf{1}\rangle. \quad (29)$$

Just as before, we will make use of phase invariant root-SWAP-like operations, which introduce imaginary i factors; thus, it will be more convenient to directly implement the gate,

$$G_\theta(\alpha) : \begin{aligned} |\mathbf{0}\rangle &\mapsto \alpha|\mathbf{0}\rangle + \sqrt{1-\alpha^2}ie^{i\theta}|\mathbf{1}\rangle \\ |\mathbf{1}\rangle &\mapsto \sqrt{1-\alpha^2}ie^{-i\theta}|\mathbf{0}\rangle + \alpha|\mathbf{1}\rangle, \end{aligned} \quad (30)$$

$$|\mathbf{1}\rangle \mapsto \sqrt{1-\alpha^2}ie^{-i\theta}|\mathbf{0}\rangle + \alpha|\mathbf{1}\rangle, \quad (31)$$

and then we have, for example, $ZSG_\theta(\alpha)SZ = H_\theta(\alpha)$, where Z is the (phase invariant) Pauli- Z gate

$$Z = \begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix} \quad (32)$$

and S is defined in Eq. (23). Also, for clarity of exposition, we will assume $\alpha = 1/\sqrt{2}$ (but we will indicate in footnotes how the procedure is modified for general α). Let $G_\theta := G_\theta(1/\sqrt{2})$.

Consider how one might create $G_\theta|\mathbf{0}\rangle$ starting from $|\mathbf{0}\rangle|\mathbf{1}\rangle^{\otimes t}$. A simple root-SWAP gate applied to the first two registers maps

$$|\mathbf{0}\rangle \underbrace{|\mathbf{1}\rangle|\mathbf{1}\rangle^{\otimes(t-1)}}_{|\Psi\rangle} \mapsto |\mathbf{0}\rangle \underbrace{|\mathbf{1}\rangle|\mathbf{1}\rangle^{\otimes(t-1)}}_{|a\rangle} + i|\mathbf{1}\rangle \underbrace{|\mathbf{0}\rangle|\mathbf{1}\rangle^{\otimes(t-1)}}_{|b\rangle}. \quad (33)$$

Since $|a\rangle$ and $|b\rangle$ are very different (in fact, orthogonal) vectors, the quantity on the right-hand side of Eq. (33) cannot be well approximated by the product state $(|\mathbf{0}\rangle + i|\mathbf{1}\rangle)|\Psi'\rangle$ for some state $|\Psi'\rangle$. Instead of starting with $|\Psi\rangle = |\mathbf{1}\rangle^{\otimes t}$ as the resource of $|\mathbf{1}\rangle$'s, can we find some other state $|\Psi\rangle$ that is approximately invariant under the removal (swapping out) of one copy of $|\mathbf{1}\rangle$? Here, we take inspiration from a coherent light state $\sum_{w=0}^{\infty} (\gamma^w/\sqrt{w!})|w\rangle$, which is a resource of photons with this property: if you take one photon away, the coherent state is unchanged up to a slight correction in the amplitudes (it is an eigenstate of the photon-annihilation operator). Recalling the definition in Eq. (19), we mimic coherent light states with the following states

$$|\Psi_\theta^t\rangle := \sum_{w=1}^t e^{iw\theta}|w^t\rangle \quad (34)$$

defined for all $\theta \in [0, 2\pi)$. Each occurrence of $|\mathbf{1}\rangle$ (respectively, $|\mathbf{0}\rangle$) in the state $|w^t\rangle$ is analogous to one photon (respectively, one vacuum). Thus, it will be convenient to refer to the state $|w^t\rangle$ as a **1-number state**, in analogy with the photon-number state $|w\rangle$. (In the right-hand side of Eq. (34), we could have had the summation start at $w = 0$; we choose $w = 1$ to make the analysis that follows cleaner, while not significantly affecting the quality of the approximation).

Remark 4. Note that since we are not restricted to the standard interaction Hamiltonians present in Nature (because we are just mimicking such interactions using a universal quantum

computer), our version of the coherent states, as well as how they interact with the other systems, looks slightly different; we need only mimic some of the main properties of coherent light states, for example, that the argument (phase angle) of successive coefficients scales linearly with the photon number. In general, to achieve an efficient approximation, there is some freedom in the choice of the moduli of the coefficients of our coherent state analogues. For clarity of presentation, we have chosen to use the simplest coefficients, with constant modulus. However, one could specify a cost function and optimize the moduli accordingly, with modest gain in the quality of the approximation.⁴

Define the phase-invariant controlled-root-SWAP gate U , which, for fixed t , acts on $(t + 1)$ equally-sized registers, and in particular operates as follows for any $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$ from known orthogonal subspaces:

$$U : |\mathbf{0}\rangle|a^t\rangle \mapsto |\mathbf{0}\rangle|a^t\rangle + i|\mathbf{1}\rangle|(a - 1)^t \quad (35)$$

$$|\mathbf{1}\rangle|b^t\rangle \mapsto i|\mathbf{0}\rangle|(b + 1)^t + |\mathbf{1}\rangle|b^t\rangle, \quad (36)$$

for all $a = 1, 2, \dots, t$ and all $b = 0, 1, \dots, (t - 1)$.⁵ Now we note that

$$\frac{1}{2\pi} \int_0^{2\pi} d\theta |\Psi_\theta^t\rangle \langle \Psi_\theta^t| = \frac{1}{t} \sum_{w=1}^t |w^t\rangle \langle w^t|; \quad (37)$$

thus we can prepare the state $|\Psi\rangle = |\Psi_\theta^t\rangle$ for a random value of θ by preparing a uniformly random $\mathbf{1}$ -number state, which is easy to do with t copies each of $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$. Let $|\phi\rangle$ be an arbitrary one-logical-qubit pure state to which we want to apply G_θ . Applying U to $|\phi\rangle|\Psi_\theta^t\rangle$, the resulting state contains the term

$$\sqrt{\frac{t-2}{t}} (G_\theta|\phi\rangle) \left(\frac{1}{\sqrt{t-2}} \sum_{w=2}^{t-1} e^{i\theta w} |w^t\rangle \right). \quad (38)$$

⁴States that are similar to our coherent-state analogues $|\Psi_\theta^t\rangle$ have independently been used in Ref. [5]. In their application, the phase parameter is not an issue. Rather, they use this property of coherent states behaving more and more “classically”, i.e. with less and less disturbance to the coherent state, as the size of the coherent state gets bigger. In their case, a bigger coherent state corresponds to a larger amount of shared entanglement, and they used this to show that more entanglement always improves the success probability of their protocol. Generally, all such states are forms of “embezzling” states [6, 7].

⁵Here is a complete description of U : If the registers are enumerated $0, 1, \dots, t$ starting from the left, then U applies the root-SWAP to registers 0 and j (for $j \geq 1$) exactly when *either* registers 0 through $(j - 1)$ are in the state subspace containing $|\mathbf{0}\rangle$ and registers j, \dots, t are in the subspace containing $|\mathbf{1}\rangle$ *or* registers 1 through j are in the subspace containing $|\mathbf{0}\rangle$ and registers 0 and $j + 1, \dots, t$ are in the subspace containing $|\mathbf{1}\rangle$ (and, otherwise, U acts as the identity operator). In the case of general α , use the root-SWAP-like operator (defined in a previous footnote) instead of the root-SWAP.

The other (“junk”) terms are of **1**-number 0, 1, and t . Note that terms of different **1**-number are orthogonal. Recall that it suffices to compute the minimum gate fidelity over all *pure* inputs $|\phi\rangle$, because of the joint concavity of the fidelity [3]. Thus, the G_θ gate was effectively applied with minimum fidelity $\sqrt{(t-2)/t}$, and the rightmost $(t+1)$ registers have this same fidelity with the state $|\Psi_\theta^t(1)\rangle$, where we define

$$|\Psi_\theta^t(i)\rangle := (1/\sqrt{t-2i}) \sum_{w=1+i}^{t-i} e^{i\theta w} |w^t\rangle, \quad (39)$$

for $i \geq 0$. To implement a second G_θ gate, we use these *same* rightmost t registers (whose state is close to $|\Psi_\theta^t(1)\rangle$). And so on. In general, we find that $U|\phi\rangle|\Psi_\theta^t(i)\rangle$ equals

$$\sqrt{\frac{t-2(i+1)}{t-2i}} (G_\theta|\phi\rangle)|\Psi_\theta^t(i+1)\rangle \quad (40)$$

plus orthogonal “junk”, where $|\phi\rangle$ is, again, an arbitrary pure state of a logical qubit. The gate fidelity of the l th approximation of G_θ is thus at least $\sqrt{(t-2l)/t}$ (for sufficiently large t). Thus, to achieve a minimum gate fidelity of $\sqrt{1-\epsilon^2}$ for l arbitrary applications of G_θ , it suffices to have

$$t = \lceil 2l/\epsilon^2 \rceil \quad (41)$$

copies each of $|0\rangle$ and $|1\rangle$.

4 Applications to public-key authentication

Our motivation is information-theoretically-secure *quantum-public-key* cryptography, a framework for which was first proposed by Gottesman and Chuang in Ref. [2]; we describe an example of that framework now.

Let $A_\delta \subset \mathbf{C}^M$ be a set of superpolynomially (in $\log(M)$) many quantum states such that, for every distinct $|\psi\rangle$ and $|\phi\rangle$ in A_δ ,

$$|\langle\psi|\phi\rangle| \leq \delta \quad (42)$$

for some positive constant $\delta < 1$. The states in A_δ are sometimes called *quantum fingerprints*, and explicit constructions for such A_δ , with $|A_\delta| \in 2^{\Omega(M)}$, are known [8]. A (succinct) classical description of A_δ is published.

As part of the key generation procedure, Alice randomly chooses a $|\psi\rangle$ uniformly from A_δ and keeps this choice secret, but she authentically distributes (e.g., by trusted courier) a limited

number of physical copies of $|\psi\rangle$ among several members of the public (including Bob). The classical description of $|\psi\rangle$, which can be encoded by a bit-string of length $\Theta(\log(|A_\delta|))$, serves as part of the *private key*, while several authentic copies of the state $|\psi\rangle$ serve as part of the *public key*. Assuming each copy of $|\psi\rangle$ is an $O(\log(M))$ -qubit state, the maximum number of bits of information one can extract from T copies of $|\psi\rangle$ is $O(T\log(M))$, by the Holevo bound [9, 3]. Thus, as long as $T \ll \log(|A_\delta|)/\log(M)$, the part of the private key corresponding to $|\psi\rangle$ is protected even if T copies of $|\psi\rangle$ exist.

The full private/public key would typically consist of several independent instances of this setup, that is, Alice independently chooses several states $|\psi\rangle \in A_\delta$ and distributes the corresponding copies. This naturally allows for protocols that are the composition of independent instances of an atomic protocol, or *kernel*, that succeeds with only a certain probability. Repeating the kernel sufficiently many times, with independent $|\psi\rangle$ -values each time, can amplify the success probability to an acceptable level. In the case of authentication schemes, “to succeed” means “to correctly ‘accept’ or ‘reject’ a purported message or entity”. In the case of encryption schemes, it means “to securely encrypt/decrypt a message”.

A more general framework can be obtained by allowing the public key to contain other states that may depend on the private key; we will use this more general framework in Section 4.2.

We are primarily interested in public-key *authentication* protocols — either for classical messages, as in digital signature schemes, or for entities, as in identification schemes — a general approach to which is the following. Suppose that A_δ also satisfies the condition

$$\langle 0|\psi\rangle = 0 \tag{43}$$

for all $|\psi\rangle \in A_\delta$ and some known $|0\rangle \in \mathbf{C}^M$. Alice can easily create states like $|0\rangle + |\psi\rangle$ (we will sometimes omit normalization factors) and, more generally, she can perform any computation in the basis $\{|0\rangle, |\psi\rangle\}^{\otimes n}$.

Remark 5. In general, it is not known how to perform such computations efficiently, and we conjecture that it takes superpolynomially (in $\log(M)$) many copies of a uniformly random $|\psi\rangle \in A_\delta$ to prepare even one copy of $|0\rangle + |\psi\rangle$, if the procedure is to work for all $|\psi\rangle \in A_\delta$. We call this the *No-Squashing Conjecture*. We call the task of creating $|0\rangle + |\psi\rangle$ for every $|\psi\rangle \in A_\delta$, given copies of $|\psi\rangle$, *squashing*. See the Appendix for more details about squashing and the No-Squashing Conjecture.

The hope is to use this framework, for example, for Alice to convince Bob that she has prepared some state (like a signature) that no one without full knowledge of $|\psi\rangle$ could have done with only the limited number of copies of the state $|\psi\rangle$ available. Moreover, we are interested in *reusable* schemes, by which we mean that the same private key (and corresponding public keys)

can be used to identify Alice many times or sign many messages from Alice (the digital signature scheme in Ref. [2] is not reusable: it can only be used to sign one message). Our framework may be suitable for reusable schemes, because, as suggested by our example protocol in Section 4.2, it seems to allow protocols where Alice does not divulge (to a verifier or adversary) a significant amount of extra information about the private key (beyond that which is already available from all the copies of the public key), yet retains some advantage over the adversary.

In our cryptographic setting, the unknown state $|\psi\rangle$ is now playing the role of $|\mathbf{1}\rangle$. Thus, for this section of the paper, we redefine all the objects (e.g., $|w^t\rangle$, $|\Psi_\theta^t\rangle$, $|S_w^n\rangle$, H) that depend on $|\mathbf{0}\rangle$ and $|\mathbf{1}\rangle$, by replacing each occurrence of $|\mathbf{0}\rangle$ with $|0\rangle$ and each occurrence of $|\mathbf{1}\rangle$ with $|\psi\rangle$. For example, we now have

$$|w^t\rangle := |0\rangle^{\otimes(t-w)} |\psi\rangle^{\otimes w} \quad (44)$$

and

$$\begin{aligned} H : |0\rangle &\mapsto |0\rangle + |\psi\rangle \\ |\psi\rangle &\mapsto |0\rangle - |\psi\rangle. \end{aligned} \quad (45)$$

Note that $|0\rangle$ (no boldface) is a known vector; our cryptographic framework only needs one unknown state, though it can easily be generalized to a framework that uses two (or more).

4.1 Insecurity of a class of digital signature schemes for classical messages

Theorem 3 can be interpreted as a restriction on any digital signature scheme for classical messages in the above framework. Before we state the result, we give a more detailed description of such a signature scheme.

Suppose that, in the key generation procedure described in the previous section, Alice chose K independent values $|\psi_k\rangle$ from A_δ , $k = 1, 2, \dots, K$. Let x denote the message to be signed. We assume that the full signature state for message x is a J -fold tensor product of states

$$\bigotimes_{j=1}^J \sigma_j(|\psi_{k(j,x)}\rangle), \quad (46)$$

where $k(j, x) \in \{1, 2, \dots, K\}$ is a function depending on the particular scheme, and each $\sigma_j(|\psi_{k(j,x)}\rangle)$ is a density operator on $\text{span}(\{|0\rangle, |\psi_{k(j,x)}\rangle\}^{\otimes n})$ such that the coefficients of $\sigma_j(|\psi_{k(j,x)}\rangle)$ with respect to the basis $\{|0\rangle, |\psi_{k(j,x)}\rangle\}^{\otimes n}$ are publicly known.⁶ Note that, in general, $\sigma_j(|\psi\rangle)$ need not equal $\sigma_{j'}(|\psi\rangle)$ when $j \neq j'$.

⁶These coefficients, which may also depend on the message x , are known in that they do not depend on the private key (classical description of $|\psi_{k(j,x)}\rangle$). This allows the adversary to compute the conditional probabilities required for our state preparation algorithm of Section 2.2.

We assume further that the full verification procedure breaks up into J independent procedures, each denoted P_j , one for each $\sigma_j(|\psi_{k(j,x)}\rangle)$. Thus, if no adversary interferes, Bob would apply the procedure P_j to $\sigma_j(|\psi_{k(j,x)}\rangle)$ (using his copy of the public key and the message) and obtain some measurement statistics. After doing this for all $j = 1, 2, \dots, J$, he would process all the statistics and determine whether to “accept” or “reject” the message-signature pair.

Corollary 6 (Insecurity of a class of digital signature schemes). *Suppose there is a signature scheme with signature state and verification procedure as described above. Suppose further that an adversary can obtain n copies of $|\psi_{k(j,x)}\rangle$, for all $j = 1, 2, \dots, J$. Then the scheme is not information-theoretically secure if, for all $j = 1, 2, \dots, J$, the procedure P_j applied to the state $\sigma_j(e^{i\theta}|\psi_{k(j,x)}\rangle)$ produces the same statistics as if it were applied to $\sigma_j(|\psi_{k(j,x)}\rangle)$, for any $\theta \in [0, 2\pi]$.*

Proof. From Theorem 3, it follows that the adversary can create the uniform mixture over $\theta \in [0, 2\pi)$ of $\sigma_j(e^{i\theta}|\psi_{k(j,x)}\rangle)$. The procedure P_j applied to this mixture will also produce the same statistics as if it were applied to $\sigma_j(|\psi_{k(j,x)}\rangle)$, thus the scheme is not information-theoretically secure.

Recall that the SWAP-test [8, 2] of two registers (labelled 2 and 3) in the states $|\xi\rangle_2$ and $|\phi\rangle_3$ is a measurement (with respect to the computational basis $\{|0\rangle_1, |1\rangle_1\}$) of the control register (labelled 1) of the state

$$(H_1 \otimes I_2 \otimes I_3)(c - \text{SWAP}_{2,3})(|0\rangle_1 + |1\rangle_1)|\xi\rangle_2|\phi\rangle_3/\sqrt{2}, \quad (47)$$

where H_1 is the Hadamard gate (applied to register 1) and $c - \text{SWAP}_{2,3}$ is the controlled-SWAP gate. The probability that the state is $|0\rangle_1$ immediately after the measurement — which corresponds to a *pass* — is $(1 + |\langle \xi | \phi \rangle|^2)/2$. When the registers 2 and 3 are in the mixed states ρ and ρ' , this probability is $(1 + \text{tr}(\rho\rho'))/2$.

We note that, for example, Corollary 6 applies to any scheme such that the only public key states available for use in verification of $\sigma_j(|\psi_{k(j,x)}\rangle)$ are copies of $|\psi_{k(j,x)}\rangle$ (and no other state dependent on the private key) and the verification procedure uses the copies of $|\psi_{k(j,x)}\rangle$ only as input to SWAP-tests (or similar tests for symmetry under permutations [8, 10]). Generally, the corollary implies that the verification procedure for any secure signature scheme in our framework, where the adversary can obtain sufficiently many copies of $|\psi_{k(j,x)}\rangle$, will have to exploit the global phase of the state vector $|\psi_{k(j,x)}\rangle \in A_\delta$ determined by its classical description.

4.2 Example of a cryptographic protocol in this framework

We now give an example of a cryptographic protocol that uses some of the ideas we have presented. The protocol is actually a translation of the honest-verifier identification scheme of

Ref. [11] into our hidden basis setting. The following is an intuitive description (adapted from Section 4.7.5.1 in Goldreich’s book [12]) of how a secure identification scheme works.

Suppose Alice generates a private key and authentically distributes copies of the corresponding public key to any potential users of the scheme, including Bob. If Alice wants to identify herself to Bob (i.e. prove that it is she with whom he is communicating), she invokes the identification protocol by first telling Bob that she is Alice, so that Bob knows he should use the public key corresponding to Alice (assuming Bob possesses public keys from many different people). The ensuing protocol, whatever it is, has the property that the *prover* Alice can convince the *verifier* Bob (except perhaps with negligible probability) that she is indeed Alice, but an adversary Eve cannot fool Bob (except with negligible probability) into thinking that she is Alice, even after having listened in on the protocol between Alice and Bob or having participated as a (dishonest) verifier in the protocol with Alice several times. An *honest-verifier identification protocol* is only intended to be secure under the assumption that Eve can never participate as a (dishonest) verifier (but she may have listened in on Alice and Bob). Note that no identification protocol is secure against a person-in-the-middle attack, where Eve concurrently acts as a verifier with Alice and as a prover with Bob.

As part of the key generation procedure for our protocol, we assume Alice has chosen a random $|\psi\rangle \in A_\delta$ and has distributed at most r copies of the state

$$|\psi\rangle(|0\rangle + |\psi\rangle). \tag{48}$$

This state is the public key for one iteration of the kernel of the protocol. The parameter r is the *reusability* parameter, dictating the maximum number of secure uses of the scheme for a particular public key.

The kernel of our interactive protocol is the following three steps, which form a typical “challenge-response” interactive proof. If the kernel is repeated s times in total, then one copy of the (full) public key (of which there are still r copies in total) would be $\otimes_{i=1}^s |\psi_i\rangle(|0\rangle + |\psi_i\rangle)$, where the $|\psi_i\rangle$ are each independently and uniformly randomly picked from A_δ by Alice. The parameter s is the *security parameter*, which is chosen after r is fixed.

1. Bob uses $|\psi\rangle$ to create the symmetric state $|S_1^2\rangle = |0\rangle|\psi\rangle + |\psi\rangle|0\rangle$ (as shown in Section 2.2), and sends the leftmost register of this state to Alice.
2. On the received register, Alice performs the logical Hadamard gate H (defined in Eq. (45)) and then measures with respect to an orthogonal basis $\{|0\rangle, |\psi\rangle, \dots\}$. If the state of the register immediately after the measurement is $|0\rangle$, then Alice sends “0” to Bob; otherwise, Alice sends “1”.
3. If Bob receives “1”, then he applies the Z gate to the register that he kept (that contained half of the symmetric state he made in Step 1). Finally, Bob SWAP-tests this register with

the register containing the authentic copy of $|0\rangle + |\psi\rangle$ (the SWAP-test is defined in Section 4.1).

After the kernel is repeated s times, Bob “accepts” if all the SWAP-tests passed; otherwise, Bob “rejects”. Before discussing the potential security of this scheme, we note that the honest protocol is correct because

$$|S_1^2\rangle = (H^{-1}|0\rangle)(|0\rangle + |\psi\rangle) - (H^{-1}|\psi\rangle)Z^{-1}(|0\rangle + |\psi\rangle); \quad (49)$$

that is, Bob’s SWAP-test always passes when the prover is honest (assuming perfect quantum channels).

4.2.1 Discussion of potential security

Within our hidden basis cryptographic framework, we refer to as *black-box attacks* those attacks where Eve does not use any information about the structure of A_δ to help her cheat. In the following discussion, we restrict our attention to the honest-verifier setting.

One obvious black-box attack that Eve could perform is as follows. Eve can collect $r' := (r - 1)$ copies of $|0\rangle + |\psi\rangle$, which are in the state

$$\left(\frac{|0\rangle + |\psi\rangle}{\sqrt{2}}\right)^{\otimes r'} = \frac{1}{\sqrt{2^{r'}}} \sum_{w=0}^{r'} \sqrt{\binom{r'}{w}} e^{iw\theta} |S_w^{r'}\rangle. \quad (50)$$

Now, assume Eve performs the inverse of the phase-invariant operation given in Section 2.2, which maps $|S_w^{r'}\rangle \mapsto |w^{r'}\rangle$ with no error. The state thus becomes

$$\frac{1}{\sqrt{2^{r'}}} \sum_{w=0}^{r'} \sqrt{\binom{r'}{w}} |w^{r'}\rangle. \quad (51)$$

Note that this state is similar to $|\Psi_0^{r'}\rangle$, but for the coefficients, which now have non-constant moduli (see Remark 4). Thus, Eve can use this state as a phase reference in order to mimic Alice’s Hadamard gate.

In the black-box (honest-verifier) setting, there indeed exists a value of s (dependent on r) such that the protocol is secure (assuming perfect quantum channels). For, in this case, the protocol reduces to the honest-verifier-secure protocol of Ref. [11]. The security proof follows from the work of Bartlett et al. [4] on bounded quantum reference frames and is a formalization of the following intuition. Note that Alice always causes Bob’s SWAP-test to pass. However, Eve’s information about the correct reference frame is limited to her r samples of it

(because Eve cannot extract any further information from Alice). Since only an infinite number of samples should suffice for Eve to be able to perform a measurement in the logical Hadamard basis perfectly (as Alice can), there is always some nonzero probability that Eve causes Bob’s SWAP-test to fail. With sufficiently large s , Bob will find such a failure (except with negligible probability). It turns out that $s \in \Omega(r \log(r))$ suffices [11].

A security proof would of course need to consider all attacks — not just black-box ones. Note that if squashing required only a small number of copies of $|\psi\rangle$ (see Remark 5), then Eve could prepare more copies of $|0\rangle + |\psi\rangle$ to use as a phase reference for her approximate implementation of H . This is one way that the security of our scheme depends on the assumed difficulty of squashing (e.g., the No-Squashing Conjecture); however, even if Eve could somehow transform her copies of $|\psi\rangle$ into one or more copies of $|0\rangle + |\psi\rangle$, the parameter s could be modestly increased to account for Eve’s extra samples of the reference frame, assuming there exists an s such that the scheme is secure for r' samples of $|0\rangle + |\psi\rangle$. The security of the scheme depends more crucially on the weaker conjecture that it is impossible to perform a measurement with respect to the logical Hadamard basis $\{|0\rangle \pm |\psi\rangle\}$ (given the limited number of copies of $|\psi\rangle$) much more efficiently than with our black-box reference-frame approach (this conjecture is weaker because if Eve could carry out the measurement, then she could squash).

5 Closing Remarks

By exploiting phase invariance and mimicking properties of coherent states of light, we have shown how to perform various computational tasks, defined with respect to a hidden computational basis $\{|0\rangle, e^{i\theta} |1\rangle\}^{\otimes n}$, efficiently in the required number of copies of $|0\rangle$ and $|1\rangle$. We have shown that such tasks, which were previously not known to be possible, have cryptological application.

We have identified several open problems, including the squashing problem and the harder problem of performing measurements with respect to the hidden Hadamard basis $\{|0\rangle \pm |1\rangle\}$. Another open problem is to investigate to what extent state preparation and universal computation are possible when the assumption that $|0\rangle$ and $|1\rangle$ come from known orthogonal subspaces is dropped, that is, when the only promise is that $\langle 0|1\rangle = 0$ with $|0\rangle, |1\rangle \in A$, where A contains no two states that are equal up to global phase.

Acknowledgements

We thank Scott Aaronson for discussions on the squashing problem and for naming it. We thank Daniel Gottesman for discussions on signature and identity schemes. L. M. Ioannou was

partially supported by the EPSRC and SCALA. M. Mosca was partially supported by NSERC, DTO-ARO, CFI, CIFAR, Ontario-MRI, CRC, OCE, QuantumWorks and MITACS.

References

- [1] Phillip Kaye and Michele Mosca. Quantum networks for generating arbitrary quantum states. In *International Conference on Quantum Information*, OSA Technical Digest Series, page PB28, Washington, D.C., June 2001. Optical Society of America.
- [2] Daniel Gottesman and Isaac L. Chuang. Quantum digital signatures, 2001. arXiv:quant-ph/0105032.
- [3] M. Nielsen and I. Chuang. *Quantum Computation and Quantum Information*. Cambridge University Press, Cambridge, 2000.
- [4] Stephen D. Bartlett, Terry Rudolph, Robert W. Spekkens, and Peter S. Turner. Degradation of a quantum reference frame. *New J. Phys.*, 8:58, 2006.
- [5] Debbie Leung, Ben Toner, and John Watrous. Coherent state exchange in multi-prover quantum interactive proof systems, 2008. arXiv:0804.4118.
- [6] Wim van Dam and Patrick Hayden. Universal entanglement transformations without communication. *Phys. Rev. A*, 67(6):060302(R), 2003.
- [7] Wim van Dam and Patrick Hayden. Embezzling entangled quantum states, 2002. arXiv:quant-ph/0201041.
- [8] Harry Buhrman, Richard Cleve, John Watrous, and Ronald de Wolf. Quantum fingerprinting. *Phys. Rev. Lett.*, 87:167902, 2001.
- [9] A. S. Holevo. Statistical problems in quantum physics. In Gisiro Maruyama and Jurii V. Prokhorov, editors, *Proceedings of the Second Japan-USSR Symposium on Probability Theory*, volume 330 of *Lecture Notes in Mathematics*, pages 104–119, Berlin, 1973. Springer-Verlag.
- [10] Georgios M. Nikolopoulos and Lawrence M. Ioannou. Deterministic quantum-public-key encryption: Forward search attack and randomization. *Phys. Rev. A*, to appear.
- [11] Lawrence M. Ioannou and Michele Mosca. Public-key cryptography based on bounded quantum reference frames. arXiv:0903.5156.

- [12] O. Goldreich. *Foundations of cryptography (Volume I): Basic tools*. Cambridge University Press, Cambridge, 2001.
- [13] A.Y. Shiekh. The role of quantum interference in quantum computing. *International Journal of Theoretical Physics*, 45(9):1646–1648, 2006.
- [14] V. Bužek, M. Hillery, and F. Werner. Universal-NOT gate. *J. Mod. Opt.*, 47, 2000.

Appendix: Squashing and the No-Squashing Conjecture

The squashing problem can be meaningfully (and nontrivially) defined for a broad class of sets of states — not just sets of type A_δ . Let A be a set of pure state vectors in \mathbf{C}^M such that no two distinct elements in A are equal up to global phase. (Formally, let $\{A(M)\}_{M=1,2,\dots}$ be a family of sets $A(M) \subset \mathbf{C}^M$ of complex unit vectors expressed relative to the standard basis $\{|0\rangle, |1\rangle, |M-1\rangle\}$. For clarity of presentation, we usually omit the “family” notation $\{\cdot\}_{M=1,2,\dots}$.) Let $\epsilon > 0$ be the error tolerance parameter. The pair (A, ϵ) specifies an instance of the general squashing problem, which is to compute, for every $|\psi\rangle \in A$, a state ρ such that

$$D(\sigma_{0,\psi}, \rho) \leq \epsilon, \tag{52}$$

given physical copies of $|\psi\rangle$, where D is the trace distance [3],

$$\sigma_{0,\psi} := (|0\rangle + |\psi\rangle)(\langle 0| + \langle \psi|), \tag{53}$$

and $|0\rangle$ is some known reference state (which, in general, need not be orthogonal to all $|\psi\rangle \in A$). Note that the classical description of A also specifies a global phase for each possible state vector $|\psi\rangle$, so the ideal target state $|0\rangle + |\psi\rangle$ is well defined. The set A should be *nontrivial*, meaning that it should contain elements that are, pairwise, not orthogonal (as would be the case when $A = A_\delta$); this is analogous to the problem of quantum cloning, where it is trivial to clone states that are promised to come from a prescribed orthogonal set.

Define $t(A, \epsilon)$ to be the smallest t for which there exists a quantum operation Q such that, for all $|\psi\rangle \in A$,

$$D(Q((|\psi\rangle\langle\psi|)^{\otimes t}), \sigma_{0,\psi}) \leq \epsilon. \tag{54}$$

A quantum operation Q that, for some t , satisfies Eq. (54) for all $|\psi\rangle \in A$ is called an (A, ϵ) -squasher, because it “squashes” part of the generalized Bloch sphere towards its $|0\rangle$ -pole. We view the number $t(A, \epsilon)$ as measuring the complexity of the squashing problem instance (A, ϵ) . We assume all $|\psi\rangle$ in A are reasonably encoded into qubits and thus take the input size of the problem to be $\log(M)$.

Our cryptographic motivation leads us to look for sets A such that $t(A, \epsilon)$ is necessarily large (for sufficiently small ϵ). For some instances of the general squashing problem, exponential lower bounds on $t(A, \epsilon)$ might be relatively easily obtainable, because it might be the case that, for subexponential values of t , the states $\sigma_{0,\psi}$ and $\sigma_{0,\phi}$ are further in trace distance (or, equivalently, have lower fidelity) than $|\psi\rangle^{\otimes t}$ and $|\phi\rangle^{\otimes t}$. The following example of this shows that the general squashing problem subsumes the black-box search problem (this fact has already been pointed out in Ref. [13], though the author of that paper assumes that squashing is an easy task).

Example 2. Denote by F the quantum Fourier transform on \mathbf{C}^M , so that

$$F|0\rangle = (1/\sqrt{M}) \sum_{i=0}^{M-1} |i\rangle. \quad (55)$$

For every $j = 0, 1, \dots, M-1$, define the state $|j^*\rangle$ via

$$\langle i|j^*\rangle = \begin{cases} +1/\sqrt{M} & \text{if } i = j, \\ -1/\sqrt{M} & \text{if } i \neq j. \end{cases} \quad (56)$$

Let $A_2 := \{F^\dagger|j^*\rangle : j = 0, 1, \dots, M-1\}$ (note that A_2 does *not* have the property that $\langle 0|\psi\rangle = 0$ for all $|\psi\rangle \in A_2$). Noting that $|j^*\rangle + F|0\rangle \propto |j\rangle$, we can solve the black-box search problem with a good (A_2, ϵ) -squasher, where ϵ is a constant (i.e., if the solution to the search problem is j , then the black box can be used t times to make t copies of $|j^*\rangle$). Thus, the well-known \sqrt{M} search lower bound applies to $t(A_2, \epsilon)$. But this is overkill: the lower bound we get from the fact that quantum operations cannot increase trace distance is larger when $\epsilon < 1/2$, as we now show. If Q is an (A_2, ϵ) -squasher, then we have (for $i \neq j$)

$$1 - 2\epsilon \leq D(Q((F^\dagger|i^*\rangle\langle i^*|F)^\otimes t), Q((F^\dagger|j^*\rangle\langle j^*|F)^\otimes t)) \quad (57)$$

$$\leq D((|i^*\rangle\langle i^*|)^\otimes t, (|j^*\rangle\langle j^*|)^\otimes t) \quad (58)$$

$$\leq \sqrt{1 - |\langle i^*|j^*\rangle|^{2t}} \quad (59)$$

$$= \sqrt{1 - (1 - 4/M)^{2t}}, \quad (60)$$

so that $t \geq \log(4\epsilon(1 - \epsilon))/2 \log(1 - 4/M)$ and thus, for example, $t(A_2, \frac{1}{3}, 1) \in \Omega(M)$. The first line follows from several applications of the triangle inequality and the fact that the trace distance between the squasher's ideal outputs is 1. In subsequent lines, we have used the well-known relationship between trace distance and fidelity (see Ref. [3]) and the power series expansion $\log(1 - x) = -x - x^2/2 - x^3/3 - \dots$ for $x \in [-1, 1]$ and the fact that, for $x \leq 1/2$,

$$x + x^2/2 + x^3/3 + \dots \leq x(1 + x + x^2 + \dots) = x(1 - x)^{-1} \leq 2x. \quad (61)$$

Our cryptographic framework uses sets of type A_δ , that have, among others, the two properties defined in Eq. (42) and Eq. (43). The latter property, that $\langle 0|\psi\rangle = 0$ for all $|\psi\rangle$ in A_δ , is particular to our framework. The former property of pairwise δ -almost-orthogonality is a reasonable condition to impose on quantum-public-key cryptography in general, in order to avoid a situation where two different private keys correspond to practically indistinguishable physical scenarios. For example, suppose Alice- x has private key x and Alice- y has private key y , and $x \neq y$; we would not want Alice- y to be able to convince Bob that she is Alice- x with significant probability. This property also rules out trivial lower-bound arguments based on distinguishability, like in Example 2, because an $(A_\delta, 0)$ -squasher *does not increase pairwise distinguishability*, by which we mean that, for all distinct $|\psi\rangle$ and $|\phi\rangle$ in A_δ ,

$$D(\sigma_{0,\psi}, \sigma_{0,\phi}) \leq D((|\psi\rangle\langle\psi|)^{\otimes t}, (|\phi\rangle\langle\phi|)^{\otimes t}) \quad (62)$$

for some $t \in O(\text{polylog}(M))$; in the particular case of A_δ , the inequality (62) actually holds for a constant t (dependent on δ). The set A_2 in Example 2 has neither of the two properties discussed in this paragraph, and we cannot see how to harness the provable difficulty of squashing A_2 for potential cryptographic application.

We now state the No-Squashing Conjecture more precisely. Call A_δ *efficient* if and only if there is a succinct description of A_δ (so that its classical description may be easily published) and each state in A_δ is efficiently computable given its classical description (i.e., although we do not bound Eve’s computational power, we prefer that Alice and Bob are bounded by polynomial time). Since the trace distance between $\sigma_{0,\psi}$ and the trivially-preparable mixture $|0\rangle\langle 0| + |\psi\rangle\langle\psi|$ is $1/2$, we take $\epsilon < 1/2$ in the conjecture.

Conjecture 7 (No-Squashing). *There exists an efficient A_δ such that $t(A_\delta, \epsilon) \in \omega((\log(M))^k)$ for all constants $k > 0$ and any nonnegative constant $\epsilon < 1/2$.*

Our choice of the superpolynomial bound in the conjecture corresponds to the usual meaning of “large” or “inefficient” in complexity theory. We do not claim that proving such a bound has immediate cryptographic application: recall that no result about the difficulty of squashing is sufficient for establishing the honest-verifier security of the protocol of Section 4.2.

We also leave as an open problem to find any set A such that the $(A, 0)$ -squasher does not increase pairwise distinguishability and is not completely positive (or prove no such A exists). Note that the one-qubit universal-NOT gate [14], which maps

$$\alpha|0\rangle + \beta|1\rangle \mapsto \beta^*|0\rangle - \alpha^*|1\rangle \quad (63)$$

for any qubit state $\alpha|0\rangle + \beta|1\rangle$, does not increase pairwise distinguishability and is known to be not completely positive.