

# Quantum Kolmogorov Complexity and Quantum Key Distribution

Takayuki Miyadera\* and Hideki Imai†

*Research Center for Information Security (RCIS),  
National Institute of Advanced Industrial Science and Technology (AIST),  
Daibiru building 1102, Sotokanda, Chiyoda-ku, Tokyo, 101-0021, Japan.*

(Dated: May 29, 2019)

We discuss BB84 quantum key distribution protocol in light of quantum algorithmic information. While Shannon's information theory needs a probability to define a notion of information, algorithmic information theory does not need it and can assign a notion of information to an individual object. The theory regards a program length necessary to describe an object, Kolmogorov complexity, as the most fundamental quantity. Recently, its quantum versions were proposed by a several researchers. We employ a definition of quantum Kolmogorov complexity given by Vitányi. A goal of the quantum key distribution is to distribute a random binary sequence only between legitimate users. In the context of quantum algorithmic complexity, a security criterion is formulated with the quantum Kolmogorov complexity. We show that a simple BB84 protocol indeed distribute a binary sequence between Alice and Bob that looks almost random for Eve in a probability exponentially close to 1.

PACS numbers: 03.67.Dd, 03.67.Ac

## I. INTRODUCTION

Cryptography is one of the most important arts in the modern society. It enables us to communicate securely with our friends who live far away. In 1984, Bennett and Brassard [1] proposed a simple but also an astonishing protocol which is called BB84 protocol. The protocol uses quantum theory in its essential part to achieve unconditionally secure key distribution [2, 3, 4, 5]. The security notion of BB84 is based on Shannon's information theory [6]. Roughly speaking, the security criterion demands that a random variable expressing a final key and another random variable expressing Eve's guess are almost independent. That is, Shannon entropy of the final key from Eve's viewpoint should attain a value sufficiently close to its maximum value. In this paper, we give an alternative point of view on this problem. We reconsider the protocol in algorithmic information theory. In the middle of 1960's, Kolmogorov [7] and independently Chaitin [8] found an innovative idea that makes a bridge between information theory and computation theory. While Shannon's conventional information theory treats probability distributions and needs them to define a notion of information, their theory, algorithmic information theory, takes randomness with respect to algorithm as a heart of information. Their formalism thus does not need probability to define information, and can assign a notion of information to each individual object such as a binary sequence. The theory has been applied to problems in various fields including physics [9]. As entropy does in Shannon's information theory, in algorithmic information theory a quantity called Kolmogorov complexity plays the most fundamental roles. Kolmogorov complexity is defined as a length of the shortest description of an object. Kolmogorov complexity has some good properties and behaves rather rationally as well as entropy in Shannon's information theory. Thus, a security criterion that we are to consider in this paper should not be based on Shannon's entropy, but on Kolmogorov complexity instead. Moreover, since Eve has a quantum state, the Kolmogorov complexity has to be extended to be able to treat quantum states as its inputs. That is, a secure final key should have sufficiently large quantum Kolmogorov complexity for Eve.

Recently, some versions of quantum Kolmogorov complexity have been proposed. We employ one of them which was defined by Vitányi [10]. It has a natural interpretation in terms of classical programs for quantum Turing machines. We, in section II, give a brief review of Vitányi's definition. Its two properties that play important roles in our paper are explained. In subsection III A we discuss the security that can be attained in a classical communication using a shared random binary sequence. We investigate one-time pad and show that it provides a secure communication also in the context of algorithmic information. In subsection III C, the main part of the present paper, the security proof of BB84 is discussed. We introduce a simple BB84 quantum key distribution protocol and show that it enables Alice and Bob to share a binary sequence that looks almost random for Eve in probability exponentially close to 1. In section IV, we give some discussions on our results and future problems.

---

\*Electronic address: miyadera-takayuki@aist.go.jp

†Also at Graduate School of Science and Engineering, Chuo University. 1-13-27 Kasuga, Bunkyo-ku, Tokyo 112-8551, Japan .

## II. QUANTUM KOLMOGOROV COMPLEXITY BASED ON CLASSICAL DESCRIPTION

Recently some quantum versions of Kolmogorov complexity were proposed by a several researchers. Svozil [11], in his pioneering work, defined a quantum Kolmogorov complexity as a minimum classical description length of a quantum state through a quantum Turing machine [12, 13]. As easily seen by comparing cardinality of a set of all the programs with one of a set of all the quantum states, the value often becomes infinity. Vitányi's definition [10], while similar to Svozil's, does not have this disadvantage. He added a term that compensates a difference between a target state and an output state. Berthiaume, van Dam and Laplante [14] defined their quantum Kolmogorov complexity as a length of the shortest quantum program that outputs a target state. The definition was settled down and its properties were extensively investigated by Müller [15, 16]. Gacs [17] employed a different starting point related with an algorithmic probability to define his quantum Kolmogorov complexity.

In this paper we employ a definition given by Vitányi [10]. He gave a description of one-way quantum Turing machine and utilized it to define a prefix quantum Kolmogorov complexity. A one-way quantum Turing machine consists of four tapes and an internal control. (See [10] for more details.) Each tape is a one-way infinite qubit chain and has a corresponding head on it. One of the tapes works as an input tape and is read-only from left-to-right. A program is given on this tape as an initial condition. The second tape works as a work tape. The work tape is initially set to be 0 for all the cells. A head on it can read and write a cell and moves to both directions. The third tape is called an auxiliary tape. One can put an additional input on this tape. The additional input is written at the leftmost qubits and can be a quantum state or a classical state. This input is needed when one treats conditional Kolmogorov complexity. The fourth tape works as an output tape. It is assumed that after the halting the state over this tape will not be changed. The internal control is a quantum system described by a finite dimensional Hilbert space which has two special orthogonal vectors  $|q_0\rangle$  (initial state) and  $|q_f\rangle$  (halting state). After each step one makes a measurement of a coarse grained observable on the internal control  $\{|q_f\rangle\langle q_f|, \mathbf{1} - |q_f\rangle\langle q_f|\}$  to know if the computation halts. Although there are subtle problems [18, 19, 20, 21] in the halting process of quantum Turing machine, we do not get into this problem and employ a simple definition of the halting. A computation halts at time  $t$  if and only if a probability to observe  $q_f$  at time  $t$  is one, and at any time  $t' < t$  a probability to observe  $q_f$  is zero. By using this one-way quantum Turing machine, Vitányi defined a quantum Kolmogorov complexity as follows. He treated a length of the shortest classical description of a quantum state. That is, the programs of quantum Turing machine are restricted to classical ones. While the programs must be classical, auxiliary inputs can be quantum states. We write  $U(p, y) = |x\rangle$  iff a quantum Turing machine  $U$  with a classical program  $p$  and an auxiliary (classical or quantum) input  $y$  halts and outputs  $|x\rangle$ . The following is the precise description of Vitányi's definition.

**Definition 1** [10] *The (self-delimiting) quantum Kolmogorov complexity of a pure state  $|x\rangle$  with respect to a one-way quantum Turing machine  $U$  with  $y$  (possibly a quantum state) as conditional input given for free is*

$$K_U(|x\rangle, |y\rangle) := \min_{p, |z\rangle} \{l(p) + \lceil -\log |\langle z|x\rangle|^2 \rceil : U(p, y) = |z\rangle\},$$

where  $l(p)$  is the length of a classical program  $p$ , and  $\lceil a \rceil$  is the smallest integer larger than  $a$ .

One-wayness of the quantum Turing machine ensures that the halting programs compose a prefix free set. Due to it, a length  $l(p)$  is defined consistently. The term  $\lceil -\log |\langle z|x\rangle|^2 \rceil$  represents how insufficiently an output  $|z\rangle$  approximates the desired output  $|x\rangle$ . This additional term has a natural interpretation using the Shannon-Fano code. Vitányi has shown the following invariance theorem which is very important.

**Theorem 1** [10] *There is a universal quantum Turing machine  $U$ , such that for all machines  $Q$ , there is a constant  $c_Q$ , such that for all quantum states  $|x\rangle$  and all auxiliary inputs  $y$  we have:*

$$K_U(|x\rangle | y\rangle) \leq K_Q(|x\rangle | y\rangle) + c_Q.$$

Thus the value of quantum Kolmogorov complexity does not depend on a choice of a quantum Turing machine if one neglects the unimportant constant term  $c_Q$ . Thanks to this theorem, one often writes  $K$  instead of  $K_U$ . Moreover, the following theorem is crucial for our discussion.

**Theorem 2** [10] *On classical objects (that is, finite binary strings that are all directly computable) the quantum Kolmogorov complexity coincides up to a fixed additional constant with the self-delimiting Kolmogorov complexity. That is, there exists a constant  $c$  such that for any classical binary sequence  $|x\rangle$ ,*

$$\min_q \{l(q) : U(q, y) = |x\rangle\} \geq K(|x\rangle | y\rangle) \geq \min_q \{l(q) : U(q, y) = |x\rangle\} - c$$

holds.

According to this theorem, for classical objects it essentially suffices to treat only programs that exactly output the object.

### III. SECURITY PROOF OF QUANTUM KEY DISTRIBUTION IN LIGHT OF QUANTUM ALGORITHMIC INFORMATION

#### A. Security of One-time Pad

The goal of the quantum key distribution is to distribute a secret key only between legitimate users. In context of the algorithmic information, a secret key is nothing but a binary sequence that looks random for Eve. We first show that a random binary sequence shared only by Alice and Bob does work for secure communication thereafter. Suppose that Alice and Bob share a common binary sequence  $k \in \{0, 1\}^M$ . Eve does not know the sequence except for its length. That is, the uncertainty of  $k$  for Eve is  $K(k|M)$ . Suppose that Alice sends a message  $x \in \{0, 1\}^M$  to Bob by one-time pad. That is, Alice sends a binary sequence  $x \oplus k \in \{0, 1\}^M$  which is known also by Eve. Bob, who knows  $k$ , can decode it easily to obtain  $x$ . Moreover, we can show the following.

**Theorem 3** *There exists a constant  $c$  (that depends only on a choice of a quantum Turing machine) such that the following statement holds. Let  $M$  be an arbitrary positive integer and let  $k \in \{0, 1\}^M$  be a binary sequence. For any  $\delta > 0$ , we define a set  $B_\delta \subset \{0, 1\}^M$  as*

$$B_\delta := \{x | K(x|x \oplus k, M) \leq K(k|M) - \delta M - c\}.$$

The size of this  $B_\delta$  is bounded as

$$|B_\delta| \leq 2^{(1-\delta)M}.$$

**Proof:** According to the fundamental properties [9] of Kolmogorov complexity it is known that

$$|K(x, k|M) - (K(k|M) + K(x|k, K(k), M))| \leq c_1$$

holds for some constant  $c_1$ . (The proof also holds for the quantum Kolmogorov complexity thanks to theorem 2.) For a fixed  $\delta > 0$ , we define a set  $\mathcal{D}_\delta \subset \{0, 1\}^M$  as

$$\mathcal{D}_\delta := \{x | K(x|k, K(k), M) \leq (1 - \delta)M\}.$$

It can be easily shown that  $|\mathcal{D}_\delta| \leq 2^{(1-\delta)M}$  holds. Now let us consider its complement  $\mathcal{D}_\delta^c := \{0, 1\}^M \setminus \mathcal{D}_\delta$  which is expressed as  $\mathcal{D}_\delta^c = \{x \in \{0, 1\}^M | K(x|k, K(k), M) > (1 - \delta)M\}$ . For  $x \in \mathcal{D}_\delta^c$ ,  $K(x, k|M) > K(k|M) + (1 - \delta)M - c_1$  holds. By the way we have, in general,

$$K(x, k|M) = K(x \oplus k, k|M) + c_2 \leq K(x \oplus k|M) + K(x|x \oplus k, M) + c_3$$

for some  $c_2, c_3$ . Thus for  $x \in \mathcal{D}_\delta^c$ , we have

$$K(x \oplus k|M) + K(x|x \oplus k, M) + c_3 > K(k|M) + (1 - \delta)M - c_1.$$

Since  $K(x \oplus k|M) \leq M + c_4$  holds for some  $c_4$ , if we put  $c = c_1 + c_3 + c_4$  we obtain

$$K(x|x \oplus k, M) > K(k|M) - \delta M - c$$

for  $x \in \mathcal{D}_\delta^c$ . Thus  $\mathcal{D}_\delta^c \subset B_\delta^c$  and  $B_\delta \subset \mathcal{D}_\delta$  holds. It ends the proof. Q.E.D.

The following corollary is obvious.

**Corollary 1** *There exists a constant  $c$  such that the following statement holds. Let  $M$  be an arbitrary positive integer and let  $k \in \{0, 1\}^M$  be a binary sequence that looks random for Eve who knows its length only. That is,  $K(k|M) \geq M$  holds. For any  $\delta > 0$ , we define a set  $B_\delta \subset \{0, 1\}^M$  as*

$$B_\delta := \{x | K(x|x \oplus k, M) \leq (1 - \delta)M - c\}.$$

The size of this  $B_\delta$  is bounded as

$$|B_\delta| \leq 2^{(1-\delta)M}.$$

The size  $|B_\delta|$  is thus much smaller than  $|\{0, 1\}^M| = 2^M$ . This corollary represents that if Alice and Bob share a random binary sequence only between them, they can achieve a secret communication by one-time pad.

Let us note a remark. One may wonder whether one can show the size of a set  $\{x | K(x|x \oplus k, M) \leq M - c\}$  exponentially small compared with  $|\{0, 1\}^M| = 2^M$ . It is not possible and not even natural to expect that because many  $x$ 's have a small Kolmogorov complexity even if Eve does not know  $x \oplus k$ . For instance, Kolmogorov complexity of  $x = 00 \dots 00 \in \{0, 1\}^M$  is almost vanishing. Thus even  $|\{x | K(x|M) \leq M - c\}|$  can be comparable with  $2^M$ , while  $|\{x | K(x|M) \leq (1 - \delta)M - c\}| \leq 2^{(1-\delta)M}$  holds for  $c \geq 0$ .

## B. BB84 Protocol

As was discussed in the last subsection, if Alice and Bob have shared a binary sequence that is random for Eve, they can communicate securely by using the sequence. Our goal in the following is to show that a quantum key distribution indeed achieves this distribution of a random binary sequence. In this subsection, a concrete protocol to be analyzed is introduced. We consider a quantum key distribution protocol that uses a preshared secret key for error correction and uses a public linear code for privacy amplification. Although there are more sophisticated or realistic ones, we treat one of the simplest protocols since our aim is to present a new viewpoint from the algorithmic information. Let us introduce the protocol.

- (i) Alice encodes a probabilistically [22] chosen  $2N$  bit classical sequence to a quantum state of  $2N$  qubits with respect to a probabilistically [22] chosen basis  $b \in \{+, \times\}^{2N}$ .
- (ii) After confirming Bob's receipt of all the sent qubits, Alice announces the basis  $b$ . Bob makes a measurement with the basis  $b$  on his qubits to obtain an outcome.
- (iii) Alice probabilistically [22] chooses half number of  $2N$  bits  $T \subset \{1, 2, \dots, 2N\}$  ( $|T| = N$ ), which are called test bits. Remaining bits  $I := \{1, 2, \dots, 2N\} \setminus T$  are called information bits. Alice announces the classical sequence  $z_T \in \{0, 1\}^N$  which was encoded to the test bits.
- (iv) Alice and Bob check the error rate in test bits by public discussions. If the error rate is larger than a preagreed threshold  $p$ , they abort the protocol.
- (v) Alice and Bob perform an error correction by using a preshared secret key. They consume  $Nh(p) + \text{const.}$  secret bits for this procedure.
- (vi) Alice and Bob perform a privacy amplification. (See below for the detail.)

After error correction, Alice and Bob have a common sifted key  $x \in \{0, 1\}^N$  (information bits). On the other hand, Eve has a quantum state that may be correlated with  $x$ . Due to this correlation, Eve may have a part of information on  $x$ . Alice and Bob, therefore, cannot use  $x$  itself as the final key. Privacy amplification is a protocol that extracts a shorter final key which cannot be guessed by Eve at all. The privacy amplification in our protocol is performed by use of a linear code. All players including Eve know a set of linear independent vectors  $\{v_1, v_2, \dots, v_M\} \subset \{0, 1\}^N$  which span a linear code  $\mathcal{C}$ . The vectors could be announced before the whole protocol. Its Hamming distance  $d(\mathcal{C}) = \min\{|v| : v \neq 0, v \in \mathcal{C}\}$  is assumed to satisfy  $d(\mathcal{C}) > 2N(p + \epsilon)$ , where  $p$  is the allowed error rate in test bits and  $\epsilon > 0$  is a small security parameter. A final key is obtained from a sifted key by a function  $f : \{0, 1\}^N \rightarrow \{0, 1\}^M$  which is defined as

$$f(x) = x \cdot v := (x \cdot v_1, x \cdot v_2, \dots, x \cdot v_M).$$

Eve's purpose is to obtain a knowledge on  $f(x)$ .

## C. Security Proof

Suppose that Alice has chosen a basis  $b \in \{0, 1\}^{2N}$ , test bits  $T$ , a value of test bits  $z_T \in \{0, 1\}^N$ , and Bob has obtained  $z'_T \in \{0, 1\}^N$  as a value of test bits. After (v) in the above protocol Eve also knows all of them. As is well-known, one can view the protocol also from the E91 like setting. In E91 like setting, After the error correction there is an entangled state over Alice's information bits, Bob's information bits and Eve's apparatus. We denote the state as  $\rho_{b,T,z_T,z'_T}$ . Alice makes measurement  $X_A = \{|x\rangle\langle x|\}$  on her information bits to obtain a sifted key  $x \in \{0, 1\}^N$ . This measurement changes the state on Bob's information bits and Eve's apparatus [24]. We denote the a-posteriori state on Bob's information bit and Eve's apparatus as  $\rho_{x,b,T,z_T,z'_T}$ . We further write its restriction on Eve's apparatus as  $\rho_{x,b,T,z_T,z'_T}^E$ . Eve's purpose is to extract information on the final key  $f(x)$  from this quantum state and her knowledge;  $b, T, z_T, z'_T$  and  $f$ . Therefore in the context of quantum Kolmogorov complexity, Eve's uncertainty on the final key is written as  $K(f(x)|\rho_{x,b,T,z_T,z'_T}^E, f, b, T, z_T, z'_T)$  [23]. We prove the following theorem.

**Theorem 4** *There exists a constant  $c$  (that depends only on a choice of a quantum Turing machine) such that the following statement holds. For any  $N$ , any  $p$ , any  $\epsilon > 0$ , any independent vectors  $\{v_1, v_2, \dots, v_M\}$  whose span  $\mathcal{C}$  satisfies  $d(\mathcal{C}) > 2N(p + \epsilon)$ , and any  $\delta > 0$ ,*

$$\Pr(K(f(x)|\rho_{x,b,T,z_T,z'_T}^E, f, b, T, z_T, z'_T) \leq M - \delta N - c \wedge |z_T \oplus z'_T| < Np) \leq 2^{-\delta N} + 3e^{-\frac{\epsilon^2}{4}N}$$

holds.

**Proof:**

We fix a universal quantum Turing machine  $U$  and discuss the values of quantum Kolmogorov complexity with respect to it. Since  $f(x)$  is classical, to discuss quantum Kolmogorov complexity of  $f(x)$  it essentially suffices to consider programs that exactly output  $f(x)$  thanks to theorem 2. For each output  $x \in \{0, 1\}^M$ , there is the shortest program  $t_{x,b,T,z_T,z'_T}$  (take an arbitrary one if it is not unique) that produces  $f(x)$  exactly as its output with auxiliary inputs  $\rho_{x,b,T,z_T,z'_T}^E$  and  $f, b, T, z_T, z'_T$ . Although  $t_{x,b,T,z_T,z'_T}$ 's may have different halting times, thanks to lemma proved by Müller (Lemma 2.3.4. in [16]), there exists a completely positive map (CP map)  $\Gamma_U : \Sigma(\mathcal{H}_A \otimes \mathcal{H}_I) \rightarrow \Sigma(\mathcal{H}_O)$  satisfying

$$\Gamma_U(\rho_{x,b,T,z_T,z'_T}^E \otimes |t_{x,b,T,z_T,z'_T}\rangle\langle t_{x,b,T,z_T,z'_T}|) = |f(x)\rangle\langle f(x)|,$$

where  $\mathcal{H}_A$  is a Hilbert space for auxiliary input and  $\mathcal{H}_I$  is a Hilbert space for programs and  $\mathcal{H}_O = \otimes^M \mathbf{C}_2$  is a Hilbert space for outputs, and  $\Sigma(\mathcal{H})$  denotes a set of all the density operators on  $\mathcal{H}$ .

For a while we proceed with our analysis for fixed  $b, T, z_T, z'_T$ . For each  $t \in \{0, 1\}^*$  (a set of all the finite length binary sequences), let us define a set  $\mathcal{E}_t^{b,T,z_T,z'_T} \subset \{0, 1\}^N$  as  $\mathcal{E}_t^{b,T,z_T,z'_T} = \{x \mid t_{x,b,T,z_T,z'_T} = t\}$ . That is, for each  $x \in \mathcal{E}_t^{b,T,z_T,z'_T}$  the program  $t$  with auxiliary inputs  $\rho_{x,b,T,z_T,z'_T}^E$  and  $f, b, T, z_T, z'_T$  produces exactly  $f(x)$ . The set is further decomposed with respect to their outputs as  $\mathcal{E}_t^{b,T,z_T,z'_T} = \cup_y \mathcal{E}_t^{b,T,z_T,z'_T}(y)$ , where  $\mathcal{E}_t^{b,T,z_T,z'_T}(y) := \{x \mid t_{x,b,T,z_T,z'_T} = t, f(x) = y\}$ . That is, for each  $x \in \mathcal{E}_t^{b,T,z_T,z'_T}(y)$  the program  $t$  with an auxiliary inputs  $\rho_{x,b,T,z_T,z'_T}^E, f, b, T, z_T, z'_T$  produces  $y$ . Since the CP map  $\Gamma_U$  does not increase distinguishability among states, for any  $x \in \mathcal{E}_t^{b,T,z_T,z'_T}(y)$  and  $x' \in \mathcal{E}_t^{b,T,z_T,z'_T}(y')$  with  $y \neq y'$ ,  $\rho_{x,b,T,z_T,z'_T}^E$  and  $\rho_{x',b,T,z_T,z'_T}^E$  must be completely distinguishable. We denote  $E_t^{b,T,z_T,z'_T} := \{E_t^{b,T,z_T,z'_T}(y)\}_y$  a projection valued measure (PVM) that perfectly distinguishes states which belong to different  $y$ . That is,

$$\text{tr}\left(E_t^{b,T,z_T,z'_T}(y)\rho_{x,b,T,z_T,z'_T}^E\right) = \delta_{f(x)y} \quad (1)$$

holds for each  $x$  and  $y$ .

Let us consider the problem in E91 like setting. Now Alice, Bob and Eve have a state  $\rho_{b,T,z_T,z'_T}$  over their systems. For an arbitrary fixed finite  $L \subset \{0, 1\}^*$ , let us consider an observable over Alice's information bits and Eve's apparatus;

$$Q_L^{b,T,z_T,z'_T} := \sum_{t \in L} \sum_y A_t^{b,T,z_T,z'_T}(y) \otimes E_t^{b,T,z_T,z'_T}(y),$$

where  $A_t^{b,T,z_T,z'_T}(y)$  is defined as

$$A_t^{b,T,z_T,z'_T}(y) := \sum_{x \in \mathcal{E}_t^{b,T,z_T,z'_T}(y)} |x\rangle\langle x|.$$

One can easily show that this  $Q_L^{b,T,z_T,z'_T}$  is a projection operator. We hereafter consider an expectation value of this projection operator with respect to the state  $\rho_{b,T,z_T,z'_T}$ . ( $Q_L^{b,T,z_T,z'_T}$  is naturally identified with an operator  $Q_L^{b,T,z_T,z'_T} \otimes \mathbf{1}_B$  on Alice, Bob and Eve's tripartite system.) One can write it as follows:

$$\begin{aligned} \text{tr}(\rho_{b,T,z_T,z'_T} Q_L^{b,T,z_T,z'_T}) &= \langle Q_L^{b,T,z_T,z'_T} \rangle_{b,T,z_T,z'_T} \\ &= \sum_{t \in L} \sum_y \langle A_t^{b,T,z_T,z'_T}(y) \otimes E_t^{b,T,z_T,z'_T}(y) \rangle_{b,T,z_T,z'_T} \\ &= \sum_{t \in L} \sum_y \sum_{x \in \mathcal{E}_t^{b,T,z_T,z'_T}(y)} \langle |x\rangle\langle x| \otimes E_t^{b,T,z_T,z'_T}(y) \rangle_{b,T,z_T,z'_T}, \end{aligned}$$

where we put  $\langle \cdot \rangle_{b,T,z_T,z'_T} = \text{tr}(\rho_{b,T,z_T,z'_T} \cdot)$ . If we consider Alice's measurement of  $X_A = \{|x\rangle\langle x|\}$  on her information bits and denote  $p(x|b, T, z_T, z'_T)$  a probability to obtain  $x$ , it is represented as

$$\begin{aligned} & \sum_{t \in L} \sum_y \sum_{x \in \mathcal{E}_t^{b,T,z_T,z'_T}(y)} \langle |x\rangle\langle x| \otimes E_t^{b,T,z_T,z'_T}(y) \rangle_{b,T,z_T,z'_T} \\ &= \sum_{t \in L} \sum_y \sum_{x \in \mathcal{E}_t^{b,T,z_T,z'_T}(y)} p(x|b, T, z_T, z'_T) \text{tr}(\rho_{x,b,T,z_T,z'_T}^E E_t^{b,T,z_T,z'_T}(y)) \\ &= \sum_{t \in L} \sum_y \sum_{x \in \mathcal{E}_t^{b,T,z_T,z'_T}(y)} p(x|b, T, z_T, z'_T) = \Pr \left( x \in \bigcup_{t \in L} \mathcal{E}_t^{b,T,z_T,z'_T} \mid b, T, z_T, z'_T \right), \end{aligned} \quad (2)$$

where we have used the condition (1).

In addition, this quantity can be represented in a different form (see appendix B for its proof).

**Lemma 1** *Suppose that Alice virtually makes a measurement on her information bits with a PVM  $Z_A := \{|\bar{z}\rangle\langle \bar{z}|\}$  which is conjugate to  $X_A = \{|x\rangle\langle x|\}$  that is actually measured to obtain a sifted key, and Bob virtually makes a measurement on his information bits with  $Z_B := \{|\bar{z}\rangle\langle \bar{z}|\}$  which is conjugate to  $X_B$  that is actually measured. We denote their outcomes  $z_I$  and  $z'_I$ . It holds that*

$$\text{tr}(\rho_{b,T,z_T,z'_T} Q_L^{b,T,z_T,z'_T}) \leq |L|2^{-M} + 3\sqrt{\Pr(|z_I \oplus z'_I| > N(p + \epsilon) \mid b, T, z_T, z'_T)}, \quad (3)$$

where the second term in the right hand side is the square root of a probability to obtain distant  $z_I$  and  $z'_I$  with respect to a state  $\rho_{b,T,z_T,z'_T}$ .

Combining these different expressions eq.(2) and eq.(3), we obtain

$$\Pr \left( x \in \bigcup_{t \in L} \mathcal{E}_t^{b,T,z_T,z'_T} \mid b, T, z_T, z'_T \right) \leq |L|2^{-M} + 3\sqrt{\Pr(|z_I \oplus z'_I| > N(p + \epsilon) \mid b, T, z_T, z'_T)}.$$

Now if we take  $L$  as  $L := \{t \mid l(t) \leq M - \delta N\}$ , since  $|L| \leq 2^{M - \delta N}$  holds the above inequality can be rewritten as

$$\Pr \left( x \in \bigcup_{t: l(t) \leq M - \delta N} \mathcal{E}_t^{b,T,z_T,z'_T} \mid b, T, z_T, z'_T \right) \leq 2^{-\delta N} + 3\sqrt{\Pr(|z_I \oplus z'_I| > N(p + \epsilon) \mid b, T, z_T, z'_T)}.$$

Thanks to theorem 2, there exists a constant  $c$  such that if  $x$  satisfies  $K(f(x) | \rho_{x,b,T,z_T,z'_T}^E, b, T, z_T, z'_T, f) \leq M - \delta N - c$ , then  $l(t_{x,b,T,z_T,z'_T}) \leq M - \delta N$  follows. That is, we obtain

$$\Pr \left( K(f(x) | \rho_{x,b,T,z_T,z'_T}^E, b, T, z_T, z'_T, f) \leq M - \delta N - c \mid b, T, z_T, z'_T \right) \leq 2^{-\delta N} + 3\sqrt{\Pr(|z_I \oplus z'_I| > N(p + \epsilon) \mid b, T, z_T, z'_T)}.$$

We multiply both sides of this inequality with  $p(b, T, z_T, z'_T)$  which is defined as a probability to obtain  $b, T, z_T, z'_T$  and take a summation with respect to  $b, T, z_T, z'_T$  for all  $b, T$  and  $z_T, z'_T$  with  $|z_T \oplus z'_T| \leq Np$  and use Jensen's inequality. It finally derives

$$\begin{aligned} & \Pr \left( K(f(x) | \rho_{x,b,T,z_T,z'_T}^E, b, T, z_T, z'_T, f) \leq M - \delta N - c \wedge |z_T \oplus z'_T| < Np \right) \\ & \leq \Pr(|z_T \oplus z'_T| < Np) 2^{-\delta N} + 3\sqrt{\Pr(|z_T \oplus z'_T| \leq Np)} \sqrt{\Pr(|z_I \oplus z'_I| > N(p + \epsilon), |z_T \oplus z'_T| \leq Np)} \end{aligned}$$

The second term of the right hand side is bounded by Hoeffding's lemma as  $\Pr(|z_I \oplus z'_I| > N(p + \epsilon), |z_T \oplus z'_T| \leq Np) \leq e^{-\frac{\epsilon^2}{2}N}$  (see e.g. [5]). We thus obtain

$$\Pr \left( K(f(x) | \rho_{x,b,T,z_T,z'_T}^E, b, T, z_T, z'_T, f) \leq M - \delta N - c \wedge |z_T \oplus z'_T| < Np \right) \leq 2^{-\delta N} + 3e^{-\frac{\epsilon^2}{4}N}.$$

It ends the proof.

Q.E.D.

## IV. DISCUSSIONS

In this paper, we considered the security of quantum key distribution protocol in light of quantum Algorithmic information. We employed the quantum Kolmogorov complexity defined by Vitányi as fundamental quantity and discussed a possible security criterion and showed that the simple BB84 protocol satisfies it. According to the main theorem, a probability for Eve to obtain an almost random final key is exponentially close to 1. The length of the final keys  $M$  is determined by a condition for Hamming distance. One can take it as  $M \simeq N(1 - h(2p + \epsilon))$ . Since the legitimate users have consumed  $Nh(p + \epsilon)$  bits for the error correction, the length of the produced key amounts to  $N(1 - h(2(p + \epsilon)) - h(p + \epsilon))$ . It coincides with the rate obtained in [5] where the security criterion was based on Shannon's information theory.

Although we hope that the present work can be a first pivot toward the study of quantum cryptography from the viewpoint of quantum algorithmic information, there still remain a lot of things to be investigated. The security criterion employed in this paper utilizes the quantum Kolmogorov complexity, but it still needs the probability. Therefore, the original motivation of the algorithmic information theory, in some sense, has not been perfectly accomplished. In addition, as we noted in section II, there are some other definitions of quantum Kolmogorov complexity. It is interesting to investigate whether one can apply them to the security problem and to discuss which one gives the most reasonable security criterion. Application of our argument to other protocols will be another interesting problem.

### Acknowledgments

The authors thank K. Imafuku and K. Nuida for their helpful comments.

### APPENDIX A: TECHNICAL LEMMAS

**Lemma 2** *For any state  $\rho$  and any projection operators  $Q$  and  $P$ , it holds that*

$$|\text{tr}(\rho Q) - \text{tr}(PQP)| \leq 3\text{tr}(\rho(\mathbf{1} - P))^{1/2}.$$

**Proof:** Since  $\mathbf{1} = P + (\mathbf{1} - P)$  holds,  $Q$  can be decomposed as

$$Q = \mathbf{1}Q\mathbf{1} = PQP + PQ(\mathbf{1} - P) + (\mathbf{1} - P)QP + (\mathbf{1} - P)Q(\mathbf{1} - P).$$

Thus we obtain

$$|\text{tr}(\rho Q) - \text{tr}(\rho PQP)| \leq |\text{tr}(\rho PQ(\mathbf{1} - P))| + |\text{tr}(\rho(\mathbf{1} - P)QP)| + |\text{tr}(\rho(\mathbf{1} - P)Q(\mathbf{1} - P))|.$$

Cauchy-Schwarz inequality bounds the first term in the right hand side as

$$|\text{tr}(\rho PQ(\mathbf{1} - P))| = \text{tr}(\rho PQP)^{1/2} \text{tr}(\rho(\mathbf{1} - P))^{1/2} \leq \text{tr}(\rho(\mathbf{1} - P))^{1/2}.$$

Other terms can be bounded by a similar manner. It ends the proof. Q.E.D.

**Lemma 3** *For given linearly independent vectors  $\{v_1, v_2, \dots, v_M\} \subset \{0, 1\}^N$ , we define  $f : \{0, 1\}^N \rightarrow \{0, 1\}^M$  as  $f(x) = (x \cdot v_1, x \cdot v_2, \dots, x \cdot v_M)$ . Let  $\mathcal{C}$  be a code generated by  $\{v_1, v_2, \dots, v_M\}$  and  $d(\mathcal{C})$  be its Hamming distance. For  $s, t \in \{0, 1\}^N$  satisfying  $|s|, |t| < \frac{d(\mathcal{C})}{2}$  and for any  $y \in \{0, 1\}^M$ ,*

$$\sum_{x: f(x)=y} (-1)^{x \cdot (s \oplus t)} = \delta_{st} 2^{N-M}$$

holds, where  $\delta_{st}$  is Kronecker's delta.

**Proof:** If we fix an element  $w_y \in \{0, 1\}^N$  satisfying  $f(w_y) = y$ ,  $\{x | f(x) = y\}$  is represented as  $w_y \oplus \mathcal{C}^\perp$ . Thus we obtain

$$\sum_{x: f(x)=y} (-1)^{x \cdot (s \oplus t)} = (-1)^{w_y \cdot (s \oplus t)} \sum_{x \in \mathcal{C}^\perp} (-1)^{x \cdot (s \oplus t)}.$$

For  $s \oplus t \in \mathcal{C}$ , it gives  $2^{N-M} (-1)^{w_y \cdot (s \oplus t)}$ . Since  $|s \oplus t| \leq |s| + |t| < d(\mathcal{C})$  holds,  $s \oplus t \in \mathcal{C}$  means  $s = t$ . For  $s \oplus t \notin \mathcal{C}$ , thanks to Lemma D.1 in [5],

$$\sum_{x \in \mathcal{C}^\perp} (-1)^{x \cdot (s \oplus t)} = 0$$

holds. It ends the proof. Q.E.D.

**APPENDIX B: PROOF OF LEMMA 1**

**Proof of Lemma 1** Let  $\rho_{b,T,z_T,z'_T}$  be a state over Alice's information bits, Bob's information bits and Eve's apparatus. Suppose that Bob virtually makes a measurement of  $Z_B = \{|\bar{z}\rangle\langle\bar{z}|\}$  on his system (information bits). This observable is conjugate with  $X_B$  which is actually measured by Bob to obtain a sifted key. Suppose that Bob obtains an outcome  $z'_I$ . We denote  $p(z'_I|b,T,z_T,z'_T)$  a probability to obtain  $z'_I$ . The a-posteriori state on Alice's information bits and Eve's apparatus is denoted as  $\rho_{z'_I}^{b,T,z_T,z'_T}$ .

Define a projection operator  $P_{z'_I}^{b,T}$  on Alice's information bits as

$$P_{z'_I}^{b,T} := \sum_{s}^{|s| \leq N(p+\epsilon)} |z'_I \oplus s\rangle\langle z'_I \oplus s|.$$

Applying lemma 2 with  $P_{z'_I}^{b,T} = P$ ,  $Q_L^{b,T,z_T,z'_T} = Q$  and  $\overline{\rho_{z'_I}^{b,T,z_T,z'_T}} = \rho$ , we obtain

$$|\langle Q_L^{b,T,z_T,z'_T} \rangle_{b,T,z_T,z'_T,z'_I} - \langle P_{z'_I}^{b,T} Q_L^{b,T,z_T,z'_T} P_{z'_I}^{b,T} \rangle_{b,T,z_T,z'_T,z'_I}| \leq 3\langle \mathbf{1} - P_{z'_I}^{b,T} \rangle_{b,T,z_T,z'_T,z'_I}^{1/2}, \quad (\text{B1})$$

where we put  $\langle \cdot \rangle_{b,T,z_T,z'_T,z'_I} = \text{tr}(\overline{\rho_{z'_I}^{b,T,z_T,z'_T}}(\cdot))$ . In addition, if we introduce  $A^{b,T}(y) := \sum_x^{f(x)=y} |x\rangle\langle x|$ , it satisfies  $A^{b,T}(y) \geq A_t^{b,T,z_T,z'_T}(y)$ . Thus one can easily show that

$$Q_L^{b,T,z_T,z'_T} \leq \sum_{t \in L} \sum_y A^{b,T}(y) \otimes E_t^{b,T,z_T,z'_T}(y)$$

holds. It derives

$$P_{z'_I}^{b,T} Q_L^{b,T,z_T,z'_T} P_{z'_I}^{b,T} \leq \sum_{t \in L} \sum_y P_{z'_I}^{b,T} A^{b,T}(y) P_{z'_I}^{b,T} \otimes E_t^{b,T,z_T,z'_T}(y). \quad (\text{B2})$$

Combining eq.(B1) and eq.(B2), we obtain the following inequality:

$$\begin{aligned} \text{tr}(\overline{\rho_{z'_I}^{b,T,z_T,z'_T}} Q_L^{b,T,z_T,z'_T}) &= \langle Q_L^{b,T,z_T,z'_T} \rangle_{b,T,z_T,z'_T,z'_I} \\ &\leq \sum_{t \in L} \sum_y \langle P_{z'_I}^{b,T} A^{b,T}(y) P_{z'_I}^{b,T} \otimes E_t^{b,T,z_T,z'_T}(y) \rangle_{b,T,z_T,z'_T,z'_I} + 3\langle \mathbf{1} - P_{z'_I}^{b,T} \rangle_{b,T,z_T,z'_T,z'_I}^{1/2}. \end{aligned} \quad (\text{B3})$$

$\langle P_{z'_I}^{b,T} A^{b,T}(y) P_{z'_I}^{b,T} \otimes E_t^{b,T,z_T,z'_T}(y) \rangle_{b,T,z_T,z'_T,z'_I}$  in the first term on the right hand side of eq.(B3) is estimated as follows. Suppose that with respect to  $\overline{\rho_{z'_I}^{b,T,z_T,z'_T}}$  Eve made a measurement of the PVM  $E_t^{b,T,z_T,z'_T}$  and has obtained  $y$ . The probability to obtain  $y$  is denoted as  $p(y|b,T,z_T,z'_T,z'_I)$ . The a-posteriori state over Alice's information bits is denoted as  $\overline{\rho_{z'_I,y}^{b,T,z_T,z'_T}}$ . We write its diagonalization as  $\overline{\rho_{z'_I,y}^{b,T,z_T,z'_T}} = \sum_\nu \lambda_\nu |\phi_\nu\rangle\langle\phi_\nu|$ . The vector  $|\phi_\nu\rangle$  has a expansion  $|\phi_\nu\rangle = \sum_s c'_s |\overline{z'_I \oplus s}\rangle$ . Now  $\langle \phi_\nu | P_{z'_I}^{b,T} A^{b,T}(y) P_{z'_I}^{b,T} | \phi_\nu \rangle$  is calculated as

$$\begin{aligned} \langle \phi_\nu | P_{z'_I}^{b,T} A^{b,T}(y) P_{z'_I}^{b,T} | \phi_\nu \rangle &= \sum_s^{|s| \leq N(p+\epsilon)} \sum_t^{|t| \leq N(p+\epsilon)} \overline{c'_s c'_t} \langle \overline{z'_I \oplus s} | A^{b,T}(y) | \overline{z'_I \oplus t} \rangle \\ &= \sum_s^{|s| \leq N(p+\epsilon)} \sum_t^{|t| \leq N(p+\epsilon)} \overline{c'_s c'_t} 2^{-N} \sum_x^{f(x)=y} (-1)^{x \cdot (s \oplus t)} \leq 2^{-M}, \end{aligned}$$

where we have used lemma 3 and  $\sum_s |c'_s|^2 = 1$  to obtain the last inequality. We thus obtain for each  $y$  and  $z'_I$ ,

$$\frac{\langle P_{z'_I}^{b,T} A^{b,T}(y) P_{z'_I}^{b,T} \otimes E_t^{b,T,z_T,z'_T}(y) \rangle_{b,T,z_T,z'_T,z'_I}}{p(y|b,T,z_T,z'_T,z'_I)} = \langle P_{z'_I}^{b,T} A^{b,T}(y) P_{z'_I}^{b,T} \rangle_{b,T,z_T,z'_T,z'_I,y} \leq 2^{-M}.$$



Multiplying both sides of this inequality with  $p(y|b, T, z_T, z'_T, z'_I)$  and summing up it with respect to  $y$ , we obtain

$$\sum_y \overline{\text{tr}(\rho_{z'_I}^{b, T, z_T, z'_T} (P_{z'_I}^{b, T} A^{b, T}(y) P_{z'_I}^{b, T} \otimes E_t^{b, T, z_T, z'_T}(y)))} \leq 2^{-M}.$$

Summation of this inequality over  $t \in L$  further derives

$$\sum_{t \in L} \sum_y \langle P_{z'_I}^{b, T} A^{b, T}(y) P_{z'_I}^{b, T} \otimes E_t^{b, T, z_T, z'_T}(y) \rangle_{b, T, z_T, z'_T, z'_I} \leq |L| 2^{-M}.$$

We next estimate the second term  $3 \langle \mathbf{1} - P_{z'_I}^{b, T} \rangle_{b, T, z_T, z'_T, z'_I}^{1/2}$  in eq.(B3). This term can be represented in a simple form by considering Alice's measurement on her information bits with  $Z_A := \{|\bar{z}_I\rangle\langle\bar{z}_I|\}$  which is conjugate to  $X_A = \{|x\rangle\langle x|\}$  that is actually measured to obtain a sifted key in the E91 like picture. One can show

$$\langle \mathbf{1} - P_{z'_I}^{b, T} \rangle_{b, T, z_T, z'_T, z'_I} = \Pr(|z_I \oplus z'_I| > N(p + \epsilon) | b, T, z_T, z'_T, z'_I),$$

where the right hand side is a probability for Alice to obtain a distant  $z_I$  from Bob's  $z'_I$ . Combining the above estimates, we obtain

$$\langle Q_L^{b, T, z_T, z'_T} \rangle_{b, T, z_T, z'_T, z'_I} \leq |L| 2^{-M} + 3 \sqrt{\Pr(|z_I \oplus z'_I| > N(p + \epsilon) | b, T, z_T, z'_T, z'_I)}.$$

We multiply both sides of this inequality with  $p(z'_I|b, T, z_T, z'_T)$  and take a summation over  $z'_I$  to obtain

$$\langle Q_L^{b, T, z_T, z'_T} \rangle_{b, T, z_T, z'_T} \leq |L| 2^{-M} + 3 \sqrt{\Pr(|z_I \oplus z'_I| > N(p + \epsilon) | b, T, z_T, z'_T)},$$

where we have used Jensen's inequality once.

Q.E.D.

- [1] C. H. Bennett and G. Brassard, In *Proc. of IEEE Int. Conf. on Computers, Systems and Signal Processing*, 175 (1984).
- [2] D. Mayers, in *Advances in cryptology - CRYPTO'96*, LNCS **1109**, 343 (1996).
- [3] H-K. Lo and H-F. Chau, *Science*, **283**, 2050 (1999).
- [4] P. W. Shor and J. Preskill, *Phys.Rev.Lett.*, **85**, 441 (2000).
- [5] E. Biham, M. Boyer, P. O. Boykin, T. Mor, and V. Roychowdhury, *J. of Cryptology* **19**, 381 (2006).
- [6] Not all the security notions use Shannon entropy explicitly. They anyway can be interpreted in terms of probability theory.
- [7] A. N. Kolmogorov, *Probl. Inform. Transm.* **1**, 1, 1 (1965).
- [8] G. Chaitin, *J. Assoc. Comput. Mach.*, **13** 547 (1966).
- [9] M. Li and P. Vitányi, *An Introduction to Kolmogorov Complexity and Its Applications*, New York: Springer-Verlag (1997).
- [10] P. Vitányi, *IEEE Trans. Inform. Theory*, **47**: 6, 2464 (2001).
- [11] K. Svozil, *J. of Universal Comput. Sci.*, **2**, 311 (1996).
- [12] D. Deutsch, *Proc. Roy. Soc. London A*, **400**, 96 (1985).
- [13] A. Bernstein and U. Vazirani, *SIAM J. Comput.*, **26**, 1411 (1997).
- [14] A. Berthiaume, W. van Dam, and S. Laplante, *J. Comput. System. Sci.*, **63**, 201 (2001).
- [15] M. Müller, *IEEE Trans. Inform. Theory*, **54** : 2, 763 (2008).
- [16] M. Müller, Ph.D. thesis (2007).
- [17] P. Gacs, *J. Phys. A: Math. Gen.*, **34**, 1 (2001).
- [18] J. M. Myers, *Phys. Rev. Lett.*, **78**, 1823 (1997).
- [19] N. Linden and S. Popescu, [quant-ph/9806054](https://arxiv.org/abs/quant-ph/9806054).
- [20] M. Ozawa, *Phys. Rev. Lett.*, **80**, 631 (1998).
- [21] T. Miyadera and M. Ohya, *Open Sys. Info. Dyn.*, **12**, 261 (2005).
- [22] The word "probabilistically" here is used to mean "randomly in a probabilistic sense". That is, we use an unbiased probability  $1/|\Omega|$  to choose a sample from a sample space  $\Omega$  (say  $\Omega = \{0, 1\}^{2N}$ ). (To avoid a possible confusion of it with randomness in algorithmic sense, we just write "probabilistically".)
- [23] To treat  $\rho_{x, b_T, z_T, z'_T}^E$  as an auxiliary input for a quantum Turing machine, Eve's apparatus is somehow identified with a system consisting of qubits. Our discussion does not depend on how we identify them.
- [24] In general, a-posteriori state after a measurement is determined as follows. Suppose that there exist two system  $A$  and  $B$  that are described by Hilbert spaces  $\mathcal{H}_A$  and  $\mathcal{H}_B$  respectively. Let us consider a state  $\rho$  over the bipartite system  $\mathcal{H}_A \otimes \mathcal{H}_B$ . Suppose that on  $A$  one made a measurement described by a POVM  $F = \{F_x\}$  and obtained an outcome  $x$ . A-posteriori state on the system  $B$  conditioned with this  $x$  becomes

$$\rho_x = \frac{\text{tr}_A(\rho(F_x \otimes \mathbf{1}))}{\text{tr} \rho F_x \otimes \mathbf{1}}.$$

That is, it is a unique state that satisfies  $\text{tr}(\rho_x G) \text{tr}(\rho(F_x \otimes \mathbf{1})) = \text{tr}(\rho(F_x \otimes G))$  for any operator  $G$  on  $\mathcal{H}_B$ .