Canonical Phase Measurements in the Presence of Photon Loss

Aravind Chiruvelli and Hwang Lee

Hearne Institute for Theoretical Physics, Department of Physics and Astronomy

Louisiana State University, Baton Rouge, LA 70803, USA

We analyze the optimal state, as given by Berry and Wiseman [Phys. Rev. Lett **85**, 5098, (2000)], under the canonical phase measurement in the presence of photon loss. The model of photon loss is a generic fictious beam splitter, and we present the full density matrix calculations, which are more direct and do not involve any approximations. We find for a given amount of loss the upper bound for the input photon number that yields a sub-shot noise estimate.

PACS numbers: 42.50.St, 42.50.Ar, 42.50.Dv, 42.50.-p

I. INTRODUCTION

Canonical phase measurement in quantum mechanics is a significant problem, for the main reason that phase is a quantity that is conjugate to the number, N, of photons in a particular electromagnetic mode [1, 2, 3]. Due to this conjugate nature, the phase estimate $\Delta \varphi$ is ultimately limited by the number N of the photons as $\Delta \varphi = 1/N$, which is traditionally referred as the Heisenberg limit. Accurate phase estimation has many practical applications such as metrology, imaging and sensing [4]. Achieving such a limit in practice is not a trivial problem and there have been numerous proposals to achieve this limit [5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15]. Canonical phase measurement has been first dealt by Helstrom [16] and Shapiro [17], and later Sanders and Milburn [18, 19] used it to obtain a phase estimate in a Mach-Zehender inerferometer (MZI) as shown in Fig.1 (Loss not included). The phase estimate thus obtained is independent of the system phase, unlike in other methods [5, 6, 8] where the ultimate limit is achieved for a particular system phase. Also, the measurement specified by Sanders and Milburn is not particular to a specific input state.

Motivated by this work, Berry and Wiseman [7] analytically derived an input state, called as the optimal state, subject to the canonical measurement. They also suggested an adaptive method of approximately implementing the canonical phase measurement [7, 20], which has been used in the recent experimental realization of the Heisenberg limited phase measurement by Higgins *et.al* [21]. The canonical measurement, written as a Positive Operator Measured Value (POVM) by Sanders and Milburn [18] is,

$$\hat{F}(\varphi)d\varphi = \frac{2j+1}{2\pi} \left| j\varphi \right\rangle \left\langle j\varphi \right| d\varphi, \tag{1}$$

in terms of the phase states

$$\left|j\varphi\right\rangle = \frac{1}{\sqrt{2j+1}}\sum_{\alpha=-j}^{j}e^{i\alpha\varphi}\left|j\alpha\right\rangle_{y}$$

In defining this, the Schwinger's representation is used, and for completeness we wish to outline the notation. The three angular momentum components \hat{J}_x, \hat{J}_y and \hat{J}_z are very effective in analyzing twoport, lossless, interferometers [5, 6, 7, 18]. For the two modes, \hat{a} and \hat{b} of the MZI (Fig. 1), these two mode operators are,

$$\begin{split} \hat{J}_x &= (\hat{a}^{\dagger}\hat{b} + \hat{a}\hat{b}^{\dagger})/2, \quad \hat{J}_y = (\hat{a}^{\dagger}\hat{b} - \hat{a}\hat{b}^{\dagger})/2i, \\ \hat{J}_z &= (\hat{a}^{\dagger}\hat{a} - \hat{b}^{\dagger}\hat{b})/2, \quad \hat{J}^2 = \hat{J}_x^2 + \hat{J}_y^2 + \hat{J}_z^2. \end{split}$$

In the context of the MZI, \hat{J}_x implements the operation of a 50-50 beam splitter as $e^{i(\pi/2)\hat{J}_x}$ and \hat{J}_z defines the photon number difference in two modes. The simultaneous eigenvector of \hat{J}^2 and \hat{J}_z , $|j,m\rangle_z$ represents the joint input state $|j+m\rangle_a$ and $|j-m\rangle_b$ in the Fock-state basis, and the total input number of photons is N = 2j. The simultaneous eigenvector of \hat{J}^2 and \hat{J}_y , which is $|j,n\rangle_y$, represents the states within the interferometer. The beam splitter transformation in this representation performs a rotation about the \hat{J}_x . The phase states discussed above, are defined in terms of states within the interferometer in Fig. 1 and thus the output modes or detectors are irrelevant for the present purpose. Thus the probability distribution for the system phase ϕ is obtained as

$$P(\varphi)d\varphi = \langle \psi | \hat{F}(\varphi) | \psi \rangle d\varphi = \operatorname{Tr}[\rho \hat{F}(\varphi)]d\varphi.$$
(2)

Note that φ is the estimate of the system phase ϕ . The optimal state, to be specified below, is derived conditioned upon minimizing the Holevo variance calculated from the above probability distribution. The Holevo phase variance is defined as

$$(\Delta\varphi)^2 \equiv -1 + |\langle e^{i\varphi} \rangle|^{-2}, \qquad (3)$$

where $|\langle e^{i\varphi}\rangle| = \int_0^{2\pi} d\varphi P(\varphi) e^{i\varphi-\bar{\varphi}}$, is also called the sharpness. Here $\bar{\varphi}$ is a mean phase and we take it to be zero. The Holevo variance for the optimal state, from Ref. [7, 20] is,

$$(\Delta\varphi)^2 = \tan^2(\frac{\pi}{N+2}) \approx \frac{\pi^2}{N^2},\tag{4}$$

thus giving rise to Heisenberg limit.

It is natural to ask how such a scheme behaves under more realistic conditions, such as photon-loss associated with the propagation, which is what we study in this paper. We use the generic beam splitter model for photon



FIG. 1: Schematic of Mach-Zehender Interferometer (MZI) with photon loss at the phase shift. The state $|\psi\rangle_{\rm in}$ represents the joint input state at $\hat{a}_{\rm in}$ and $\hat{b}_{\rm in}$. Photons in the lower arm first encounter the fictious beam splitter (BS), for which vaccum enters through the other input, and depending the transmission coefficient, some of them are scattered into the mode \hat{c}' , which are ignored (traced out), and the remaining pass through the phase shifter.

loss [22], as shown in Fig. 1. The input mode \hat{c} for this fictious beam splitter is a vaccum mode, and the output mode \hat{c}' is then to be traced out. This typically implies that the photons that are lost in mode \hat{c}' , due to the nonzero reflection r, correspond to the photon loss. In the next Section we describe optimal state in presence of photon loss and in Section III, we carry out the explicit density matrix calculation. We conclude with Section IV, where we quantitatively describe the effect of loss on the canonical phase estimation.

II. OPTIMAL STATE IN PRESENCE OF PHOTON LOSS

We now proceed to develop the mathematical framework to study optimal-state canonical interferometry with photon loss. The beam splitter representing loss, with arbitrary transmission and reflection, can be characterized by an angle θ , such that transmission and reflection coefficients are $\tau = \cos^2(\theta/2)$ and $r = 1 - \cos^2(\theta/2)$, respectively. Therefore, the loss is simply the reflection coefficient,

$$L = r = 1 - \cos^2(\theta/2).$$
 (5)

The action of such an arbitrary beam splitter on an input state $|j, \alpha\rangle$ in Schwinger notation is simply given as [6],

$$e^{i\theta \hat{J}_x} \left| j, \alpha \right\rangle = \sum_{\beta = -j}^{j} e^{i\theta(\beta - \alpha)} d^j_{\alpha,\beta}(\theta) \left| j, \beta \right\rangle, \qquad (6)$$

where $d^{j}_{\alpha,\beta}(\theta)$ is the usual rotational matrix element given as:

$$\begin{aligned} l_{\nu\mu}^{j}(\theta) &= (-1)^{\nu-\mu} 2^{-\nu} \sqrt{\frac{(j-\nu)!(j+\nu)!}{j-\mu)!(j+\mu)!}} P_{j-\nu}^{(\nu-\mu,\nu+\mu)}(\cos\theta) \\ &\times (1-\cos\theta)^{\frac{\nu-\mu}{2}} (1+\cos\theta)^{\frac{\nu+\mu}{2}}, \end{aligned}$$
(7)

where $P_n^{(\alpha,\beta)}(x)$ is the Jacobi polynomial [23].

The optimal state was originally derived by Berry and Wiseman [7] conditioned on minimizing the phase variance with the canonical probability distribution given in Eq.(2). This state is,

$$|\psi\rangle_{\text{opt}} = \sum_{\mu=-j}^{j} \frac{1}{\sqrt{j+1}} \sin(\frac{(\mu+j+1)\pi}{2j+2}) |j\mu\rangle_{y}.$$
 (8)

Recall that the simultaneous eigenstates of \hat{J}^2 and \hat{J}_y denote the states *within* the interferometer, and thus the above state is after the first beam splitter. Further it will be useful to rewrite the above state in more explicit form as the product of the states of the two arms of the interferometer as,

$$\left|\psi\right\rangle_{\text{opt}} = \sum_{\mu=-j}^{j} \psi_{\mu} \left|j+\mu\right\rangle_{a} \left|j-\mu\right\rangle_{b}, \qquad (9)$$

where

$$\psi_{\mu} = \frac{1}{\sqrt{j+1}} \sin(\frac{(\mu+j+1)\pi}{2j+2})$$

With the loss in mode \hat{a} , which is represented by the fictious beam splitter, and $|0\rangle_c$ is the state entering the other input port, the combined input state for the fictious beam splitter is: $|j + \mu\rangle_a |0\rangle_c$, and thus the state to be considered is,

$$|\psi\rangle = |\psi\rangle_{opt} |0\rangle_c \,. \tag{10}$$

Making use of the Schwinger representation for modes \hat{a} and \hat{c} , the input for the fictious beam splitter would be $\left|\frac{j+\mu}{2}, \frac{j+\mu}{2}\right\rangle_{a,c}$ which immediately leads to,

$$|\psi\rangle = \sum_{\mu=-j}^{j} \psi_{\mu} \left[e^{i\theta \hat{J}_{x}} \left| \frac{j+\mu}{2}, \frac{j+\mu}{2} \right\rangle_{a,c} \right] |j-\mu\rangle_{b}.$$
(11)

The term enclosed in square bracket in the above equation can be evaluated explicitly using Eq.(6). After some straight-forward rearrangement, we arrive at a pure state in the modes \hat{a}', \hat{c}' and \hat{b}

$$\begin{split} |\psi\rangle &= \sum_{\mu=-j}^{j} \sum_{m=-k}^{k} \psi_{\mu} e^{i\frac{\pi}{2}(m-k)} d_{mk}^{k}(\theta) \\ &\times |k+m\rangle_{a'} |k-m\rangle_{c'} |j-\mu\rangle_{b} \,, \end{split}$$
(12)

where $k = (j + \mu)/2$ and $d_{mk}^k(\theta)$ is the usual rotational matrix element, as defined earlier.

III. DENSITY MATRIX DESCRIPTION

The state specified in Eq. (12) is a pure state and cannot be used further, so we need to calculate the reduced density matrix, by tracing out, mode \hat{c}' , as we have no more access to the lost photons. Thus first we need to calculate the total density matrix, representing the pure state of Eq.(12),

$$\rho = |\psi\rangle \langle \psi| \\
= \sum_{\mu,\nu=-j}^{j} \sum_{m=-k}^{k} \sum_{n=-k'}^{k'} \Omega(\mu,\nu,m,k,n,k') e^{i\frac{\pi}{2}(m-k)} e^{-i\frac{\pi}{2}(n-k')} |k+m\rangle_{a'} |k-m\rangle_{c'} |j-\mu\rangle_{b\ a'} \langle k'+n|_{c'} \langle k'-n|_{b} \langle j-\nu|, \quad (13)$$

where $\Omega(\mu, \nu, m, k, n, k') = \psi_{\mu}\psi_{\nu}d_{m,k}^{k}(\theta)d_{n,k'}^{k'}(\theta)$ and $k' = (j + \nu)/2$. The total density matrix given in Eq.(13) explicitly represents the state within the interferometer for a given loss, characterized by the angle θ , and is useful in analyzing lossy interferometers such as the present one.

As the mode \hat{c}' is to be ignored, we need the reduced density matrix by tracing out that mode from the total density matrix given in Eq.(13). Thus we have,

$$\rho' = \operatorname{Tr}_{c'}[|\psi\rangle \langle \psi|] = \sum_{\mu,\nu=-j}^{j} \sum_{m=-k}^{k} \sum_{n=-k'}^{k'} \Omega(\mu,\nu,m,k,n,k') e^{i\frac{\pi}{2}(m-k)} e^{-i\frac{\pi}{2}(n-k')} |k+m\rangle_{a'} |j-\mu\rangle_{b\ a'} \langle k'-n|_{b} \langle j-\nu| [_{c'} \langle k-m|k'-n\rangle_{c'}].$$
(14)

Noting that $_{c'}\langle k-m||k'-n\rangle_{c'}=\delta_{k-m,k'-n}$, we eliminate the two exponential terms in Eq.(14). This leads to:

$$\rho' = \sum_{\mu,\nu=-j}^{j} \sum_{m=-k}^{k} \sum_{n=-k'}^{k'} \Omega(\mu,\nu,m,k,n,k') \delta_{k-m,k'-n} |k+m\rangle_{a'} |j-\mu\rangle_{b\ a'} \langle k'-n|_{b} \langle j-\nu|.$$
(15)

We can now use Eq.(15) in Eq.(2) to obtain the probability distribution and thus minimum detectable phase as a function of θ , which characterizes the photon loss and the input photon number 2j. For ease of calculation, we let $|k+m\rangle_{a'}|j-\mu\rangle_b = |xy\rangle_{a'b}$, where $x = (k+m+j-\mu)/2$ and $y = (k+m-j+\mu)/2$, and similarly the conjugate, $a' \langle k'-n|_b \langle j-\nu| = a'b \langle x'y'|$, where $x' = (k'+n+j-\nu)/2$ and $y' = (k'+n-j+\nu)/2$. Thus, leaving the summation indices unchanged, we rewrite the reduced density matrix Eq.(15) as,

$$\rho' = \sum_{\mu,\nu=-j}^{j} \sum_{m=-k}^{k} \sum_{n=-k'}^{k'} \Omega \, \delta_{k-m,k'-n} \, |x,y\rangle_{a'\,b} \, \langle x',y'| \,. \tag{16}$$

Here Ω replaces $\Omega(\mu, \nu, m, k, n, k')$ for conciseness.

IV. PHASE ESTIMATE IN PRESENCE OF PHOTON LOSS

except for the indices μ and ν . Hence the probability distribution explicitly now is given as

Thus using Eq.(1), and the phase states described in the introduction, we have

$$P(\varphi) = \operatorname{Tr}[\rho' F(\varphi)]$$

= $\sum_{\mu,\nu=-j}^{j} \sum_{m=-k}^{k} \sum_{n=-k'}^{k'} \Omega e^{i(\alpha-\beta)\varphi} \langle x'y'|j\alpha\rangle \langle xy|j\beta\rangle, (17)$

which leads to two Kronecker delta functions, $\langle x'y'|j\alpha \rangle = \delta_{j,x'}\delta_{y',\alpha}$ and $\langle xy|j\beta \rangle = \delta_{x,j}\delta_{y,\beta}$. Invoking the definitions of x, x' and y, y', we find that the only nonzero terms in the summations are, $n = k', \alpha = \nu, m = k$, and $\beta = \mu$. Further, these delta functions eliminate all summations

$$P(\varphi) = \frac{1}{2\pi} \sum_{\mu,\nu=-j}^{j} \psi_{\mu} \psi_{\nu} e^{i(\nu-\mu)\varphi} d_{k,k}^{k}(\theta) d_{k',k'}^{k'}(\theta).$$
(18)

With the probability distribution given in Eq.(18), we can calculate any moments of the phase estimate. Here we calculate the Holevo phase variance rather than the standard variance, because the optimal state is derived by minimizing the Holevo phase variance [7]. Using Eq. (18) and definitions of k, k' and the rotational matrix element, sharpness $|\langle e^{i\varphi} \rangle|$ is given as,



FIG. 2: Log-Log graph of minimum detectable phase versus the input photon number N = 2j for two different values of Loss. (a) $L = 10^{-3}$ and (b) L = 0.3. The dotted line in both figures is the shot noise limit $1/\sqrt{2j}$ and the dashed line in (a) is the Heisenberg limit given be Eq. (4), for comparison.

$$|\langle e^{i\varphi}\rangle| = \sum_{\mu=-j}^{j} \psi_{\mu}\psi_{\mu-1} \left[\cos^2\left(\frac{\theta}{2}\right)\right]^{j+\mu-\frac{1}{2}}.$$
 (19)

We can use Eq. (19) in Eq. (3) to obtain the estimate as



FIG. 3: The optimal number, $N_{\rm opt}$ as a function of loss for various values of loss L.

a function of loss.

In the present case we use Eq.(18) to plot the minimum detectable phase $\Delta \varphi$ as a function of 2j = N, the number of input photons, for two different values of loss, $L = 10^{-3}$ and L = 0.3, in Fig. 2. For comparison we also plot the Heisenberg limit for the optimal state given in Eq. (4). We can immediately observe that the minimum detectable phase is not always a continuously decreasing function, depending on the loss, the minimum detectable phase starts to diverge at certian photon numbers, which we shall call the *optimal number*, N_{opt} . As we do not have a closed form expression for the Holevo variance, as a function of loss L and input photon number N, we have not found an analytical form for the optimal number, N_{opt} as function of loss, L [see Eq.(5)]. So we numerically plot N_{opt} as a function of L in Fig. 3 and it clearly decreases as the loss L increases.

On the other hand, the upper bound for a certain number of input photons can be found where $\Delta \varphi$ meets the shot-noise limit in Fig. 2(a). That is to say, for a small amount of loss, we can still operate the interferometer, with the input number of photons less than the upper bound and achieve a sub-shot noise limited phase estimate.

To summarize, we analyzed the canonical phase measurement in presence of photon loss. Our formalism is based on the density matrix, which describes the mixed states, which naturally arise due to the presence of loss. Our analysis shows that the minimum detectable phase is not monotonically decreasing function and would tend to increase at certain photon numbers, depending the loss present. Nevertheless, we can for small loss have considerably high number of input photons for the optimal state, that achieve sub-shot noise level phase estimates. We also have numerically plotted the optimal number, where the minimum detectable phase shift starts to diverge, as a function of loss, L, which would determine the optimal number of the input photon number for the optimal state, in presence of given amount of loss.

Acknowledgments: We acknowledge financial support from the US Defense Advanced Research Projects Agency, the US Intelligence Advanced Research Projects Activity, and the US Army Research Office. We would like to acknowledge J. P. Dowling for helpful discussions.

- A. S. Lane, S. L. Braunstein, and C. M. Caves, Phys. Rev. A 47, 1667 (1993).
- [2] Z. Hradil, Phys. Rev. A 51, 1870 (1995).

[3] Z. Hradil, et al. Phys. Rev. Lett **76**, 4295 (1996).

^[4] V. Giovannetti, S. Lloyd, and L. Maccone, Science 306, 1330 (2004).

- [5] H. Lee, P. Kok, and J.P. Dowling, J. Mod. Opt. 49, 2325 (2002).
- [6] T. Kim, O. Pfister, M. J. Holland, J. Noh, and J. L. Hall, Phys. Rev. A 57, 4004 (1998).
- [7] D. W. Berry and H. M. Wiseman, Phys. Rev. Lett. 85, 5098 (2000).
- [8] R. A. Campos, C. C. Gerry, and A. Benmoussa, Phys. Rev. A 68, 023810 (2003).
- [9] C. M. Caves, Phys. Rev. D 23, 1693 (1981).
- [10] C. C. Gerry and R. A. Campos, Phys. Rev. A 64, 063814 (2001).
- [11] H. P. Yuen, Phys. Rev. Lett 56, 2176 (1986).
- [12] B. Yurke, S. L. McCall, and J. R. Klauder, Phys. Rev. A 33, 4033 (1986).
- [13] J. J. Bollinger, W. M. Itano, D. J. Wineland, and D. J. Heinzen, Phys. Rev. A 54, R4649 (1996).
- [14] J. P. Dowling, Phys. Rev. A 57, 4736 (1998).
- [15] M. J. Holland and K. Burnett, Phys. Rev. Lett. 71, 1335

(1993).

- [16] C. W. Helstrom, Quantum Detection and Estimation Theory, (Acedemic, New York, 1976).
- [17] J. H. Shapiro, Phys. Scr. **T48**, 105, (1993).
- [18] B.C. Sanders and G.J. Milburn, Phys. Rev. Lett. 75, 2944 (1995).
- [19] B. C. Sanders, G. J. Milburn, and Z. Zhang, J. Mod. Opt. 44, 1309 (1997).
- [20] D. W. Berry, H. M. Wiseman, and J. K. Breslin Phys. Rev. A 63, 053804 (2001).
- [21] B. L. Higgins, D. W. Berry, S. D. Bartlett, H. M. Wiseman, and G. J. Pryde, Nature 450, 393 (2007).
- [22] R. Loudon, *The Quantum Theory of Light* 3rd ed. (Oxford University Press, Oxford, UK, 2000).
- [23] D. M. Brink and G. R. Satchler, Angular Momentum 3rd ed. (Clarendon Press, Oxford, UK, 1993).