Constraints on effective constitutive parameters of certain bianisotropic laminated composite materials

AKHLESH LAKHTAKIA

Nanoengineered Metamaterials Group Department of Engineering Science & Mechanics 212 Earth & Engineering Sciences Building Pennsylvania State University University Park, PA 16802–6812 USA

Abstract

When the electrically thin unit cell of a laminated composite material is made of two bianisotropic sheets whose constitutive properties in the thickness direction are decoupled from the constitutive properties in the interfacial planes, the laminated composite material can be homogenized into a material not all of whose constitutive parameters are independent of each other. This non-independence of the constitutive dyadics of the constituent materials and the homogenized composite material is captured by two simple constraints, which may not hold if even one of the two constituent materials has more complicated constitutive properties than stated above.

Key words: Bianisotropic composite materials, homogenization, laminated composite materials, magnetoelectric parameters.

1 Introduction

The electromagnetic response properties of laminated composite materials have been and continue to be of technoscientific importance (Herpin, 1947, Abelès, 1950; Lafait *et al.*, 1990; Neelakanta, 1995; Lakhtakia, 1996). A laminated composite material is made by stacking together sheets of different materials one on top of another, in order to form a unidirectionally nonhomogeneous material with piecewise-uniform constitutive properties. When a monochromatic plane wave is incident on this stratified composite material, standing waves are set up in each sheet, and electromagnetic energy may also be absorbed therein. In addition, the phenomenons of reflection and transmission occur. Across any interface, the tangential components of the electric and the magnetic field phasors are continuous. These tangential components are the essential ingredients of a two-point boundary value problem that can be adequately stated and solved using matrix calculus. Whereas 2×2 matrixes suffice for isotropic dielectric-magnetic sheets, 4×4 matrixes are needed for sheets with more complicated electromagnetic properties (Teitler & Henvis, 1970; Mrozowski, 1986; Lakhtakia, 1987).

A homogenization problem emerges when electrically thin sheets are stacked periodically and the unit cell is also electrically thin (Wiener, 1912; Rytov, 1956; Rumsey, 1964). Such a periodically nonhomogeneous composite material whose unit cell comprises two or more sheets *may* be considered equivalent to a homogeneous material that necessarily has direction-dependent constitutive properties. Analytically straightforward techniques can be employed to predict the effective (i.e., post-homogenization) constitutive parameters of a laminated composite material (Reese & Lakhtakia, 1991; Ramakrishna & Lakhtakia, 2009). The effective constitutive parameters depend on the constitutive parameters of the constituent materials as well as on their volume fractions.

Are all effective constitutive parameters necessarily independent of each other? Or, knowledge of some effective constitutive parameters is sufficient to determine the others without recourse to the volume fractions of the constituent materials. This brief communication addresses this issue.

An $\exp(-i\omega t)$ time-dependence is implicit, with ω denoting the angular frequency. The permeability and permittivity of free space (i.e., vacuum) are denoted by μ_o and ε_o , respectively. Vectors are in boldface, dyadics are underlined twice, column vectors are in boldface and enclosed within square brackets, and matrixes are underlined twice and similarly bracketed. Cartesian unit vectors are identified as \mathbf{u}_x , \mathbf{u}_y and \mathbf{u}_z , with the z axis oriented normal to the sheets.

2 Analysis

Let us consider a periodic laminated composite material whose unit cell is made of two sheets of dissimilar, homogeneous, bianisotropic materials labeled 1 and 2. The Tellegen constitutive relations of the two materials are written in the frequency domain as (Lakhtakia, 1987)

$$\mathbf{D} = \varepsilon_o \left(\underline{\underline{\varepsilon}}^{(n)} \cdot \mathbf{E} + \underline{\underline{\alpha}}^{(n)} \cdot \mathbf{H} \right)$$

$$\mathbf{B} = \mu_o \left(\underline{\underline{\mu}}^{(n)} \cdot \mathbf{H} + \underline{\underline{\beta}}^{(n)} \cdot \mathbf{E} \right)$$

$$n \in \{1, 2\} .$$

$$(1)$$

The relative permittivity dyadic and the relative permeability dyadic of the *n*-th material are denoted by $\underline{\underline{\varepsilon}}^{(n)}$ and $\underline{\underline{\mu}}^{(n)}$, respectively, whereas the dyadics $\underline{\underline{\alpha}}^{(n)}$ and $\underline{\underline{\beta}}^{(n)}$ denote the magnetoelectric properties. The thickness of the sheets made of the *n*-th constituent material is denoted by d_n , so that

$$f_n = d_n / (d_1 + d_2), \quad n \in \{1, 2\},$$
 (2)

is the volume fraction of the *n*-th material, with $f_2 = 1 - f_1$.

Wave propagation in the laminated composite material can be handled by using the spatial Fourier transform as (Krowne, 1984)

$$\mathbf{E}(x, y, z) = \int_{-\infty}^{\infty} \int_{0}^{2\pi} \mathbf{e}(z, \kappa, \psi) \exp\left[i\kappa(x\cos\psi + y\sin\psi)\right] d\psi d\kappa \\
\mathbf{H}(x, y, z) = \int_{-\infty}^{\infty} \int_{0}^{2\pi} \mathbf{h}(z, \kappa, \psi) \exp\left[i\kappa(x\cos\psi + y\sin\psi)\right] d\psi d\kappa \\$$
(3)

where κ is the spatial frequency and ψ is an angle. Substitution of this representation along with the constitutive relations (1) in the two Maxwell curl equations leads to the 4×4-matrix ordinary differential equation (Lakhtakia, 1987)

$$\frac{d}{dz}\left[\mathbf{F}(z,\kappa,\psi)\right] = i\left[\underline{\underline{P}}^{(n)}(\kappa,\psi)\right] \cdot \left[\mathbf{F}(z,\kappa,\psi)\right], \quad n \in \{1,2\},$$
(4)

in any sheet made of the n-th material. The column vector

$$[\mathbf{F}(z,\kappa,\psi)] = \begin{bmatrix} e_x(z,\kappa,\psi) \\ e_y(z,\kappa,\psi) \\ h_x(z,\kappa,\psi) \\ h_y(z,\kappa,\psi) \end{bmatrix}$$
(5)

represents components of the electric and magnetic field phasors that are tangential to the bimaterial interfaces in the laminated composite material. The 4×4 matrix $\left[\underline{\underline{P}}^{(n)}(\kappa,\psi)\right]$ is too cumbersome to reproduce here, but it can be put in the following form (Lakhtakia & Weiglhofer, 1997):

$$\left[\underline{\underline{P}}^{(n)}(\kappa,\psi)\right] = \left[\underline{\underline{Q}}_{1}^{(n)}\right] + \kappa \left\{\left[\underline{\underline{Q}}_{2}^{(n)}\right] e^{-i\psi} + \left[\underline{\underline{Q}}_{3}^{(n)}\right] e^{i\psi}\right\} + \kappa^{2} \left[\underline{\underline{Q}}_{4}^{(n)}(\psi)\right], \quad n \in \{1,2\}.$$
(6)

Provided the sheets are electrically thin (Lakhtakia & Krowne, 2003; Mackay, 2008), the laminated composite material is equivalent to a homogeneous material with the following constitutive relations:

$$\mathbf{D} = \varepsilon_o \left(\underline{\underline{\varepsilon}}^{eff} \cdot \mathbf{E} + \underline{\underline{\omega}}^{eff} \cdot \mathbf{H} \right) \\
\mathbf{B} = \mu_o \left(\underline{\underline{\mu}}^{eff} \cdot \mathbf{H} + \underline{\underline{\beta}}^{eff} \cdot \mathbf{E} \right) \\$$
(7)

Equations (3) and (4) govern wave propagation in the homogenized composite material, except that the matrix $\left[\underline{\underline{P}}^{(n)}(\kappa,\psi)\right]$ must be replaced by

$$\left[\underline{\underline{P}}^{eff}(\kappa,\psi)\right] = \left[\underline{\underline{Q}}_{1}^{eff}\right] + \kappa \left\{\left[\underline{\underline{Q}}_{2}^{eff}\right] e^{-i\psi} + \left[\underline{\underline{Q}}_{3}^{eff}\right] e^{i\psi}\right\} + \kappa^{2} \left[\underline{\underline{Q}}_{4}^{eff}(\psi)\right].$$
(8)

As the sheets and the unit cell are electrically thin, invocation of the long–wavelength approximation (Reese & Lakhtakia, 1991; Lakhtakia & Krowne, 2003) yields the relation

$$\left[\underline{\underline{P}}^{eff}(\kappa,\psi)\right] = f_1 \left[\underline{\underline{P}}^{(1)}(\kappa,\psi)\right] + f_2 \left[\underline{\underline{P}}^{(2)}(\kappa,\psi)\right], \quad \forall \{\kappa,\psi\} , \qquad (9)$$

which can be used to determine $\left\{\underline{\underline{\varepsilon}}^{eff}, \underline{\underline{\mu}}^{eff}, \underline{\underline{\alpha}}^{eff}, \underline{\underline{\beta}}^{eff}\right\}$ in terms of $\left\{\underline{\underline{\varepsilon}}^{(1)}, \underline{\underline{\mu}}^{(1)}, \underline{\underline{\alpha}}^{(1)}, \underline{\underline{\beta}}^{(1)}\right\}$, $\left\{\underline{\underline{\varepsilon}}^{(2)}, \underline{\underline{\mu}}^{(2)}, \underline{\underline{\alpha}}^{(2)}, \underline{\underline{\beta}}^{(2)}\right\}$, f_1 , and f_2 . The equation

$$\left[\underline{\underline{Q}}_{4}^{eff}(\psi)\right] = f_1 \left[\underline{\underline{Q}}_{4}^{(1)}(\psi)\right] + f_2 \left[\underline{\underline{Q}}_{4}^{(2)}(\psi)\right]$$
(10)

is satisfied $\forall \psi \in [0, 2\pi)$ by

where $\varepsilon_{zz}^{eff} = \mathbf{u}_z \cdot \underline{\underline{\varepsilon}}^{eff} \cdot \mathbf{u}_z$, etc., and

$$\Phi^{(n,m)} = \varepsilon_{zz}^{(n)} \mu_{zz}^{(m)} - \alpha_{zz}^{(n)} \beta_{zz}^{(m)} \gamma^{-1} = f_1^2 \Phi^{(2,2)} + f_2^2 \Phi^{(1,1)} + f_1 f_2 \left(\Phi^{(1,2)} + \Phi^{(2,1)} \right)$$
(12)

Solution of the equations

$$\left[\underline{\underline{Q}}_{m}^{eff}\right] = f_{1}\left[\underline{\underline{Q}}_{m}^{(1)}\right] + f_{2}\left[\underline{\underline{Q}}_{m}^{(2)}\right], \quad m \in \{1, 2, 3\},$$
(13)

yields analytical expressions for the remaining components of $\left\{\underline{\underline{\varepsilon}}^{eff}, \underline{\underline{\mu}}^{eff}, \underline{\underline{\beta}}^{eff}, \underline{\underline{\beta}}^{eff}\right\}$, but those expressions are far too unwieldy, in general, for reproduction here.

2.1 A special case

A special case emerges when all four constitutive dyadics of both constituent materials are of the form

$$\underline{\underline{a}}^{(n)} = a_{zz}^{(n)} \mathbf{u}_{z} \mathbf{u}_{z} + \underline{\underline{A}}^{(n)} \\ \mathbf{u}_{z} \cdot \underline{\underline{A}}^{(n)} = \underline{\underline{A}}^{(n)} \cdot \mathbf{u}_{z} = \mathbf{0}$$
, $a \in \{\varepsilon, \mu, \alpha, \beta\}$, $n \in \{1, 2\}$, (14)

so that $a_{zx}^{(n)} = a_{zy}^{(n)} = a_{xz}^{(n)} = a_{yz}^{(n)} = 0$. Then, $\left[\underline{\underline{Q}}_{2}^{(n)}\right] = \left[\underline{\underline{Q}}_{3}^{(n)}\right] = \left[\underline{\underline{0}}\right], (n \in \{1, 2\})$, and the simplifications

$$a_{zx}^{eff} = a_{zy}^{eff} = a_{xz}^{eff} = a_{yz}^{eff} = 0, \quad a \in \{\varepsilon, \mu, \alpha, \beta\} ,$$
(15)

follow from eqs. (13). Furthermore, those equations yield

$$a_{pq}^{eff} = f_1 a_{pq}^{(1)} + f_2 a_{pq}^{(2)}, \quad a \in \{\varepsilon, \mu, \alpha, \beta\}, \quad p \in \{x, y\}, \quad q \in \{x, y\}.$$
(16)

These expressions hold in addition to eqs. (11) for a_{zz}^{eff} .

Equations (11) and (16) indicate that—once ε_{pq}^{eff} and μ_{pq}^{eff} , $(p \in \{x, y, z\}, q \in \{x, y, z\})$, have been calculated by using the constitutive parameters and the volume fractions of both constituent materials— α_{pq}^{eff} and β_{pq}^{eff} can be obtained without using the volume fractions at all. Thus, 10 of the 20 effective constitutive parameters in the special case under consideration require knowledge of the volume fractions, but thereafter the remaining 10 effective constitutive parameters do not. Accordingly, all effective constitutive parameters are not independent of each other.

2.2 General consideration

Equations (11) and (16) suggest the formulation of the constraints

$$\operatorname{Det}\left[\begin{array}{cc}\underline{\underline{\varepsilon}}^{(1)} & \underline{\underline{\varepsilon}}^{(2)} & \underline{\underline{\varepsilon}}^{eff} \\ \underline{\underline{\mu}}^{(1)} & \underline{\underline{\mu}}^{(2)} & \underline{\underline{\mu}}^{eff} \\ \underline{\underline{\alpha}}^{(1)} & \underline{\underline{\alpha}}^{(2)} & \underline{\underline{\alpha}}^{eff} \end{array}\right] = \operatorname{Det}\left[\begin{array}{cc}\underline{\underline{\varepsilon}}^{(1)} & \underline{\underline{\varepsilon}}^{(2)} & \underline{\underline{\varepsilon}}^{eff} \\ \underline{\underline{\mu}}^{(1)} & \underline{\underline{\mu}}^{(2)} & \underline{\underline{\mu}}^{eff} \\ \underline{\underline{\beta}}^{(1)} & \underline{\underline{\beta}}^{(2)} & \underline{\underline{\beta}}^{eff} \end{array}\right] = 0.$$
(17)

Both certainly hold true for the special case treated in Sec. 2.1. Could these constraints hold in a more general sense?

When even one of the two constituent materials is more general than in Sec. 2.1, analytical expressions for $\{\underline{\underline{\varepsilon}}^{eff}, \underline{\underline{\mu}}^{eff}, \underline{\underline{\alpha}}^{eff}, \underline{\underline{\beta}}^{eff}\}$ turn out to be so huge that analytical expressions of the determinants in the two constraints (17) could not be manipulated to ascertain if both constraints hold true in general.

Several numerical experiments were conducted, wherein all 36 effective constitutive parameters were computed with $f_1 \in (0, 1)$ and with none of the 72 constitutive parameters of the two constituent materials of null value. The determinants in eqs. (17) turned out be significantly different from zero, indicating thereby that the constraints (17) do not hold in general.

2.3 Unit cell with 3 or more sheets

Suppose the unit cell of a certain laminated composite material comprises three different sheets. Two adjacent sheets can be homogenized into one thicker sheet, and the conclusions in Sec. 2.1 and 2.2 apply to that homogenization. This thicker sheet and the third sheet can also be homogenized into a single sheet of the thickness of the unit cell, and the conclusions in Sec. 2.1 and 2.2 also apply to that homogenization. This procedure can be adopted for unit cells with 4 or more sheets, so long as the unit cell, after all homogenization steps, remains electrically thin.

3 Concluding Remarks

Suppose that the unit cell of a laminated composite material is made of two bianisotropic sheets whose constitutive properties in the thickness direction are decoupled from the constitutive properties in the interfacial planes. Provided that the long-wavelength approximation is applicable, the laminated composite material can be homogenized into a material all of whose constitutive parameters are not independent of each other. This non-independence of the constitutive dyadics of the constituent materials and the homogenized composite material is captured by two simple constraints. When even one of the two constituent materials has more complicated constitutive properties, the constraints are not expected to hold.

Given that magnetoelectric properties are considerably rarer and usually weaker than dielectricmagnetic properties, the two constraints, when valid, should be considered as applicable on the magnetoelectric dyadics. Isotropic chiral and biisotropic materials, general uniaxial bianisotropic materials, gyrotropic materials such as ferrites and Faraday chiral materials, etc., (Mackay & Lakhtakia, 2008) all lie within the scope of the two constraints. In the realm of classical electromagnetics (i.e., at frequencies not exceeding about 750 THz), we can expect the homogenization procedure to hold for sheets as thin as 10 molecular diameters (Kim *et al.*, 2005). Thus, the conclusions drawn in this communication can also be expected to hold at optical and lower frequencies for many types of nanotextured thin films.

Acknowledgments. Thanks are due to S. Anantha Ramakrishna (IISER, Mohali, India) for discussions. The Charles Godfrey Binder Endowment at Penn State is gratefully acknowledged for partial financial support.

References

Abelès, F. 1950. Recherches sur la propagation des ondes électromagnétiques sinusodales dans les milieux stratifiés. Application aux couches minces (1re partie). Ann. Phys. (Paris) $5:596-640.^1$

Herpin, A. 1947. Calcul du pouvoir réflecteur d'un système stratifié quelconque. C. R. Acad. Sci. (Paris) 225:182–183.

Kim, H.-Y., J.O. Sofo, D. Velegol, M.W. Cole, and G. Mukhopadhyay. 2005. Static polarizabilities of dielectric nanoclusters. *Phys. Rev. A* 72:053201.

Krowne, C.M. 1984. Fourier transformed matrix method of finding propagation characteristics of complex anisotropic layered media. *IEEE Trans. Microw. Theory Tech.* 32:1617–1625.

Lafait, J., T. Yamaguchi, J. M. Frigerio, A. Bichri, and K. Driss-Khodja. 1990. Effective medium equivalent to a symmetric multilayer at oblique incidence. *Appl. Opt.* 29:2460–2464.

Lakhtakia, A. 1987. Cartesian solutions of Maxwell's equations for linear, anisotropic media— Extension of the Mrozowski algorithm. Arch. Elektr. Über. 41:178–179.

Lakhtakia, A. (ed.) 1996. Selected papers on linear optical composite materials. Bellingham, WA, USA: SPIE.

¹See Lakhtakia (1996) for a facsimile reproduction.

Lakhtakia, A., and C.M. Krowne. 2003. Restricted equivalence of paired epsilon-negative and munegative layers to a negative phasevelocity material (*alias* left-handed material). *Optik* 114:305–307.

Lakhtakia, A., and W.S. Weiglhofer. 1997. Green function for radiation and propagation in helicoidal bianisotropic mediums. *IEE Proc.-Microw. Antennas Propagat.* 144:57–59.

Mackay, T.G. 2008. Lewin's homogenization formula revisited for nanocomposite materials. J. Nanophoton. 2:029503.

Mackay, T.G., and A. Lakhtakia. 2008. Electromagnetic fields in linear bianisotropic mediums. *Prog. Opt.* 51:121–209.

Mrozowski, M. 1986. General solutions to Maxwell's equation in a bianisotropic medium.—A computer oriented, spectral domain approach. Arch. Elektr. Über. 40:195–197.

Neelakanta, P.S. 1995. Handbook of composite materials. Boca Raton, FL, USA: CRC Press.

Ramakrishna, S.A., and A. Lakhtakia. 2009. Spectral shifts in the properties of a periodic multilayered stack due to isotropic chiral layers. J. Opt. A: Pure Appl. Opt. (accepted for publication).

Reese, P.S., and A. Lakhtakia. 1991. Low-frequency electromagnetic properties of an alternating stack of thin uniaxial dielectric laminae and uniaxial magnetic laminae. Z. Natürforsch. A 46:384–388.

Rumsey, V.H. 1964. Propagation in generalized gyrotropic media. *IEEE Trans. Antennas Propagat.* 12:83–88

Rytov, S.M. 1956. Electromagnetic properties of a finely stratified medium. *Sov. Phys. JETP* 2:466–475.

Teitler, S., and B.W. Henvis. 1970. Refraction in stratified, anisotropic media. J. Opt. Soc. Am. 60:830–834.

Wiener, O. 1912. Die Theorie des Mischkörpers für das Feld der Stationären Strömung. Erste Abhandlung: Die Mittelwertsätze für Kraft, Polarisation und Energie. *Abh. Math.-Phys. Kl. Königl. Schs. Ges. Wissen.* 32:507–604.²

 $^{^{2}}$ See Lakhtakia (1996) for Bernhard Michel's synposis in English of this landmark paper.