A (possible) mathematical model to describe biological "context-dependence" : case study with protein structure

Anirban Banerji

Bioinformatics Centre, University of Pune Pune-411007, Maharashtra, India. Email address : anirbanab@gmail.com

Abstract

Context-dependent nature of biological phenomena are well documented in every branch of biology. While there have been few previous attempts to (implicitly) model various facets of biological context-dependence, a formal and general mathematical construct to model the wide spectrum of contextdependence, eludes the students of biology. An objective and rigorous model, from both 'bottom-up' as well as 'top-down' perspective, is proposed here to serve as the template to describe the various kinds of context-dependence that we encounter in different branches of biology. Interactions between biological contexts was found to be transitive but non-commutative. It is found that a hierarchical nature of dependence amongst the biological contexts models the emergent biological properties efficiently. Reasons for these findings are provided with a general model to describe biological reality. Scheme to algorithmically implement the hierarchic structure of organization of biological contexts was achieved with a construct named 'Context tree'. A 'Context tree' based analysis of context interactions among biophysical factors influencing protein structure was performed.

Keywords : Biological contexts; mathematical model; hierarchical organization; emergence; thread-mesh model; context tree.

Introduction :

'Context-dependence' is omnipresent in Biology. From the realm of substitution of nucleotides (Siepel et al. 2004, Zhang et al. 2007) to the paradigm of protein structure-function (Main et al. 1998, Nobeli et al. 2009), from the sphere of cellular dynamics (Hagan and Sharrocks 2002) to that in virulence studies in host-parasite systems (Brown et al., 2003) and evolutionary dynamics (Jablonski et al. 2006), one encounters events and processes that are "context-dependent". While various attempts have been made from differing perspectives to somehow quantify context-sensitiveness of particular biological events (Andrianantoandro et al. 2006, Torney et al. 2009, Banerji and Ghosh 2011), a general mathematical framework that attempts to capture and describe the ubiquitous 'context-dependence', eludes the students of Biology. In the present work, such a mathematical structure is proposed that attempts to model biological 'context-dependence' from bottom-up as well as top-down perspectives. Although the need to engineer an exact scheme to describe biological context-dependence was felt by many in recent past (Loewe 2009, Haseltine and Arnold 2007, Marguet et al. 2007, Platzer and Meinzer 2002), the present approach takes these concerns to a tangible outcome by proposing a general and robust theoretical construct to model biological organisation from both top-down and bottom-up perspectives with algorithmically implementable constructs. Unlike some previous attempts constructs proposed here do not tangentially touch upon context-dependence modelling (Standish 2001, Edmonds 1999, Yartseva et al. 2007), but concentrate solely on it; nor do they restrict themselves into (successful yet) particular scopes (Doboli et al. 2000, Hoare et al. 2004). On the other hand, it does not attempt to construct a computational structure that helps in retrieval of biological data from some repository in a context-dependent manner (Yu et al. 2009, Boeckmann et al. 2005), nor does it propose some (effective) visualization tool to observe context-dependent interactions between biological properties (Gopalacharyulu et al. 2006). A reliable and general mathematical model to describe biological context-dependence is of utmost necessity for contemporary Biology. This paper suggests a possible construct to achieve the same.

(A recent work that attempted constructing a mathematical model to unambiguously describe the concept 'evolvability' (Valiant 2009), underlines the necessity of present genre of works.)

We suggest the triad of the form \leq Structure of biological goals (F) , Biological contexts (C) , Physical structure of the system (P) , $(*F, C, P >*$), to describe the structure of any biological process. Components of this triad are (of course) not independent; F determines the suitable choice of C ; while C , in its turn, operates upon some particular subset of P with definite features. To ensure F is achieved, C engages only certain elements of P. Such triad-based structure is necessary because same physical structures can be subjected to different contexts to achieve different biological goals; for example, same proteins under different set of contexts may be involved in different biological processes, so that the goals of these processes (each different) are achieved (Gopalacharyulu et al. 2006). The present work attempts to formulate general and formal principles of contextual interactions, by modeling the nature of dependencies between biological contexts that operate upon physical (structural) parameters to ensure that biological goals are achieved.

Since the motivation of any biological process is solely to accomplish a set of necessary biological goals, and the structure of biological goals is hierarchic (Troyanskaya et al. 2003, Camon et al. 2004); we propose a hierarchic organizational structure for biological contexts too. Thus, structure of C will assume that of a tree (namely, the 'Context-Tree' (CT)), where the root-vertex will denote the biological context necessary to achieve the global goal of the system under consideration. The lowest level of CT will be occupied by basic, elementary contexts (- for example, the genes. A systematic combination of the molecular function of their products (proteins) is studied with respect to achieving a specific biological goal (Camon et al. 2004)), and their set $A = \{a_1, a_2, \ldots, a_n\}$ will constitute the leaves of CT. This form of hierarchic structure for CT , helps in analyzing the measure of performance of any component of the physical structure of the system under specific context to achieve any particular F, in the form $\sum_i \frac{\partial F}{\partial a_i} = \sum_i \frac{\partial F}{\partial C_i} \cdot \frac{\partial C_i}{\partial a_i}$. In this manner, every context, including the global context, may be described as a function of composition of basic contextual elements of CT . However, to accomplish a definite set of biological goal, the contexts describing various facets of a biological system need to interact between themselves. We define a set of rules $U(U = {\alpha_1, \alpha_2, \ldots, \alpha_n}$ that governs these interactions. Taken in entirety, they form the framework for composition between the base elements of CT, denoted by α . We note here that set U might be infinite, and the compositions $a_i\alpha a_j$ with $\alpha \in U$ need not necessarily be defined for all $a_i, a_j \in A$ (that is, some of these context interactions might well be mere theoretical possibilities, unrealized in biological paradigm).

Importance of set U is paramount; it is this set of rules that governs how the various elements of CT will interact to ensure the necessary dependencies between contexts, which in turn will (ultimately) ensure that the system achieves the desired goal F. Let us assign to each element α of the set U, an $n \times n$ incidence matrix (Skiena 1990). A^{α} with entries a_{ij}^{α} is unity if the composition $a_i\alpha a_j$ is defined, or zero otherwise. We can then introduce a matrix A^U whose elements are given by :

$$
a_{ij} = \bigvee_{\alpha \in U} a_{ij}^{\alpha} \tag{1}
$$

stating that $a_{ij} = 1$ if there exists a valid composition rule between a_i and a_j , taken in order.

Matrix A^U conforms to constraints of biological reality perfectly because it suggests that for certain magnitudes of i, the ith row and ith column of the matrix A^U can be all zeros. These cases describe algorithmically the fact that interactions between certain basic elements of context-set $A = \{a_1, a_2, \ldots, a_n\}$ are not allowable biologically. We demonstrate such non-allowable biological contexts with two examples :

Example-1) When λ phage (a virus that infects the bacteria *Escherichia coli*) encounters a bacterium, it attaches itself only to certain particular receptors with specific structural features, on the bacterial membrane. That is, the relevant biological contexts ensure that binding of λ phage to various other candidate receptor sites with slightly varying structural aspects, is not allowed. Subsequently, when the virus genome enters the bacterium, only two pathways (out of theoretically infinite number of pathways) of alternative nature, namely the 'lytic pathway' or the 'lysogenic pathway' are allowed biologically (Yartseva et al. 2007); although a theoretical thermodynamic study of the situation can suggest many possible pathways with (almost) similar efficiencies. This entire process, in the context-space description can be modeled with non-zero entries for the aforementioned two pathways, while the rest of the entries in A^U will be assigned zero to represent the fact that U specifies the contexts that ultimately ensures certain biological goals.

Example-2) Out of the entire spectrum of possible mRNAs that can be generated from a single gene, only one or a few are created at a time; nature of A^U ensures that other possibilities do not come to being, although these theoretically possible elements of context-set A would have operated upon the same structural parameters that constituteP. This act of ensuring the interplay between set of allowable contexts to achieve any particular goal, form the so-called 'regulatory mechanism' that includes an extremely sensitive balance between concentration magnitudes of pertinent entities, the destination, sequence variety, structural diversity and finally the functional options of the resulting protein related to the type of tissue or the stage of development, etc.. (Boeckmann et al. 2005).

Henceforth, we remove corresponding rules to describe the biological impossibilities in U , making it sure thereby that these compositions do not participate in the construction of the tree CT . Removing these aforementioned entries, from the set A we obtain a non-redundant set of basic rules of context composition. From here onwards, we will denote this non-redundant set as set A.

Model :

Section-1) : Modeling biological context-dependence from bottom-up perspective

We can now attempt to describe the biological process of transportation, as an example. We assume three elements $\{a_1, a_2, a_3\}$ from the set of basic contexts A. We denote a_1 as the context for loading, a_2 for delivery and a³ for unloading. To provide an example, we consider the case when axon of a neuron transports the transmission of action potentials from the cell body to the synapse. The complicated mechanism of action potential propagation and their active transportation from their site of synthesis in the cell body through the axoplasm to intracellular target sites in the axon and synapse, - provides an ideal case to demonstrate the various context-specific activities. Here the loading and delivery contexts $(a_1 \text{ and } a_2 \text{ respectively})$ involves the series synchronized couplings between allowed set of specific membranous organelles, synaptic vesicle precursors, signaling molecules, growth factors, protein complexes, cytoskeletal components, sodium and potassium channels and many other biological components. On the other hand, the unloading context (a_3) describes the neurotrophic signals that are transported back from the synapse to the cell body, keeping an account of efficiency and reliability of loading and delivery operations (Duncan and Goldstein 2006). Here we introduce the set of compositional rules U . U may then operate upon these three basic elements to ensure a sequential execution of elementary processes to ensure that final goal (F) is achieved. In this case the matrix A^U can be written as :

$$
\begin{array}{cccc}\n a_1 & a_2 & a_3 \\
 a_1 & 0 & 0 & 0 \\
 a_2 & 1 & 0 & 0 \\
 a_3 & 0 & 1 & 0\n\end{array} \tag{2}
$$

Hence the elementary biological context, α , is defined for only two cases from the entire spectrum of possible contextual interactions; they are $a_2\alpha a_1$ (implying the existence of a pipeline where context for delivery comes into action after the context for loading is ensured) and $a_3\alpha a_2$ (implying the existence of context for unloading after the operation of context for delivery is performed). It is interesting to note that a pipeline with $a_3\alpha a_1$ is not biologically relevant, since it implies the existence of context for unloading after the context for loading without any delivery action. Similarly contextual relations like $a_1 \alpha a_1$ (loading certain contexts repeatedly without a purpose), $a_1 \alpha a_2$ (existence of the context to ensure delivery when the initiation of the process is not ensured), $a_2\alpha a_3$ (context to ensure unloading when the delivery process is incomplete) and other spurious context-relations like $a_2\alpha a_2$, $a_3\alpha a_3$ are assigned a magnitude zero because they are biological impertinent. On a global scale, the composition $a_3\alpha a_2\alpha a_1$ captures the purposeful nature of biological goals.

The findings of the last paragraph implies that interactions between biological contexts, are transitive but are not commutative (since $a_3\alpha a_2$ and $a_2\alpha a_1$ are defined, $a_3\alpha a_2\alpha a_1$ can be defined; but merely because

 $a_3\alpha a_2$ exists doesn't imply that $a_2\alpha a_3$ exists too). The non-commutative nature of biological contexts can be understood better from the general treatment of the problem elaborated later.

The (bottom-up) paradigm of description of interplay of biological contexts can be generalized by describing the entire biological universe with the Thread-Mesh (TM) model (Banerji 2009). The TM model segments the biological space-time into a series of different biological organizations, viz. the nucleotides; amino acids; macromolecules (proteins, sugar polymers, glycoproteins); biochemical pathways; network of pathways; biological cell; tissue; organs; organisms; society and ecosystem; where these organizational schemes are called threshold levels. Emergence of a single biological property (compositional and/or structural and/or functional) creates a new biological threshold level in the TM model. Thus, if any arbitrarily chosen ith biological threshold level is denoted as TH_i , the succeeding one, viz. TH_{i+1} will be containing at least one biological property that THⁱ didn't possess. Schemes with similar philosophy to identify biological threshold levels were proposed previously (Testa and Kier 2000, Dhar 2007), but representation of emergence of any biological property and subsequent classification of biological organization with respect to this emergent behavior, was not done in either of these models. The basic principles for subsequent discourse are general and can be applied to any threshold level. Every possible property that a threshold level is endowed with, is represented by a 'thread' in the TM model. Thus an environmental property capable of influencing biological action will be called as an 'environmental thread' in the present parlance. Threads can be compositional, structural or functional. For example, for the biological threshold level corresponding to the enzymes (threshold level representing the macromolecules), one of the compositional threads is the amino acid sequence; whereas the radius of gyration, the resultant backbone dipole moment and each of the bond lengths, bond angles, torsion angles are some examples of structural threads and the values for K_m , V_{max} , K_{cat} are some examples of it's functional threads. It is advantageous to work with the TM model because it can attempt describing context-dependence and emergence from the framework of an invariant template.

Section-2) : Modeling biological context-dependence from top-down perspective

While framework of $eq^n s$ [1 – 5] along with examples 1 and 2 describe the nature of multilevel organization of CT, such description is 'bottom-up' in nature. Hence, while it is helpful to describe the context-mapping between any two particular adjacent biological threshold levels $'l'$ and $'l + 1'$, (say between threshold levels representing nucleotides and amino acids, amino acids and proteins, or between proteins and biochemical pathways, etc ..) the general mode of dependency within CT with a birds-eye ('top-down') view of the organization of it, can hardly be guessed from such bottom-up approach.

We start the construction of the top-down scheme of description of dependencies between biological contexts, by enlisting the assumptions involved therein. Hence :

Assumption-1) : In absence of random external disturbances and without a failure of any component belonging to physical structure of the system (P) all the rules of multilevel interactions between the contexts representing any biological threshold level, can be constructed and described in deterministic manner. (Success of recent attempts with deterministic modeling of various biological phenomena from diverse backgrounds (Janda and Gegina 2008, Kim and Maly 2009, Ferreira and Azevedo 2007) suggest that such assumption is not ill-founded, and that too in absence of possible perturbations.)

Assumption-2) : The necessary and sufficient condition in order these deterministic rules of inter-level context interactions hold true, is in their accounting for the accomplishment of certain biological goals (F) . (Previous studies (Yartseva et al. 2007, Troyanskaya et al. 2003, Camon et al. 2004) vindicate such assumption.)

Assumption-3) : Although biological systems will be exposed to randomly varying magnitudes of external parameters, the essence of the deterministic criteria of context interactions in order to accomplish any set of required biological function, will not be perturbed by significant margin. This assumption implies that deterministic manner of context interactions will not be undergoing significant change when the magnitudes of components of underlying physical structures $\{p_i\}$ ($p_i \in P$), comprised of relevant biological parameters, are altered within some allowable range. We describe this allowable range of assumed magnitude of some arbitrarily chosen parameter π by an interval $[\pi_0, \pi_1]$.

Relevance of the last assumption is easily understood when one analyzes the nature of some previous results in depth. Since every biological property operates within a specified bound of magnitude, something that has been referred to as 'fluctuation' in an earlier study (Testa and Kier 2000) the functions that represent them will also be bounded in their ranges. Examples for such fluctuation are many; in the biological threshold level representing cells, for the mitogen-activated protein kinase cascade studies, the total concentrations of MKKK, MKK and MAPK have been found to be in the range $10-1000$ nm and the estimates for the K_{cat} values of the protein kinases and phosphatases have been found to range from 0.01 to 1 s⁻¹(Kholodenko 2000). Similarly, for the proteins, the mass fractal dimension and hydrophobicity fractal dimension representing compactness of mass and hydrophobicity distribution, have been found to be in the range between 2.18 to 2.37 and 2.22 to 2.43 respectively (Banerji and Ghosh 2009).

Based on these assumptions, we propose the functional that defines the probability of attaining the biological goal (F) under consideration, to assume the form :

$$
F_0 = \int_{x_i \in S} \phi(x_1, x_2, \dots, x_n) \, dx_i \qquad (1 \le i \le n)
$$
\n(3)

where ϕ is the probability density of attaining the objective (biological goal) and X is the feasibility domain of the contexts x_i .

Since to achieve every biological goal, many (say, m) successive stages of context interactions are required, we can express $eqⁿ - 6$ at a higher resolution as :

$$
\phi(x_1, x_2, \dots, x_n) = \prod_{j=1}^m \phi_j |\phi_{j-1}(x_1, x_2, \dots, x_n)
$$
\n(4)

where $\phi_j | \phi_{j-1}$ represent the conditional probability associated with context $\{x_i\}$ interactions, while attempting to achieve a particular biological goal.

However, we note that individual physical parameters p_i ($p_i \in P$), upon which the contexts are working, may not always be strongly correlated and although related with each other, can be considered independent when viewed individually with respect to their functional contribution to the system. For example, the time-dependent and context-dependent fluctuations in individual bond lengths, bond angles and torsion angles in the protein interior, although might be related in some intricate way to the resultant dipole moment for the protein; can be considered, for all practical purposes, in terms of their individual (and not linked) contributions in ensuring proteins stability and functionality. Hence we attempt to partition the relevant contexts into a sum of disjoint domains; such that : $(x_i \in X_i)$ and $\sum_i X_i = S$.

Considering this partition we can re-write $eqⁿ - 6$ as :

$$
F_0 = \int_{x_1 \in X_1} \int_{x_2 \in X_2} \int_{x_n \in X_n} \phi_1(x_1, x_2, \dots, x_n) \times \phi_{2|1}(x_1, x_2, \dots, x_n) \dots \phi_{m|m-1}(x_1, x_2, \dots, x_n) dx_1 dx_2 \dots dx_m \tag{5}
$$

In other words, purely in terms of achievement of biological goals :

$$
F_0 = F_1 F_{2|1} \dots F_{m|m-1} \tag{6}
$$

where

$$
F_{j|j-1} = \int_{x_1 \in X_1} \int_{x_2 \in X_2} \dots \int_{x_n \in X_n} \phi_{j|j-1} (x_1, x_2, \dots, x_n) dx_1 dx_2 \dots dx_n \tag{7}
$$

are the conditional probabilities of context-interactions of the system realizing the successive stages of the task. It is necessary to mention here that to achieve any biological function, the domain of integration for every x_i in $eq^n - 8$ must be within their respective permissible range, say $[x_{\pi_0}, x_{\pi_1}].$

While it is difficult to assume that every context-interaction necessary to realize certain biological goal will always be operating in deterministic manner with perfect efficiency, experience teaches us that biological goals are seldom compromised with. Hence we assume that the reliability of any arbitrarily chosen context interaction at any arbitrarily chosen jth state in the realization of certain biological function, is statistically independent of the probability of the realization of that particular biological function. In that case, the integrand in $eq^{n} - 10$, can be expressed as a product $\phi_{j|j-1}(x_1, x_2, \ldots, x_n) r_j(x_1, x_2, \ldots, x_n)$, where $r_j, (r_j \in R)$ describes the probability of reliability of any arbitrarily chosen context-interaction at jth state in the realization of certain biological function.

Hence $eq^{n} - 7$, can be expressed more realistically as :

$$
\phi(x_1, x_2, \dots, x_n) = \prod_{j=1}^m \phi_{j|j-1}(x_1, x_2, \dots, x_n) r_j(x_1, x_2, \dots, x_n)
$$
\n(8)

Thus, when the reliability of context-interactions are taken into account, assuming that $eq^{n} - 8$ and $eq^{n} - 10$ are valid, $eq^{n} - 6$ and $eq^{n} - 7$ can be re-written as :

$$
F_0 = \prod_{j=1}^{m} F_j |F_{j-1} R_j \tag{9}
$$

where

$$
R_j = \int_{x_1 \in X_1} \int_{x_2 \in X_2} \cdots \int_{x_n \in X_n} r_j(x_1, x_2, \dots, x_n) dx_1 dx_2 \dots dx_n
$$
 (10)

In other words, $eq^{n} - 12$, can be re-written as :

$$
F_0 = F_1 F_{2|1} \dots F_{n|n-1} R_1 R_2 \dots R_m \tag{11}
$$

Result :

(Bottom-Up) Modeling hierarchical organization with 'context tree':

Case-study with protein structure :

To describe the 'Context-Tree'(CT) in such hierarchic paradigm under a generalized scheme we introduce a construct C, which is a family of embedded partitions of contexts $C = \langle C^1, C^2, \ldots, C^r \rangle$ that operate upon any relevant subset of structural threads (J) representing the physical structure (P) of any arbitrarily chosen threshold level S. $J \subset P$ and $J = \{1, 2, ..., m\}$. For example, it has been found (Main et al. 1998) that at the threshold level of proteins; $(S : \mathbf{TH}_{\text{Proteins}})$ in an urea-induced media (the 'environmental thread' influencing J), the extent of stability of mutant proteins are highly dependent on the contexts (C) which operate upon the various structural parameters (J) , that form a subset of (P) describing (S) .

We can describe the situation as :

$$
C^{S} = \langle C_{1}^{S}, C_{2}^{S}, \dots, C_{l}^{S} \rangle \qquad \cup_{j=1}^{l} C_{j}^{S} = J, \quad C_{i}^{S} \cap C_{j}^{S} = \emptyset \quad (i \neq j), \quad S = \overline{1, r}
$$
 (12)

The embedding refers to any element of the partition of the S^{th} biological threshold level; i.e., the set C_j^s represents the union of several sets $C_{i_1}^{S-1}, C_{i_2}^{S-1}, \ldots, C_{i_z}^{S-1}$ of the $(S-1)^{th}$ biological threshold level. Such description of CT) conforms to a previous study on similar topic (Andrianantoandro et al. 2006). Findings

from a recent study (Haseltine and Arnold 2007) vindicates $C_i^S \cap C_j^S = \emptyset$. To elaborate the hierarchic structure, we can write $C \longleftrightarrow < C_1^{S-1}, C_2^{S-1}, \dots, C_l^{S-1} >$, if $C^S = \cup_{i=1}^l C_i^{S-1}$. Since the entire set of interactions between various contexts is ultimately geared to satisfy biological goals and since the nature of organization of biological goals is hierarchic, we attempt to describe it by defining $l(C^S) = l$ and $C^{root} = \{1, 2, ..., m\} >$; i.e., the partition at the highest (root) level consists of one set, namely J.

We can associate each element C_j^S $(s = \overline{2, r})$ of the partition to the context-interaction function, namely $f_j^S\left(\alpha_1,\alpha_2,\ldots,\alpha_{l\left(C_j^S\right)}\right)$, where $\alpha\in\{0,-1,+1\},$ conforming to the previously defined $U\left(U=\{\alpha_1,\alpha_2,\ldots,\alpha_n\}\right)$. We associate each element C_j^1 of the first level to a binary relation R_j (the previously defined elementary contexts are related by this, say aRb, where $A = \{a, b, \ldots, z\}$ on the biological sub-space EC_j^1 .

These concepts can formally be described as :

Let $C_j^2 \longleftrightarrow < C_1^1, \ldots, C_l^1 >$ and define a relation R_j^2 on $E_{C_j^2}$ using the formula (for $l > 1$):

$$
a_{C_j^2} R_{bC_j^2}^2 \Longleftrightarrow f_j^2(\alpha_1, \alpha_2, \dots, \alpha_l) = 1
$$
\n(13)

$$
\begin{array}{rcl}\n\alpha_i & = & +1 & if \ a_{C_i^1} R_i b_{C_i^1} \\
\alpha_i & = & -1 & if \ a_{C_i^1} \overline{R} b_{C_i^1} \\
\alpha_i & = & 0 & if \ a_{C_i^1} = b_{C_i^1}\n\end{array}
$$

In case of $l = 1, R_j^2 = R_j$. If all the relations R^{S-1} of the $(S-1)^{th}$ biological threshold level are defined, then the relations R_j^S of the S^{th} threshold level with $(l > 1)$ can be defined by the following construct:

If
$$
C_j^S \longleftrightarrow C_1^{S-1}, C_2^{S-1}, \dots, C_l^{S-1}, >
$$
, then
\n
$$
a_{C_j^S} R_{bC_j^S}^S \Longleftrightarrow f_j^S (\alpha_1, \alpha_2, \dots, \alpha_l) = 1
$$
\n
$$
\alpha_i = +1 \quad if \ a_{C_i^{S-1}} R_i^{S-1} b_{C_i^{S-1}}
$$
\n(14)

$$
\begin{array}{rcl}\n\alpha_i & = & -1 & \text{if } a_{C_i^{S-1}} \overline{R^{S-1}} b_{C_i^{S-1}} \\
\alpha_i & = & 0 & \text{if } a_{C_i^{S-1}} = b_{C_i^{S-1}}\n\end{array}
$$

If $C^{S} = C^{S-1}$, then $R^{S} = R^{S-1}$; in other words the construction requires the relation R to coincide with R^r , which is a single relation at the r^{th} upper level.

To describe the entire bottom-up paradigm of description of interaction scheme between biological contexts, we consider an example where we describe the contextual constraints on the active site of an enzyme in simplistic terms. For this case, without any loss of generality, we consider the threshold level representing proteins to be the root level in this case. The goal of the system (F) for the present purpose is to make the enzyme functional. We assume the elementary contexts that can influence functionality of the enzyme active site to be represented with 3 basic partitions; namely, first, the contextual differences originating out of internal coordinates; second, contextual differences arising out of interaction profile of the active site atoms with water; and third, contextual differences arising out of the capability of the active site to undergo a shape change. Hence we describe the family of partitions C, as $C^1 = \{1, 2, 3\}$, $\{4, 5\}$, $\{6\} >$ and $C^2 = \{J >$; where element 1 denotes (possible) contextual difference arising out of the fluctuation of bond lengths, element 2 denotes (possible) contextual difference arising out of the fluctuation of bond angles, element 3

denotes (possible) contextual difference arising out of the fluctuation of torsion angles. Similarly, element 4 stands for (possible) contextual difference arising out of the hydrophobicity of active site patch, element 5 denotes the (possible) contextual difference arising out of the local electrostatic profile of the active site patch. Element 6 denotes the extent of (possible) contextual difference arising out of the change in the local shape of the active site patch. Denoting the set $\{1, 2, 3\}$ as D_1^2 , $\{4, 5\}$ as D_2^2 and $\{6\}$ as D_3^2 , the hierarchic nature of these contextual dependencies can easily be described as :

 $D_2RD_1 \Longleftrightarrow [D_2 \geq D_1]$ similarly, $D_3RD_2 \leftrightarrow [D_3 \ge D_2]$ and $D_3RD_1 \leftrightarrow [D_3 \ge D_1]$

Implying that a (possible) contextual difference arising out of the hydrophobicity of active site patch, or a (possible) contextual difference due to the local electrostatic profile of the active site patch will surely account for some change in the distribution profile of bond length, bond angle and torsion angle distribution. But inverse of this case, viz., a (secondary) change in the local electrostatics profile and local hydrophobic profile due to a (primary) change in bond-length, bond-angle or torsion angle might or might not be observed in reality. Similarly, in case of a possible change in local shape the local electrostatic profile, local hydrophobicity profile, local distribution of bond length, bond angle, torsion angle will surely be taking place; but the other way round might or might not be observed. This vindicates and generalizes our previous finding that interactions between biological contexts, are transitive but are not commutative (hence, if D_2RD_1 and D_3RD_2 are defined, $D_3RD_2RD_1$ can be defined; but merely because D_3RD_2 exists doesn't imply that D_2RD_3 exists too).

Conclusion :

While $eq^{n} - 1$ to $eq^{n} - 5$ constructed the bottom-up scheme of describing the interactions and dependencies between biological contexts, the framework of equations $eq^{n} - 6$ to $eq^{n} - 14$ describe the top-down view of the same. Together these set of equations present a comprehensive way to quantitatively model the omnipresent "context-dependence" in biology. Evidences for the reliability of such mathematical treatise can easily be obtained from the various experimentally proved results that are provided to emphasize the reasonable nature of these formulations. Since contemporary biology, as never before, is attempting to be objective in its philosophy, the necessity of a mathematical model to describe the "context-dependent" nature of it can hardly be ignored. The model proposed here, therefore, assumes immense importance.

Acknowledgment: This work was supported by COE-DBT (Department of Biotechnology, Government of India) scholarship.

References :

Andrianantoandro E, Basu S, Karig D, Weiss R (2006) Synthetic biology: new engineering rules for an emerging discipline. Mol. Syst. Biol. 2:0028.

Banerji A, Ghosh I (2009) Revisiting the Myths of Protein Interior: Studying Proteins with Mass-Fractal Hydrophobicity-Fractal and Polarizability-Fractal Dimensions. PLoS One 4(10), e7361. doi:10.1371/journal.pone.0007361.

Banerji A (2009) Existence of biological uncertainty principle implies that we can never find 'THE' measure for biological complexity. arXiv:0902.0490v2.[q-bio.OT]

Banerji A, Ghosh I (2011) Mathematical criteria to observe mesoscopic emergence of protein biochemical properties. J. Math. Chem. 49(3):643-665.

Boeckmann B, Blatter M, Famiglietti L, Hinz U, Lane L, Roechert B, Bairoch A (2005) Protein variety and functional diversity: Swiss-Prot annotation in its biological context. C. R. Biologies 328,882-899.

Brown M, Schmid-Hempel R, Schmid-Hempel P (2003) Strong context-dependent virulence in a host-parasite system: reconciling genetic evidence with theory. J. Anim. Ecol., 72(6):994-1002.

Camon E, Magrane M, Barrell D, Lee V, Dimmer E, Maslen J, Binns D, Harte N, Lopez R, Apweiler R (2004) The gene ontology annotation (goa) database: sharing knowledge in uniprot with gene ontology. Nucl. Acids Res. 32:D262-D266.

Dhar P (2007) The next step in biology: A periodic table? J. Biosci. 32:1005–1008.

Doboli S, Minai A, Best P (2000) Latent attractors: a model for context-dependence place representations

in the hippocampus, Neural Comput. 12(5): 1009-1043.

Duncan J, Goldstein L (2006) The Genetics of Axonal Transport and Axonal Transport Disorders; PLoS Genet. 2(9): e124.

Edmonds B (1999) Syntactic measures of complexity. Ph.D. thesis,University of Manchester.

http://www.cpm.mmu.ac.uk/~bruce/thesis

Ferreira P, Azevedo P (2007) Evaluating deterministic motif significance measures in protein databases; Algorithms for Mol. Biol., 2:16.

Gopalacharyulu P, Lindfors E, Bounsaythip C, Oresic M (2006) Context dependent visualization of protein function, In: Rousu J, Kaski S, Ukkonen E (eds) Proc. Probabilistic Modelling and Machine Learning in Structural and Systems Biology Workshop, pp 26-31.

Hagan I, Sharrocks A (2002) Understanding cancer: from the gene to the organism. Conference on genes and cancer. EMBO Rep. 3(5):415–419.

Haseltine E, Arnold F (2007) Synthetic Gene Circuits: Design with Directed Evolution. Ann. Rev. Biophys. Biomol. Struct. 36:1-19.

Hoare D, Couzin I, Godin J, Krause J (2004) Context-dependent group size choice in fish. Anim. Behav. 67:155-164.

Jablonski P, Lee S, Jerzak L (2006) Innate plasticity of a predatory behavior: nonlearned context dependence of avian flush-displays. Behav. Ecol. 17(6): 925-932.

Janda J, Gegina G (2008) A deterministic model for the processing and presentation of bacteria-derived antigenic peptides. J. Th. Biol. 250(3): 532-546.

Kholodenko B (2000) Negative feedback and ultrasensitivity can bring about oscillations in the mitogenactivated protein kinase cascades. Eur. J. Biochem. 267(6):1583–1588.

Kim M, Maly I (2009) Deterministic mechanical model of T-killer cell polarization reproduces the wandering of aim between simultaneously engaged targets. PLoS Comp .Biol. 5(1):1-12.

Loewe L (2009) A framework for evolutionary systems biology, BMC Sys. Biol. 3:27.

Main E, Fulton K, Jackson S (1998) Context-Dependent Nature of Destabilizing Mutations on the Stability of FKBP12. Biochemistry. 37(17):6145–6153.

Marguet P, Balagadde F, Tan C, You L (2007) Biology by design: reduction and synthesis of cellular components and behaviour. J. R. Soc. Interface, 4:607-623.

Nobeli I, Favia A, Thornton J (2009) Protein promiscuity and its implications for biotechnology. Nature biotechnology; 27(2):157-167.

Platzer U, Meinzer H (2002) Simulation of genetic networks in multicellular context.

In: Polani D, Kim J, Martinez T (eds) 5th German workshop on artificial life: abstracting and synthesizing the principles of living systems, Berlin, Germany: Akad. Verl.-Ges, pp. 43-51.

Siepel A, Haussler D (2004) Phylogenetic Estimation of Context-Dependent Substitution Rates by Maximum Likelihood. Mol. Biol. Evol. 21(3):468-488.

Skiena S (1990) Implementing Discrete Mathematics: Combinatorics and Graph Theory with Mathematica. Reading, MA: Addison-Wesley, pp. 135-136.

Standish R (2001) On Complexity and Emergence, arXiv:nlin/0101006v1 [nlin.AO].

Testa B, Kier L (2000) Emergence and Dissolvence in the Self-organisation of Complex Systems. Entropy 2:1-25.

Torney C, Neufeld Z, Couzin I (2009) Context-dependent interaction leads to emergent search behavior in social aggregates. Proc. Nat. Acad. Sc. USA, 106(52):22055-22060.

Troyanskaya O, Dolinski K, Owen A, Altman R, Botstein D (2003) A Bayesian framework for combining heterogeneous data sources for gene function prediction (in Saccharomyces cerevisiae). Proc. Nat. Acad. Sc. USA $100(14):8348 - 8353$.

Valiant L (2009) Evolvability. J. Assoc. Comp. Mach. 56,1, 56:1, 3:1-3:21.

Yartseva A, Klaudel H, Devillers R, Kepes F (2007) Incremental and unifying modelling formalism for biological interaction networks. BMC Bioinformatics 8: 433.

Yu C, Zavaljevski N, Desai V, Reifman J (2009) Genome-wide enzyme annotation with precision control: catalytic families (CatFam) databases. Proteins. 74:449-460.

Zhang W, Bouffard G, Wallace S, Bond J (2007) Estimation of DNA Sequence Context-dependent Mutation Rates Using Primate Genomic Sequences. J. Mol. Evol. 65:207-214.