

PARALLEL DNA IMPLEMENTATION OF FAST MATRIX MULTIPLICATION TECHNIQUES BASED ON AN n -MODULI SET

ARAN NAYEBI

ABSTRACT. On distributed memory computers, the implementation and association of fast parallel matrix multiplication algorithms has yielded astounding results and insights. In this discourse, we use the tools of molecular biology to demonstrate the feasibility of performing Strassen's fast matrix multiplication algorithm with DNA based on an n -moduli set in the residue number system, thereby demonstrating the viability of computational mathematics with DNA. As a result, a general scalable implementation of this model in the DNA computing paradigm is presented and can be generalized to the application of *all* fast matrix multiplication algorithms on a DNA computer. Fast methods of matrix computations with DNA are important because they also allow for the efficient implementation of other algorithms (i.e. inversion, computing determinants, and graph theory) on a DNA computer.

1. INTRODUCTION

The multiplication of matrices is a fundamental operation applicable to a diverse range of algorithms from computing determinants, inverting matrices, and solving linear systems to graph theory. Indeed, Bunch and Hopcroft [Bunch et al. (1974)] successfully proved that given an algorithm for multiplying two $n \times n$ matrices in $O(n^\alpha)$ operations where $2 < \alpha \leq 3$, then the triangular factorization of a permutation of any $n \times n$ nonsingular matrix as well as its inverse can be found in $O(n^\alpha)$ operations. The standard method of square matrix multiplication requires $2n^3$ operations. Let ω be the smallest number such that $O(n^{\omega+\epsilon})$ multiplications suffice for all $\epsilon > 0$. Strassen [Strassen (1969)] presented a divide-and-conquer algorithm using noncommutative multiplication to compute the product of two matrices (of order m^{2^k}) by $m^{3 \cdot 7^k}$ multiplications and $(5 + m)m^{2 \cdot 7^k} - 6m^2 2^{2^k}$ additions. Thus, by recursive application of Strassen's algorithm, the product of two matrices can be computed by at most $(4.7)n^{\log_2 7}$ operations. Following Strassen's work, Coppersmith and Winograd [Coppersmith et al. (1990)] were able to improve the exponent to 2.38. Their approaches and those of subsequent researchers rely on the same framework: For some k , they devise a method to multiply matrices of order k with $m \lll k^3$ multiplications and recursively apply this technique to show that $\omega < \log_k m$. Only until recently, it was long supposed that ω could take on the value of 2 without much evidence. Using a group-theoretic construction, Cohn, Kleinberg, Szegedy, and Umans [Cohn et al. (2005)] rederived the Coppersmith-Winograd algorithm to describe several families of wreath product groups that yield nontrivial upper bounds on ω , the best asymptotic result being 2.41. They also presented two conjectures in which either one would imply an exponent of 2.

Unfortunately, although these improvements to Strassen's algorithm are theoretically optimal, they lack pragmatic value. In practice, only the Strassen algorithm is fully implemented and utilized as such:

For even integers m , n , and k , let $X \in \mathbb{R}^{m \times k}$ and $Y \in \mathbb{R}^{k \times n}$ be matrices with product $Q \in \mathbb{R}^{m \times n}$, and set

$$X = \begin{pmatrix} X_{00} & X_{01} \\ X_{10} & X_{11} \end{pmatrix}, \quad Y = \begin{pmatrix} Y_{00} & Y_{01} \\ Y_{10} & Y_{11} \end{pmatrix}, \quad Q = \begin{pmatrix} Q_{00} & Q_{01} \\ Q_{10} & Q_{11} \end{pmatrix},$$

where $X_{ij} \in \mathbb{R}^{m/2 \times k/2}$, $Y_{ij} \in \mathbb{R}^{k/2 \times n/2}$, and $Q_{ij} \in \mathbb{R}^{m/2 \times n/2}$. Then perform the following to compute $Q = XY$,

$$M_0 := (X_{00} + X_{11})(Y_{00} + Y_{11}),$$

Date: October 28, 2009.

2000 Mathematics Subject Classification. Primary 65F05, 03D10; Secondary 68Q10, 68Q05, 03D80.

Key words and phrases. DNA computing; residue number system; logic and arithmetic operations; Strassen algorithm.

$$\begin{aligned}
M_1 &:= (X_{10} + X_{11})Y_{00}, \\
M_2 &:= X_{00}(Y_{01} - Y_{11}), \\
M_3 &:= X_{11}(-Y_{00} + Y_{10}), \\
M_4 &:= (X_{00} + X_{01})Y_{11}, \\
M_5 &:= (-X_{00} + X_{10})(Y_{00} + Y_{01}), \\
M_6 &:= (X_{01} - X_{11})(Y_{10} + Y_{11}), \\
Q_{00} &= M_0 + M_3 - M_4 + M_6, \\
Q_{01} &= M_1 + M_3, \\
Q_{10} &= M_2 + M_4, \\
Q_{11} &= M_0 + M_2 - M_1 + M_5.
\end{aligned}$$

Even if the dimension of the matrices is not even or if the matrices are not square, it is easy to pad the matrices with zeros and perform the aforementioned algorithm.

Typically, computations such as this one are performed using electronic components on a silicon substrate. In fact, it is a commonly held notion that *most* computers should follow this model. In the last decade however, a newer and more revolutionary form of computing has come about, known as DNA computing. DNA's key advantage is that it can make computers much smaller than before, while at the same time maintaining the capacity to store prodigious amounts of data. Since Adleman's [Adleman (1994)] pioneering paper, DNA computing has become a rapidly evolving field with its primary focus on developing DNA algorithms for NP-complete problems. However, unlike quantum computing, the viability of computational mathematics on a DNA computer has not yet been fully demonstrated. In fact, only recently have the primitive operations in mathematics (i.e. addition, subtraction, multiplication, and division) been fully implemented and optimized. Thus, one of the goals in this paper is to show that computational mathematics is feasible with DNA. Fujiwara, Matsumoto, and Chen [Fujiwara et al. (2004)] proved a DNA representation of binary integers using single strands and presented procedures for primitive mathematical operations through simple manipulations in DNA. It is important to note that the work of Fujiwara et al. [Fujiwara et al. (2004)] and those of subsequent researchers have relied upon a fixed-base number system. The fixed-base number system is a bottleneck for many algorithms as it restricts the speed at which arithmetic operations can be performed and increases the complexity of the algorithm. In fact, parallel arithmetic operations are simply not feasible in the fixed-base number system because of the effect of a carry propagation. Recently, Zheng, Xu, and Li [Zheng et al. (2009)] have presented an improved DNA representation of an integer based on the residue number system (RNS) and give algorithms of arithmetic operations in $Z_M = \{0, 1, \dots, M - 1\}$ where Z_M is the ring of integers with respect to modulo M . Their results exploit the massive parallelism in DNA mainly because of the carry-free property of all arithmetic operations (except division, of course) in RNS.

In this paper we present a parallelization method for performing Strassen's fast matrix multiplication methods on a DNA computer, thereby demonstrating the practicality of this paradigm in the mathematics of computation. Divide-and-conquer algorithms particularly benefit from the parallelism of the DNA computing paradigm because distinct sub-processes can be executed on different processors. Our approach uses the Cannon algorithm at the bottom level (within a tube containing a memory strand) and the Strassen algorithm at the top level (between memory strands). We show that the Strassen-Cannon algorithm decreases in complexity as the recursion level r increases [Nguyen et al. (2005)]. If the Cannon algorithm is replaced by other parallel matrix multiplication algorithms at the bottom level (such as the Fox algorithm), our result still holds. The difficulty that arises is that in order to use the Strassen algorithm at the top level, we must determine the sub-matrices after the recursive execution of the Strassen formula r times and then to find the resultant matrix. On a sequential machine, this problem is trivial; however, on a parallel machine this situation becomes much more arduous. Nguyen, Lavallée, and Bui [Nguyen et al. (2005)] present a method for electronic computers to determine all the nodes at the unspecified level r in the execution tree of the Strassen algorithm, thereby allowing for the direct calculation of the resultant matrix from the sub-matrices calculated by parallel matrix multiplication algorithms at the bottom level. Thus, we show that this result can be obtained using DNA, and combined with a storage map of sub-matrices to DNA strands and

with the usage of the Cannon algorithm at the bottom level, we have a general scalable implementation of the Strassen algorithm on Adleman’s DNA computer. The reason why we concentrate on the Strassen algorithm is that it offers superior performance than the traditional algorithm for practical matrix sizes less than 10^{20} [Nguyen et al. (2005)]. However, our methods are also applicable to *all* fast matrix multiplication algorithms on a DNA computer, as these algorithms are always in recursive form [Pan (1984)]. In addition, our results can be used to implement other algorithms such as inversion and computing determinants on a DNA computer since matrix multiplication is almost ubiquitous in application.

2. PRELIMINARY THEORY

2.1. The Residue Number System. The residue number system is defined by a set of pairwise, coprime moduli $P = \{q_{n-1}, \dots, q_0\}$. Furthermore, an integer in RNS is represented as a vector of residues with respect to the moduli set P . As a consequence of the Chinese remainder theorem, for any integer $x \in [0, M - 1]$ where $M = \prod_{i=0}^{n-1} q_i$, each RNS representation is unique. As stated by Zheng, Xu, and Li [Zheng et al. (2009)], the vector (x_{n-1}, \dots, x_0) denotes the residue representation of x .

It has been previously mentioned that one of the important characteristic of RNS is that all arithmetic operations except for division are carry-free. Thus, for any two integers $x \rightarrow (x_{n-1}, \dots, x_0) \in Z_M$ and $y \rightarrow (y_{n-1}, \dots, y_0) \in Z_M$ we obtain the following from [Paun et al. (1998)]

$$(2.1.1) \quad |x \circ y|_M \rightarrow (|x_{n-1} \circ y_{n-1}|_{q_{n-1}}, \dots, |x_0 \circ y_0|_{q_0}),$$

in which \circ is any operation of addition, subtraction, or multiplication.

2.2. The Adleman-Lipton Model. In this section we present a theoretical and practical basis for our algorithms. By the Adleman-Lipton model, we define a test tube T as a multi-set of (oriented) DNA sequences over the nucleotide alphabet $\{A, G, C, T\}$. The following operations can be performed as follows:

- *Merge*(T_1, T_2): merge the contents in tube T_1 and tube T_2 , and store the results in tube T_1 ;
- *Copy*(T_1, T_2): make a copy of the contents in tube T_1 and store the result in tube T_2 ;
- *Detect*(T): for a given tube T , this operation returns “True” if tube T contains *at least* one DNA strand, else it returns “False”;
- *Separation*(T_1, X, T_2): from all the DNA strands in tube T_1 , take out only those containing the sequences of X over the alphabet $\{A, G, C, T\}$ and place them in tube T_2 ;
- *Selection*(T_1, l, T_2): remove all strands of length l from tube T_1 into tube T_2 ;
- *Cleavage*($T, \sigma_0\sigma_1$): given a tube T and a sequence $\sigma_0\sigma_1$, for every strand containing $\begin{bmatrix} \sigma_0\sigma_1 \\ \overline{\sigma_0\sigma_1} \end{bmatrix}$, then the cleavage operation can be performed as such:

$$\begin{bmatrix} \alpha_0\sigma_0\sigma_1\beta_0 \\ \alpha_1\overline{\sigma_0\sigma_1}\beta_1 \end{bmatrix} \xrightarrow{\text{Cleavage}(T, \sigma_0\sigma_1)} \begin{bmatrix} \alpha_0\sigma_0 \\ \alpha_1\overline{\sigma_0} \end{bmatrix}, \quad \begin{bmatrix} \sigma_1\beta_0 \\ \overline{\sigma_1}\beta_1 \end{bmatrix},$$

where the overhead bar denotes the complementary strand.

- *Annealing*(T): produce *all* feasible double strands in tube T and store the results in tube T (the assumption here is that ligation is executed after annealing);
- *Denaturation*(T): disassociate every double strand in tube T into two single strands and store the results in tube T ;
- *Empty*(T): empty tube T .

According to [Paun et al. (1998)], the complexity of each of the aforementioned operations is $O(1)$.

3. DNA MATRIX OPERATIONS IN RNS

3.1. DNA Representation of a Matrix in RNS. We extend the DNA representation of integers in RNS presented in [Zheng et al. (2009)] to representing an entire matrix Y in RNS by way of single DNA strands.

Let matrix Y be a $t \times t$ matrix with:

$$Y = \begin{pmatrix} y_{11} & y_{12} & \cdots & y_{1t} \\ y_{21} & y_{22} & \cdots & y_{2t} \\ \vdots & \vdots & \ddots & \vdots \\ y_{t1} & y_{t2} & \cdots & y_{tt} \end{pmatrix}.$$

The key here is the RNS representation of each element y_{qr} in the hypothetical matrix Y with $1 \leq q \leq t$ and $1 \leq r \leq t$ by way of DNA strands.

We first utilize the improved DNA representation of n binary numbers with m binary bits as described in [Zheng et al. (2009)] for the alphabet Σ :

$$\Sigma = \{A_i, B_j, C_0, C_1, E_0, E_1, D_0, D_1, 1, 0, \# | 0 \leq i \leq M-1, 0 \leq j \leq m\}.$$

Here, A_i indicates the address of M integers in RNS; B_j denotes the binary bit position; C_0, C_1, E_0, E_1, D_0 , and D_1 are used in the *Cleavage* operation; $\#$ is used in the *Separation* operation; and 0 and 1 are binary numbers. Thus, in the residue digit position, the value of the bit y_{qr} with a bit address of i and a bit position of j can be represented by a single DNA strand $(S_{i,j})y_{qr}$:

$$(3.1.1) \quad (S_{i,j})_{qr} = (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0) y_{qr},$$

for $V \in \{0, 1\}$. Hence, the matrix Y can be represented as such:

$$Y = \begin{pmatrix} (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{11}} & (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{12}} & \cdots & (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{1t}} \\ (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{21}} & (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{22}} & \cdots & (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{2t}} \\ \vdots & \vdots & \ddots & \vdots \\ (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{t1}} & (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{t2}} & \cdots & (D_1 B_j E_0 E_1 A_i C_0 C_1 V D_0)_{y_{tt}} \end{pmatrix},$$

where each strand-element is not necessarily distinct. The reader must keep in mind that M integers in RNS defined by the n -moduli set P can be represented by $2M(m+1)$ different memory strands, whereas in the binary system, the representation of M integers requires $2M \left(1 + \sum_{i=0}^{n-1} m_i\right)$ different memory strands.

3.2. Binary Addition using DNA. In order to properly add matrices using DNA, we must devise a method of adding their individual elements together. Let $a = (a_{s-1}, \dots, a_0)$ and $b = (b_{s-1}, \dots, b_0)$ be binary numbers such that $a_{s-1} = b_{s-1} = 0$ and $a_j, b_j \in \{0, 1\}$ for $j = 0, \dots, s-2$ [Zheng et al. (2009)]. The process of addition proceeds as follows:

$$(3.2.1) \quad a + b = a \oplus b + \text{Leftshift}(a * b),$$

for the arithmetic operations \oplus and $*$ over $GF(2)$. We do not define the procedure *Leftshift* here (nor *ValueAssignment*, which will be used later), as it is explained in great depth by [Zheng et al. (2009)]. Note that subtraction is merely the two's complement of addition and that multiplication can be obtained through serial operations of addition according to

$$(3.2.2) \quad a \times b = \sum_{0 \leq j \leq s-1, b_j=1} a \times 2^j.$$

Thus, we show here only the procedure of addition.

We define the procedure *BinaryAdd* which takes in three tubes, namely, $(T_1)_a$ containing the memory strands for the binary number a , $(T_2)_b$ containing the memory strands for the binary number b , and $(T_{sum})_{a,b}$ to store the memory strands for the result of addition. From (3.2.1), we can construct auxiliary tubes as presented in [Fujiwara et al. (2004)] to realize the operations \oplus and $*$ over $GF(2)$,

$$T_j = \left\{ \overline{0\#D_0 S_{1,j}(0) S_{2,j}(0) D_1 0\#}, \overline{1\#D_0 S_{1,j}(0) S_{2,j}(1) D_1 0\#}, \overline{1\#D_0 S_{1,j}(1) S_{2,j}(0) D_1 0\#}, \overline{0\#D_0 S_{1,j}(1) S_{2,j}(1) D_1 1\#} \right\},$$

where $j = 0, \dots, s-1$. Now, let $T = \bigcup_{j=0}^{s-1} T_j$ and let T_3, T_4 , and T_{temp} be used as temporary tubes. We further use other auxiliary tubes as defined in [Zheng et al. (2009)]:

$$\begin{aligned} T_e &= \{0\#D_0, 1\#D_0, D_1 0\#, D_1 1\#\}, & T_{e,j}^1 &= \{\overline{0\#D_0 S_{1,j}(0)}, \overline{0\#D_0 S_{1,j}(1)}\}, \\ T_{e,j}^2 &= \{\overline{1\#D_0 S_{1,j}(1)}, \overline{1\#D_0 S_{1,j}(0)}\}, & T_{e,j}^3 &= \{\overline{S_{2,j}(0) D_1 0\#}, \overline{S_{2,j}(1) D_1 0\#}\}, \\ T_{e,j}^4 &= \{\overline{S_{2,j}(1) D_1 1\#}\}, \text{ where } j = 0, \dots, s-1, & T_e^1 &= \bigcup_{j=0}^{s-1} T_{e,j}^1, & T_e^2 &= \bigcup_{j=0}^{s-1} T_{e,j}^2, & T_e^3 &= \bigcup_{j=0}^{s-1} T_{e,j}^3, & T_e^4 &= \bigcup_{j=0}^{s-1} T_{e,j}^4. \end{aligned}$$

As a result, we proceed as follows [Zheng et al. (2009)]:

Algorithm 3.1: BINARYADD($(T_1)_a, (T_2)_b, (T_{sum})_{a,b}$)

```

Copy( $(T_2)_b, T_3$ );
Separation( $T_3, \{1\}, T_{temp}$ );
Empty( $T_3$ );
while Detect( $T_{temp}$ ) = True
do
    Empty( $T_{temp}$ );
    Merge( $(T_1)_a, (T_2)_b$ );
     $\{\Rightarrow (T_1)_a = \{S_{1,j}, S_{2,j} | 0 \leq j \leq s-1\}$ 
    Empty( $(T_2)_b$ );
    Merge( $(T_1)_a, T$ );
    Annealing( $(T_1)_a$ );
     $\{\Rightarrow (T_1)_a = \left\{ \left[ \frac{S_{1,j}S_{2,j}}{\alpha\#D_0S_{1,j}S_{2,j}D_1\beta\#} \right], \overline{\alpha\#D_0S_{1,j}S_{2,j}D_1\beta\#} | 0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\} \right\}$ 
    Cleavage( $(T_1)_a, D_0D_1$ );
     $\{\Rightarrow (T_1)_a = \left\{ \left[ \frac{S_{1,j}}{\alpha\#D_0S_{1,j}} \right], \left[ \frac{S_{2,j}}{S_{2,j}D_1\beta\#} \right], \overline{\alpha\#D_0S_{1,j}S_{2,j}D_1\beta\#} | 0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\} \right\}$ 
    Merge( $(T_1)_a, T_e$ );
    Annealing( $(T_1)_a$ );
     $\{\Rightarrow (T_1)_a = \left\{ \left[ \frac{\alpha\#D_0S_{1,j}}{\alpha\#D_0S_{1,j}} \right], \left[ \frac{S_{2,j}D_1\beta\#}{S_{2,j}D_1\beta\#} \right], \frac{\alpha\#D_0D_1\beta\#}{\alpha\#D_0S_{1,j}S_{2,j}D_1\beta\#} | 0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\} \right\}$ 
    Denaturation( $(T_1)_a$ );
     $\{\Rightarrow (T_1)_a = \{\alpha\#D_0S_{1,j}, \overline{\alpha\#D_0S_{1,j}}, S_{2,j}D_1\beta\#, \overline{S_{2,j}D_1\beta\#}, \alpha\#D_0, D_1\beta\#, \overline{\alpha\#D_0S_{1,j}S_{2,j}D_1\beta\#} |$ 
     $\{0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\}\}$ 
    Separation( $(T_1)_a, \{C_0C_1\}, T_{temp}$ );
     $\{\Rightarrow T_{temp} = \{\alpha\#D_0S_{1,j}, S_{2,j}D_1\beta\# | 0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\}\}$ 
    Empty( $(T_1)_a$ );
    Copy( $T_{temp}, (T_1)_a$ );
     $\{\Rightarrow (T_1)_a = \{\alpha\#D_0S_{1,j}, S_{2,j}D_1\beta\# | 0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\}\}$ 
    Empty( $T_{temp}$ );
    Separation( $(T_1)_a, \{A_1\}, T_3$ );
     $\{\Rightarrow T_3 = \{\alpha\#D_0S_{1,j} | 0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\}\}$ 
    Separation( $(T_1)_a, \{A_2\}, T_4$ );
     $\{\Rightarrow T_4 = \{S_{2,j}D_1\beta\# | 0 \leq j \leq s-1, \alpha, \beta \in \{0, 1\}\}$ 
    Empty( $(T_1)_a$ );
    Separation( $T_3, \{1\# \}, (T_1)_a$ );
     $\{\Rightarrow (T_1)_a = \{1\#D_0S_{1,j} | 0 \leq j \leq s-1\}, T_3 = \{0\#D_0S_{1,j} | 0 \leq j \leq s-1\}$ 
    Separation( $T_4, \{1\# \}, (T_2)_b$ );
     $\{\Rightarrow (T_2)_b = \{S_{2,j}D_11\# | 0 \leq j \leq s-1\}, T_4 = \{S_{2,j}D_10\# | 0 \leq j \leq s-1\}$ 
    for  $r \leftarrow 1$  to 4
    do in parallel
        Merge( $T_r, T_e^r$ );
        Annealing( $T_r$ );
         $\{\Rightarrow T_r = \left\{ \left[ \frac{V\#D_0S_{1,j}}{V\#D_0S_{1,j}} \right] | 0 \leq j \leq s-1, V \in \{0, 1\} \right\}$  or  $T_r = \left\{ \left[ \frac{S_{2,j}D_1V\#}{S_{2,j}D_1V\#} \right] | 0 \leq j \leq s-1, V \in \{0, 1\} \right\}$ 
        Cleavage( $T_r, \{D_0D_1\}$ );
        Denaturation( $T_r$ );
        Separation( $T_r, \{\#, \overline{\#}, \overline{C_0C_1}\}, T_{temp}$ );
         $\{\Rightarrow T_r = \{S_{i,j} | 0 \leq j \leq s-1, i = 1, 2\}$ 
    Empty( $T_{temp}$ );
    ValueAssignment( $(T_1)_a, T_{V'(1)}$ );  $\Rightarrow (T_1)_a = \{s_{1,j}(1) | 0 \leq j \leq s-1\}$ 
    ValueAssignment( $(T_2)_b, T_{V'(1)}$ );  $\Rightarrow (T_2)_b = \{s_{2,j}(1) | 0 \leq j \leq s-1\}$ 
    ValueAssignment( $T_3, T_{V'(0)}$ );  $\Rightarrow T_3 = \{s_{1,j}(0) | 0 \leq j \leq s-1\}$ 
    ValueAssignment( $T_4, T_{V'(0)}$ );  $\Rightarrow T_4 = \{s_{2,j}(0) | 0 \leq j \leq s-1\}$ 
    Merge( $(T_1)_a, T_3$ );
    Empty( $T_3$ );
    Merge( $(T_2)_b, T_4$ );
    Empty( $T_4$ );
    LeftShift( $(T_2)_b$ );
    Copy( $(T_2)_b, T_3$ );
    Separation( $T_3, \{1\}, T_{temp}$ );
    Empty( $T_3$ );
Copy( $(T_1)_a, (T_{sum})_{a,b}$ );
    
```

3.3. Residue Number Arithmetic with Matrices. From (2.1.1), it is apparent that the operation \circ is carry-free, thereby allowing for the employment of parallel procedures in all residue digits. In [Zheng et al. (2009)] two properties are given for the modular operation involving two integers $x \rightarrow (x_{n-1}, \dots, x_0)$ and $y \rightarrow (y_{n-1}, \dots, y_0)$ in RNS defined by the set $P = \{2^{m_{n-1}}, 2^{m_{n-2}} - 1, \dots, 2^{m_0} - 1\}$.

Lemma 3.3.1. *For $\forall j, m_{n-1} \in \mathbb{N}$, if $j < m_{n-1}$ then $|2^j|_{2^{m_{n-1}}} = 2^j$ else $|2^j|_{2^{m_{n-1}}} = 0$.*

Lemma 3.3.2. *For $l = 0, \dots, n - 2$, let $x_l + y_l = z_l$ where $z_l = (z_{l(m_l)}, \dots, z_{l0})$. If $z_l > 2^{m_l} - 1$, then $|z_l|_{2^{m_l-1}} = 1 + \sum_{j=0}^{m_l-1} z_{lj} 2^j$.*

Next, the procedures *RNSAdd* and *RNSDiff* add and subtract two integers in RNS defined by the moduli set P , respectively [Zheng et al. (2009)]. The inputs are $2n$ tubes $T_l^{x_{qr}}$ and $T_l^{y_{qr}}$ (for $l = 0, \dots, n - 1$) containing the memory strands representing the elements x_{qr} and y_{qr} of $t \times t$ matrices X and Y , respectively. Once either operation is complete, it returns n tubes T_l^{Rsum} and T_l^{Rdiff} containing the result of residue addition or subtraction. We also use the following n temporary tubes for *RNSAdd*, namely, T_{temp}^l, T_{sum}^l , and $T_{sum'}^l$. Similarly for *RNSDiff*, the n temporary tubes, T_{temp}^l, T_{diff}^l , and $T_{diff'}^l$ are used.

Thus, based on Lemma 3.3.1 and Lemma 3.3.2, we introduce the following two algorithms for matrix addition and subtraction in RNS which will be used when dealing with the block matrices in Strassen's algorithm. For the sake of example, we are adding (and subtracting) the hypothetical $t \times t$ matrices X and Y .

3.3.3. *Matrix Addition.* The procedure *RNSMatrixAdd* is defined as:

Algorithm 3.2: RNSMATRIXADD(T_X, T_Y)

```

for  $q \leftarrow 0$  to  $t$ 
do
  for  $r \leftarrow 0$  to  $t$ 
  do
    RNSAdd( $T_{n-1}^{xqr}, \dots, T_0^{xqr}, T_{n-1}^{yqr}, \dots, T_0^{yqr}$ ):
    for  $l \leftarrow 0$  to  $n-2$ 
    do in parallel
      BinaryAdd( $T_{n-1}^{xqr}, T_{n-1}^{yqr}, T_{sum}^{n-1}$ );
       $\{ \Rightarrow T_{n-1}^{xqr} = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V D_0 | 0 \leq j \leq m_{n-1}, V \in \{0, 1\}\}$ 
       $\{ \Rightarrow T_{n-1}^{yqr} = \{D_1 B_j E_0 E_1 A_{yqr} C_0 C_1 V D_0 | 0 \leq j \leq m_{n-1}, V \in \{0, 1\}\}$ 
       $\{ \Rightarrow T_{n-1}^{sum} = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j \leq m_{n-1}, V' \in \{0, 1\}\}$ 
      Separation( $T_{sum}^{n-1}, \{B_{m_{n-1}}\}, T_{temp}^{n-1}$ );
       $\{ \Rightarrow T_{temp}^{n-1} = \{D_1 B_{m_{n-1}} E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | V' \in \{0, 1\}\}$ ,
      ValueAssignment( $T_{temp}^{n-1}, T_{V'(0)}$ );
       $\{ \Rightarrow T_{temp}^{n-1} = \{D_1 B_{m_{n-1}} E_0 E_1 A_{xqr} C_0 C_1 0 D_0\}$ ,
      Merge( $T_{sum}^{n-1}, T_{temp}^{n-1}$ );
       $\{ \Rightarrow T_{sum}^{n-1} = \{D_1 B_{m_{n-1}} E_0 E_1 A_{xqr} C_0 C_1 0 D_0, D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j < m_{n-1}, V' \in \{0, 1\}\}$ ,
      Empty( $T_{temp}^{n-1}$ );
      BinaryAdd( $T_{n-1}^{xqr}, T_{n-1}^{yqr}, T_{sum}^l$ );
       $\{ \Rightarrow T_{n-1}^{xqr} = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V D_0 | 0 \leq j \leq m_l, V \in \{0, 1\}\}$ ,
       $\{ \Rightarrow T_{n-1}^{yqr} = \{D_1 B_j E_0 E_1 A_{yqr} C_0 C_1 V D_0 | 0 \leq j \leq m_l, V \in \{0, 1\}\}$ 
       $\{ \Rightarrow T_{n-1}^{sum} = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j \leq m_l, V' \in \{0, 1\}\}$ 
      Copy( $T_{sum}^l, T_{sum}'^l$ );
       $\{ \Rightarrow T_{sum}'^l = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j \leq m_l, V' \in \{0, 1\}\}$ 
      Separation( $T_{sum}'^l, \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}, T_{temp}^l$ );
       $\{ \Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}$  or  $T_{temp}^l = \{\}$ 
      if Detect( $T_{temp}^l$ ) = True
      then  $\Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}$ 
      { Empty( $T_{sum}^l$ );
      ValueAssignment( $T_{temp}^l, T_{V'(0)}$ );
       $\{ \Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}$ 
      Merge( $T_{sum}'^l, T_{temp}^l$ );
      BinaryAdd( $T_{sum}'^l, T_{V'(1)}, T_{sum}^l$ );

      else  $\Rightarrow T_{temp}^l = \{\}$ 
      { Separation( $T_{sum}'^l, \{D_1 B_{m_l} E_0\}, T_{temp}^l$ )
       $\{ \Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 0 D_0\}$ 
      { Empty( $T_{temp}^l$ );
       $\{ \Rightarrow T_{temp}^l = \{\}$ 
      Separation( $T_{sum}'^l, \{0\}, T_{temp}^l$ );
       $\{ \Rightarrow T_{temp}^l = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 0 D_0 | j \in \{0, \dots, m_l - 1\}\}$  or  $T_{temp}^l = \{\}$ 
      if Detect( $T_{temp}^l$ ) = False
      then  $\Rightarrow T_{temp}^l = \{\}$ 
      ValueAssignment( $T_{sum}^l, T_{V'(0)}$ );
       $\{ \Rightarrow \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 0 D_0 | 0 \leq j \leq m_l\}$ 
    
```

3.3.4. *Matrix Subtraction.* The procedure *RNSMatrixDiff* is defined as:
Algorithm 3.3: RNSMATRIXDIFF(T_X, T_Y)

```

for q ← 0 to t
do
  for r ← 0 to t
  do
    RNSDiff( $T_{n-1}^{xqr}, \dots, T_0^{xqr}, T_{n-1}^{yqr}, \dots, T_0^{yqr}$ ):
    for l ← 0 to n - 2
    do in parallel
      BinarySubtract( $T_{n-1}^{xqr}, T_{n-1}^{yqr}, T_{diff}^{n-1}$ );
      {  $\Rightarrow T_{n-1}^{xqr} = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V D_0 | 0 \leq j \leq m_{n-1}, V \in \{0, 1\}\}$ 
         $T_{n-1}^{yqr} = \{D_1 B_j E_0 E_1 A_{yqr} C_0 C_1 V D_0 | 0 \leq j \leq m_{n-1}, V \in \{0, 1\}\}$ 
         $T_{diff}^{n-1} = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j \leq m_{n-1}, V' \in \{0, 1\}\}$ 
      }
      Separation( $T_{diff}^{n-1}, \{B_{m_{n-1}}\}, T_{temp}^{n-1}$ );
      {  $\Rightarrow T_{temp}^{n-1} = \{D_1 B_{m_{n-1}} E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | V' \in \{0, 1\}\}$ ,
      }
      ValueAssignment( $T_{temp}^{n-1}, T_{V'(0)}$ );
      {  $\Rightarrow T_{temp}^{n-1} = \{D_1 B_{m_{n-1}} E_0 E_1 A_{xqr} C_0 C_1 0 D_0\}$ ,
      }
      Merge( $T_{diff}^{n-1}, T_{temp}^{n-1}$ );
      {  $\Rightarrow T_{diff}^{n-1} = \{D_1 B_{m_{n-1}} E_0 E_1 A_{xqr} C_0 C_1 0 D_0, D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j < m_{n-1}, V' \in \{0, 1\}\}$ ,
      }
      Empty( $T_{temp}^{n-1}$ );
      BinarySubtract( $T_l^{xqr}, T_l^{yqr}, T_{diff}^l$ );
      {  $\Rightarrow T_{n-1}^{xqr} = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V D_0 | 0 \leq j \leq m_l, V \in \{0, 1\}\}$ ,
         $T_{n-1}^{yqr} = \{D_1 B_j E_0 E_1 A_{yqr} C_0 C_1 V D_0 | 0 \leq j \leq m_l, V \in \{0, 1\}\}$ 
         $T_{diff}^l = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j \leq m_l, V' \in \{0, 1\}\}$ 
      }
      Copy( $T_{diff}^l, T_{diff}'^l$ );
      {  $\Rightarrow T_{diff}'^l = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 V' D_0 | 0 \leq j \leq m_l, V' \in \{0, 1\}\}$ 
      }
      Separation( $T_{diff}'^l, \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}, T_{temp}^l$ );
      {  $\Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}$  or  $T_{temp}^l = \{\}$ 
      }
      if Detect( $T_{temp}^l$ ) = True
      then  $\Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}$ 
      { Empty( $T_{diff}^l$ );
        ValueAssignment( $T_{temp}^l, T_{V'(0)}$ );
        {  $\Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 1 D_0\}$ 
        }
        Merge( $T_{diff}'^l, T_{temp}^l$ );
        BinarySubtract( $T_{diff}'^l, T_{V'(1)}, T_{diff}^l$ );
      }
      else  $\Rightarrow T_{temp}^l = \{\}$ 
      { Separation( $T_{diff}'^l, \{D_1 B_{m_l} E_0\}, T_{temp}^l$ )
        {  $\Rightarrow T_{temp}^l = \{D_1 B_{m_l} E_0 E_1 A_{xqr} C_0 C_1 0 D_0\}$ 
          Empty( $T_{temp}^l$ );
          {  $\Rightarrow T_{temp}^l = \{\}$ 
          }
          Separation( $T_{diff}'^l, \{0\}, T_{temp}^l$ );
          {  $\Rightarrow T_{temp}^l = \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 0 D_0 | j \in \{0, \dots, m_l - 1\}\}$  or  $T_{temp}^l = \{\}$ 
          }
          if Detect( $T_{temp}^l$ ) = False
          then  $\Rightarrow T_{temp}^l = \{\}$ 
          ValueAssignment( $T_{diff}^l, T_{V'(0)}$ );
          {  $\Rightarrow \{D_1 B_j E_0 E_1 A_{xqr} C_0 C_1 0 D_0 | 0 \leq j \leq m_l\}$ 
          }
        }
      }
    }
  }

```


4. STRASSEN'S ALGORITHM REVISITED

4.1. Bottom-Level Matrix Multiplication. Although a vast repository of traditional matrix multiplication algorithms can be used between processors (test tubes containing memory strands; however for the sake of brevity, we shall just use the term “memory strand” or “strand”), we will employ the Cannon algorithm [Cannon (1969)] since it can be used on matrices of any dimensions. We will only discuss square strand arrangements and square matrices for simplicity's sake. Assume that we have p^2 memory strands, organized in a logical sequence in a $p \times p$ mesh. For $i \geq 0$ and $j \leq p - 1$, the strand in the i^{th} row and j^{th} column has coordinates (i, j) . The matrices X , Y , and their matrix product Q are of size $t \times t$, and again as a simplifying assumption, let t be a multiple of p . All matrices will be partitioned into $p \times p$ blocks of $s \times s$ sub-matrices where $s = t/p$. As described in [Nguyen et al. (2005)], the mesh can be perceived as an amalgamation of rings of memory strands in both the horizontal and vertical directions (opposite sides of the mesh are linked with a torus interconnection). A successful DNA implementation of Cannon's algorithm requires communication between the strands of each ring in the mesh where the blocks of matrix X are passed *in parallel* to the left along the horizontal rings and the blocks of the matrix Y are passed to the top along the vertical rings. Let X_{ij} , Y_{ij} , and Q_{ij} denote the blocks of X , Y , and Q stored in the strand with coordinates (i, j) . The Cannon algorithm on a DNA computer can be described as such:

Algorithm 4.1: CANNON($T_{X_{ij}}, T_{Y_{ij}}$)

```

for  $i^{\text{th}}$  column  $\leftarrow 0$  to  $i$ 
  do
  {LeftShift( $T_{X_{ij}}$ )
  for  $j^{\text{th}}$  column  $\leftarrow 0$  to  $j$ 
    do
    {UpShift( $T_{Y_{ij}}$ )
     $\forall$  strands  $(i, j)$ 
      do
      {ValueAssignment( $T_{X_{ij}Y_{ij}}, T_{Q_{ij}}$ )

      do  $(p - 1)$  times
      {
        LeftShift( $T_{X_{ij}}$ )
        UpShift( $T_{Y_{ij}}$ )
        ValueAssignment ( $T_{\text{RNSMatrixAdd}(T_{Q_{ij}}, T_{X_{ij}Y_{ij}}), T_{Q_{ij}}$ )
      }

```

Note that the procedure *UpShift* can be derived from Zheng et al.'s [Zheng et al. (2009)] *LeftShift*. Now we examine the run-time of the Cannon algorithm. The run time can be componentized into the communication time and the computation time, and the total communication time is

$$(4.1.1) \quad 2p\alpha + \frac{2B\beta t^2}{p},$$

and the computation time is

$$(4.1.2) \quad \frac{2t^3 t_{\text{comp}}}{p^2},$$

where t_{comp} is the execution time for one arithmetic operation, α is the latency, β is the sequence-transfer rate, the total latency is $2p\alpha$, and the total sequence-transfer time is $2p\beta B(m/p)^2$ with B as the number of sequences to store one entry of the matrices. According to [Nguyen et al. (2005)], the running time is

$$(4.1.3) \quad T(t) = \frac{2t^3 t_{\text{comp}}}{p^2} + 2p\alpha + \frac{2B\beta t^2}{p}.$$

4.2. Matrix Storage Pattern. The primary difficulty is to be able to store the different sub-matrices of the Strassen algorithm in different strands, and these sub-matrices must be copied or moved to appropriate strands if tasks are spawned. Hence, we present here a storage map of sub-matrices to strands based on the result of Luo and Drake [Luo et al. (1995)] for electronic computers. Essentially, if we allow each strand to have a portion of each sub-matrix at each recursion level, then we can make it possible for all strands to act as *one* strand. As a result, the addition and subtraction of the block matrices performed in the Strassen algorithm at all recursion levels can be performed in parallel without any inter-strand communication [Nguyen et al. (2005)]. Each strand performs its local sub-matrix additions and subtractions in RNS (via *RNSMatrixAdd* and *RNSMatrixDiff* described in §3). At the final recursion level, the block matrix multiplications are calculated using the Cannon algorithm in §4.1.

For instance, if we suppose that the recursion level in the Strassen-algorithm is r , and let $n = t/p$, $t_0 = t/2$, and $n_0 = t_0/p$ for $n, t_0, n_0 \in \mathbb{N}$, then the run-time of the Strassen-Canon algorithm is:

$$(4.2.1) \quad T(t) = 18T_{add}\left(\frac{t}{2}\right) + 7T\left(\frac{t}{2}\right),$$

where $T_{add}\left(\frac{t}{2}\right)$ is the run-time to add or subtract block matrices of order $t/2$. Additionally, according to (9) of [Nguyen et al. (2005)],

$$(4.2.2) \quad T_t \approx \frac{2\left(\frac{7}{8}\right)^r t^3 t_{comp}}{p^2} + \frac{5\left(\frac{7}{4}\right)^r t_{comp}}{p^2} + \left(\frac{7}{4}\right)^r 2p\alpha.$$

Since the asymptotically significant term $\frac{2\left(\frac{7}{8}\right)^r t^3 t_{comp}}{p^2}$ decreases as the recursion level r increases, then for t significantly large, the Strassen-Cannon algorithm should be faster than the Cannon algorithm. Even if the Cannon algorithm is replaced at the bottom level by other parallel matrix multiplication algorithms, the same result holds.

4.3. Recursion Removal. As has been previously discussed, in order to use the Strassen algorithm between strands (at the top level), we must determine the sub-matrices after r times recursive execution and then to determine the resultant matrix from these sub-matrices. Nguyen et al. [Nguyen et al. (2005)] recently presented a method on electronic computers to ascertain all of the nodes in the execution tree of the Strassen algorithm at the unspecified recursion level r and to determine the relation between the sub-matrices and the resultant matrix at level r . We extend it to the DNA computing paradigm. At each step, the algorithm will execute a multiplication between 2 factors, namely the linear combinations of the elements of the matrices X and Y , respectively. Since we can consider that each factor is the sum of all elements from each matrix, with coefficient of 0, -1, or 1 [Nguyen et al. (2005)], then we can represent these coefficients with the RNS representation of numbers with DNA strands described in §3.1 as such:

$$\begin{aligned} & (\{D_1B_1E_0E_1A_0C_0C_10D_0, D_1B_0E_0E_1A_0C_0C_10D_0\}, \{D_1B_1E_0E_1A_0C_0C_10D_0, D_1B_0E_0E_1A_0C_0C_10D_0\}, \\ & \quad \{D_1B_1E_0E_1A_0C_0C_10D_0, D_1B_0E_0E_1A_0C_0C_10D_0\}), \\ & (\{D_1B_1E_0E_1A_{-1}C_0C_11D_0, D_1B_0E_0E_1A_{-1}C_0C_11D_0\}, \{D_1B_1E_0E_1A_{-1}C_0C_11D_0, D_1B_0E_0E_1A_{-1}C_0C_11D_0\}, \\ & \quad \{D_1B_1E_0E_1A_{-1}C_0C_11D_0, D_1B_0E_0E_1A_{-1}C_0C_11D_0\}), \end{aligned}$$

or

$$\begin{aligned} & (\{D_1B_1E_0E_1A_1C_0C_10D_0, D_1B_0E_0E_1A_1C_0C_11D_0\}, \{D_1B_1E_0E_1A_1C_0C_10D_0, D_1B_0E_0E_1A_1C_0C_11D_0\}, \\ & \quad \{D_1B_1E_0E_1A_1C_0C_10D_0, D_1B_0E_0E_1A_1C_0C_11D_0\}), \end{aligned}$$

respectively. For the sake of brevity, we shall denote the latter three equations as $(0)_{RNS}$, $(-1)_{RNS}$, and $(1)_{RNS}$, respectively. This coefficient is obtained for each element in each recursive call and is dependent upon both the index of the call and the location of an element in the division of the matrix by 4 sub-matrices [Nguyen et al. (2005)]. If we view the Strassen-Cannon algorithm's execution as an execution tree [Nguyen et al. (2005)], then each scalar multiplication is correlated on a leaf of the execution tree and the path from the root to the leaf represents the recursive calls leading to the corresponding multiplication.

Furthermore, at the leaf, the coefficient of each element (either $(0)_{RNS}$, $(-1)_{RNS}$, or $(1)_{RNS}$) can be determined by the combination of all computations in the path from the root. The reason is that since all of the computations are linear, they can be combined in the leaf (which we will denote by t_l).

Utilizing the nomenclature of [Nguyen et al. (2005)], Strassen's formula can be depicted as such:
For $l = 0 \dots 6$,

$$(4.3.1) \quad t_l = \sum_{i,j=0,1} x_{ij} SX(l, i, j) \times \sum_{i,j=0,1} y_{ij} SY(l, i, j),$$

and

$$(4.3.2) \quad q_{ij} = \sum_{l=0}^6 t_l SQ(l, i, j),$$

in which

$$\begin{aligned}
 SX &= \begin{array}{c|c|c|c|c}
 \mathbf{1 \setminus ij} & \mathbf{00} & \mathbf{01} & \mathbf{10} & \mathbf{11} \\
 \mathbf{0} & (1)_{RNS} & (0)_{RNS} & (0)_{RNS} & (0)_{RNS} \\
 \mathbf{1} & (0)_{RNS} & (1)_{RNS} & (0)_{RNS} & (0)_{RNS} \\
 \mathbf{2} & (0)_{RNS} & (0)_{RNS} & (1)_{RNS} & (1)_{RNS} \\
 \mathbf{3} & (-1)_{RNS} & (0)_{RNS} & (1)_{RNS} & (1)_{RNS} \\
 \mathbf{4} & (1)_{RNS} & (0)_{RNS} & (-1)_{RNS} & (0)_{RNS} \\
 \mathbf{5} & (0)_{RNS} & (0)_{RNS} & (1)_{RNS} & (1)_{RNS} \\
 \mathbf{6} & (0)_{RNS} & (0)_{RNS} & (0)_{RNS} & (1)_{RNS}
 \end{array} \\
 SY &= \begin{array}{c|c|c|c|c}
 \mathbf{1 \setminus ij} & \mathbf{00} & \mathbf{01} & \mathbf{10} & \mathbf{11} \\
 \mathbf{0} & (1)_{RNS} & (0)_{RNS} & (0)_{RNS} & (0)_{RNS} \\
 \mathbf{1} & (0)_{RNS} & (0)_{RNS} & (1)_{RNS} & (0)_{RNS} \\
 \mathbf{2} & (-1)_{RNS} & (1)_{RNS} & (0)_{RNS} & (0)_{RNS} \\
 \mathbf{3} & (1)_{RNS} & (-1)_{RNS} & (0)_{RNS} & (1)_{RNS} \\
 \mathbf{4} & (0)_{RNS} & (-1)_{RNS} & (0)_{RNS} & (1)_{RNS} \\
 \mathbf{5} & (0)_{RNS} & (1)_{RNS} & (0)_{RNS} & (1)_{RNS} \\
 \mathbf{6} & (-1)_{RNS} & (1)_{RNS} & (1)_{RNS} & (-1)_{RNS}
 \end{array} \\
 SQ &= \begin{array}{c|c|c|c|c}
 \mathbf{1 \setminus ij} & \mathbf{00} & \mathbf{01} & \mathbf{10} & \mathbf{11} \\
 \mathbf{0} & (1)_{RNS} & (1)_{RNS} & (1)_{RNS} & (1)_{RNS} \\
 \mathbf{1} & (1)_{RNS} & (0)_{RNS} & (0)_{RNS} & (0)_{RNS} \\
 \mathbf{2} & (0)_{RNS} & (1)_{RNS} & (0)_{RNS} & (0)_{RNS} \\
 \mathbf{3} & (0)_{RNS} & (1)_{RNS} & (1)_{RNS} & (1)_{RNS} \\
 \mathbf{4} & (0)_{RNS} & (0)_{RNS} & (0)_{RNS} & (1)_{RNS} \\
 \mathbf{5} & (0)_{RNS} & (1)_{RNS} & (0)_{RNS} & (0)_{RNS} \\
 \mathbf{6} & (0)_{RNS} & (0)_{RNS} & (0)_{RNS} & (1)_{RNS}
 \end{array}
 \end{aligned}$$

At recursion level r , t_l can be represented as such:

For $l = 0 \dots 7^k - 1$,

$$(4.3.3) \quad t_l = \sum_{i,j=n-1} x_{ij} SX_k(l, i, j) \times \sum_{i,j=0,n-1} y_{ij} SY_k(l, i, j),$$

and

$$(4.3.4) \quad q_{ij} = \sum_{l=0}^{7^k-1} t_l SQ_k(l, i, j).$$

It is easy to see that $SX = SX_1$, $SY = SY_1$, and $SQ = SQ_1$; however, the difficulty that arises is to determine the values of matrices SX_k , SY_k , and SQ_k in order to have a *general* algorithm. The following relations were proved in [Nguyen et al. (2006)], and we shall prove that these results hold with DNA:

$$(4.3.5) \quad SX_k(l, i, j) = \prod_{r=1}^k SX(l_r, i_r, j_r),$$

$$(4.3.6) \quad SY_k(l, i, j) = \prod_{r=1}^k SY(l_r, i_r, j_r),$$

$$(4.3.7) \quad SQ_k(l, i, j) = \prod_{r=1}^k SQ(l_r, i_r, j_r).$$

First we shall extend the definition of the tensor product for arrays of arbitrary dimensions [Nguyen et al. (2006)] by representing the tensor product in RNS by way of single DNA strands.

Proposition 4.3.1. *Let A and B be arrays of the same dimension l and of size $m_1 \times m_2 \times \cdots \times m_l$ and $n_1 \times n_2 \times \cdots \times n_l$, respectively. The elements of A and B are represented using RNA by way of DNA strands as presented in detail in §3.1. The tensor product can thus be described as an array of the same dimension and of size $m_1 n_1 \times m_2 n_2 \times \cdots \times m_l n_l$ in which each element of A is replaced with the product of the element and B . This product can be computed with the algorithm *RNSMult* which is recognized by a serial of operations of the *RNSAdd* algorithm detailed in §3.3 of this paper and §4.4 of Zheng et al. [Zheng et al. (2009)]. $P = A \otimes B$ where $P[i_1, i_2, \dots, i_l] = A[k_1, k_2, \dots, k_l]B[h_1, h_2, \dots, h_l]$. $1 \leq \forall j \leq l$, $i_j = k_j n_j + h_j$ ($k_j n_j$ and h_j will be added with *RNSAdd*).*

If we let $P = \otimes_{i=1}^n A_i = (\cdots (A_1 \otimes A_2) \otimes A_3) \cdots \otimes A_n$ where A_i is an array of dimension l and of size $m_{i1} \times m_{i2} \times \cdots \times m_{il}$, the following theorem allows us to directly compute the elements of P . All products and sums of elements can be computed with *RNSMult* and *RNSAdd*, respectively.

Theorem 4.3.2. *If we let $j_k = \sum_{s=1}^n (h_{sk} \prod_{r=s+1}^n m_{rk})$, then $P[j_1, j_2, \dots, j_l] = \prod_{i=1}^n A_i[h_{i1}, h_{i2}, \dots, h_{il}]$.*

Proof. We give a proof by induction. For $n = 1$ and $n = 2$, the statement is true. Assume it is true with n , then we shall prove that it is true with $n + 1$.

$P_{n+1}[v_1, v_2, \dots, v_l] = \prod_{i=1}^{n+1} A_i[h_{i1}, h_{i2}, \dots, h_{il}]$ where

$$v_k = \sum_{s=1}^{n+1} \left(h_{sk} \prod_{r=s+1}^{n+1} m_{rk} \right),$$

for $1 \leq \forall k \leq l$. Hence, $P_{n+1} = P_n \otimes A_{n+1}$.

Furthermore, by definition,

$$P_{n+1}[j_1, j_2, \dots, j_l] = P_n[p_1, p_2, \dots, p_l] A_{n+1}[h_{(n+1)}, h_{2(n+1)}, \dots, h_{l(n+1)}] = \prod_{i=1}^{n+1} A_i[h_{i1}, h_{i2}, \dots, h_{il}],$$

where

$$j_k = \sum_{s=1}^n \left(h_{sk} \prod_{r=s+1}^{n+1} m_{rk} \right) + h_{k(n+1)} = \sum_{s=1}^{n+1} \left(h_{sk} \prod_{r=s+1}^{n+1} m_{rk} \right).$$

■

Theorem 4.3.3. $SX_k = \otimes_{i=1}^k SX$, $SY_k = \otimes_{i=1}^k SY$, and $SQ_k = \otimes_{i=1}^k SQ$.

Proof. We give a proof by induction. For $k = 1$, the statement is true. Assume it is true with k , then we shall prove that it is true with $k + 1$.

According to (4.3.3) and (4.3.4), at level $k + 1$ of the execution tree, for $0 \leq l \leq 7^{k+1} - 1$

$$T_l = \left(\sum_{i \geq 0, j \leq 2^{k+1} - 1} X_{k+1, ij} SX_{k+1}(l, i, j) \right) \times \left(\sum_{i \geq 0, j \leq 2^{k+1} - 1} Y_{k+1, ij} SY_{k+1}(l, i, j) \right).$$

It follows from (4.3.1) and (4.3.2) that at level $k+2$, for $0 \leq l \leq 7^{k+1} - 1$ and $0 \leq l' \leq 6$,

$$(4.3.8) \quad T_l[l'] = \sum_{i' \geq 0, j' \leq 1} \left(\sum_{i \geq 0, j \leq 2^{k+1}-1} X_{k+1,ij}[i', j'] SX_{k+1}(l, i, j) SX(l', i', j') \right) \times \\ \sum_{i' \geq 0, j' \leq 1} \left(\sum_{i \geq 0, j \leq 2^{k+1}-1} Y_{k+1,ij}[i', j'] SY_{k+1}(l, i, j) SY(l', i', j') \right),$$

where $X_{k+1,ij}[i', j']$ and $Y_{k+1,ij}[i', j']$ are $2^{k+2} \times 2^{k+2}$ matrices obtained by partitioning the matrices $X_{k+1,ij}$ and $Y_{k+1,ij}$ into 4 sub-matrices (we use i' and j' to denote the sub-matrix's quarter).

We represent l, l' in base 7 RNS, and i, j, i', j' in base 2 RNS. Since $X_{k+1,ij}[i', j'] = X_{k+2,ij}[\overline{i'_{(2)}}, \overline{j'_{(2)}}]$, then for $0 \leq \overline{l'_{(7)}} \leq 7^{k+1} - 1$,

$$(4.3.9) \quad M[\overline{l'_{(7)}}] = \left(\sum_{\overline{i'_{(2)}} \geq 0, \overline{j'_{(2)}} \leq 2^{k+1}-1} X_{k+2}[\overline{i'_{(2)}}, \overline{j'_{(2)}}] SX_{k+1}(l, i, j) SX(l', i', j') \right) \times \\ \left(\sum_{\overline{i'_{(2)}} \geq 0, \overline{j'_{(2)}} \leq 2^{k+1}-1} Y_{k+2}[\overline{i'_{(2)}}, \overline{j'_{(2)}}] SY_{k+1}(l, i, j) SY(l', i', j') \right).$$

Moreover, it directly follows from (4.3.3) and (4.3.4) that for $0 \leq \overline{l'_{(7)}} \leq 7^{k+1} - 1$,

$$(4.3.10) \quad M[\overline{l'_{(7)}}] = \left(\sum_{\overline{i'_{(2)}} \geq 0, \overline{j'_{(2)}} \leq 2^{k+1}-1} X_{k+2}[\overline{i'_{(2)}}, \overline{j'_{(2)}}] SX_{k+2}(\overline{l'_{(7)}}, \overline{i'_{(2)}}, \overline{j'_{(2)}}) \right) \times \\ \left(\sum_{\overline{i'_{(2)}} \geq 0, \overline{j'_{(2)}} \leq 2^{k+1}-1} Y_{k+2}[\overline{i'_{(2)}}, \overline{j'_{(2)}}] SY_{k+2}(\overline{l'_{(7)}}, \overline{i'_{(2)}}, \overline{j'_{(2)}}) \right).$$

From (4.3.12) and (4.3.10), we have

$$SX_{k+2}(\overline{l'_{(7)}}, \overline{i'_{(2)}}, \overline{j'_{(2)}}) = SX_{k+1}(l, i, j) SX(l', i', j'),$$

and

$$SY_{k+2}(\overline{l'_{(7)}}, \overline{i'_{(2)}}, \overline{j'_{(2)}}) = SY_{k+1}(l, i, j) SY(l', i', j').$$

Thus,

$$SX_{k+2} = SX_{k+1} \otimes SX = \otimes_{i=1}^{k+2} SX,$$

$$SY_{k+2} = SY_{k+1} \otimes SY = \otimes_{i=1}^{k+2} SY,$$

and

$$SQ_{k+2} = SQ_{k+1} \otimes SQ = \otimes_{i=1}^{k+2} SQ. \quad \blacksquare$$

From Theorem 4.3.2 and Theorem 4.3.3, (4.3.5), (4.3.6), and (4.3.7) follow.

As a consequence of (4.3.3)-(4.3.7), we can form the following sub-matrices:

$$(4.3.11) \quad T_l = \sum_{i,j=0,2^r-1} X_{ij} \left(\prod_{u=1}^r SX(l_u, i_u, j_u) \right) \times \sum_{\substack{i,j=0,2^r-1 \\ l=0 \dots 7^r-1}} Y_{ij} \left(\prod_{u=1}^r SX(l_u, i_u, j_u) \right).$$

As a result of the storage map of sub matrices to strands presented in §4.2, the following sub-matrices can be *locally* determined within each strand, and their product T_l can be computed by parallel matrix multiplication algorithms (such as the DNA implementation of the Cannon algorithm in §4.1):

$$\left(\sum_{\substack{i=0,2^r-1 \\ j=0,2^r-1}} X_{ij} \left(\prod_{u=1}^r SX(l_u, i_u, j_u) \right) \right),$$

and

$$\left(\sum_{\substack{i=0,2^r-1 \\ j=0,2^r-1}} Y_{ij} \left(\prod_{u=1}^r SY(l_u, i_u, j_u) \right) \right).$$

All of the sub-matrices are added with the *RNSMatrixAdd* algorithm presented in §3.3.3.

Lastly, it is important to note that due to (4.3.3)-(4.3.7), we have derived a method to directly compute the sub-matrix elements of the resultant matrix via the application of matrix additions (using the *RNSMatrixAdd* algorithm of §3.3.3) instead of backtracking manually down the recursive execution tree to compute:

$$(4.3.12) \quad Q_{ij} = \sum_{l=0}^{7^r-1} T_l SQ_r(l, i, j) = \sum_{l=0}^{7^r-1} T_l \left(\prod_{u=1}^r SQ(l_u, i_u, j_u) \right).$$

5. CONCLUSIONS

Unlike sequential machines, DNA computers perform calculations parallel to other calculations, and it is parallel computing that allows DNA to solve complex mathematical problems in hours, whereas it might take electronic computers hundreds of years to complete them. Our general scalable implementation can be used for all of the matrix multiplication algorithms that use fast matrix multiplication algorithms at the top level (between strands) on a DNA computer. Moreover, since the computational complexity of these algorithms decreases when the recursion level r increases, we can now find optimal algorithms for all *particular* cases.

REFERENCES

- [Adleman (1994)] L. Adleman, *Molecular Computation of Solutions to Combinatorial Problems*, Science **266** (1994), 1021–1024.
- [Bunch et al. (1974)] R. Bunch and J. E. Hopcroft, *Triangular Factorization and Inversion by Fast Matrix Multiplication*, Math. Comp. **28** (1974), 231–236.
- [Nguyen et al. (2005)] D. K. Nguyen, I. Lavallée, and M. Bui, *A General Scalable Implementation of Fast Matrix Multiplication Algorithms on Distributed Memory Computers*, Proceedings of the Sixth International Conference on Software Engineering, Artificial Intelligence, Networking and Parallel/Distributed Computing and First ACIS International Workshop on Self-Assembling Wireless Networks, 2005.
- [Nguyen et al. (2006)] D. K. Nguyen, I. Lavallée, and M. Bui, *A New Direction to Parallelize Winograd’s Algorithm on Distributed Memory Computers*, Modeling, Simulation and Optimization of Complex Processes Proceedings of the Third International Conference on High Performance Scientific Computing, March 6–10, 2006, Hanoi, Vietnam, 445–457.
- [Cannon (1969)] L. E. Cannon, *A cellular computer to implement the kalman filter algorithms*, Technical Report, Ph.D. Thesis, Montana State University, (1969), 1–228.
- [Cohn et al. (2005)] H. Cohn, R. Kleinberg, B. Szegedy, and C. Umans, *Group-Theoretic Algorithms for Matrix Multiplication*, Proceedings of the 46th Annual Symposium on Foundations of Computer Science, 23–25 October 2005, Pittsburgh, PA, IEEE Computer Society, pp. 379–388.
- [Coppersmith et al. (1990)] D. Coppersmith and S. Winograd, *Matrix multiplication via arithmetic progressions*, J. Symb. Comp. **9** (1990), 251–280.
- [Fujiwara et al. (2004)] A. Fujiwara, K. Matsumoto, and W. Chen, *Procedures for logic and arithmetic operations with DNA molecules*, Int. J. Found. Comput. Sci. **15** (2004), 461–474.
- [Luo et al. (1995)] Q. Luo and J. B. Drake, *A scalable parallel strassen’s matrix multiplication algorithm for distributed memory computers*, Proceedings of the 1995 ACM symposium on Applied computing, (1995), 221–226.
- [Pan (1984)] V. Pan, *How can we speed up matrix multiplication?*, SIAM Review, **26** (1984), 393–416.
- [Paun et al. (1998)] G. Paun, G. Rozeberg, A. Salomaa, *DNA computing*, Springer-Verlag, 1998.
- [Robinson (2005)] S. Robinson, *Toward an Optimal Algorithm for Matrix Multiplication*, SIAM News **38** (2005), 1–3.
- [Strassen (1969)] V. Strassen, *Gaussian elimination is not optimal*, Numer. Math. **13** (1969), 354–356. MR **40**:2223.
- [Zheng et al. (2009)] X. Zheng, J. Xu, and W. Li, *Parallel DNA arithmetic operation based on n -moduli set*, Appl. Math. Comp. **212** (2009), 177–184.

E-mail address: aran.nayebi@gmail.com