## Love kills Penna Ageing Model

Dietrich Stauffer\* and Stanisław Cebrat

Department of Genomics, Wrocław University, ul. Przybyszewskiego 63/77, 51-148 Wrocław, Poland

 $\ast$  visiting from Institute for Theoretical Physics, Cologne University, D-50923 Köln, Euroland

Love may have been a female invention long ago, when the brain of genus homo became large and required more food. Thus the father was needed to help feed mother and baby. Pekalski [1] assumed mate selection to be governed by a Major Histocompatibility Complex MHC. In the same spirit now the sexual Penna ageing model is modified to include mate selection by an additional string of 32 bits for each individual, unrelated to the two usual bit-strings of length L containing the age-relevant genome. Initially, the additional love bit-string is chosen randomly, different for each individual. This model is therefore more complicated than the gamete recognition of Cebrat and Stauffer [2] based on one bit.

During the at most 20 attempts per iteration of a female to find a suitable male partner, the two new "love" bit-strings of the male and the female which should be similar, are compared bit by bit. If the number of differences is larger than a universal love limit between 0 and 32, the male is rejected. Thus with too stringent requirements for love, the female will often not find a suitable partner within the allowed 20 attempts, stay single during this iteration, thus reduce the total number of new babies, and finally lead the population to extinction, as indicated for Germany by present trends. (Sons get the love bit-string from their father, and daughters from their mother.)

We start with the standard Penna model [3] with L = 64, a minimum reproduction age R = 16, T = 3 active mutations kill, B = 2 births are attempted per female and iteration, d = 8 loci are dominant, both males and females suffer from one (deleterious) mutation per bitstring and iteration, Verhulst deaths are applied to births only with a carrying capacity K up to 30 million. If the male partner can differ in at most  $6 \pm 1$  bit pairs (i.e. they agree in at least (32 - 6 = 26 bit pairs) to remain suitable, the population survives; with the limit one bit less, the population dies down. For L = 1024, R = 256 and Kup to 3 million instead, survival requires  $5 \pm 1$  bits. If observation time would go to infinity at a fixed population size and a small love limit, we might get an Eve effect for the love bit-strings: All surviving males have one string and all surviving females the same or the complementary bit-string. However, if our populations vanish they do so rather quickly as shown in our figure, and prevent this Eve effect. (If love starts only after 10,000 iterations, close to equilibrium, the limits are higher.)

Love entails the danger of monogamy. Assuming that a loving couple stays together until death, but then can remarry, we find the threshold to decrease from about six bits for K = thousand to about zero or one bit for K = 30 million.



Figure 1: a: Sexual Penna model with love (lower curves) and without love restriction (upper squares): Extinction threatens with too narrow requirements for love. b: Love is switched on after 10,000 iterations.

## References

- A. Pekalski, Int. J. Mod. Phys. C 18, 1619 (2007); for real humans see S. Jacob, M.K. McClintock, B. Zelano and C. Ober, Nat. Genet. 30, 175 (2002).
- [2] S. Cebrat and D. Stauffer, Int. J. Mod. Phys. C 19, 259 (2008)
- [3] T.J.P. Penna: J. Stat. Phys. 78, 1629 (1995), D. Stauffer, S. Moss de Oliveira, P.M.C. de Oliveira, J.S. Sá Martins, Biology, Sociology, Geology by Computational Physicists (Elsevier, Amsterdam 2006), D. Stauffer, Bioinformatics and Biology Insights. 1, 91 (2007): http://www.la-press.com/article.php?article\_id=520