Computational procedures for weighted projective spaces

Michele Rossi Università degli Studi di Torino Italy <u>michele.rossi@unito.it</u>

LeaTerracini Università degli Studi di Torino Italy <u>lea.terracini@unito.it</u>

Introduction

Let us introduce the main geometric objects the following procedures are dealing with. For any further detail the interested reader is referred to the extensive mathematical treatment of the subject [RT] and to references therein.

A weighted projective space (wps) is a suitable finite quotient $P(Q) := P^n / W_Q$ of the *n*-dimensional projective space, where $Q = (q_0, ..., q_n)$ is the *weights vector*, i.e. a (n + 1)-vector with coprime positive integer entries, characterizing the action defining the quotient [RT, 1.4]. It is probably the better known example of a *singular, complete, normal toric variety*.

Since normal toric varieties can be defined starting from convex geometric objects like cones, fans of cones and, for projective ones, polytopes [RT, 1.1], the approach to wps's via toric geometry naturally provides an algorithmic treatment of the subject. Moreover polytopes associated with polarized wps's turns out to be simplices, meaning that their treatment can be further reduced to consider suitable associated matrices.

Here we will provide procedures which are able to produce the toric data associated with a (polarized) wps i.e. fans, polytopes and their equivalences. But more originally we will provide procedures which are able to detect a weights vector *Q* starting from either a fan or a polytope: we will call this process *the recognition of a (polarized) wps*. Moreover we will give procedures connecting polytopes of a polarized wps with an associated fan and viceversa.

Although there already exist many mathematical packages which are able to compute the toric data of a given toric variety, and in particular of a given wps (the interested reader is referred to the well updated D. Cox web-page [Cox] and references therein), the recognition of toric data, the connection between fans and polytopes and the detection of equivalence between toric data with the computation of the linking transformations are all original procedures which do not find comparisons elsewhere.

restart :
with(LinearAlgebra) :

0.a Preliminaries

1. Reduction of weights vector Given a weights vector Q, computes its reduction (see [RT, 1.6]: > ReducedWeights := $\mathbf{proc}(Q)$ local nn, dd, i, aa, L: nn := nops(Q) - 1: dd := []: for i from 1 to nn + 1 do dd := [op(dd), igcd(seq(Q[j], j=1..i-1), seq(Q[j], j=i+1)][..nn + 1)] end do; aa := []: for *i* from 1 to nn + 1 do aa := [op(aa),ilcm(seq(dd[j], j=1..i-1), seq(dd[j], j=i+1..nn+1))] end do: L := []: for *i* from 1 to nn + 1 do $L := \left[op(L), \frac{Q[i]}{aa[i]} \right]$ end do: *L* end proc: **Example:** > Q := [3, 2, 4]:> ReducedWeights(Q) [3, 1, 2](2.1.1)2. From fan and polytopes to matrices and conversely The following procedures associate a matrix to the (ordered) 1-skeleton of a fan and viceversa. The same is done for vertices of a polytope. > FanMatrix := proc(fan) Transpose(Matrix(fan)) end proc:> $MatrixFan := \mathbf{proc}(V)$ convert(Transpose(V), listlist) end proc: > PolytopeMatrix := proc(P) Transpose(Matrix([seq(P[i] - P[1], i=2..nops(P[1])))))+1)) end proc: > MatrixPolytope := $\mathbf{proc}(W)$ [[seq(0, i=1..op(W) [1])], op(convert(Transpose(W), *listlist*))] end proc: **Example:** > fan := [[3, 2, 1], [7, 3, 1], [0, 0, 2], [3, 1, 3]]fan := [[3, 2, 1], [7, 3, 1], [0, 0, 2], [3, 1, 3]](2.2.1)> FM := FanMatrix(fan) $FM := \begin{bmatrix} 3 & 7 & 0 & 3 \\ 2 & 3 & 0 & 1 \\ 1 & 1 & 2 & 3 \end{bmatrix}$ (2.2.2)> MatrixFan(FM)[[3, 2, 1], [7, 3, 1], [0, 0, 2], [3, 1, 3]] (2.2.3)P := [[1, 2, 3, 4], [3, 2, 6, 1], [2, 1, 3, 5], [2, 4, 1, 1], [7, 8, 8, 8]]P := [[1, 2, 3, 4], [3, 2, 6, 1], [2, 1, 3, 5], [2, 4, 1, 1], [7, 8, 8, 8]](2.2.4)> PM := PolytopeMatrix(P) $PM := \begin{bmatrix} 2 & 1 & 1 & 6 \\ 0 & -1 & 2 & 6 \\ 3 & 0 & -2 & 5 \\ 2 & 1 & 2 & 4 \end{bmatrix}$ (2.2.5)*MatrixPolytope(PM)* [[0, 0, 0, 0], [2, 0, 3, -3], [1, -1, 0, 1], [1, 2, -2, -3], [6, 6, 5, 4]] (2.2.6)



0.b Given a weights vector Q, determine a fan associated to Q

Given a weights vector Q, the following procedure computes a fan associated to Q: $Fan := \operatorname{proc}(Q)$ $\operatorname{local} n, U1, U2, SS, TT, VV:$ n := nops(Q) - 1: U1 := LinearAlgebra[HermiteForm](Matrix([seq([Q[i]], i = 1 ..n + 1)]), output = ['U ']): U2 := Matrix([seq(convert(Row(U1, i), list), i = 2 ..n + 1)]): VV := convert(Transpose(U2), listlist): VV

end proc: **Examples:** > Q := [3, 2, 4](3.1)Q := [3, 2, 4]Fan(Q)[[-2, -2], [3, 1], [0, 1]](3.2)> RQ := ReducedWeights(Q)(3.3) RQ := [3, 1, 2]Fan(RQ)(3.4)[[-1, -1], [3, 1], [0, 1]]> Q := [1, 1, 2, 4]Q := [1, 1, 2, 4](3.5)> Fan(Q)[[-1, -2, -4], [1, 0, 0], [0, 1, 0], [0, 0, 1]](3.6) > Q := [16, 24, 54, 27, 63, 32, 45, 56, 34, 84, 178, 236, 142, 266, 988, 1016]Q := [16, 24, 54, 27, 63, 32, 45, 56, 34, 84, 178, 236, 142, 266, 988, 1016](3.7) > RedQ := ReducedWeights(Q)*RedQ* := [16, 24, 54, 27, 63, 32, 45, 56, 34, 84, 178, 236, 142, 266, 988, 1016] (3.8) > Fan(O)(3.9) 7, 11, 0, 1, 8, 10, 4, 10, 12, 6, 2, 12, 8], [0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], [16, 14, 8, 11, 0, 1, 8, 10, 4, 10, 12, 6, 2, 12, 8], [0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [1, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0], [0, 0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0] 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0], Given a weights vector Q, determine the Q-canonical fan of P(Q)Given a weights vector Q, *QcanonicalFan* returns the Q-canonical fan of P(Q), as defined in [RT, 2.4]. > $Q canonicalFan := \mathbf{proc}(Q)$ local n, U1, U2, U3, SS, TT, VV, VV1, Q1, UU4, U4, VVV: $n \coloneqq nops(Q) - 1$: Q1 := [seq(Q[i], i=2..n+1), Q[1]]:U1 := LinearAlgebra[HermiteForm](Matrix([seq([Q1[i]], i=1..n+1)]), output=['U']): U2 := Matrix([seq(convert(Row(U1, i), list), i=2...n+1)]):U3 := LinearAlgebra[HermiteForm](U2, output = ['H']) :VV := convert(Transpose(U3), listlist) :VV1 := [VV[n+1], seq(VV[i], i=1...n)]:UU4 := Matrix[column](VV1): U4 := Transpose(UU4): VVV := convert(Transpose(U4), listlist) :VVVend proc:

Example:

- Fan(Q)
 [[-51, -48, -24, -39, -2, -6, -29, -34, -18, -43, -53, -28, -23, -100, -89], [16, (3.1.1)
 14, 7, 11, 0, 1, 8, 10, 4, 10, 12, 6, 2, 12, 8], [0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
 [16, 14, 8, 11, 0, 1, 8, 10, 4, 10, 12, 6, 2, 12, 8], [0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0], [0, 0, 0, 0],
 [0, 0, 0, 0, 0, 1, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0], [0, 0, 0, 0],
 [0, 0, 0, 0, 0, 1, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0], [0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 1, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0], [0, 0, 0, 0, 0],
 [0, 0, 0, 0, 0, 0, 1]]
- > MF := QcanonicalFan(Q)

0.c Given a weights vector Q and a polarization O(m), determine a polytope associated to (Q,m)

1. Transverse and weighted trasverse of a matrix

The *weighted transversion* is a process giving a matrix associated with the polytope of a minimally polarized wps when starting from a given fan of it [RT, 3.1]. Here this is realized by the procedure *WeightedTransverse*.

Let us first introduce some technical procedures. In the procedure *Matri*, *M* is a $n \times (n + 1)$ matrix, *j* an index with $1 \le j \le n + 1$ and *Matri*(*M*,*j*) is the matrix obtained by eliminating from *M* the *j*-th column.

>
$$Matri := \operatorname{proc}(M, j) \operatorname{local} n, Mi :$$

 $n := op(M) [1] : Mi := Minor(Matrix([[seq(1, k = 1 ..n + 1)], seq(convert(Row(M, i), list), i = 1 ..n)]), 1, j, output = ['matrix'])$
end proc:
Example:
> $M := Matrix([[1, 2, 5, 4], [3, 4, 2, 1], [5, 6, 7, 2]])$
 $M := \begin{bmatrix} 1 & 2 & 5 & 4 \\ 3 & 4 & 2 & 1 \\ 5 & 6 & 7 & 2 \end{bmatrix}$
(4.1.1)
> $Matri(M, 2);$

$$\begin{bmatrix} 1 & 5 & 4 \\ 3 & 2 & 1 \\ 5 & 7 & 2 \end{bmatrix}$$
(4.1.2)
The procedure Vzero eliminates the first column from a $n \times (n + 1)$ matrix by using Matri
> Vzero := proc(M) Matri(M, 1) end proc:
Example:
> Vzero(M)

$$\begin{bmatrix} 2 & 5 & 4 \\ 4 & 2 & 1 \\ 6 & 7 & 2 \end{bmatrix}$$
(4.1.3)
The procedure Transverse computes the transverse of a square matrix M, as defined in [RT,1.3]
> Transverse := proc(M) (LinearAlgebra[Transpose](M))^{-1} end proc:
Finally the procedure WeightedTransverse computing the weighted transverse matrix strating
from a fan V.
> WeightedTransverse := proc(V) local n, M, SS, QQ, de : n := nops(V) - 1 : M
:= Transpose(Matrix(V)) :
SS := [seq(Determinant(Matri(M, i), i = 1 ..n + 1)] :
QQ := [seq(abs(SS[i]), i = 1 ..n + 1)] : de := ilcm(op(QQ)) :
Transpose(MatrixInverse(Vzero(M))).Matrix(1 ..n, 1 ..n, de · Vector([seq($\frac{1}{QQ[j]}, j$
= 2.. $n + 1$)]), shape = diagonal) end proc:
Example:
> WeightedTransverse([[-2, -2], [3, 1], [0, 1]])
[2 - 1]
0 3]
(4.1.4)

2. Computing the polytope matrix

QpolMat(Q,m) computes a polytope matrix associated with (P(Q), O(m)), as defined in [RT, Thm.3.3], starting from a weights vector Q and a polarization m: if not expressed as an input, the value m = 1 is taken by default. *FpolMat* computes the same polytope matrix when starting from a fan.

> QpolMat := proc(Q, m :: integer := 1) local VQ : VQ := Fan(Q) : m • WeightedTransverse(VQ) end proc:

> $FpolMat := proc(V, m :: integer := 1) m \cdot WeightedTransverse(V) end proc:$

Examples:

F := Fan(Q) $F := [[-51, -48, -24, -39, -2, -6, -29, -34, -18, -43, -53, -28, -23, -100, -89], \quad (4.2.2)$ $[16, 14, 7, 11, 0, 1, 8, 10, 4, 10, 12, 6, 2, 12, 8], [0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], \quad (4.2.2)$

equal to 1 when not expressed as an input.

 > Qpolytope := proc(Q, m :: integer := 1) [[seq(0, i = 1..nops(Q) - 1)], op(convert(Transpose(QpolMat(Q, m)), listlist))]
 end proc:
 > Fpolytope := proc(fan, m :: integer := 1) [[seq(0, i = 1..nops(fan[1]))], op(convert(Transpose(FpolMat(fan, m)), listlist))] end proc:

Examples:

>

> Qpolytope([3, 2, 4])[[0, 0], [2, 0], [-1, 3]]

$$Q$$
[16, 24, 54, 27, 63, 32, 45, 56, 34, 84, 178, 236, 142, 266, 988, 1016] (4.3.2)

$$F := Fan(Q)$$

(4.3.1)

$$F := [[-51, -48, -24, -39, -2, -6, -29, -34, -18, -43, -53, -28, -23, -100, -89],$$
(4.3.3)
[16, 14, 7, 11, 0, 1, 8, 10, 4, 10, 12, 6, 2, 12, 8], [0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], (4.3.3)

0, 0], [0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0]0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0], [0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0], [0, 0, 0, 0] [0, 0, 0, 0, 0, 0, 0, 1]]> Qpolytope(Q)0, 0, 0], [-65609073133890, 0, 0, 95431379103840, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], [0, 0, 0, 0, 187880527610685, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], [-8350245671586, 0, 0, 0] 0, 133603930745376, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], [-53680150745910, 0, 0, 0, 0, 0, 0, 0] 107360301491820, 0, 0, 0, 0, 0, 0, 0, 0], [-110517957418050, 0, 0, 0, 0, 0, 0, 0] 71573534327880, 0, 0, 0, 0, 0, 0], [-21110171641650, 0, 0, 0, 0, 0, 0, 0, 0, 0] 33776274626640, 0, 0, 0, 0, 0], [-19106494333290, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0] 5917496932620]] > Fpolytope(F, 4)[[0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], [501014740295160, 0, -1002029480590320, 0, **(4.3.5)**] 0, 0], [0, 0, 0, 0, 751522110442740, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0], [-33400982686344, 0, 0, 0, 0, 534415722981504, 0, 0, 0, 0, 0, 0, 0, 0, 0], [-214720602983640, 0, 0, 0, 707314927475520, 0, 0, 0, 0, 0, 0, 0], [-71573534327880, 0, 0, 0, 0, 0, 0, 0, 0, 0] 135105098506560, 0, 0, 0, 0, 0], [-76425977333160, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0] 101901303110880, 0, 0, 0, 0], [-63508910741640, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0] 23669987730480]]

1. Given a fan, say if it is associated to P(Q) for some Q

Let us now introduce the procedures recognizing the fan of a wps following Section 2 in [RT].

1. Recognizing an admissible fan

IsWPSFan determines if a given list of n + 1 vectors in \mathbb{Z}^n generates a fan of a wps, by checking <u>condition</u> (3) in [RT, Thm.2.1].

> IsWPSFan := proc(V)local n, MM, SS, TT, co, i: n := nops(V[1]): MM := Transpose(Matrix(V)): SS := [seq(Determinant(Matri(MM, i)), i=1..n+1)]:TT := [seq(abs(SS[i]), i=1..n+1)]:co := 0: for *i* from 1 to n + 1 do if SS[i] = 0 then co := 1 end if end do: if co = 0 and igcd(op(TT)) = 1 and $add(TT[i] \cdot V[i], i = 1 ... n + 1) = [seq(0, i = 1)]$..*n*)] then *true* else *false* end if: end proc: **Examples:** > V := [[2, 4, 1, 2], [2, 1, 2, 2], [4, 5, 6, 1], [7, 7, 1, 1], [0, 0, 0, 1]]V := [[2, 4, 1, 2], [2, 1, 2, 2], [4, 5, 6, 1], [7, 7, 1, 1], [0, 0, 0, 1]](5.1.1)> IsWPSFan(V)false (5.1.2)> V1 := [[-2, -4, -1, -2], [2, 1, 2, 2], [4, 5, 6, 1], [7, 7, 1, 1], [0, 0, 0, 1]]VI := [[-2, -4, -1, -2], [2, 1, 2, 2], [4, 5, 6, 1], [7, 7, 1, 1], [0, 0, 0, 1]](5.1.3)> IsWPSFan(V1) false (5.1.4)> V0 := [[-2, -4, -1, -2], [1, 0, 0, 0], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]]V0 := [[-2, -4, -1, -2], [1, 0, 0, 0], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]](5.1.5)> *IsWPSFan(V0)* (5.1.6)true > V := Fan([5, 3, 2, 2, 4, 16])V := [[-3, -1, -1, -2, -5], [5, 1, 1, 2, 3], [0, 1, 0, 0, 0], [0, 0, 1, 0, 0], [0, 0, 0, 1, 0], [0, 0, 0, 1, 0], [0, 0, 0, 1, 0], [0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0(5.1.7)[0, 0, 0, 0, 1]]> IsWPSFan(V)(5.1.8)true

2. Determining the weights vector Q

By using *IsWPSFan* the following procedure *FWeights* recognizes the fan of a wps P(Q) and compute the weights vector Q.

FWeights := proc(V) local n, MM, SS, TT: if IsWPSFan(V) = false then error "It is not a fan of a WPS" else n := nops(V[1]) : MM := Transpose(Matrix(V)) : SS := [seq(Determinant(Matri(MM, i)), i = 1 ..n + 1)]: TT := [seq(abs(SS[i]), i = 1 ..n + 1)]: TT end if

end proc: **Examples:** > V1 [[-2, -4, -1, -2], [2, 1, 2, 2], [4, 5, 6, 1], [7, 7, 1, 1], [0, 0, 0, 1]](5.2.1)FWeights(V1) (in FWeights) It is not a fan of a WPS V0[[-2, -4, -1, -2], [1, 0, 0, 0], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]](5.2.2)FWeights(V0) [1, 2, 4, 1, 2](5.2.3)Q := [3, 2, 7, 181, 22]:V := Fan(O);V := [[-2, -3, -61, -8], [3, 1, 1, 1], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]](5.2.4)> FWeights(V) [3, 2, 7, 181, 22] (5.2.5)3. Given a weights vector Q and a fan, say if the latter is a fan of P **(Q)** The following procedure IsFanQ answers the question if a given fan V defines the wps of given weights Q. > IsFanO := proc(V, O)**local** *Q1* : Q1 := FWeights(V): if $\{op(Q)\} = \{op(Q1)\}$ then true else false end if end proc: **Examples:** > Q := [3, 2, 7, 181, 22]:> V := Fan(Q);V := [[-2, -3, -61, -8], [3, 1, 1, 1], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]](5.3.1)> IsFanO(V, O)(5.3.2)true Q1 := [181, 22, 2, 7, 3]

$$QI := [181, 22, 2, 7, 3]$$

$$QI := [181, 22, 2, 7, 3]$$
(5.3.3)

$$Q2 := [3, 2, 4, 8, 1] Q2 := [3, 2, 4, 8, 1] IsFanQ(V, Q2) false (5.3.6)$$

2. Given a polytope, say if it is associated to P(Q) for some QLet us then pass to the *recognition process* for polytopes defining a polarized wps (P(Q), O(m)).

1. Technicalities

Given a square matrix *W* with coprime entries, the following procedure *WPP* computes a list containing

1) the list of associated pseudo-weights, which are effective weights when the columns of W and the origin are the vertices of a polytope defining a polarized wps, 2) the what of W as defined in [PT. Def. 2 10]

2) the *what* of *W* as defined in [RT, Def. 3.10],

3) the associated pseudo-fan, which for general W may be gnerated by *rational* vectors in Q^n , <u>4</u>) the associated polarization.

>
$$WPP := \operatorname{proc}(W1)$$

 $\operatorname{local} W, m, M, n, M1, i, KK, M2, IQ, qzero, deQ, M12, vzero, fan3 :
 $m := igcd(op(convert(W1, list))) :$
 $W := \frac{1}{m} \cdot W1 :$
 $n := op(W) [1] :$
 $M := convert(sign(Determinant(W)) \cdot Adjoint(W), listlist) :$
 $M1 := [] : \operatorname{for} i \operatorname{from} 1 \operatorname{to} n \operatorname{do} KK := igcd(op(M[i])) :$
 $M1 := [op(M1), \frac{1}{KK} \cdot M[i]] :$
 $end \operatorname{do}: M12 := Matrix(M1) :$
 $M2 := Transpose(M12) :$
 $IQ := convert(M12.W, listlist) :$
 $qzero := \operatorname{abs}(Determinant(M2)) :$
 $deQ := ilcm(qzero, seq(IQ[k, k], k = 1 ..n)) :$
 $vzero := -\frac{1}{qzero} \cdot add \left(\frac{deQ}{IQ[r, r]} \cdot M1[r], r = 1 ..n \right) :$
 $fan3 := [vzero, op(M1)] :$
 $\left[\left[qzero, seq \left(\frac{deQ}{IQ[h, h]}, h = 1 ..n \right) \right], M2, fan3, m \right]$
end proc:$

The different outputs of *WPP* will be individually recalled in the following by using the <u>_</u>following procedures:

 \rightarrow WPseudoWeights := proc(W) WPP(W) [1] end proc:

> $What := \mathbf{proc}(W) WPP(W) [2]$ end proc:

 \rightarrow PseudoFan := proc(W) WPP(W) [3] end proc:

> *Polarization* := **proc**(*W*) *WPP*(*W*) [4] **end proc**:

Examples

> WW := RandomMatrix(3, 3)

$$WW := \begin{bmatrix} 27 & 99 & 92 \\ 8 & 29 & -31 \\ 69 & 44 & 67 \end{bmatrix}$$
(6.1.1)

 \blacktriangleright WPP(WW)

$$107088635536, 327244, 327244, 327244], \begin{bmatrix} -3307 & 2675 & 1649 \\ 2585 & 4539 & -5643 \\ 5737 & -1573 & 9 \end{bmatrix}, \begin{bmatrix} -\frac{1017}{327244}, \text{ (6.1.2)} \end{bmatrix}$$

 $\frac{1481}{327244}$, $-\frac{4173}{327244}$, [-3307, 2585, 5737], [2675, 4539, -1573], [1649, -5643,

 $\begin{bmatrix} 9 \\ 9 \end{bmatrix}, 1 \end{bmatrix}$ WW2 := QpolMat([2, 2, 7, 4, 3, 14]) $WW2 := \begin{bmatrix} 42 & -6 & 0 & -14 & 0 \\ -42 & 12 & 0 & 0 & 0 \\ 0 & 0 & 21 & 0 & 0 \\ 0 & 0 & 0 & 28 & 0 \\ 0 & 0 & 0 & 0 & 6 \end{bmatrix}$ WPP(WW2) $\begin{bmatrix} 2 & 2 & 0 & 0 & 0 \\ 1 & 2 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 1 & 1 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{bmatrix}, [[-9, -8, -2, -6, -7], [2, 1, 0, 1, 0], [2, 2, 0, 1, (6.1.4)]$ 0], [0, 0, 1, 0, 0], [0, 0, 0, 1, 0], [0, 0, 0, 0, 1]], 1

2. Admissible matrices

The following procedure says if a given matrix is *P*-admissible [RT, Def. 3.8] i.e. if it is the weighted transverse matrix of a wps fan. This is done by checking that the obtained pseudo-fan is <u>a</u>ctually a fan generated by integer vectors.

> IsAdmissible := proc(W) local V, r, i: V := PseudoFan(W) [1]: r := 0: for i from 1 to nops(V) do if floor(V[i]) $\neq V[i]$ then r := 1 end if: end do: if r = 1 then false else true end if end proc: Examples > WW := RandomMatrix(3, 3) $WW := \begin{bmatrix} 57 & -76 & -32 \\ 27 & -72 & -74 \\ -93 & -2 & -4 \end{bmatrix}$ (6.2.1) > IsAdmissible(WW) false
(6.2.2) > WW2 := QpolMat([2, 2, 7, 4, 3, 19])

$$WW2 := \begin{bmatrix} 798 & -114 & 0 & -266 & -42 \\ -798 & 228 & 0 & 0 & 0 \\ 0 & 0 & 399 & 0 & 0 \\ 0 & 0 & 0 & 532 & 0 \\ 0 & 0 & 0 & 0 & 84 \end{bmatrix}$$
(6.2.3)
> IsAdmissible(WW2)
true (6.2.4)

3. Recognizing an admissible polytope

The following procedure recognizes a polytope defining a polarized wps by running the previous procedure on the associated polytope matrix.

 $IsPAdmissible := \mathbf{proc}(P)$ local W, m : $W := PolytopeMatrix(P) : \mathbf{m} := igcd(op(convert(W, list))) : IsAdmissible\left(\frac{1}{m} \cdot W\right)$ end proc: **Examples** > P := [[2, 4, 5], [6, 6, 1], [3, 1, 2], [5, 1, 1]]P := [[2, 4, 5], [6, 6, 1], [3, 1, 2], [5, 1, 1]](6.3.1)*IsPAdmissible*(*P*) false (6.3.2)> Q := [2, 2, 7, 4, 3, 19]:> PP2 := Opolytope(Q)PP2 := [[0, 0, 0, 0, 0], [798, -798, 0, 0, 0], [-114, 228, 0, 0, 0], [0, 0, 399, 0, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0(6.3.3)-266, 0, 0, 532, 0], [-42, 0, 0, 0, 84]] > IsPAdmissible(PP2)(6.3.4)true > $mPP2 := [seq(3 \cdot PP2[i], i=1 ..nops(PP2))]$ mPP2 := [[0, 0, 0, 0, 0], [2394, -2394, 0, 0, 0], [-342, 684, 0, 0, 0], [0, 0, 1197, 0, 0], (6.3.5)[-798, 0, 0, 1596, 0], [-126, 0, 0, 0, 252]] > *IsPAdmissible(mPP2)* (6.3.6)true > PP20 := [seq(PP2[i] + [1, 1, 1, 1], i = 1..nops(PP2))]PP20 := [[1, 1, 1, 1, 1], [799, -797, 1, 1, 1], [-113, 229, 1, 1, 1], [1, 1, 400, 1, 1], [(6.3.7)-265, 1, 1, 533, 1], [-41, 1, 1, 1, 85]] IsPAdmissible(PP20) (6.3.8)true

4. Determining the associated weights vector, fan and polarization

The following procedures *PPolarization*, *PWeights* and *PFan* recognize the polytope of a polarized wps, by using *IsAdmissible*, and in the affermative case return the polarization m, the weights vector Q and a fan of P(Q), respectively. The last two outputs are obtained by running *WPP*.

> PPolarization := proc(P) local W, W1, m : $W1 := PolytopeMatrix(P) : \mathbf{m} := igcd(op(convert(W1, list))) : W := \frac{1}{2} \cdot W1 :$ **if** IsAdmissible(W) = false **then error** "It is not an admissible polytope" else *m* end if end proc: > PWeights := proc(P)local W, W1, m : $W1 := PolytopeMatrix(P) : m := igcd(op(convert(W1, list))) : W := \frac{1}{2} \cdot W1 :$ **if** IsAdmissible(W) = false **then error** "It is not an admissible polytope" else *WPseudoWeights(W)* end if end proc: > PFan := proc(P)local W, W1, m : $W1 := PolytopeMatrix(P) : m := igcd(op(convert(W1, list))) : W := \frac{1}{2} \cdot W1 :$ **if** *IsAdmissible*(*W*) = *false* **then error** "It is not an admissible polytope" else *PseudoFan(W)* end if end proc: Examples > P := [[3, 5, 1], [8, 9, 2], [12, 6, 4], [4, 1, 5]]P := [[3, 5, 1], [8, 9, 2], [12, 6, 4], [4, 1, 5]](6.4.1)> PW eights(P)ror, (in PWeights) It is not an admissible polytope > Q[2, 2, 7, 4, 3, 19](6.4.2)> PP2 := Opolytope(Q)PP2 := [[0, 0, 0, 0, 0], [798, -798, 0, 0, 0], [-114, 228, 0, 0, 0], [0, 0, 399, 0, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 10, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0(6.4.3)-266, 0, 0, 532, 0], [-42, 0, 0, 0, 84]] > *PPolarization*(*PP2*) 1 (6.4.4)> *PWeights*(*PP2*) [2, 2, 7, 4, 3, 19](6.4.5)> PF := PFan(PP2)PF := [[-9, -8, -2, -6, -14], [2, 1, 0, 1, 1], [2, 2, 0, 1, 1], [0, 0, 1, 0, 0], [0, 0, 0, 1], [0, 0, 0, 1], [0, 0, 0, 1], [0, 0, 0, 1], [0, 0, 0, 0], [0, 0, 0, 1], [0, 0, 0], [0, 0, 0, 1], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0, 0], [0,(6.4.6)0], [0, 0, 0, 0, 1]] > PP20 := [seq(PP2[i] + [1, 1, 1, 1, 1], i = 1..nops(PP2))]*PP20* := [[1, 1, 1, 1, 1], [799, -797, 1, 1, 1], [-113, 229, 1, 1, 1], [1, 1, 400, 1, 1], [(6.4.7) -265, 1, 1, 533, 1], [-41, 1, 1, 1, 85]] > *PWeights*(*PP20*) [2, 2, 7, 4, 3, 19](6.4.8)PPolarization(PP20) 1 (6.4.9) $\begin{array}{c} > PFan(PP20) \\ [[-9, -8, -2, -6, -14], [2, 1, 0, 1, 1], [2, 2, 0, 1, 1], [0, 0, 1, 0, 0], [0, 0, 0, 1, 0], [0, (6.4.10) \\ 0, 0, 0, 1]] \\ > PWeights(mPP2) \\ [2, 2, 7, 4, 3, 19] \\ (6.4.11) \\ \hline \\ > PFan(mPP2) \\ [[-9, -8, -2, -6, -14], [2, 1, 0, 1, 1], [2, 2, 0, 1, 1], [0, 0, 1, 0, 0], [0, 0, 0, 1, 0], [0, (6.4.12) \\ 0, 0, 0, 1]] \\ \hline \\ > PPolarization(mPP2) \\ \hline \\ \end{array}$

3. Equivalences

In the following two fans are said equivalent if they defines isomorphic wps's. Analogously two polytopes are said equivalent if they defines isomorphic polarized wps's, meaning that two polytopes giving different polarizations on the same wps are not considered equivalent. We will give several procedures which are able to determine the equivalence of fans and polytopes and to give concrete transformations connecting equivalent toric data.

1. Equivalent fans

The following procedure establishes if two fans are associated to the same reduced weights vector Q. First it checks if the input fans are admissible, by using *IsWPSFan*, then it compares the associated reduced weights vectors.

```
> AreEquivalentFans := proc(fan1, fan2)
       local W1, W2 :
       if IsWPSFan(fan1) = false then error "The first one is not a fan of a WPS"
       else if IsWPSFan(fan2) = false then error "The second one is not a fan of a WPS"
       else W1 := sort(ReducedWeights(FWeights(fan1))) : W2
             := sort(ReducedWeights(FWeights(fan2))):
       if W1 = W2 then true else false end if
       end if end if
       end proc:
 Examples
 > fan1 := [[3, 5, 1], [8, 9, 2], [12, 6, 4], [4, 1, 5]]
                          fan1 := [[3, 5, 1], [8, 9, 2], [12, 6, 4], [4, 1, 5]]
                                                                                                                     (7.1.1)
 > IsWPSFan(fan1)
                                                       false
                                                                                                                     (7.1.2)
    fan2 := [[5, 2, 1], [6, 7, 5], [4, 9, 1], [8, 0, 0]]
                           fan2 := [[5, 2, 1], [6, 7, 5], [4, 9, 1], [8, 0, 0]]
                                                                                                                     (7.1.3)
 SWPSFan(fan2) false 
 fan3 := Fan([3, 1, 5, 4]) 
 fan3 := [[-1, -2, -2], [3, 1, 2], [0, 1, 0], [0, 0, 1]] 
 fan4 := Fan([7, 2, 1, 6]) 
 fan4 := [[-2, -1, -2], [7, 3, 4], [0, 1, 0], [0, 0, 1]] 
 fan4 := [[-2, -1, -2], [7, 3, 4], [0, 1, 0], [0, 0, 1]] 
 fan4 := [[-2, -1, -2], [7, 3, 4], [0, 1, 0], [0, 0, 1]] 
                                                                                                                     (7.1.4)
                                                                                                                     (7.1.5)
                                                                                                                     (7.1.6)
      fan5 := Fan([5, 9, 3, 12])
                                                                                                                      - - -
```



> L2 := [3, 5, 1, 1, 3, 3, 7]: for *i* from 1 to 7 do print([i, perm(L1, L2, i)]) end do: [1, 3][2, 4][3, 2][4, 1][5, 5][6, 7][7, 6] (7.1.1.8) > L3 := [seq(L2[perm(L1, L2, i)], i = 1..nops(L1))]L3 := [1, 1, 5, 3, 3, 7, 3](7.1.1.9) *PermCol(M, \sigma)* permutes the columns of the matrix *M* according to the permutation σ ; *PermMat*(n,σ) is the $n \times n$ permutation matrix corresponding to σ . > $PermCol := proc(M, \sigma)$ local Ml : Ml := convert(Transpose(M), listlist) :*Transpose* (*Matrix*($[seq(M1[\sigma(i)], i=1..nops(M1))]$)) end proc: > $PermMat := \mathbf{proc}(n, \sigma) PermCol(Matrix(n, shape = identity), \sigma)$ end proc: **Examples** > $\sigma := \operatorname{proc}(i)$ if i = 1 then 3 else if i = 2 then 4 else if i = 3 then 2 else if i = 4 then 4 fi fi fi fi end proc: > M := RandomMatrix(2, 4) $M := \left[\begin{array}{rrrr} 45 & -38 & 87 & -98 \\ -81 & -18 & 33 & -77 \end{array} \right]$ (7.1.1.10)• $PermCol(M, \sigma)$

 87
 -98
 -38
 -98

 33
 -77
 -18
 -77

 (7.1.1.11)> PermMat(4, σ) (7.1.1.12)Given two equivalent fans fan1 and fan2, let RedFan1 and RedFan2 their reductions. The procedure FSwitchMatrices computes matrices α , β , γ , δ such that • α and β are diagonal matrices with positive integer entries such that $FanMatrix(fan1) = \alpha \cdot FanMatrix(RedFan1)$ and $FanMatrix(fan2) = \beta \cdot FanMatrix(RedFan2)$. • γ is an invertible integer matrix and δ is a permutation matrix such that $FanMatrix(RedFan2) = \gamma \cdot FanMatrix(RedFan1) \cdot \delta$, according with [RT, Prop.2.7]. > FSwitchMatrices := proc(fan1, fan2)local K1, K2, α , β , γ , δ , W1, W2, RW1, RW2, F, RedFan1, RedFan2, V1, V2, Vzero1, Vzero2:

if AreEquivalentFans(fan1, fan2) = false then error "The two fans are not equivalent" else K1 := [seq(igcd(op(fan1[i])), i=1..nops(fan1))]: K2:= [seq(igcd(op(fan2[i])), i=1..nops(fan2))]: $\alpha := Matrix(Vector(K1), shape = diagonal) : \beta := Matrix(Vector(K2), shape)$ = diagonal) : W1 := FWeights(fan1) : W2 := FWeights(fan2) :RW1 := ReducedWeights(W1); RW2 := ReducedWeights(W2) : $F := \mathbf{proc}(i) \ perm(RW1, RW2, i)$ end proc: $\delta := PermCol(Matrix(nops(fan1), shape = identity), F)$: RedFan1 := ReducedFan(fan1) : RedFan2 := ReducedFan(fan2) :V1 := FanMatrix(RedFan1) : V2 := FanMatrix(RedFan2) : $Vzero1 := Vzero(V1) : Vzero2 := Vzero(V2.\delta) :$ $\gamma := Vzero1.MatrixInverse(Vzero2)$: $|\alpha, \beta, \gamma, \delta|$ end if: end proc: Examples > B := RandomMatrix(7)70 42 -67 -95 65 31 -2 -32 18 22 -20 86 -50 50 -1 -59 14 -25 20 -80 10 $B := \begin{bmatrix} 52 & 12 & 16 & 51 & -61 \end{bmatrix}$ 43 -16 (7.1.1.13)

 -13
 -62
 9
 76
 -48
 25
 -9

 82
 -33
 99
 -44
 77
 94
 -50

 60 24 9 12 -22 > C := HermiteForm(B, output = U');*C* := [[59523579227, 97498373629, 210296252447, 234258218556, (7.1.1.14)151884931336, 97390657747, -264296715696], [1871447117, 3065391104, 6611805279, 7365179874, 4775328039, 3062004470, -8309603237], [48093966353, 78776907600, 169915536342, 189276367911, 122720254260, 78689875132, -213546925722], [49139979620, 80490255380, 173611091497, 193393008874, 125389341961, 80401330011, -218191435925], [56152476216, 91976577642, 198386176826, 220991062982, 143282966266, 91874962222, -249328337355], [2246013516, 3678923005, 7935144887, 8839305901, 5731100399, 3674858543, -9972753712], [67456847740, 110492900968, 238324416405, 265480019619, 172128067905, 110370828775, -299522030436]] *Determinant*(*C*)

0 0 0 0 0 1 0 0 491 1744 762 -551 225 -235 -803 0 0 0 0 0 0 1 0 85 51 -52 57 -6 -23 -120 0 1 0 0 0 0 0 0 114 354 166 -82 0 -61 -167 0 0 0 0 0 0 0 1 144 309 249 -177 138 -3 -299 0 0 0 1 0 0 0 0 -75 -390 300 986 334 -437 217 1 0 0 0 0 0 0 0 241 612 -11 -551 335 82 -102 0 0 0 0 1 0 0 0 167 543 265 -234 111 -99 -270 $0 \ 0 \ 1 \ 0 \ 0 \ 0 \ 0$ > fan77 := [[-29, -1, -6, -6, -16, -9, -10], [12, 0, 2, 2, 6, 2, 4], [0, 1, 0, 0, 0, 0]0], [18, 0, 4, 3, 9, 3, 6], [0, 0, 0, 1, 0, 0, 0], [0, 0, 0, 0, 1, 0, 0], [0, 0, 0, 0, 0, 1, 0], [0, 0, 0, 0, 0, 0, 1]] fan77 := [[-29, -1, -6, -6, -16, -9, -10], [12, 0, 2, 2, 6, 2, 4], [0, 1, 0, 0, 0, 0, (7.1.1.22)]0], [18, 0, 4, 3, 9, 3, 6], [0, 0, 0, 1, 0, 0, 0], [0, 0, 0, 0, 1, 0, 0], [0, 0, 0, 0, 0, 0] [1, 0], [0, 0, 0, 0, 0, 0, 1]]> $fan88 := [seq(i \cdot F8[i], i=1..8)]$ fan88 := [[-9905176817293, -311423050140, -8003202205882,(7.1.1.23)-8177266778230, -9344199607473, -373753751016, -11225333104614],[6903915234700, 217062085812, 5578237587754, 5699560717570, 6512913723406, 260506628328, 7824065098992], [292495120887, 9196173312, 236330722800, 241470766140, 275929732926, 11036769015, 331478702904], [841185009788, 26447221116, 679662145368, 694444365988, 793544707304, 31740579548, 953297665620], [1171291092780, 36825899370, 946381839555, 966965044370, 1104955314910, 44196529505, 1327400098095], [911309588016, 28651968234, 736321525560, 752336051766, 859697797596, 34386602394, 1032768407430], [681734604229, 21434031290, 550829125924, 562809310077, 643124735554, 25724009801, 772595801425], [-2114373725568, -66476825896, -1708375405776, -1745531487400,-1994626698840, -79782029696, -2396176243488]] > *FSwitchMatrices*(*fan7*, *fan8*) $1 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0$ 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 (7.1.1.24)0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1

2. Equivalent polytopes

The following procedure establishes if two polytopes are associated with isomorphic polarized wps's. First it checks if the input polytopes are admissible, by using *IsPadmissible*, then it compares the associated weights vectors and the associated polarizations.

> AreEquivalentPols := proc(pol1, pol2) **local** *W1*, *W2*: **if** *IsPAdmissible*(*pol1*) = *false* **then error** "The first one is not admissible" : else if *IsPadmissible*(*pol2*) = *false* then error "The second one is not admissible" : else W1 := sort(PWeights(pol1)) : W2 := sort(PWeights(pol2)) :if Wl = W2 and PPolarization(pol1) = PPolarization(pol2) then true else false end if end if end if end proc: **Examples** > Q [6, 8, 6, 7, 7, 9, 25, 2](7.2.1)> P1 := Qpolytope(Q);PI := [[0, 0, 0, 0, 0, 0, 0], [1050, 0, -4725, 0, 0, 0, 0], [0, 2100, 0, 0, 0, 0, 0], [-300, 0, (7.2.2)]1800, 0, 0, 0, 0], [-300, 0, 0, 1800, 0, 0, 0], [-700, 0, 0, 0, 1400, 0, 0], [-84, 0, 0, 0, 0, 504, 0, [-2100, 0, 0, 0, 0, 0, 6300]] > Q1 [9, 25, 8, 2, 7, 6, 7, 6](7.2.3)> P2 := Opolytope(O1);P2 := [[0, 0, 0, 0, 0, 0], [56, 0, 0, 0, 0, 0], [-700, 1575, 0, 0, 0, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [(7.2.4)6300, 0, 0, 0, 0], [-1600, 0, 0, 1800, 0, 0, 0], [-700, 0, 0, 0, 2100, 0, 0], [-1600, 0, 0, 0, 0, 1800, 0], [-700, 0, 0, 0, 0, 0, 0, 2100]]

AreEquivalentPols(*P1*, *P2*) true (7.2.5)**>** fan3 [[-1, -2, -2], [3, 1, 2], [0, 1, 0], [0, 0, 1]](7.2.6)fan5 [[-9, -6, -6], [5, 3, 2], [0, 1, 0], [0, 0, 1]](7.2.7)> P3 := Fpolytope(fan3)P3 := [[0, 0, 0], [20, 0, 0], [-4, 12, 0], [-10, 0, 15]](7.2.8) $P5 \coloneqq Fpolytope(fan5)$ P5 := [[0, 0, 0], [4, 0, 0], [-36, 60, 0], [-6, 0, 15]](7.2.9)*AreEquivalentPols*(*P3*, *P5*) true (7.2.10)P30 := [seq(P3[i] + [1, 1, 2], i = 1..nops(P3))]P30 := [[1, 1, 2], [21, 1, 2], [-3, 13, 2], [-9, 1, 17]](7.2.11)AreEquivalentPols(P5, P30) (7.2.12)true $mP3 := [seq(3 \cdot P3[i], i=1 ..nops(P3))]$ mP3 := [[0, 0, 0], [60, 0, 0], [-12, 36, 0], [-30, 0, 45]](7.2.13)AreEquivalentPols(P5, mP3) (7.2.14)false **Compute switching data connecting equivalent polytopes** Given two equivalent polytopes *pol1* and *pol2*, let *CP1* and *CP2* be the $n \times n + 1$ matrices whose columns are given by vertices of *pol1* and *pol2*, respectively. The procedure PSwitchMatrices computes matrices θ , δ and a vector v such that • θ is an invertible $n \times n$ matrix (it is the transverse of the matrix α in the procedure FSwitchMatrices); • δ is an $(n+1) \times (n+1)$ permutation matrix (it is the same matrix δ given by the procedure FSwitchMatrices); • v is a vector in Z^n , • and finally $\theta \cdot CP2 \cdot \delta + v = CP1$, according with [RT, Prop.3.21]. > PSwitchMatrices := proc(pol1, pol2)**local** F1, F2, δ, CP1, CP2, CCP1, pol3, CP3, θ, v : **if** *AreEquivalentPols*(*pol1*, *pol2*) = *false* **then** error "The two polytopes are not equivalent" else F1 := PFan(pol1) : F2 := PFan(pol2) : $\theta := MatrixInverse(Transpose(FSwitchMatrices(F1, F2)[3]))$: $\delta := FSwitchMatrices(F1, F2)[4]:$ CP1 := Transpose(Matrix(pol1)): CP2 := Transpose(Matrix(pol2)): $CCP1 := \theta.CP2.\delta$: $v \coloneqq poll[1] - convert(Column(CCP1, 1), list) :$ pol3 := [seq(convert(Transpose(CCP1), listlist)[i] + v, i = 1..nops(F1))]:CP3 := Transpose(Matrix(pol3)): $[\theta, \delta, v]$

end if: end proc: Example > $PP3 \coloneqq Fpolytope(fan3)$ PP3 := [[0, 0, 0], [20, 0, 0], [-4, 12, 0], [-10, 0, 15]](7.2.1.1)> PP5 := Fpolytope(fan5)PP5 := [[0, 0, 0], [4, 0, 0], [-36, 60, 0], [-6, 0, 15]](7.2.1.2)> P2 [[0, 0, 0, 0, 0, 0], [56, 0, 0, 0, 0, 0], [-700, 1575, 0, 0, 0, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700, 0], [-700,(7.2.1.3)6300, 0, 0, 0, 0], [-1600, 0, 0, 1800, 0, 0, 0], [-700, 0, 0, 0, 2100, 0, 0], [-1600, 0, 0, 0, 0, 1800, 0], [-700, 0, 0, 0, 0, 0, 2100]] > PSM := PSwitchMatrices(PP3, PP5) $PSM := \begin{bmatrix} 1 & 1 & 0 \\ -3 & -2 & -2 \\ 0 & 0 & 1 \end{bmatrix}, \begin{bmatrix} 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, \begin{bmatrix} -4, 12, 0 \end{bmatrix}$ (7.2.1.4)> CP1 := Transpose(Matrix(PP3)); CP2 := Transpose(Matrix(PP5)); $CP1 := \begin{bmatrix} 0 & 20 & -4 & -10 \\ 0 & 0 & 12 & 0 \\ 0 & 0 & 0 & 15 \end{bmatrix}$ $CP2 := \begin{bmatrix} 0 & 4 & -36 & -6 \\ 0 & 0 & 60 & 0 \\ 0 & 0 & 0 & 15 \end{bmatrix}$ (7.2.1.5)> P3 := [seq(convert(Transpose(PSM[1].CP2.PSM[2]), listlist)[i] + PSM[3], i = 1]...*nops*(*PP3*))]: evalb(P3 = PP3)(7.2.1.6)true

4. Cohomology

Finally we want end up this collection of procedures on wps, by computing the cohomology of line bundles and sheaves of holomorphic forms. It is a well known fact that such a computation for toric varieties reduces to a count of lattice points in a polytope.

1. Lattice points in a polytope

Given a polytope *pol*, the following procedure *PPP* computes a list of two vectors: *Lm* is the vector of the smallest coordinates of the points in *pol*, *LM* is the vector of the greatest coordinates in *pol*.

> *PPP* := **proc**(*pol*) **local** *n*, *m*, *M*, *Lm*, *LM*, *i* : *n* := *nops*(*pol*[1]) :

 $m := \mathbf{proc}(i) \min(seq(pol[j][i], j=1..n+1))$ end proc: $M := \mathbf{proc}(i) \max(seq(pol[j][i], j=1..n+1))$ end proc: Lm := []:for *i* from 1 to *n* do Lm := [op(Lm), m(i)]: end do: LM := []: for *i* from 1 to *n* do LM := [op(LM), M(i)]: end do: [Lm, LM]end proc: Example > Pol := [[2, 3, 5], [-1, 4, 6], [3, 2, 5], [4, 2, 8]]:> PPP(Pol)[[-1, 2, 5], [4, 4, 8]](8.1.1)The following procedure determines the polytope, called the *reduced polytope*, whose vertices _are obtained by reducing the vertices of a given polytope. > RedPol := proc(pol) $\mathbf{local} rr: rr := igcd(seq(igcd(op(pol[i])), i=1..nops(pol))): \left[seq\left(\frac{1}{rr} \cdot pol[i], i\right)\right]$ =1..nops(pol) : end proc: $\rightarrow RedPol([[4, 6, 10], [-4, 8, 12]])$ [[2, 3, 5], [-2, 4, 6]](8.1.2)The following procedures determines points which either belongs or are internal to a a given polytope. Namely *IsInPolytope(point,pol)* is *true* if the integer *point* belongs to the polytope *pol*, *false* otherwise, while *IsInternal(point,pol)* verifies if the *point* is internal to the polytope *pol*: > IsInPolytope := proc(point, pol)local P1, F, X, L, i, co, A, AA, M, n, newpoint, newpol : n := nops(pol[1]):M := PolytopeMatrix(pol): newpol := [[seq(0, t=1..n)], seq(pol[k] - pol[1], k=2..n+1)]:newpoint := point - pol[1]:A := convert(sign(Determinant(M)).Adjoint(M), listlist) :AA := [-add(A[r], r=1..nops(A)), op(A)]:X := Vector(newpoint);L := [DotProduct(X - Vector(newpol[2]), Vector(AA[1]))]:for *i* from 2 to nops(AA) do L := [op(L), DotProduct(X, Vector(AA[i]))]: end do: co := 0: for *i* from 1 to nops(L) do if L[i] < 0 then co := 1: end if end do: **if** *co* = 0 **then** *true* **else** *false* end if end proc: > IsInternal := proc(point, pol) local P1, F, X, L, i, co, A, AA, M, n, newpoint, newpol : $n \coloneqq nops(pol[1])$: M := PolytopeMatrix(pol): newpol := [[seq(0, t=1..n)], seq(pol[k] - pol[1], k=2..n+1)]:newpoint := point - pol[1]: $A \coloneqq convert(sign(Determinant(M))).Adjoint(M), listlist) :$ AA := [-add(A[r], r=1..nops(A)), op(A)]:X := Vector(newpoint);L := [DotProduct(X - Vector(newpol[2]), Vector(AA[1]))]:for *i* from 2 to nops(AA) do L := [op(L), DotProduct(X, Vector(AA[i]))]: end do: co := 0: for *i* from 1 to nops(L) do if $L[i] \le 0$ then co := 1: end if end do:

if *co* = 0 **then** *true* **else** *false* end if end proc: Examples > Q := [2, 5, 7, 5, 2]:> Pol := Qpolytope(Q); Pol := [[0, 0, 0, 0], [7, 0, 0, 0], [-5, 10, 0, 0], [-7, 0, 14, 0], [0, 0, 0, 35]](8.1.3)> IsInPolytope([0, 0, 0, 0], Pol)true (8.1.4) > IsInternal([0, 0, 0, 0], Pol)false (8.1.5)> IsInPolytope([0, 1, 0, 0], Pol)(8.1.6) true > IsInternal([0, 1, 0, 0], Pol)(8.1.7) false > IsInPolytope([0, 1, 1, 1], Pol)true (8.1.8)> *IsInternal*([0, 1, 1, 1], *Pol*) (8.1.9) true > IsInPolytope([0, -1, 0, 10], Pol)false (8.1.10)> Pol := [[0, 0, 0], [2, 0, 0], [0, 5, 0], [0, 0, 12]]Pol := [[0, 0, 0], [2, 0, 0], [0, 5, 0], [0, 0, 12]](8.1.11)*IsInPolytope*([1, 1, 1], *Pol*) true (8.1.12) > *IsInternal*([0, 1, 0], *Pol*) false (8.1.13)The procedure *PointsInPol* computes the number of points belonging to the polytope and a list of such points, by using procedures PPP and IsInPolytope; the procedure InternalPoints does the same for internal points by finally applying *IsInternal*. > PointsInPol := proc(pol)local n, Lm, LM, Lm1, LM1, Count, P, T, O, u, L, uu, uuu : $L \coloneqq []:$ n := nops(pol[1]): Lm := PPP(pol)[1]:LM := PPP(pol)[2]:Lm1 := [seq(ceil(Lm[i]), i=1..n)]:LM1 := [seq(ceil(LM[i]), i=1..n)]:Count := 0: P := Lm1: $T := \mathbf{proc}(x) evalb(x > 0)$ end proc: while $P \neq LM1$ do if IsInPolytope(P, pol) then Count := Count + 1 : L := [op(L), P] : end if: Q := LM1 - P:

 $\mathcal{Q} := Lini \quad i :$ if $Q \neq [seq(0, i=1..n)]$ then

uu := ListTools[SelectLast](T, Q) :

```
uuu := [ListTools[SearchAll](uu, Q)]:
    u := uuu[nops(uuu)]: end if:
   P := [seq(P[i], i=1..u-1), P[u] + 1, seq(Lm1[i], i=u+1..n)]:
    end do:
   if IsInPolytope(LM1, pol) then Count := Count + 1 : L := [op(L), LM1] : end if:
    [Count, L]
    end proc:
> PointsInPol := proc(pol)
   local n, Lm, LM, Lm1, LM1, Count, P, T, Q, u, L, uu, uuu, L1, co, point, M, newpol, A,
       AA, newpoint, i, X:
   n := nops(pol[1]):
   M := PolytopeMatrix(pol):
   newpol := [[seq(0, t=1..n)], seq(pol[k] - pol[1], k=2..n+1)]:
   A := convert(sign(Determinant(M))).Adjoint(M), listlist) :
   AA := [-add(A[r], r=1..nops(A)), op(A)]:
   Lm := PPP(pol)[1]:
   LM := PPP(pol)[2]:
   Lm1 := [seq(ceil(Lm[i]), i=1..n)]:
   LM1 := [seq(ceil(LM[i]), i=1..n)]:
   L \coloneqq []:
   Count := 0 :
   T := \mathbf{proc}(x) evalb(x > 0) end proc:
   P := Lm1:
   while P \neq LM1 do
    newpoint := P - pol[1]:
   X := Vector(newpoint);
   L1 := [DotProduct(X - Vector(newpol[2]), Vector(AA[1]))]:
   for i from 2 to nops(AA) do L1 := [op(L1), DotProduct(X, Vector(AA[i]))]: end do:
   co := 0: for i from 1 to nops(L1) do if L1[i] < 0 then co := 1: end if end do:
   if co = 0 then Count := Count + 1 : L := [op(L), P] : end if:
    O := LM1 - P:
   if Q \neq [seq(0, i=1..n)] then
   uu := ListTools[SelectLast](T, Q):
   uuu := [ListTools[SearchAll](uu, Q)]:
   u := uuu[nops(uuu)]: end if:
   P := [seq(P[i], i=1..u-1), P[u] + 1, seq(Lm1[i], i=u+1..n)]:
    end do:
    P := LM1:
   newpoint := P - pol[1]:
   X := Vector(newpoint);
   L1 := [DotProduct(X - Vector(newpol[2]), Vector(AA[1]))]:
   for i from 2 to nops(AA) do L1 := [op(L1), DotProduct(X, Vector(AA[i]))]: end do:
   co := 0: for i from 1 to nops(L1) do if L1[i] < 0 then co := 1: end if end do:
    if co = 0 then Count := Count + 1 : L := [op(L), LM1] : end if:
    [Count, L]
    end proc:
  InternalPoints := proc(pol)
    local n, Lm, LM, Lm1, LM1, Count, P, T, Q, u, L, uu, uuu, L1, co, point, M, newpol, A,
```

```
AA, newpoint, i, X:
```

```
n \coloneqq nops(pol[1]):
    M \coloneqq PolytopeMatrix(pol):
    newpol := [[seq(0, t=1..n)], seq(pol[k] - pol[1], k=2..n+1)]:
    A \coloneqq convert(sign(Determinant(M))).Adjoint(M), listlist) :
    AA \coloneqq [-add(A[r], r=1..nops(A)), op(A)]:
    Lm := PPP(pol)[1]:
    LM := PPP(pol)[2]:
    Lm1 := [seq(ceil(Lm[i]), i=1..n)]:
    LM1 := [seq(ceil(LM[i]), i=1..n)]:
    L := []:
    Count := 0 :
    T := \mathbf{proc}(x) evalb(x > 0) end proc:
    P := Lm1:
    while P \neq LM1 do
    newpoint := P - pol[1]:
    X := Vector(newpoint);
    L1 := [DotProduct(X - Vector(newpol[2]), Vector(AA[1]))]:
    for i from 2 to nops(AA) do L1 := [op(L1), DotProduct(X, Vector(AA[i]))]: end do:
    co := 0: for i from 1 to nops(L1) do if L1[i] \le 0 then co := 1: end if end do:
    if co = 0 then Count := Count + 1 : L := [op(L), P]: end if:
    Q := LM1 - P:
    if Q \neq [seq(0, i=1..n)] then
    uu := ListTools[SelectLast](T, Q):
    uuu := [ListTools[SearchAll](uu, Q)]:
    u := uuu[nops(uuu)]: end if:
    P := [seq(P[i], i=1..u-1), P[u] + 1, seq(Lm1[i], i=u+1..n)]:
    end do:
    P := LM1:
    newpoint := P - pol[1]:
    X := Vector(newpoint);
    L1 := [DotProduct(X - Vector(newpol[2]), Vector(AA[1]))]:
    for i from 2 to nops(AA) do L1 := [op(L1), DotProduct(X, Vector(AA[i]))]: end do:
    co := 0: for i from 1 to nops(L1) do if L1[i] \le 0 then co := 1: end if end do:
    if co = 0 then Count := Count + 1 : L := [op(L), LM1] : end if:
    [Count, L]
    end proc:
Examples
> Q := [2, 3, 5]
                                    Q := [2, 3, 5]
                                                                                      (8.1.14)
> Pol := Opolytope(Q)
                            Pol := [[0, 0], [5, 0], [-3, 6]]
                                                                                      (8.1.15)
> Pol := [[0, 0], [0, 3], [5, 0]]
                            Pol := [[0, 0], [0, 3], [5, 0]]
                                                                                      (8.1.16)
> PointsInPol(Pol)
[13, [[0, 0], [0, 1], [0, 2], [0, 3], [1, 0], [1, 1], [1, 2], [2, 0], [2, 1], [3, 0], [3, 1],
                                                                                      (8.1.17)
    [4, 0], [5, 0]]
   InternalPoints(Pol)
                          [4, [[1, 1], [1, 2], [2, 1], [3, 1]]]
                                                                                      (8.1.18)
```

The following procedure H(point, pol) returnes the dimension of the smallest face of *pol* containing the given *point*. This the key point to provide a procedure computing Bott-Tu formulas. This corresponds precisely to the function s(u, D) in [RT, Theorem 4.8].

$$H := \operatorname{proc}(point, pol)$$

$$\operatorname{local} n, PI, F, X, L, i, co, M, newpol, newpoint, A, AA :$$

$$n := nops(pol[1]) :$$

$$if not lslnPolytope(point, pol) then 0 :$$

$$else if lslnternal(point, pol) then n :$$

$$else$$

$$newpol := [[seq(0, t = 1 ..n)], seq(pol[k] - pol[1], k = 2 ..n + 1)] :$$

$$newpoint := point - pol[1]:$$

$$M := Matri(Transpose(Matrix(newpol)), 1) :$$

$$A := convert(sign(Determinant(M)).Adjoint(M), listlist) :$$

$$AA := [-add(A[r], r = 1 ..nops(A)), op(A)] :$$

$$PI := Vector(pol[1]) :$$

$$F := PFan(pol) :$$

$$X := Vector(point);$$

$$L := [DotProduct(X - Vector(pol[2]), Vector(AA[1]))] :$$

$$for i from 2 to nops(F) do L := [op(L), DotProduct(X, Vector(AA[i]))] :$$

$$end do:$$

$$co := 0 : for i from 1 to nops(L) do if L[i] = 0 then co := co + 1 :$$

$$end if end di :$$

$$end proc:$$

$$H([1, \frac{12}{5}], Pol)$$

$$1$$

$$(8.1.20)$$

$$H([1, 1], Pol)$$

$$0$$

$$(8.1.21)$$

$$H([12, 0], Pol)$$

$$0$$

$$(8.1.22)$$

2. Cohomology of line bundles

The following procedure hO(q, m, Q) computes the complex dimension of complex *q*--th cohomogy vector space $H^q(\mathbf{P}(Q), \mathcal{O}(m))$ where $\mathcal{O}(1)$ is the generator of $\text{Pic}(\mathbf{P}(Q))$, and *m* is an integer. This procedure produces a result for any $q \ge 0$ and for any $m \ge 0$. Moreover if $\mathbf{P}(Q)$ is Gorenstein

then
$$hO(q, m, Q)$$
 produces a result also for $m \le -\frac{|Q|}{\delta}$, where $|Q| := \sum_{i=0}^{n} q_i$ and δ

:= lcm(Q) (computed by procedures *Qsum* and *Qdelta* in the Preliminaries). It is obtained by Proposition 4.6 in [RT]. Although it admits large ranges of uncomputability on the polarization *m*, it is actually faster than the following powerful procedure hOmega(q,p,m,Q).

> hO := proc(q, m, Q) local h; if q < 0 then error "Cohomology of negative level"end if: if m ≥ 0 then if q = 0 then h := PointsInPol(MatrixPolytope(HermiteForm(PolytopeMatrix(Qpolytope(Q, m)))))[1] else h := 0 end if: elif IsGorenstein(Q) = false then print("Unable to compute it: no Gorenstein case, please use hOmega")elif m ≤

$-\frac{Qsum(Q)}{Qdelta(Q)} \text{ then if } q = nops(Q) - 1 \text{ then } h := hO\left(0, -m - \frac{Qsum(Q)}{Qdelta(Q)}, Qsum(Q)\right)$	2)
else $h := 0$ end if: else $print\left(-\frac{Qsum(Q)}{Qdelta(Q)} < m < 0\right)$:	
<i>print</i> ("Unable to compute it in this range. Please use hOmega") end if: end	proc:
Examples	
$ \bar{ } > \varrho^{-1}$	
[2, 3, 5]	(8.2.1)
$ \begin{array}{ } \hline > hO(-1, 1, [1, 1, 1]) \\ \hline \\ $	
hO(0, 1, Q)	
21	(8.2.2)
$\mid \sum hO(1, 1, Q)$	
0	(8.2.3)
> $hO(0, -1, Q)$ "Unable to compute it: no Gorenstein case, please use hOmega"	(8.2.4)
= hO(0 - 1 [1 1 1])	()
<i>true</i>	
"Unable to compute it in this range. Please use hOmega"	(8.2.5)
hO(2, -1, [1, 1, 1])	
true	
"Unable to compute it in this range. Please use hOmega"	(8.2.6)
hO(0, 0, [1, 1, 1])	
1	(8.2.7)
> hO(2, -3, [1, 1, 1])	
	(8.2.8)
> hO(1, -1, [1, 1, 1])	
true	
"Unable to compute it in this range. Please use hOmega"	(8.2.9)

3. Bott-Tu formulas

The following procedure hOmega(q,p,m,Q) computes the complex dimension of complex q-th cohomogy vector space $H^q(P(Q), \Omega^P(m))$ where m is a twisting integer. This procedure produces a result for any $q \ge 0, p \ge 0$ and for any m. It is obtained by Theorem 4.9 in [RT]. Although it is a more powerful procedure than hO(q,m,Q) it is unfortunately slower. > $hOmega := \operatorname{proc}(q, p, m, Q) \operatorname{local} h, PP, i$; if q < 0 then error "Cohomology of negative level"end if: if p < 0 then error "Cohomology of negative level differential forms"end if: if m = 0 then if q = pthen h := 1 else h := 0 end if: elif m > 0 then if q = 0 then h := 0 : PP := PointsInPol(MatrixPolytope(HermiteForm(PolytopeMatrix(Qpolytope(Q, m)), p) end do:else h := 0 end if: elif m < 0 then if q = nops(Q) - 1 then h := 0 : PP := PointsInPol(Qpolytope(Q, -m)) : for i to PP[1] do h := h+ binomial(H(PP[2][i], Qpolytope(Q, -m)), nops(Q) - 1 - p) end do:else h:= 0 end if: end if: h; end proc: **Examples**

<pre>bOmega(-1, 0, 1, [1, 1, 1]) Error, (in hOmega) Cohomega</pre>	ology of negative level	
hOmega(0, 0, 2, Q)	71	(8 3 1)
	/ 1	(0.5.1)
$\begin{bmatrix} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	71	(8.3.2)
	21	(8.3.3)
bOmega(0, 0, 1, Q)	21	(8.3.4)
$ \mid hO(0, 3, Q) $	151	(8.3.5)
$\rightarrow hOmega(0, 0, 3, Q)$	151	(9.2.0)
hOmega(1, 0, 1, Q)	151	(8.3.0)
$\begin{bmatrix} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	0	(8.3.7)
- <i>nomegu</i> (0, 0, 1, <i>Q</i>)	0	(8.3.8)
bOmega(0, 0, -1, [1, 1, 1])	0	(8.3.9)
bOmega(2, 0, -1, [1, 1, 1])	0	(8.3.10)
bOmega(0, 0, 0, [1, 1, 1])		(0.2.11)
hOmega(2, 0, -3, [1, 1, 1])	1	(8.3.11)
bOmagg(1, 0, 1, [1, 1, 1])	1	(8.3.12)
nOmega(1, 0, -1, [1, 1, 1])	0	(8.3.13)
> $hOmega(2, 0, -1, Q)$	11	(8.3.14)
hO(2,-1,Q)	o Gorenstein case, please use hOmega"	(8 3 15)
bOmega(0, 1, 1, [1, 2, 2, 3])	o obrenstem euse, preuse use nomegu	(0.0.13)
hOmega(0, 2, 1, [1, 2, 2, 3])	13	(8.3.16)
	3	(8.3.17)
$\int nO(0, 1, [1, 1, 2])$	4	(8.3.18)
> $hO(0, 3, [1, 1, 2])$	16	(8.3.19)
$\rightarrow hOmega(0, 2, 3, [1, 1, 2])$	4	(0 2 10)
hO(0, 1, [1, 3, 3, 2])	4	(8.3.20)
	11	(8.3.21)

> hO(0, 2, [1, 3, 3, 2])42 (8.3.22) *hOmega*(0,-1,1,[1,1,1]) <u>mega) Cohomology of negative level differential</u> orms

References

[RT] M. Rossi, L. Terracini Weighted projective spaces from the toric point of view with computational applications, http://www2.dm.unito.it/paginepersonali/rossi/wps.pdf [Cox] http://www.cs.amherst.edu/~dac/toric.html