Identifying edge clusters in networks via edge graphlet degree vectors (edge-GDVs) and edge-GDV-similarities

Ryan W. Solava, Ryan P. Michaels, and Tijana Milenković * Department of Computer Science and Engineering, University of Notre Dame, IN 46556, USA

ABSTRACT

arXiv:1204.2255v1 [q-bio.MN] 10 Apr 2012

1

Inference of new biological knowledge, e.g., prediction of protein function, from protein-protein interaction (PPI) networks has received attention in the post-genomic era. A popular strategy has been to cluster the network into functionally coherent groups of proteins and predict protein function from the clusters. Traditionally, network research has focused on clustering of nodes. However, why favor nodes over edges, when clustering of edges may be preferred? For example, nodes belong to multiple functional groups, but clustering of nodes typically cannot capture the group overlap, while clustering of edges can. Clustering of adjacent edges that share many neighbors was proposed recently, outperforming different node clustering methods. However, since some biological processes can have characteristic "signatures" throughout the network, not just locally, it may be of interest to consider edges that are not necessarily adjacent. Hence, we design a sensitive measure of the "topological similarity" of edges that can deal with edges that are not necessarily adjacent. We cluster edges that are similar according to our measure in different baker's yeast PPI networks, outperforming existing node and edge clustering approaches.

INTRODUCTION

A *network* (*graph*) consists of *nodes* and *edges*. Network research spans many domains. Biomedical domain is no exception. We focus on *protein-protein interaction* (*PPI*) *networks*, in which nodes are proteins and undirected edges correspond to physical binding between the proteins. Of all biological networks, we focus on PPI networks since it is the proteins, gene products, that carry out most biological processes, and they do so by interacting with other proteins. High-throughput screens for interaction detection, such as yeast two-hybrid (Y2H) assays or affinity purification coupled to mass spectrometry (AP/MS), have yielded partial PPI networks for many model organisms and human (Giot *et al.*, 2003; Stelzl *et al.*, 2005; Yu *et al.*, 2008; Simonis *et al.*, 2009), as well as for bacterial and viral pathogens (Parrish *et al.*, 2007; LaCount *et al.*, 2005). Many biological network datasets are now publicly available (Peri *et al.*, 2004; Breitkreutz *et al.*, 2008).

Analogous to genomic sequence research, biological network research is expected to have invaluable impacts on our biological understanding. However, unlike genomic sequence research, biological network research is in its infancy, owing to computational hardness of many graph theoretic problems (Cook, 1971), as well as to incompleteness of the available network data. Importantly, the number of functionally uncharacterized proteins is large even for simple and well studied model organisms (Sharan *et al.*, 2007). Functional characterization of proteins via computational analysis could save resources needed for biological experiments. In particular, PPI network analysis could help in suggesting top candidates for future experimental validation, since proteins aggregate to perform a function, and since PPI networks model these aggregations.

Thus, it is no surprise that prediction of protein function (Sharan *et al.*, 2007; Milenković & Pržulj, 2008) and the role of proteins in disease (Sharan & Ideker, 2008; Radivojac *et al.*, 2008; Goh *et al.*, 2007; Milenković *et al.*, 2010; Vanunu *et al.*, 2010) from PPI networks have received attention in the post-genomic era. For example, it has been argued that proteins which are close in the network are likely to be involved in similar biological processes (Sharan *et al.*, 2007), that "topologically central" proteins correspond to "biologically central" (e.g., lethal, aging-, or cancer-related) proteins (Jeong *et al.*, 2001; Sharan & Ideker, 2008; Jonsson & Bates, 2006; Milenković *et al.*, 2011), or that proteins with similar topological neighbourhoods have similar biological characteristics (Milenković & Pržulj, 2008; Ho *et al.*, 2010).

A particularly popular strategy for functional characterization of proteins has been to *cluster* the network into functionally "coherent" groups of nodes and assign the entire cluster with a function based on functions of its annotated members (Sharan et al., 2007; Sharan & Ideker, 2008). A variety of clustering approaches exist, each with its own (dis)advantages (Brohee & van Helden, 2006; Fortunato, 2010). Typically, they aim to group nodes that are in a dense connected network region (Fortunato, 2010). Also, approaches exist that cluster "topologically similar" nodes without the nodes necessarily being connected in the network. This is important, since a biological process can have characteristic topological "signatures" throughout the network, not just localy in close network proximity (Milenković & Pržulj, 2008; Milenković et al., 2010; Ho et al., 2010). For example, we designed a measure that computes the topological similarity of the extended network neighborhoods of two nodes, without the nodes necessarily being close in the network (Milenković & Pržulj, 2008). We found that 96% of known cancer gene pairs that are topologically similar according to our measure are actually not neighbours in the PPI network; instead, they are at the shortest path distance of up to six (Milenković et al., 2010). As such, they may be missed by approaches that focus on connected nodes only. We clustered proteins in the human PPI network that are topologically similar and showed that function of a protein and its network position are closely related (Milenković & Pržulj, 2008) and that the topology around cancer and non-cancer genes is different (Milenković et al., 2010). We used these observations to predict new cancer genes in melanogenesis-related pathways and our predictions were validated phenotypically (Ho et al., 2010).

Traditionally, network research has focused on clustering of *nodes* (Fortunato, 2010). However, a network consists of nodes *and* edges. Hence, why favor nodes over edges, especially when clustering of *edges* may be preferred? For example, since nodes typically belong to multiple functional groups, and since clusters are

^{*}To whom correspondence should be addressed (tmilenko@nd.edu)

expected to correspond to the functional groups, it may be desirable to allow for a node to belong to multiple clusters. Clustering of nodes typically cannot capture the group overlap, especially if the network is partitioned into disjoint node sets, as is the case with many (although not all) node clustering approaches (Fortunato, 2010; Ahn *et al.*, 2010). However, clustering of edges can trivially capture the group overlap (Fig. 1). Edge clustering methods were proposed only recently (Ahn *et al.*, 2010; Evans & Lambiotte, 2009). Adjacent (connected) edges that share many neighbors were defined as similar and were thus clustered together (see below), outperforming different node clustering methods, including a method which allows for the group overlap (Ahn *et al.*, 2010). However, it may be of interest to consider edges that are *not* necessarily adjacent (see above).



Fig. 1. Node clustering (left) versus edge clustering (right).

Hence, we introduce a new measure of edge similarity that is not only capable of dealing with edges that are not necessarily adjacent, but is also a more sensitive measure of topology than the above shared-neighborhood measure (Ahn *et al.*, 2010). For a fair evaluation of our measure, when grouping edges that are similar according to our measure, we precisely mimic the above edge clustering approach by Ahn *et al.* (2010). We show that using our measure results in clusters of comparable or better quality.

2 APPROACH

We recently designed a graphlet-based measure of the topological position of a node in the network; graphlets are small induced subgraphs of a network (Fig. 2) (Pržulj, 2007). This measure generalizes the degree of a node that counts the number of edges that the node touches (where an edge is the only 2-node graphlet) into the node graphlet degree vector (node-GDV) that counts the number of different graphlets that the node touches, for all 2-5node graphlets (Fig. 2; also, see Methods). Hence, node-GDV describes the topology of the node's up to 4-deep neighborhood (Milenković & Pržulj, 2008). This is effective: going to distance of four around a node captures a large portion of the network due to the small-world nature of many real networks (Watts & Strogatz, 1998). For this reason, and since the number of graphlets on nnodes increases exponentially with n, using larger graphlets could unnecessarily increase the computational complexity of the method. Also, we designed node-GDV-similarity measure to compare node-GDVs of two nodes and hence quantify the topological similarity of their extended network neighborhoods (Milenković & Pržulj, 2008).

Since a graphlet consists of nodes *and* edges, we now design *edge-GDV* to count the number of different 3-5-node graphlets that an *edge* touches (Fig. 2). (We exclude the count for the only 2-node

graphlet, an edge, as each edge touches exactly one 2-node graphlet, itself.) Also, we design *edge-GDV-similarity* to compare edge-GDVs of two edges and hence quantify the topological similarity of their extended network neighborhoods. Unlike the shared-neighborhood measure (Ahn *et al.*, 2010), edge-GDV-similarity can measure similarity between edges independent on whether they are adjacent. Also, by counting the shared neighborhood measure actually counts the 3-node paths that the end nodes share (Ahn *et al.*, 2010). Since edge-GDV counts the different 3-5-node graphlets that an edge touches, including a 3-node path, edge-GDV is a more constraining measure of topology. See Methods for details.

We evaluate our approach against existing clustering methods, as follows (also, see Methods). The existing edge clustering method mentioned above, henceforth denoted by edge - shared neighborhood (edge-SN), was already shown to be superior to different node clustering methods on four baker's yeast PPI networks (Ahn et al., 2010). For a fair evaluation, we mimic edge-SN exactly, except that we use edge-GDV-similarity instead of the shared-neighborhood measure as the distance metric for the same clustering method, namely hierarchical clustering. Just as edge-SN, we (initially) cluster only adjacent edges, and of all partitions, we choose the one with the maximum density (see Methods). Just as edge-SN, we evaluate such partition with respect to four measures: cluster coverage (the portion of the network "covered" by "nontrivial" clusters), overlap coverage (the amount of node overlap between clusters), cluster quality (enrichment of clusters in Gene Ontology (GO) terms (Ashburner et al., 2000)), and overlap quality (the correlation between the number of clusters and the number of GO terms that nodes participate in). When applied to the same yeast networks, our approach in comparable or superior to edge-SN (and hence to the node clustering approaches that were outperformed by edge-SN on the same networks). Thus, we gain by using a more sensitive measure of topology compared to edge-SN. Furthermore, when we cluster both adjacent and non-adjacent edges, our method in general performs even better. Hence, we gain additionally by using a measure that can capture similarity of edges that are not necessarily adjacent. We note that we do not propose a new edge clustering method but a new edge similarity measure that can serve as a distance metric for existing clustering methods.

3 METHODS

3.1 Data sets

We cluster the same four baker's yeast PPI networks that edge-SN was evaluated on (Ahn *et al.*, 2010; Yu *et al.*, 2008): 1) *Y2H* network, obtained by Y2H, with 1,647 proteins and 2,518 PPIs; 2) *AP/MS* network, obtained by AP/MS, with 1,004 proteins and 8,319 PPIs; 3) *LC* network, obtained by literature curation, with 1,213 proteins and 2,556 PPIs; and 4) *ALL* network, representing the union of Y2H, AP/MS, and LC, with 2,729 proteins and 12,174 PPIs. Using these different networks ensures that our method is robust to different types of experiments for PPI detection.

3.2 Related work

We compare our method to three popular node clustering methods: clique percolation (Palla *et al.*, 2005), greedy modularity optimization (Newman, 2004), and Infomap (Rosvall & Bergstrom, 2008). Also, we compare it to the existing edge clustering algorithm, edge-SN (Ahn *et al.*, 2010). Briefly, *clique percolation* is the most prominent overlapping node clustering

algorithm, greedy modularity optimization is the most popular modularitybased technique, and Infomap is often considered the most accurate method available (Ahn et al., 2010). Edge-SN hierarchically groups adjacent edges whose non-common end-nodes share many neighbors (see below). We did not run these algorithms on the yeast networks ourselves. Instead, we use the results reported by Ahn et al. (2010) who ran the algorithms on the same networks. For details on how the methods were implemented, see Ahn et al. (2010). We do explain how edge-SN was implemented, as we implement our method in the same way (except that we use a different distance metric).

Edge-SN algorithm works as follows. If the set of node *i* and its neighbors is denoted as n(i), the similarity between adjacent edges e_{ik} and e_{jk} with common node k is $S(e_{ik}, e_{jk}) = |n(i) \cap n(j)|/|n(i) \cup n(j)|$. This shared-neighborhood measure is used as a distance metric for single-linkage hierarchical clustering. With this method, a tree, or dendrogram, is created. Leaves of the tree are edges of the network and an interior node in the tree represents a cluster made up of all children of the node. The tree is constructed by assigning each edge to its own cluster and iteratively merging the most similar pair of clusters. The tree has to be cut in order to create a partition of K clusters. To determine where to cut the tree, edge-SN uses an objective function called partition density, computed as follows. For a network with M edges, $\{P_1, \cdots, P_K\}$ is a partition of the edges into Kclusters. Cluster C has $m_C = |C|$ edges and $n_C = |\cup_{e_{ij} \in C} i, j|$ nodes. C's density is $D_C = \frac{m_C - (n_C - 1)}{n_C (n_C - 1)/2 - (n_C - 1)}$, and the partition density is $D = \frac{2}{M} \sum_K m_C \frac{m_C - (n_C - 1)}{(n_C - 2)(n_C - 1)}$. For details, see Ahn *et al.* (2010). Edge-SN cuts the tree at different levels and chooses a partition with the maximum value of D. However, meaningful structure may also exist above and below the level corresponding to maximum D (Ahn et al., 2010).

3.3 New measures of network topology: edge graphlet degree vector (edge-GDV) and edge-GDV-similarity

A graphlet is an *induced* subgraph of graph X that contains *all* edges of X connecting its nodes (Fig. 2). We generalized the degree of node v that counts the number of edges that v touches (where an edge is the only 2-node graphlet, G_0 in Fig. 2) into node graphlet degree vector (node-GDV) of v that counts the number of 2-5-node graphlets $(G_0, G_1, \ldots, G_{29}$ in Fig. 2) that v touches (Milenković & Pržulj, 2008). We need to distinguish between v touching, e.g., a G_1 at an end node or at the middle node, since G_1 admits an automorphism that maps its end nodes to each other and the middle node to itself. To understand this, recall the following. An isomorphism f from graph X to graph Y is a bijection of nodes of X to nodes of Y such that xyis an edge of X if and only if f(x)f(y) is an edge of Y. An automorphism is an isomorphism from X to itself. The automorphisms of X form the automorphism group, Aut(X). If x is a node of X, then the automorphism node orbit of x is $Orb(x) = \{y \in V(X) | y = f(x) \text{ for some } f \in V(X) | y = f(x) \}$ Aut(X)}, where V(X) is the set of nodes of X. Thus, end nodes of a G_1 belong to one node orbit, while its middle node belongs to another one. There are 73 node orbits for 2-5-node graphlets. Hence, node-GDV of v has 73 elements counting how many node orbits of each type touch v (v's degree is the first element). It captures v's up to 4-deep neighborhood and thus a large portion of real networks, as they are small-world (Watts & Strogatz, 1998).

Since a graphlet contains nodes and edges, we propose a new graphletbased measure of the topological position of an *edge* in the network. We define *edge-GDV* to count the number of graphlets that an *edge* touches at a given "edge orbit" (Fig. 2). We define edge orbits are follows. Given the automorphism group of graph X, Aut(X), if xy is an edge of X, then the edge orbit of xy is $Orb_e(xy) = \{zw \in E(X) | z = f(x) \text{ and } w = f(y) \text{ for some } f \in Aut(X)\}$, where E(X) is the set of edges of X. For example, in Fig. 2, in a G_1 , both edges are in edge orbit 1. In a G_2 , all three edges are in edge orbit 2. In a G_3 , the two "outer" edges are in edge orbit 3, while the "middle" edge is in edge orbit 4. And so on. There are 68 edge orbits for 3-5-node graphlets. (We intentionally exclude orbit 0 in the only 2-node graphlet, G_0 , as each edge touches exactly one G_0 , namely itself.)



Fig. 2. All the connected graphs on 2 to 5 nodes. When appearing as induced subgraphs of a network, they are called *graphlets*. They contain 73 topologically unique node types, or "node orbits." In a graphlet, nodes in the same node orbit are of the same shade (Pržulj, 2007). They also contain 69 topologically unique edge types, or "edge orbits." (3-5-node graphlets contain 68 edge orbits.) Edge orbit of an edge is defined by node orbits of its end nodes. In a graphlet, different edge orbits are numbered differently.

Comparing edge-GDVs of two edges gives a sensitive measure of their topological similarity, since their extended network neighborhoods are compared. Using some existing measure, e.g., Euclidean distance, to compare edge-GDVs might be inappropriate, as some edge orbits are not independent. Instead, we design edge-GDV-similarity measure as follows. For an edge e, e_i is the i^{th} element of its edge-GDV. The distance between the i^{th} edge orbits of edges e and f is $D_i(e, f) = w_i \times U_i(e, f)$ $\frac{|log(e_i+1)-log(f_i+1)|}{log(max\{e_i,f_i\}+2)}$, where w_i is the weight of edge orbit i that accounts for edge orbit dependencies. For example, the differences in counts of orbit 2 of two edges will imply the differences in counts of all other orbits that contain orbit 2, such as orbits 8-12 (Fig. 2). This is applied to all edge orbits: the smaller the number of orbits that affect orbit i (including itself), o_i , the higher its weight w_i , where $w_i = 1 - \frac{\log(o_i)}{\log(68)}$. Clearly, w_i is in (0,1] and the highest weight of 1 is assigned to orbit i with $o_i = 1$. The log is used in the formula for D_i because the i^{th} elements of two edge-GDVs can differ by several orders of magnitude and we do not want the distance between edge-GDVs to be dominated by large values; also, we want to account for the relative difference between e_i and f_i and that is why we divide by the value of the denominator, which also scales D_i to [0, 1). The constants are added to prevent D_i to be infinite. The total distance is $D(e, f) = \frac{\sum_{i=0}^{68} D_i}{\sum_{i=0}^{68} w_i}$. Finally, edge-GDV-similarity is S(e, f) = 1 - D(e, f). It is in (0, 1]. The higher the edge-GDVsimilarity, the higher the topological similarity of edges' extended network neighborhoods. We design edge-GDV-similarity as described because we already designed node-GDV-similarity, which compares node-GDVs, in a similar way (Milenković & Pržulj, 2008), and because we showed in different contexts that node-GDV-similarity successfully extracts function from network topology (Milenković et al., 2010; Memisević et al., 2010; Kuchaiev et al., 2010; Milenković et al., 2010, 2011). So, we expect edge-GDV-similarity to successfully extract function from topology as well.

3.4 Our clustering strategies

We cluster the yeast PPI networks in the same manner as edge-SN, except that we use edge-GDV-similarity as the distance metrics instead of using the shared-neighborhood measure. Initially, for a fair comparison with edge-SN, we cluster adjacent edges only, to test if and how much we gain by using our more sensitive measure of edge similarity. Later on, we cluster all edges, to test if and how much we gain by taking into account edges that are not necessarily adjacent. Some further information is provided below, after defining measures of partition quality.

3.5 Quality of partitions

We evaluate a partition with respect to the same measures that were used by edge-SN: cluster coverage (CC), overlap coverage (OC), cluster quality (CQ), and overlap quality (OQ). CC is the fraction of nodes that belong to at least one "non-trivial" cluster of three or more nodes. OC is the average number of non-trivial clusters that nodes belong to. CQ is the ratio of the average Gene Ontology (GO) term (Ashburner *et al.*, 2000) similarity over all node pairs that are in at least one same cluster and the average GO terms similarity over all node pairs in the network. OQ is the mutual information between the number of GO terms and the number of non-trivial clusters that proteins are involved in. Raw values for the four measures do not necessarily fall in [0, 1]. Hence, just as Ahn *et al.* (2010), we normalize each measure such that the best method has a value of one. Then, the overall partition quality is the sum of these four normalized measures, such that the maximum achievable score is four.

We can now note the following. To mimic Ahn et al. (2010), we would report for a given network the partition with maximum partition density D. However, we find that CC is strongly negatively correlated with CQ and OQ, and sometimes with OC, over all of our partitions (Fig. 3). Thus, choosing the partition with low CC would result in high CQ and OQ (and sometimes OC), hence artificially increasing the overall partition quality. Since in three out of four yeast networks CC is lower for edge-SN than for the node clustering methods, it might not be surprising that edge-SN's overall partition quality is the highest. Analogously, since edge-SN's partitions with maximum D have lower CC than our partitions with maximum D, our partitions may have lower overall partition quality simply because of the strong negative correlation between CC and other measures. Hence, we find the partition with maximum D among all partitions that have CC less than or equal to CC of edge-SN's partition with maximum D. Then, we report either the partition obtained in this way or the partition with maximum D (independent of its CC), whichever has better overall partition quality. Furthermore, when we cluster both adjacent and non-adjacent edges, selecting the partition based on its density, as just described, might be inappropriate (see above). Thus, when we cluster both adjacent and nonadjacent edges, we also report the partition with the best overall partition quality.

4 RESULTS

We evaluate our method against three node clustering methods (clique percolation – CliqPerc, greedy modularity optimization – GreedMod, and Infomap) and one edge clustering method (edge-SN) on four yeast PPI networks (Y2H, AP/MS, LC, and ALL), with respect to four measures of partition quality (cluster coverage – CC, overlap coverage - OC, cluster quality – CQ, and overlap quality – OQ) that are combined into the normalized overall partition quality; see Methods. We denote our method when clustering adjacent edges only and reporting the partition with the maximum density as eGDV-A-D. We denote our method when clustering both adjacent and non-adjacent edges and reporting the partition with the maximum density as eGDV-NA-D. We denote our method when clustering both adjacent and non-adjacent edges and reporting the partition with the maximum density as eGDV-NA-D. We denote our method when clustering both adjacent and non-adjacent edges and reporting the partition with the best overall partition quality as eGDV-NA-B. See Methods for details. Results are shown in Fig. 4.

We gain by using edge-GDV-similarity for clustering: eGDV-A-D outperforms all node clustering approaches on all networks. (This includes node clustering by using node-GDV-similarity, as shown in Fig. 5). Also, it outperforms edge-SN on Y2H and AP/MS. Although edge-SN is slightly better than and comparable to eGDV-A-D on LC and ALL networks, respectively, eGDV-NA-D outperforms edge-SN on these two networks, as well as on AP/MS. Hence, we gain further by clustering non-adjacent edges in addition to adjacent ones. The only exception is Y2H, for which edge-SN is slightly better than eGDV-NA-D. However, as already noted, eGDV-A-D outperforms edge-SN on Y2H network. Hence, we are always superior, with either eGDV-A-D or eGDV-NA-D or both eGDV-A-D and eGDV-NA-D. With eGDV-NA-B, we further demonstrate our superiority over all other methods on all networks.

REFERENCES

- Ahn, Y., Bagrow, J. & Lehmann, S. (2010) Link communities reveal multiscale complexity in networks. *Nature*, 466 (7307), 761–764.
- Ashburner, M., Ball, C. A., Blake, J. A., Botstein, D., Butler, H., Cherry, J. M., Davis, A. P., Dolinski, K., Dwight, S. S., Eppig, J. T., Harris, M. A., Hill, D. P., Issel-Tarver, L., Kasarskis, A., Lewis, S., Matese, J. C., Richardson, J. E., Ringwald, M., Rubin, G. M. & Sherlock, G. (2000) Gene Ontology: tool for the unification of biology. *Nature Genetics*, 25 (1), 25–29.
- Breitkreutz, B. J., Stark, C., Reguly, T., Boucher, L., Breitkreutz, A., Livstone, M., Oughtred, R., Lackner, D. H., Bahler, J., Wood, V., Dolinski, K. & Tyers, M. (2008) The BioGRID Interaction Database: 2008 update. *Nucleic Acids Research*, 36, D637–D640.
- Brohee, S. & van Helden, J. (2006) Evaluation of clustering algorithms for proteinprotein interaction networks. *BMC Bioinformatics*, 7 (1), 488+.
- Cook, S. (1971) The complexity of theorem-proving procedures. In Proceedings of the 3rd Annual ACM Symposium on Theory of Computing pp. 151–158.
- Evans, T. S. & Lambiotte, R. (2009) Line graphs, link partitions, and overlapping communities. *Physical Review E (Statistical, Nonlinear, and Soft Matter Physics)*, 80 (1), 016105+.
- Fortunato, S. (2010) Community detection in graphs. Physics Reports, 486, 75-174.
- Giot, L., Bader, J., Brouwer, C., Chaudhuri, A., Kuang, B., Li, Y., Hao, Y., Ooi, C., Godwin, B., Vitols, E., Vijayadamodar, G., Pochart, P., Machineni, H., Welsh, M., Kong, Y., Zerhusen, B., Malcolm, R., Varrone, Z., Collis, A., Minto, M., Burgess, S., McDaniel, L., Stimpson, E., Spriggs, F., Williams, J., Neurath, K., Ioime, N., Agee, M., Voss, E., Furtak, K., Renzulli, R., Aanensen, N., Carrolla, S., Bickelhaupt, E., Lazovatsky, Y., DaSilva, A., Zhong, J., Stanyon, C., Finley, R. J., White, K., Braverman, M., Jarvie, T., Gold, S., Leach, M., Knight, J., Shimkets, R., McKenna, M., Chant, J. & Rothberg, J. (2003) A protein interaction map of Drosophila melanogaster. *Science*, **302** (5651), 1727–1736.
- Goh, K.-I., Cusick, M., Valle, D., Childs, B., Vidal, M. & Barabási, A.-L. (2007) The human disease network. PNAS, 104 (21), 8685–8690.
- Ho, H., Milenković, T., Memisevic, V., Aruri, J., Przulj, N. & Ganesan, A. (2010) Protein interaction network uncovers melanogenesis regulatory network components within functional genomics datasets. *BMC Systems Biology*, **4** (84).
- Jeong, H., Mason, S. P., Barabási, A.-L. & Oltvai, Z. N. (2001) Lethality and centrality in protein networks. *Nature*, **411** (6833), 41–2.
- Jonsson, P. & Bates, P. (2006) Global topological features of cancer proteins in the human interactome. *Bioinformatics*, 22 (18), 2291–2297.
- Kuchaiev, O., Milenković, T., Memišević, V., Hayes, W. & Pržulj, N. (2010) Topological network alignment uncovers biological function and phylogeny. *Journal of the Royal Society Interface*, 7, 1341–1354.
- LaCount, D., Vignali, M., Chettier, R., Phansalkar, A., Bell, R., Hesselberth, J., Schoenfeld, L., Ota, I., Sahasrabudhe, S., Kurschner, C., Fields, S. & Hughes, R. (2005) A protein interaction network of the malaria parasite plasmodium falciparum. *Nature*, 438, 103–107.
- Memisević, V., Milenković, T. & Pržulj, N. (2010) Complementarity of network and sequence information in homologous proteins. *Journal of Integrative Bioinformatics*, 7(3):135.
- Milenković, T., Memisević, V., Ganesan, A. K. & Pržulj, N. (2010) Systems-level cancer gene identification from protein interaction network topology applied to melanogenesis-related interaction networks. *Journal of the Royal Society Interface*, 7, 423–437.
- Milenković, T., Memišević, V., Bonato, A. & Pržulj, N. (2011) Dominating biological networks. *PLoS ONE*, 6 (8), e23016.
- Milenković, T., Ng, W., Hayes, W. & Pržulj, N. (2010) Optimal network alignment with graphlet degree vectors. *Cancer Informatics*, 9, 121–137.



Fig. 3. Pairwise Pearson correlations for four measures of partition quality (cluster coverage – CC, overlap coverage – OC, overlap quality – OQ, and cluster quality – CQ) over all partitions for a given yeast PPI network (Y2H, AP/MS, LC, and ALL), when clustering adjacent edges only (Adjacent Edges; panels **A-D**) and when clustering both adjacent and non-adjacent edges (All Edges; panels **E-H**). In all eight panels, CC is strongly negatively correlated with OQ and CQ.

- Milenković, T. & Pržulj, N. (2008) Uncovering biological network function via graphlet degree signatures. *Cancer Informatics*, 6, 257–273.
- Newman, M. E. J. (2004) Fast algorithm for detecting community structure in networks. *Physical Review E*, **69** (6), 066133+.
- Palla, G., Derenyi, I., Farkas, I. & Vicsek, T. (2005) Uncovering the overlapping community structure of complex networks in nature and society. *Nature*, 435 (7043), 814–818.
- Parrish, J., Yu, J., G.Liu, Hines, J., Chan, J., Mangiola, B., Zhang, H., Pacifico, S., Fotouhi, F., DiRita, V., Ideker, T., Andrews, P. & Jr, R. F. (2007) A proteome-wide protein interaction map for campylobacter jejuni. *Genome Biology*, 8, R130.
- Peri, S., Navarro, J. D., Kristiansen, T. Z., Amanchy, R., Surendranath, V., Muthusamy, B., Gandhi, T. K., Chandrika, K. N., Deshpande, N., Suresh, S., Rashmi, B. P., Shanker, K., Padma, N., N iranjan, V., Harsha, H. C., Talreja, N., Vrushabendra, B. M., Ramya, M. A., Yatish, A. J., Joy, M., S hivashankar, H. N., Kavitha, M. P., Menezes, M., Choudhury, D. R., Ghosh, N., Saravana, R., Chandran, S., Mohan, S., Jonnalagadda, C. K., Prasad, C. K., Kumar-Sinha, C., Deshpande, K. S. & Pandey, A. (2004) Human protein reference database as a discovery resource for proteomics. *Nucleic Acids Res*, **32 Database issue**, D497–501. 1362-4962 Journal Article.
- Pržulj, N. (2007) Biological network comparison using graphlet degree distribution. *Bioinformatics*, 23, e177–e183.
- Radivojac, P., Peng, K., Clark, W. T., Peters, B. J., Mohan, A., Boyle, S. M. & D., M. S. (2008) An integrated approach to inferring gene-disease associations in humans. *Proteins*, **72** (3), 1030–1037.
- Rosvall, M. & Bergstrom, C. T. (2008) Maps of random walks on complex networks reveal community structure. *Proceedings of the National Academy of Sciences of the United States of America*, **105** (4), 1118–1123.
- Sharan, R. & Ideker, T. (2008) Protein networks in disease. Genome Research, 18, 644–652.

Sharan, R., Ulitsky, I. & Shamir, R. (2007) Network-based prediction of protein function. *Molecular Systems Biology*, 3 (88), 1–13.

- Simonis, N., Rual, J. F., Carvunis, A. R., Tasan, M., Lemmens, I., Hirozane-Kishikawa, T., Hao, T., Sahalie, J. M., Venkatesan, K., Gebreab, F., Cevik, S., Klitgord, N., Fan, C., Braun, P., Li, N., Ayivi-Guedehoussou, N., Dann, E., Bertin, N., Szeto, D., Dricot, A., Yildirim, M. A., Lin, C., de Smet, A. S., Kao, H. L., Simon, C., Smolyar, A., Ahn, J. S., Tewari, M., Boxem, M., Milstein, S., Yu, H., Dreze, M., Vandenhaute, J., Gunsalus, K. C., Cusick, M. E., Hill, D. E., Tavernier, J., Roth, F. P. & Vidal, M. (2009) Empirically controlled mapping of the Caenorhabditis elegans protein-protein interactome network. *Nature methods*, 6 (1), 47–54.
- Stelzl, U., Worm, U., Lalowski, M., Haenig, C., Brembeck, F., Goehler, H., Stroedicke, M., Zenkner, M., Schoenherr, A., Koeppen, S., Timm, J., Mintzlaff, S., Abraham, C., Bock, N., Kietzmann, S., Goedde, A., Toksoz, E., Droege, A., Krobitsch, S., Korn, B., Birchmeier, W., Lehrach, H. & Wanker, E. (2005) A human proteinprotein interaction network: a resource for annotating the proteome. *Cell*, **122**, 957–968.
- Vanunu, O., Magger, O., Ruppin, E., Shlomi, T. & Sharan, R. (2010) Associating genes and protein complexes with disease via network propagation. *PLoS Computational Biology*, 6, e1000641.
- Watts, D. & Strogatz, S. (1998) Collective dynamics of 'small-world' networks. *Nature*, 393, 440–442.
- Yu, H., Braun, P., Yıldırım, M. A., Lemmens, I., Venkatesan, K., Sahalie, J., Hirozane-Kishikawa, T., Gebreab, F., Li, N., Simonis, N., Hao, T., Rual, J.-F., Dricot, A., Vazquez, A., Murray, R. R., Simon, C., Tardivo, L., Tam, S., Svrzikapa, N., Fan, C., de Smet, A.-S., Motyl, A., Hudson, M. E., Park, J., Xin, X., Cusick, M. E., Moore, T., Boone, C., Snyder, M., Roth, F. P., Barabási, A.-L., Tavernier, J., Hill, D. E. & Vidal, M. (2008) High-Quality Binary Protein Interaction Map of the Yeast Interactome Network. *Science*, **322** (5898), 104–110.



Fig. 4. Method comparison for (A) Y2H, (B) AP/MS, (C) LC, and (D) ALL yeast PPI networks. The following methods are compared: clique percolation (CliqPerc), greedy modularity optimization (GreedMod), Infomap, edge-SN, our method when clustering adjacent edges only and choosing the partition with the maximum density (eGDV-A-D), our method when hierarchically clustering both adjacent and non-adjacent edges and choosing the partition with the best overall partition quality (eGDV-NA-PD), and our method when hierarchically clustering both adjacent and non-adjacent edges and choosing the partition with the best overall partition quality (eGDV-NA-B). Clustering methods are compared with respect to the following measures: cluster coverage (CC), overlap coverage(OC), cluster quality (CQ), and overlap quality (OQ). The overall partition quality score (*y*-axis) is the sum of these four measures after each is normalized to [0,1], such that the maximum achievable score is four.



Fig. 5. Comparison of our node and edge clustering methods on the four yeast PPI networks (Y2H, LC, AP/MS, and ALL). nGDV-A denotes the node clustering method when node-GDV-similarity is used as the distance metric for hierarchical clustering of adjacent nodes only and the partition with the maximum partition density is selected. nGDV-NA denotes the node clustering method when node-GDV-similarity is used as the distance metric for hierarchical clustering of both adjacent and non-adjacent nodes and the partition with the best overall partition quality is selected. eGDV-A denotes the edge clustering method when edge-GDV-similarity is used as the distance metric for hierarchical clustering of adjacent edges only and the partition with the maximum partition density is selected. eGDV-A denotes the edge clustering method when edge-GDV-similarity is used as the distance metric for hierarchical clustering of adjacent edges only and the partition with the maximum partition density is selected. eGDV-NA denotes the edge clustering method when edge-GDV-similarity is used as the distance metric for hierarchical clustering of both adjacent and non-adjacent edges and the partition with the best overall partition quality is selected. The clustering methods are compared with respect to the following measures: cluster coverage (CC), overlap coverage (OC), cluster quality (CQ), and overlap quality (OQ). The overall partition quality score (*y*-axis) is the sum of these four measures after each is normalized to [0,1], such that the maximum achievable score is four. We compare our approach when using edge-GDV-similarity as the distance metric for node clustering of edges compared to clustering of nodes. And to answer this, one should use conceptually similar edge and node clustering methods, such as these. The figure shows that in each network: 1) we gain by clustering both adjacent and non-adjacent edges.