Evidence for Non-Finite-State Computation in a Human Social System

Simon DeDeo*

Santa Fe Institute, Santa Fe, NM 87501, USA (Dated: October 24, 2018)

We investigate the computational structure of a paradigmatic example of distributed social interaction: that of the open-source Wikipedia community. The typical computational approach to modeling such a system is to rely on finite-state machines. However, we find strong evidence in this system for the emergence of processing powers over and above the finite-state. Thus, Wikipedia, understood as an information processing system, must have access to (at least one) effectively unbounded resource. The nature of this resource is such that one observes far longer runs of cooperative behavior than one would expect using finitestate models. We provide evidence that the emergence of this non-finite-state computation is driven by collective interaction effects.

Social systems—particularly human social systems—process information. From the pricesetting functions of free-market economies [1, 2] to resource management in traditional communities [3], from deliberations in large-scale democracies [4, 5] to the formation of opinions and spread of reputational information in organizations [6] and social groups [7, 8], it has been recognized that such groups can perform functions analogous to (and often better than) engineered systems. Such functional roles are found in groups in addition to their contingent historical aspects and, when described mathematically, may be compared across cultures and times.

The computational phenomena implicit in social systems are only now, with the advent of large, high-resolution data-sets, coming under systematic, empirical study at large scales. What does not appear to be appreciated in the literature is the extent to which the statistics of their behaviors inform us about the expressive capability and processing abilities of the abstract computations the system is, in fact, performing.

Such constraints are important for both the prediction and conceptual understanding of observed phenomena. In order to make good predictions of symbolic systems, most learning algorithms assume that the (predictive) description being fit falls within the same model class as the observed process. Thus, evidence for a non-finite-state process is crucial because of the central role that finite-state models—often known as Hidden Markov Models, or HMMs—currently play in the description and inference of complex biological and social processes.

From the point of view of theory, the computational hierarchy (actually a partial order, see e.g., Ref. [9]) provides a mathematically rigorous way to classify the functional properties of a system independent of its material substrate, and allows one to determine when one system has strictly greater powers than another. From this point of view, it allows one to determine the emergence of novel computational abilities. A classic example of the importance of this conceptual aspect of the problem can be found in the persistent influence of the Chomsky Hierarchy for studies of both human [10] and non-human [11] communication.

A particular consequence of the general discussion of grammatical inference to be found in Ref. [12] is that a finite amount of data *by itself* can never distinguish between two classes whose distinctions are defined in terms of bounded *vs.* unbounded resources [13]. Our argument for

^{*} simon@santafe.edu; http://santafe.edu/~simon

the emergence of non-finite computational properties thus relies on the statistical inference of asymptotic properties of a finite-state system.

In particular, we prove a result that we refer to as the *probabilistic pumping lemma*: for any finite-state process, and any string w, of sufficient length, produced by the process, the probability that a word of length |w|n is found to be w^n decays exponentially as n becomes large.

The outline of our paper is as follows. We state, and prove, the lemma described above, in Sec. I and Appendix V. We establish the main empirical result of this work in Sec. II, where we examine the symbolic dynamics of the large-scale social phenomenon of article editing in Wikipedia. In considering the top ten most-edited articles in the encyclopædia, we find strong evidence in a majority of cases for a violation of the probabilistic pumping lemma, and thus symbolic dynamics over and above that of the finite-state.

We then discuss the possible origins of this effectively resource-unbounded system in Sec. III. We conclude with the implications of this finding for the computational complexity of social systems in the concluding Sec. IV, where we compare our findings with recent work and explore the analogy between formal grammars and social behavior.

I. THE PROBABILISTIC PUMPING LEMMA

We first show explicitly that probabilistic finite-state process have an exponential cutoff in the asymptotic distribution of repeated words. We do this by showing that the limiting ratio of $P(w^k)$ (the probability of observing the word w repeated k times in a sample of length |w|k), and $P(w^{k+1})$, as k becomes large, approaches a constant strictly less than unity [14]. We will be able to determine that limiting constant in terms of the properties of the underlying system.

Statement of Lemma. For any probabilistic finite-state process, and any initial distribution over internal states, there exists a positive real number ϵ , strictly less than unity, such that

$$\exp\left[\lim_{k \to \infty} \sup\left(\frac{1}{k} \log P(w^k)\right)\right] = \epsilon, \tag{1}$$

as k becomes large, with $0 < \epsilon < 1$, ϵ strictly greater than zero and strictly less than one. The limiting value, ϵ is the spectral radius of $A_{ij}(w)$, the natural extension of $A_{ij}(\sigma)$, the (Mealy-formalism) symbol transition matrix, to multi-letter words.

The complete proof is given in Appendix V. Tests of the numerical convergence of this relation are presented in Appendix VI, where we study how small machines (n, number of states, of order ten) converge to the bound of Eq. 1 for a uniform prior over spectral radius.

Informally, the lemma says that $P(w^k)$ is bounded above by an exponential cutoff of the form ϵ^k , $0 < \epsilon < 1$. For most processes, the relevant scale for the limit to obtain is k of order p, the number of states in the underlying process; we present numerical evidence for this in Appendix VI. Under the mild assumption that the system has passed through its transient states to an aperiodic final class, the probability $P(w^k)$ takes the form of a sum of exponentials,

$$P_{\text{nEXP}}(w^k) = \sum_{i=1}^n A_i e^{\log \beta_i k},$$
(2)

where here n is the number of states, and β_i , all strictly less than unity, are the eigenvalues of the $A_{ij}(w)$ transition matrix. Eq. 2, which we refer to as the nEXP model, forms the basis of our model comparisons, and our claims of evidence of non-finite-state computation, in the next section.

II. THE CASE OF WIKIPEDIA

We now consider a real-world example of how the probabilistic pumping lemma can be used to study complex processes, and to determine when the data may not be well-described by a hidden Markov model.

In particular, we consider whether the coarse-grained dynamics of the editing of a single article on the collaboratively-edited online system Wikipedia are well-described by a finite-state model. The probabilistic pumping lemma of Sec. I will provide the central source of evidence against this claim.

Wikipedia is an unusually successful example of collaborative, or crowd-sourced, editing; indeed, the distinctions between users and editors is so small that the terms can be used interchangeably. Despite the vast numbers of edits—including a non-trivial number of which are classified as "van-dalism" by other editors—and the dominance of anonymous and pseudonymous contributions, the accuracy of Wikipedia rivals that of more traditionally curated references such as the Encyclopædia Britannica over a wide range of technical topics [15].

Questions about the nature of the underlying processes that allow for this level of accuracy, along with those about the emergence of novel institutions [16] and behavioral norms [17, 18], puts the study of Wikipedia in a long tradition of questions about the nature of decentralized and self-organizing systems. In such systems, questions of conflict dynamics and conflict resolution are particularly compelling, and have received a great deal of recent attention [19]. It is for this reason that, in considering the edits that are made to an individual page, we consider a coarse-graining of the system sensitive to the initiation and resolution of conflict.

Coarse-graining is, of course, always necessary: the number of possible edits that editors can make is essentially unbounded and any edit may change, add, or delete arbitrary amounts of text from the article. A well-known distinction, however, exists between edits that alter the text in a novel fashion and those that "roll back" the text to a previous state. The latter kind of edit, called a "reversion" is used when an editor disagrees with an edit made by someone else and, instead of altering the text further, simply undoes the work of his or her opponent. Reverts are a natural class to consider in a study of online conflict [20–22]; as noted by Ref. [23], who studied reversion as a measure of conflict across multiple Wikipedia-like systems, reversions capture implicit cases of task conflict, which are strongly associated with the broader phenomenon of relationship conflict [24].

We thus coarse-grain the history of edits made on an article into two classes, C ("cooperate") and R ("revert"); an example of this process is shown in Table I, while the details of our processing of the raw data are given in Appendix VII. We ask the following: is the time series of C and R in the class of finite-state processes?

A negative answer to this question has great generality, in part due to the very weakness of the question itself. For example, establishing that this (very) coarse-grained description of the processes does not lead to a finite-state model means that no finer-grained description can be either. As an example of this, it is clear "by eye" that many edits that fall under the cooperate category are actually signs of other forms of conflict—for example, partial reversions, explicitly conflicting edits, and so forth—but a further subdividing of the symbol space, compatible with the original coarse-graining, can only exacerbate the problem.

By the same logic, if the dynamics of a single article, considered in isolation, are not finite-state, it necessarily implies that those describing an interacting system of articles are also non-finite-state.

time (UTC)	user	SHA1 (partial)	code
02:08	Sarah	4abc4aef1ea5	\mathbf{C}
05:02	Alexh25	1e3a2a4656d8	\mathbf{C}
05:04	Mhking	4abc4aef1ea5	\mathbf{R}
11:39	Trezatium	3b03700b0d9c	\mathbf{C}
12:15	Brazilfantoo	94a5c05ba10e	\mathbf{C}
12:31	Brandon39	3b03700b0d9c	\mathbf{R}
23:28	Titoxd	109986b8f390	\mathbf{C}
23:31	Titoxd	334a315944ce	\mathbf{C}
23:38	Titoxd	739c15e5bc6a	\mathbf{C}
23:40	Titoxd	3063a0289680	\mathbf{C}
23:42	Titoxd	7aafc8f3f762	\mathbf{C}

TABLE I. A day of edits on the George_W._Bush page, starting at midnight UTC, 21 March 2006. As can be seen by comparing SHA1 hashes of the page content, user Mhking reverted an edit by user Alexh25 to the previous version by user Sarah. Later in the day, user Brandon39 reverted user Brazilfantoo. In between, one can see "cooperative" stretches involving both single and multiple users. This sequence of events is coarse-grained into the substring "CCRCCRCC-CCC." The full string of (in this case) 44,955 action symbols forms the basis of the finite-state analysis. As with all data used in this study, this sequence is publicly available, in this case at http://en.wikipedia.org/w/index.php?title=George_W._Bush&offset=200603218&action=history.

It is well known, for example, that editors will often encounter each other, by accident or design, on different articles; including these processes in the model will, again, never decrease the complexity of the system.

Strictly speaking, a further condition obtains: if the collective phenomenon is not finite-state, then it can not be due to the interaction of a finite set of systems that are themselves finitestate. However, the aggregation of large numbers of finite-state systems may be able to accomplish non-finite-state tasks over a limited range. In this case, the combinatorics of the interactions of these finite-state systems are leveraged to produce a state space sufficiently large that it may be well-described by a system with truly unbounded resources.

Fig. 1 shows the distribution of consecutive C edits for the most edited article in the Wikipedia "main space" (*i.e.*, that set of pages supposed to constitute the encyclopedic content): that referring to George W. Bush, the 43rd President of the United States. We refer the reader to Appendix VII, where we show that $N(RC^kR)$ is a preferred estimator of the probability of repeated cooperation under the assumption of a finite-state process.

Even at a glance it is clear that a single exponential—which would appear as a straight line on a log-linear plot—is insufficient to describe the decay of $P(RC^kR)$ as a function of k. However, visual inspection alone is insufficient to determine whether to prefer a sum of exponentials (Eq. 2) or a sum of products of exponentials (Eq. 15) (both of which would be compatible with the asymptotics of a finite-state process) to an explicitly non-finite-state process.

We adopt a fully Bayesian approach to this question, and compare the simplest prediction of the probabilistic pumping lemma, Eq. 2, to alternative models that violate the asymptotic convergence



FIG. 1. Solid line: distribution of consecutive C ("cooperative") events in the edit history of the mostedited article on the English-language Wikipedia, George_W._Bush. Dashed line: maximum-likelihood fit for the asymptotic (ASY) model of Eq. 3, preferred over the sum of exponential model (nEXP) of Eq. 2. As derived in Appendix VII, Eq. 22, the count of prefix-suffix free strings RC^kR is a good estimator of $P(C^k) - P(C^{k+1})$. We note that the log-linear scale can make expected events seem anomalous; the best-fit model has a 34% chance of seeing at least one string RC^kR with k greater than 80.

sig.	page name	history length	$\Delta \mathcal{L}$
			ASY vs. nEXP
$< 10^{-8}$	George_WBush	44,984	18.6
$< 10^{-6}$	Islam	$17,\!586$	14.8
$< 10^{-5}$	United_States	30,715	12.2
	Global_warming	$19,\!376$	12.1
$< 10^{-4}$	Wikipedia	$31,\!591$	11.3
	Michael_Jackson	$26,\!662$	10.4
$< 10^{-3}$	2006_Lebanon_War	19,510	8.8
	Deaths_in_2009	20,902	7.7
$> 10^{4}$	Deaths_in_2007	18,215	-11.5
$> 10^7$	Deaths_in_2008	19,072	-17.5

TABLE II. log-Evidence ratios for the ten most-edited pages on Wikipedia; eight pages show strong (*p*-value $\leq 10^{-3}$) evidence for the asymptotic (ASY) model of Eq. 3 over and above that for the sum of exponentials (nEXP) model for the simplest version of the Probabilistic Pumping Lemma, Eq. 2. The strongest evidence in favor of finite-state computation are for two of the three "death list" pages, which collate otherwise unrelated information from other parts of the encyclopedia. Appendix VIII gives details on the use and computation of \mathcal{E} for model selection.

properties. In particular, we choose the following model,

$$P_{\rm asy}(w^k) = A \prod_{i=1}^k \left(1 - \frac{p}{i^{\alpha}}\right),\tag{3}$$

which we refer to as the asymptotic model, or ASY. Despite its simplicity (two parameters and an overall normalization) ASY appears to fit the data well over a wide range, reproducing the approximately-exponential cutoff at small k, but allowing for an extended tail of long cooperative

strings. It also explicitly violates the probabilistic pumping lemma, since

$$\exp\left[\lim_{k \to \infty} \sup\left(\frac{1}{k} \log P_{\text{asy}}(w^k)\right)\right] = 1.$$
(4)

We note in passing two alternative models, both of which share this property. The first is the commonly-used power-law

$$P_{\rm pl}(w^k) = \frac{A}{k^{\alpha}},\tag{5}$$

which is unable to reproduce the small-k regime and is thus strongly disfavored in model selection over the full range relative to nEXP. The second is the q-Pochhammer function,

$$P_{\rm qP}(w^k) = \prod_{i=1}^k (1 - pq^i), \tag{6}$$

which is a better fit to the data than the power-law case, but disfavored relative to ASY.

We compute Bayesian Evidence ratios for the nEXP and ASY model classes; explicitly, we compute an approximation to

$$\Delta \mathcal{E} = \log \frac{P(D|\text{nEXP})}{P(D|\text{ASY})},\tag{7}$$

where P(D|nEXP) and P(D|ASY) are the probabilities of finding the observed data D given either the nEXP or ASY as the underlying process. Details of this computation are presented in Appendix VIII. Table II shows that strong evidence against the nEXP model, and thus against the description of these series as finite-state, can be found in a majority of cases of the top-ten most-edited articles on the encyclopædia.

III. DISCUSSION

The results of the previous section strongly suggest that the social process of collaborative editing on Wikipedia is not finite-state.

The cases in Table II for which this is not the case are themselves of interest. These articles are of a very different nature ("death lists," collections of single sentences listing the dates of deaths of noteworthy individuals). That these cases are better described by the sum-of-exponentials model—in some cases, with extremely good evidence—suggests that the article content is relevant to the emergence of non-finite-state computation. This can be either because the user bases that particular content-types attract make it easier for the resultant system to produce non-finite-state behavior. Or, conversely, it could be that the article content itself leads to non-finite-state editing patterns.

As concrete—but, we emphasise, toy—examples of these two hypotheses, consider first Loop_quantum_gravity vs. Alternative_medicine. Both articles have a similar in-depth style of presentation, but will attract different communities of users and editors. These differing communities may hold social norms that lead to comparatively greater or lesser difficulties in producing the kinds of complex social phenomena that lead to non-finite-state time-series.

Conversely, consider Loop_quantum_gravity vs. List_of_physicists. In this case, the differing nature of the articles themselves—the latter simply a list of names—will lead to differing editing



FIG. 2. Solid line: distribution of consecutive single-user C ("cooperative") events in George_W._Bush. The contrast to the multi-user case is clear, showing that long periods of cooperative editing can not be accounted for by unbroken single-user patters. The distribution is well-modeled by a limiting form of ASY, Eq. 8, with distinct functional form and parameter values from the ASY fit for the multi-user case. The limit-ASY fit is preferred to the finite-state nEXP model at $\Delta \mathcal{E} \approx 7.6$ ($p < 10^{-3}$).

patterns. Users may be unlikely to take numerous consecutive edits to adjust the list article, and will have reduced probabilities of interaction. Behaviors are different despite the (presumably) similar composition and norms of the underlying communities.

An extreme version of the second hypothesis would be to claim that *all* of the non-finite-state computation comes from non-interacting users who independently and separately come into contact with an article. The interactions between individuals, on this picture, are unimportant; the content of the page itself serves as an effectively unbounded resource that allows violation of the exponential cutoffs required by the finite-state case.

For example, upon interacting with the page cooperatively (C), the user might alter it in such a way as to make the probability of a second cooperative edit (by the same user) more likely, and so on. Such a process could potentially lead to behaviors of the same nature as those accounted for by the ASY model, without having anything to do with any interpersonal or group-level interaction.

Fig. 2 examines this question in detail for the George_W._Bush case. We now augment the timeseries with an additional symbol, N, representing a change of user (for example, for the data shown in Table I, the new series would be CNCNRNCNCNRNCCCCCC), and count strings of consecutive Cs bracketed either by R or N; in other words, a change of user is considered to interrupt the run of Cs. We find the ASY model strongly disfavored compared to the nEXP model, while a limiting form of ASY, limit-ASY,

$$P_{\text{limit-ASY}}(w^k) = A \prod_{i=2}^k \left(1 - \frac{1}{i^{\alpha}} \right)$$
(8)

is preferred at the 10^{-3} level over nEXP. We caution that this non-exponential form is not necessarily evidence for non-finite computation in any particular individual, since the limit-ASY distribution found for the collection could be understood as the superposition of finite-state machines drawn from a distribution representing the spread of the properties of individuals.

The distinct functional form of the distribution at the individual level suggests that some aspect of interpersonal interaction plays a role in the non-finite nature of the full process. Whether this is driven by how groups are more able to take advantage of the effectively unbounded resource of the page itself (a "large scratchpad" model), or because some system memory is encoded in the interactions between the users themselves (an "interaction combinatorics" model) is an open question.

As a further check on the robustness of our results, we do a bootstrap resampling of the singleuser sequences, remove the 'N' symbols, and analyse the subsequent distribution. The resultant time-series show no evidence for violation of the pumping lemma (on average, slight evidence against ASY, $\langle \Delta \mathcal{E} \rangle$ equal to -1.2). This is in constrast to the strong evidence for ASY in the original series ($\Delta \mathcal{E}$ of +17.5), and is a further demonstration of the role of interaction effects in driving the violation of the finite-state case.

An obvious visual difference between Figs. 1 and 2 is the elimination of the long tail; it so turns out that long cooperative runs are multi-user events. While it is not the case that long cooperative events necessarily imply the ASY over the nEXP model (they can be found as well in the "death list" pages, where they are fit by a single long timescale exponential component), it is certainly true that the exponential decays implied by the probabilistic pumping lemma require increasingly unlikely fine-tunings of amplitude and decay constants to fit long periods of cooperative behavior.

The difficulties caused by this fine-tuning can be seen by examining the properties of explicitlyformulated maximum-likelihood finite state machines. For the George_W._Bush timeseries, we use a standard implementation [25] of the Expectation-Maximization algorithm [26] to find the particular finite-state machine most likely to have generated the observed (multi-user) system. We then measure $N(RC^kR)$ over multiple realizations of the output of these best-fit machines.

For machines with eight states (and thus a total of sixty-four underlying parameters), we find the predicted distribution $N(RC^kR)$ disfavored relative to the ASY model by $\Delta \mathcal{L}$ of 36.9 (or $p = 10^{-16}$). The majority of the relative log-likelihood penalty comes from longer cooperative runs. For shorter runs (less than twenty consecutive cooperations), the contribution to $\Delta \mathcal{L}$ is 3.57 (p = 0.03); for runs between twenty and eighty Cs, a total of 87 events, $\Delta \mathcal{L}$ is 10.6 (10^{-5}) ; and a single long cooperative event, of length 103 contributes $\Delta \mathcal{L}$ of 22.7 (10^{-10}) [27]. It is these more extreme cases in the long tail that are hardest to account for by reference to the finite-state case.

Recent work on the symbolic dynamics of bird song is relevant to the discussion of long tails and finite-state processes. Once regarded as strictly finite-state [28], the sound sequences produced by songbirds are now recognized to show features of non-finite-state computation. A recent, compact model of song production in the Bengalese finch (*Lonchura striata domestica*) [29], demonstrates the need for a self-modifying (and thus non-finite-state) Markov process; an analysis of data on a different species, the Zebra finch (*Taeniopygia guttata*), shows that the probability of an additional repetition, the analog of this paper's $P(C^{k+1})/P(C^k)$, decreases exponentially [30]. This is, of course, the other way to violate the probabilistic pumping lemma: the exponential of the limsup, Eq. 1, going to zero as opposed to unity. It is just as much evidence against finite-state computation, but found in the anomalous absence, rather than presence, of extreme events.

The absence of a violation of the probabilistic pumping lemma is not evidence against nonfinite-state computation. Even in the case of infinite data, it is easy to construct non-finite-state processes that show exponential decay in all repeated strings; an example can be constructed for a stochastic context-free language that generates strings of matched, but arbitrarily nested, parentheses: "...()((()))...". We defer detailed discussion of this question, and the extension of statistical constraints on stochastic grammars, to later work.

IV. CONCLUSIONS

This work has examined how cooperative behavior in a large-scale social system exceeds the finite-state case. Among other things, it strongly implies that game-theoretic models of cooperation that rely on finite-state models (such as the base-case tit-for-tat strategy for iterated prisoner's dilemma [31]) may yet be incomplete accounts of real-world cooperative behavior. The results of Sec. III further suggest that distinct mechanisms for the violation of the finite-state case are associated with, on the one hand, the cognitive properties of individuals taken separately, and on the other, the fundamentally social phenomenon of Wikipedia as a whole.

Much work remains to be done to determine the nature of this violation. The computational complexity of the process may be fundamentally connected to reputation or memory effects beyond the finite state [32–34]; alternatively, "rational actor" models may be insufficient and full accounts may require attention to the emergence of social norms [35].

Our work here has taken a rigorously *functionalist* viewpoint. Under this systemic view, what is important about a social system is not its particular material instantiation, nor even its history of formation or the psychological states of its individuals, but rather the way in which the sum of all these facts locate the system in an abstract state space, and the ways in which the historically, psychologically and materially-determined interactions are arranged so as to determine this more abstract system's future evolution.

In the modern version, the functionalist viewpoint leads us to give *computational* accounts of thought. This is most clearly seen in modern linguistics, where the biochemical processes that underlie the comprehension and production of language are reformulated as an abstract mathematical object: the formal languages of theoretical computer science. Formal language theory has been extended beyond the human language case to describe human social behavior (see, *e.g.*, Ref. [36] on "shaking hands"), animal communication [11, 37] and animal behavior [38] and pattern recognition more generally (Ref. [10] and references therein). This joins the empirical study of cognitive phenomena to a long tradition in the theory of complexity [9].

In general, computational accounts are indifferent to notions of the individual. When the state of a group is taken to be the sum of the states of the individuals that compose it, coarse-grainings of the system state will in general lead to effective theories [39] whose basic units are not descriptions of the state of any one individual. In the cognitive sciences the possibility of going beyond the boundaries of an individual agent when producing an account of a large-scale computation is sometimes called Wide Computationalism [40, 41] or the Extended Mind Hypothesis [42, 43].

We have previously given such accounts in the case of an animal system [44, 45], where a single formalism is used to attribute computational ("strategic") states to both individual animals and emergent groups. Ref. [46] provides an explicit analogy between the formal language hierarchy and the decompositions of Ref. [44].

Our work in this paper takes the necessary and logical step of extending this account to human social systems, considered not as ensembles of individual (formal) language users but as a freestanding and unreduced process. Over and above its role in the discussion about cooperative phenomena in social systems, our main result presents a challenge to theory: what formalisms are most natural for the description of non-finite-state processes in the physical world?

Our discussion in Sec. III demonstrates that empirical study itself can play a role in determining the relative importance of different ways a system can transcend the finite-state aspects of a system: large scratchpads vs. interaction combinatorics. While formal language theory presents us with a number of "post-finite" languages, such as the context-free grammars and pushdown automata [47], it seems likely that these will have to be extended or modified to provide tractable models for empirical investigation.

Acknowledgements. I thank John Miller, Nathan Collins, Jim Crutchfield, Ryan James, Cosma Shalizi and Cris Moore, and the attendees of the Santa Fe Institute Complex Systems Summer School 2012, in particular Christa Brelsford, Georg M. Goerg and Oleksandr Ivanov, for helpful conversations. I acknowledge the support of the Santa Fe Institute Omidyar Postdoctoral Fellowship, the National Science Foundation Grant EF-1137929, "The Small Number Limit of Biological Information Processing," and the Emergent Institutions Project.

- [1] F. A. Hayek. The use of knowledge in society. The American Economic Review, pages 519–530, 1945.
- [2] Allin Cottrell and W. Paul Cockshott. Calculation, complexity and planning: the Socialist Calculation debate once again. *Quantitative Finance*, 5(1):73–112, January 1993.
- [3] J. S. Lansing and W.C. Clark. Priests and Programmers: Technologies of Power in the Engineered Landscape of Bali. Princeton University Press, 2007.
- [4] A. Campbell, P. E. Converse, W. E. Miller, and D. E. Stokes. *The American Voter*. Midway Reprint Series. University of Chicago Press, 1980.
- [5] M.X.D. Carpini and S. Keeter. What Americans Know About Politics and Why It Matters. Yale University Press, 1997.
- [6] Stephen J. DeCanio and William E. Watkins. Information processing and organizational structure. Journal of Economic Behavior and Organization, 36(3):275–294, August 1998.
- [7] M. Gluckman. Gossip and Scandal. Current anthropology, 4(3):307–316, 1963.
- [8] M. Gluckman. Psychological, sociological and anthropological explanations of witchcraft and gossip: a clarification. *Man*, pages 20–34, 1968.
- [9] James P. Crutchfield. The calculi of emergence: computation, dynamics and induction. *Physica D:* Nonlinear Phenomena, 75(1-3):11-54, 1994.
- [10] Vitor C. Zimmerer, Patricia E. Cowell, and Rosemary A. Varley. Individual behavior in learning of an artificial grammar. *Memory & Cognition*, 39(3):491–501, December 2010.
- [11] C. ten Cate and K. Okanoya. Revisiting the syntactic abilities of non-human animals: natural vocalizations and artificial grammar learning. *Philosophical transactions of the Royal Society of London Series* B, Biological sciences, 367(1598):1984–1994, June 2012.
- [12] N. Chomsky. Aspects of the Theory of Syntax. MIT Press, 1969. Ch. 1.8.
- [13] C. de la Higuera. Grammatical Inference: Learning Automata and Grammars. Cambridge University Press, 2010.
- [14] We urge caution in the use of the term "probability of the word w^k ," which can be read ambiguously. Throughout this paper we take it to mean "probability that a randomly drawn string of length |w|k will be w^k ." Detailed discussion of the measurement of $P(w^k)$ from data appears in Appendix VII.
- [15] J. Giles. Internet encyclopaedias go head to head. Nature, 438(7070):900–901, 2005.
- [16] F. B. Viégas, M. Wattenberg, and M. M. McKeon. The hidden order of Wikipedia. Proceedings of the 2nd international conference on Online communities and social computing, pages 445–454, 2007.
- [17] F. B. Viégas, Martin Wattenberg, Jesse Kriss, and Frank van Ham. Talk Before You Type: Coordination in Wikipedia. In 40th Annual Hawaii International Conference on System Sciences, pages 78–78. IEEE, September 2007.
- [18] Jodi Schneider, Alexandre Passant, and John Breslin. A Qualitative and Quantitative Analysis of How

Wikipedia Talk Pages Are Used. In Proceedings of the WebSci10: Extending the Frontiers of Society On-Line, Raleigh, NC,, April 2010.

- [19] Taha Yasseri, Robert Sumi, András Rung, András Kornai, and János Kertész. Dynamics of conflicts in Wikipedia. PLoS ONE, 7(6):e38869, February 2012.
- [20] Bongwon Suh, Ed H. Chi, Bryan A. Pendleton, and Aniket Kittur. Us vs. Them: Understanding Social Dynamics in Wikipedia with Revert Graph Visualizations. In *IEEE Symposium on Visual Analytics Science and Technology*, pages 163–170. IEEE, October 2007.
- [21] Aniket Kittur, Bongwon Suh, Bryan A. Pendleton, and Ed H. Chi. He says, she says: conflict and coordination in Wikipedia. In *Proceedings of the SIGCHI conference on Human factors in computing* systems, pages 453–462. ACM Press, 2007.
- [22] Ulrik Brandes and Jürgen Lerner. Visual analysis of controversy in user-generated encyclopedias. Information Visualization, 7(1):34–48, February 2008.
- [23] Aniket Kittur and Robert E. Kraut. Beyond Wikipedia: Coordination and Conflict in Online Production Groups. In *Proceedings of the 2010 ACM conference on Computer supported Cooperative Work*, page 215, Savannah, GA,, February 2010. ACM Press.
- [24] Carsten K. W. De Dreu and Laurie R. Weingart. Task versus relationship conflict, team performance, and team member satisfaction: A. meta-analysis. *Journal of Applied Psychology*, 88(4):741–749, 2003.
- [25] Tapas Kanungo. UMDHMM: Hidden Markov Model Toolkit. In A. Kornai, editor, Extended Finite State Models of Language. Cambridge University Press, 1999. http://www.kanungo.com/software/software.html.
- [26] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery. Numerical Recipes 3rd Edition: The Art of Scientific Computing. Cambridge University Press, 2007. Ch. 16.
- [27] Although preference for the non-finite-state case does not depend on the inclusion of the longest run, this extreme event is itself of interest. It began May 26th, 2006, 19:54 UTC and ran until the 31st, lasting over 116 hours, and involving thirty-two editors. The page history can be found at http://en.wikipedia.org/w/index.php?title=George_W._Bush&offset=20060531162800&limit=105&action=hist
- [28] Robert C. Berwick, Kazuo Okanoya, Gabriel J. L. Beckers, and Johan J. Bolhuis. Songs to syntax: the linguistics of birdsong. *Trends in Cognitive Sciences*, 15(3):113–121, March 2011.
- [29] Dezhe Z. Jin and Alexay A. Kozhevnikov. A compact statistical model of the song syntax in Bengalese finch. PLoS computational biology, 7(3):e1001108, March 2011.
- [30] Mark Liberman. Finch linguistics. In Language Log, http://languagelog.ldc.upenn.edu/nll/?p=3261, July 2011. Informal analysis of data supplied by Ofer Tchernickovski and Dina Lipkind.
- [31] R. M. Axelrod. The Evolution of Cooperation: Revised Edition. Basic Books, 2006.
- [32] Robert Boyd. Mistakes allow evolutionary stability in the repeated prisoner's dilemma game. *Journal* of *Theoretical Biology*, 136(1):47–56, 1989.
- [33] Werner Raub and Jeroen Weesie. Reputation and Efficiency in Social Interactions: An Example of Network Effects. American Journal of Sociology, 96(3):626–654, November 1990.
- [34] Jonathan Bendor and Piotr Swistak. The Evolution of Norms. American Journal of Sociology, 106(6):1493–1545, May 2001.
- [35] E. Ostrom. Collective action and the evolution of social norms. *The Journal of Economic Perspectives*, 14(3):137–158, 2000.
- [36] R. S. Jackendoff. Language, Consciousness, Culture: Essays on Mental Structure. Jean Nicod Lectures. MIT Press, 2007.
- [37] M. D. Hauser, N. Chomsky, and T. Fitch. The Faculty of Language: What Is It, Who Has It, and How Did It Evolve? *Science*, 298(5598):1569–1579, November 2002.
- [38] R. Stoop, P. Nüesch, R. L. Stoop, and L. Bunimovich. Fly out-smarts man. arXiv preprint arXiv:1202.5913, 2012.
- [39] Simon DeDeo. Effective theories for circuits and automata. Chaos, 21:7106, September 2011.
- [40] R. A. Wilson. Wide computationalism. *Mind*, 103(411):351–372, 1994.
- [41] R. A. Wilson. Boundaries of the Mind: The Individual in the Fragile Sciences—Cognition. Cambridge

University Press, 2004.

- [42] D. Chalmers and A. Clark. The extended mind. Analysis, 58(1):7–19, 1998.
- [43] A. Clark. Supersizing the Mind: Embodiment, Action, and Cognitive Extension. Philosophy of Mind Series. Oxford University Press, 2011.
- [44] Simon DeDeo, David C. Krakauer, and Jessica C. Flack. Inductive Game Theory and the Dynamics of Animal Conflict. PLoS computational biology, 6(5):e1000782, May 2010.
- [45] Simon DeDeo, David Krakauer, and Jessica Flack. Evidence of strategic periodicities in collective conflict dynamics. *Journal of the Royal Society*, February 2011.
- [46] Jessica C. Flack and David C. Krakauer. Challenges for complexity measures: A. perspective from social dynamics and collective social computation. *Chaos*, 21:7108, September 2011.
- [47] C. Moore and S. Mertens. The Nature of Computation. Oxford University Press Oxford, 2011.
- [48] A. Berman and R. J. Plemmons. Nonnegative Matrices in the Mathematical Sciences. Classics in Applied Mathematics. Society for Industrial and Applied Mathematics, 1987. Ch. 2.3.
- [49] J. Hartmanis and R. E. Stearns. *Algebraic structure theory of sequential machines*. Prentice-Hall international series in applied mathematics. Prentice-Hall, 1966.
- [50] An index *i* leads to an index *j* (written $i \to j$) iff there exists a *k* such that $A_{ij}^k(w) > 0$. Indices *i* and *j* communicate if $i \to j$ and $j \to i$. Communication is an equivalence relation, so that classes can be built that contain indices that communicate with each other. Essential classes (sometimes called "final" classes [48]) are those which do not lead to any index outside the class; inessential classes are those which may.
- [51] E. Seneta. Non-negative Matrices and Markov Chains. Springer Series in Statistics. Springer, 2006. Ch. 1.2.
- [52] For any set of transitions between classes, the number of self-transitions is bounded by k, and the number of distinct classes to assign those self-transitions to is bounded by p, the number of states in the machine. The number of ways p terms can sum to k is $\binom{k-1}{p-1}$, which is bounded by the polynomial k^p .
- [53] N. Pippenger. Theories of Computability. Cambridge University Press, 1997.
- [54] Robert E. Kass and Adrian E. Raftery. Bayes Factors. Journal of the American Statistical Association, 90(430):773–795, June 1995.
- [55] Andrew R. Liddle. How many cosmological parameters? Monthly Notices of the Royal Astronomical Society: Letters, 351(3):L49–L53, July 2004.
- [56] A simple (and usually unwarranted) approximation to this function gives the BIC, or "Bayesian Information Criterion," which prescribes a penalty of $n \log |D|$, where |D| is the amount of data.
- [57] Michael J. Mortonson, Hiranya V. Peiris, and Richard Easther. Bayesian analysis of inflation: Parameter estimation for single field models. *Physical Review D.*, 83(4):43505, February 2011.
- [58] Richard Easther and Hiranya V. Peiris. Bayesian analysis of inflation. II. Model selection and constraints on reheating. *Physical Review D.*, 85(1):103533, May 2012.
- [59] Jorge Noreña, Christian Wagner, Licia Verde, Hiranya V. Peiris, and Richard Easther. Bayesian analysis of inflation. III. Slow roll reconstruction using model selection. *Physical Review D.*, 86(2):23505, July 2012.
- [60] D. J. C. MacKay. Information Theory, Inference and Learning Algorithms. Cambridge University Press, 2003. Ch. 28.

V. APPENDIX: PROOF OF THE PROBABILISTIC PUMPING LEMMA

Statement of Lemma. For any probabilistic finite-state process, and any initial distribution over internal states, if there exists a p such that for all k > p, $P(w^k) > 0$, there exists a positive real number ϵ , $0 < \epsilon < 1$, such that $\exp \lim_{k \to \infty} \sup (1/k) \log P(w^k) = \epsilon$ as k becomes large.

Proof. We will assume the Mealy machine formalism (observed symbols are emitted upon transitions between internal states [49]). Let A be the transition matrix for the process; an element $A_{ij}(\sigma)$ gives the conditional probability of a transition to state j, emitting symbol $\sigma \in \Sigma$, given that one was previously in state i. If the process is reducible, we will assume that sufficient time has passed for the process to reach irreducible subspace of this matrix, and we confine our attention to that subspace.

We may extend the definition of $A(\sigma)$ to words, as

$$A_{ij}(w) = \sum_{a_1,\dots,a_{|w|}} A(w_0)_{ia_1} A(w_1)_{a_1 a_2} \cdots A(w_{|w|})_{a_{|w|}j},$$

where w_i is the *i*th symbol in word w. We have, further, given assumptions,

$$0 < A_{ij}(w) \le A_{ij}^{|w|}, (9)$$

or, in words, the probability to go from state i to state j and emit the word w is less than or equal to that of simply going from i to j in the same number of steps.

By the Perron-Frobenius theorem, the inequality of Eq. 9 implies that all eigenvalues, β_i , of $A_{ij}(w)$ are within the unit circle $(|\beta_i| \leq 1 \text{ for all } i)$ with equality obtaining only in the case that $A_{ij}(w)$ is identical to $A_{ij}^{|w|}$. We neglect this latter, trivial case, which only obtains when w is shift-invariant and the all observation runs are given by repeated instances of w.

If the system (or our knowledge of it) is distributed over its internal states according to probability vector π_i , we can write the probability of observing a repeated string w as a trace,

$$P(w^k) = \sum_{i,j=1}^n \pi_i A_{ij}^k(w).$$
 (10)

Eq. 9 implies that all eigenvalues, β_i , of $A_{ij}(w)$ are within the unit circle $(|\beta_i| \leq 1 \text{ for all } i)$ with equality obtaining only in the case that $A_{ij}(w)$ is identical to $A_{ij}^{|w|}$. In this latter case, of course, the system produces the same word w, and only that word, repeatedly and without variation, and so $P(w^k)$ is (in the case that w is shift-invariant) trivially one. Excluding this case, which can be read easily off the data, we may take the bound to be a strict inequality.

While we have assumed for simplicity that A_{ij} is irreducible, this will not usually be the case for $A_{ij}(w)$. This latter matrix will in general contain both essential and inessential "self-communicating" classes [50] along with a set of nuisance indices that connect to no other class (*i.e.*, *i* for which $A_{ij}(w)$ is equal to zero for all *j*) [51].

The structure of $A_{ij}(w)$ may be visualized as a directed acyclic graph. Inessential classes may have non-zero out-degree, while essential classes, and nuisance indices, are the terminal nodes. Self-loops are permitted, and exist for both inessential and essential classes; these will be crucial to our argument below.

Because the initial distribution π may have zero entries, we consider only the part of $A_{ij}(w)$ corresponding to descendants of the non-zero part of π in the associated directed acyclic graph.

Transitions among the set of nuisance indices, by definition, can not repeat an index. Thus their structure is not relevant to the asymptotic behavior of $P(w^k)$, and we may focus on the essential and inessential classes.

We are particularly interested in the classes that will dominate the $P(w^k)$ probability as k becomes large. Consider the restriction of $A_{ij}(w)$ to a particular class α : *i.e.*, construct a submatrix from $A_{ij}(w)$ using only $i, j \in \alpha$. Call this restriction $\alpha_{ij}(w)$. Consider, similarly, the restriction of the distribution π to this class. Then, the probability of producing k copies of w, while remaining in the class α , is

$$P(w^{k}|\alpha) = \sum_{i,q=1}^{|\alpha|} \beta_{q}^{k} \pi^{(q)} v_{i}^{(q)},$$
(11)

where β_q is the *q*th eigenvalue of $\alpha(w)$, and

$$\pi_i = \sum_{q=1}^{|\alpha|} \pi^{(q)} v_i^{(q)}.$$
(12)

By construction of the equivalence classes, α is irreducible. Then, the largest eigenvalue of this matrix, β_1 , is real, has a strictly positive eigenvector, and $\pi^{(1)}$ is necessarily greater than zero.

If $\alpha_{ij}(w)$ is acyclic, then the leading term in $P(w^k|\alpha)$ can be written

$$P(w^k|\alpha) = A_1 \beta_1^k \left(1 + \sum_{q=2}^{\alpha} A_q \left(\frac{\beta_q}{\beta_1}\right)^k \right), \tag{13}$$

where $A_1 > 0$ and $\beta_q < \beta_1$.

If the period, d, of $\alpha_{ij}(w)$ is greater than one, we will have additional eigenvectors associated with complex rotations of r, $r \exp 2\pi i k/d$, $k = \{1 \dots d-1\}$. These will lead to additional oscillatory terms in both the leading order term and its corrections. The oscillations of the leading term will be governed by an overall exponentially-decaying envelope, so that

$$\exp\left[\lim_{k \to \infty} \sup\left(\frac{1}{k} \log P(w^k | \alpha)\right)\right] = \beta_1, \tag{14}$$

regardless of the period of $\alpha_{ij}(w)$.

Having understood the single-class case, we now consider w^k strings generated by multiple classes.

Any particular string w^k may be generated by a set of transitions within and between classes. Because these transitions are governed by the directed acyclic graph structure, there will be a finite number of transitions between states. Thus, as k becomes large, the probability of $P(w^k)$ for a particular set of transitions will be governed by the self-transitions, given by terms of the form Eq. 14.

In particular, $P(w^k)$ is the sum of a finite number of terms; each term in the sum is a product of at most p transitions between classes, and at least k - p terms of the form $P(w^n | \alpha)$, for different α . Explicitly,

$$P(w^{k}) = \sum_{i \in p(G)} T_{i} \prod_{j=1}^{N} P(w^{n_{i,j}} | \alpha_{j}),$$
(15)

where *i* indexes the paths of length *k* through the graph *G* representing the underlying $A_{ij}(w)$ structure, T_i is a prefactor governing the probabilities of transitions between classes, *N* is the number of classes, and the total number of within-class transitions is forced to grow with *k*,

$$\sum_{j=1}^{N} n_{i,j} \ge k - p \tag{16}$$

for all possible paths i.

For large k, the growth in the number of possible paths (*i.e.*, the growth of the |p(G)|) is bounded by the growth in the number of ways to partition the sum in Eq. 16. In particular, for large k, the number of possible paths relevant to $P(w^k)$ can increase only polynomially in k [52].

For large k, each term in the sum of Eq. 15 is decreasing exponentially, governed by products of the $\beta_{i,1}$, the largest eigenvalues for the classes that have self-transitions for that term. The dominant terms in the sum will be those for which the exponential decline is slowest. By the Perron-Frobenius theorem, the largest eigenvalue of a submatrix associated with a class of $A_{ij}(w)$ is equal to the spectral radius of the matrix as a whole. If $P(w^k)$ is greater than zero for k larger than p, the pigeonhole principle invoked in the ordinary pumping lemma [53] allows us to assume the existence of at least one self-communicating class; this then means that the spectral radius is equal to that of $A_{ij}(w)$ itself.

$$0 < \exp\left[\lim_{k \to \infty} \sup\left(\frac{1}{k} \log P(w^k)\right)\right] = \rho(A_{ij}(w)) < 1,$$
(17)

which was to be proved.



FIG. 3. Numerical study of convergence of repeated word frequencies to exponential decay with cutoff predicted by the spectral radius. Shown here is the the measured decay rate to the asymptotic limit predicted by Eq. 17, for irreducible finite-state processes with ten states, two output symbols $\{C, R\}$, wequal to C, and a uniform distribution over values of $\rho(A_{ij}(w))$, the spectral radius and asymptotic decay rate, between $0 \leq \rho < 1$. Light blue shows 2σ , and dark blue 1σ ranges about the median value. For empirical work, convergence is much faster when considering $[P(w^{q+k})/P(w^q)]^{1/k}$, with q larger than the (assumed) number of states.

VI. APPENDIX: NUMERICAL TESTS OF CONVERGENCE PROPERTIES

With a view towards determining how the lemma of the previous section applies to actual finitestate processes, we study a restricted class of machines numerically. We sample from the space of probabilistic unifilar machines with p states over a two-symbol alphabet. Such a system can be represented by a weighted, directed graph, with each node having at least one, and at most two outgoing edges, each of which is associated with one of the two symbols, and whose weights sum to unity.

For small p, this space can be described completely: for each node, we have a choice of one vs. two outgoing edges; in the case of only one outgoing edge, we must choose between the two symbols. Neglecting the possibility of equivalent machines, we then have the number of such machines, as a function of p, as

$$N(p) = (2p + p^2)^p,$$
(18)

which grows rapidly: there are 12 billion such machines with six states, and more than 10^{400} with one hundred states.

We are most interested in how quickly the statistics of an actual machine approaches the limiting value given by Eq. 17. For any particular $A_{ij}(w)$, we can compute the spectral radius and compare that to the ratio $P(w^k)/P(w^{k-1})$ found for distributions over initial conditions that include a self-communicating class as a function of k.

In Fig. 3 we show convergence to the limit by sampling the space of strongly-connected ten-state machines, and considering the frequency of a single repeated symbol. We take a uniform prior over $\rho(A_i(w))$, the spectral radius and limit established by the lemma of the previous section, and show



FIG. 4. Convergence to exponential cutoff as seen with $\hat{C}(q, k)$ (Eq. 20), for the same system as in Fig. 3. Here we take q equal to ten, the number of states. For the same amount of data, convergence is faster for \hat{C} than C; here convergence for \hat{C} to the asymptotic value (at 1σ confidence), is achieved for k equal to thirty.

the convergence ratio, *i.e.*,

$$C(k) = \frac{[P(w^k)]^{1/k}}{\rho(A_{ij}(w))},$$
(19)

to provide a numerical example of the limiting process established in the previous section. For small $k, P(w^k)$ may be dominated by movement through nuisance states and inessential classes, and by contributions from essential classes that have small self-communication probability. Convergence to the spectral radius thus occurs much faster when considering

$$\hat{C}(q,k) = \frac{[P(w^{q+k})/P(w^q)]^{1/k}}{\rho(A_{ij}(w))},$$
(20)

where q is longer than the relevant scales of the transient phenomena (*e.g.*, at least as large as the assumed number of states.) This is shown explicitly in Fig. 4, where we take q to be the number of states in the system.

VII. APPENDIX: WIKIPEDIA ANALYSIS

Our coarse-graining of behaviors on any particular page aims at locating where one user reverts (undoes) the contributions of another editor completely. We locate reversion edits in two distinct ways. Firstly, following Ref. [23], we can identify reversion edits by the presence of keywords, such as rv and revert, in the edit summaries; we do so with the following regular expression: /([Rr]v | [Uu]ndid|[Rr]evert)/. Secondly, following analyses such as those of Ref. [19], we can look for versions of a page with identical SHA1 checksums; the version with the later timestamp may thus be considered a revert to the earlier page. In general, these two metrics align very well, although not perfectly; in this work, we focus on the latter method as a more objective one that does not rely on editors self-reporting. We do not include self-reverts, or edits that do not alter any aspect of the page (*i.e.*, that would otherwise look like "reverts to the current version").

A feature of the naive classification of non-revert edits is the presence of so-called "vandalism"– improper and non-constructive modifications or blanking of the page, which (since they usually do not take the form of reversion) would be classed as cooperative. As noted in the main text of Sec. II, this does not undermine the use of the resultant series to test for non-finite computation. More detailed descriptions ("prosocial non-revert" vs. "antisocial non-revert") and similarly for the revert case, where pro-social reverts repair vandalism) are certainly possible, and, from the point of view of a detailed understanding, extremely desirable. However, this fine-graining of the time-series can only increase the complexity of the process.

The probabilistic pumping lemma works in terms of $P(w^k)$, and our analysis considers the probability of repeated cooperation. However, the measurement of $P(C^k)$ in the data, if done naively, leads to unacceptable results. In particular, estimating $P(C^k)$ for a particular page by counting the number of times the string C^k appears in the time-series, leads to strong bin-to-bin correlations, since an observation of a string C^k necessarily leads to observations of strings of the form $C^{k-1}, C^{k-2}, \ldots, C^{k-\lfloor k/2 \rfloor+1}$, and then *two* observations of the form $C^{k-\lfloor k/2 \rfloor}$, and so on. This would lead to excessive complications in the likelihood analysis; conversely, if the correlations are neglected, it leads to claims of heavy-tailed distributions that spuriously rule out exponential decay.

Instead, we count prefix-suffix-free strings that do not have this shift problem—in particular, we consider the quantity $N(RC^kR)$. As long as $N(RC^kR)$ is significantly less than N, counts of RC^kR and RC^mR are independent of each other and we can write

$$P(RC^kR) \approx \frac{N(RC^kR)}{N}$$

The quantity $P(RC^kR)$ itself can be written as

$$P(RC^{k}R) = P(R)P(C^{k}|R)P(R|RC^{k}) = P(R)P(C^{k}|R)\left[1 - P(C|RC^{k})\right]$$
$$= P(R)\left[P(C^{k}|R) - P(C^{k+1}|R)\right].$$
(21)

In the case that $P(C^k|R)$ is the sum of exponentials in k, we have

$$N(RC^k R) \propto P(C^k | R) \propto P(C^k), \tag{22}$$

or, in words, that if $P(C^k)$ is a sum of exponentials, so is $N(RC^kR)$. The relationship between these two quantities is not always so simple; in the ASY case, as well as the power-law and q-Pochhammer case, Eq. 21 implies that the quantity $N(RC^kR)$ has a different functional form from

$$\Delta P_{\text{asy}} = \frac{Ap}{(k+1)^{\alpha}} \prod_{i=1}^{k} \left(1 - \frac{p}{i^{\alpha}} \right), \qquad (23)$$

$$\Delta P_{\rm pl} = A \left(\frac{1}{k^{\alpha}} - \frac{1}{(k+1)^{\alpha}} \right) \approx \frac{A\alpha}{k^{\alpha+1}},\tag{24}$$

and

$$\Delta P_{\rm qP} = pq^{k+1} \prod_{i=1}^{k} \left(1 - pq^k \right).$$
(25)

In words, Eq. 23 shows that measurement of $N(RC^kR)$ leads to power-law behavior in the long tail. Conversely, note that the q-Pochammer function leads to an exponential cutoff.

VIII. APPENDIX: DETAILS ON MODEL SELECTION

In this section we describe in greater detail our methods for distinguishing between the asymptotic and exponential models.

Computation of the likelihood ratio requires an error model for the distributions of $N(RC^kR)$, such as those shown in Fig. 1. Since we lack an explicit model for the errors themselves, as a first approximation, we take measurements of $N(RC^kR)$ to be identically and independently distributed. For $N(RC^kR) \ll N$, N the total number of observations, this is a reasonable assumption. Given this assumption, the Poisson distribution of counts follows, and computation of \mathcal{L} , the log-Likelihood, or $\log P(D|\vec{w}, M)$, for any particular model M with parameters \vec{w} , can be written as

$$\Delta \mathcal{L} = \sum_{k=1}^{k_{\text{max}}} N(RC^k R) \log \lambda(\vec{w}, k) - \lambda(\vec{w}, k), \qquad (26)$$

where we drop model-independent constants. Given sufficiently flat priors, $P(\vec{w}|M)$ around the peak of this function, this is sufficient to estimate many quantities of interest, including the maximum *a posteriori* values of \vec{w} and the error bars on those estimates.

Our main goal, however, is not parameter estimation, but rather model selection, where one compares models with different sets of parameters. In our particular case, one class of models (nEXP) can approximate, by superposition of exponentials, the other class (ASY). As the number of exponentials in the sum increases, the approximation becomes increasingly good. We would like to know when we are justified in preferring the more parsimonious model.

Two main frameworks for the resolution of this question exist. On the one hand, the Aikiake Information Criterion (AIC) can be used to estimate the expected KL divergence between the predictions of a model and the "true process." In the limit of large amounts of data, it prescribes a constant penalty of n, the number of parameters, to the likelihood.

This penalty is sometimes taken as an "Occam penalty," but the correct interpretation is as a guide for prediction out of sample. Prediction out of sample is a conceptually distinct problem, since a complicated approximation to the true model may work very well in a limited range, particularly in the presence of experimental noise; in Monte Carlo testing, AIC is insufficiently rigorous, and tends to prefer complicated approximations [54]. A well-known formal result is that AIC is "dimensionally inconsistent," meaning that even in the limit of infinite data, use of the AIC will lead to non-zero probability of choosing an (incorrect) approximation [55].

On the other hand, one can compute (or approximate) what is called the Evidence [56], which requires knowledge of both the likelihood, $P(D|\vec{w}, M)$, and the prior expectation of parameter ranges, $P(\vec{w}|M)$,

$$E = P(D|M) = \int P(D|\vec{w}, M) P(\vec{w}|M) \ d^k w, \tag{27}$$

where k is the number of parameters (dimensionality of \vec{w}). Formally, the Evidence is proportional to "the probability of the model M, given the data observed," if equal prior probability is given to the models under consideration. As in all model selection cases, absolute values of the Evidence are irrelevant. One considers only ratios and phrases the question, as in Table II, as to whether (for example) "model A is at least a factor of 10^3 more likely than model B."

In this work, we take the latter approach, operating entirely within the Bayesian framework. This is because our contrasting model classes have small numbers (less than ten) of parameters, all of which have clearly specifiable priors, $P(\vec{w}|M)$. Computation of the full posterior is now common when these circumstances obtain, as is often the case in the exact sciences [57–59].

In order to calculate E, we use the Laplace (or saddle point) approximation; in log-units,

$$\mathcal{E} = \log E \approx \mathcal{L}(\vec{w}_{\max}) + \log P(\vec{w}_{\max}|M) - \frac{1}{2}\log \det A + \frac{1}{2}k\log 2\pi,$$

where \mathcal{L} is the log-likelihood, \vec{w}_{max} are the parameters that maximize the likelihood, and A is the Hessian, equal to

$$A_{ij} = -\frac{\partial^2 \mathcal{L}}{\partial w_i \partial w_j}.$$
(28)

We refer the reader to Ref. [60] for details on this approximation.

It remains to specify the priors $P(\vec{w}_{\text{max}}|M)$ for the two models. The nEXP class has 2n parameters; the ASY class has 3. The parameters are of two kinds.

Both nEXP and ASY have a parameter corresponding to the one-step decay of the underlying quantity $P(C^k)$, in the case of nEXP, there are *n* such parameters, β_i , that play this role; these correspond to the eigenvalues of the transition matrix $A_{ij}(w)$. In the case of ASY, there is only one, *p*. We take a uniform prior in *p* (ASY) and β_i (nEXP). We allow all *p* to range independently between zero and 0.995; the high end corresponds to an exponential cutoff of order 200 repeats, much longer than seen in the data.

We then have normalizations of terms (*n* normalizations for nEXP, one for ASY). These are fixed by the value of $P(C^1)$, the overall cooperative fraction.

$$N(C) \approx NP(C). \tag{29}$$

The maximum value of P(C) is unity. This then leads to an overall area factor of

$$\frac{N^n}{n!},\tag{30}$$

for nEXP, where the factor of n! is because the overall sum of all normalizations is confined to the interior of an *n*-dimensional simplex. In the case of ASY, $P(C^1)$ is equal to A(1-p). We thus have to integrate over the range of p values to find the area associated with the ASY normalization prior,

$$N \int_0^{0.995} \frac{1}{1-p} \, dp \approx 5.29832N. \tag{31}$$

Finally, ASY has a third parameter, α . For each value of 1 - p, we allow this to range between zero (pure exponential) and $\alpha(p)$, where $\alpha(p)$ is set to give a 1/e cutoff at 200 repeats. As an example, $\alpha(0.995)$ is zero; if α were greater than zero, the overall function would have an exponential cutoff longer than 200 repeats. Given these, the area factor for nEXP is 0.995^n , and for ASY is it

$$\int_{0}^{0.995} \alpha(p) \ dp \approx 1.28841. \tag{32}$$

Putting together all these area factors, we can then pre-compute $-\log A$, equal to $\log P(\vec{w}_{\max}|M)$, a constant independent of \vec{w} . For the George_W._Bush article, for example, we have $-\log A$ equal to -12.6 for the ASY case, and -10.3 (1EXP), -18.7 (2EXP), -27.4 (3EXP). Note that prior areas are not directly comparable between different models; "change of units" (*e.g.*, working in terms of $P(RC^kR)$ vs. $N(RC^kR)$) will scale A. This scaling, however, is directly compensated for by the Hessian determinant term.

Together with the max log-likelihood, the determinant of the Hessian, and the $+k \log 2\pi$, these are sufficient to compute the (Gaussian approximation to) the relative log-Evidence for the two model classes $\Delta \mathcal{E}$, reported in Table II. In general, the highest evidence member of the nEXP class is either 3EXP or 4EXP. Table III gives the results for the top thirty most-edited pages.

sig.	page name	history length	$\Delta \mathcal{L}$
			ASY vs. nEXP
$< 10^{-8}$	George_WBush	44,984	18.6
$< 10^{-6}$	World_War_I	14,515	15.9
	Islam	17,586	14.8
$< 10^{-5}$	Iraq_War	14,785	12.8
	Scientology	14,468	12.2
	United_States	30,715	12.2
	Global_warming	19,376	12.1
$< 10^{-4}$	Australia	$13,\!574$	11.4
	Wikipedia	$31,\!591$	11.3
	September_11_attacks	17,078	11.3
	Israel	16,036	11.1
	Super_Smash_BrosBr	15,300	11.1
	Turkey	13,703	11.0
	Gaza_War	$14,\!654$	10.7
	List_of_Omnitrix_ali	16,263	10.6
	Michael_Jackson	26,662	10.4
	Canada	17,441	9.4
	Blink-182	13,839	9.3
$< 10^{-3}$	2006_Lebanon_War	19,510	8.8
	Blackout_(Britney_Sp	$15,\!637$	7.9
	Deaths_in_2009	20,902	7.7
$< 10^{-2}$	Heroes_(TV_series)	13,980	6.6
	Xbox_360	16,465	6.4
	Lost_(TV_series)	14,500	5.1
	Paul_McCartney	$16,\!453$	4.7
(no det.)	Eminem	17,071	4.3
	Pink_Floyd	15,606	2.9
	Deaths_in_2006	14,072	0.8
$> 10^{4}$	Deaths_in_2007	18,215	-11.5
$> 10^{7}$	Deaths_in_2008	19,072	-17.5

TABLE III. log-Evidence ratios for the thirty most-edited pages on Wikipedia.