arXiv:1302.3869v4 [q-bio.NC] 1 Sep 2013

The Ising model on a brain network maximizes Information Transfer at criticality

D. Marinazzo,¹ M. Pellicoro,² Guo-Rong Wu,³ L. Angelini,² J.M. Cortes,^{4,5} and S. Stramaglia²

¹Faculty of Psychology and Educational Sciences, Department of Data Analysis,

Ghent University, Henri Dunantlaan 1, B-9000 Ghent, Belgium

²Dipartimento di Fisica, Universitá degli Studi di Bari and INFN, via Orabona 4, 70126 Bari, Italy

³Key Laboratory for NeuroInformation of Ministry of Education, School of Life Science and Technology,

University of Electronic Science and Technology of China, Chengdu 610054, China

⁴Ikerbasque, The Basque Foundation for Science, E-48011, Bilbao, Spain.

⁵Biocruces Health Research Institute. Hospital Universitario de Cruces. E-48903, Barakaldo, Spain.

(Ω Dated: November 2, 2018)

We implement the Ising model on a structural connectivity matrix describing the brain at a coarse scale. Tuning the model temperature to its critical value, i.e. at the susceptibility peak, we find a maximal amount of total information transfer between the spin variables. At this point the amount of information that can be redistributed by some nodes reaches a limit and the net dynamics exhibits signature of the law of diminishing marginal returns, a fundamental principle connected to saturated levels of production. Our results extend the recent analysis of dynamical oscillators models on the connectome structure, taking into account lagged and directional influences, focusing only on the nodes that are more prone to became bottlenecks of information. The ratio between the outgoing and the incoming information at each node is related to the number of incoming links.

PACS numbers: 05.50.+q,87.19.L-

Methods based on the theory of complex networks are becoming more and more popular in neuroscience [1]. Moreover, the inference of the underlying network structure of complex systems [2] from time series data is an important problem that received great attention in the last years, in particular for studies of brain connectivity [3–6]. This problem can be handled by estimating, from data, the flow of information between variables, as measured by the transfer entropy [7, 8], a model-free measure designed as the Kullback-Leibler distance of transition probabilities. Recently [9] it has been shown that transfer entropy is strongly related to Granger causality [10], a powerful and diffuse model-based approach to reveal drive-response relationships in dynamical systems which is based on prediction: if the prediction error of the first time series is reduced by including measurements from the second one in the linear regression model, then the second time series is said to have a causal influence on the first one.

In a recent paper [11] it has been shown that the pattern of information flow among the components of a complex system is the result of the interplay between the topology of the underlying network and the capacity of nodes to handle the incoming information, and that, under suitable conditions, this pattern can reveal the emergency of the law of diminishing marginal returns [12], a fundamental principle of economics which states that when the amount of a variable resource is increased, while other resources are kept fixed, the resulting change in the output will eventually diminish. The origin of such behavior resides in the structural constraint related to the fact that each node of the network may handle a limited amount of information. In [11] the information flow pattern of several dynamical models on hierarchical networks has been considered and found to be characterized by an exponential distribution of the incoming information and a fat-tailed distribution of the outgoing information, a clear signature of the law of diminishing marginal returns. This pattern was thus found in artificial hierarchical networks, and in electroencephalography signals recorded on the scalp.

Motivated by the evidence that brain function resides in its ability to process and store information, and by the fact that brain dynamics is associated to criticality [13– 15], in this study we investigate a dynamical model implemented on a structure derived from the actual structural connections in the human brain. We consider an anatomical connectivity matrix describing the brain at a coarse scale (66 nodes), obtained via diffusion spectrum imaging (DSI) and white matter tractography [16], provided by one of the authors of the original paper. We implement on it an Ising model with Glauber dynamics [17], estimating numerically the information transfer between spins. Varying the temperature, the susceptibility shows a peak which is related to a phase transition occurring in the limit of large networks [18], characterized by long range correlations; although we are dealing with a network of small size, we will refer to the temperature at the peak of χ as the *critical* state of the system. We find that at criticality the Ising model dynamics results in the maximal amount of total information transfer among variables and that this information transfer is affected by the law of diminishing marginal returns, as it appears comparing the distributions of incoming and outgoing information. The spatial modulation of this phenomenon is analyzed evaluating, at each node, the ratio r between the outgoing and the incoming information. It turns out that r is related to the in-strength of the brain network:

nodes with high r are those more prone to become bottlenecks as the information flow increases.

The couplings of the Ising model are $J_{ij} = \beta A_{ij}$, where A is the 66×66 anatomical connectivity matrix, which corresponds to an undirected weighted network with average degree 17.4. Whilst in [11] we studied the diluted Ising model on an artificial network, here we analyze the Ising model on the structural architecture of the brain, characterized by two main modules corresponding to the two hemispheres. Since it has been shown that for Ising models Granger causality provides a good approximation to the transfer entropy while being computationally much more efficient [19], here we estimate information flows in terms of the Granger causality; in other words, we adopt the Gaussian approximation to the Ising model. The order of the regressive model (maximum lag) is fixed to m = 1. Samples of 10^4 iterations are used to estimate the Granger causality; we verified that these samples are long enough to provide robust results. Moreover, we have also estimated the total bivariate transfer entropy (summing over all pairs of spins connected by a non-vanishing interaction) and found very similar results to those obtained by Granger causality. We remark that direct evaluation of the multivariate transfer entropy is feasible only for very small systems; a promising approach, which might render larger systems tractable, is described in [20] where transfer entropy is expressed as a likelihood ratio.



FIG. 1: For the Ising model implemented on the brain network, the following quantities are depicted versus the temperature β : R, the ratio between the standard deviations of outgoing and incoming information transfers; the total transferred information C, i.e. the sum of all information transfers in the network; the susceptibility χ . All quantities have been normalized in the interval [0,1].

In figure (1) we depict three quantities as a function of the inverse temperature β : (1) the ratio between the



FIG. 2: The sum of bivariate transfer entropies for all pairs of spins, connected by a non-vanishing interaction, is depicted versus the coupling β for the 2D Ising model on a square lattice of size L^2 , with L = 32, 64, and 96, with periodic boundary conditions. Transfer entropies have been evaluated averaging over 20 runs of 10000 iterations. The vertical line corresponds to the critical point. Since the maximum of the heat capacity matches quite well the critical point, this suggests that the system of linear size 96 is a reasonably good approximation to the thermodynamic limit, and that the transfer entropy has its maximum in the paramagnetic phase.

standard deviation of the distributions of the outgoing information and the incoming information [11],

$$R = \frac{\sigma(c_{out})}{\sigma(c_{in})},$$

where c_{out} (c_{in}) is obtained by summing over columns (rows) the matrix $c = \{c_{ij}\}$ of the information flows $i \rightarrow j$ as estimated by Granger causality. As explained in [11], R is an indicator of the law of diminishing marginal returns, and it is a quantity calculated in this case at a global level, pooling all the nodes together (complementary to the local measure r; (2) the sum C of all the information transfers between spins, quantifying the circulation of information in the network, obtained summing matrix c over rows and columns; (3) the susceptibility χ , whose peak corresponds to criticality (pseudotransition). We find that the around this critical state of the Ising model the total amount of information transfer and R assume large values; while the total transferred information is maximum at the critical point, R is maximized for a lower temperature. At criticality some units are close to be receiving the maximal amount of input information, but the explanation of why these two related quantities are maximal for different temperatures will need further investigation.

It is worth mentioning that the transfer entropy may be



ຼິ⁰¹³¹ 0 10 20 30 40 50 0 60 1 In Str. 0.5 0 40 50 60 Ó 10 20 30 1 苗 0.5 0 20 30 40 50 60 0 10 1 Betw 0.5 0' 0 10 20 30 40 50 60 Node

FIG. 3: The sum of bivariate transfer entropies for all pairs of spins, connected by a non-vanishing interaction, is depicted versus the coupling β for the 2D Ising model on a square lattice of size L^2 , with L = 16, with periodic boundary conditions. Transfer entropies have been evaluated averaging over 20 runs of 10000 iterations. The vertical line corresponds to the critical point. Stars refer to Metropolis updating scheme, whilst empty squares refer to Glauber dynamics.

seen as a dynamical counterpart of the mutual information, the static measure of statistical dependencies among components of the whole system. It is well known that for a large class of dynamical systems that the mutual information peaks at the order-disorder phase transition [21, 22]. We find that for the 2D Ising model the transfer entropy has a peak in the paramagnetic phase, see figure (2). Moreover we stress that the amount of information flow depends on the updating scheme, but the maximum is attained in correspondence of the same coupling, see e.g. figure (3) where Metropolis and Glauber dynamics are compared for the 2D Ising model.

The modulation of the law of diminishing marginal returns can be analyzed evaluating, at each node, the ratio between the outgoing and the incoming information. Figure (4) refers to the value of β leading to the maximum of R, and describes, for each node, the ratio

$$r = \frac{\langle c_{out} \rangle}{\langle c_{in} \rangle}$$

compared with topological properties of the graph, such as the strength, the node-efficiency and the nodebetweeness; nodes have been ordered according to growing values of the in-strength, i.e. the number of incoming links. In figure (5) we plot r versus the in-strength, for the Ising model. We observe that r is to some extent correlated by the in-strength and it thus reflects an intrinsic property of nodes, the propensity to become bot-

FIG. 4: The pattern of r for the Ising model is shown and compared with the in-strength, i.e. the indegree in the weighted connectivity matrix A_{ij} , the efficiency and the betweeness of nodes [2]. The values of r have been normalized to the interval [0,1]. Nodes are ordered according to increasing in-strength. Note that r is not fully explained by the in-strength, there are node with intermediate in-strength but with high r: the ratio r thus measures a property of nodes which is connected but not equivalent to the in-strength. Similar patterns are obtained at critical β .

tlenecks of information. Fig. (4) shows that other network properties related with "hubness" such as efficiency (connected with the shortest path length between neighbors of a given node, when that node is not present [2]) and betweeness (accounting for the number of shortest paths passing through a given node) are not correlated with the the r value in each node.

The regions which are recognized as potential bottlenecks by the present analysis are symmetrical in the two hemispheres, and are Superior Frontal Cortex, Precuneus, Superior Temporal Cortex, Medial and Lateral Orbitofrontal Cortex, see fig.(6). Some of these regions are considered as hubs both for the structural and for the functional connectome. It is worth to recall anyway that being a hub (in particular for incoming connections) does not necessary imply that a node is a bottleneck of information flow.

Recent works [13, 15, 23–25] have simulated the spontaneous brain activity implementing models of dynamical oscillators with different levels of complexity and biological foundation on the connectome structure, retrieving in some cases correlation-based networks similar to those observed from the analysis of neuroimaging data (mainly fMRI at rest). The present work extends the analysis to dynamical networks who take into account lagged and directional influences. We have shown that the critical state of the Ising model on a brain network, unlike



FIG. 5: The ratio between the outgoing and the incoming information at each node is depicted versus the in-strength of nodes. Pearson linear correlation is 0.69. Varying β , the pattern remains the same although the numerical values of r slightly change.



FIG. 6: The value of r for each of the 66 regions for the Ising model. The size of the spheres is proportional to r, thus showing the most prone regions to became bottlenecks of information.

the Ising model on a regular 2D grid, is characterized by the maximal amount of information transfer among units, and that brain effective connectivity networks may also be considered in the light of the law of diminishing marginal returns: some units more prominently express this disparity between incoming and outgoing information and are thus liable to become bottlenecks of information.

We have also implemented the Ising model on a symmetric network built by preferential attachment [2], and with the same weight on links. As β is varied, we find that the peak of the susceptibility does not correspond to the peak of the information flow. This confirms what we have already found in relation with the 2D Ising model, i.e. the characterization of the critical state as the maximizer of the total information transfer is not a generic property; on the other hand it suggests that the distribution of weights of the links, rather than the heterogeneity, is crucial for the connectome in order to show such characterization.

Apart from the insights on how structure and dynamics interact to generate brain function, the approach here described could have more general implications revealing nodes of a network which are particularly representative [26] or influential for the others [27].

- [1] Sporns, O. Networks of the Brain. MIT Press.
- [2] A.L. Barabasi, Linked: the new science of networks. (Perseus Publishing, Cambridge Mass., 2002); S. Boccaletti, V. Latora, Y. Moreno, M. Chavez and D.-U. Hwang, Phys. Rep. 424, 175 (2006).
- [3] Y. Roudi, J. Tyrcha, J. Hertz, Phys. Rev. E 79 (5), 051915 (2009).
- [4] S.L. Bressler, A.K. Seth, Neuroimage 58 323 (2011)
- [5] D. Marinazzo, W.Liao, H.Chen, S.Stramaglia. NeuroImage, 58, 330 (2011).
- [6] K.J. Friston, Brain connectivity $\mathbf{1}$, 13 (2011)
- [7] T. Schreiber, Phys. Rev. Lett. 85, 461 (2000)
- [8] M. Staniek, K. Lehnertz, Phys. Rev. Lett. 100, 158101 (2008)
- [9] L. Barnett, A.B. Barrett, and A.K. Seth, Phys Rev. Lett. 103, 238701 (2009).
- [10] C.W.J. Granger, Econometrica **37**, 424 (1969); K. Hlavackova-Schindler, M. Palus, M. Vejmelka, J. Bhattacharya, Physics Reports **441**, 1 (2007).
- [11] D. Marinazzo, G. Wu, M. Pellicoro, L. Angelini, S. Stramaglia, PLoS ONE 7(9), e45026 (2012).
- [12] P. Samuelson, W. Nordhaus, *Microeconomics*, Mc Graw Hill, Edition 17 (2001)
- [13] D. Fraiman, P. Balenzuela , J. Foss, D. Chialvo, Phys. Rev. E 79, 061922 (2009).
- [14] DR Chialvo, Physica A, Volume 340, Issue 4, p. 756-765 (2004).
- [15] A. Haimovici, E. Tagliazucchi, P. Balenzuela, D. R. Chialvo, Phys. Rev. Lett. (101), 178101 (2013).
- [16] P. Hagmann, L. Cammoun, X. Gigandet, R. Meuli, C. Honey, V. Weeden, O. Sporns O., PLoS Biology 6(7) e159 (2008).
- [17] R.J. Glauber, J. Math. Phys. 4, 294 (1963).
- [18] JN Dorogovtsev, AV Goltsev, JFF Mendes, Phys. Rev. E 66 016104 (2002).
- [19] M. Pellicoro, S. Stramaglia, Physica A: Statistical Mechanics and its Applications 389 (21), 4747 (2010).
- [20] L. Barnett, T. Bossomaier, Phys. Rev. Lett. 109 (13) 2012.
- [21] S.J. Gu, C.P. Sun, H.Q. Lin, J. Phys. A 41, 25002 (2008).
- [22] H.W. Lau, P. Grassberger, Phys. Rev. E 87, 022128 (2013).
- [23] J. Cabral, E. Hugues, O. Sporns, G. Deco, NeuroImage 57 (2011) 130139
- [24] G. Deco, V.K. Jirsa, The Journal of Neuroscience, March 7, 2012, 32(10):3366 3375
- [25] G. Deco V.K. Jirsa, AR Mc Intosh, Nature Reviews Neuroscience vol. 12, (2011) 43
- [26] Y.Y. Liu, J.J. Slotine, A.L. Barabasi, Proc. Natl Acad. Sci. USA 110, 2460-2465 (2013)

[27] Y.Y. Liu, J.J. Slotine, A.L. Barabasi, Nature 473, 167-173 (2013)