A temporal logic of security

Masoud Koleini Michael R. Clarkson Department of Computer Science George Washington University

Kristopher K. Micinski Department of Computer Science University of Maryland, College Park

July 9, 2013

Abstract

A new logic for verification of security policies is proposed. The logic, HyperLTL, extends linear-time temporal logic (LTL) with connectives for explicit and simultaneous quantification over multiple execution paths, thereby enabling HyperLTL to express information-flow security policies that LTL cannot. A model-checking algorithm for a fragment of HyperLTL is given, and the algorithm is implemented in a prototype model checker. The class of security policies expressible in HyperLTL is characterized by an arithmetic hierarchy of hyperproperties.

1 Introduction

The theory of trace properties, which characterizes correct behavior of programs in terms of properties of individual execution paths, developed out of an interest in proving the correctness of programs [27]. Practical model-checking tools [10, 22, 23, 28] now enable automated verification of correctness. Verification of security, unfortunately, isn't directly possible with such tools, because some important security policies require sets of execution paths to model [34]. But there is reason to believe that similar verification methodologies could be developed for security:

• The *self-composition* construction [7, 41] reduces properties of pairs of execution paths to properties of single execution paths, thereby enabling verification of a class of security policies.

• The theory of hyperproperties [12] generalizes the theory of trace properties to security policies, showing that certain classes of security policies are amenable to verification with invariance arguments [2] and with stepwise refinement [47].

Prompted by these ideas, this paper develops an automated verification methodology for security. In our methodology, security policies are expressed as logical formulas, and a model checker verifies those formulas.

We propose a new logic named HyperLTL, which generalizes linear-time temporal logic (LTL) [38]. LTL implicitly quantifies over only a single execution path of a system, but HyperLTL allows explicit quantification over multiple execution paths simultaneously, as well as propositions that stipulate relationships among those paths. For example, HyperLTL can express information-flow policies such as "for all execution paths π_1 , there exists an execution path π_2 , such that π_1 and π_2 always appear equivalent to observers who are not cleared to view secret information." Neither LTL nor branching-time logics (e.g., CTL [15] and CTL* [16]) can directly express such policies, because they lack the capability to correlate multiple execution paths [3, 34]. Providing that capability is the key idea of HyperLTL. The syntax that enables it is described in §2, along with several examples of information-flow policies. The semantics of HyperLTL is given in §3. It is based on a standard LTL semantics [38] that models a formula with a single computation, which is a propositional abstraction of an execution path. Our HyperLTL semantics models a formula with a sequence of computations, making it possible to correlate multiple execution paths.

We also define a new model-checking algorithm for HyperLTL. Our algorithm uses a well-known LTL model-checking algorithm [46,48] based on Büchi automata: As input, that algorithm takes a formula ϕ to be verified and a system S modeled as a Büchi automaton A_S . The algorithm mechanically translates the formula to another Büchi automaton A_{ϕ} , then applies automata-theoretic constructions to A_S and A_{ϕ} . The output is either "yes," the system satisfies the formula, or "no," along with a counterexample path demonstrating that ϕ does not hold of S. In §4, we upgrade that algorithm with a self-composition construction, so that it can verify formulas over multiple paths. We obtain a model-checking algorithm that handles an important fragment of HyperLTL, including all of the examples in §2.1. We implemented that algorithm in a prototype model-checker, which §4 describes.

Hyperproperties can characterize the security policies expressible in HyperLTL. The quantifiers appearing in a HyperLTL formula give rise to a

hierarchy of hyperproperties, which we define in $\S 5$. The hierarchy contains 2-safety [41] and k-safety [12] hyperproperties as special cases. And it yields an *arithmetic hierarchy* of hyperproperties that elegantly characterizes which hyperproperties can be verified by our model-checking algorithm.

This paper thus contributes to the theory of computer security by

- defining a new logic for expressing security polices,
- showing that logic is expressive enough to formulate important information-flow policies,
- giving an algorithm for model-checking a fragment of the logic,
- prototyping that algorithm and using it to verify security policies, and
- characterizing the mathematical structure of security policies in terms of an arithmetic hierarchy of hyperproperties.

Though our results build upon the formal methods literature, our interest and application is entirely within the science of constructing systems that are provably secure.

We proceed as follows. §2 defines the syntax of HyperLTL and provides several example formulations of information-flow policies. §3 defines the semantics of HyperLTL. §4 defines our model-checking algorithm. §5 discusses hyperproperties and HyperLTL. §6 reviews related work.

2 Syntax

HyperLTL extends propositional linear-time temporal logic (LTL) [38] with explicit quantification over *paths*, which are infinite sequences of execution states. Formulas of HyperLTL are formed according to the following syntax:

$$\begin{array}{ll} \phi & ::= & \mathbf{A} \, \phi \mid \mathbf{E} \, \phi \mid \psi \\ \psi & ::= & p \mid \neg \psi \mid \psi \lor \psi \mid \langle \psi, \dots, \psi \rangle \mid \mathbf{X} \, \psi \mid \psi \, \mathbf{U} \, \psi \end{array}$$

A HyperLTL formula ϕ starts with a sequence of path quantifiers. A and E are universal and existential path quantifiers, respectively, read as "along all paths" and "along some path." For example, AAE ψ means that for all paths π_1 and π_2 , there exists another path π_3 , such that ψ holds on those three paths. (Since branching-time logics also have explicit path quantifiers, it is natural to wonder why we don't use one of them. We postpone addressing that question until §2.2.) An atomic proposition p

expresses some fact about states. The focus connective, written $\langle \psi_1, \dots, \psi_n \rangle$, is used to restrict attention to individual paths: ψ_1 must hold of the first path quantified over, ψ_2 of the second, and so forth. Boolean connectives \neg and \lor have the usual classical meanings. Implication, conjunction, and bi-implication are defined as syntactic sugar: $\psi_1 \to \psi_2 = \neg \psi_1 \lor \psi_2$, and $\psi_1 \wedge \psi_2 = \neg (\neg \psi_1 \lor \neg \psi_2)$, and $\psi_1 \leftrightarrow \psi_2 = \psi_1 \to \psi_2 \wedge \psi_2 \to \psi_1$. True and false, written \top and \bot , are defined as $p \lor \neg p$ and $\neg \top$, respectively.

Temporal connective X is read as "next." Formula X ψ means that ψ holds on the next state of every quantified path. Likewise, U is read "<u>u</u>ntil," and ψ_1 U ψ_2 means that ψ_2 will eventually hold of all quantified paths, and until then ψ_1 holds. The other standard temporal connectives F, G and R, read as "<u>f</u>uture," "<u>g</u>lobally," and "<u>r</u>elease," are defined as syntactic sugar: F $\psi = \top U \psi$, meaning in the future, ψ must eventually hold; G $\psi = \neg F \neg \psi$, meaning ψ must hold, globally; and ψ_1 R $\psi_2 = \neg(\neg \psi_1 U \neg \psi_2)$, meaning ψ_2 must hold until released by ψ_1 .

A HyperLTL formula ϕ is well-formed iff (i) ϕ contains at least one path quantifier, and (ii) the length n of all focus subformulas $\langle \psi_1, \dots, \psi_n \rangle$ equals the number of path quantifiers at the beginning of ϕ .

2.1 Security policies in HyperLTL

We now put HyperLTL into action by formulating several security policies.

Access control. An access control policy permits an operation op on an object o to proceed only if the subject s requesting op has the right to perform op on o. Let $\mathsf{permit}_{op,o}$ be a proposition denoting that op is $\mathsf{permitted}$ on o, and $\mathsf{req}_{s,op,o}$ that s has requested to $\mathsf{perform}$ op on o, and $\mathsf{hasRight}_{s,op,o}$ that s has the right to $\mathsf{perform}$ op on o. Access control can be expressed in HyperLTL as follows:

$$\operatorname{AG}(\mathsf{req}_{s,op,o} \to (\mathsf{hasRight}_{s,op,o} \leftrightarrow \mathsf{permit}_{op,o})). \tag{1}$$

Guaranteed service. If a system always eventually responds to a request for service, then it provides *guaranteed service*:

$$AG(req \rightarrow F resp).$$
 (2)

Both access control (1) and guaranteed service (2) are examples of trace properties expressible in LTL. Any LTL property can be expressed in HyperLTL simply by prepending a universal path quantifier to its LTL formula.

Nonin(ter)ference. A system satisfies noninterference [20] when the outputs observed by low-security users are the same as they would be in the absence of inputs submitted by high-security users. Noninterference thus requires a system to be closed under purging of high-security inputs. The original formulation [20] of noninterference uses an event-based system model, in which an execution path is a sequence of individual events (e.g., commands), and purging removes high-security events from the sequence. An alternative formulation [33] called noninference uses a state-based system model, in which an execution path is a sequences of states (e.g., values of variables), and purging assigns an "empty" value, denoted λ , to the high-security component of the state. Noninterference and noninference are both intended to be used with deterministic systems.

Here, we pursue the state-based model, because it blends well with temporal logic, which is also based on states. We note that for any event-based system, there is a state-based system equivalent to it [35], though an infinite number of states might be required.

Inputs, outputs, and users are classified into *security levels* in the following examples. For simplicity, we consider only two levels, *high* and *low*. We assume that each state contains input and output variables of each security level.

Let high hold in a state when its high inputs and outputs are not λ , and let low-equiv hold on a pair of states whenever those states have the same low inputs and outputs. Using those propositions, noninference can be expressed as follows:

$$AEG(\langle \top, \neg high \rangle \land low-equiv).$$
 (3)

The formula starts with AE, which means "for all paths, there exists another path." Low equivalence of those paths is formulated as G low-equiv, which means that at each time step, the current states in the two paths are low equivalent. Subformula $\langle \top, \neg \mathsf{high} \rangle$ requires all states of the second path to have empty high inputs and outputs. The second path is therefore the first path, but with its high inputs and outputs purged.

Nondeterminism and noninterference. Goguen and Meseguer's definition of noninterference [20] requires systems to be deterministic. Nondeterminism is useful for specification of systems, however, so many variants of noninterference have been developed for nondeterministic systems.

A (nondeterministic) system satisfies observational determinism [49] if every pair of executions with the same initial low observation remain indistinguishable by low users. That is, the system appears to be deterministic

to low users. Systems that satisfy observational determinism are immune to *refinement attacks* [49], because observational determinism is preserved under refinement. Observational determinism can be expressed as follows:

$$AA low-equiv \rightarrow G low-equiv.$$
 (4)

There are many definitions of noninterference that do permit low-observable nondeterminism. Generalized noninterference (GNI) [31], for example, stipulates that the low-security outputs may not be altered by the injection of high-security inputs. Like noninterference, GNI was original formulated for event-based systems, but it can also be formulated for state-based systems [33]. GNI can be expressed as follows:

$$AAE\ G(\mathsf{high-in-equiv}_{1,3} \land \mathsf{low-equiv}_{2,3}). \tag{5}$$

Proposition high-in-equiv_{1,3} holds when the current states of the first and third paths have the same high inputs, and low-equiv_{2,3} holds when the current states in the second and third paths are low equivalent. The third path is therefore an *interleaving* of the high inputs of the first path and the low inputs and outputs of the second path. Other security policies based on interleavings, such as *restrictiveness* [32] and *separability* [33], can similarly be expressed in HyperLTL.

2.2 Comparison with other temporal logics

Why did we invent a new temporal logic instead of using an existing, well-studied logic? In short, because we don't know of an existing temporal logic that can directly express all the policies in §2.1:

- Linear time. LTL formulas express properties of individual execution paths. But all of the noninterference properties of §2.1 are properties of sets of execution paths [12,33], hence cannot be formulated in LTL. Explicit path quantification does enable their formulation in Hyper-LTL.
- Branching time. CTL [15] and CTL* [16] have explicit path quantifiers. But their quantifiers don't enable expression of relationships between paths, because only one path is "in scope" at a given place in a formula. (See appendix A for an example.) So they can't directly express policies such as observational determinism (4) and GNI (5). HyperLTL does allow many paths to be in scope, as well as propositions over all those paths.

By using the self-composition construction, it is possible to express relational noninterference in CTL [7] and observational determinism in CTL* [24]. Those approaches resemble HyperLTL, but HyperLTL formulas express policies directly over the original system, rather than over a self-composed system.

Furthermore, the self-composition approach does not seem capable of expressing policies, such as noninference (3) and generalized noninterference (5), that have both universal and existential path quantifiers over infinite paths. (A recent upgrade of self-composition, asymmetric product programs [6], does enable verification of refinement properties involving both kinds of quantifiers. It might be possible to express policies like noninference with that upgrade.) Nonetheless, it is straightforward to express such policies in HyperLTL.

• Modal μ -calculus. Modal μ -calculus [26] generalizes CTL*. But as expressive as modal μ -calculus is, it remains insufficient [3] to express all opacity policies [8], which prohibit observers from discerning the truth of a predicate. (Alur et al. [3] actually write "secrecy" rather than "opacity.") Simplifying definitions slightly, a trace property P is opaque iff for all paths π of a system, there exists another path π' of that system, such that π and π' are low-equivalent, and exactly one of π and π' satisfies P. HyperLTL is able to express all opacity policies over linear-time properties: given LTL formula ϕ_P that expresses a linear-time trace property P, HyperLTL formula

$$AE((G | \text{low-equiv}) \land (\langle \phi_P, \neg \phi_P \rangle \lor \langle \neg \phi_P, \phi_P \rangle))$$

stipulates that P is opaque. Noninference (3), for example, is a linear-time opacity policy [40].

3 Semantics

HyperLTL formulas are interpreted with respect to computations. A computation abstracts away from the states in a path, representing each state by the propositions that hold of that state. Let Atoms denote the set of atomic propositions. Formally, a computation γ is an infinite sequence over $\mathcal{P}(\mathsf{Atoms})$, where \mathcal{P} denotes the powerset operator. Define $\gamma[i]$ to be element i of computation γ . Hence, $\gamma[i]$ is a set of propositions. And define $\gamma[i...]$ to be the suffix of γ starting with element i—that is, the sequence $\gamma[i]\gamma[i+1]\ldots$ We index sequences starting at 1, so $\gamma[1...] = \gamma$.

A computation represents a single path, but HyperLTL formulas may quantify over multiple paths. To represent that, let Γ denote a finite tuple $(\gamma_1, \ldots, \gamma_k)$ of computations. Define $|\Gamma|$ to be the length k of Γ , and define projection $prj_i(\Gamma)$ to be element γ_i . Given a tuple Γ define $\Gamma \cdot \gamma$ to be the concatenation of element γ to the end of tuple Γ , yielding tuple $(\gamma_1, \ldots, \gamma_k, \gamma)$. Extend that notation to concatenation of tuples by defining $\Gamma \cdot \Gamma'$ to be the tuple containing all the elements of Γ followed by all the elements of Γ' . Extend notations $\gamma[i]$ and $\gamma[i...]$ to apply to computation tuples by defining $\Gamma[i] = (\gamma_1[i], \ldots, \gamma_k[i])$ —that is, the tuple containing element i from each computation in Γ —and $\Gamma[i...] = (\gamma_1[i...], \ldots, \gamma_k[i...])$.

HyperLTL formulas may involve propositions over multiple states. For example, low-equiv in the definition of noninference (3) holds when two states have the same low inputs and outputs. We therefore need a means to determine what *compound* propositions hold of a tuple of states, given what atomic propositions hold of the individual states. To do that, we introduce bonding functions that describe how to produce compound propositions out of tuples of atomic propositions. Let Compounds denote the set of compound propositions, and assume that Atoms \subseteq Compounds. Let B be a family $\{B_i \mid i \in \mathbb{N}\}\$ of functions, such that each B_i is a function from $\mathcal{P}(\mathsf{Atoms})^i$ to $\mathcal{P}(\mathsf{Compounds})$. Notation X^n is the n-ary cartesian power of set X. We require B_1 to be the identity function, so that length-1 tuples are not changed by bonding. As an example, consider a bonding function B_2 that describes when two states are low-equivalent. Given a set $\{low_i \mid 1 \leq i \leq n\}$ of atoms, describing n different low states, we could define B_2 such that $B_2(\{\mathsf{low}_i\}, \{\mathsf{low}_i\}) = \{\mathsf{low-equiv}\}, \text{ and } B_2(\{\mathsf{low}_i\}, \{\mathsf{low}_i\}) = \emptyset \text{ if } i \neq j. \text{ Given}$ a tuple, it is always clear from the length of the tuple which function B_i should be applied to it, so henceforth we omit the subscript.

The validity judgment for HyperLTL formulas is written $\Gamma \models \phi$. Formula ϕ must be well-formed. The judgment implicitly uses a $model\ M$, which is a set of computations, and a family B of bonding functions. We omit notating M and B as part of the judgment, because they do not vary during the interpretation of a formula. Validity is defined as follows:

- 1. $\Gamma \models A \psi$ iff for all $\gamma \in M : \Gamma \cdot \gamma \models \psi$
- 2. $\Gamma \models E \psi$ iff there exists $\gamma \in M : \Gamma \cdot \gamma \models \psi$
- 3. $\Gamma \models p \text{ iff } p \in B(\Gamma[1])$
- 4. $\Gamma \models \neg \psi \text{ iff } \Gamma \not\models \psi$
- 5. $\Gamma \models \psi_1 \lor \psi_2$ iff $\Gamma \models \psi_1$ or $\Gamma \models \psi_2$

- 6. $\Gamma \models \langle \psi_1, \dots, \psi_n \rangle$ iff for all $i : \text{if } 1 \leq i \leq n \text{ then } prj_i(\Gamma) \models \psi_i$
- 7. $\Gamma \models X \psi \text{ iff } \Gamma[2..] \models \psi$
- 8. $\Gamma \models \psi_1 \cup \psi_2$ iff there exists $k : k \geq 1$ and $\Gamma[k..] \models \psi_2$ and for all j : if $1 \leq j < k$ then $\Gamma[j..] \models \psi_1$

Clauses 1 and 2 quantify over a computation γ from M, and they concatenate γ to Γ to evaluate subformula ψ . Clause 3 means satisfaction of atomic propositions is determined by the first element of each computation in Γ . Clauses 4 and 5 are standard. In clause 6, elements of a focus formula are independently evaluated over their corresponding individual computations. Clauses 7 and 8 are the standard LTL definitions of X and U, upgraded to work over a sequence of computations.

4 Model Checking

Model-checking is possible at least for fragments of HyperLTL. For example, HyperLTL contains LTL as a fragment, and LTL enjoys a decidable model-checking algorithm. Here's a much larger fragment of HyperLTL that can be model checked:

- The series of quantifiers at the beginning of a formula may involve only a single alternation of quantifiers. For example, $E \psi$ and $AAE \psi$ are allowed, but $AEA \psi$ is not.
- In focus formulas $\langle \psi_1, \dots, \psi_n \rangle$, the subformulas ψ_i may not use temporal connectives X and U. Hence all the ψ_i must be propositional formulas.

We name this fragment $HyperLTL_2$, because every formula in it may begin with at most two kinds of quantifiers—a sequence of A's followed by a sequence of E's, or vice-versa. HyperLTL₂ is an important fragment, because it is expressive enough for all the security policies formulated in §2.1.

We now give a model-checking algorithm for HyperLTL₂. Our algorithm adapts previously known algorithms for LTL model-checking [18, 19, 44, 45]. Those LTL algorithms determine whether a set M of computations satisfies an LTL formula ϕ , as follows:

- 1. Represent M as a Büchi automaton [9], A_M . Its language is M.
- 2. Construct Büchi automaton $A_{\neg\phi}$, whose language is the set of all computations that don't satisfy ϕ .

- 3. Intersect A_M and $A_{\neg \phi}$, yielding automaton $A_M \cap A_{\neg \phi}$. Its language contains all computations of M that don't satisfy ϕ .
- 4. Check whether the language of $A_M \cap A_{\neg \phi}$ is empty. If so, all computations of M satisfy ϕ , hence M satisfies ϕ . If not, then any element of the language is a counterexample showing that M doesn't satisfy ϕ .

Our algorithm for model-checking HyperLTL₂ adapts that LTL algorithm. Without loss of generality, assume that the HyperLTL₂ formula to be verified has the form $A^k \to j \psi$, where A^k and E^j denote sequences of universal and existential path quantifiers of lengths k and j. (Formulas of the form $E^k \to j \psi$ can be verified by rewriting them as $A^k \to j \psi$.) Let n equal k+j. Semantically, a model of ψ must be an n-tuple of computations. Let zip denote the usual function that maps an n-tuple of sequences to a single sequence of n-tuples—for example, zip([1,2,3],[4,5,6]) = [(1,4),(2,5),(3,6)]—and let unzip denote its inverse. To determine whether a system M satisfies HyperLTL₂ formula $A^k \to j \psi$, our algorithm follows the same basic steps as the LTL algorithm:

- 1. Represent M as a Büchi automaton, A_M . Construct the n-fold product of A_M with itself—that is, $A_M \times A_M \times \cdots \times A_M$, where " A_M " occurs n times. This construction is straightforward and formalized in appendix B. Denote the resulting automaton as A_M^n . If $\gamma_1, \ldots \gamma_n$ are all computations of M, then $zip(\gamma_1, \ldots \gamma_n)$ is a word in the language of A_M^n .
- 2. Construct Büchi automaton A_{ψ} . Its language is the set of all words w such that $unzip(w) = \Gamma$ and $\Gamma \models \psi$ —that is, the tuples Γ of computations that satisfy ψ . This construction, formalized in appendix B, is a generalization of the corresponding LTL construction.
- 3. Intersect A_M^n and A_{ψ} , yielding automaton $A_M^n \cap A_{\psi}$. Its language is essentially the tuples of computations of M that satisfy ψ . This construction is standard [11].
- 4. Check whether $\mathcal{L}(((A_M^n \cap A_{\psi})|_k)^C \cap A_M^k)$ is empty, where (i) A^C denotes the *complement* of an automaton A, (complement constructions are well-known—e.g., [44]—so we do not formalize one here), and (ii) $A|_k$ denotes the same automaton as A, but with every transition label (which is an n-tuple of propositions) projected to only its first k elements. That is, if $\mathcal{L}(A)$ contains words of the form $zip(\gamma_1, \ldots \gamma_n)$, then $\mathcal{L}(A|_k)$ contains words of the form $zip(\gamma_1, \ldots \gamma_k)$. Projection erases the

final j computations from each letter of a word, leaving only the initial k computations. Thus a word is in the projected language iff there exists some extension of the word in the original language.

If $\mathcal{L}(((A_M^n \cap A_{\psi})|_k)^C \cap A_M^k)$ is empty, then M satisfies $A^k \to \emptyset^j$. If not, then any element of the language is a counterexample showing that M doesn't satisfy $A^k \to \emptyset^j$.

The final step of the above algorithm is a significant departure from the LTL algorithm. Intuitively, it works because projection introduces an existential quantifier, thus enabling verification of formulas with a quantifier alternation. The following theorem states the correctness of our algorithm:

Theorem 4.1. Let ϕ be HyperLTL₂ formula $A^k E^j \psi$, and let n = k + j. Let M be a set of computations. Then ϕ holds of M iff $\mathcal{L}(((A_M^n \cap A_{\psi})|_k)^C \cap A_M^k)$ is empty.

Proof. (\Rightarrow , by contrapositive) We seek a countermodel showing that $A^k \to b^j \psi$ doesn't hold of M. For that countermodel to exist,

there must exist a
$$k$$
-tuple Γ_k :
for all j -tuples Γ_j : if $set(\Gamma_k \cdot \Gamma_j) \subseteq M$ then $\Gamma_k \cdot \Gamma_j \models \neg \psi$, (6)

where $set(\Gamma)$ denotes the set containing the same elements as tuple Γ . To find that countermodel Γ_k , consider $\mathcal{L}(A_M^n \cap A_{\psi})$. If that language is empty, then

for all
$$k$$
-tuples Γ_k and
for all j -tuples Γ_j : if $set(\Gamma_k \cdot \Gamma_j) \subseteq M$ then $\Gamma_k \cdot \Gamma_j \models \neg \psi$. (7)

That's almost what we want, except that Γ_k is universally quantified in (7) rather than existentially quantified as in (6). So we introduce projection and complementation to relax the universal quantification to existential. First, note that language $\mathcal{L}((A_M^n \cap A_\psi)|_k)$ contains all $zip(\Gamma_k)$ for which there exists a Γ_j such that $set(\Gamma_k \cdot \Gamma_j) \subseteq M$ and $\Gamma_k \cdot \Gamma_j \models \psi$. So if there exists a Γ_k^* such that $zip(\Gamma_k^*) \notin \mathcal{L}((A_M^n \cap A_\psi)|_k)$, then for all Γ_j , if $set(\Gamma_k \cdot \Gamma_j) \subseteq M$ then $\Gamma_k \cdot \Gamma_j \models \neg \psi$. That Γ_k^* would be exactly the countermodel we seek according to (6). To find such a Γ_k^* , it suffices to determine whether $\mathcal{L}((A_M^n \cap A_\psi)|_k) \subset \mathcal{L}(A_M^k)$, because any element that strictly separates those sets would satisfy the requirements to be a Γ_k^* . By simple set theory, $X \subset Y$ iff $X^C \cap Y$ is not empty. Therefore, if $\mathcal{L}(((A_M^n \cap A_\psi)|_k)^C \cap A_M^k)$ is not empty, then a countermodel Γ_k^* exists.

(\Leftarrow) The same argument suffices: if $\mathcal{L}(((A_M^n \cap A_{\psi})|_k)^C \cap A_M^k)$ is empty, then no countermodel can exist.

We are currently investigating the complexity of this model-checking algorithm.

Formulas without quantifier alternation. Define HyperLTL₁ to be the fragment of HyperLTL₂ that contains formulas with no alternation of quantifiers. HyperLTL₁ can be verified more efficiently than HyperLTL₂. Suppose ϕ is HyperLTL₁ formula $A^n \psi$. Then it suffices to check whether $A_M^n \cap A_{\neg \psi}$ is non-empty. This is essentially the self-composition construction, as used in previous work [7,12,41].

Prototype. We implemented a prototype for the model-checking algorithm in OCaml. The prototype accepts an input file for the state transition system description, and a HyperLTL $_2$ formula. For the prototype, the description language of the state transition system requires explicit definition of the states, single-state and multistate labels. For automata complementation, the prototype uses GOAL [42], an interactive tool for manipulating Büchi automata. In the case that a HyperLTL $_2$ property doesn't hold, a witness will be produced.

5 Hyperproperties

The mathematical structure of the class of security policies expressible in HyperLTL can be precisely characterized by hyperproperties. We begin by summarizing the theory of hyperproperties.

Definition 5.1 (Hyperproperties [12]). A trace is a finite or infinite sequence of states. (The terms "infinite trace" and "path" are therefore synonymous.) Define Ψ_{fin} to be the set of finite traces and Ψ_{inf} to be the set of infinite traces. A trace property is a set of infinite traces. A set T of traces satisfies a trace property P iff $T \subseteq P$. A hyperproperty is a set of sets of infinite traces, or equivalently a set of trace properties. The interpretation of a hyperproperty as a security policy is that the hyperproperty is the set of systems allowed by that policy. Each trace property in a hyperproperty is an allowed system, specifying exactly which executions must be possible for that system. Thus a set T of traces satisfies hyperproperty H iff T is in H. Given a trace property P, the powerset of P is the unique hyperproperty that expresses the same policy as P. Denote that hyperproperty as [P].

5.1 k-hyperproperties

A system satisfies a trace property if every trace of the system satisfies the property. To determine whether a trace satisfies the property, the trace can be considered in isolation, without regard for any other traces that might or might not belong to the system. Similarly, a system satisfies observational determinism if every pair of its traces—where every pair can be considered in isolation—satisfies HyperLTL formula (4). These examples suggest a new class of hyperproperties based on the idea of satisfaction determined by bounded sets of traces.

Let a k-hyperproperty be a hyperproperty that is definable by a k-ary relation on traces as follows. Intuitively, one needs to consider at most k traces at a time to decide whether a system satisfies a k-hyperproperty. Formally, a hyperproperty \mathbf{H} is a k-hyperproperty iff

$$(\exists R \subseteq \Psi_{\mathsf{inf}}^k : (\forall S \in \mathbf{H} : (\forall \vec{t} \in \Psi_{\mathsf{inf}}^k : set(\vec{t}) \subseteq S \implies \vec{t} \in R))),$$

where Ψ_{\inf}^k denotes the k-fold Cartesian product of Ψ_{\inf} (i.e., the set of all k-tuples of infinite traces), \vec{t} denotes a k-tuple (t_1, \ldots, t_k) of traces, and $set(\vec{t})$ denotes $\{t_i \mid 1 \leq i \leq k\}$. For a system S to be a member of \mathbf{H} , all k-tuples of traces from S must satisfy R, in which case relation R defines \mathbf{H} .

Trace properties are 1-hyperproperties: to decide whether a system S satisfies a 1-hyperproperty, it suffices to consider each trace of S in isolation. For a trace property P, the relation that defines hyperproperty [P] is P itself, because

$$(\forall\,S\in[P]\,:\,(\forall\,\vec{t}\in\Psi^1_{\mathsf{inf}}\,:\,set(\vec{t}\,)\subseteq S\implies\vec{t}\in P)).$$

The k-hyperproperties form a hierarchy in which each level requires consideration of one more trace than the previous level. Formally, any k-hyperproperty defined by R is also a (k+1)-hyperproperty defined by relation $\{\vec{t} \cdot u \mid \vec{t} \in R \land u \in \Psi_{\mathsf{inf}}\}$, where \cdot denotes appending an element to a tuple—that is, $(t_1, \ldots, t_k) \cdot u = (t_1, \ldots, t_k, u)$. So all 1-hyperproperties are also 2-hyperproperties, etc.

Observational determinism is a 2-hyperproperty, because it suffices to consider pairs of traces to decide whether a system satisfies it. The Hyper-LTL formula (4) that characterizes it makes this apparent:

• The two quantifiers at the beginning of the formula, AA, show that the policy is defined in terms of pairs of traces.

• The subformula following the quantifiers, low-equiv \Rightarrow G low-equiv gives the relation that defines the policy as a 2-hyperproperty. That relation is the set of all pairs (t_1, t_2) of traces such that

$$comp(t_1), comp(t_2) \models low-equiv \Rightarrow G low-equiv.$$

Noninference, however, is not a 2-hyperproperty. Though it can be defined as a relation on pairs of traces, one of those traces is existentially quantified; k-hyperproperties allow only universal quantification. That suggests the following generalization of k-hyperproperties.

5.2 Q-hyperproperties

Let Q be a finite sequence of universal and existential quantifiers—for example, $\forall \exists$. Define hyperproperty \boldsymbol{H} to be an Q-hyperproperty iff |Q|=k and

$$(\exists R \subseteq \Psi_{\inf}^k : (\forall S \in \boldsymbol{H} : (Q \vec{t} \in \Psi_{\inf}^k : \vec{t} \subseteq S : \vec{t} \in R))).$$

Notation $Q \vec{t} \in \Psi_{\inf}^k$ is an abbreviation for k nested quantifications:

$$Q_1 t_1 \in \Psi_{\mathsf{inf}} : Q_2 t_2 \in \Psi_{\mathsf{inf}} : \ldots : Q_k t_k \in \Psi_{\mathsf{inf}},$$

where Q_i denotes quantifier i from sequence Q. For example, $\forall \exists \vec{t} \in \Psi_{inf}^k$ abbreviates $\forall t_1 \in \Psi_{inf} : \exists t_2 \in \Psi_{inf}$.

Noninference is a $\forall \exists$ -hyperproperty. The HyperLTL formula (3) that characterizes it makes this apparent. The two quantifiers show that the policy is defined in terms of pairs of traces. Its defining relation is the set of all pairs (t_1, t_2) of traces such that

$$comp(t_1), comp(t_2) \models G(\langle \top, \neg \mathsf{high-in} \rangle \wedge \mathsf{low-equiv}).$$

Likewise, separability and generalized noninterference are both $\forall\forall\exists$ -hyper-properties, and restrictiveness is the intersection of two $\forall\forall\exists$ -hyper-properties.

The Q-hyperproperties strictly generalize the k-hyperproperties, because (i) for all k, a k-hyperproperty is a \forall^k -hyperproperty, where \forall^k denotes a sequence of k universal quantifiers, and because (ii) no Q-hyperproperty, such that Q contains \exists , is a k-hyperproperty. As do the k-hyperproperties, the Q-hyperproperties form a hierarchy: any Q-hyperproperty is also a Q'-hyperproperty if sequence Q is a prefix of sequence Q'.

A Q-hyperproperty is linear-time if its defining relation R is linear-time, meaning that it can be expressed with the linear-time temporal connectives, X and U. (Or, equivalently [17], that it can be expressed in S1S, the monadic second-order theory of one successor.)

Proposition 5.2. \boldsymbol{H} is a linear-time Q-hyperproperty iff there exists a HyperLTL formula ϕ , such that $S \in \boldsymbol{H}$ iff $S \models \phi$.

Proof. The relation R that defines **H** is equivalent to formula ϕ .

HyperLTL therefore expresses exactly the linear-time Q-hyperproperties, just as LTL expresses exactly the linear-time trace properties, which are themselves \forall -hyperproperties.

5.3 Safety

Safety [1] proscribes "bad things." A bad thing is *finitely observable*, meaning its occurrence can be detected in finite time, and *irremediable*, so its occurrence can never be remediated by future events.

Definition 5.3 (Hypersafety [12]). A hyperproperty S is a safety hyperproperty (is hypersafety) iff

$$(\forall T \subseteq \Psi_{\mathsf{inf}} : T \notin \mathbf{S} \implies (\exists B \subseteq \Psi_{\mathsf{fin}} : |B| \in \mathbb{N} \land B \leq T$$
$$\land (\forall U \subseteq \Psi_{\mathsf{inf}} : B < U \implies U \notin \mathbf{S}))).$$

For a system T that doesn't satisfy a safety hyperproperty, the bad thing is a finite set B of finite traces. B cannot be a prefix of any system U satisfying the hyper safety property. A finite trace t is a prefix of a (finite or infinite) trace t', denoted $t \leq t'$, iff t' = tt'' for some $t'' \in \Psi$. And a finite set T of finite traces is a prefix of a (finite or infinite) set T' of (finite or infinite) traces, denoted $T \leq T'$, iff $(\forall t \in T : (\exists t' \in T' : t \leq t'))$. A k-safety hyperproperty is a safety hyperproperty in which the bad thing never involves more than k traces. A hyperproperty S is a k-safety hyperproperty (is k-hypersafety) [12] iff

$$(\forall T \subseteq \Psi_{\mathsf{inf}} : T \notin \mathbf{S} \implies (\exists B \subseteq \Psi_{\mathsf{fin}} : |B| \le k \land B \le T \\ \land (\forall U \subseteq \Psi_{\mathsf{inf}} : B \le U \implies U \notin \mathbf{S}))).$$

This is just the definition of hypersafety but with the cardinality of B bounded by k.

Define a relation R to be a k-safety relation iff

$$(\forall \, \vec{t} \in \Psi^k_{\mathsf{inf}} \, : \, \vec{t} \not \in R \implies (\exists \, \vec{b} \in \Psi^{\leq k}_{\mathsf{fin}} \, : \, \vec{b} \leq \vec{t} \, \land \\ (\forall \, \vec{u} \in \Psi^k_{\mathsf{inf}} \, : \, \vec{b} \leq \vec{u} \implies \vec{u} \not \in R))).$$

Prefix on tuples of traces is the pointwise application of prefix on traces: $\vec{t} \leq \vec{u}$ iff, for all i, it holds that $t_i \leq u_i$. Set $\Psi_{\text{fin}}^{\leq k}$ is all n-tuples of traces where $n \leq k$.

Observational determinism is a 2-safety hyperproperty [12], as well as a 2-hyperproperty definable by a 2-safety relation. Moreover, the k-safety hyperproperties are all k-hyperproperties:

Proposition 5.4. A k-hyperproperty H is definable by a k-safety relation iff H is a k-safety hyperproperty.

Proof. (\Rightarrow) The bad thing for a system that doesn't satisfy \boldsymbol{H} is tuple b. (\Leftarrow) The relation is the set of all k-tuples of traces that do not contain a bad thing as a prefix.

The k-safety hyperproperties are known [12] to have a relatively complete verification methodology based on self-composition. Our model-checking algorithm in §4 increases the class of hyperproperties that can be verified from k-safety to k-hyperproperties and a fragment of Q-hyperproperties.

5.4 Arithmetic hierarchy

The Q-hyperproperties categorize by quantifier structure. The arithmetic hierarchy, first studied by Kleene [25], similarly categorizes computable relations. Rogers [39] gives the following characterization of the arithmetic hierarchy:

Definition 5.5 (Arithmetic hierarchy [39]). An n-ary relation S is in the arithmetic hierarchy iff S is decidable or there exists a decidable k-ary relation R such that

$$S = \{(x_1, x_2, \dots, x_n) \mid Q_1 y_1 Q_2 y_2 \dots Q_k y_k :$$

$$R(x_1, \dots, x_n, y_1, \dots, y_k)\},$$

where, for all $1 \leq i \leq k$, quantifier Q_i is either \forall or \exists . The sequence of quantifiers Q_i is the quantifier prefix. When such a prefix does exist for S, then S is expressible by Q_i . The number of alternations in a prefix the number of pairs of adjacent but unlike quantifiers. For example, in the prefix $\forall\forall\exists\forall$, there are two alternations. A Σ_n -prefix, where n>0, is a prefix that begins with \exists and has n-1 alternations. A Σ_0 -prefix is a prefix that is empty. Likewise, a Π_n -prefix, where n>0, is a prefix that begins with \forall and has n-1 alternations. A Π_0 -prefix is a prefix that is empty, so Π_0 -prefixes are the same as Σ_0 -prefixes. The arithmetic hierarchy comprises the following classes:




Figure 1: Arithmetic hierarchy of hyperproperties

- Σ_n is the class of all relations expressible by Σ_n -prefixes.
- Π_n is the class of all relations expressible by Π_n -prefixes.
- (Another class, $\Delta_n = \Sigma_n \cap \Pi_n$, does not concern us here.)

A relation expressible by $\exists \forall$ is, for example, in Σ_2 , and a relation expressible by \forall is in Π_1 , but a relation expressible by $\forall \forall$ is also in Π_1 . These classes form a hierarchy, because they grow strictly larger as n increases: $\Sigma_n \subset \Sigma_{n+1}$ and $\Pi_n \subset \Pi_{n+1}$.

The same idea is applicable to Q-hyperproperties:

- The Σ_n -hyperproperties are the Q-hyperproperties such that Q is a Σ_n -prefix and the defining relation R is decidable.
- The Π_n -hyperproperties are the Q-hyperproperties such that Q is a Π_n -prefix and the defining relation R is decidable.

Figure 1 depicts this hierarchy. Simply by reading off the quantifier prefix, any HyperLTL formula makes it easy to determine (an upper bound on) the hierarchy level in which it dwells. Observational determinism (whose prefix is AA) is a Π_1 -hyperproperty, as are all k-hyperproperties. Noninference (prefix AE) is a Π_2 -hyperproperty, as are separability and generalized noninterference (prefix AAE). Their defining relations are decidable, because HyperLTL₂ validity is decidable.

This arithmetic hierarchy of hyperproperties yields insight into verification. Our model-checking algorithm in §4 permits up to one quantifier alternation, thus verifying a linear-time subclass of Π_2 -hyperproperties. What about hyperproperties higher than Π_2 in the hierarchy? We don't yet know of any security policies that are examples. As Rogers [39] writes, "The human mind seems limited in its ability to understand and visualize beyond four or five alternations of quantifier. Indeed, it can be argued that the inventions... of mathematics are devices for assisting the mind in dealing with one or two additional alternations of quantifier." For practical purposes, we might not need to go much higher than Π_2 .

6 Related Work

McLean [33] formalizes security policies as closure with respect to selective interleaving functions. He shows that trace properties cannot express security policies such as noninterference and average response time, because those are not properties of single execution traces. Mantel [30] formalizes security policies with basic security predicates, which stipulate closure conditions for trace sets.

Clarkson and Schneider [12] introduce hyperproperties, a framework for expressing security policies. Hyperproperties are sets of trace sets, and are able to formalize security properties such as noninterference, generalized noninterference, observational determinism and average response time. Clarkson and Schneider use second-order logic to formulate hyperproperties. That logic isn't verifiable, in general, because it cannot be effectively and completely axiomatized. Fragments of it, such as HyperLTL, can be verified.

van der Meyden and Zhang [43] use model-checking to verify noninterference policies. They reduce noninterference properties to safety properties expressible in standard linear and branching time logics. Their methodology requires customized model-checking algorithms for each security policy, whereas HyperLTL uses the same algorithm for every policy.

Dimitrova et al. [14] propose SecLTL, which extends LTL with a *hide* modality \mathcal{H} that requires observable behavior to be independent of secret values. SecLTL is designed for output-deterministic systems. Generalized noninterference (5), and other policies for nondeterministic systems, do not seem to be expressible with \mathcal{H} .

Balliu et al. [5] use a linear-time temporal epistemic logic to specify many declassification policies derived from noninterference. Their definition of noninterference, however, seems to be that of observational determinism (4). They do not consider any information-flow policies involving existential quantification, such as noninference (3). They also do not consider systems that accept inputs after execution has begun. Halpern and O'Neill [21] use a similar temporal epistemic logic to specify *secrecy* policies, which subsume many definitions of noninterference; they do not pursue model checking algorithms.

Milishev and Clarke [36,37] propose a verification methodology based on formulating hyperproperties as coinductive predicates over trees. They use the polyadic modal μ -calculus [4] to express hyperproperties and game-based model-checking to verify them. Their logic, because it includes fixpoint operators, seems to be more expressive than HyperLTL. Nonetheless, HyperLTL is able to express many security policies, suggesting that a simpler logic suffices.

Acknowledgements

Fred B. Schneider suggested the name "HyperLTL" for our logic. We thank him, Dexter Kozen, José Meseguer, and Moshe Vardi for discussions about this work. Adam Hinz worked on an early prototype of the model checker. This work was supported in part by AFOSR grant FA9550-12-1-0334 and NSF grant CNS-1064997.

References

- [1] Bowen Alpern and Fred B. Schneider. Defining liveness. *Information Processing Letters*, 21(4):181–185, 1985.
- [2] Bowen Alpern and Fred B. Schneider. Recognizing safety and liveness. *Distributed Computing*, 2(3):117–126, 1987.
- [3] Rajeev Alur, Pavol Černý, and Steve Zdancewic. Preserving secrecy under refinement. In *Proc. International Colloquium on Automata, Languages and Programming*, pages 107–118, 2006.
- [4] Henrik Reif Andersen. A polyadic modal mu-calculus. Technical Report 1994-145, Technical University of Denmark (DTU), 1994.
- [5] Musard Balliu, Mads Dam, and Gurvan Le Guernic. Epistemic temporal logic for information flow security. In Proc. Workshop on Programming Languages and Analysis for Security, Jun. 2011.

- [6] Gilles Barthe, Juan Manuel Crespo, and César Kunz. Beyond 2-safety: asymmetric product programs for relational program verification. In Symposium on Logical Foundations of Computer Science, 2013.
- [7] Gilles Barthe, Pedro R. D'Argenio, and Tamara Rezk. Secure information flow by self-composition. In *Proc. IEEE Computer Security Foundations Workshop*, pages 100–114, June 2004.
- [8] Jeremy Bryans, Maciej Koutny, Laurent Mazaré, and Peter Y. A. Ryan. Opacity generalised to transition systems. In Workshop on Formal Aspects in Security and Trust, pages 81–95, 2005.
- [9] Julius R. Büchi. On a decision method in restricted second order arithmetic. In *Proc. International Congress on Logic, Methodology, and Philosophy of Science*, pages 1–12, 1962.
- [10] Alessandro Cimatti, Edmund M. Clarke, Fausto Giunchiglia, and Marco Roveri. NuSMV: A new symbolic model verifier. In *Proc. International Conference on Computer Aided Verification*, pages 495–499, July 1999.
- [11] Edmund M. Clarke, Orna Grumberg, and Doron Peled. *Model Checking*. The MIT Press, December 1999.
- [12] Michael R. Clarkson and Fred B. Schneider. Hyperproperties. *Journal of Computer Security*, 18(6):1157–1210, 2010.
- [13] Costas Courcoubetis, Moshe Vardi, Pierre Wolper, and Mihalis Yannakakis. Memory-efficient algorithms for the verification of temporal properties. Formal Methods in System Design, 1(2/3):275–288, October 1992.
- [14] Rayna Dimitrova, Bernd Finkbeiner, Máté Kovács, Markus N. Rabe, and Helmut Seidl. Model checking information flow in reactive systems. In Proc. International Conference on Verification, Model Checking, and Abstract Interpretation, pages 169–185, January 2012.
- [15] E. Allen Emerson and Edmund M. Clarke. Using branching time logic to synthesize synchronization skeletons. Science of Computer Programming, 2:241–266, October 1982.
- [16] E. Allen Emerson and Joseph Y. Halpern. "Sometimes" and "not never" revisited: On branching versus linear time temporal logic. *Journal of the ACM*, 33(1):151–178, January 1986.

- [17] Dov Gabbay, Amir Pnueli, Saharon Shelah, and Jonathan Stavi. On the temporal analysis of fairness. In *Proc. ACM Symposium on Principles of Programming Languages*, pages 163–173, January 1980.
- [18] Paul Gastin and Denis Oddoux. Fast LTL to Büchi automata translation. In Proc. International Conference on Computer Aided Verification, pages 53–65, July 2001.
- [19] Rob Gerth, Doron Peled, Moshe Y. Vardi, and Pierre Wolper. Simple on-the-fly automatic verification of linear temporal logic. In *Proc. IFIP WG6.1 International Symposium on Protocol Specification, Testing and Verification*, pages 3–18, June 1995.
- [20] Joseph A. Goguen and José Meseguer. Security policies and security models. In *Proc. IEEE Symposium on Security and Privacy*, pages 11–20, April 1982.
- [21] Joseph Y. Halpern and Kevin R. O'Neill. Secrecy in multiagent systems. *Transactions on Information and System Security*, 12(1):5:1–47, October 2008.
- [22] Ronald H. Hardin, Zvi Har'El, and Robert P. Kurshan. COSPAN. In Proc. International Conference on Computer Aided Verification, pages 423–427, July 1996.
- [23] Gerard J. Holzmann. The model checker SPIN. *IEEE Transactions on Software Engineering*, 23:279–295, 1997.
- [24] Marieke Huisman, Pratik Worah, and Kim Sunesen. A temporal logic characterisation of observational determinism. In *Proc. IEEE Computer Security Foundations Workshop*, pages 3–15, July 2006.
- [25] Stephen C. Kleene. Recursive predicates and quantifiers. *Transactions of the American Mathematical Society*, 53:41–73, 1943.
- [26] Dexter Kozen. Results on the propositional μ -calculus. Theoretical Computer Science, 27:333–354, 1983.
- [27] Leslie Lamport. Proving the correctness of multiprocess programs. *IEEE Transactions on Software Engineering*, 3(2):125–143, 1977.
- [28] Leslie Lamport. Specifying Systems: The TLA+ Language and Tools for Hardware and Software Engineers. Addison-Wesley, Boston, 2002.

- [29] Peng Li and Steve Zdancewic. Downgrading policies and relaxed non-interference. In *Proc. ACM Symposium on Principles of Programming Languages*, pages 158–170, January 2005.
- [30] Heiko Mantel. Possibilistic definitions of security: An assembly kit. In *Proc. IEEE Computer Security Foundations Workshop*, pages 185–199, July 2000.
- [31] Daryl McCullough. Noninterference and the composability of security properties. In *Proc. IEEE Symposium on Security and Privacy*, pages 177–186, April 1988.
- [32] Daryl McCullough. A hookup theorem for multilevel security. *Proc. IEEE Transactions on Software Engineering*, 16(6):563–568, June 1990.
- [33] John McLean. A general theory of composition for trace sets closed under selective interleaving functions. In *Proc. IEEE Symposium on Security and Privacy*, pages 79–93, May 1994.
- [34] John McLean. A general theory of composition for a class of "possibilistic" properties. *IEEE Transactions on Software Engineering*, 22(1):53–67, 1996.
- [35] Jonathan K. Millen. Unwinding forward correctability. In *Proc. IEEE Computer Security Foundations Workshop*, pages 2–10, June 1994.
- [36] Dimiter Milushev and Dave Clarke. Towards incrementalization of holistic hyperproperties. In *Proc. Conference on Principles of Security and Trust*, pages 329–348, 2012.
- [37] Dimiter Vladimirov Milushev. Reasoning about Hyperproperties. PhD thesis, Katholieke Universiteit Leuven, Jun. 2013.
- [38] Amir Pnueli. The temporal logic of programs. In *Proc. IEEE Symposium on Foundations of Computer Science*, pages 46–57, November 1977.
- [39] Hartley Rogers, Jr. Theory of Recursive Functions and Effective Computability. MIT Press, Cambridge, Massachusetts, 1987.
- [40] Peter Y. A. Ryan and Thea Peacock. Opacity—further insights on an information flow property. Technical Report CS-TR-958, University of Newcastle upon Tyne, April 2006.

- [41] Tachio Terauchi and Alexander Aiken. Secure information flow as a safety problem. In *Proc. Static Analysis Symposium*, pages 352–367, September 2005.
- [42] Yih-Kuen Tsay, Yu-Fang Chen, Ming-Hsien Tsai, Kang-Nien Wu, and Wen-Chin Chan. Goal: a graphical tool for manipulating Büchi automata and temporal formulae. In *Proc. International Conference on Tools and Algorithms for the Construction and Analysis of Systems*, pages 466–471, March 2007.
- [43] Ron van der Meyden and Chenyi Zhang. Algorithmic verification of noninterference properties. *Electronic Notes in Theoretical Computer Science (ENTCS)*, 168:61–75, February 2007.
- [44] Moshe Y. Vardi. An automata-theoretic approach to linear temporal logic. In *Proc. Banff Higher Order Workshop on Logics for Concurrency*, pages 238–266, August 1996.
- [45] Moshe Y. Vardi. Automata-theoretic model checking revisited. In *Proc. International Conference on Verification, Model Checking, and Abstract Interpretation*, pages 137–150, January 2007.
- [46] Moshe Y. Vardi and Pierre Wolper. Reasoning about infinite computations. *Information and Computation*, 115(1):1–37, 1994.
- [47] Niklaus Wirth. Program development by stepwise refinement. Communications of the ACM, 14(4):221–227, April 1971.
- [48] Pierre Wolper. Constructing automata from temporal logic formulas: A tutorial. In *Lectures on Formal Methods and Performance Analysis*, volume 2090 of *Lecture Notes in Computer Science*, pages 261–277, 2000.
- [49] Steve Zdancewic and Andrew C. Myers. Observational determinism for concurrent program security. In *Proc. IEEE Computer Security Foundations Workshop*, pages 29–43, June 2003.

A The insufficiency of branching-time logic

CTL and CTL* have explicit path quantifiers. It's tempting to try to express security policies with those quantifiers. Unfortunately, that doesn't work for

information-flow policies such as observational determinism (4). Consider the following fragment of CTL* semantics [16]:

$$s \models A \phi$$
 iff for all $\pi \in M$, if $\pi(1) = s$ then $\pi \models \phi$
 $\pi \models \Phi$ iff $\pi(1) \models \Phi$

Path formulas ϕ are modeled by paths π , and state formulas Φ are modeled by states s. Set M is all paths in the model. State formula $A \phi$ holds at state s when all paths proceeding from s satisfy ϕ . Any state formula Φ can be treated as a path formula, in which case Φ holds of the path iff Φ hold of the first state on that path. Using this semantics, consider the meaning of $AA \phi$, which is the form of observational determinism (4):

$$s \models AA \phi$$

= for all $\pi \in M$ if $\pi(1) = s$ then $\pi \models A \phi$
= for all $\pi \in M$ and $\pi' \in M$, if $\pi(1) = \pi'(1) = s$ then $\pi' \models \phi$

Note how the meaning of AA ϕ is ultimately determined by the meaning of ϕ , where ϕ is modeled by the single trace π' . Trace π is ignored in determining the meaning of ϕ ; the second universal path quantifier causes π to "leave scope." Hence ϕ cannot express correlations between π and π' , as observational determinism requires. So CTL* path quantifiers do not suffice to express information-flow policies. Neither do CTL path quantifiers, because CTL is a sub-logic of CTL*. Self-composition does enable expression of some, though not all, information-flow policies in branching-time logics, as we discuss in §2.2.

B Model-checking Constructions

B.1 Self-composition construction

Self-composition is the technique that Barthe et al. [7] adopt to verify non-interference policies. It was generalized by Terauchi and Aiken [41] to verify observational determinism policies [29, 49], and by Clarkson and Schneider [12] to verify k-safety hyperproperties. We extend this technique to model-checking of HyperLTL₂.

Büchi automata. Büchi automata [46] are finite-state automata that accept strings of infinite length. A Büchi automaton is a tuple $(\Sigma, S, \Delta, S_0, F)$ where Σ is an alphabet, S is the set of states, Δ is the transition relation such that $\Delta \subseteq S \times \Sigma \times S$, S_0 is the set of initial states, and F is the set of

accepting states, where both $S_0 \subseteq S$ and $F \subseteq S$. A string is a sequence of letters in Σ . A path $s_0s_1...$ of a Büchi automaton is over a string $\alpha_1\alpha_2...$ if, for all $i \geq 0$, it holds that $(s_i, \alpha_{i+1}, s_{i+1}) \in \Delta$. A string is recognized by a Büchi automaton if there exists a path π over the string with some accepting states occurring infinitely often, in which case π is an accepting path. The language $\mathcal{L}(A)$ of an automaton A is the set of strings that automaton accepts. A Büchi automaton can be derived [11] from a Kripke structure, which is a common mathematical model of interactive, state-based systems.

Self composition. The n-fold self-composition A^n of Büchi automaton A is essentially the product of A with itself, n times. This construction is defined as follows:

Definition B.1. Büchi automaton A^n is the n-fold self-composition of Büchi automaton A, where $A = (\Sigma, S, \Delta, S_0, F)$, if $A^n = (\Sigma^n, S^n, \Delta', S_0^n, F^n)$ and for all $s_1, s_2 \in S^n$ and $\alpha \in \Sigma^n$ we have $(s_1, \alpha, s_2) \in \Delta'$ iff for all $1 \le i \le n$, it holds that $(prj_i(s), prj_i(\alpha), prj_i(s')) \in \Delta$.

 A^n recognizes $zip(\gamma_1,\ldots,\gamma_n)$ if A recognizes each of γ_1,\ldots,γ_n :

Proposition B.2.
$$\mathcal{L}(A^n) = \{zip(\gamma_1, \dots, \gamma_n) \mid \gamma_1, \dots, \gamma_n \in \mathcal{L}(A)\}$$

Proof. By the construction of A^n .

B.2 Formula-to-automaton construction

Given a HyperLTL₂ formula $A^k \to b^j \psi$ and a set B of bonding functions, we now show how to construct an automaton that accepts exactly the strings w for which $unzip(w) \models \psi$. Our construction extends standard methodologies for LTL automata construction [18, 19, 44, 45].

1. Negation normal form. We begin by preprocessing ψ to put it in a form more amenable to model checking. The formula is rewritten to be in *negation normal form* (NNF), meaning (i) negation connectives are applied only to atomic propositions in ψ , (ii) the only connectives used in ψ are X, U, R, \neg , \vee , \wedge , and focus formulas, and (iii) every focus formula contains exactly one non- \top subformula—for example, $\langle \top, \dots, \top, p, \top, \dots, \top \rangle$ or $\langle \top, \dots, \top, \neg p, \top, \dots, \top \rangle$ —and that subformula must be an atomic proposition or its negation. We identify $\neg \neg \psi$ with ψ .

2. Construction. We now construct a generalized Büchi automaton [13] A_{ψ} for ψ . A generalized Büchi automaton is the same as a Büchi automaton except that it has multiple sets of accepting states. That is, a generalized Büchi automaton is a tuple $(\Sigma, S, \Delta, S_0, F)$ where Σ, S, Δ and S_0 are defined as for Büchi automata, and $F = \{F_i \mid 1 \leq i \leq m \text{ and } F_i \subseteq S\}$. Each of the F_i is an accepting set. A string is recognized by a generalized Büchi automaton if there is a path over the string with at least one of the states in every accepting set occurring infinitely often.

To construct the states of A_{ψ} , we need some additional definitions. Define *closure* $cl(\psi)$ of ψ to be the least set of subformulas of ψ that is closed under the following rules:

- if $\langle \top, \dots, \top, \psi', \top, \dots, \top \rangle \in cl(\psi)$, then $\langle \top, \dots, \top, \neg \psi', \top, \dots, \top \rangle \in cl(\psi)$.
- if $\psi' \in cl(\psi)$ and ψ' is not in the form of $\langle \psi_1, \dots, \psi_n \rangle$, then $\neg \psi' \in cl(\psi)$.
- if $\psi_1 \wedge \psi_2 \in cl(\psi)$ or $\psi_1 \vee \psi_2 \in cl(\psi)$, then $\{\psi_1, \psi_2\} \subseteq cl(\psi)$.
- if $X \psi' \in cl(\psi)$, then $\psi' \in cl(\psi)$.
- if $\psi_1 \cup \psi_2 \in cl(\psi)$ or $\psi_1 \cap \psi_2 \in cl(\psi)$, then $\{\psi_1, \psi_2\} \subseteq cl(\psi)$.

And define K to be a maximal consistent set with respect to $cl(\psi)$ if $K \subseteq cl(\psi)$ and the following conditions hold:

- if ψ' is not a focus formula, then $(\psi' \in K \text{ iff } \neg \psi' \notin K)$.
- if ψ' is a focus formula $\langle \top, \dots, \top, \psi', \top, \dots, \top \rangle$ and $\psi' \in cl(\psi)$, then $(\psi' \in K \text{ iff } \langle \top, \dots, \top, \neg \psi', \top, \dots, \top \rangle \notin K)$.
- if $\psi_1 \wedge \psi_2 \in cl(\psi)$, then $(\psi_1 \wedge \psi_2 \in K \text{ iff } \{\psi_1, \psi_2\} \subseteq K)$.
- if $\psi_1 \vee \psi_2 \in cl(\psi)$, then $(\psi_1 \vee \psi_2 \in K \text{ iff } \psi_1 \in K \text{ or } \psi_2 \in K)$.
- if $\psi_1 \cup \psi_2 \in K$ then $\psi_1 \in K$ or $\psi_2 \in K$.
- if $\psi_1 \mathbf{R} \psi_2 \in K$ then $\psi_2 \in K$.

Define $ms(\psi)$ to be the set of all maximal consistent sets with respect to ψ . The elements of $ms(\psi)$ will be the states of A_{ψ} ; hence each state is a set of formulas. Intuitively, a state s describes a set of computation tuples where each tuple is a model of all the formulas in s. There will be a transition from a state s_1 to a state s_2 iff every computation tuple described by s_2 is

an immediate suffix of some tuple described by s_1 . (Tuple Γ is an immediate suffix of Γ' iff $\Gamma = \Gamma'[2..]$.)

Automaton $A_{\psi} = (\Sigma_{\psi}, S_{\psi}, \Delta_{\psi}, \{\iota_{\psi}\}, F_{\psi})$ is defined as follows:

- The alphabet Σ_{ψ} is $\mathcal{P}(\mathsf{Atoms})^n$. Each letter of the alphabet is, therefore, an *n*-tuple of sets of atomic propositions.
- The set S_{ψ} of states is $ms(\psi) \cup \{\iota_{\psi}\}$, where $ms(\psi)$ is defined above and ι_{ψ} is a distinct initial state.
- The transition relation Δ_{ψ} contains (s_1, α, s_2) , where $\{s_1, s_2\} \subseteq S_{\psi} \setminus \{\iota_{\psi}\}$ and $\alpha \in \Sigma_{\psi}$, iff
 - For all $p \in \mathsf{Atoms}$, if $\langle \top, \dots, \top, p, \top, \dots, \top \rangle \in s_2$, and p is element i of that focus formula, then $p \in prj_i(\alpha)$. Likewise, if $\langle \top, \dots, \top, \neg p, \top, \dots, \top \rangle \in s_2$, then $p \notin prj_i(\alpha)$.
 - For all $p \in \mathsf{Compounds}$, if $p \in s_2$ then $p \in B(\alpha)$. Likewise, if $\neg p \in s_2$ then $p \notin B(\alpha)$.
 - If $X \psi' \in s_1$ then $\psi' \in s_2$.
 - If $\psi_1 \cup \psi_2 \in s_1$ and $\psi_2 \notin s_1$ then $\psi_1 \cup \psi_2 \in s_2$.
 - If $\psi_1 R \psi_2 \in s_1$ and $\neg \psi_1 \in s_1$ then $\psi_1 R \psi_2 \in s_2$.

And Δ_{ψ} contains $(\iota_{\psi}, \alpha, s_2)$ iff $\psi \in s_2$ and $(\iota_{\psi}, \alpha, s_2)$ is a transition permitted by the above rules for Atoms and Compounds.

- The set of initial states contains only ι_{ψ} .
- The set F_{ψ} of sets of accepting states contains one set $\{s \in (S_{\psi} \setminus \{\iota_{\psi}\}) \mid \neg(\psi_1 \cup \psi_2) \in s \text{ or } \psi_2 \in s\}$ for each until formula $\psi_1 \cup \psi_2$ in $cl(\psi)$.

The definition of F_{ψ} guarantees that, for every until formula $\psi_1 \cup \psi_2$, eventually ψ_2 will hold. That is because the transition rules don't allow a transition from a state containing $\psi_1 \cup \psi_2$ to a state containing $\neg(\psi_1 \cup \psi_2)$ unless ψ_2 is already satisfied.

3. Degeneralization of Büchi automata. Finally, convert generalized Büchi automaton A_{ψ} to a "plain" Büchi automaton. This conversion is entirely standard [19], so we do not repeat it here.

Correctness of the construction. The following proposition states that A_{ψ} is constructed such that it recognizes computation tuples that model ψ :

Proposition B.3. $\Gamma \models \psi \text{ iff } zip(\Gamma) \in \mathcal{L}(A_{\psi}).$

- *Proof.* (\Leftarrow) By the construction of A_{ψ} , the states with a transition from ι_{ψ} contain ψ . Hence by Lemma B.4 below, for all the strings w such that $w = zip(\Gamma)$ in $\mathcal{L}(A_{\psi})$, it holds that $\Gamma \models \psi$.
- (\Rightarrow) Let $s_i = \{\psi' \in cl(\psi) \mid \Gamma[i..] \models \psi'\}$ for all $i \in \mathbb{N}$. Then by the definition, $s_i \in ms(\psi)$. We show that $\iota_{\psi}s_1s_2...$ is an accepting path in A_{ψ} . By $\Gamma \models \psi$ we have $\psi \in s_1$. By the construction of A_{ψ} , $(i_{\psi}, \alpha_1, s_1) \in \Delta_{\psi}$ where $\alpha_1 = zip(\Gamma)[1]$. The construction of the path inductively follows the construction of A_{ψ} , which respects the semantics of HyperLTL.

Lemma B.4. Let $\iota_{\psi}s_1...$ be an accepting path in A_{ψ} over the string $w = \alpha_1\alpha_2...$ Let $\Gamma = unzip(w)$. Then for all $i \geq 0$, it holds that $\psi' \in s_i$ iff $\Gamma[i..] \models \psi'$.

Proof. The proof proceeds by induction on the structure of ψ' :

Base cases:

- 1. $\psi' = p$ where $p \in \mathsf{Compounds}$
 - (\Rightarrow) Assume that $p \in s_i$. By the construction of A_{ψ} , if $p \in s_i$ then $p \in B_n(\alpha_i)$ or equivalently $p \in B_n(\Gamma[i])$. By the semantics of HyperLTL, we have $\Gamma[i..] \models p$.
 - (\Leftarrow) Assume that $\Gamma[i..] \models p$. Then $p \in B_n(\Gamma[i])$, which is equivalent to $p \in B_n(\alpha_i)$. By the fact that states are maximal consistent sets, one of p or $\neg p$ must appear in s_i . By the construction of A_{ψ} and the fact that $p \in B_n(\alpha_i)$, we have $p \in s_i$.
- 2. $\psi' = \langle \psi_1, \dots, \psi_n \rangle$
 - (\Rightarrow) Assume that $\psi' \in s_i$. By the construction of A_{ψ} , for all $1 \leq r \leq n$, if $\psi_r = p$ we have $p \in prj_r(\alpha_i)$ or equivalently $p \in prj_r(\Gamma[i])$. Then by the semantics of HyperLTL, $prj_r(\Gamma[i]) \models \psi_r$. If $\psi_r = \neg p$, then $p \notin prj_r(\Gamma[i])$, which again concludes $prj_r(\Gamma[i]) \models \psi_r$. Therefore we have $\Gamma[i...] \models \psi'$.
 - (\Leftarrow) Assume that $\Gamma[i..] \models \psi'$. Then for all $1 \leq r \leq n$, $prj_r(\Gamma[i]) \models \psi_r$. If $\psi_r = p$ we have $p \in prj_r(\Gamma[i])$, which is equivalent to $p \in prj_r(\alpha_i)$. If $\psi_r = \neg p$ then $p \notin prj_r(\Gamma[i])$, which is $p \notin prj_r(\alpha_i)$. By the fact that states are maximal consistent sets, one of $\langle \psi_1, \ldots, \psi_n \rangle$ or a member of

 $\overline{\langle \psi_1, \dots, \psi_n \rangle}$ must appear in s_i . By the semantics of HyperLTL and the construction of A_{ψ} , only $\langle \psi_1, \dots, \psi_n \rangle$ can be in s_i , that means $\psi' \in s_i$.

Inductive cases:

- 1. $\psi' = \neg \psi''$
 - (\Rightarrow) Assume that $\neg \psi'' \in s_i$, Then $\psi'' \notin s_i$. By induction hypothesis, $\Gamma[i..] \not\models \psi''$, or equivalently, $\Gamma[i..] \models \neg \psi''$. Hence, $\Gamma[i..] \models \psi'$.
 - (\Leftarrow) Similar to \Rightarrow .
- 2. $\psi' = \psi_1 \vee \psi_2$
 - (\Rightarrow) By the construction of A_{ψ} , if $\psi_1 \vee \psi_2 \in s_i$ then $\psi_1 \in s_i$ or $\psi_2 \in s_i$. By induction hypothesis, $\Gamma[i..] \models \psi_1$ or $\Gamma[i..] \models \psi_2$, which concludes $\Gamma[i..] \models \psi_1 \vee \psi_2$.
 - (\Leftarrow) Similar to \Rightarrow .
- 3. $\psi' = X \psi''$
 - (⇒) Assume that $\psi' \in s_i$. By the construction of A_{ψ} , $\psi'' \in s_{i+1}$. By induction hypothesis, $\Gamma[i+1..] \models \psi''$, which concludes $\Gamma[i..] \models X \psi''$.
 - (⇐) Similar to \Rightarrow and the fact that always one of $X \psi''$ or $\neg X \psi''$ appears in a state.
- 4. $\psi' = \psi_1 \cup \psi_2$
 - (\Rightarrow) Assume that $\psi_1 \cup \psi_2 \in s_i$. By the construction of A_{ψ} and the fact that the path is accepting, there is some $j \geq i$ such that $\psi_2 \in s_j$. Let j be the smallest index. By induction hypothesis, $\Gamma[j..] \models \psi_2$. By the construction of A_{ψ} , for all $i \leq k < j$, $\psi_1 \in s_k$. Therefore by induction hypothesis, $\Gamma[k..] \models \psi_1$. which concludes $\Gamma[i..] \models \psi_1 \cup \psi_2$.

 (\Leftarrow) Similar to \Rightarrow .