Geography and similarity of regional cuisines in China

Yu-Xiao Zhu^{1,2,3}, Junming Huang⁴, Zi-Ke Zhang⁵, Qian-Ming Zhang^{1,3}, Tao Zhou^{1,3}, Yong-Yeol Ahn^{2,*}
1 Web Sciences Center, School of Computer Science and Engineering, University of Electronic Science and Technology of China, Chengdu, Sichuan, People's Republic of

- China
 2 School of Informatics and Computing, Indiana University, Bloomington 47408, United
- 3 Beijing Computational Science Research Center, Beijing 100084, People's Republic of China
- 4 Institute of Computing Technology, Chinese Academy of Sciences, Beijing 100190, People's Republic of China
- 5 Institute of Information Economy, Alibaba Business College, Hangzhou Normal University, Hangzhou, Zhejiang, People's Republic of China
- * Corresponding Author: yyahn@indiana.edu

Abstract

States of America

Food occupies a central position in every culture and it is therefore of great interest to understand the evolution of food culture. The advent of the World Wide Web and online recipe repositories has begun to provide unprecedented opportunities for data-driven, quantitative study of food culture. Here we harness an online database documenting recipes from various Chinese regional cuisines and investigate the similarity of regional cuisines in terms of geography and climate. We found that the geographical proximity, rather than climate proximity is a crucial factor that determines the similarity of regional cuisines. We develop a model of regional cuisine evolution that provides helpful clues to understand the evolution of cuisines and cultures.

1 Introduction

The most essential need for all living organisms is energy, which is usually obtained by consuming food. So it is not hard to imagine why food affects all aspects of human life and culture [1–3]. Food has been studied in depth by many disciplines including history [4–7], sociology [8–10], philosophy [11, 12], and literary criticism [13], etc. Understanding how food culture evolves will have profound impact on numerous domains. Despite its manifest importance, few studies have taken quantitative, systematic approaches towards food culture, mainly due to the scarcity of systematically collected databases.

Nevertheless, such an approach is promising. For example, one pioneering study revealed the connections between climate and the use of spices through the manual digitization of a large number of traditional recipes [14]. Recent increases in online recipe repositories have begun to allow for easier access to structured recipe data [15–17]. Harnessing this opportunity, we address the following questions about the evolution of regional cuisines: (1) How does the similarity between regional cuisines scale with geographical distance? (2) Is climate similarity the main factor determining similarity? Climate obviously plays an important role in shaping food culture, because it both limits the availability of ingredients and affects the usage of spices [14]. However, geographical proximity alone might drive nearby cuisines close because of frequent communication and migration. To address these questions, we examine regional recipes in China — the second largest and the most populous country in the world, which is home to billions of people with diverse cultural heritages. The landmass of China spans North-South and East-West rather evenly, providing a good test bed to study the effect of geography and climate.

Our investigation suggests that geographical distance alone plays a more important role than climate. Based on our results, we propose a model of cuisine evolution based on the copy-mutate mechanism. The

key idea is that nearby regional cuisines tend to learn from each other either due to communication or migration. We demonstrate that our simple model reproduces important characteristics of the real data.

2 Data and Methods

2.1 Data collection

In April 2012 we downloaded all the recipes from the Chinese recipe website $Meishijie^1$, which categorizes all recipes into 20 regional cuisines. Figure 1 shows a map of China, annotated with the names of provinces and cuisines, where the colors represent cuisines. Multiple provinces may belong to the same cuisine. Each recipe has the following properties: (i) a cuisine (each recipe belongs to only one cuisine); (ii) a list of ingredients; and (iii) a cooking method. We manually consolidated synonymous ingredient names and removed the recipes that do not have cooking method or have too few (less than three) ingredients. There are 8,498 recipes and 2,911 ingredients in the cleaned dataset. Basic statistics of the dataset are reported in Table 1. Figure 2 shows that the number of ingredients per recipe contains is similarly distributed across all regions (the mode is around 10).

$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	
Chuan 1,148 877 195 10.4608 SiChuan, ChongQing Yue 775 900 23 10.2839 GuangDong Su 372 573 88 10.3199 JiangSu	
Yue 775 900 23 10.2839 GuangDong Su 372 573 88 10.3199 JiangSu	
Su 372 573 88 10.3199 JiangSu	
Min 468 648 60 10 1880 Fulian	
1v111 400 040 03 10.1000 FuJian	
Zhe 460 594 14 10.5978 ZheJiang	
Xiang 691 592 7 11.4660 HuNan	
Hui 218 442 111 9.8899 AnHui	
DongBei 358 458 237 10.0363 JiLin, HeiLongJiang, LiaoNi	ing
HK 151 367 210 9.4040 HongKong	
HuBei 160 266 115 10.7375 HuBei	
Hu 744 692 117 9.4274 ShangHai	
JiangXi 143 210 87 10.3147 JiangXi	
Jing 606 565 74 10.3614 BeiJing	
Other $52 171 16 9.5962 -$	
QingZhen 521 426 131 10.7524 Sinkiang	
ShanXi 125 191 5 11.4720 ShanXi	
XiBei 188 338 52 10.8351 SanXi,GanSu, QingHai, Ning	gXia
Yu 173 291 10 10.6936 HeNan	
YunGui 79 184 23 8.8101 GuiZhou, YunNan	
All 8,498 2911 - 10.4399 -	

Table 1. The basic statistics of regional cuisines in China.

There are M=20 different regional cuisines in total. The eight major regional cuisines, labeled in bold, are the most representative and typical cuisines in China. N_r : number of recipes. N_i : number of ingredients. \hat{N}_i : number of ingredients used only in the cuisine. $\langle K \rangle$: average number of ingredients in a recipe. The last column reports the provinces where a regional cuisine originates in.

¹http://www.meishij.net/



Figure 1. Map of regional cuisines in China.




Figure 2. Probability distribution of the number of ingredients per recipe. All cuisines sow similar distributions, which have a peak around 10.

As previously observed, the ingredient usage frequency follows a skewed distribution; only a small fraction of popular ingredients are widely used, while many ingredients are observed in only a small number of recipes. As shown in Fig. 3, the frequency distribution of ingredients follows a power-law [18] ($\lambda \sim 1.65$ using method in paper [19]), capturing the intuition that a few ingredients such as salt, sugar, and egg constitute a major part of our every day diet. As a result, the set of distinct ingredients roughly follows Heap's law, as seen in Fig. 4, with an exponent around 0.64. According to the method in paper [20], the exponent of Zipf's law corresponding to Fig. 3 can be estimated by $\frac{1}{\lambda-1}$. The product of this exponent and the exponent of Heap's law (0.64) is close to 1, which is consistent with the previous result [21].




Figure 3. Cumulative frequency distribution of ingredient usage. The usage frequency is calculated using all recipes in our dataset. The exponent is obtained by the method in paper [19].

2.2 Quantifying similarity between cuisines

Our dataset can be considered as a bipartite network with a set of recipes and a set of ingredients. An edge between a recipe and an ingredient indicates that the recipe contains the corresponding ingredient. Since each recipe belongs to one and only one regional cuisine, the edges could be categorized into cuisines. Given a cuisine c and an ingredient i, we use n_i^c to denote the degree of ingredient i, counted with edges in cuisine c. In other words, n_i^c is the number of recipes (in cuisine c) that use ingredient i. Therefore,




Figure 4. The number of distinct ingredients discovered VS. the number of recipes scanned. The plot (blue curve) approximately follows Heap's law (black guideline). The graph is obtained by averaging 100 implementations with independently random sequences of recipes.

the ingredient usage vector of regional cuisine c is written in the following form:

$$\widetilde{P}^c = (p_1^c, p_2^c, \dots, p_i^c, \dots, p_n^c), \tag{1}$$

where $p_i^c = \frac{n_i^c}{\sum_{i=1}^c n_i^c}$ is the fraction of recipes in the cuisine c that contain the ingredient i. For example, if recipes in a regional cuisine c use 1,000 ingredients (with duplicates) in total and ingredient i appears in 10 recipes in that cuisine, we have $p_i^c = \frac{10}{1000}$.

Since common ingredients carry little information, we use an ingredient usage vector inspired by TF-IDF (Term Frequency Inverse Document Frequency) [22]:

$$P^{c} = (w_{1}p_{1}^{c}, w_{2}p_{2}^{c}, \dots, w_{i}p_{i}^{c}, \dots, w_{n}p_{n}^{c}),$$
(2)

where a prior weight $w_i = log \frac{\sum_c \sum_i n_i^c}{\sum_c n_i^c}$ is introduced to penalize a popular ingredient. We use P^c for all calculations in this paper. With this representation in hand, we quantify the similarity between two cuisines using the Pearson correlation coefficient (Eq. 3) and cosine similarity (Eq. 4).

(i) Pearson product-moment correlation [23]: This metric measures the extent to which a linear relationship is present between the two vectors. It is defined as

$$PCC(P^a, P^b) = \frac{\sum_{i} (P_i^a - \overline{P^a})(P_i^b - \overline{P^b})}{\sqrt{\sum_{i} (P_i^a - \overline{P^a})^2} \sqrt{\sum_{i} (P_i^b - \overline{P^b})^2}},$$
(3)

where P^a and P^b are ingredient usage vectors of regional cuisine a and b, respectively.

(ii) Cosine similarity [24]: It is a measure of similarity between two vectors of an inner product space that measures the cosine of the angle between them. For regional cuisines a and b, the cosine similarity is represented using a dot product and magnitude as

$$cosine(P^a, P^b) = \frac{\sum_i P_i^a P_i^b}{\sqrt{\sum_i (P_i^a)^2} \times \sqrt{\sum_i (P_i^b)^2}}.$$
 (4)

3 Results

3.1 Outlier detection

As an overview, we apply Principal Component Analysis to identify principal components of the ingredient usage matrix [25]. The distributions of regional cuisines in two principal components (capturing 44% of the information) are presented in Fig. 5. The two most obvious outliers (in solid red) are YunGui and Hong Kong cuisine. This may reflect the facts that ethnic minorities have historically resided in the YunGui region and that Hong Kong was ruled by the British Empire and Japan for more than 100 years.




Figure 5. The distribution of regional cuisines in the first two principal component spaces. YunGui and Hong Kong (red) stand out as outliers.

3.2 Geography and climate

Climate shapes ingredient usage patterns not only by affecting the availability of ingredients but also by exerting other pressures, such as a need to use additional spices as preservatives [14]. At the same time, we expect nearby regions to have a higher probability of similar food culture even without similar climate, because they are more likely to have more communication and migration.

To estimate the effect of climate we use temperature as a proxy. We assume that the annual average temperature approximately captures one of the most fundamental aspects of climates. As shown in the previous work on spices [14], annual temperature strongly predicts the usage of spices, and we further assume that temperature is a strong climate factor that affects ingredient availability. For two regions A and B, the temperature difference $\Delta T_{A,B}$ is simply $|T_A - T_B|$, where T_A is the annual average temperature of region A.

We quantify geographical proximity using two distance measures: physical distance and topological distance. We measure physical distance between two cuisines by identifying the central cities of the cuisines and then calculating the great-circle distance [26]. To measure topological distance between two cuisines, we construct a graph of cuisines, where a node represent a regional cuisine and an edge represents adjacency of two cuisines, we then measure topological distance by the shortest path length on the graph. Figure 6 shows that the geographical distance and topological distance are correlated yet exhibit large variance.

Figure 7 compares how temperature and physical distance are related to the similarities between regional cuisines. The left column shows the results of temperature and the right column shows that of




Figure 6. Topological distance vs. physical distance.

physical distance. Each circle represents a pair of cuisines. The Pearson correlation coefficient between the temperature difference and PCC is -0.134 (Figure 7A), indicating a weak correlation between similarity of regional cuisines and their temperature difference. When we delete the two outliers mentioned above (YunGui and HK), the Pearson correlation coefficient between the temperature difference and PCC becomes -0.216 (Figure 7C). That is, regions with similar temperature tend to share similar usage patterns of ingredients, which is consistent with previous results [14]. However, this may not be the effect of temperature, because climate is correlated with distance. The Pearson correlation coefficient between the physical distance and PCC is -0.289 (Figure 7B), indicating a stronger correlation. When neglecting outliers, it becomes -0.385 (Figure 7D). The p-values of all cases indicate significant difference ($p \ll 0.05$ for both cases).

The previous analysis does not provide a complete picture, since geography and climate are strongly correlated; nearby regions are more likely to have similar climates. To estimate the effect of climate and geographical proximity, we calculate partial correlation [27], which is used to measure the linear association between two factors while removing the effect of other additional factors. The partial correlation coefficients between physical distance and PCC, given temperature difference as a control variable, is -0.280. However, the partial correlation between temperature difference and ingredient usage similarity, given physical distance as a control variable, the expected negative correlation completely vanishes and the correlation coefficient becomes 0.116. Our results indicate that the effect of temperature on the ingredient usage pattern may not exist at all. The results with cosine and the cases without outliers also show the same tendency.

Here we examine the relationship between topological distance and the similarity of cuisines. Figure 8 shows the similarity distribution of cuisines with respect to topological distance. Analysis of variance (ANOVA) [28] shows that the difference in the similarity distribution is significant ($p \ll 0.001$ for both cases). The figure shows a clear trend that geographically closer regional cuisines have more similar ingredient usage patterns. We perform a simple permutation significance test by classifying all regional cuisine pairs into two classes: the first class contains regional cuisine pairs with the topological distance less than or equal to 2 and the second class contains those of topological distance larger than 2. Denote the similarities of two classes as F (far, with topological distance > 2) and C (close, with topological distance ≤ 2), and \overline{F} and \overline{C} is the mean of F and C, respectively. n_F and n_C are the sample sizes corresponding to each group. The null hypothesis H_0 says the two classes F and C have identical probability distributions. We performed the test as follows. First, the difference between F and C is calculated. This is the observed value of the test statistic, namely $T_{obs} = \overline{C} - \overline{F}$. The observations of





Figure 7. The dependence of similarities between different regional cuisines on the climate and geography. (A): scatter plot of PCC and temperature difference (all regional cuisine pairs); (B): scatter plot of PCC and physical distance (all regional cuisine pairs); (C): scatter plot of PCC and temperature difference (neglecting outliers); (D): scatter plot of PCC and temperature difference (neglecting outliers);






Figure 8. Similarity distributions of regional cuisine pairs with different topological distance ($hops = 1, hops = 2, ..., hops \ge 6$). (A): result for all regional cuisines; (B): result when neglecting outliers.

classes F and C are then pooled. Next, the difference in sample means is calculated and recorded for every possible way of dividing these pooled values into two groups of size n_F and n_C , denoted by T. Lastly the one-sided p-value of the test is calculated as $p = p(T > T_{obs})$. The p-values of Fig. 8 indicate significant difference ($p \ll 0.01$ for both cases).

4 Model and Validation

We build an evolution model of Chinese cuisines based on the simple notion that geographical proximity breeds more communication and migration. Our model uses the copy-and-mutate model of recipe evolution [16]. We tested two models that use topological distance and physical distance respectively, and found that the model using topological distance produces better results. There are three elements in the model: regional cuisines, recipes, and ingredients. We assume the same set of Chinese regional cuisines in the same location. A recipe is a set of ingredients and belongs to one of the regional cuisines. We assume that each recipe has exactly the same number of ingredients (K). Each ingredient i has a fitness value f_i , randomly drawn from a uniformly distribution in [0,1]. This fitness represents intrinsic properties such as nutritional value, flavor, cost, and availability [16]. All the symbols used in our model are listed in Table 2.

Let us describe our model in detail. In the initial state there are $N_i(0) = 20$ ingredients in the ingredient pool, and each regional cuisine contains one recipe that consists of K random ingredients chosen from the initial ingredient set; that is, $N_c^*(0) = 1$.

Step 1: Choose one regional cuisine preferentially. Regional cuisine c is chosen with probability

$$p(c) = \frac{N_r^c}{N_r},\tag{5}$$

where N_r^c is the number of recipes of regional cuisine c and N_r is the total number of recipes of all regional cuisines. With probability P_L the chosen regional cuisine (c) will interact with another region (**Step 2**). With probability $1 - P_L$ cuisine c will develop a recipe itself by randomly selecting K unique ingredients from the ingredient pool.

Table 2. Notations for parameters and quantities in the model

N_i	number of all ingredients
$N_i(t)$	number of initial ingredients at time t
N_r	number of all recipes
N_r^c	number of recipes in the regional cuisine c
$N_r^c(t)$	number of initial recipes in the regional cuisine c at time t
K	number of ingredients per recipe
K'	number of ingredients to be mutated in each recipe, $K' \leq K$
P_L	probability of interaction
f_{i}	the fitness of ingredient i
$L_{i,j}$	the topological distance of regional cuisine i and j

Step 2: Generate a recipe by learning from others. With probability proportion to their topological distance, cuisine c will select another regional cuisine c'. Regional cuisine c' will be chosen with probability

$$p(c') = \frac{(1 + L_{c,c'})^{\alpha}}{\sum_{c'} (1 + L_{c,c'})^{\alpha}},$$
(6)

where $L_{c,c'}$ is the topological distance between cuisine c and c'. α is a free parameter to tune the importance of topological distance. Regional cuisines with smaller topological distance from cuisine c will have higher probability to be chosen in this step when $\alpha < 0$. Assuming cuisine c' is chosen to interact with c, then cuisine c will randomly choose one recipe (as a template) of cuisine c' as a template and copy it. From this copy, we randomly chose an ingredient i and compare it with an ingredient j that is randomly chosen from the ingredients pool, if $f_j > f_i$, we replace ingredient i by ingredient j. This process is repeated K' times. We then execute **Step 3**.

process is repeated K' times. We then execute **Step 3**. **Step 3**. Add new ingredients. With probability $\frac{N_i - N_i(t)}{N_r - N_r(t)}$ we add one new ingredient to the ingredients pool and replace the ingredient having the smallest fitness in the recipe that was generated in the previous steps with the new ingredient in order to assure all the ingredients in the ingredient pool have been used. We then add the modified new recipe to the pool of cuisine c. If no new ingredient is added in this step, then add the new recipe to the pool of cuisine c without modification. If we already have N_r recipes, stop the simulation, or else repeat the previous steps.

The parameters N_r^c and N_i are obtained from the data. For simplicity, we set K=10, which means that every recipe has ten unique ingredients. In the initial state, there are $N_i(0)=20$ ingredients in the ingredient pool, and each regional cuisine contains one recipe that choose randomly from the initial ingredients; that is, $N_r^c(0)=1$. The cuisines then evolve as new recipes and ingredients join over time. We used k'=2, $P_{learn}=0.85$, and $\alpha=-5$, which generates results that closely resemble the empirical findings. Figure 9 demonstrates that our model produces a qualitatively similar, skewed degree distribution.

Figure 10 shows the comparison between the real data and our model in terms of the similarity distribution with topological distance. Fig. 10A is the result of all regional cuisine pairs, displaying that our model can achieve the similar tendency as the real dataset, although the real dataset shows more diversity than our model. We think this is a result of the existance of outliers in the dataset. Fig. 10B shows the result without outliers, displaying a better match with our dataset. Figure 11 shows the dependency between physical distance and cuisine similarity in our model. The results display a similar tendency found in the real data (C and D in Fig. 7). Results of cosine similarity are not displayed, as all of them display similar tendencies with PCC.




Figure 9. Cumulative frequency distribution of the cuisine network generated by our model compared to the the empirical distribution from the dataset of Chinese cuisine.




Figure 10. Similarity distributions of regional cuisine pairs with different topological distance (hops = 1, hops = 2 and hops > 2). The blue ones are the results generated by our model, while the yellow ones are results of the dataset. (A): result for all regional cuisines; (B): result when neglecting outliers.




Figure 11. The dependence of similarities between different regional cuisines on the geographical distance in the model. (A): result for all regional cuisines; (B): result when neglecting outliers.

5 Conclusion and Discussion

We empirically analyzed the similarity relations between major regional cuisines in China in terms of climate and physical proximity. We find that climate (temperature) does not show any correlation with ingredient usage similarity if we control geographical distance, while geographical proximity seems to be a key factor in the shaping of regional cuisines. Based on the finding, we propose a copy-and-mutate model that incorporates geographical proximity. We show that the results of our model agree with our empirical findings.

Acknowledgments

We thanks Huawei Shen, Yu Huang, Shaojian Wang and Giovanni Luca Ciampaglia for helpful discussion and useful suggestion, and John McCurley for editorial assistance. This work is partially supported by the National Natural Science Foundation of China under Grant Nos. 11105024, 11205042 and 11105025. YXZ acknowledges the supporting from the Program of Outstanding PhD Candidate in Academic Research by UESTC (Grant No. YBXSZC20131035) and China Scholarship Council. QMZ acknowledges the supporting from the Program of Outstanding PhD Candidate in Academic Research by UESTC (Grant No. YBXSZC20131034).

References

- 1. Counihan C, Esterik PV (1997) Food and culture: a reader. Routledge, London.
- 2. Richards AI (1939) Hunger and work in a savage tribe. Routledge, London.
- 3. Firth R (1934) The sociological study of native diet. Journal of the international institute of african languages and cultures VII: 401-414.
- 4. Moyers S (1996) Garlic in health, history, and world cuisine. Suncoast Press.

- 5. Tregear A (2003) From Stilton to Vimto: Using Food History to Re-think Typical Products in Rural Development. Wiley-Blackwell.
- 6. Civitello L (2011) Cuisine and Culture: A History of Food and People. Wiley; 3th edition.
- 7. Diamond JM (1999) Guns, Germs, and Steel: The Fates of Human Societies. W. W. Norton and Company.
- 8. Mennell SJ, Murcott A, Otterloo AHv (1993) The Sociology of Food: Eating, Diet and Culture. Sage Publications; 2nd edition.
- 9. Beardsworth A, Keil T (1997) Sociology on the Menu: An Invitation to the Study of Food and Society. Routledge.
- Germov J, Williams L (2004) A Sociology of Food and Nutrition: The Social Appetite. Oxford University Press.
- 11. Allhoff F, Monroe D (2007) Food and Philosophy: Eat, Think, and Be Merry. Wiley-Blackwell; 1st edition.
- 12. Curtin DW, Heldke LM (1992) Cooking, Eating, Thinking: Transformative Philosophies of Food. Indiana University Press; 1st Edition edition.
- 13. Skubal SM (2002) Word of Mouth: Food and Fiction After Freud. Routledge.
- 14. Sherman PW, Billing J (1999) Darwinian gastronomy: Why we use spices. Bioscience 49: 453-463.
- 15. Ahn YY, Ahnert SE, Bagrow JP, Barabási AL (2011) Flavor network and the principles of food pairing. Scientific Reports 1: srep00196.
- 16. Kinouchi O, Diez-Garcia RW, Holanda AJ, Zambianchi P, Roque AC (2008) The non-equilibrium nature of culinary evolution. New Journal of Physics 10: 073020.
- 17. Ahn YY, Ahnert SE (2013) The flavor network. Leonardo 46: 272-273.
- 18. Barabási AL, Albert R (1999) Emergence of scaling in random networks. Science 286: 509-512.
- 19. Clauset A, Shalizi CR, Newman M (2009) Power-law distributions in empirical data. SIAM Review 51: 661-703.
- 20. Adamic LA (2000) Zipf, power-law, and pareto a ranking tutorial.
- 21. Lü L, Zhang ZK, Zhou T (2010) Zipf's law leads to heaps' law: Analyzing their relation in finite-size systems. PLoS ONE 5: e14139.
- 22. Salton G, McGill MJ (1986) Introduction to Modern Information Retrieval. McGraw-Hill Book Company, New York.
- 23. Rodgers JL, Nicewander AW (1988) Thirteen ways to look at the correlation coefficient. The American Statistician 42: 59-66.
- 24. Tan PN, Steinbach M, Kumar V (2005) Introduction to Data Mining. Addison-Wesley.
- 25. Jolliffe IT (2008) Principal Component Analysis. Springer, New York.
- 26. http://mathworld.wolfram.com/SphericalDistance.html. [Online; accessed 12-June-2013].
- 27. Cramér H (1999) Mathematical Methods of Statistics. Princeton University Press.
- 28. Freedman DA (2009) Statistical Models: Theory and Practice. Cambridge University Press.