Algorithms for the Constrained Perfect Phylogeny with Persistent Characters

Paola Bonizzoni¹, Anna Paola Carrieri¹, Gianluca Della Vedova¹, and Gabriella Trucco²

¹ Dipartimento di Informatica Sistemistica e Comunicazione Univ. degli Studi di Milano - Bicocca

bonizzoni,annapaola.carrieri,dellavedova@disco.unimib.it

² Dipartimento di Tecnologie dell'Informazione Univ. degli Studi di Milano, Crema

gabriella.trucco@unimi.it

Abstract. The perfect phylogeny is one of the most used models in different areas of computational biology. In this paper we consider the problem of the Persistent Perfect Phylogeny (referred as P-PP) recently introduced to extend the perfect phylogeny model allowing *persistent* characters, that is characters can be gained and lost at most once. We define a natural generalization of the P-PP problem obtained by requiring that for some pairs (character, species), neither the species nor any of its ancestors can have the character. In other words, some characters cannot be persistent for some species. This new problem is called **Constrained P-PP** (CP-PP). Based on a graph formulation of the CP-PP problem, we are able to provide a polynomial time solution for the CP-PP problem for matrices having an empty conflict-graph. In particular we show that all such matrices admit a persistent perfect phylogeny in the unconstrained case. Using this result, we develop a parameterized algorithm for solving the CP-PP problem where the parameter is the number of characters. A preliminary experimental analysis of the algorithm shows that it performs efficiently and it may analyze real haplotype data not conforming to the classical perfect phylogeny model.

1 Introduction

The perfect phylogeny is one of the most investigated and used models in several applications where a coalescent model is required for analyzing genomic data. Conceptually the model is based on the infinite sites assumption, that is no character can mutate more than once in the whole tree. While this assumption is quite restrictive, the perfect phylogeny model turned out to be splendidly coherent within the haplotyping problem [3,9], where we want to distinguish the two haplotypes present in each individual when given only genotype data. More precisely, the interest here is in computing a set of haplotypes and a perfect phylogeny such that the haplotypes (i) label the vertices of the perfect phylogeny and (ii) explain the input set of genotypes. This context has been deeply studied in the last decade, giving rise to a number of algorithms [1,5].

In the general framework, the model is used to reconstruct the evolution of species (taxa) characterized by a set of binary characters that are gained and/or lost during the evolution. Characters can take only the states 0 or 1, usually interpreted as the presence or absence of the character. Restrictions on the type of changes from zero to one and vice versa lead to a variety of specific models [6].

Still, the perfect phylogeny model and the assumptions that have been central in the previous decades cannot be employed without adaptations or improvements. In fact, this model is too restrictive to explain the biological complexity of real data, where homoplasy events (such as recurrent mutations or back mutations) are present. Thus a central goal in this model is to extend its applicability, while retaining the computational efficiency. The problem of constructing phylogenies where the deviations from perfect phylogeny are small has been tackled for example in [7] under the name of near perfect phylogeny. In particular, the near perfect phylogeny haplotyping problem has been explored in [15]. Especially the impossibility of losing a character that has been previously acquired turned out to be too restrictive, resulting in more elaborated models, such as the notion of persistent character [14] and the General Character Compatibility [11].

Following the research direction proposed in [14] to investigate the dynamics of protein interactions, the Persistent Perfect Phylogeny problem has been introduced [2] to address the computational problem of constructing a perfect phylogeny under the assumption that only a special type of back mutation may occur in the tree: a character may change state at most twice in the tree: once from 0 to 1, and (maybe) once from 1 to 0.

In the paper we consider a natural generalization of the P-PP problem, called Constrained P-PP problem (CP-PP), that is obtained by adding a constraint for some characters in the input data, given by the fact they cannot be persistent in some species. Then we explore algorithmic solutions for the CP-PP problem as well as for the restricted case of the P-PP problem.

Since our main aim is to find algorithmic solutions, following the approach in [2], we first explore a graph formulation of the CP-PP problem, called **Red-black graph reduction** based on the equivalence of P-PP to a problem of completing a matrix where each character c has two columns c^+, c^- , with c^+ (c^+) equal to 1 in a species s in the matrix corresponds to the fact that shas gained (lost) the character c. Based on the above graph formulation, we prove that there exists a class of binary matrices that always admit a positive solution for the P-PP problem, that is they admit a *persistent perfect phylogeny*. For this special case we also provide a polynomial algorithm that works for the general CP-PP problem. Based on this polynomial time algorithm we show that CP-PP is fixed parameter tractable in the number of characters and propose a branch and bound based algorithm, called **Decide-pp-opt**.

The algorithms and models discussed in the paper may have interesting applications in the construction of evolutionary trees based on the analysis of binary genetic markers, where variants of the perfect phylogeny have already been considered, such as in the study of evolution based on introns [14] or progression pathways using tumor markers or in discovering significant associations between phenotypes and single-nucleotide polymorphism markers [12] and also in haplotype analysis. In the paper we have run a preliminary experimental analysis aimed to show the applicability of our algorithm for the CP-PP model to deal with biological data (binary characters) incorporating recombination events. The results show that the algorithm performs efficiently on simulated matrices as well as on real data. The algorithm applied to haplotypes taken from the HapMap project is able to detect in binary matrices characters that may be persistent, whenever they do not obey the standard perfect phylogeny model.

Finally, we observe that the CP-PP problem (P-PP problem) is equivalent to cases of the General Character Compatibility problem (GCC) investigated in [11] whose complexity is still open. Thus our results also apply to those problems.

2 The persistent perfect phylogeny and the red-black graph reduction problem

In this section we present the persistent perfect phylogeny problem and its constrained version. We show that the CP-PP problem reduces to a graph problem, the **red-black graph reduction** problem: this result generalizes the Theorem 12 given in [2] to the constrained persistent perfect phylogeny problem.

In this paper the input is an $n \times m$ binary matrix M whose columns are associated with the set $C = \{c_1, \ldots, c_m\}$ of characters and whose rows are associated with the set $S = \{s_1, \ldots, s_n\}$ of species. Then M[i, j] = 1 if and only if the species s_i has character c_j , otherwise M[i, j] = 0. The gain of a character c in a phylogenetic tree is represented by an edge labeled by the character c^+ . In order to model the presence of persistent characters, the loss of a character c in the tree is represented by an edge that is labeled by the negated character, labeled by c^- . Formally, we define the persistent perfect phylogeny model as follows [2, 16].

Definition 1 (Persistent Perfect Phylogeny). Let M be an $n \times m$ binary matrix. Then a persistent perfect phylogeny, in short p-pp, for M is a rooted tree T such that:

1. each node x of T is labeled by a vector l_x of length m;

- 2. the root of T is labeled by a vector of all zeroes, while for each node x of T the value $l_x[j] \in \{0,1\}$ represents the state of character c_j in tree T;
- 3. each edge e = (v, w) is labeled by at least a character;
- 4. for each character c_j there are at most two edges e = (x, y) and e' = (u, v) such that $l_x[j] \neq l_y[j]$ and $l_u[j] \neq l_v[j]$ (representing a change in the state of c_j). In that case e, e' occur along the same path from the root of T to a leaf of T; if e is closer to the root than e', then $l_x[j] = l_v[j] = 0$, $l_y[j] = l_u[j] = 1$, and the edge e is labeled c_j^+ , while e' is labeled c_j^- ;
- 5. each row r of M labels exactly one node x of T. Moreover the vector l_x is equal to the row r.

Let us state the main problems investigated in the paper.

The **Persistent Perfect Phylogeny problem (P-PP):** Given a binary matrix M, returns a p-pp tree for M if such a tree exists.

A natural generalization of the P-PP problem is obtained by considering as input data a pair (M, E^*) , called *constrained matrix* where M is a matrix over binary alphabet and $E^* = \{(i_1, j_1), \dots, (i_k, j_k)\}$ is a set of 0-entries of M. Now a p-pp tree T for matrix M is consistent with E^* if and only if $(i, j) \in E^*$ means that character c_j is absent in species s_i and cannot be gained and then lost in the species s_i in tree T, that is c_i is not persistent in species s_i .

The Constrained Persistent Perfect Phylogeny problem (P-PP): Given a constrained matrix (M, E^*) , returns a p-pp tree T for M if such a tree exists, such that tree T is consistent with E^* .

Another fundamental observation is that we can restate the CP-PP problem as variant of the Incomplete Directed Perfect Phylogeny [13].

Definition 2 (Extended Matrix). Let (M, E^*) be an instance of the CP-PP problem. The extended matrix associated with M is an $n \times 2m$ matrix M_e over alphabet $\{0, 1, ?\}$ which is obtained by replacing each column c of M by a pair of columns (c^+, c^-) . Moreover for each row s of M if M[s, c] = 1, then $M_e[s, c^+] = 1$ and $M_e[s, c^-] = 0$, while if M[s, c] = 0 and $(s, c) \notin E^*$, then $M_e[s, c^+] = ?$ and $M_e[s, c^-] = ?$, otherwise $M_e[s, c^+] = 0$ and $M_e[s, c^-] = 0$.

In this case the characters (c^+, c^-) are called conjugate. Informally, the assignment of the *conjugate* pair (?, ?) in a species row s for two conjugate characters (c^+, c^-) means that character c could be persistent in species s, i.e., it is first gained and then lost. On the contrary, the pair (1, 0) means that character c is only gained by the species s. Finally, the pair (0, 0) means that character c is never gained by the species s. A *completion* of a pair (?, ?) associated to a species s and characters (c^+, c^-) of M_e consists of forcing $M_e[c^+, s] = M_e[c^-, s] = 0$ or $M_e[c^+, s] = M_e[c^-, s] = 1$.

A (partial) completion M_e is a completion of some of its conjugate pairs. A fundamental result states that M admits a persistent phylogeny if and only if there exists a completion of M_e admitting a directed perfect phylogeny [2]. Now, the same result holds when the input is a constrained matrix (M, E^*) . In fact, if (M, E^*) admits a solution, it means that it is possible to build a p-pp tree Twhere each (i, j) in E^* implies that c_j is not persistent in species s_i of tree T. As a consequence of this fact, there exists a completion of M_e where $M_e[c_j^+, s_i] = M_e[c_j^-, s_i] = 0$. Moreover, by interpreting a conjugate pair of characters as characters of M_e is immediate to verify that tree Tis a directed perfect phylogeny for M_e . Vice versa, given an extended matrix M_e that admits a perfect phylogeny T, then it is possible to show that T is a persistent phylogeny for M. This fact is an immediate consequence of definition 2 and the result in [2].

2.1 The conflict graph and red-black graph reduction

Let M be a binary matrix. Given two characters c_1 and c_2 , the configurations induced by the pair (c_1, c_2) in matrix M is the set of ordered pairs $(M[s, c_1], M[s, c_2])$ over all species S. Two characters c_1 and c_2 of M are *conflicting* if and only if the configurations induced by such pair of columns is the set of all possible pairs (0, 1), (1, 1), (1, 0) and (0, 0). Notice that being in conflict is a symmetric relation, therefore we can define the *conflict graph* $G_c = (C, E_c \subseteq C \times C)$ of a matrix M, where a pair $(c_i, c_j) \in E_c$ if and only if c_1 and c_2 are conflicting in M. Notice that a conflict graph with no edges (called *empty*) does not necessarily imply the existence of a rooted perfect phylogeny, because of the occurrence of the forbidden matrix with only the three configurations (1,1), (1,0) and (1,0). However, by allowing a character to be persistent, the matrix admits a rooted persistent perfect phylogeny. We also need some graph-theoretic definitions. A graph is called *edgeless* if it has no edges. A connected component is called *nontrivial* if it has more than one vertex.

	c_1	c_2	c_3	c_4	c_5	C1 C3
s_1	0	0	0	1	0	
s_2	0	0	1	1	1	
s_3	0	1	1	0	0	
s_4	1	1	0	0	0	
s_5	1	1	1	0	1	C5 C2

Fig. 1. A matrix and its conflict graph

The first step is to simplify, if possible, the instance. In fact we can always remove duplicate rows or columns. Moreover a character c is called *universal* if all species have c, while c is called *void* if no species has c. Again, we can always start by removing void characters. In the rest of the paper, by an extended matrix M_e we mean a matrix that may be partially or fully completed. Besides the conflict graph, we introduce a second graph, called *red-black graph* and denoted by G_{RB} , which will be fundamental in our algorithm.

Definition 3 (Red-black graph). Let M_e be an extended matrix. Then the red-black graph $G_{RB} = \langle V, E \rangle$ associated to M_e is the edge-colored graph where (i) the vertices are the species and the conjugate pairs of M_e (that is for each two conjugate characters c^+ and c^- , only c is a vertex of G_{RB}), (ii) a pair (s, c) is a black edge iff the conjugate pairs c^+ and c^- are still incomplete in matrix M_e and $M_e[s, c^+] = 1$ and $M_e[s, c^-] = 0$, (iii) (s, c) is a red edge iff $M_e[s, c^+] = M_e[s, c^-] = 1$.

2.2 Realizing characters in a red-black graph

In the following we describe some completions of conjugate pairs of an extended matrix M_e that can be expressed as graph operations over the red-black graph G_{RB} associated to the extended matrix. Let (c^+, c^-) be two conjugate characters of M_e , and let C(c) be the connected component of G_{RB} containing the vertex c. Given a partially completed matrix or, equivalently, a red-black graph, a character is in one of three possible states: inactive (the initial state of all characters), active, and free. The *realization* of a character c in G_{RB} consists of the following steps:

- 1. if c is inactive and for all species $s \in \mathcal{C}(c)$, $M_e[s, c^+] = M_e[s, c^-] \neq 0$ then:
 - (a) for each species $s \notin C(c)$, pose $M_e[s, c^+] = M_e[s, c^-] = 0$;
 - (b) for each species $s \in C(c)$ if (c, s) is not an edge of G_{RB} , add a red edge (c, s) and complete M_e by posing $M_e[s, c^+] = M_e[s, c^-] = 1$;
 - (c) remove from G_{RB} all black edges (c, s) and label c active.
- 2. else if c is active and c is connected by red edges to all species in $\mathcal{C}(c)$, then:
 - (a) all such red edges are deleted from G_{RB} and c is labeled *free*;

In some cases (c is free, or c is active but there exists a species $s \in C(c)$ that is not connected to c by a red edge, or c is inactive but persistent for a species $s \in C(c)$, i.e. $M_e[s, c^+] = M_e[s, c^-] = 0$) none of the stated conditions hold, therefore the realization is *impossible*. Notice that realizing a character corresponds to a partial completion of the matrix M_e that is called the *canonical completion* of c in M_e , which in turn corresponds to the construction of a standard tree, as follows. **Definition 4 (Standard tree).** Let M_e be an extended matrix, then a standard *p*-pp [2] solving M_e has the following additional properties:

- 1. some edge e = (v, w) may not labeled by any character. In this case $l_v = l_w$;
- 2. no internal node has more than one child that is a leaf;
- 3. each leaf is incident on an unlabeled edge;
- 4. each species labels a leaf x of T and the parent of x in T;
- 5. each internal node x is labeled with the set S(x) of species and with the set C(x) of characters appearing in the subtree T(x) of T rooted at x;
- 6. some nodes x are also labeled by a red-black graph $G_{RB}(x)$ defined as follows. The graph associated to the root r is the red-black graph associated to the extended matrix M_e and where all vertices are inactive. Each other node x might be labeled by the connected components of the red-black graph having species and characters of tree T(x) and obtained from graph $G_{RB}(r)$ realizing in sequence all characters (active or inactive) labeling the edges on the path from r to x in T.
- 7. Each internal node x is labeled with the conflict graph $G_c(x)$ computed on the submatrix of M_e induced by the columns and rows in C(x) and S(x).
- 8. Each subtree rooted at a node y of T whose parent x is labeled by the red-black graph $G_{RB}(x)$ has species S(y) and characters C(y) such that $S(y) \cup C(y)$ is a union of connected components of $G_{RB}(x)$.
- 9. Let x be a node such that the red-black graph $G_{RB}(x)$ has connected components C_1, \ldots, C_k with k > 1 (i.e., G_{RB} is disconnected). Then x has k children x_1, \ldots, x_k , where $S(x_i) \cup C(x_i) = C_i$ and each edge (x, x_i) are not labeled by any character.

It is easy to show that given a generic p-pp tree solving a matrix M_e , we can modify it to satisfy the properties from 1 to 7 of a standard tree. In fact, these properties are obtained by adding a labeling of nodes and leaves of the tree (see 4-5-6-7) or are obtained by assuming that there are not any identical rows (see 2) or by adding additional edges (see 3). Consequently, when proving that a p-pp tree is standard, we need to prove that properties 8-9 hold under the assumption that the tree is in the form specified by properties 1-7.



Fig. 2. Figures (a) and (b) illustrates the realization of a character in a red-black graph associated to an extended matrix. The canonical completion of the extended matrix after the graph operations is shown for the characters c_4 (a) and c_3 (b).

The following property of a standard tree is central in characterizing matrices M_e that do not have a solution.

Property 5. Let T be a standard tree for an extended matrix M_e and let x be a node of T. Then the red-black graph $G_{RB}(x)$ that labels x does not contain an induced simple path starting from a species vertex and consisting of four red edges (such an induced graph is called red Σ -graph). Since a red-black graph G_{RB} implicitly induces a submatrix M_1 of M whose rows and columns are the species and characters of G_{RB} , we can define the the conflict graph induced by G_{RB} as the conflict graph on such submatrix M_1 . Observe that for every descendant x_i of node x, then by Definition 4 of standard tree, there will be a connected component of $G_{RB}(x)$ whose species are exactly those of $T(x_i)$. Moreover, given an internal node x of a tree T, the *label sequence* of x is the sequence of characters of the edges on the unique path from the root of T to x. Then we associate to x the matrix $M_e(x)$ that is the partially completion of M_e according to the label sequence of x where only the rows and columns corresponding to vertices of $G_{RB}(x)$ are retained.

Property 6. Let $G_{RB}(x)$ be the red-black graph associated to a node x, let c be any character of $G_{RB}(x)$, let e^+ be the edge of T labeled by c^+ and let e^- be the edge of T labeled by c^- (if it exists). By construction of the red-black graph, only three cases are possible:

- 1. c is inactive, all edges of $G_{RB}(x)$ that are incident on c are black, and c^+ does not belong to the label sequence of x;
- 2. c is active, all edges of $G_{RB}(x)$ that are incident on c are red, moreover c^+ belongs to the label sequence of x, but c^- does not;
- 3. c is free, c is an isolated vertex of $G_{RB}(x)$.

Using the stated properties we can prove the characterization stated in Theorem 12 used to test the existence of a solution of the CD-PP problem. We discover that the Theorem builds upon an analogous characterization for the P-PP problem [2], stating that an extended matrix M_e has a perfect phylogeny (i.e., a pp tree) if and only if it has a standard tree. Moreover a standard tree represents a canonical completion of all characters of the matrix, i.e. the realization of a sequence of all characters, called *c-reduction* that leads to an edgeless red-black graph (see Definition 9 given below).

Lemma 7. Let M_e be an extended matrix admitting a perfect phylogeny. Then there exists a perfect phylogeny T realizing M_e such that for each node x of T and for each character c_1 , if c_1 is adjacent to two species s_1 , s_2 in $G_{RB}(x)$, then s_1 , s_2 are either both in T(x) or none of them is in T(x), where $G_{RB}(x)$ is the red-black graph obtained by realizing the label sequence of x from the red-black graph associated to M_e .

Now Lemma 7 is used to prove the following lemma, first proved in [2], showing that when an extended matrix admits a solution, than it must have a standard tree. Moreover its proof establishes a correspondence between a standard tree and the red-black graphs associated to nodes. More precisely, given a standard tree T, such a tree represents the canonical completion of M_e that we obtain by visiting tree T and realizing characters of visited edges of tree T in the red-black graph for M_e . Then, when reaching a node x of T by visiting tree T, the red-back graph $G_{RB}(x)$ represents the species and characters that still have to be completed in the extended matrix.

Lemma 8. Let M_e be an extended matrix admitting a p-pp tree. Then, there exists a completion of M_e that is realized by a standard tree T.

Consider an extended matrix M_e that has been completed and M_e admits a standard tree T. Let us consider the sequence of character corresponding to a depth-first visit of T and the corresponding red-black graph G_{RB}^* obtained from G_{RB} by realizing all characters in the visit. First of all, notice that G_{RB}^* cannot contain any black edges, for otherwise we would immediately contradict the hypothesis that T solves M_e . Moreover we can prove that G_{RB}^* cannot contain any red edge (c, s). Assume to the contrary that such an edge exists. Since T solves M_e , the path of T from the root to the leaf labeled by c^- . By point 9 of Definition 4, the red-black graph $G_{RB}(y)$ is connected, therefore all red edges connecting c and a leaf of T(y) are deleted. Since s is a leaf of T(y), the red edge (c, s) is deleted.

Definition 9. Let G_{RB} be a red-black graph for an extended matrix M_e and let R be a sequence of characters such that each negative character c^- appears after the corresponding positive character c^+ , and all characters of G_{RB} appear in R. Then R is a successful c-reduction of G_{RB} if and only if all single character realization of R are possible and the graph reduced by R has no edge. Then we say that M_e is solvable.

Lemma 10. Let T be a standard tree that solves a matrix M and let V be the sequence of characters labeling the edges of T according to a depth-first visit. Then V is a successful c-reduction of M_e .

By Lemma 10 a standard tree is represented by a canonical completion of all characters, i.e. a c-reduction that leads to an edgeless red-black graph. Now we can show that having such a edgeless red-black graph is not only a necessary but a sufficient condition for having a canonical completion admitting a tree.

We have shown that an extended matrix admits a persistent phylogeny if and only if it has a directed perfect phylogeny. Since the matrices admitting a perfect phylogeny are those that do not contain a forbidden submatrix [8], we know that an extended matrix admits a persistent phylogeny if and only if there exists a completion such that no forbidden matrix induced by two negated characters, two positive characters, or one of each kind, is induced by the completion. Let us show that having an edgeless red-black graph due to a successful reduction implies that the associated canonical completion M' of M_e has no forbidden matrix. First, observe that no forbidden matrix between two positive characters in M' is possible, since completing or realizing two characters c_1^+ and c_2^+ that are in the same connected component of the red-black implies a containment relation between the two characters (note that two characters in disjoint components of the red-black graph cannot be connected during the successful c-reduction). Finally, observe that the only way to have red-edges in a reduced graph is with a path of length four in the graph, i.e., the red Σ -graph, corresponding to the forbidden matrix induced by negative characters. Notice that if a red-black graph has only red edges and a red Σ -graph is forbidden, then the graph must be edgeless.

Theorem 11. Let M be a binary matrix and let M_e be the extended matrix associated with M such that its associated red-black graph admits a successful c-reduction. Then M_e is solvable by a standard tree.

Lemmas 11 and 10 allow to generalize the Theorem initially proved in [2] for the P-PP problem.

Theorem 12. Let M_e be an instance of the CP-PP problem. Then M_e is solvable if and only if there exists a successful c-reduction for the red-black graph G_{RB} associated to M_e .

Therefore we only need to find a successful c-reduction; if none exists, then the initial instance has no solution. Finally, observe that the property 8 and 9 of a standard tree imply that we need to find a successful c-reduction for each connected component of the red-black graph, and any concatenation of those successful c-reductions on a single component gives a successful c-reduction for the whole graph.

3 Solving the CP-PP problem in polynomial time on matrices with empty conflict graphs

In the following, by using properties of the red-black graph, we show that a persistent perfect phylogeny always exists for a matrix M that has an empty conflict graph. The main characterization given by Theorem 12 is used to solve the CP-PP problem, since we design a procedure that finds a successful *c*-reduction of the red-black graph associated to the extended matrix for M.

Given M a binary matrix, the *partial order graph* for M is the partial order P obtained by ordering columns of M under the < relation which is defined as follows: character c < c' if and only if $M[s,c] \leq M[s,c']$ for each species s, otherwise we say that c and c' are not comparable. Moreover, we build a graph G = (V, E), called *adjacency graph* for M: V is the set of columns of

M and (u, v) is an edge of G if and only if u, v are *adjacent*, i.e. there is a species s that is adjacent to both u and v in the red-black graph for the extended matrix M_e associated with M. Then the following result holds.

Lemma 13. Let M be a binary matrix with an empty conflict graph. Assume that the extended matrix associated with M induces a connected red-black graph and let P be the partial order graph for M. Let C_M be the set of maximal elements in P. Then C_M consists of elements that are pairwise adjacent in the adjacency graph.

Lemma 14. Let M be a binary matrix that has an empty conflict graph. Let G_{RB} be the red-black graph for the extended matrix associated with M. The realization of two characters a and b that are adjacent in the adjacency graph for M produces at most two red disjoint components, one with only vertex a and the other with only vertex b.

The above Lemma 14 combined with Lemma 13 implies that maximal characters can be realized in an arbitrary order and are crucial to prove the following Theorem.

Theorem 15. Let M be a binary matrix that has an empty conflict graph. Then M admits a persistent perfect phylogeny T and there exists a polynomial time algorithm to compute T.

If we consider a constrained matrix (M, E^*) where $E^* \neq \emptyset$ and having an empty conflict graph, the CP-PP problem might not have a solution for (M, E^*) since some characters cannot be realized. In fact, if all characters are not persistent, we obtain the classical perfect phylogeny problem, and even this problem might not have a solution when the conflict graph is empty, since the matrix (M, E^*) could contain the forbidden matrix. However, Lemmas 13, 14 and Theorem 12 allow to prove the correctness of the following procedure that can be used to solve the CP-PP in polynomial time in the case of empty conflict graph. In fact, the two Lemmas hold also for constrained matrices (M, E^*) (see proof in the Appendix).

Procedure Solve-CP-PP-empty-conflict (M, E^*)

Input: a constrained binary matrix (M, E^*) that has an empty conflict graph. Output: a realization S_c of characters to successfully reduce graph G_{RB} .

- Build the partial order P for M; let G_{RB} be the red-black graph for the extended matrix for M.
- let C_M be the set of all maximal elements in P that are in the same connected component of the red-black graph G_{RB} ; then realize in an arbitrary order those characters in C_M that can be realized. Repeat the step till all characters have been realized. Otherwise, return no solution.

Now, the correctness of the algorithm for the CP-PP problem is again a consequence of the fact that maximal characters can be realized in an arbitrary order and the fact that maximal characters are realized before characters they include by the <-relation. This fact relies on the observation that if c < c' and c' is not persistent in a species s, then also c is not persistent in the same species. In fact, if c' occurs in the p-pp tree after c then, assuming that c is persistent in a species s, also cmust be persistent in the same species, since c' occurs before the negated character c^- . Otherwise, if c' occurs in the tree before c, then all species below c^+ and the negated character c^- are also in c', thus forbidding to have c persistent in the same species of c. The correctness of the algorithm is proved in the Appendix.

4 An optimized algorithm

In this section we propose an algorithm for the CP-PP problem called **Decide-pp-opt** that is based on the procedure **Solve-CP-PP-empty-conflict**(M). Just as the algorithm in [2], **Decidepp-opt** reduces an instance M of P-PPH to an instance M_e of the IP-PPH problem. In fact,we know that M_e admits a pph tree T if and only if T is a solution of matrix M. Then, by Theorem 12, M_e admits a pph tree T if and only if there exists a successful c-reduction of the red-black graph for M_e . The algorithm in [2] explores all permutations of the set C of characters of M_e in order to find one that is a successful c-reduction, if it exists. On the other hand, **Decide-pp-opt** builds a decision tree, where each edge represents a character and each path of the tree from the root to a leaf is a permutation $\Pi(C')$ of a subset C' of the set C of characters such that the realization of $\Pi(C')$ makes the conflict-graph induced by the red-black graph empty. Thus **Decide-pp-opt** strongly relies on the polynomial time solution of the P-PP problem in the case the conflict-graph is empty. The algorithm works in a branch and bound like manner, in the sense that if a branch of the decision tree ending in node x does not lead to a solution, then the decision tree below x is discarded. More precisely, each branch ending in node x gives a partial permutation π that consists of all characters labeling the path from root r to node x. A partial completion M_{π} is computed by realizing characters provided by the partial permutation π . Whenever M_{π} contains the forbidden matrix, then the branch ending in x does not lead to a solution, and x is labeled as a *fail* node. The algorithm either finds the first permutation of characters that provides a successful c-reduction of the red-black graph for the extended matrix, if it exists, or will decide that the matrix does not admit a pph tree by visiting the whole decision tree.

Let us describe the recursive procedure **Decide-pp-opt** which is initial invoked as **Decide-pp-opt** $(M, Me, r, \{r\})$, where r is the root of the decision tree and the visited tree is the set $\{r\}$.

Algorithm Decide-pp-opt (M, M', x, \mathcal{T})

Input: a binary constrained matrix (M, E^*) of size $n \times m$, the set E^* of constraints, a partial depth-first visit tree \mathcal{T}' of the decision tree \mathcal{T} and a leaf node x of \mathcal{T} , a partial completion M' of the extend matrix M_e obtained by the realization of the characters labeling a path π from r to node x of the tree \mathcal{T}' ;

Output: the tree \mathcal{T}' extended with the depth-first visit of \mathcal{T} from node x. The procedure eventually outputs a successful c-reduction r or fails to find such a successful c-reduction.

- Step 1: if the edge incident to node x is labeled c and c is admissible, then realize c in G_{RB} and complete the pair of columns (c, c') in M'. If the matrix M' has a forbidden matrix, then label x as a fail node. If x is a leaf node, then mark x as a successful node and output the permutation labeling the path from the root r of tree T and the leaf x of \mathcal{T}' .
- Step 2: compute the conflict graph G_c for the matrix M, updated after the realization of the characters along the path π from the root r to node x (i.e. M is obtained after eliminating the rows that correspond to species-nodes that are singletons in G_{RB}),
- Step 3: if the conflict graph G_c is empty, then apply the polynomial-time algorithm for an empty conflict graph and return a successful c-reduction, if it exists. Else for each node x_i that is a child of node x in tree \mathcal{T}' and is labeled by a non-active character in G_{RB} , apply **Decide-pp**-opt $(M, M', x_i, \mathcal{T}' \cup \{x_i\})$.

Notice that testing whether a character may be realized in a connected component of the red-black graph G_{RB} requires time that is linear in the number of species of the component. Clearly, the algorithm requires to compute the connected components of G_{RB} , which can be done in time O(f(n,m)), where f(n,m) is polynomial in the size of graph G_{RB} . Consequently, the time required to evaluate a single path of the tree is O(f(n,m)m), since the path may have m characters to be realized and completed. The total number of explored paths is clearly equal to the number of permutations of set C of characters on the input matrix, in the worst case.

5 Experimental analysis

We have implemented the algorithm **Decide-pp-opt** and tested it over simulated data produced by the tool *ms* by Hudson [10] and on real data coming from the International HapMap project, a multi-country research to identify and catalog genetic similarities and differences in human beings [4]. The main goal of these preliminary experiments has been to test the average running time when the number of rows and columns increase, since we wanted to test the applicability of the method on matrices of given sizes. The experimental analysis on real haplotype data aims to investigate the use of the persistent model to detect haplotypes data that cannot be explained by the perfect phylogeny model but can exhibit persistent characters.

We have implemented the algorithm in C++ and the experiments have been run on a standard Windows workstation with 4 GB of main memory.

The results of a first experiment are reported in Table 1. The table reports the computation time to solve sets of 50 matrices for each dimension 50×15 —i.e., 50 species and 15 characters— 100×15 , 200×15 , and 500×15 with a recombination rate 1/15. The sets contain only matrices that are solved within five minutes. Clearly, the number of unsolved matrices increases with the size of the input matrices but also with the number of conflicts that are present in the conflict graph. The table also reports the results obtained by comparing the execution times of the exact algorithm given in [2] (**Decide-pp**) with the optimized algorithm on sets of matrices with a fixed number of columns and different numbers of rows. Since **Decide-pp**works on unconstrained matrices, we have not introduced any constraints in the input matrices. The **Decide-pp-opt** algorithm is able to find a solution for all matrices in contrast to the **Decide-pp** algorithm that in some cases takes more than 10 minutes to find a solution for a single matrix.

The average execution time to solve 10 matrices with a single conflict is of 0.031s, 0.047s, 0.093s for matrices of size 100x15, 200x15, 500x15 respectively.

In order to test the performance of the algorithm for large matrices in terms of number of species we have processed a set of 20 matrices, 10 of size 1000×30 and 10 of size 1000×40 , with conflict graphs having a number of conflicts (edges) between 40 and 236. We fixed a maximum time (900 seconds), after which the execution is stopped. In all cases the simulation terminates without finding a solution, i.e. all matrices do not admit a p-pp tree. Therefore those instances are likely to be the worst cases for our algorithm, since the entire search tree is explored. Considering the set of matrices of size 1000×30 , in 40% of tested cases the simulation halts before the timeout. In particular, in 10% of cases we obtain a result in a time between 10 and 15 minutes, and in 50% of cases the result is given in less than 3 minutes. Considering the set of matrices of size 1000×40 , in 50% of tested cases the execution is stopped because the timeout is reached. In the remaining 50% the result is given in a time between 3 and 6 minutes, with an average time of 216 seconds.

nxm	number	total	average	solved	matrices	total t	ime in s	average time in s	
	P-PPH	conflicts	conflicts	Decide-pp [2]	Decide-pp-opt	Decide-pp [2]	Decide-pp-opt	Decide-pp [2]	Decide-pp-opt
50x15	6	236	4.72	47	50	89.12	32.32	1.90	0.65
100x15	4	175	3.5	48	50	436.02	194.63	9.08	3.89
200x15	3	147	2.94	48	50	1583.50	43.21	32.99	0.86
500x15	7	219	4.38	44	50	888.59	889.43	20.20	17.79

Table 1. The table has entries to specify the average time to solve a single matrix (in seconds shortened as s), the number of matrices that do not admit a p-pp tree, the total number of conflicts, measured as the number of edges in the conflict graph of the matrices of each set, and the average number of conflicts. Each considered matrix has a conflict graph that consists of a single non trivial component.

Finally, the algorithm has been tested on real data coming from the International HapMap project. The data are classified by type of population. In our case, we used data from the set ASW (African ancestry in Southwest USA). Each individual is described by the two haplotypes (in our application the two haplotypes correspond to two different species, i.e. two different rows of the matrix). The data set consists of binary matrices of dimensions 10×10 , 26×15 , 26×25 , and 26×30 . For each group we considered 10 matrices. In all cases the matrices do not admit perfect phylogeny, and the number of conflicts changes from a minimum of 4 to a maximum of 138. Increasing the size of the matrix, and therefore the number of conflicts, the percentage of matrices that admit persistent perfect phylogeny decreases. More in detail, 80% of the tested matrices of size 10×10 admits solution, only 20% of the tested matrices of size 26×15 admits solution, and none of the sets 26×25 , and 26×30 admits solution. The results confirm the conjecture that haplotype data may be related by the persistent phylogeny in case they cannot be explained by the perfect model. Moreover, the results on simulated and real data show the good performance in terms of

time for matrices of a certain size even in the case that no solution is given, i.e. the searching space increases. This behavior is due to the fact that the algorithm includes a test to bound a path whenever the path does not lead to a solution, since we test whether a partial completion includes the forbidden matrix.

A final experiment an interesting case where we have matrices of size 30 x 60 with 4 or 5 conflicts (hence those matrices do not admit a perfect phylogeny). On those matrices **Decide-pp** have always reached the 15-minute timeout without computing a solution. On the other hand, imposing that a few (less than 10) characters cannot be persistent allows **Decide-pp-opt** to find a solution in a few seconds. This experiment shows that introducing some constraints can help in finding a solution, hence a feasible strategy to determine if a matrix has a persistent phylogeny is to introduce some random constraints. We are currently planning an extension of **Decide-pp-opt** that introduce some deterministic constraints, based on an analysis of the initial conflict graph, to speed up the computation.

6 Conclusions and open problems

In this paper we have investigated the CP-PP problem, which is the general problem of computing a persistent perfect phylogeny for binary matrices where some characters may be forced not to be persistent. The case where all characters may be persistent is called P-PP problem. The computational complexity of this problem is still open, except when the output is a specific tree, that is, a branch or a path. In order to find algorithmic solutions of the CP-PP problem we proved that, similarly to the P-PP problem [2], CP-PP can be reduced to a problem, called *Red-black* graph reduction problem, of emptying a graph with a sequence of operations on characters. This formulation of the problem allows us to find a polynomial time solution for matrices whose conflict graph is empty. Based on this result we propose a fixed parameter algorithm (the parameter is the number of characters) that uses a branch-and-bound technique to reduce the computation time.

An experimental analysis over simulated matrices and on binary matrices representing real haplotypes shows that the algorithm is able to process the majority of matrices with 40 characters, 1000 species, and no solution in a few minutes (clearly, for all those cases the algorithm determines that no solution exists—those instances are usually the hardest for our approach), while being very fast on matrices with 1000 species and 15–20 characters that admit a solution.

Finally, we observe that the CP-PP problem (P-PP problem) is equivalent to cases of the General Character Compatibility problem (GCC) investigated in [11], when states are over set $\{0, 1, 2\}$ and when, for each generalized character $\hat{\alpha}$, $\alpha(s) \in \{\{1\}, \{0\}, \{0, 2\}\}$ (respectively, $\alpha(s) \in \{\{1\}, \{0, 2\}\}$ for the P-PP case) for each species s and $T_{\alpha} = 0 \rightarrow 1 \rightarrow 2$. It is interesting to note that the computational complexity of the cases of the GCC problem that are equivalent to P-PP and CP-PP, i.e. cases 5 and 6 of Table 1 in [11], is still open, while only partial results are obtained when the solution is constrained to be a branch or a path (see the Appendix). Thus the results we give in the paper also apply to those cases.

6.1 Acknowledgements

The authors would like to thank Rob Gysel for pointing out the connection of the persistent perfect phylogeny with the GCC problem. Anna Paola Carrieri also thanks Dan Gusfield for useful discussions on the problem.

References

- 1. P. Bonizzoni. A linear time algorithm for the Perfect Phylogeny Haplotype problem. *Algorithmica*, 48(3):267–285, 2007.
- P. Bonizzoni, C. Braghin, R. Dondi, and G. Trucco. The binary perfect phylogeny with persistent characters. *Theor. Comput. Sci.*, 454:51–63, 2012.

- 3. P. Bonizzoni, G. Della Vedova, R. Dondi, and J. Li. The haplotyping problem: a view of computational models and solutions. *International Journal of Computer and Science Technology*, 18:675–688, 2003.
- The International Human Consortium. A second generation human haplotype map of over 3.1 million SNPs. Nature, 449(7164):851–861, Oct. 2007.
- 5. Z. Ding, V. Filkov, and D. Gusfield. A linear time algorithm for Perfect Phylogeny Haplotyping (pph) problem. *Journal of Computational Biology*, 13(2):522–553, 2006.
- 6. J. Felsenstein. Inferring Phylogenies. Sinauer Associates, 2004.
- D. Fernández-Baca and J. Lagergren. A polynomial-time algorithm for near-perfect phylogeny. SIAM J. Comput., 32(5):1115–1127, 2003.
- D. Gusfield. Algorithms on Strings, Trees and Sequences: Computer Science and Computational Biology. Cambridge University Press, Cambridge, 1997.
- D. Gusfield. Haplotyping as perfect phylogeny: Conceptual framework and efficient solutions. In Proc. 6th Annual Conference on Research in Computational Molecular Biology (RECOMB 2002), pages 166–175, 2002.
- R. R. Hudson. Generating samples under a wright-fisher neutral model of 31 genetic variation. Bioinformatics, 18(2):337–338, 2002.
- 11. J. Manuch, M. Patterson, and A. Gupta. Towards a characterisation of the generalised cladistic character compatibility problem for non-branching character trees. In *ISBRA*, pages 440–451, 2011.
- F. Pan, L. McMillan, F. P.-M. de Villena, D. Threadgill, and W. Wang. Treeqa: Quantitative genome wide association mapping using local perfect phylogeny trees. In *Pacific Symposium on Biocomputing*, pages 415–426, 2009.
- I. Peer, T. Pupko, R. Shamir, and R. Sharan. Incomplete directed perfect phylogeny. Siam Journal on Computing, 33(3):590–607, 2004.
- 14. T. Przytycka, G. Davis, N. Song, and D. Durand. Graph theoretical insights into dollo parsimony and evolution of multidomain proteins. *Journal of Computational Biology*, 13(2):351—363, 2006.
- 15. R. V. Satya, A. Mukherjee, G. Alexe, L. Parida, and G. Bhanot. Constructing near-perfect phylogenies with multiple homoplasy events. In *ISMB (Supplement of Bioinformatics)*, pages 514–522, 2006.
- J. Zheng, I. B. Rogozin, E. V. Koonin, and T. M. Przytycka. Support for the Coelomata Clade of Animals from a Rigorous Analysis of the Pattern of Intron Conservation. *Mol. Biol. Evol.*, 24(11):2583– 2592, 2007.

Appendix

Proof of Lemma 7

Proof. Assume to the contrary that no such tree exists. More precisely, we will consider, among all realizations of M_e , a tree T with an edge e = (u, x) that is closest to the root among all edges contradicting the lemma, that is $s_1 \in T(x)$, $s_2 \notin T(x)$. Clearly e is labeled by c^+ or c^- . Let y be the least common ancestor of s_1 and s_2 . Since $s_2 \notin T(x)$, y must be an ancestor of x.

By cases (1) and (2) of Prop. 6, since c_1 has incident edges from s_1 and s_2 in $G_{RB}(x)$, both edges (c_1, s_1) , (c_1, s_2) are black or red. Assume they are both black in graph $G_{RB}(x)$: thus they must be black also in graph $G_{RB}(y)$. For this reason, note that c_1 is adjacent to s_1 and s_2 also in graph $G_{RB}(y)$ as they are adjacent after the the realization of the characters in the label sequence of x.

Since both s_1 and s_2 have the character c_1 , the edge e_1 of T labeled by c_1 must lie on the common portion of the paths from the root to both s_1 and s_2 that is e_1 lies on the path from the root to node y (as y is the the least common ancestor of s_1 and s_2). Therefore both edges (c_1, s_1) , (c_1, s_2) are red in graph $G_{RB}(y)$ (by definition of graph associated to a node), contradicting the previous assumption. Thus assume that (c_1, s_1) , (c_1, s_2) are red in $G_{RB}(x)$.

By case 2 of Prop. 6, x precedes the edge $e_1 = (v, z)$ that is labeled by c_1^- , as c_1^+ belongs to the label sequence of x, but c_1^- does not. Two cases are possible. If c_1^+ belongs to the label sequence for y, since both s_1 and s_2 do not have character c_1 but are descendant of y, they must also be two descendants of z and a fortiori of x, a contradiction of the initial assumption. Thus, assume that c_1^+ does not belong to the label sequence of y.

Thus there exists an edge (u', v') labeled c_1^+ that occurs along the path from node y to u. In the graph $G_{RB}(v')$, c_1 is connected to s_1 and s_2 with red edges, for otherwise the same property would not hold for $G_{RB}(v')$. Since we have asked for a vertex x that is the closest to the root for which this Lemma does not hold, the Lemma does hold for all vertices on the path from the root to u. Consequently, s_1 and s_2 are both descendants of u, contradicting the hypothesis that y is the lca of s_1 and s_2 .

Proof of Lemma 8

Proof. Consider the tree T realizing M_e that satisfies Lemma 7. It is immediate to modify T in such a way that it has properties 1-7 of definition of a standard tree. Let e = (u, x) be an edge labeled by c^+ or c^- , and let S(x), C(x) be respectively the species and the characters of T(x). Notice that an immediate consequence of Lemma 7 is that the set of species that are in the same connected component C of graph $G_{RB}(u)$ is either contained in T(x) or disjoint from T(x). Therefore T(x) is the union of some connected components of $G_{RB}(u)$. It is easy to show that properties 8-9 of a standard tree holds for T.

Proof of Lemma 10

Proof. By definition of standard tree and of depth-first visit, each negative character c^- is preceded in V by c^+ . Therefore we only have to prove that all all single character reductions of V are possible and the graph reduced by V has no edge.

Let us prove the lemma by induction on the number n of nodes of T. Clearly the lemma holds when n = 1, that is the tree consists of a single leaf, therefore assume that the lemma holds for all tree with at most n nodes.

If G_{RB} is disconnected, then it is easy to show that visiting separately and successively each subtree of a standard tree T is equivalent to visiting all of T, from which the lemma easily follows.

Assume now that G_{RB} is connected, therefore the root r of T has only a child x. Let e = (r, x) be the only edge of T incident on r and let c be the character labeling e. Since x is the only child of r, V consists of the edge e followed by the depth-first visit of T(x).

By definition of standard tree (point 6), $G_{RB}(x)$ is obtained from G_{RB} by realizing character c. Consequently T(x) solves the graph $G_{RB}(x)$ and, by inductive hypothesis, the lemma holds for T(x). Moreover T(x) contains no black edges incident on c, as they all have been removed when realizing c. All other edges of G_{RB} are removed by realizing the characters in the depth-first visit of T(x), therefore no edge remains from G_{RB} after realizing V.

Proof of Theorem of 11

Proof. Let M be the completion of matrix M_e obtained from a successful c-reduction of the red-black graph for M_e . In the following we show that M has no forbidden matrix. This fact will prove that M admits a pp tree. Let G_R be the red-black obtained after the realization of the characters of the successful c-reduction. Assume to the contrary that M has two characters c, c_1 that induce a forbidden matrix F, and let s_1, s_2, s_3 be the species of M having the configuration (1, 1), (1, 0) and (0, 1) in F, respectively.

We must consider the following cases.

Case 1. Assume that the forbidden matrix is induced by two negated characters. This fact implies that G_R will have an induced Σ -graph, thus contradicting the fact that G_R is edgeless.

Case 2. Assume that the forbidden matrix is induced by two positive characters.

Then c, c_1 must be in the same connected component of the red-black graph before their realization, as species s_1 is connected to both characters (we do not know if s_1 is connected by a black or red edge). Now, the realization of c produces the red edge (c, s_3) , since $M_e[s_3, c] =$?. Then $M[s_3, c] = 1$ in the completion M, a contradiction with the assumption.

Case 3. Assume that the forbidden matrix is induced by a positive and negated character.

Assume that c is the negated character. Since c and c_1 share a species in the forbidden matrix F, it means that c and c_1 are in the same connected component of the red-black graph when c_1 and c are realized in the graph. Since (0, 1) is given in the matrix F in row s_2 , by definition of realization of c_1 , it must be that $M[s_2, c_1] = 1$ and $M[s_2, \bar{c_1}] = 1$ as $M_e[s_2, c_1] = 0$. But this is a contradiction.

Proof of Lemma 13

Proof. Let a, b be an arbitrary pair of elements that are in set C_M . Since the red-black is connected, there exists a path π connecting the two vertices a and b. Then by induction on the number k of internal vertices of the smallest path that connects a to b we show that (a, b) is an edge of the adjacency graph G. Assume first that k = 1. Then assume that (a, c), (c, b) are edges of the shortest path π connecting the two vertices a and b.

Assume on the contrary that there is no edge (a, b) in the adjacency graph. The following cases must be considered. Assume that c is not comparable with both a and b. Since c adjacent with ait follows that there exists a species s such that s contains a but not c and similarly there exists a species s' such that s' contains c, but not a. But this fact would imply that (a, c) is an edge of the conflict graph which is a contradiction. For the same reason c must be comparable with b. Assume that c is comparable with b and a in P. Since $a, b \in C_M$, it holds that c < b and c < a. But this fact would imply that a, b are adjacent in graph G as they share a common species. Then assume that k = n > 1. Clearly, G must have edge (a, c) where c is the vertex adjacent to a on the path having k internal vertices. Since the path connecting c and b has k - 1 internal vertices, by induction it holds that also edge (c, b) is in graph G. Consequently, there exists a path with 1 vertex in the red-black graph connecting a and b. By induction, we show that (a, b) must be an edge of the graph G, as required.

Proof of Lemma 14

Proof. Take two characters a and b that are consecutive in the graph G_{RB} .

Then two cases are possible. Case 1: assume that a < b or b < a. Then the realization of a and b produces a unique red graph that is connected, otherwise there exists a species to which a is connected but b is not and vice-versa, which contradicts the containment relation between the two characters. This fact proves the lemma.

Case 2: if a and b are not comparable, then there exists a species s such that a connected to s but b is not connected to s, and vice-versa there exists a species s' such that b is connected to s.

to s', but a is not. Then there does not exist a specie x of graph G_{RB} that is not connected to both a and b. In fact, if on the contrary, such a species exists, then the pair (a, b) induces the four gametes and thus (a, b) is an edge of the conflict graph, contradicting the fact that it is empty. Consequently, if species x does not exist, then the realization of a and b induces two red disjoint components thus proving the lemma.

Theorem 16. Let (M, E^*) be a binary matrix that has an empty conflict graph. Then there exists a polynomial time algorithm to build the p-pp tree for M and if E^* is empty then M admits a solution.

Proof. Clearly, the algorithm for an empty conflict graph described in the paper works in polynomial time in the size of the input matrix M. In the following we show that the algorithm outputs a sequence r that is a successful c-reduction of graph G_{RB} . In the following we assume that a maximal character c can be realized before a character c' such that c' < c in a successful c-reduction. In particular, in the case that of the P-PP problem a solution always exists. In fact at each iteration all characters may be realized and in the following we show that no red sigma-graph is induced at any iteration of the algorithm, till the red-black graph is edgeless. By Lemma 13, the set C_M of P forms a clique. Then by Lemma 14, these characters can be realized in any arbitrary order without inducing a Σ -graph in the red-black graph. More precisely, by Lemma 14, after the realization of set C_M , each character in C_M is connected to red-edges and the red components induced by a single character in C_M are disjoint. Observe that at a second iteration of step 1, a maximal element c_m of the first iteration of step 1.

In the following we show that after the realization of elements in C_M , the red-black graph consists of disjoint components and each maximal element c that is in the poset P after the removal of C_M is in one of such disjoint connected components and it is a universal characters or the component has a unique maximal character in C_M that is free. In the first case, no red-edge is induced by the realization of c, while in the second case, the red-edges of the component induced by an element in C_M are removed. Consequently, it follows that by the application of Lemma 14 and Lemma 13, no red sigma-graph is induced in the new iteration of the algorithm.

Let c be an element such that $c < c_m$. Assume that $S_1 = S(c_n)/S(c_m)$ and $S_2 = S(c_m)/S(c_n)$. Clearly S_1 and S_2 are disjoint sets and since $S(c) \subseteq S(c_m)$, it holds that $S(c)/S(c_n) \subset S_2$. Now, we have three cases: (1) there exists a species $s \in S_2$ such that s is not in S(c) and a species $s_1 \in S_2$ such that s_1 is in S(c), or (2) all species in S_2 are not in S(c) or (3) all species in S_2 are in S(c). Assume that case 1) holds. Then, if there exists a species s' that is of c_n and c_m and s' has character c, it holds that c and c_n form an edge of the conflict graph, thus this case is not possible. Consequently, if case 1) holds it means that c is in the component consisting only of species in S_2 and c_n is free in such a component. Assume that case (2) holds. Then c is connected to a species that is of c_n and c_m . It follows that c is universal for the component consisting of the species of c_n and c_m to which c is connected. Assume now that case 3) holds. Again this case shows that c is universal for the connected component to which c belongs.

We shows that the CP-PP problem is equivalent to a case of the General Character Compatibility [11] (GCC) whose computational complexity is still open and similarly we show the connection of the restricted P-PP problem with the GCC one.

In the General Character Compatibility problem, the input is a set S of species. Observe that a set of species S is defined by means of a set of generalized characters. A generalized character $\hat{\alpha}$ consists of a pair (α, T_{α}) where $\alpha : S \to 2^{Q_{\alpha}}$ (Q_{α} is the set of states for $\hat{\alpha}$), and $T_{\alpha} = (V(T_{\alpha}), E)$ is a rooted character tree with nodes bijectively labeled by the elements of Q_{α} .

Then a the solution of the GCC problem is a rooted tree T = (V, E) and a *state-assignment* function c that assigns to each vertex $v \in V(T)$ and generalized character $\hat{\alpha}$ a state, in such a way that $c(v, \hat{\alpha}) \in Q_{\alpha}$ such that the following fact holds.

1. For each species $s \in S$ there is a vertex v_s of tree T such that $c(v_s, \hat{\alpha}) \in \alpha(s)$ for each $\hat{\alpha}$.

- 2. For every $\hat{\alpha} \in C$ and state $i \in Q_{\alpha}$, the set of vertices of T where $\hat{\alpha}$ assumes value *i* is a connected component of T.
- 3. For every $\hat{\alpha} \in C$, the tree $T(\alpha)$ is an induced subtree of T_{α} , where $T(\alpha)$ is obtained from T by labeling the nodes of T only with their α -states (as chosen by function c), and then contracting edges having the same α -state at their endpoints.

In the following we show that the P-PP problem is equivalent to the GCC problem where $\alpha(s) \in \{\{1\}, \{0, 2\}\}$ for each species s and moreover $T_{\alpha} = 0 \rightarrow 1 \rightarrow 2$.

We can show that state 2 in the GCC problem is equivalent to the fact that a character is persistent that is, it is in state 0 (lost) but it has been in state 1 before (gain). Given an instance of the GCC problem where for each generalized character $\hat{\alpha}$ it holds that $\alpha(s) \in \{\{1\}, \{0, 2\}\}$ for each species s and $T_{\alpha} = 0 \rightarrow 1 \rightarrow 2$, we can associate a matrix M that is an instance of the P-PP problem as follows: we assign a column c_j in M to each generalized character $\hat{\alpha}_j$ and a row for each species $s \in S$, where $M[s, c_j] = 0$ if and only if $\hat{\alpha}_j(s) \in \{0, 2\}$, otherwise $M[s, c_j] = 1$. Given a solution T_{pp} of the PP-problem, it is easy to verify that the underlying unlabeled tree T together with the function c such that for each vertex v and vector l_v , it holds that $l_v[i] = c(v, \hat{\alpha}_i)$, if c_i is in state 0 or 1 for the first time, otherwise if $l_v[i] = 0$ for the second time, then $c(v, \hat{\alpha}_i) = 2$ is a solution of the associated GCC problem instance. Consequently, GCC reduces to the P-PP-problem.

The vice versa, that is the P-PP-problem reduces to GCC, is easily proved as follows. For each species s of an input matrix M of the PP-problem and character c_j , we define the generalized character $\hat{\alpha}_j$, where $\hat{\alpha}_j(s) \in \{0, 2\}$ if and only if $M[s, c_j] = 0$ otherwise $\hat{\alpha}_j(s) \in \{1\}$ if and only if $M[s, c_j] = 1$. Moreover $T_{\alpha_j} = 0 \to 1 \to 2$ for each $\hat{\alpha}_j$.

In fact we can show that given a tree T which is solution of the GCC problem, then we can build a tree T_{pp} obtained by assigning to each vertex v of the tree T a vector l_v such that $l_v[i] = c(v, \hat{\alpha}_i) = j$, when $j \in \{0, 1\}$ otherwise if j = 2, then $l_v[i] = 0$.

Now, T_{pp} is a solution of the initial P-PP problem instance. In fact the four properties of Definition 1 holds for T_{pp} . In particular condition 4 of such definition is proved as follows. Notice that, by property 3 of tree T, the tree $T(\alpha)$ represents the change in states of each character $\hat{\alpha}$. Since $T_{\alpha} = 0 \rightarrow 1 \rightarrow 2$, the state of a character changes from 0 to 1 and again to 0 (which we represent with state 2) only if persistent. A direct consequence of property 2 of tree T, is that in tree T we can label only one edge (u, v) of the tree with a character c_j^+ or c_j^- , more precisely, when then the state of the generalized character $\hat{\alpha}_j$ changes from 0 to 1 in l_u and l_v , and respectively, from 1 to 2 in l_u and $_v$ in the tree T. In fact, the set of vertices with a common state $c(v, \hat{\alpha}_j) = k$ for a character $\hat{\alpha}_j$ must be a connected component. Now, when $k \in \{1\}$ (or $k \in \{2\}$), the connected component induced by vertices v labeled k by the c function represents the substree of tree T_{pp} rooted in the end of the edge labeled c_i^+ (or c_j^- , respectively).

Using the above result, assuming that some characters may have only state 0 in a given species, it is easy to show that the CP-PP problem is equivalent to the GCC in the case that $\alpha(s) \in \{\{1\}, \{0\}, \{0, 2\}\}$ for each species s and $T_{\alpha} = 0 \rightarrow 1 \rightarrow 2$.