Non-linear Nyquist theorem: A conjecture

Navinder Singh

Physical Research Laboratory, Ahmedabad, India, PIN: 380009.

Thermodynamics of equilibrium states is well established. However, in nonequilibrium few general results are known. One prime and important example is that of Nyquist theorem. It relates equilibrium tiny voltage fluctuations across a conductor with its resistance. In linear systems it wa[s](#page-4-0) proved in its generality in a beautiful piece of work by Callen and Welton (in $1950s¹$). However Callen-Welton's formalism has not been extended to nonlinear systems up to now, although alternative methods exist (like Kubo's approach) that leads to formal and implicit expressions *at nonlinear order* with no practical consequence. Here–using a brute-force method–we conjecture "a non-linear Nyquist theorem". This is an explicit formula much like Nyquist's original one. Our conjecture is based upon tests of the conjectured explicit formula in specific systems. We conjecture that higher moments of *equilibrium* fluctuations bear a relation to *nonlinear* admittance very similar to Nyquist's relation. Thus one can easily compute nonlinear admittance from the character of *equilibrium* fluctuations. Our relation will have great practical applicability, for example for electronic devices that operate under nonlinear response.

By a brute-force method an extension of Callen and Welton's seminal work of $1951¹$ $1951¹$ is developed. Before we present that, we review the seminal works of Nyquist[2](#page-4-1) and of Callen-Welton^{[1](#page-4-0)}. If you connect a resistance with a

FIG. 1: (a) Two resistances connected with each other. Both are at same temperature T . (b) Arrangement to show that at any frequency equal power flows from both sides. (c) Standing modes in the shunted transmission line.

sensitive voltmeter or oscilloscope you observe an ac voltage of zero mean but non-zero Root Mean Square (RMS) value of very small magnitude (sub-micro volts in ordinary conductors). This thermally induced noise voltage (the Johnson-Nyquist noise) was first observed by John B. Johnson of Bell Labs in 1926 and its theoretical explanation was provided by his colleague Harry Nyquist in 1927. Hence called Johnson-Nyquist (JN) noise. Nyquist proved that the frequency integrated variance of voltage is proportional to the frequency integrated resistance: $\langle V^2 \rangle = 4k_BT \int_0^\infty R(\omega) d\omega$. He proved this by using sim-ple but ingenious thermodynamical arguments^{[2](#page-4-1)}. He first shows that if you connect two equal resistances in parallel with each other (figure $1(a)$), then the power dissipated in first resistance due to JN noise voltage produced by the second resistance will be equal to power dissipated in the second due JN noise voltage produced by the first,

provided both resistances are kept at the same temperature. Thus there is a balance of power flow. This is in accordance with second law of thermodynamics. He further refines it by showing that the above inference is true at all frequencies^{[2](#page-4-1)} thus obtaining an important conclusion that RMS voltage must be a universal function of frequency. This he shows by connecting a LC circuit in between the resistances (figure $1(b)$). LC circuit acts like a shunt at a specific frequency $\omega = \frac{1}{\sqrt{LC}}$. If the power transfer is non uniform in frequency, then more power will be shunted from 1 to 2 as compared to that from 2 to 1, or vice versa. Thus the arrangement in figure 1 (b) will spontaneously leads to heating of one resistance as compared to the other, again violating the second law of thermodynamics. Thus, there is a balance of power flow in each frequency interval and power transferred must be a universal function of frequency.

It was know from the experiments of Johnson that the JN noise is a universal function of resistance and temperature (it does not depend on the material of the resistance i.e. whether it is carbon resistance or metallic). Thus $V_{rms} = f(R, T, \omega)$. Where f is some universal function. Nyquist explicitly derives this universal function using the law of equipartition of energy and counting the number of standing modes in a transmission line.

In his thought experiment he first disconnects the resistances and then connects them at the ends of a lossless transmission line for a time interval l/v . Where l is the length of the transmission line and v is speed of electromagnetic waves in the line. After this, he removes the resistances and short circuits the ends of the transmission line. This leads to standing modes in the transmission line (figure $1(c)$). Number of standing modes in the frequency interval f to $f + df$ will be $(2l/v)df$. By equipartition of energy each mode has k_BT of energy. Thus energy in the frequency interval f to $f + df$ will be $k_BT(2l/v)df$. Average power transferred in time l/v is $2k_bT df$ (energy/time). For a linear system average power is $\frac{\langle V^2 \rangle_f}{2R} df$ (where $\langle V^2 \rangle_f$ is variance per unit frequency).

Thus leading to $\langle V^2 \rangle_f df = 4k_BT Rdf$. If the resistance is frequency dependent then frequency integrated variance bears the relation

$$
\langle V^2 \rangle = 4k_B T \int_0^\infty R(\omega) d\omega, \tag{1}
$$

known as Nyquist theorem^{[2](#page-4-1)}. The fundamental importance of this relation and other general linear fluctuationdi[s](#page-4-2)sipation theorems³ is that the equilibrium fluctuations (for example, JN noise) has "hidden" information regarding transport coefficients (here the resistance R). This fact is the cornerstone of liner nonequilibrium sta-tistical mechanics^{[4](#page-4-3)}.

Callen and Welton gave rigorous quantum mechanical foundation to Nyquist's result. They consider a conductor of length L and of impedance $Z(\omega)$ biased with an ac voltage $V(t) = V_0 \sin(\omega t)^{11}$ $V(t) = V_0 \sin(\omega t)^{11}$ $V(t) = V_0 \sin(\omega t)^{11}$. The total Hamiltonian H of the system composes two parts: H_0 the unperturbed part, and $V(t)\hat{Q}$ the perturbation. That is $H = H_0 + V(t)\hat{Q}$. Where $\hat{Q} = \sum_i e^{\hat{x}_i}$ and x_i is the position of i^{th} particle from one end of the conductor (\hat{x}_i) is an operator corresponding to that). They assume that eigensystem of H_0 is known with E_n as eigen energies and ϕ_n as eigenfunctions. Compute an average power absorbed by the conductor from the battery. For this, let the wavefunction of the perturbed system is $\psi(t) = \sum_{n} a_n(t) \phi_n$ which obey the Schroedinger's equation $i\hbar \frac{\partial \psi(t)}{\partial t} = (H_0 + V(t)\hat{Q})\psi(t)$. Under the assumption of weak perturbation (which is usually the case) the expansion coefficients $a_n(t)$ are expressed as perturbation series. Retaining up to the first order, the transition probability to find the system in some final state $|f\rangle$ of energy E_f at time t when the system was in state $|i\rangle$ at an initial time $t = 0$ is calculated to be $\mathscr{P}_{if}(t) = |\langle f | \psi(t) \rangle|^2 = \frac{1}{2} \pi t \frac{V_0^2}{\hbar} |Q_{E_f, E_i}|^2 (\delta(\omega + \omega_{if}) +$ $\delta(\omega - \omega_{if}))^1$ $\delta(\omega - \omega_{if}))^1$. Where the notation Q_{E_f, E_i} means matrix element $\langle E_f | Q | E_i \rangle$.

If the final states form a continuum (generally true for a system in thermodynamic limit) then the total transition probability from initial state $|i\rangle$ to any final state per unit time is $\mathscr{P}_i = \frac{1}{t} \sum_{f} \mathscr{P}_{if} =$ $\frac{1}{t} \int dE_f \rho(E_f) \mathscr{P}_{if} = \frac{\pi}{2}$ $\frac{V_0^2}{\hbar}(|\langle E_i+\hbar\omega|\hat{Q}|E_i\rangle|^2\rho(E_i+\hbar\omega)+$ $|\langle E_i - \hbar \omega | \hat{Q} | E_i \rangle|^2 \rho(E_i - \hbar \omega)$. While replacing sums by integrals we introduce density of states $\rho(E)$ (number of states per unit energy). Two terms in the parenthesis has the following physical meaning. First term (with $\langle E_i + \hbar \omega | Q | E_i \rangle$) represents photon absorbed by the system (conductor) from the battery in which initial state with energy E_i changes to a state with energy $E_i + \hbar \omega$. The other term represents loss of a photon by the system (i.e., $\langle E_i - \hbar \omega | \hat{Q} | E_i \rangle$). Thus power absorbed is $Power(E_i) = \hbar \omega \times \frac{\pi}{2}$ $\frac{V_0^2}{\hbar}(|\langle E_i+\hbar\omega|\hat{Q}|E_i\rangle|^2\rho(E_i+\hbar\omega) |\langle E_i-\hbar\omega|\hat{Q}|E_i\rangle|^2 \rho(E_i-\hbar\omega)$. As $\hbar\omega$ is the energy of a single photon. Also notice the minus sign between the two terms in the parenthesis that represents gain minus loss $(qain - loss)$. The *average* power absorbed at frequency

 ω is $\langle Power \rangle_{\omega} = \int_0^{\infty} dE_i \rho(E_i) f(E_i) Power(E_i)$ and is obtained by summing over all possible initial states with thermodynamic weighting factor $f(E_i) = e^{-E_i/k_B T}$. For a linear system $\langle Power \rangle_{\omega} = \frac{1}{2} V_0^2 \frac{R(\omega)}{|Z(\omega)|}$ $\frac{R(\omega)}{|Z(\omega)|^2} = \frac{1}{2} V_0^2 Y(\omega),$ and from this they obtain an expression for $Y(\omega)$ (the real part of linear admittance).

Next, they analyze the nature of equilibrium voltage fluctuations in the conductor (when battery is disconnected). Average current $\langle \hat{Q} \rangle = \frac{i}{\hbar} \langle E_n | [H_o, \hat{Q}] | E_n \rangle$ vanishes in equilibrium (as expected), but its square does not. With a simple calculation they show that $\langle |\hat{Q}^2| \rangle = \int_0^\infty d\omega \hbar \omega^2 \int_0^\infty dE \rho(E) f(E) (|\langle E_i +$ that $\; \langle | \dot{\hat Q}^{\,2} | \rangle \;$ $\hbar\omega|\hat{Q}|E_i\rangle|^2\rho(E_i + \hbar\omega) + |\langle E_i - \hbar\omega|\hat{Q}|E_i\rangle|^2\rho(E_i - \hbar\omega)).$ With the expression $V(\omega) = |Z(\omega)|\hat{Q}(\omega)$ variance of the voltage $\langle V^2 \rangle$ can be expressed in terms of the matrix elements and Density Of States (DOS). From these expressions of admittance and variance of equilibrium voltage it can be shown that $\langle V^2 \rangle = \frac{2}{\pi} \int_0^\infty d\omega R(\omega) E(\omega, T)$ with $E(\omega,T) = \hbar \omega / 2 + \hbar \omega / (e^{\hbar \omega / k_B T} - 1)$. This is known as the Callen-Welton's theorem^{[1](#page-4-0)}. In the high temperature limit $k_BT \gg \hbar \omega$, $E(\omega, T)$ can approximated by k_BT . This leads to $\langle V^2 \rangle = \frac{2}{\pi} k_B T \int_0^\infty d\omega R(\omega)$ which is nothing but the Nyquist's result now with correct coefficient!

A survey of literature: Callen-Welton's theorem and its statistical mechanical formulation by Kubo^{[3](#page-4-2)} completed the program of linear Fluctuation-Dissipation Theorems (FDT) by 1957 (i.e., connecting transport coefficients of linear irreversible processes (for example, Ohm's law: current proportional to voltage) with *equilibrium* fluctuations). The next logical step was to extend these theorems of Nyquist, Callen-Welton, and Kubo to nonlinear regime (in which, for example, current is also proportional to higher powers of voltage). First steps in these directions were taken by William Bernard and Herbert Callen^{[5](#page-4-5)}, and by Russian investigators: R. L. Stratonovic[h](#page-4-6)^{6[,7](#page-4-7)}; G. F. Efremov^{[8](#page-4-8)}; G. N. Bochkov and Yu. E. Kuzovlev^{[9](#page-4-9)}.

In Bernard-Callen's work^{[5](#page-4-5)} an expression for nonlinear FDT is given (equation (162) in^{[5](#page-4-5)}). However, as they point out, it does not constitute a thermodynamical relation as their function $f_{jki}^{(0)}(\omega_1, \omega_2)$ is not macroscopically observable (see discussion below equation (162) in^{[5](#page-4-5)}). In general at the nonlinear order admittance and fluctuation expressions becomes extremely complicated and this algebraic complexity hindered the progress. But Russian investigators were able to make progress by exploiting the principle of time reversal invariance[7](#page-4-7) . In 1967 Stratonovich derives nonlinear FDT under the Markovian assumption[7](#page-4-7) and using a master equation. In 1968, going beyond the Markovian limit, Efremov proves the non-Markovian quadratic FDT^{[7](#page-4-7)}. The expressions (called three-subscript and four-subscript relations) obtained by these investigators are highly formal and implicit (see, for example, equation $(6.1.88)$ in^{[7](#page-4-7)} for fourfold correlator). In 1977, Bochkov and Kuzovlev, again by exploiting the principle of time reversal invariance of microscopic dynamics, develop a general theory of thermal fluctuations in nonlinear systems^{[9](#page-4-9)}. They obtain a formula (equation (4) in^{[9](#page-4-9)}) that characterizes the excitation of the system from the state of thermodynamic equilibrium. From this fundamental formula 12 they obtain three and four index relations between the equilibrium and nonequilibrium moment functions. Again, these formulae suffer from analytical complexity and a direct and explicit analogy with Nyquist theorem is difficult to obtain.

In the present investigation we obtain a direct generalization the the linear Nyquist's theorem without using any master equation. Our method is a brute-force extension of the original Callen-Welton result. End result is an explicit and compact formula much like Nyquist's original one. In addition, with the present approach, we

obtain an explicit expression for nonlinear admittance in terms of density-of-states of a system and current matrix elements. Thus, present work will also be useful in direct calculations of nonlinear admittances.

With this physical background and a survey of literature, we now motivate a nonlinear Nyquist theorem. We start with the setting used by Callen and Welton (a conductor biased with a battery). The total Hamiltonian is $H = H_0 + V(t)\hat{Q}$ where $\hat{Q} = \sum_i e_i^{\hat{x}_i}$ as before. Our aim is to compute the average power absorbed by our system (the conductor) at the next order of the applied voltage. To the second order in perturbation theory the expansion coefficient $a_n(t)$ of $\psi(t) = \sum_n a_n(t) \phi_n$ can be written as

$$
b_n(t) = (-i/\hbar)^2 \sum_m \int_0^t dt' H'_{nm}(t') \int_0^{t'} dt'' H'_{mi}(t'') e^{-i(\omega_{mn}t' + \omega_{in}t'')}.
$$
\n(2)

Here $H'_{nm}(t) = V_0 \sin(\omega t) \hat{Q}$ and $e^{-iE_n t/\hbar} b_n(t)$. This leads to the transition probability $(\mathscr{P}_{fi} = |\langle f | \psi(t) \rangle|^2)$:

$$
\mathscr{P}_{fi} = (V_0/\hbar)^4 \sum_{m,n} Q_{fn} Q_{ni} Q_{fm}^* Q_{mi}^* \int_0^t dt' \sin(\omega t') e^{-i\omega_{nf}t'} \int_0^{t'} dt'' \sin(\omega t'') e^{-i\omega_{in}t''}
$$

$$
\times \int_0^t dt' \sin(\omega t') e^{-i\omega_{mf}t'} \int_0^{t'} dt'' \sin(\omega t'') e^{-i\omega_{im}t''}. \tag{3}
$$

With tedious algebra (see supplementary information), this can be simplified to

$$
\mathscr{P}_{fi} = (\pi t/8)(V_0/\hbar)^4 \sum_{m,n} Q_{fn} Q_{ni} Q_{fm}^* Q_{mi}^* \left(\frac{\delta(2\omega - \omega_{if})}{(\omega - \omega_{in})(\omega - \omega_{im})} + \frac{\delta(2\omega + \omega_{if})}{(\omega + \omega_{in})(\omega + \omega_{im})} \right)
$$

$$
+ (\pi t/2)(V_0/\hbar)^4 \sum_n |Q_{fn}|^2 |Q_{ni}|^2 \left(\frac{\omega}{\omega^2 - \omega_{in}^2} \right)^2 (\delta(\omega - \omega_{nf}) + \delta(\omega + \omega_{nf})). \tag{4}
$$

By converting sums into integrals $\sum_n \longrightarrow \int dE \rho(E)$ it is possible to do integrals over the final states using the properties of the Dirac delta functions and then by recog-

nizing the emission and absorption process the average power transferred (from battery to conductor) can expressed as

$$
\langle Power_{\omega} \rangle^{(4)} = (\pi V_0^4 \omega/4) \int_0^{\infty} dE_i \rho(E_i) f(E_i) \int_0^{\infty} dE_m \rho(E_m) \int_0^{\infty} dE_n \rho(E_n)
$$

$$
\times \left(\frac{\rho(E_i + 2\hbar \omega) Q_{E_i + 2\hbar \omega, E_n} Q_{E_n, E_i} Q_{E_i + 2\hbar \omega, E_m}^* Q_{E_m, E_i}^*}{(\hbar \omega + E_i - E_n)(\hbar \omega + E_i - E_m)}
$$

$$
- \frac{\rho(E_i - 2\hbar \omega) Q_{E_i - 2\hbar \omega, E_n} Q_{E_n, E_i} Q_{E_i - 2\hbar \omega, E_m}^* Q_{E_m, E_i}^*}{(\hbar \omega - E_i + E_n)(\hbar \omega - E_i + E_m)} \right). \tag{5}
$$

Г

Technical details are given in supplementary information. For nonlinear system under consideration $\langle Power_{\omega} \rangle^{(4)} =$

 $\frac{3}{8}V_0^4Y_R^{(4)}(\omega)$ where $Y_R^{(4)}(\omega)$ is the real part of the nonlinear admittance. Thus real part of the nonlinear admittance can be expressed in terms of matrix elements of Q and Density Of States (DOS). An important difference at this nonlinear order is that the system absorbs two quanta ($2\hbar\omega$) from battery while in the linear order it absorbs one quantum ($\hbar\omega$). Notice the matrix elements $Q_{E_i+2\hbar\omega,E_n} Q_{E_n,E_i}.$

When battery is disconnected from the conductor the conductor regains equilibrium in some relaxation time. In equilibrium, voltage has tiny fluctuations, mean of odd powers of voltage vanishes but mean of even powers does not. In the present case we need to compute an average of the fourth power of the current operator $\langle \dot{Q}^4 \rangle = \sum_n f(E_n) \langle E_n | \dot{Q}^4 | E_n \rangle$. The expression in terms of the DOS and matrix elements is extremely lengthy and is given in the supplementary information (equation (19)). Due to horrendous analytical complexity, it is not

possible to establish a direct relation between $Y_R^{(4)}(\omega)$ and $\langle \hat{\bar{Q}}^4 \rangle$ as was done by Callen and Welton in the linear regime where the formulae were simpler.

We adopt the following strategy. We simplify the above expressions for $Y_R^{(4)}$ $\chi_R^{(4)}(\omega)$ and $\langle \hat{Q}^4 \rangle$ by considering two simple physical systems and test whether there exists a relation analogous to the Nyquist relation or not. In the first system we consider constant DOS and constant matrix elements and in the second system we consider constant DOS but (non)constant matrix elements which are obtained by an explicit calculation. For the first system let us assume that $\rho(E) = \rho_0 \Theta(E_{up} - E)$ (step function DOS) and $Q_{E_i,E_j} = \eta e$. Here E_{up} is the upper cut-off in the DOS, and η is dimensionless constant and e is the electronic charge. Nonlinear admittance (equation (17), supplementary information) in this case can be simplified to

$$
Y_R^{(4)}(\omega) = \frac{2\pi}{3}\omega\eta^4 e^4 \rho_0^4 \left(\int_0^{E_{up}-2\hbar\omega} dE f(E) \left(\ln \left| \frac{E_{up}-E-\hbar\omega}{E+\hbar\omega} \right| \right)^2 \right) - \int_{2\hbar\omega}^{E_{up}} dE f(E) \left(\ln \left| \frac{E_{up}-E+\hbar\omega}{E-\hbar\omega} \right| \right)^2 \right).
$$
 (6)

Г

And, with a lengthy calculation, the fluctuation (equation (19) in supplementary information) can be simplified to

$$
\langle \dot{\hat{Q}}^4 \rangle = \frac{1}{6} \rho_0^4 \eta^4 e^4 \omega_{up}^7
$$

$$
\times \int_0^{E_{up}} dE e^{-\beta E} (\frac{1}{3} \gamma^7 + \frac{4}{3} \gamma^6 + \frac{6}{3} \gamma^5 + \frac{4}{3} \gamma^4 + \frac{1}{3} \gamma^3)
$$

(7)

Here $\gamma = \frac{E}{E_{up}}$. Let us define

$$
R_{Callen-Welton}(T) = \frac{\langle \dot{\hat{Q}}^4 \rangle}{\int_0^\infty d\omega Y_R^{(4)}(\omega)},\tag{8}
$$

and call it Callen-Welton's ratio. $R_{Callen-Welton} \propto T$ establishes the Nyquist's relation. This is plotted in figure 2 as a dashed line (the solid line is for Nyquist's original result). We notice that at high temperatures $(k_BT \gg \hbar\omega)$ we have the following relation for our first example

$$
\langle \dot{\hat{Q}}^4 \rangle \propto k_B T \int_0^\infty d\omega Y_R^{(4)}(\omega). \tag{9}
$$

Next, we show that the above relation also holds good in our second system. The DOS model is the same as before but the matrix elements are calculated by considering free electron gas in a 1-D "box" of length L.

Periodic boundary condition is applied to the plane wave state wavefunctions $\phi_n(x) = \frac{1}{\sqrt{2}}$ $\frac{1}{L}e^{ik_nx}$ to mimic thermodynamic limit (later $L \to \infty$ limit is taken). The matrix element $\langle E_i|\hat{Q}|E_j\rangle$ is equal to $\frac{e\eta}{\sqrt{E_i-1}}$ $\frac{e\eta}{E_j - \sqrt{E_i}}$ (see supplementary information).

The expression for $Y_R^{(4)}(\omega)$ in this case is quite lengthy and is given in the supplementary information (equation (20)) but the fluctuations can be expressed by a simple formula

$$
\langle \dot{\hat{Q}}^4 \rangle = \frac{8e^4 \rho_0^4 \eta^4}{m^2 \hbar^3} \int_0^{E_{up}} dE f(E) E^2(E + E_{up})
$$

$$
\times \left(E_{up}^2 \log \left(\frac{E_{up}}{E_{up} - E} \right) + E^2 \log \left(\frac{E_{up} - E}{E} \right) \right) 0
$$

Again, the Callen-Welton's ratio is plotted in figure 2 (dotted line) and we observe the validity of equation [\(9\)](#page-3-0) in this case too^{[13](#page-4-11)}. This relation (equation [\(9\)](#page-3-0)) which is an exact analogue to the linear Nyquist theorem should be valid in general and can be dubbed as the nonlinear Nyquist theorem. Thus we conjecture that the equation [\(9\)](#page-3-0) is a universal relation, an extension of the linear Nyquist relation to nonlinear regime. We further conjecture that

$$
\langle \dot{\hat{Q}}^{2n} \rangle \propto k_B T \int_0^\infty d\omega Y_R^{(n)}(\omega). \tag{11}
$$

FIG. 2: $\sum_{R_{\text{Callen}-\text{Welton}}(T)}$ Normalized Callen-Welton ratio $R_{Callen-Welton}(T{=}30\ K)$ as a function of temperature T (Kelvin). Solid line is the original Nyquist's theorem. Dashed and dotted lines represents nonlinear Nyquist theorem. Notice the linearity of Callen-Welton's ratios for $T \gtrsim 5$ K.

 $n = 1$ is the Nyquist theorem and $n \geq 2$ are its nonlinear extensions! Thus one can in principle compute nonlinear admittances from the character of *equilibrium fluc*tuations. Our conjectured relation(s) should be tested in other physical models, both theoretically and experimentally. The conjecture is likely to be true in real physical systems as it is valid in our considered examples especially in second physical system that has plane wave states. Plane wave states is a reasonable approximation to electronic states in real metals. These compact and explicit relations should have great practical applicability.

- 1 H. B. Callen and T. A. Welton, Phys. Rev. 83, 34 (1951).
- 2 H. Nyquist, Phys. Rev. 32, 110 (1928).
- ³ R. Kubo, Statistical-mechanical theory of irreversible processes. I. General theory and simple applications to magnetic and conduction problems, J. Phys. Soc. Jpn. 12, 570 (1957); Rep. Prog. Phys.,29, 255 (1966).
- ⁴ R. Zwanzig, *Nonequilibrium statistical mechanics*, Oxford university press (2001).
- ⁵ W. Bernard and H. B. Callen, Rev. Mod. Phys. 31, 1017 (1959).
- 6 R. L. Stratonovich, Zh. Eksp. Teor. Fiz. 39, 1647 (1960).
- ⁷ R. L. Stratonovich, *Nonlinear nonequilibrium thermodynamics I: linear and nonlinear fluctuation-dissipation theorems*, Springer-Verlag (1992).
- ⁸ G. F. Efremov, Sov. Phys. JETP 24, 105 (1967); G. F. Efremov, Sov. Phys. JETP 27, 1232 (1969).
- ⁹ G. N. Bochkov and Yu. E. Kuzovlev, Sov. Phys. JETP 45, 125 (1977).
- 10 G. N. Bochkov and Yu. E. Kuzovlev, Phys. -Usp, ${\bf 56},\,590$ (2013).
- 11 Here, the electrical circuit case is an illustrative example. Applicability of these relations is much more general^{[1](#page-4-0)}
- ¹² This formula is the genesis of the recent "Fluctuation Theorems^{[10](#page-4-12)}".
- ¹³ In figure 2 we plot normalized $R_{Callen-Welton}$ as we are

not interested in the proportionality constants.

Supplementary Information

All the technical details are collected here.

The total Hamiltonian is $H = H_0 + V(t)\hat{Q}$. Where $\hat{Q} = \sum_i e^{\hat{x}_i}$. Let eigen energies (E_n) and eigenfunctions (ϕ_n) of H_0 are known.

We want to compute an average power absorbed by the conductor from the battery. For this, let the wavefunction of the perturbed system is $\psi(t) = \sum_n a_n(t) \phi_n$ which obey the Schroedinger's equation $i\hbar \frac{\partial \psi(t)}{\partial t} = (H_0 +$ $V(t) \hat{Q} \psi(t)$. To the second order in perturbation theory, the expansion coefficient $a_n(t)$ of $\psi(t) = \sum_n a_n(t) \phi_n$ can be written as

$$
b_n(t) = (-i/\hbar)^2 \sum_m \int_0^t dt' H'_{nm}(t') \int_0^{t'} dt'' H'_{mi}(t'') e^{-i(\omega_{mn}t' + \omega_{in}t'')}.
$$
\n(12)

With the transformation $a_n(t) = e^{-iE_n t/\hbar} b_n(t)$. Here $H'_{nm}(t) = V_0 \sin(\omega t) \hat{Q}.$ The transition probability

 $(\mathscr{P}_{fi} = |\langle f | \psi(t) \rangle|^2)$ takes the form:

$$
\mathscr{P}_{fi} = (V_0/\hbar)^4 \sum_{m,n} Q_{fn} Q_{ni} Q_{fm}^* Q_{mi}^* \int_0^t dt' \sin(\omega t') e^{-i\omega_{nf}t'} \int_0^{t'} dt'' \sin(\omega t'') e^{-i\omega_{in}t''}
$$

$$
\times \int_0^t dt' \sin(\omega t') e^{-i\omega_{mf}t'} \int_0^{t'} dt'' \sin(\omega t'') e^{-i\omega_{im}t''}.
$$
(13)

After performing the integrals in equation [\(13\)](#page-5-0) the tran- sition probability can be written as

$$
\mathscr{P}_{fi} = (V_0/2\hbar)^4 \sum_{m,n} Q_{fn} Q_{ni} Q_{fm}^* Q_{mi}^*
$$
\n
$$
\times \left(\frac{e^{i(2\omega + \omega_{fi})t} - 1}{(\omega - \omega_{in})(2\omega + \omega_{fi})} - \frac{e^{i(\omega - \omega_{nf})t} - 1}{(\omega - \omega_{in})(\omega - \omega_{nf})} - \frac{e^{-i\omega_{if}t} - 1}{(\omega + \omega_{in})\omega_{if}} - \frac{e^{i(\omega - \omega_{nf})t} - 1}{(\omega + \omega_{in})(\omega - \omega_{nf})} \right)
$$
\n
$$
+ \frac{e^{-i\omega_{if}t} - 1}{(\omega - \omega_{in})\omega_{if}} - \frac{e^{-i(\omega + \omega_{nf})t} - 1}{(\omega - \omega_{in})(\omega + \omega_{nf})} + \frac{e^{-i(2\omega + \omega_{if})t} - 1}{(\omega + \omega_{in})(2\omega + \omega_{if})} - \frac{e^{-i(\omega + \omega_{nf})t} - 1}{(\omega + \omega_{in})(\omega + \omega_{nf})} \right)
$$
\n
$$
\times \left(\frac{e^{-i(2\omega + \omega_{fi})t} - 1}{(\omega - \omega_{im})(2\omega + \omega_{fi})} - \frac{e^{-i(\omega - \omega_{mf})t} - 1}{(\omega - \omega_{im})(\omega - \omega_{mf})} - \frac{e^{i\omega_{if}t} - 1}{(\omega + \omega_{im}\omega_{if})} - \frac{e^{-i(\omega - \omega_{mf})t} - 1}{(\omega + \omega_{im})(\omega - \omega_{mf})} \right)
$$
\n
$$
+ \frac{e^{i\omega_{if}t} - 1}{(\omega - \omega_{im})\omega_{if}} - \frac{e^{i(\omega + \omega_{mf})t} - 1}{(\omega - \omega_{im})(\omega + \omega_{mf})} + \frac{e^{i(2\omega + \omega_{if})t} - 1}{(\omega + \omega_{im})(2\omega + \omega_{if})} - \frac{e^{i(\omega + \omega_{mf})t} - 1}{(\omega + \omega_{im})(\omega + \omega_{mf})} \right)
$$
\n
$$
(14)
$$

Г

There are total 64 terms, not all contribute in the long time limit: when t is much greater than a characteristic time scale in the system and oscillation period of the applied field i.e., $t \gg \frac{1}{|\omega_{if}|}$ and $t \gg \frac{1}{\omega}$. Using the identity

$$
lim_{t \to \infty} \left| \frac{e^{ixt} - 1}{x} \right|^2 = 2\pi t \delta(x), \tag{15}
$$

Equation [\(14\)](#page-5-1) can be reduced to equation [\(4\)](#page-2-0). Equation

[\(5\)](#page-2-1) in the main text is obtained as follows. First sums are converted into integrals $\sum_n \longrightarrow \int dE \rho(E)$. Then integrals were performed over the final states using the properties of the Dirac delta functions. This leads to total transition probability from initial state $|i\rangle$ to any final state per unit time i.e., $\mathscr{P}_i = \frac{1}{t} \sum_f \mathscr{P}_{if}$:

$$
\mathcal{P}_{i} = (\pi V_{0}^{4}/8\hbar) \int_{0}^{\infty} dE_{m}\rho(E_{m}) \int_{0}^{\infty} dE_{n}\rho(E_{n})
$$
\n
$$
\times \left(\frac{\rho(E_{i} + 2\hbar\omega)Q_{E_{i}+2\hbar\omega,E_{n}}Q_{E_{n},E_{i}}Q_{E_{i}+2\hbar\omega,E_{m}}^{*}Q_{E_{m},E_{i}}^{*}}{(\hbar\omega + E_{i} - E_{n})(\hbar\omega + E_{i} - E_{m})} + \frac{\rho(E_{i} - 2\hbar\omega)Q_{E_{i}+2\hbar\omega,E_{n}}Q_{E_{n},E_{i}}Q_{E_{i}+2\hbar\omega,E_{m}}Q_{E_{m},E_{i}}^{*}}{(\hbar\omega - E_{i} + E_{n})(\hbar\omega - E_{i} + E_{m})} + (\pi V_{0}^{4}/2\hbar) \int_{0}^{\infty} dE_{n}\rho(E_{n}) \left(\frac{\hbar\omega}{(\hbar\omega)^{2} - (E_{i} - E_{n})^{2}} \right)^{2} \times (\rho(E_{n} - \hbar\omega)|Q_{E_{n} - \hbar\omega,E_{n}}|^{2}|Q_{E_{n},E_{i}}|^{2} + \rho(E_{n} + \hbar\omega)|Q_{E_{n} + \hbar\omega,E_{n}}|^{2}|Q_{E_{n},E_{i}}|^{2}) \tag{16}
$$

Γ

The power absorbed by the conductor from battery (equation [\(5\)](#page-2-1)) is calculated by subtracting the loss

from the gain (as done in Callen-Welton's formulation). Important point to notice in this nonlinear regime is that one has matrix elements of the form $\langle E_i +$ $2\hbar\omega|Q|E_n\rangle\langle E_n|Q|E_i\rangle$ which represents the absorption of two quanta from the battery in which initial state's energy changes from E_i to $E_i + 2\hbar\omega$ via some intermediate state of energy E_n and the second matrix element $\langle E_i - 2\hbar\omega|\hat{Q}|E_n\rangle\langle E_n|\hat{Q}|E_i\rangle$ represents the loss of two quanta. The second term in the above equation [\(16\)](#page-5-2) in which only the intermediate states $|n\rangle$ are changed does not contribute to the absorption of energy by the system from the battery because the energy of the initial state E_i in which the system was prepared at time $t = 0$ remains unchanged. Thus net gain of energy by the system (final

energy – initial energy $=E_n \pm \hbar \omega - E_i$) is zero when sum is performed on n while in the first term we have: final energy – initial energy = $E_i \pm 2\hbar\omega - E_i \neq 0$. Finally by performing an ensemble average over all possible initial states of energy E_i (in which the system was prepared at time $t = 0$) with thermodynamical weighting factor $e^{-E_i/k_B T}$ leads to desired equation [\(5\)](#page-2-1).

In linear regime the average power is given by $\langle Power_{\omega} \rangle = \langle \frac{V_0^2 \sin^2(\omega t)}{R}$ $\frac{\text{n}^2(\omega t)}{R}$ = $\frac{V_0^2}{2R(\omega)}$ = $\frac{1}{2}V_0^2Y(\omega)$. In nonlinear regime it is $\frac{1}{2}V_0^2 Y(\omega) + \frac{3}{8}V_0^4 Y_R^{(4)}(\omega) + ...$ with real part of the nonlinear admittance given by $\langle Power_{\omega} \rangle^{(4)} =$ $\frac{3}{8}V_0^4Y_R^{(4)}$ $\tilde{R}^{(4)}(\omega)$

$$
Y_R^{(4)}(\omega) = \frac{2\pi}{3}\omega \int_0^\infty dE_i \rho(E_i) f(E_i) \int_0^\infty dE_m \rho(E_m) \int_0^\infty dE_n \rho(E_n) \times \left(\frac{\rho(E_i + 2\hbar\omega) Q_{E_i + 2\hbar\omega, E_n} Q_{E_n, E_i} Q_{E_i + 2\hbar\omega, E_m}^* Q_{E_m, E_i}^*}{(\hbar\omega + E_i - E_n)(\hbar\omega + E_i - E_m) \right) - \frac{\rho(E_i - 2\hbar\omega) Q_{E_i - 2\hbar\omega, E_n} Q_{E_n, E_i} Q_{E_i - 2\hbar\omega, E_m}^* Q_{E_m, E_i}^*}{(\hbar\omega - E_i + E_n)(\hbar\omega - E_i + E_m)}
$$
\n(17)

This is an important and useful expression for $Y_R^{(4)}(\omega)$ that can be used to calculate nonlinear admittance once matrix elements and DOS of a system are known!

The fluctuations are calculated according to Callen-Welton's formulation. Thermal and quantum mechanical averages of fourth power of current operator are $\langle \dot{\hat{Q}}^4 \rangle = \sum_n f(E_n) \langle E_n | \dot{\hat{Q}}^4 | E_n \rangle$. By inserting complete set of states one will have

$$
\langle E_n|\dot{\hat{Q}}^4|E_n\rangle = \sum_{m,p,q} \langle E_n|\dot{\hat{Q}}|E_m\rangle \langle E_m|\dot{\hat{Q}}|E_p\rangle \langle E_p|\dot{\hat{Q}}|E_q\rangle \langle E_q|\dot{\hat{Q}}|E_n\rangle.
$$
\n(18)

Using $\dot{Q} = \frac{i}{\hbar} [H_0, \hat{Q}]$ and in parallel with Callen-Welton's formulation, the quantum mechanical expectation value of the fluctuation takes the form

$$
\langle E_n|\dot{Q}^4|E_n\rangle =
$$
\n
$$
-\int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' - \omega) \int_0^\infty d\omega'' (\omega'' - \omega') \rho(E_n - \hbar \omega) \rho(E_n - \hbar \omega') \rho(E_n - \hbar \omega'')
$$
\n
$$
\times Q_{E_n - \hbar \omega', E_n + \hbar \omega''} Q_{E_n + \hbar \omega'', E_n} Q_{E_n, E_n - \hbar \omega} Q_{E_n - \hbar \omega', E_n - \hbar \omega'}
$$
\n
$$
-\int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' - \omega) \int_0^\infty d\omega'' (\omega'' + \omega') \rho(E_n - \hbar \omega) \rho(E_n - \hbar \omega') \rho(E_n + \hbar \omega'')
$$
\n
$$
\times Q_{E_n - \hbar \omega', E_n - \hbar \omega''} Q_{E_n - \hbar \omega'', E_n} Q_{E_n, E_n - \hbar \omega} Q_{E_n - \hbar \omega', E_n - \hbar \omega'}
$$
\n
$$
+\int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' + \omega) \int_0^\infty d\omega'' (\omega'' + \omega') \rho(E_n - \hbar \omega) \rho(E_n + \hbar \omega') \rho(E_n - \hbar \omega'')
$$
\n
$$
\times Q_{E_n + \hbar \omega', E_n + \hbar \omega''} Q_{E_n + \hbar \omega'', E_n} Q_{E_n, E_n - \hbar \omega} Q_{E_n - \hbar \omega, E_n + \hbar \omega'}
$$
\n
$$
+\int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' + \omega) \int_0^\infty d\omega'' (\omega'' - \omega') \rho(E_n - \hbar \omega) \rho(E_n + \hbar \omega') \rho(E_n + \hbar \omega'')
$$
\n
$$
\times Q_{E_n + \hbar \omega', E_n - \hbar \omega''} Q_{E_n - \hbar \omega'', E_n} Q_{E_n, E_n - \hbar \omega} Q_{E_n - \hbar \omega, E_n + \hbar \omega'}
$$
\n
$$
+\int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' + \omega) \int_0^\infty d\omega'' (\omega'' - \omega') \
$$

$$
\times Q_{E_n - \hbar \omega', E_n + \hbar \omega''} Q_{E_n + \hbar \omega'', E_n} Q_{E_n, E_n + \hbar \omega} Q_{E_n + \hbar \omega, E_n - \hbar \omega'}
$$
\n
$$
+ \int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' + \omega) \int_0^\infty d\omega'' (\omega'' + \omega') \rho(E_n + \hbar \omega) \rho(E_n - \hbar \omega') \rho(E_n + \hbar \omega'')
$$
\n
$$
\times Q_{E_n - \hbar \omega', E_n - \hbar \omega''} Q_{E_n - \hbar \omega'', E_n} Q_{E_n, E_n + \hbar \omega} Q_{E_n + \hbar \omega, E_n - \hbar \omega'}
$$
\n
$$
- \int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' - \omega) \int_0^\infty d\omega'' (\omega'' + \omega') \rho(E_n + \hbar \omega) \rho(E_n + \hbar \omega') \rho(E_n - \hbar \omega'')
$$
\n
$$
\times Q_{E_n + \hbar \omega', E_n + \hbar \omega''} Q_{E_n + \hbar \omega'', E_n} Q_{E_n, E_n + \hbar \omega} Q_{E_n + \hbar \omega, E_n + \hbar \omega'}
$$
\n
$$
- \int_0^\infty d\omega \omega \int_0^\infty d\omega' (\omega' - \omega) \int_0^\infty d\omega'' (\omega'' - \omega') \rho(E_n + \hbar \omega) \rho(E_n + \hbar \omega') \rho(E_n + \hbar \omega'')
$$
\n
$$
\times Q_{E_n + \hbar \omega', E_n - \hbar \omega''} Q_{E_n - \hbar \omega'', E_n} Q_{E_n, E_n + \hbar \omega} Q_{E_n + \hbar \omega, E_n + \hbar \omega'}
$$
\n(19)

Г

Due to this horrendous analytical complexity, it is not possible to establish a direct relation between $Y_R^{(4)}(\omega)$ and $\langle \hat{Q} \rangle$. Thus the above expressions are simplified in simple specific models. In our first model with constant DOS and constant matrix elements the expressions for nonlinear admittance and fluctuation are simpler and are given in equations [\(6\)](#page-3-1) and [\(7\)](#page-3-2) respectively (in the main text).

For our second model the nonlinear admittance takes the form:

$$
Y_R^{(4)} = \frac{2\pi}{3}\omega\eta^4 e^4 \rho_0^4
$$

\n
$$
\times \int_0^{E_{up-2\hbar\omega}} dE f(E) \left(\frac{\ln[(f_c(E_{up}) - f_a(E))/f_a(E)]}{2(f_a(E) - f_b(E))(f_a(E) - f_c(E))} + \frac{\ln[(f_c(E_{up}) + f_a(E))/f_a(E)]}{2(f_a(E) + f_b(E))(f_a(E) + f_c(E))} \right)
$$

\n
$$
- \frac{f_b(E)\ln[(f_c(E_{up}) - f_b(E))/f_b(E)]}{(f_a^2(E) - f_b^2(E))(f_b(E) - f_c(E))} - \frac{f_c(E)\ln[(f_c(E_{up}) - f_c(E))/f_c(E)]}{(f_a^2(E) - f_c^2(E))(f_c(E) + f_b(E))} \right)^2
$$

\n
$$
- \frac{2\pi}{3}\omega\eta^4 e^4 \rho_0^4 \int_{2\hbar\omega}^{E_{up}} dE f(E) \left(\dots f_a, f_b \dots \text{ replaced with } \dots \bar{f}_a, \bar{f}_b \dots \right)^2.
$$
 (20)

 Γ

Here $f_a(E) = \sqrt{E + \hbar \omega}$, $f_b(E) = \sqrt{E + 2\hbar \omega}$, $f_c(E) =$ \sqrt{E} and $\vec{f}_a(E) = \sqrt{E - \hbar \omega}$, $\vec{f}_b(E) = \sqrt{E - 2\hbar \omega}$. In low frequency regime when $\hbar\omega \ll E_{up}$ and $\hbar\omega \ll k_BT$ the above expression takes a simpler form:

$$
Y_R^{(4)} \sim \frac{(\hbar\omega)^2}{k_B T} \log(\frac{E_{up}}{2\hbar\omega}) \int_{2\hbar\omega}^{E_{up}} dx \frac{e^{-x/k_B T}}{x^2} \tag{21}
$$

This is in sharp contrast to the Drude form $\sigma(\omega) \sim$

 $1/(1+\omega^2\tau^2)$ of linear admittance (τ is the Drude scattering rate). In the low frequency limit $(\omega^2 \tau^2 \ll 1)$ Drude conductivity (which is proportional to linear admittance) is approximately constant and then decrease with frequency whereas the nonlinear admittance increases with frequency in the low frequency limit (ref to above equation). The matrix elements in our second model are computed as follows:

$$
\langle E_i|\hat{Q}|E_j\rangle = \frac{e}{L} \sum_{l=1}^N \langle E_i|\hat{x}_l|E_j\rangle = \sum_{l=1}^N \sum_{j,j'} \int dx_j \int dy_{j'} \langle E_n|x_j\rangle \langle x_j|\hat{x}_l|y_{j'}\rangle \langle y_{j'}|E_m\rangle.
$$
 (22)

Here N is the number of particles in the system and $\langle E_n|x_j\rangle = \frac{1}{\sqrt{j}}$ $\frac{1}{L}e^{-ik_nx_j}$ are plane wave states. Using the properties of delta-functions resulting from $\langle x_j | \hat{x}_i | y_{j'} \rangle =$

 $x_i \delta_{i,j'} \delta_{j,j'} \delta(x_i - y_{j'}) \delta(x_j - y_{j'})$, the sums and integrals can be easily simplified. Further using the periodic boundary conditions $k_f - k_i = k_{fi} = 2n(\pi/L)$ (to mimic a thermodynamic system), the matrix elements takes the form $e\eta/(\sqrt{E_j}-\sqrt{E_i})$, where η is a constant, and $E_i = \frac{\hbar^2 k_i^2}{2m}$ for plane wave state.