

Optimal Offline and Competitive Online Strategies for Transmitter-Receiver Energy Harvesting

Rushil Nagda, Siddharth Satpathi, Rahul Vaze

Abstract—Transmitter-receiver energy harvesting model is assumed, where both the transmitter and receiver are powered by random energy source. Given a fixed number of bits, the problem is to find the optimal transmission power profile at the transmitter and ON-OFF profile at the receiver to minimize the transmission time. Structure of the optimal offline strategy is derived together with an optimal offline policy. An online policy with competitive ratio of strictly less than two is also derived.

Index Terms—Energy harvesting, offline algorithm, online algorithm, competitive ratio.

I. INTRODUCTION

Extracting energy from nature to power communication devices has been an emerging area of research. Starting with [1], [2], a lot of work has been reported on finding the capacity, approximate capacity [3], structure of optimal policies [4], optimal power transmission profile [5]–[8], competitive online algorithms [9], etc. One thing that is common to almost all the prior work is the assumption that energy is harvested only at the transmitter while the receiver has some conventional power source. This is clearly a limitation, however, helped to get some critical insights into the problem.

In this paper, we broaden the horizon, and study the more general problem when energy harvesting is employed both at the transmitter and the receiver. The joint (tx-rx) energy harvesting model has not been studied in detail and only some preliminary results are available, e.g., a constant approximation to the maximum throughput has been derived in [10]. This problem is fundamentally different than using energy harvesting only at the transmitter, where receiver is always assumed to have energy to receive. The receiver energy consumption model is binary, since it uses a fixed amount of energy to stay *on*, and is *off* otherwise. Since useful transmission happens only when the receiver is *on*, the problem is to find jointly optimal decisions about transmit power and receiver ON-OFF schedule. Under this model, there is an issue of coordination between the transmitter and receiver to implement the joint decisions, however, we ignore that currently in the interest to make some analytical progress.

We study the canonical problem of finding the optimal transmission power and receiver ON-OFF schedule to minimize the time required for transmitting a fixed number of bits. We first consider the offline case, where the energy

arrivals both at the transmitter and the receiver are assumed to be known non-causally. Even though offline scenario is unrealistic, it still gives some design insights. Then we consider the more useful online scenario, where both the transmitter and receiver only have causal information about the energy arrivals. To characterize the performance of an online algorithm, typically, the metric of competitive ratio is used that is defined as the maximum ratio of profit of the online and the offline algorithm over all possible inputs.

In prior work [5], an optimal offline algorithm has been derived for the case when energy is harvested only at the transmitter, which cannot be generalized with energy harvesting at the receiver together with the transmitter. To understand the difficulty, assume that the receiver can be *on* for a maximum time of T . The policy of [5] starts transmission at time 0, and power transmission profile is the one that yields the tightest piecewise linear energy consumption curve that lies under the energy harvesting curve at all times and touches the energy harvesting curve at end time. With receiver *on* time constraint, however, the policy of [5] may take more than T time and hence may not be feasible. So, we may have to either delay the start of transmission and/or keep stopping in-between to accumulate more energy to transmit with higher power for shorter bursts, such that the total time for which transmitter and receiver is *on*, is less than T .

The contributions of this paper are :

- For the offline scenario, we derive the structure of the optimal algorithm, and then propose an algorithm that is shown to satisfy the optimal structure. The power profile of the proposed algorithm is fundamentally different than the optimal offline algorithm of [5], however, the two algorithms have some common structural properties.
- For the online scenario, we propose an online algorithm and show that its competitive ratio is strictly less than 2 for any energy arrival inputs. With only energy harvesting at the transmitter, a 2-competitive online algorithm has been derived in [9]. This result is more general with different proof technique that allows energy harvesting at the receiver.

II. SYSTEM MODEL

The energy arrival instants at transmitter are marked by τ_i 's with energy \mathcal{E}_i 's for $i \in \{0, 1, \dots\}$. The total energy harvested at the transmitter till time t is given by

$\mathcal{E}(t) = \sum_{i:\tau_i < t} \mathcal{E}(t)$. Similarly, the energy arrival instants at the receiver are denoted as r_i with energy \mathcal{R}_i . With fixed power consumption of P_r at the receiver to stay *on*, each energy arrival of \mathcal{R}_i adds $\Gamma_i = \frac{\mathcal{R}_i}{P_r}$ amount of receiver *on* time, and the total ‘time’ harvested at the receiver till time t is given by $\Gamma(t)$.

Assuming an AWGN channel, the rate of bits transmission, using transmit power p and receiver is *on* is given by a monotonically increasing function $g(p)$, such that, $g(0) = 0$ and $\lim_{x \rightarrow \infty} g(x) = \infty$, $g(x)$ is concave, $\frac{g(x)}{x}$ is convex monotonically decreasing, and $\lim_{x \rightarrow \infty} \frac{g(x)}{x} = 0$. log function is one such example.

Let a transmission policy change its transmission power at time instants s_i 's, i.e. p_i is the power used between time s_i and s_{i+1} , and $p_i \neq p_{i+1}$. The start and the end time of any policy is denoted by s_1 and s_{N+1} , respectively. Thus, any policy can be represented as $\{\mathbf{p}, \mathbf{s}, N\}$, where $\mathbf{p} = \{p_1, p_2, \dots, p_N\}$ and $\mathbf{s} = \{s_1, s_2, \dots, s_{N+1}\}$. The energy used by a policy at the transmitter upto time t is denoted by $U(t)$, and the number of bits sent by time t is represented by $B(t)$. Clearly, for $j = \arg \max_i \{\tau_i < t\}$, $U(t) = \sum_{i=1}^j p_i (s_{i+1} - s_i) + p_{j+1} (t - s_j)$, and $B(t) = \sum_{i=1}^j g(p_i) (s_{i+1} - s_i) + g(p_{j+1}) (t - s_j)$. Similarly, the total time for which the receiver is *on* till time t is denoted as $O(t)$.

We assume that an infinite battery capacity is available both at the transmitter and the receiver to store the harvested energy. Finite battery case can be handled, however, the description is more laborious and currently under preparation. Our objective is, given a fixed number of bits B_0 , minimize the time of their transmission. For any policy, the total time for which the receiver is *on* is referred to as the ‘transmission time’ or the ‘transmission duration’, and the time by which the transmission of B_0 bits is finished, is called as the ‘finish time’. Thus, we want to minimize the finish time,

$$\min_{\{\mathbf{p}, \mathbf{s}, N\}} T \quad (1)$$

$$\text{subject to } B(T) = B_0, \quad (2)$$

$$U(t) \leq \mathcal{E}(t), \quad \forall t \in [0, T], \quad (3)$$

$$O(t) \leq \Gamma(t). \quad (4)$$

Constraints (3) and (4) are the energy neutrality constraints at the transmitter and receiver, i.e. energy/time used cannot be more than available energy/time. Compared to the no receiver constraint [5], problem (1) is far more complicated, since it involves jointly solving for optimal transmitter power allocation and time for which to keep the receiver *on*.

III. OPTIMAL OFFLINE ALGORITHM

In this section, we consider an offline scenario, i.e., all energy arrival epochs τ_i 's at the transmitter are known ahead of time non-causally. Moreover, for simpler exposition, however, without losing the richness of the problem, we assume that the receiver gets energy \mathcal{R} only at time 0, and

hence the total receiver *on* time is $\Gamma_0 = \frac{\mathcal{R}}{P_r}$. With only one receiver arrival, constraint (4) in Problem (1) specializes to $\sum_{i=1}^N p_i (s_{i+1} - s_i) \leq \Gamma_0$. Note that even with restriction, the problem is still challenging since we have to find the optimal receiver *on* periods (breakup of the total receiver *on* time of Γ_0) depending on the energy arrivals at the transmitter to minimize the finish time.

Lemma 1. *In an optimal solution to (1), if $p_i \neq 0$, then $p_i \geq p_j \quad \forall j < i$ with $i, j \in \{1, 2, \dots, N\}$.*

Proof involves the argument that, if powers are decreasing, then utilizing the concavity of $g(p)$, we can construct another strategy that can send same number of bits in less time. It is similar to Lemma 1 in [5], however, requires a separate proof because, with the receiver *on* time constraint, the optimal solution can intermittently have zero transmit powers. Note: For space constraints, proofs are included/omitted depending on their significance and the non-triviality.

Lemma 2. *The optimal solution to (1) may not be unique, but there always exists an optimal solution where once transmission has started, the receiver remains ‘on’ throughout, until the transmission is complete.*

Lemma 2 tells us that there is no need to stop in-between transmission and start again. Without affecting optimality, the start of the transmission can be delayed so that transmission power is non-zero throughout.

Proof: We construct an optimal solution for which $p_i > 0$ for all $i \in \{1, \dots, N\}$, i.e., with no breaks in transmission, from any other optimal solution. Let an optimal policy X be characterized by $\{\mathbf{p}, \mathbf{s}, N\}$. Now, if $p_i \neq 0 \quad \forall i$, then we are done. Suppose some powers, say $p_{i_1}, p_{i_2}, \dots, p_{i_k} = 0$ for some $k < N$, where $i_1 < i_2 < \dots < i_k$. We first look at instant i_1 .

Consider Fig. 1 (a), and a new policy (say Y) which is same as policy X before time s_{i_1-1} and after time s_{i_1+1} . But, it keeps the receiver *off* for a duration of $(s_{i_1+1} - s_{i_1})$ starting from time s_{i_1-1} (i.e. from s_{i_1-1} to $s'_{i_1} = (s_{i_1-1} + s_{i_1+1} - s_{i_1})$) and transmits with power p_{i_1-1} from time s'_{i_1} till s_{i_1+1} . Y transmits same amount of bits in same time as X and also satisfies constraints (2)-(4). So Y is also an optimal policy. But the receiver *off* duration in Y , $(s_{i_1+1} - s_{i_1})$, has been shifted to left.

Next, we generate another policy Z from Y by shifting the *off* duration $s'_{i_1} - s_{i_1-1} = (s_{i_1+1} - s_{i_1})$ to start from epoch s_{i_1-2} upto s'_{i_1-1} , $s'_{i_1-1} - s_{i_1-2} = s'_{i_1} - s_{i_1-1} = (s_{i_1+1} - s_{i_1})$, as shown Fig. 1 (b). p_{i_1-2} is shifted right to start from s'_{i_1-1} . Note that Z is also optimal. We continue this process of shifting the receiver *off* period to the left to generate new optimal policies till we reach a policy (say W) where the receiver is *off* for time $(s_{i_1+1} - s_{i_1})$ from s_1 , i.e. from s_1 to s'_1 , $s'_1 - s_1 = (s_{i_1+1} - s_{i_1})$, as shown in Fig. 1(c). As W has 0 transmission power from the start time s_1 to s'_1 , the effective start time of W can now be changed to s'_1 .

We can repeat this procedure for each *off* period corresponding to p_{i_2}, \dots, p_{i_k} till the total *off* period is shifted

to the beginning of transmission. This results in a policy with no zero powers in between, that starts *after* time s_1 (at $s_1 + (s_{i_1+1} - s_{i_1}) + \dots + (s_{i_k+1} - s_{i_k})$) and ends at the same time s_{N+1} as policy X . ■




Fig. 1. Illustration of Lemma 2. Receiver off time of $(s_j - s_{i_1})$ is progressively shifted to left as shown in (a) to (b) to (c).

In the subsequent discussion, the optimal solution means one with no breaks in transmission.

Lemma 3. For optimal policy $\{\mathbf{p}, \mathbf{s}, N\}$, $s_i = \tau_j$ for some j , $U(s_i) = \mathcal{E}(s_i^-) \forall i \in \{2, \dots, N\}$, and $U(s_{N+1}) = \mathcal{E}(s_{N+1}^-)$.

Proof: By Lemma 1 and 2, $p_i \neq 0$ and $p_{i+1} \geq p_i, \forall 1 \leq i \leq N$. So, the proof follows similar to Lemma 2,3 in [5]. ■

Lemma 3 states that in an optimal solution, the transmission power changes only at energy arrival epochs, and the energy used is equal to all the energy that has arrived till then. It may happen that at some epoch τ_k , $U(\tau_k) = \mathcal{E}(\tau_k^-)$ holds true, but transmission power does not change. For notational simplicity, we include all such τ_k 's in \mathbf{s} , where $U(\tau_k) = \mathcal{E}(\tau_k^-)$.

Lemma 4. Consider two policies $X, \{\mathbf{p}, \mathbf{s}, N\}$ and $Y, \{\tilde{\mathbf{p}}, \tilde{\mathbf{s}}, N\}$, which are feasible with respect to energy constraint (3), have non-decreasing powers and transmit same number of bits in total. If Y is same as X from time s_2 to s_N , but $\tilde{p}_1 = p_1 - \alpha, \tilde{p}_N = p_N + \beta, \tilde{s}_1 = s_1 - \gamma, \tilde{s}_{N+1} = s_{N+1} - \delta$ and $U(s_{N+1}) = U(\tilde{s}_{N+1})$, where $\alpha, \beta, \gamma, \delta > 0$, then $(\tilde{s}_{N+1} - \tilde{s}_1) > (s_{N+1} - s_1)$.

This lemma states that if we take any feasible policy, and decrease its first power p_1 & increase its last power p_N while keeping the same number of transmitted bits, the time of transmission will increase, while the finish time of the policy will reduce. The proof is algebraic using the concavity of $g(p)$, and convexity of $g(p)/p$.

Lemma 5. For an optimal policy $\{\mathbf{p}, \mathbf{s}, N\}$, either $s_{N+1} - s_1 = \Gamma_0$ or $s_1 = 0$.

Proof: We use the method of contradiction. Suppose the optimal policy say X , starts at $s_1 > 0$ and has transmission time $(s_{N+1} - s_1) < \Gamma_0$. We will generate another policy which has finish time less than that of X , having transmission time squeezed in between $(s_{N+1} - s_1)$ and Γ_0 . Consider policy Y ($\{\tilde{\mathbf{p}}, \tilde{\mathbf{s}}, N\}$) in relation to X , as defined in Lemma 4. As $\alpha, \beta, \delta, \gamma$ are all related (by constraints presented in Lemma 4), choice of one variable (we consider α) defines Y . By definition of s_i 's, s_2 is the

first energy arrival which is on the boundary of energy constraint (3) i.e. $U(s_2) = \mathcal{E}(s_2^-)$ and s_N is the last epoch satisfying $U(s_N) = \mathcal{E}(s_N^-)$. Hence, we can choose $\alpha > 0$, such that \tilde{p}_1 and \tilde{p}_N would be feasible with respect to energy constraint (3). Note that if $s_1 = 0$, then any value of α would have made \tilde{p}_1 infeasible.

From Lemma 4, we know that the transmission time of policy Y is more than that of X , i.e. $(\tilde{s}_{N+1} - \tilde{s}_1) > (s_{N+1} - s_1)$. From the hypothesis $(s_{N+1} - s_1) < \Gamma_0$. Therefore, let $(s_{N+1} - s_1) = \Gamma_0 - \epsilon$, with $\epsilon > 0$. If the chosen value of α is such that $\gamma - \delta \leq \epsilon$, then $(\tilde{s}_{N+1} - \tilde{s}_1) < \Gamma_0$. If not, then we can further reduce α so that $\gamma - \delta \leq \epsilon$ ($\alpha, \beta, \gamma, \delta$ being related by continuous functions). Note that, when $\epsilon = 0$, any choice of α would make $(\tilde{s}_{N+1} - \tilde{s}_1) > \Gamma_0$. Hence, with this choice of α , $(s_{N+1} - s_1) < (\tilde{s}_{N+1} - \tilde{s}_1) < \Gamma_0$ holds and policy Y contradicts the optimality of policy X (as finish time of Y , $\tilde{s}_{N+1} = s_{N+1} - \delta < s_{N+1}$ from Lemma 4). Thus $s_{N+1} - s_1 = \Gamma_0$ if $s_1 \neq 0$ in an optimal policy. ■

Theorem 1. A policy $\{\mathbf{p}, \mathbf{s}, N\}$ is an optimal solution to Problem 1 if and only if,

$$\sum_{i=1}^{i=N} g(p_i)(s_{i+1} - s_i) = B_0; \quad (5)$$

$$p_1 \leq p_2 \leq \dots \leq p_N; \quad (6)$$

$$s_i = \tau_j \quad \text{for some } j, i \in \{2, \dots, N\} \quad \text{and} \quad (7)$$

$$U(s_i) = \mathcal{E}(s_i^-), \quad \forall i \in \{2, \dots, N+1\};$$

$$s_{N+1} - s_1 = \Gamma_0, \quad \text{if } s_1 > 0 \quad \text{or} \quad (8)$$

$$s_{N+1} \leq \Gamma_0, \quad \text{if } s_1 = 0; \quad (8)$$

$$\exists s_j : s_j \in \mathbf{s} \text{ and } s_j = \tau_q, \quad (9)$$

where τ_q is defined in INIT_POLICY of section IV.

Proof: The necessity of these conditions is established in Lemmas 1-6. For lack of space, sufficiency proof is omitted. ■

IV. OPTIMAL OFFLINE ALGORITHM

In this section, we propose an offline algorithm OFF, and show that it satisfies the sufficiency conditions of Theorem 1. Algorithm OFF first finds an initial feasible solution via INIT_POLICY, and then iteratively improves upon it via PULL_BACK. Finally, QUIT produces the output.

A. INIT_POLICY

We find a simple constant power policy that is feasible and starts as early as possible. Also, we try to make it satisfy most of the sufficient conditions of Theorem 1.

Step1: Identify the first energy arrival instant τ_n , so that using $\mathcal{E}(\tau_n)$ energy and Γ_0 time, B_0 or more bits can be transmitted with a constant power (say p_c), i.e. $\Gamma_0 g\left(\frac{\mathcal{E}(\tau_n)}{\Gamma_0}\right) \geq B_0$. Then solve for $\tilde{\Gamma}_0$,

$$\tilde{\Gamma}_0 g\left(\frac{\mathcal{E}(\tau_n)}{\tilde{\Gamma}_0}\right) = B_0, \quad p_c = \frac{\mathcal{E}(\tau_n)}{\tilde{\Gamma}_0}. \quad (10)$$




Fig. 2. Figure showing point τ_q .




Fig. 3. Figures showing possible configurations in any iteration of the PULL_BACK. The solid line represents the transmission policy in the previous iteration and dash dotted lines are for the current iteration.

Step2: Find the earliest time T_{start} , such that transmission with power p_c from T_{start} for $\tilde{\Gamma}_0$ time, is feasible with energy constraint (3). Set $T_{stop} = T_{start} + \tilde{\Gamma}_0$. Let τ_q be the first epoch where $U(\tau_q) = \mathcal{E}(\tau_q^-)$ (Fig. 2). Next Lemma shows that point τ_q thus found is a ‘good’ starting solution.

Lemma 6. *In every optimal solution, at energy arrival epoch τ_q defined in INIT_POLICY, $U(\tau_q) = \mathcal{E}(\tau_q^-)$.*

Continuing with INIT_POLICY, if $U(T_{stop}) = \mathcal{E}(T_{stop}^-)$ as shown in Fig. 2(a), then terminate INIT_POLICY with constant power policy p_c .

Otherwise if $U(T_{stop}) < \mathcal{E}(T_{stop}^-)$, then modify the transmission after τ_q as follows. Set $\tilde{B}_0 = (T_{stop} - \tau_q)g(p_c)$, which denotes the number of bits left to be sent after time τ_q . Then apply Algorithm 1 of [5] from time τ_q to transmit \tilde{B}_0 bits in as minimum time as possible without considering the receiver on time constraint. Update T_{stop} , to where this policy ends. So, $U(T_{stop}) = \mathcal{E}(T_{stop}^-)$ from [5]. Since Algorithm 1 [5] is optimal, it takes minimum time ($= T_{stop} - \tau_q$) to transmit \tilde{B}_0 starting at time τ_q . However, using power p_c to transmit \tilde{B}_0 takes $(T_{start} + \tilde{\Gamma}_0 - \tau_q)$ time. Hence, $T_{stop} \leq (T_{start} + \tilde{\Gamma}_0)$. As $\tilde{\Gamma}_0 \leq \Gamma_0$ from (10), $(T_{stop} - T_{start}) \leq \Gamma_0$. This shows that solution thus found using Algorithm 1 [5], is indeed feasible with receiver time constraint (4). Now, output of INIT_POLICY is a policy that transmits at power p_c from T_{start} to τ_q , and after τ_q uses Algorithm 1 of [5].

B. PULL_BACK

Now, we describe the iterative subroutine PULL_BACK whose input is policy $\{\mathbf{p}, \mathbf{s}, N\}$ output by INIT_POLICY.

Clearly $\{\mathbf{p}, \mathbf{s}, N\}$ satisfies all but structure (8) of Theorem 1. So, the main idea of PULL_BACK is to increase the transmission duration from $(s_{N+1} - s_1) \leq \tilde{\Gamma}_0$, in INIT_POLICY, to Γ_0 in order to satisfy (8), while decreasing the finish time for reaching the optimal solution. To achieve this, we utilize the structure presented in Lemma 4 and iteratively increase the last transmission power p_N , and decrease the first transmission power p_1 .

Initialize $\tau_l = s_2, \tau_r = s_N, p_l = p_1, p_r = p_N, T_{start} = s_1, T_{stop} = s_{N+1}$. In any iteration, τ_l and τ_r are assigned to the first and last energy arrival epochs, where $U(\tau_l) = \mathcal{E}(\tau_l^-)$ and $U(\tau_r) = \mathcal{E}(\tau_r^-)$. p_l and p_r are the constant transmission powers before τ_l and after τ_r , respectively. We reuse the notation τ here, because τ_l and τ_r will occur at energy arrival epochs from Lemma 3. T_{start} and T_{stop} are the start and finish time of the policy, found in any iteration. $\tau_l, \tau_r, p_l, p_r, T_{start}, T_{stop}$ get updated to $\tau'_l, \tau'_r, p'_l, p'_r, T'_{start}, T'_{stop}$ over an iteration. In any iteration, only one of τ_l or τ_r gets updated, i.e., either $\tau'_l = \tau_l$ or $\tau'_r = \tau_r$. Further, PULL_BACK ensures that transmission powers between τ_l and τ_r do not get changed over an iteration. Fig. 3 shows the possible updates in an iteration of PULL_BACK.

Step1, Updation of τ_r, p_r : Initialize $p'_r = p_r$ and increase p'_r till it hits the boundary of energy constraint (3), say at $(\tau'_r, \mathcal{E}(\tau'_r^-))$ as shown in Fig. 3(a). The last epoch where p'_r hits (3) is set to τ'_r . So, $U(\tau'_r) = \mathcal{E}(\tau'_r^-)$. Set T'_{stop} to where power p'_r ends. Calculate p'_l such that decrease in bits transmitted due to change from p_r to p'_r is compensated by increasing p_l to p'_l , via

$$g(p_r)(T_{stop} - \tau_r) - g(p'_r)(T'_{stop} - \tau'_r) = g(p'_l) \frac{\mathcal{E}(\tau'_l^-)}{p'_l} - g(p_l)(\tau_l - T_{start}). \quad (11)$$

Suppose, p_r can be increased till infinity without violating (3), as shown in Fig. 3(b). This happens when there is no energy arrival between τ_r and T_{stop} . In this case, set p'_r to the transmission power at τ_r^- . Set τ'_r as the epoch where p'_r starts, and T'_{stop} to τ_r . Calculate p'_l similar to (11).

Step2, Updation of τ_l, p_l : If p'_l obtained from Step1 is feasible, as shown in Fig. 3(a), set $T'_{start} = \tau_l - \frac{\mathcal{E}(\tau'_l^-)}{p'_l}$, $\tau'_l = \tau_l$. Proceed to Step3. Otherwise, if p'_l is not feasible, as shown in Fig. 3(c), the changes made to τ'_r, p'_r in Step1 are discarded. As shown in Fig. 3 (d), p'_l is increased from its value in Step1 until it becomes feasible. τ'_l is set to the first epoch where $U(\tau'_l) = \mathcal{E}(\tau'_l^-)$. Similar to Step1, calculate p'_r such that the increase in bits transmitted due to change of p_l to p'_l is compensated, and update T'_{stop} accordingly. Set $\tau'_r = \tau_r$. Proceed to Step3.

Step3, Termination condition: If $T'_{stop} - T'_{start} \geq \Gamma_0$ or $T'_{start} = 0$, then terminate PULL_BACK. Otherwise, update $\tau_l, \tau_r, p_l, p_r, T_{start}, T_{stop}$ to $\tau'_l, \tau'_r, p'_l, p'_r, T'_{start}, T'_{stop}$ respectively and GOTO Step1.

Lemma 7. *Transmission time $(T_{stop} - T_{start})$ monotonically increases over each iteration of PULL_BACK.*

Theorem 2. *Worst case running time of PULL_BACK is linear with respect to the number of energy harvests before finish time of INIT_POLICY.*

Proof: Since, in an iteration of PULL_BACK, either τ_r or τ_l updates, the number of iterations is bounded by the values attained by τ_l , plus that of τ_r . Initially, $\tau_l \leq \tau_q$ and $\tau_r \geq \tau_q$. As τ_l is non-increasing across iterations, $\tau_l \leq \tau_q$ throughout. Assume that τ_r remains $\geq \tau_q$ across INIT_POLICY. Then, both τ_l and τ_r can at max attain all τ_i 's less than finish time of initial feasible policy. Hence, we are done.

Now, it remains to show that $\tau_r \geq \tau_q$. τ_n is defined as the first energy arrival epoch with which B_0 or more bits can be transmitted in Γ_0 time and $\tau_q \leq \tau_n$, by definition. So, when T_{stop} becomes $\leq \tau_n$ or τ_q , then transmission time, $(T_{stop} - T_{start})$, should be $> \Gamma_0$. But, in the initial iteration $(T_{stop} - T_{start}) \leq \Gamma_0$ and $(T_{stop} - T_{start})$ increases monotonically, from Lemma 7. Hence, PULL_BACK will terminate before T_{stop} (and therefore τ_r) decreases beyond τ_q . ■

C. QUIT

If $T'_{start} = 0$ and $T'_{stop} - T'_{start} \leq \Gamma_0$ upon PULL_BACK's termination, then PULL_BACK's policy at termination is output. Note that structure (8) holds for this policy. Otherwise, if $T'_{stop} - T'_{start} > \Gamma_0$ (which happens for the first time), then we know that in penultimate step $T_{stop} - T_{start} < \Gamma_0$. Hence, we are looking for a policy that starts in $[T_{start}, T'_{start}]$ and ends in $[T_{stop}, T'_{stop}]$, whose transmission time is equal to Γ_0 . Hence, we solve for x, y (let the solution be \hat{x}, \hat{y}),

$$\begin{aligned} (\tau_l - x) g \left(\frac{\mathcal{E}(\tau_l^-)}{\tau_l - x} \right) + (y - \tau_r) g \left(\frac{\mathcal{E}(T_{stop}^-)}{y - \tau_r} \right) \\ = g(p_l)(\tau_l - T_{start}) + g(p_r)(T_{stop} - \tau_r), \quad (12) \\ y - x = \Gamma_0. \quad (13) \end{aligned}$$

At penultimate iteration, $(x, y) = (T_{start}, T_{stop})$, (12) is satisfied and $y - x < \Gamma_0$. At $(x, y) = (T'_{start}, T'_{stop})$, as $\mathcal{E}(T_{stop}^-) = \mathcal{E}(T'_{stop}^-)$, (12) is satisfied and $y - x > \Gamma_0$. So, there must exist a solution (\hat{x}, \hat{y}) to (12), where $\hat{x} \in [T'_{start}, T_{start}]$, $\hat{y} \in [T'_{stop}, T_{stop}]$ and $\hat{y} - \hat{x} = \Gamma_0$, for which, (8) holds. Output with this policy which starts at \hat{x} and ends at \hat{y} .

Theorem 3. *The transmission policy proposed by Algorithm OFF is an optimal solution to Problem (1).*

Proof: We show that Algorithm OFF satisfies the sufficiency conditions of Theorem 1. To begin with, we prove that the power allocations satisfy (6) by induction. First we establish the base case that INIT_POLICY's output satisfies (6). If INIT_POLICY returns the constant power policy p_c from time T_{start} to T_{stop} , then clearly the claim holds.

Otherwise, INIT_POLICY applies Algorithm 1 from [5] with $\tilde{B} = B_0 - g(p_c)(\tau_q - T_{start})$ bits to transmit after time τ_q . Algorithm 1 from [5] ensures that transmission

powers are non-decreasing after τ_q . So we only prove that the transmission power p_c between time T_{start} and τ_q is \leq to the transmission power just after τ_q (say p_q), via contradiction. Assume that $p_q < p_c$. Let transmission with p_q end at an epoch $\tau_{q'}$, where $U(\tau_{q'}) = \mathcal{E}(\tau_{q'}^-)$ from [5]. The energy consumed between time τ_q to $\tau_{q'}$ with power p_c is,

$$p_c(\tau_{q'} - \tau_q) > p_q(\tau_{q'} - \tau_q) \stackrel{(a)}{=} (\mathcal{E}(\tau_{q'}^-) - \mathcal{E}(\tau_q^-)), \quad (14)$$

where (a) follows from $U(\tau_q) = \mathcal{E}(\tau_q^-)$. Further, the maximum amount of energy available for transmission between τ_q and $\tau_{q'}$ is $(\mathcal{E}(\tau_{q'}^-) - \mathcal{E}(\tau_q^-))$. By (14), transmission with p_c uses more than this energy and therefore it is infeasible between time τ_q and $\tau_{q'}$. But, by definition of p_c , transmission with power p_c is feasible till time $(T_{start} + \tilde{\Gamma}_0)$. Also, $\tau_{q'} \leq T_{stop}$ by definition of $\tau_{q'}$ and $T_{stop} \leq (T_{start} + \tilde{\Gamma}_0)$. So, power p_c must be feasible till $\tau_{q'}$ and we reach a contradiction.

Now, we assume that the transmission powers from PULL_BACK are non-decreasing till its n^{th} iteration. Therefore, as transmission powers between τ_l and τ_r does not change over an iteration, powers would remain non-decreasing in the $(n+1)^{th}$ iteration if we show that $p'_l < p_l$ and $p'_r > p_r$. In any iteration, by definition, either τ_l or τ_r updates. Assume τ_l gets updated to τ'_l , p_l to p'_l , p_r to p'_r and τ_r remains same, shown Fig. 3(d) (when τ_r updates, the proof follows similarly). Then we are certain that $p'_r > p_r$ by algorithmic steps. So from n^{th} to $(n+1)^{th}$ iteration, the number of bits transmitted after τ_r should decrease. Thus, the number of bits transmitted before τ_l must be increasing. This implies $p'_l \leq p_l$. Hence, transmission powers by output by OFF are non-decreasing and it satisfies (6).

Now consider structure (9). As τ_q is present in INIT_POLICY, the only way it cannot be part of the policy in an iteration of PULL_BACK is when τ_r decreases beyond τ_q . But $\tau_r \geq \tau_q$ as shown in Theorem 2. So, the policy output by OFF includes τ_q . By arguments presented at end of QUIT, we know that OFF satisfies (8). To conclude, OFF satisfies (5)-(9), hence is an optimal algorithm. ■

V. ONLINE ALGORITHM

In this section, we consider solving Problem (1) in the more realistic online scenario, where the transmitter and the receiver are assumed to have only causal information about energy arrivals. To consider the most general model, even the distribution of future energy arrivals is unknown at both the transmitter and the receiver. Moreover, we do not limit ourselves to just one energy arrival at receiver as done for the offline case.

Notation: Let $B_{rem}(t)$ and $E_{rem}(t)$ denote the remaining number of bits and energy left at transmitter at any time t , respectively for the online algorithm. In place of $\{p, s, N\}$ for the offline case, we use the notation $\{l, b, M\}$ to denote an online policy, with identical definitions. T_{online} and T_{off} represent the finish time of the online and the optimal offline




Fig. 4. An example for online algorithm.

algorithm to Problem (1), respectively. We use the competitive ratio as a metric where we say that an online algorithm is r -competitive, if over all possible energy arrivals at the transmitter and the receiver, the ratio of T_{online} to T_{off} is bounded by r , i.e., $\max_{\mathcal{E}(t), \Gamma(t) \forall t} \frac{T_{\text{online}}}{T_{\text{off}}} \leq r$.

Online Algorithm: The algorithm waits till time T_{start} which is the earliest energy arrival at transmitter or time addition at receiver such that using the energy $\mathcal{E}(T_{\text{start}})$ and time $\Gamma(T_{\text{start}})$, B_0 or more bits can be transmitted, i.e.,

$$T_{\text{start}} = \min t \text{ s.t. } \Gamma(t)g\left(\frac{\mathcal{E}(t)}{\Gamma(t)}\right) \geq B_0. \quad (15)$$

Starting at T_{start} , the algorithm transmits with power l_1 , such that $\frac{\mathcal{E}(T_{\text{start}})}{l_1}g(l_1) = B_0$. After T_{start} , at every τ_j , the transmission power is changed to l_j such that

$$\frac{E_{\text{rem}}(\tau_j)}{l_j}g(l_j) = B_{\text{rem}}(\tau_j). \quad (16)$$

Transmission power is not changed at any time arrival at the receiver after T_{start} , because there is sufficient receiver time already available to finish transmission.

Example: Fig. 4 shows the output of the proposed online algorithm, (15) is not satisfied at time τ_0 , r_1 , and τ_1 . At time r_2 , (15) is satisfied and transmission starts with a power l_1 such that at rate $g(l_1)$, B_0 bits can be sent in $\mathcal{E}(r_2)/l_1$ time. Transmission power changes to l_2 at time τ_2 such that $\frac{E_{\text{rem}}(\tau_2)}{l_2}g(l_2) = B_{\text{rem}}(\tau_2)$, and so on.

Lemma 8. *The transmission power in the online algorithm is non-decreasing with time.*

Proof: Combined with proof of Lemma 8. ■

Lemma 9. *If power at time t is l , then $\frac{\mathcal{E}(t)}{l}g(l) \leq B_0$, $\forall t \in [T_{\text{start}}, T_{\text{online}}]$, with equality only at $t = T_{\text{start}}$.*

Proof: It is enough to prove that $\frac{g(l_i)}{l_i} \leq \frac{B_0}{\mathcal{E}(b_i)}$ for $i \in \{1, \dots, M\}$, because both l_i and $\mathcal{E}(t)$ remains constant in $t \in [b_i, b_{i+1}]$. We prove this by induction on i in $\{1, 2, \dots, M\}$.

With $b_1 = T_{\text{start}}$, the base case follows since at time T_{start} , $\frac{\mathcal{E}(T_{\text{start}})}{l_1}g(l_1) = B_0$. Now, assume $\frac{g(l_i)}{l_i} \leq \frac{B_0}{\mathcal{E}(b_i)}$ to be true for $i = k-1$, $k \in \{2, \dots, M\}$. As $b_k = \tau_j$ for some j ,

$$\begin{aligned} \frac{l_k}{g(l_k)} &= \frac{E_{\text{rem}}(b_k)}{B_{\text{rem}}(b_k)} = \frac{E_{\text{rem}}(b_{k-1}) - l_{k-1}(b_k - b_{k-1}) + E_j}{B_{\text{rem}}(b_{k-1}) - g(l_{k-1})(b_k - b_{k-1})}, \\ &\stackrel{(a)}{=} \frac{l_{k-1}}{g(l_{k-1})} + \frac{E_j}{B_{\text{rem}}(b_{k-1})\gamma} \stackrel{(b)}{>} \frac{\mathcal{E}(b_{k-1})}{B_0} + \frac{E_j}{B_0} = \frac{\mathcal{E}(b_k)}{B_0}. \end{aligned}$$

where (a) follows from $\frac{B_{\text{rem}}(b_{k-1})}{E_{\text{rem}}(b_{k-1})} = \frac{g(l_{k-1})}{l_{k-1}}$ and defining $\gamma = \left(1 - \frac{l_{k-1}(b_k - b_{k-1})}{E_{\text{rem}}(b_{k-1})}\right) < 1$, (b) uses induction hypothesis along with $B_{\text{rem}}(b_{k-1})\gamma < B_0$. This completes the proof of

Lemma 9. From equality (a) we can see that $g(l_k)/l_k < g(l_{k-1})/l_{k-1}$. Hence, by monotonicity of $g(p)/p$, $l_k > l_{k-1}$. This proves Lemma 8 as well. ■

Lemma 10. *For the online algorithm, $T_{\text{start}} < T_{\text{off}}$.*

Proof: We use Contradiction. Suppose $T_{\text{start}} \geq T_{\text{off}}$. From (15), either $T_{\text{start}} = \tau_i$ for some i and/or $T_{\text{start}} = r_j$ for some j . Let $T_{\text{start}} = \tau_i$. Since, the offline algorithm $\{p, s, N\}$ finishes before T_{start} , the maximum (cumulative) energy utilized by the optimal offline algorithm is at most the energy arrived till time T_{start}^- . So, $\sum_{i:p_i \neq 0} p_i(s_{i+1} - s_i) \leq \mathcal{E}(T_{\text{start}}^-) = \mathcal{E}(T_{\text{start}}) - \mathcal{E}_i \neq \mathcal{E}(T_{\text{start}})$. Similarly, if $T_{\text{start}} = r_j$, then the maximum time for which the receiver can be on is $\Gamma(T_{\text{start}}^-)$. So, $\sum_{i:p_i \neq 0} (s_{i+1} - s_i) \leq \Gamma(T_{\text{start}}^-) = \Gamma(T_{\text{start}}) - \Gamma_j \neq \Gamma(T_{\text{start}})$.

Therefore, the total bits transmitted by the optimal offline algorithm $\{p, s, N\}$ is $\sum_{i=1, p_i \neq 0}^N g(p_i)(s_{i+1} - s_i)$

$$\begin{aligned} &\stackrel{(a)}{\leq} g\left(\frac{\sum_{i:p_i \neq 0} p_i(s_{i+1} - s_i)}{\sum_{j:p_j \neq 0} (s_{j+1} - s_j)}\right) \sum_{j:p_j \neq 0} (s_{j+1} - s_j), \\ &\stackrel{(b)}{\leq} g\left(\frac{\mathcal{E}(T_{\text{start}}^-)}{\Gamma(T_{\text{start}}^-)}\right) \Gamma(T_{\text{start}}^-) \stackrel{(c)}{<} B_0, \end{aligned} \quad (17)$$

where (a) follows from Jensen's inequality since $g(p)$ is concave, (b) follows from monotonicity of $g(p)/p$, and (c) follows from (15). (17) says that offline policy transmits less than B_0 bits and therefore, we arrive at a contradiction. ■

Theorem 4. *The proposed online algorithm is 2-competitive.*

Proof:

Let the online algorithm transmit with power l_k at time T_{off}^- . Since $T_{\text{start}} < T_{\text{off}}$ by Lemma 10, $l_k > 0$. Let $b_k < T_{\text{off}}$ be the time where transmission starts with power l_k . By definition, $\sum_{i=k}^M g(l_i)(b_{i+1} - b_i) = B_{\text{rem}}(b_k)$. From Lemma 8,

$$(b_{N+1} - b_k) \leq \frac{B_{\text{rem}}(b_k)}{g(l_k)} = \frac{E_{\text{rem}}(b_k)}{l_k} \leq \frac{\mathcal{E}(b_k)}{l_k} \leq \frac{\mathcal{E}(T_{\text{off}}^-)}{l_k}. \quad (18)$$

Applying Lemma 9 at time T_{off}^- ,

$$\frac{\mathcal{E}(T_{\text{off}}^-)}{l_k}g(l_k) \leq B_0 \stackrel{(a)}{\leq} T_{\text{off}}g\left(\frac{\mathcal{E}(T_{\text{off}}^-)}{T_{\text{off}}}\right), \quad (19)$$

where (a) holds because the maximum number of bits sent by the optimal offline policy by time T_{off} can be bounded by $T_{\text{off}}g\left(\frac{\mathcal{E}(T_{\text{off}}^-)}{T_{\text{off}}}\right)$ due to concavity of $g(p)$. By monotonicity of $g(p)/p$, from (19), it follows that $\frac{\mathcal{E}(T_{\text{off}}^-)}{l_k} \leq T_{\text{off}}$. Combining this with (18), $(b_{N+1} - b_k) \leq T_{\text{off}}$. As $b_k < T_{\text{off}}$, we calculate the competitive ratio as,

$$r = \max_{\mathcal{E}(t), \Gamma(t) \forall t} \frac{T_{\text{online}}}{T_{\text{off}}} = \frac{(b_{N+1} - b_k) + b_k}{T_{\text{off}}} < 2. \quad \blacksquare$$

Discussion: Theorem 4 is a significant result, since it tells us that the proposed online (causal) algorithm will finish in at most twice the time an optimal offline algorithm takes knowing all energy arrivals non-causally. Moreover, the online algorithm is independent of the energy arrival distributions both at the transmitter and the receiver, so has built-in robustness. Also, note that the proof of Theorem 4

does not explicitly require to know the exact structure of the optimal offline algorithm.

REFERENCES

- [1] O. Ozel and S. Ulukus, "Achieving AWGN capacity under stochastic energy harvesting," *IEEE Trans. Inf. Theory*, vol. 58, no. 10, pp. 6471–6483, 2012.
- [2] R. Rajesh, V. Sharma, and P. Viswanath, "Capacity of Gaussian channels with energy harvesting and processing cost," *IEEE Trans. Inf. Theory*, vol. 60, no. 5, pp. 2563–2575, May 2014.
- [3] Y. Dong, F. Farnia, and A. Ozgür, "Near optimal energy control and approximate capacity of energy harvesting communication," *arXiv preprint arXiv:1405.1156*, 2014.
- [4] A. Sinha and P. Chaporkar, "Optimal power allocation for a renewable energy source," in *Communications (NCC), 2012 National Conference on*. IEEE, 2012, pp. 1–5.
- [5] J. Yang and S. Ulukus, "Optimal packet scheduling in an energy harvesting communication system," *IEEE Trans. Commun.*, vol. 60, no. 1, pp. 220–230, 2012.
- [6] O. Ozel, K. Tutuncuoglu, J. Yang, S. Ulukus, and A. Yener, "Transmission with energy harvesting nodes in fading wireless channels: Optimal policies," *IEEE J. Sel. Areas Commun.*, vol. 29, no. 8, pp. 1732–1743, 2011.
- [7] N. Michelusi, K. Stamatiou, and M. Zorzi, "On optimal transmission policies for energy harvesting devices," in *Information Theory and Applications Workshop (ITA), 2012*. IEEE, 2012, pp. 249–254.
- [8] R. Vaze and K. Jagannathan, "Finite-horizon optimal transmission policies for energy harvesting sensors," in *International Conference on Acoustics, Speech, and Signal Processing (ICASSP)*. IEEE, 2014.
- [9] R. Vaze, "Competitive ratio analysis of online algorithms to minimize data transmission time in energy harvesting communication system," in *IEEE INFOCOM 2013*, Apr. 2013.
- [10] J. Doshi and R. Vaze, "Long term throughput and approximate capacity of transmitter-receiver energy harvesting channel with fading," in *to appear in IEEE ICCS 2014*, Nov. 2014.