WEI CHEN, Microsoft Research

QIANG LI, Institute of Computing Technology, Chinese Academy of Sciences XIAOMING SUN, Institute of Computing Technology, Chinese Academy of Sciences JIALIN ZHANG, Institute of Computing Technology, Chinese Academy of Sciences

In Kleinberg's small-world network model, strong ties are modeled as deterministic edges in the underlying base grid and weak ties are modeled as random edges connecting remote nodes. The probability of connecting a node  $u$  with node  $v$  through a weak tie is proportional to  $1/|uv|^\alpha,$  where  $|uv|$  is the grid distance between u and v and  $\alpha > 0$  is the parameter of the model. Complex contagion refers to the propagation mechanism in a network where each node is activated only after  $k \geq 2$  neighbors of the node are activated.

In this paper, we propose the concept of routing of complex contagion (or *complex routing*), where we can activate one node at one time step with the goal of activating the targeted node in the end. We consider decentralized routing scheme where only the weak ties from the activated nodes are revealed. We study the routing time of complex contagion and compare the result with simple routing and complex diffusion (the diffusion of complex contagion, where all nodes that could be activated are activated immediately in the same step with the goal of activating all nodes in the end).

We show that for decentralized complex routing, the routing time is lower bounded by a polynomial in n (the number of nodes in the network) for all range of  $\alpha$  both in expectation and with high probability (in particular,  $\Omega(n^{\frac{1}{\alpha+2}})$  for  $\alpha \leq 2$  and  $\Omega(n^{\frac{\alpha}{2(\alpha+2)}})$  for  $\alpha > 2$  in expectation), while the routing time of simple contagion has polylogarithmic upper bound when  $\alpha = 2$ . Our results indicate that complex routing is harder than complex diffusion and the routing time of complex contagion differs exponentially compared to simple contagion at sweetspot.

Categories and Subject Descriptors: J.4 [**Social and Behavioral Science**]: Sociology, Economic

General Terms: Algorithms, Performance, Theory

Additional Key Words and Phrases: Computational social science, complex contagion, diffusion, decentralized routing, small-world networks, social networks

### **1. INTRODUCTION**

Social networks are known to be the medium for spreading disease, information, ideas, innovations, and other types of behaviors. Social scientists have been studying social networks and diffusions in the networks for decades, and many of the research results are inspirational to researches in the intersection of social science, economics, and computation on modeling social networks and diffusions in them.

In the seminal work [\[Granovetter 1973,](#page-10-0) [1974\]](#page-10-1), Granovetter classified relationships in a social network as strong ties and weak ties. Strong ties represent close relationships, such as family members and close friends, while weak ties represent acquaintance relationship that people casually maintain. The surprising result in this study is that people often obtain important job referrals leading to their current jobs through weak ties instead of strong ties, which leads to the popular term *the strength of weak*

 c YYYY ACM 0000-0000/YYYY/01-ARTA \$15.00 DOI:http://dx.doi.org/10.1145/0000000.0000000

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies show this notice on the first page or initial screen of a display along with the full citation. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, to republish, to post on servers, to redistribute to lists, or to use any component of this work in other works requires prior specific permission and/or a fee. Permissions may be requested from Publications Dept., ACM, Inc., 2 Penn Plaza, Suite 701, New York, NY 10121-0701 USA, fax +1 (212) 869-0481, or permissions@acm.org.

*ties*. His research demonstrated the importance of weak ties in information diffusion in social networks. Another famous experiment related to information diffusion is Milgram's small-world experiment [\[Milgram 1967\]](#page-10-2), in which Milgram asked subjects to forward a letter to their friends in order for the letter to reach a person not known to the initiator of the letter. The result showed that on average it takes only six hops to connect two people in U.S. unknown to each other, hence the famous term of *six-degree of separation*.

The above studies motivated the modeling of small-world networks [\[Watts and Strogatz 1998](#page-10-3); [Kleinberg 2000](#page-10-4)]. Watts and Strogatz modeled the small-world network as a ring where nodes close to one another in ring distance are connected representing strong ties, and some strong ties are rewired to connect to other random nodes on the ring, which represent weak ties [\[Watts and Strogatz](#page-10-3) [1998](#page-10-3)]. They also proposed short diameter (the distance between any pair of nodes is small) and high clustering coefficient (the probability that two friends of a node are also friends of each other) as two characteristics of small-world networks. [Kleinberg](#page-10-4) [\[2000\]](#page-10-4) improved the model of Watts and Strogatz by building a small-world network on top of a base grid, where grid edges representing strong ties, and each node  $u$ initiating a weak tie connecting to another node  $v$  with probability proportional to  $1/|uv|^{\alpha}$ , where  $|uv|$  is the grid distance between u and v and  $\alpha$  is the small-world parameter. Kleinberg showed that when  $\alpha$  equals the dimension of the grid, the decentralized greedy routing, where in each routing step the current node routes the message to its neighbor with grid distance closest to the target node, achieves efficient routing performance [\[Kleinberg 2000](#page-10-4)]. This efficient decentralized routing behavior qualitatively matches the result of Milgram's small-world experiment. Kleinberg further showed that when  $\alpha$  is not equal to the grid dimension, no decentralized routing scheme could be efficient, and in particular, the small-world model of Newman and Watts [\[Newman and Watts 1999](#page-10-5)] corresponds to the one-dimensional Kleinberg's model with  $\alpha = 0$ . Kleinberg's small-world network model is the one we use in this paper.

In another work [\[Granovetter 1978\]](#page-10-6), Granovetter proposed the threshold model to characterize diffusions of rumors, innovations, or riot behaviors. An individual in a social network is activated by a certain behavior only when the number of her neighbors already adopting the behavior exceeds a threshold. This threshold model motivated the linear threshold, fixed threshold, and general threshold models proposed by Kempe et al. [\[Kempe et al. 2003](#page-10-7)], and is directly related to the model of complex contagion we use in this paper.

More recently, Centola and Macy [\[Centola and Macy 2007](#page-9-0)] classified the threshold model into simple contagion and complex contagion. Simple contagion refers to diffusion models with threshold being one on every node, which means that a node can be activated as long as there is one active neighbor. Simple contagion corresponds to diffusions of virus or simple information, where one can get activated by simply receiving the virus and information. Complex contagion, on the other hand, refers to diffusion models with threshold at least two, meaning that a node can be activated only after multiple of its neighbors are activated. Complex contagion corresponds to diffusions requiring complex decision process by individuals, such as adopting a costly new product, adopting a disruptive innovation, etc, where people usually need multiple independent sources of confirmation about the utility of the new product or new innovation before taking the action. The important point Centola and Macy argued is that, while weak ties are effective in transmitting information quickly across a long range in a network, they may not be as effective in complex contagion. This is because for complex contagions to spread quickly in a network, it requires weak ties forming not only long bridges connecting different regions of the network but also *wide* bridges

in the sense that many weak ties can work together to bring the contagion from one region of the network to another region of the network.

Motivated by the above work, Ghasemiesfeh et al. provided the first analytical study of complex contagion in small-world networks [\[Ghasemiesfeh et al. 2013](#page-10-8)]. They studied the diffusion of k-complex contagion (or k*-complex diffusion*), where all nodes have threshold k and all nodes with at least k active neighbors are activated right away. They showed that the *diffusion time*, which is the time for the diffusion to activate all nodes in a network starting from  $k$  initial seed nodes connected with strong ties, is polylogarithmic to the size of the network when  $\alpha = 2$ . [Ebrahimi et al.](#page-9-1) [\[2015\]](#page-9-1) further generalized the results and proved that the diffusion time for k-complex diffusion has polylogarithmic upper bound when  $\alpha \in (2, \frac{2(k^2+k+1)}{k+1})$ . They also show that in Kleinberg's model with  $\alpha$  outside this range, the diffusion time is lower bounded by a polynomial in n.

In this paper, we go beyond the diffusion of complex contagion (or *complex diffusion*), to study a new propagation phenomenon closer to decentralized routing in [\[Kleinberg](#page-10-4) [2000\]](#page-10-4), which we call the *routing of complex contagion* (or *complex routing*). In complex routing, we model weak ties as directed edges as in [\[Kleinberg 2000\]](#page-10-4), and study the time for two seed nodes connected by a strong tie to activate a target node  $t$  farthest on the grid (we call it the *routing time*). At each step only one new node can be activated, and the decision of which node to activate is decentralized which means it is only based on the current activated nodes and their strong tie neighbors and outgoing weak tie neighbors, same as decentralized routing in [\[Kleinberg](#page-10-4) [2000\]](#page-10-4). Such decentralized routing behavior corresponds to real-world phenomenon where a group of people want to influence a target person by influencing intermediaries between the source group and the target person, and influencing these intermediaries requires effort and thus has to be carried out one at a time. Active friending [\[Yang et al. 2013\]](#page-10-9) is an application similar to the above scenario recently proposed in the context of online social networks such as Facebook for increasing the chance of a target user accepting the friending request from the source.

### **1.1. Our results**

In this paper, we show that, unlike simple routing or complex diffusion, in complex routing problem for any  $k \geq 2$ , for the entire range of  $\alpha$ , the routing time is polynomial in  $n$  both in expectation and with high probability for any decentralized routing algorithm. Comparing with simple routing or complex diffusion, the results at the sweetspot of  $\alpha = 2$  are the most interesting: simple routing has routing time  $O(\log^2 n)$  in expectation [\[Kleinberg 2000\]](#page-10-4) and complex diffusion has an upper bound of  $O(\log^{k+1.5} n)$  in expected diffusion time [\[Ghasemiesfeh et al. 2013](#page-10-8)], while complex  $\text{round of } \Omega(n^{\frac{1}{4}}) \text{ in expected routing time, for any } k \geq 2. \text{ This expo-}$ nentially wide gap indicates intrinsic difference between complex routing and simple routing or complex diffusion. We further show that if we allow activating  $m$  nodes in one step, the routing time is lower bounded by  $\Omega(n^{\frac{1}{4}}/m)$ , which means that to get a polylogarithmic upper bound on the routing time  $m$  has to be  $\Omega(n^{\frac{1}{4}}/\log^c n)$  for some constant c.

Our main contribution is that we propose the study of complex routing, and prove that the routing time has polynomial lower bound in the entire range of  $\alpha$  for complex routing. Our results indicate that complex routing is harder than complex diffusion and the routing time of complex contagion differs exponentially compared to simple contagion at sweetspot.

### **1.2. Additional Related Work**

Social and information networks and network diffusions have been extensively studied, and a comprehensive coverage has been provided by recent textbooks such as [\[Easley and Kleinberg 2010](#page-9-2); [Newman 2010\]](#page-10-10). In this section, we provide most related work in addition to the ones already discussed in the introduction.

Since the proposal of the small-world network models by [\[Watts and Strogatz](#page-10-3) [1998](#page-10-3); [Kleinberg 2000\]](#page-10-4), many extensions and variants have been studied. For example, Kleinberg proposed a small-world model based on tree structure [\[Kleinberg](#page-10-11) [2001](#page-10-11)], Fraigniaud and Giakkoupis extended the model to allow power-law degree distribution [\[Fraigniaud and Giakkoupis 2009](#page-9-3)] or arbitrary base graph structure [\[Fraigniaud and Giakkoupis 2010\]](#page-10-12).

In terms of network diffusion, a line of research initiated by [Kempe et al. \[2003,](#page-10-7) [2005](#page-10-13)] studied the maximization problem of finding a set of small seeds to maximize the influence spread, usually under a stochastic diffusion model. For example, [Chen et al.](#page-9-4) [\[2009\]](#page-9-4) provided efficient influence maximization algorithms for large-scale networks, while [Chen \[2008\]](#page-9-5) proved that minimizing the size of the seed set for a given coverage in the fixed threshold model is hard to approximate to any polylogarithmic factor.

Threshold behavior is also studied in bootstrap percolation [\[Adler 1991](#page-9-6)], where all nodes have the same threshold and initial seeds are randomly selected. Bootstrap percolation focuses on the study of the critical fraction  $f$  of the seed nodes selected so that the entire network is infected in the end. The network structures investigated for bootstrap percolation include grid [\[Chalupa et al. 1979\]](#page-9-7), trees [\[Balogh et al. 2006\]](#page-9-8), random regular graphs [\[Balogh and Pittel 2007\]](#page-9-9), complex networks [\[Baxter et al. 2010](#page-9-10)] etc.

The rest of the paper is organized as follows. Section [2](#page-3-0) provides the technical model and problem definitions. Sections [3](#page-4-0) presents the results and analyses on complex routing. We conclude the paper in Section [4.](#page-9-11)

### <span id="page-3-0"></span>**2. MODEL AND PROBLEM DEFINITIONS**

We now provide the precise definitions of the network model, the propagation model, and the problems we are studying in this paper.

### **2.1. Kleinberg's Small-World Networks**

The Kleinberg's small-world network model defines a random graph based on a set  $V$ of *n* nodes organized in a  $\sqrt{n} \times \sqrt{n}$  two-dimensional grid [\[Kleinberg 2000\]](#page-10-4). For convenience, we connect the top boundary nodes of the grid with the corresponding bottom boundary nodes, and connect the left boundary nodes with the corresponding right boundary nodes, creating a two-dimensional torus, in which the positions of all nodes are symmetric. For nodes u and v on the torus, the Manhattan distance  $|uv|$  between them is the shortest distance from  $u$  to  $v$  (or  $v$  to  $u$ ) using grid edges.

There are two types of edges in this random graph: *strong ties* and *weak ties*. Strong ties refer to the undirected edges between any pair of nodes with Manhattan distance no more than p, where  $p \geq 1$  is a universal constant. Weak ties refer to random edges connecting any node u with other possibly remote nodes v in the grid. Each node u has q weak tie connections created independently from one another, and the **i-th** weak tie initiated by u has endpoint v with probability proportional to  $1/|uv|^{\alpha}$ , where  $\alpha \geq 0$ is a parameter of the model. In order to get the probability distribution of weak ties, we multiply  $1/|uv|^{\alpha}$  by the normalizing factor  $\mathcal{Z} = 1/\sum_{v \in V} |uv|^{-\alpha}$  (on a torus, this value is the same for any  $u \in V$ ). For a node u in the network, u's *grid-neighbors* are nodes linked with u through strong ties while *weak-neighbors* are nodes linked with u through weak ties.

The original network model by Kleinberg [\[Kleinberg 2000](#page-10-4)] considers the weak tie from u to v as a directed edge, and we call it the *directed Kleinberg's small-world network model*, while some work including [\[Ghasemiesfeh et al. 2013](#page-10-8)] considers the weak ties as undirected edges, and we call it the *undirected Kleinberg's small-world network model*. Define random graph  $G(n, k, \alpha)$  as directed Kleinberg's small-world network with *n* nodes and parameter  $\alpha$  and  $p = q = k$  and  $\tilde{G}(n, k, \alpha)$  as undirected network with the same setting. We consider directed network models in this paper.

### **2.2. Routing of Complex Contagion**

We model the propagation of information, disease, or innovations in a network as a *contagion*. Each node in a network has three possible states — *inactive*, *exposed*, *infected* (or *activated*), and a node can transition from the inactive state to the exposed state and then to the infected state, but not in the reverse direction.

A contagion proceeds in discrete time steps  $0, 1, 2, \ldots$  At time  $t \geq 1$ , a node becomes exposed if at time  $t-1$  at least k of its neighbors (or in-neighbors in the case of directed networks) are infected. An exposed node may become infected immediately or at a later step, which will be specified later. A *simple contagion* refers to the contagion with  $k = 1$ , that is, one infected neighbor is enough to expose (and potentially infect) the node, while a *complex contagion* refers to the case of  $k \geq 2$ , that is, at least two infected neighbors are needed to infect a new node. We refer the complex contagion with  $k \geq 2$ as k-complex contagion.

We study a different propagation phenomenon closer to the decentralized routing behavior studied in [\[Kleinberg 2000\]](#page-10-4) originally for the small-world network model, which we call *routing of complex contagion*, or simply *complex routing*.

To study k-complex routing, at time 0, we set k consecutive nodes on the grid in one dimension as infected initially, which we refer as *seed nodes*. For convenience, we also set  $p = k$ . When  $p = k$ , the k-complex routing is guaranteed to infect all nodes eventually through strong ties only. In complex routing, we have a target node  $t$  besides the set of  $k$  initial seed nodes.

The task is to infect or activate node  $t$  as fast as possible. We can only select one exposed node to activate at each time step. Moreover, when selecting the node to activate at time  $i$ , one only knows the out-neighbors of already activated nodes since decentralized routing is applied. This corresponds to the situation where a group of people try to influence a target by gradually growing their allies in the social network towards the target, and they only know the friends of their allies and try to recruit one of them into the allies at the next time step. Note that when  $k = 1$ , k-complex routing is essentially the decentralized simple routing studied in [\[Kleinberg 2000](#page-10-4)].

To study how fast the routing could be successful, we define the *routing time* as the number of time steps needed to activate the farthest target node  $t$  from the seed node in terms of the Manhattan distance.

## <span id="page-4-0"></span>**3. RESULTS ON COMPLEX ROUTING**

When studying complex routing, we use the directed Kleinberg's small-world network model, same as the model originally proposed by Kleinberg in [\[Kleinberg 2000](#page-10-4)] for decentralized routing. As described in the model, we consider decentralized routing in which a node can only send activation to its out-neighbors. Hence only when a node is pointed to by edges from  $k$  different activated nodes it becomes exposed. For the strong tie, we still treat them as undirected or bi-directional. In each time step, we only have the knowledge of the current activated nodes and the out-neighbors of the current activated nodes. This allows us to apply the Principle of Deferred Decisions [\[Motwani and Raghavan 1995](#page-10-14)] in the same way as applied in [\[Kleinberg 2000\]](#page-10-4), which means that the weak ties of a node  $u$  are defined and known only when  $u$  is activated. Initial seeds set is a set of  $k$  consecutive nodes, so the  $k$ -complex routing will eventually activate target t when we set  $p = k$  in Kleinberg's small-world network model.

We consider a 2-complex routing task from a pair of grid neighbor nodes  $S_0 = \{s_0^1, s_0^2\}$ to a destination  $t$  where  $s_0^1, s_0^2$  have Manhattan distance of 1 on the grid. In this paper, we discuss the routing with initial grid distance of  $|s_0^1 t| = \Theta(\sqrt{n})$ . The strategy of activating nodes from exposed nodes set is not restricted. A special scheme is choosing the node with smallest Manhattan distance to  $t$  in each time step, which is the greedy algorithm. But our result holds for any decentralized node selection schemes, even randomized ones. The following theorem provides the lower bound result on the routing time.

<span id="page-5-0"></span>THEOREM 3.1. *For any decentralized routing schemes (even randomized ones), the routing time of* 2*-complex routing in* G(n, 2, α) *has the following lower bounds based on the parameter*  $\alpha$ *, for any small*  $\varepsilon > 0$ *:* 

- (*1*) For  $\alpha \in [0,2)$ , the routing time is  $\Omega(n^{\frac{1-\varepsilon}{\alpha+2}})$  with probability at least  $1-O(n^{-\varepsilon})$  and *the expected routing time is*  $\Omega(n^{\frac{1}{\alpha+2}})$ *.*
- (2) For  $\alpha = 2$ , the routing time is  $\Omega(n^{\frac{1}{4}})$  with probability at least  $1 O(\frac{1}{\log n})$  and the  $expected\ routing\ time\ is\ \Omega(n^{\frac{1}{4}}).$
- (3) For  $\alpha \in (2, +\infty)$ , the routing time is  $\Omega(n^{\frac{\alpha-2\varepsilon}{2(\alpha+2)}})$  with probability at least  $1-O(n^{-\varepsilon})$ and the expected routing time is  $\Omega(n^{\frac{\alpha}{2(\alpha+2)}})$ .

First we give some necessary definitions. For a set of nodes S, define  $\mathcal{E}(S)$  to be the set of exposed nodes for the current activated set S, namely  $\mathcal{E}(S) = \{x \notin S\}$  $S \mid x$  has at least two in-neighbors in set  $S$ . In a routing protocol, let  $S_i$  be the set of the current activated nodes in time i. In time step i, we can choose at most *one* node  $u \in \mathcal{E}(S_{i-1})$ , and activate u (which means we add u to  $S_{i-1}$  in time i and obtain  $S_i$ ). From the definition of  $\mathcal{E}(S)$  we know that complex routing proceeds following the direction of edges in directed Kleinberg's small-world model.

In the following subsection, we first analyse the performance of the general routing scheme in directed Kleinberg's small-world model, and then generalize our result to complex routing allowing multiple activation in one time step.

### **3.1. Proof of Deterministic Scheme**

We consider deterministic decentralized routing schemes first, and in next subsection we will show that our lower bounds still hold for randomized schemes. First we give the proof of routing time for  $\alpha = 2$ .

<span id="page-5-1"></span>Suppose  $S_0, S_1, \dots, S_\ell$  is the sequence of activated sets of nodes in routing where  $S_i$  is the set of current activated nodes in time step *i*. The initial seeds are  $\{s_0^1, s_0^2\}$  so  $S_0 = \{s_0^1, s_0^2\}, S_i = \{s_0^1, s_0^2, s_1, \cdots, s_i\}$  and in time  $i \geq 1$  we add a new node  $s_i$  selected from  $\mathcal{E}(S_{i-1})$ , particularly  $s_l = t$ . Let  $d_i = d(S_i \cup \mathcal{E}(S_i), t)$ , where  $d(S, u)$  is the minimum Manhattan distance between node  $v \in S$  and u. It is easy to observe that  $d_i$  is a nonincreasing sequence and  $d_{\ell-1} = d_{\ell} = 0$ . For convenience, we write  $s_0^1$  as  $S_{-1}$  and define that  $d_{-1} = |s_0^1 t| = \sqrt{n}$ . We then prove that when the parameter  $\alpha = 2$ ,  $Pr(\forall 0 \le i <$  $cn^{\frac{1}{4}}, d_{i-1}-d_i\leq n^{\frac{1}{4}})$  is high enough, where  $c< 1$  is a positive constant we will set later. Define event  $\chi = \{ \forall \ 0 \le i < cn^{\frac{1}{4}}, d_{i-1} - d_i \le n^{\frac{1}{4}} \}$ . Event  $\chi$  means from time step 0 to  $cn^{1/4} - 1$ , the Manhattan distance between the current activated set and target t decrease at most  $n^{\frac{1}{4}}$  in each time step.

LEMMA 3.2. *For decentralized* 2*-complex routing in directed Kleinberg's small* $world$   $network$   $G(n, 2, \alpha)$   $with$   $\alpha = 2$ , given the initial seeds  $\{s_0^1, s_0^2\}$  and farthest target  $t$ with  $|s_0^1t| = \Theta(\sqrt{n})$ *, then for some suitable constant*  $c \in (0, 1)$ *,* 

$$
\Pr(\forall 0 \le i < cn^{\frac{1}{4}}, d_{i-1} - d_i \le n^{\frac{1}{4}}) \ge 1 - O(\frac{1}{\log n}).
$$

**PROOF.** Let  $u_i = \arg \min_x \{d(x, t)|x \in S_i \cup \mathcal{E}(S_i)\}\)$ , so  $u_i$  is the node that is closest to node t and can be activated by set  $S_i$  or belong to  $S_i$ . Since  $u_{i-1}$  is the node that with the shortest Manhattan distance to t among  $\mathcal{E}(S_{i-1}) \cup S_{i-1}$  and  $s_i \in \mathcal{E}(S_{i-1}),$  $|s_i t| \geq |u_{i-1} t| = d_{i-1}$ . Thus if  $d_{i-1} - d_i > 0$ , we know that  $s_i$  is not the node closest to t among  $S_i \cup \mathcal{E}(S_i)$  since  $|s_i t| \geq d_{i-1}$ . Besides, we can also get that  $u_i \in \mathcal{E}(S_i) \setminus \mathcal{E}(S_{i-1})$ and  $s_i$  activate  $u_i$  together with another node in  $S_{i-1}$ . Combining with the definition that  $|u_it|=d_i,$  we know  $|s_iu_i|\geq |s_it|-|u_it|=d_{i-1}-d_i.$  Hence we have the following conclusions:

If  $d_{i-1} - d_i > n^{1/4}$  for  $i \ge 1$ , then

- (1)  $|s_i u_i| > n^{\frac{1}{4}}$ .
- (2)  $u_i$  is one of the out-neighbors of  $s_i$ , more specifically,  $s_i$  initiates a weak tie to  $u_i$ .
- (3)  $u_i$  is exposed exactly in time step i, so there is exactly one weak tie from some node in  $S_{i-1}$  to  $u_i$ .

For  $i = 0$ , because  $d(S_0, t) = d_{-1}$ , so the gap between  $d_{-1}$  and  $d_0$  is caused by  $u_0 \in \mathcal{E}(S_0)$ . The conclusions still hold.

We define the set of nodes that are the endpoints of the weak ties initiated by  $S_{i-1}$  as  $X_i$ .  $X_i$  is indeed the set of weak-neighbors in directed Kleinberg's small-world network. Apparently  $u_i \in X_i$  according to assertion (3) above. If  $d_{i-1} - d_i > n^{\frac{1}{4}}$  happens,  $u_i$  can be reached by  $s_i$  with a weak tie of distance at least  $n^{\frac{1}{4}}$ . Define  $u \to v$  as node  $u$  initiates a weak tie with endpoint  $v$ . By union bound, we have:

<span id="page-6-0"></span>
$$
1 - \Pr(\forall 0 \le i < cn^{\frac{1}{4}}, d_{i-1} - d_i \le n^{\frac{1}{4}})
$$
  
=  $\Pr(\exists 0 \le i < cn^{\frac{1}{4}}, d_{i-1} - d_i > n^{\frac{1}{4}})$   
 $\le \sum_{i=0}^{cn^{\frac{1}{4}-1}} \Pr(d_{i-1} - d_i > n^{\frac{1}{4}})$   
 $\le \sum_{i=0}^{cn^{\frac{1}{4}-1}} \Pr(s_i \to u_i, |s_i u_i| > n^{\frac{1}{4}}, u_i \in X_i)$   
 $\le \sum_{i=0}^{cn^{\frac{1}{4}-1}} \Pr(\exists x \in X_i, s_i \to x, |s_i x| > n^{\frac{1}{4}}).$  (1)

Since there is  $i+1$  nodes in the set  $S_{i-1}$ ,  $S_{i-1}$  initiate  $q(i+1)$  weak ties, which means that  $|X_i| \le q(i+1)$ . Denote  $\mathcal{H}_i \subseteq 2^V$  to be the set of all sets of nodes with size no more than  $q(i + 1)$ . Then we fix the randomness of  $X_i$  and  $s_i$ :

$$
\Pr(\exists x \in X_i, s_i \to x, |s_i x| > n^{\frac{1}{4}})
$$
\n
$$
\leq \sum_{C \in \mathcal{H}_i} \sum_{v \in V} \Pr((X_i = C) \land (s_i = v) \land (\exists x \in C, v \to x, |vx| > n^{\frac{1}{4}}))
$$
\n
$$
= \sum_{C \in \mathcal{H}_i} \sum_{v \in V} \Pr((X_i = C) \land (s_i = v)) \Pr(\exists x \in C, v \to x, |vx| > n^{\frac{1}{4}})
$$
\n
$$
\leq \sum_{C \in \mathcal{H}_i} \sum_{v \in V} \Pr((X_i = C) \land (s_i = v)) \sum_{x \in C} \Pr(v \to x, |vx| > n^{\frac{1}{4}})
$$
\n
$$
\leq \sum_{C \in \mathcal{H}_i} \sum_{v \in V} \Pr((X_i = C) \land (s_i = v)) \cdot |C| \cdot 2\mathcal{Z} \frac{1}{n^{2 \cdot 1/4}}
$$
\n
$$
\leq q(i+1) \cdot 2 \frac{z}{n^{1/2}} \sum_{C \in \mathcal{H}_i} \sum_{v \in V} \Pr((X_i = C) \land (s_i = v)) = 2q(i+1) \cdot \frac{z}{n^{1/2}}.
$$

By the property of decentralized routing, event  $\{(X_i = C) \wedge (s_i = v)\}\)$  only depends on the random set  $S_{i-1}$  and the outgoing weak ties from  $S_{i-1}$ , and v is not in  $S_{i-1}$ , while event  $\{\exists x \in C, v \to x, |vx| > n^{\frac{1}{4}}\}$  only depends on the outgoing weak ties of the fixed node v. Thus event  $\{(X_i = C) \wedge (s_i = v)\}\$ is independent of event  $\{\exists x \in C, v \rightarrow v\}$  $x,|vx|>n^{\frac{1}{4}}\}.$  This gives us the first "=" in the equation. For a node  $x,$  if  $|vx|\leq n^{\frac{1}{4}}.$  then

A:8 W. Chen et al.

 $Pr(v \to x, |vx| > n^{\frac{1}{4}}) = 0$ ; otherwise,  $Pr(v \to x, |vx| > n^{\frac{1}{4}}) \leq 2p(v, x) \leq 2\mathcal{Z} \frac{1}{n^{2 \cdot 1/4}}$ . Hence we have the third "≤". Substitute it into Inequality [\(1\)](#page-6-0):

$$
1 - \Pr(\forall 0 \le i < cn^{\frac{1}{4}}, d_{i-1} - d_i \le n^{\frac{1}{4}})
$$
  
\n
$$
\le \sum_{i=0}^{cn^{\frac{1}{4}}-1} \Pr(\exists x \in X_i, s_i \to x, |s_i x| > n^{\frac{1}{4}})
$$
  
\n
$$
\le \sum_{i=0}^{cn^{\frac{1}{4}}-1} q(i+1) \cdot 2 \frac{z}{n^{1/2}}
$$
  
\n
$$
\le cn^{\frac{1}{4}} \cdot qcn^{\frac{1}{4}} \cdot \Theta(\frac{1}{\log n}) \frac{2}{n^{1/2}} = O(\frac{1}{\log n}).
$$

 $\Box$ 

Due to the above lemma, it is easy to see that the routing time is at least  $cn^{\frac{1}{4}}$  with high probability for  $\alpha = 2$ .

PROOF OF THEOREM [3.1](#page-5-0) (DETERMINISTIC ROUTING SCHEME). Lemma [3.2](#page-5-1) says, for  $\alpha = 2$ , in the first  $cn^{\frac{1}{4}}$  steps, the grid distance between the current activated set and target  $t$  decreases at most  $n^{\frac{1}{4}}$  in each step. Thus, for the first  $cn^{\frac{1}{4}}$  steps, target  $t$ does not belong to the activated set and the routing procedure will continue. Hence with probability of  $1-O(\frac{1}{\log n})$ , to activate the target  $t$  in  $G(n,2,\alpha)$  with  $\alpha=2,$  decentralized 2-complex routing needs at least  $cn^{\frac{1}{4}}$  time steps. The expected routing time is  $cn^{\frac{1}{4}} \cdot (1 - O(\frac{1}{\log n})) = \Omega(n^{\frac{1}{4}}).$ 

When  $\alpha \in [0, 2)$ , like the proof in Lemma [3.2,](#page-5-1) we can prove that for small  $\varepsilon > 0$ ,

$$
1 - \Pr(\forall 0 \le i < cn^{\frac{1-\varepsilon}{\alpha+2}}, d_{i-1} - d_i \le 2n^{\frac{\alpha+2\varepsilon}{2(\alpha+2)}})
$$
  
\n
$$
\le \sum_{i=0}^{cn^{\frac{1-\varepsilon}{\alpha+2}}-1} \Pr(\exists x \in X_i, s_i \to x, |s_i x| > 2n^{\frac{\alpha+2\varepsilon}{2(\alpha+2)}})
$$
  
\n
$$
\le \sum_{i=0}^{cn^{\frac{1-\varepsilon}{\alpha+2}}-1} 2(i+1) \cdot \mathcal{Z} \cdot 2(2n^{\frac{\alpha+2\varepsilon}{2(\alpha+2)}})^{-\alpha}
$$
  
\n
$$
\le cn^{\frac{1-\varepsilon}{\alpha+2}} \cdot 2cn^{\frac{1-\varepsilon}{\alpha+2}} \cdot \Theta(\frac{1}{n^{1-\alpha/2}}) \cdot O(n^{-\frac{\alpha(\alpha+2\varepsilon)}{2(\alpha+2)}}) = O(n^{-\varepsilon}).
$$

So the routing time is  $\Omega(n^{\frac{1-\varepsilon}{\alpha+2}})$  with probability at least  $1-O(n^{-\varepsilon}).$  By setting  $\varepsilon=0$ and adjusting the parameter  $c$ , the expected routing time can be obtained.

When  $\alpha > 2$ , we can prove that for small  $\varepsilon > 0$ ,

$$
\Pr(\forall \ 0 \le i < cn^{\frac{\alpha-2\varepsilon}{2(\alpha+2)}}, d_{i-1} - d_i \le n^{\frac{1+\varepsilon}{\alpha+2}}) \ge 1 - O(n^{-\varepsilon})
$$

like the proof above. Hence with probability at least  $1 - O(n^{-\epsilon})$ , we need  $cn^{\frac{\alpha-2\varepsilon}{2(\alpha+2)}}$  time steps to find the target. Similarly we can get the bound for the expectation.  $\Box$ 

### **3.2. Proof of Randomized Scheme**

The lower bound of routing time still holds for randomized decentralized routing scheme. Here we just provide a brief proof for the case when  $\alpha = 2$ .

PROOF OF THEOREM [3.1](#page-5-0) (RANDOMIZED ROUTING SCHEME). Let A be the set of all the deterministic decentralized routing schemes,  $\mathcal G$  be the set of all the possible networks based on Kleinberg's small-world model with  $\alpha = 2$  and  $\pi$  be the corresponding distributions over G. Further define  $T(A, G')$  as the routing time of an algorithm  $A \in \overline{\mathcal{A}}$ applied on a network  $G' \in \mathcal{G}$ .

Since a randomized algorithm is just a distribution over all deterministic algorithms, all we need to show is that for any distribution  $\mu$  over  $\mathcal{A}$ ,

<span id="page-7-0"></span>
$$
\Pr_{G' \sim \pi}(\mathbb{E}_{A \sim \mu}(T(A, G')) = \Omega(n^{1/4})) = 1 - O(\frac{1}{\log n}),\tag{2}
$$

which means that for any randomized scheme  $A$ , with high probability (w.r.t the distributions over G), the expected routing time of A is no less than  $\Omega(n^{1/4})$ . That is, any randomized scheme is slow for most of the input small-world networks.

From the previous proof we know any deterministic algorithms  $A \in \mathcal{A}$ ,  $\Pr_{G'\sim \pi}(T(A,\hat{G'}) = \Omega(n^{1/4})) = 1 - O(\frac{1}{\log n})$ . Thus there exists constant  $c_1, c_2 > 0$  not depending on the scheme A, such that  $\forall A \in \mathcal{A}$ ,  $\Pr_{G' \sim \pi}(T(A, G') \ge c_1 n^{1/4}) \ge 1 - \frac{c_2}{\log n}$ . Since it holds for all  $A \in \mathcal{A}$ , it is also true that

<span id="page-8-1"></span>
$$
\Pr_{\substack{G' \sim \pi \\ A \sim \mu}} (T(A, G') \ge c_1 n^{1/4}) \ge 1 - \frac{c_2}{\log n}.
$$
 (3)

.

We claim that

<span id="page-8-0"></span>
$$
\Pr_{G' \sim \pi}(\mathbb{E}_{A \sim \mu}(T(A, G')) \ge \frac{c_1}{2} n^{1/4}) \ge 1 - \frac{3c_2}{\log n},\tag{4}
$$

which is a quantitive version of Eq. [\(2\)](#page-7-0). Suppose Inequality [\(4\)](#page-8-0) is false, then

$$
\Pr_{G' \sim \pi}(\mathbb{E}_{A \sim \mu}(T(A, G')) < \frac{c_1}{2} n^{1/4}) > \frac{3c_2}{\log n}
$$

Let  $\mathcal{G}_1 \subseteq \mathcal{G}$  be the set of all the G' satisfies  $\mathbb{E}_{A\sim\mu}(T(A, G')) < \frac{c_1}{2}n^{1/4}$ , then the above inequality tells us that  $\Pr_{G'\sim \pi}(G'\in \mathcal{G}_1) > \frac{3c_2}{\log n}$ . For any fixed  $G'\in \mathcal{G}_1$ , by Markov Inequality

$$
\Pr_{A \sim \mu}(T(A, G') \ge c_1 n^{1/4}) \le \frac{\mathbb{E}_{A \sim \mu}(T(A, G'))}{c_1 n^{1/4}} < \frac{1}{2}.
$$

So  $Pr_{A\sim \mu}(T(A, G') < c_1 n^{1/4}) \geq 1/2$  for any  $G' \in \mathcal{G}_1$ . Therefore,

$$
\Pr_{\substack{A \sim \mu \\ G' \sim \pi}} (T(A, G') < c_1 n^{1/4}) > \frac{1}{2} \cdot \frac{3c_2}{\log n} = \frac{1.5c_2}{\log n},
$$

which contradict to Inequality [\(3\)](#page-8-1).  $\Box$ 

#### **3.3. Discussion and Extension**

We can obtain the same lower bound of routing time for k-complex routing. To ensure the success of complex routing, let  $p = q = k$  for the Kleinberg's small-world network model and the size of seed nodes is  $k$ . The result is the same with 2-complex routing so we omit it.

Next, we extend our results to complex routing where at most  $m$  nodes can be activated in each time step. When  $m = 1$ , the result is what we covered in Theorem [3.1](#page-5-0) for complex routing. When we do not restrict  $m$ , complex routing becomes complex diffusion. Thus a general  $m$  allows us to connect complex routing with diffusion, and see how large  $m$  is needed to bring down the polynomial lower bound in complex routing.

THEOREM 3.3. *In decentralized routing, for* k-complex routing in  $G(n, 2, \alpha)$  with  $\alpha =$  $2$ , if at most  $m$  nodes can be activated in each time step, routing time is  $\Omega(\frac{n^{1/4}}{m})$  with *probability at least*  $1 - O(\frac{1}{\log n})$  *and the expected routing time is*  $\Omega(\frac{n^{1/4}}{m}).$ 

PROOF. Assuming that  $S$  is the set of current activated nodes. In next time step, we can activate  $m$  nodes with the knowledge of the out-neighbors of  $S$ . But consider the original complex routing, we just activate one node in each step and we have  $m$ time steps to activate nodes. After each small step, we have the knowledge of the newly added node. Hence the method of activating m nodes with  $m$  time steps is more

ACM Journal Name, Vol. V, No. N, Article A, Publication date: January YYYY.

effective than infecting  $m$  nodes in just one time step. Therefore if we need  $T$  time steps to find the target with original complex-routing, the routing time with activating  $m$  nodes in each time step is at least  $\frac{T}{m}$ . The expected routing time is  $\frac{T}{m} \cdot (1 - O(\frac{1}{\log n})) =$  $\Omega(\frac{T}{m})$ . Then the theorem follows.

From the theorem we know that we would not get polylogarithmic routing time for complex routing where  $m$  nodes can be activated in each step, unless  $m = n^{\frac{1}{4}} / \log^{O(1)} n$ .

### <span id="page-9-11"></span>**4. CONCLUSION**

In this paper, we study the the routing of complex contagion in Kleinberg's small-world networks. We show that for complex routing the routing time is lower bounded by a polynomial in the number of nodes in the network for the entire range of  $\alpha$ , which is qualitatively different from the polylogarithmic upper bound in both complex diffusion and simple routing for  $\alpha = 2$ . Our results indicate that complex routing is much harder than complex diffusion and the routing time of complex contagion differs exponentially compared to simple contagion at sweetspot.

There are a number of future directions of this work. One may look into complex routing for undirected small-world networks or other variants of the small-world models. The qualitative difference between complex diffusion and complex routing for the case of  $\alpha = 2$  may worth further investigation. For example, one may study if there is similar difference for a larger class of graphs, and under what network condition complex routing permits polylogarithmic solutions.

### **REFERENCES**

- <span id="page-9-6"></span>ADLER, J. 1991. Bootstrap percolation. *Physica A: Statistical Mechanics and its Applications 171,* 3, 453–470.
- <span id="page-9-8"></span>BALOGH, J., PERES, Y., AND PETE, G. 2006. Bootstrap percolation on infinite trees and non-amenable groups. *Combinatorics, Probability & Computing 15,* 5, 715–730.
- <span id="page-9-9"></span>BALOGH, J. AND PITTEL, B. G. 2007. Bootstrap percolation on the random regular graph. *Random Structures & Algorithms 30,* 1-2, 257–286.
- <span id="page-9-10"></span>BAXTER, G., DOROGOVTSEV, S., GOLTSEV, A., AND MENDES, J. 2010. Bootstrap percolation on complex networks. *Physical Review E 82,* 1, 011103.
- <span id="page-9-0"></span>CENTOLA, D. AND MACY, M. 2007. Complex contagions and the weakness of long ties. *American Journal of Sociology 113,* 3, 702–734.
- <span id="page-9-7"></span>CHALUPA, J., LEATH, P., AND REICH, G. 1979. Bootstrap percolation on a bethe lattice. *Journal of Physics C: Solid State Physics 12,* 1, L31.
- <span id="page-9-5"></span>CHEN, N. 2008. On the approximability of influence in social networks. In *Proceedings of the nineteenth annual ACM-SIAM Symposium on Discrete Algorithms*. Society for Industrial and Applied Mathematics, 1029–1037.
- <span id="page-9-4"></span>CHEN, W., WANG, Y., AND YANG, S. 2009. Efficient influence maximization in social networks. In *Proceedings of the 15th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. ACM, 199–208.
- <span id="page-9-2"></span>EASLEY, D. AND KLEINBERG, J. 2010. *Networks, Crowds, and Markets: Reasoning about a Highly Connected World*. Vol. 8. Cambridge Univ Press.
- <span id="page-9-1"></span>EBRAHIMI, R., GAO, J., GHASEMIESFEH, G., AND SCHOENEBECK, G. 2015. Complex contagions in kleinberg's small world model. In *Proceedings of the 2015 Conference on Innovations in Theoretical Computer Science*. ACM, 63–72.
- <span id="page-9-3"></span>FRAIGNIAUD, P. AND GIAKKOUPIS, G. 2009. The effect of power-law degrees on the navigability of small worlds: [extended abstract]. In *Proceedings of the 28th Annual ACM Symposium on Principles of Distributed Computing*. 240–249.

- <span id="page-10-12"></span>FRAIGNIAUD, P. AND GIAKKOUPIS, G. 2010. On the searchability of small-world networks with arbitrary underlying structure. In *Proceedings of the 42nd ACM Symposium on Theory of Computing*. 389–398.
- <span id="page-10-8"></span>GHASEMIESFEH, G., EBRAHIMI, R., AND GAO, J. 2013. Complex contagion and the weakness of long ties in social networks: revisited. In *ACM Conference on Electronic Commerce*. 507–524.
- <span id="page-10-1"></span>GRANOVETTER, M. 1974. Getting a job: A study of contacts and careers.
- <span id="page-10-6"></span>GRANOVETTER, M. 1978. Threshold models of collective behavior. *American Journal of Sociology*, 1420–1443.
- <span id="page-10-0"></span>GRANOVETTER, M. S. 1973. The strength of weak ties. *American Journal of Sociology*, 1360–1380.
- <span id="page-10-7"></span>KEMPE, D., KLEINBERG, J., AND TARDOS, E. 2003. Maximizing the spread of influ- ´ ence through a social network. In *Proceedings of the ninth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. ACM, 137–146.
- <span id="page-10-13"></span>KEMPE, D., KLEINBERG, J., AND TARDOS, E. 2005. Influential nodes in a diffusion ´ model for social networks. In *Proceedings of the 32nd international conference on Automata, Languages and Programming*. Springer-Verlag, 1127–1138.
- <span id="page-10-4"></span>KLEINBERG, J. 2000. The small-world phenomenon: an algorithm perspective. In *Proceedings of the thirty-second annual ACM Symposium on Theory of Computing*. ACM, 163–170.
- <span id="page-10-11"></span>KLEINBERG, J. M. 2001. Small-world phenomena and the dynamics of information. In *Advances in Neural Information Processing Systems*. 431–438.
- <span id="page-10-2"></span>MILGRAM, S. 1967. The small world problem. *Psychology Today 2,* 1, 60–67.
- <span id="page-10-14"></span>MOTWANI, R. AND RAGHAVAN, P. 1995. *Randomized Algorithms*. Cambridge Univ Press.
- <span id="page-10-10"></span>NEWMAN, M. 2010. *Networks: An Introduction*. Oxford.
- <span id="page-10-5"></span>NEWMAN, M. E. AND WATTS, D. J. 1999. Scaling and percolation in the small-world network model. *Physical Review E 60,* 6, 7332.
- <span id="page-10-3"></span>WATTS, D. J. AND STROGATZ, S. H. 1998. Collective dynamics of small-world networks. *Nature 393,* 6684, 440–442.
- <span id="page-10-9"></span>YANG, D.-N., HUNG, H.-J., LEE, W.-C., AND CHEN, W. 2013. Maximizing acceptance probability for active friending in online social networks. In *Proceedings of the 15th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. 713–721.