Bayesian prediction of minimal repair times of a series system based on hybrid censored sample of components' lifetimes under Rayleigh distribution

S. M. T. K. MirMostafaee^{1,*}, Morteza Amini² and A. Asgharzadeh¹

¹Department of Statistics, Faculty of Mathematical Sciences, University of Mazandaran, P. O. Box 47416-1467, Babolsar, Iran

²Department of Statistics, School of Mathematics, Statistics and Computer Sciences, College of Science, University of Tehran, P.O. Box 14155-6455, Tehran, Iran

October 16, 2018

Abstract

In this paper, we develop Bayesian predictive inferential procedures for prediction of repair times of a series system, applying a minimal repair strategy, using the information contained in an independent observed hybrid censored sample of the lifetimes of the components of the system, assuming the underlying distribution of the lifetimes to be Rayleigh distribution. An illustrative real data example and a simulation study are presented for the purpose of illustration and comparison of the proposed predictors.

Keywords. Bayesian interval prediction; Bayesian point prediction; Coherent systems; Highest posterior density; Reliability.

^{*}Corresponding author.

E-mail addresses: *m.mirmostafaee@umz.ac.ir* (S. M. T. K. MirMostafaee), *morteza.amini@ut.ac.ir* (Morteza Amini), *a.asgharzadeh@umz.ac.ir* (A. Asgharzadeh).

1 Introduction

Suppose that a series system with k repairable and identical components is under operation. We assume that these k components work independently and that the lifetimes of all components are identically distributed. The lifetime of this system is equal to the minimum lifetime of its components. We also assume that the system is repaired using the minimal repair strategy. In a minimal repair strategy, after each failure, the corrupt component is immediately repaired and restored to its original condition, thus putting back the system into operation. Therefore, the state of the system after a repair is the same as it was immediately before corresponding failure. We shall assume that the time needed for repair and replacement is negligible. The minimal repair times possess the same joint distribution as upper record values from the distribution of the lifetime of the system, that is the distribution of record values from the distribution of the minimum of a sample of size k (see Barlow and Hunter, 1960). It has been verified that the sequence of record values, from the distribution of minimum in a sample of size k, and the sequence of k-record values, from the parent distribution, are identically distributed (see Arnold et. al., 1998, p. 43).

The results of this paper focus on predicting the minimal repair times of a series system based on an available hybrid censored sample of its components' lifetimes. Consider a sample of n units placed on a life-test at time 0. In Type-I censoring scheme, the test is terminated at a pre-fixed time T, while in Type-II censoring scheme, it is terminated as soon as a pre-determined number, $r \ (r \leq n)$, of units fail. Under Type-I censoring scheme, the duration of the life-test is guaranteed, while the number of failures is random, which might result in a low efficiency, when the number of failures is small. In Type-II censoring scheme, the level of efficiency is guaranteed, as the number of failures, r, is pre-fixed, while the exact time of the r^{th} failure is random, thus the duration of the experiment may end up being too long. The mixture of the Type-I and Type-II censoring schemes, called *hybrid censoring* scheme, proposed first by Epstein (1954), reduces the mentioned disadvantages. Under a Type-I hybrid censoring scheme, the experiment is terminated as soon as either r units fail or the time T is reached.

Hybrid censoring has received a considerable attention in the context of reliability and life-testing. Many authors, including Draper and Guttman (1987), Kundu and Gupta

(1988), Ebrahimi (1992), Childs et al. (2003), Kundu (2007) and Kundu and Banerjee (2008), have developed statistical inference based on hybrid censored sample. For a comprehensive review of hybrid censoring, see Balakrishnan and Kundu (2012).

The real data used in this paper includes the number of revolutions to failure of ball bearings under a life test, accelerated by hybrid censoring. The ball bearings are identical, thus the components' lifetimes follow the same distribution. The test is performed before placement of k identical ball bearings in a machine. The machine, made up of the k such identical components fails as soon as the first ball bearing fails, that is that the machine is a series system of k identical components. In the case of the failure, the physical and statistical (black box) minimal repair of the system are equivalent and are performed by minimal repair of the failed component. Our aim here is to predict the minimal repair times of this machine, using the information achieved from the available censored sample.

In this paper, we assume that the underlying lifetime distribution is the two parameter Rayleigh distribution, with cumulative distribution function (cdf),

$$F(x;\mu,\sigma) = \begin{cases} 0, & x \le \mu, \\ 1 - \exp\left\{-\frac{(x-\mu)^2}{2\sigma}\right\}, & x > \mu, \end{cases}$$
(1)

where $\mu \in \mathbb{R}$ and $\sigma > 0$. When $\mu = 0$, the distribution (1) is called the *scaled Rayleigh distribution*. The corresponding probability density function (pdf) of (1) is

$$f(x;\mu,\sigma) = \frac{(x-\mu)}{\sigma} \exp\left\{-\frac{(x-\mu)^2}{2\sigma}\right\}, \quad x > \mu.$$
(2)

The Rayleigh distribution is widely applied in several areas of statistics, partly because of its linear and increasing failure rate, which makes it an appropriate distribution for modeling the lifetime distribution of components, which age rapidly with time. Several types of electro-vacuum devices have this feature (Polovko, 1968). The Rayleigh distribution was originally introduced by Lord Rayleigh (1880, 1919) in connection with a problem in the field of acoustics. Wide applications of the Rayleigh distribution in lifetime analysis is mentioned by many authors, including Polovko (1968), Johnson et al. (1994), Dyer and Whisenand (1973), Gross and Clark (1976), Balakrishnan (1989) and Lawless (2003). The Rayleigh distribution relates to a number of well-known life distributions such as generalized extreme value, Weibull and Chi-square distributions (see Dey and Dey, 2014). There are many papers dealing with estimation and prediction under Rayleigh distribution, including Howlader (1985), Howlader and Hossain (1995), Fernández (2000), Raqab and Madi (2002), Ali Mousa and Al-Sagheer (2005), Dey and Das (2007), Soliman and Al-Aboud (2008), Khan et al. (2010), Dey and Dey (2012) and Abdel-Hamid and Al-Hussaini (2014).

Considerable work has been done on prediction of future records and order statistics, using parametric and nonparametric inferential methods. The following papers consider the Rayleigh distribution as the underlying distribution and develop predictive inferential methods for records and order statistics. Howlader (1985) obtained the highest posterior density (HPD) prediction intervals for future order statistics from an independent sample, based on an observed sample of order statistics. Fernandez (2000) considered the problem of Bayesian prediction of a future observation based on an observed Type-II doubly censored sample. Raqab and Madi (2002) developed Bayesian prediction of the total time on a test based on doubly censored sample. Ali Mousa and Al-Sagheer (2005) considered Bayesian prediction of a progressive censored sample on the basis of an observed progressively Type-II censored sample. Soliman and Al-Aboud (2008) derived Bayesian prediction intervals for a future record value based on an observed sample of record values. Recently, Khan et al. (2010) have develpeed Bayesian inference about a future order statistic on the basis of a doubly censored sample.

The observed sample and the predicted future observation might be either of the same type or of different types. Recently, Ahmadi and MirMostafaee (2009), Ahmadi and Balakrishnan (2010), Ahmadi et al. (2010) and MirMostafaee and Ahmadi (2011), have considered the problem of predicting future records from a sequence of observations on the basis of order statistics observed from another independent sample and vice versa. According to our best knowledge, there is a few number of similar works in the context of prediction of record values based on an available censored sample. These works use simple Type-II censored sample as the available data. The hybrid censoring is a mixture of the Type-I and Type-II censoring schemes. Thus the termination time of the experiment in hybrid censoring would decay stochastically with respect to Type-I and Type-II censoring schemes.

In this paper, we obtain several Bayesian point predictors as well as Bayesian prediction intervals for a future repair time of a k-component series system, applying a minimal repair strategy, on the basis of observed hybrid censored sample of its components lifetime, when the underlying distribution is assumed to be scaled or two parameter Rayleigh with cdf (1), and $\mu = 0$ or $\mu \in \mathbb{R}$, respectively.

The rest of this paper is organized as follows. Section 2 is devoted to the description of the model. In Section 3, we develop the main results. Sections 4 contains a real data example, which illustrate the results. A simulation study is presented in Section 5 for comparison of the performance of the proposed predictors.

2 The model

Suppose that *n* identical components are under a life test. Let X_1, \ldots, X_n denote the lifetimes of the experimental units and $X_{1:n} < \ldots < X_{n:n}$ stand for the corresponding order statistics. Furthermore, suppose that the experiment is terminated according to a hybrid censoring strategy. Under a hybrid censoring scheme, the experiment is terminated at time $T_0 = \min\{X_{r:n}, T\}, r \leq n$, where *r* and *T* are pre-determined values. The observed hybrid censored sample is therefore $\mathbf{X} = (X_{1:n} \ldots, X_{d:n})$, where $d = \max\{s : s \leq r, X_{s:n} \leq T\}$. To simplify the notation, we henceforth denote the hybrid censored sample by (X_1, X_2, \cdots, X_d) .

When X_1, \ldots, X_n are independent and identically distributed (iid) with the common absolutely continuous cdf F and corresponding pdf f, the joint pdf of the hybrid censored sample is

$$f_{X_1,\dots,X_d}(x_1,\dots,x_d) = C \prod_{i=1}^d f(x_i) [1 - F(T_0)]^{n-d},$$
(3)

where C is the normalizing constant.

Suppose that the test is performed before placement of k identical components in a machine. Assume further that the machine, made up of the k identical components, fails as soon as the first component fails, that is the machine is a series system of k identical components.

In the sequel, we develop Bayesian prediction of the repair times of this machine, repaired using a minimal repairing strategy, based on the available hybrid censored sample (X_1, X_2, \dots, X_d) . The future m^{th} repair time of a series system, with k independent and identical components, the lifetimes of which have the same distribution as X_1 , is denoted by $U_{m(k)}$. Let the sequence $\{Y_i\}_{i=1}^{\infty}$ be independent and identically distributed random variables, independent of the sample of component lifetimes, X_1, \ldots, X_n , each of which having the same distribution as X_1 . Also, let $Y_{j:n}$ stand for the j^{th} order statistic among Y_1, \ldots, Y_n . The repair time, $U_{m(k)}$, is distributed as $(T(m, k) - k + 1)^{\text{th}}$ order statistic among $Y_1, \ldots, Y_{T(m,k)}$, where T(1, k) = k and

$$T(m,k) = \min\{j : j > T(m-1,k), Y_j > Y_{T(m-1,k)-k+1:T(m-1,k)}\}$$

for $m \geq 2$.

Indeed, $U_{1(k)}, U_{2(k)}, \ldots$ is the sequence of current k^{th} largest Ys yet seen (see Arnold et al., 1998), that is $U_{m(k)}$ is identically distributed to the m^{th} k-record value.

The sequence $\{U_{m(k)}\}_{m\geq 1}$ from a cdf F is identical in distribution to a record sequence $\{U_{m(1)}\}_{m\geq 1}$ from the cdf of the minimum in a sample of size k, $F_{1:k} = 1 - (1 - F)^k$. Consequently, the pdf of $U_{m(k)}$ is given by (see Arnold et al., 1998)

$$f_{U_{m(k)}}(u;\theta) = \frac{k}{(m-1)!} \left[-\log(1 - F(u;\theta))^k \right]^{m-1} (1 - F(u;\theta))^{k-1} f(u;\theta).$$
(4)

For a comprehensive treatment and for references to the extensive literature on the topic of k-record statistics, one may refer to the books of Arnold et al. (1998) and Nevzorov (2001).

3 Main results

From (3), the likelihood function of $\theta = (\mu, \sigma)$, under the Rayleigh distribution in (1), is given by

$$L(\theta|\mathbf{x}) \propto \sigma^{-d} \left[\prod_{i=1}^{d} (x_i - \mu) \right] \exp\left\{ \frac{-1}{2\sigma} \left[\sum_{i=1}^{d} (x_i - \mu)^2 + (n - d)(T_0 - \mu)^2 \right] \right\}, \\ \mu < x_1, \ \sigma > 0.$$
(5)

Also, from (4), the pdf of $U_{m(k)}$, under the Rayleigh distribution in (1), is

$$f_{U_{m(k)}}(u|\theta) = \frac{k^m (u-\mu)^{2m-1}}{\Gamma(m)\sigma^m 2^{m-1}} \exp\left\{-\frac{k(u-\mu)^2}{2\sigma}\right\}, \quad u > \mu.$$
(6)

In the sequel, we provide the predictive inference, under both scaled and two parameter Rayleigh distributions.

3.1 Prediction of a repair time under the scaled Rayleigh distribution

For the scaled Rayleigh distribution (the case $\mu = 0$), we consider the non-informative prior

$$\pi_1(\sigma) \propto \frac{1}{\sigma}, \quad \sigma > 0.$$
(7)

From (5) and (7), the posterior density of σ is given by

$$\pi_1^*(\sigma | \mathbf{x}) = \frac{[\delta(\mathbf{x})]^d}{\Gamma(d) 2^d \sigma^{d+1}} \exp\left\{\frac{-\delta(\mathbf{x})}{2\sigma}\right\}, \quad \sigma > 0,$$
(8)

where

$$\delta(\mathbf{x}) = \sum_{i=1}^{d} x_i^2 + (n-d)T_0^2,$$
(9)

which is the pdf of an inverted gamma distribution with parameters d and $\frac{\delta(\mathbf{x})}{2}$.

From (8) and (6), the predictive density of $U_{m(k)}$, given $\mathbf{X} = \mathbf{x}$, is

$$f_{U_{m(k)}}^{*}(u|\mathbf{x}) = \int_{0}^{\infty} f_{U_{m(k)}}(u|\sigma)\pi_{1}^{*}(\sigma|\mathbf{x})d\sigma$$

$$= \int_{0}^{\infty} \frac{k^{m}u^{2m-1}[\delta(\mathbf{x})]^{d}}{\Gamma(m)\Gamma(d)\sigma^{m+d+1}2^{d+m-1}}\exp\left\{-\frac{ku^{2}+\delta(\mathbf{x})}{2\sigma}\right\} d\sigma$$

$$= \frac{2}{B(d,m)u}p_{k}(u;\mathbf{x})^{d}(1-p_{k}(u;\mathbf{x}))^{m}, \quad u > 0, \qquad (10)$$

where $B(\cdot, \cdot)$ is the complete beta function,

$$p_k(y; \mathbf{x}) = \frac{\delta(\mathbf{x})}{\delta(\mathbf{x}) + ky^2},\tag{11}$$

and $\delta(\cdot)$ is given in (9).

From (10), it follows that $p_k(U_{m(k)}; \mathbf{x}) | \mathbf{x} \sim Beta(d, m)$, hence

$$Pr(U_{m(k)} > z | \mathbf{x}) = Pr(p_k(U_{m(k)}; \mathbf{x}) < p_k(z; \mathbf{x}) | \mathbf{x})$$

= $I(d, m, p_k(z; \mathbf{x})), \quad z > 0,$ (12)

where $I(\gamma_1, \gamma_2, x)$ is the incomplete beta function,

$$I(\gamma_1, \gamma_2, x) = \int_0^x \frac{1}{B(\gamma_1, \gamma_2)} t^{\gamma_1 - 1} (1 - t)^{\gamma_2 - 1} \mathrm{d}t.$$

Remark 1 The prior used in (7) is a special case of the conjugate inverted gamma prior with pdf

$$\tilde{\pi}(\sigma) \propto \sigma^{-(a+1)} \exp\left\{-\frac{b}{\sigma}\right\}, \quad \sigma > 0,$$
(13)

where a and b are positive hyper-parameters. The prior $\tilde{\pi}(\sigma)$ tends to $\pi_1(\sigma)$ as $(a, b) \rightarrow (0, 0)$. Since then the variance of σ tends to infinity, we shall call $\pi_1(\sigma)$ the noninformative conjugate prior for σ .

3.1.1 Interval prediction of a repair time

A two-sided equi-tailed $100(1-\alpha)\%$ Bayesian prediction interval (PI) for $U_{m(k)}$, $m \ge 1$, is obtained from (12), as the interval $(L(\mathbf{x}), U(\mathbf{x}))$, for which

$$Pr(U_{m(k)} > L(\mathbf{x})|\mathbf{x}) = 1 - \frac{\alpha}{2}$$
 and $Pr(U_{m(k)} > U(\mathbf{x})|\mathbf{x}) = \frac{\alpha}{2}$

So, the interval $(L(\mathbf{x}), U(\mathbf{x}))$ is

$$\left(\sqrt{\frac{\left[1-\beta_{\frac{\alpha}{2}}(d,m)\right]\delta(\mathbf{x})}{k\beta_{\frac{\alpha}{2}}(d,m)}},\sqrt{\frac{\left[1-\beta_{1-\frac{\alpha}{2}}(d,m)\right]\delta(\mathbf{x})}{k\beta_{1-\frac{\alpha}{2}}(d,m)}}\right),\tag{14}$$

where $\beta_{\gamma}(n_1, n_2)$ denotes the upper γ^{th} quantile of the beta distribution with parameters n_1 and n_2 , i.e., $P(T > \beta_{\gamma}(n_1, n_2)) = \gamma$, with $T \sim Beta(n_1, n_2)$.

The highest posterior density prediction interval (HPD PI) is an interval, the posterior pdf for every point inside which is greater than that for every point outside of which. A HPD PI includes the more probable values of the parameter and excludes the less probable ones. Since the posterior pdf $f_{U_{m(k)}}^*(u|\mathbf{x})$ is unimodal and $p_k(u;\mathbf{x})$ is decreasing in u, the HPD PI, (w_1, w_2) , for $U_{m(k)}$ given $\mathbf{X} = \mathbf{x}$, with coverage probability $1 - \alpha$, is the simultaneous solution of

$$\frac{1}{B(d,m)} \int_{p_k(w_2;\mathbf{x})}^{p_k(w_1;\mathbf{x})} t^{d-1} (1-t)^{m-1} \mathrm{d}t = 1 - \alpha, \tag{15}$$

and

$$\left(\frac{w_1}{w_2}\right)^{2m-1} = \left(\frac{\delta(\mathbf{x}) + kw_1^2}{\delta(\mathbf{x}) + kw_2^2}\right)^{d+m}.$$
(16)

Remark 2 For m = 1, we have $U_{1(k)} = Y_{1:k}$, that is the lifetime of the series system, and the prediction interval (14) is simplified to

$$\left(\sqrt{\frac{\delta(\mathbf{X})}{k}\left\{\left(1-\frac{\alpha}{2}\right)^{-\frac{1}{d}}-1\right\}}, \sqrt{\frac{\delta(\mathbf{X})}{k}\left\{\left(\frac{\alpha}{2}\right)^{-\frac{1}{d}}-1\right\}}\right).$$
(17)

Also, the HPD PI, (w_1, w_2) , for $U_{1(k)}$ given $\mathbf{X} = \mathbf{x}$, with coverage probability $1 - \alpha$, is the simultaneous solution of

$$[p_k(w_1; \mathbf{x})]^d - [p_k(w_2; \mathbf{x})]^d = 1 - \alpha$$

and

$$w_1[p_k(w_1;\mathbf{x})]^{d+1} = w_2[p_k(w_2;\mathbf{x})]^{d+1}$$

3.1.2 Point prediction of a repair time

Using (10) and under the squared error loss (SEL) function, the Bayes point predictor of $U_{m(k)}$ is

$$\widehat{U}_{m(k)} = E(U_{m(k)}|\mathbf{x})
= \int_{0}^{\infty} \frac{2}{B(d,m)} p_{k}(u;\mathbf{x})^{d} (1 - p_{k}(u;\mathbf{x}))^{m} du
= \int_{0}^{1} \frac{\sqrt{\frac{\delta(\mathbf{x})}{k}}}{B(d,m)} z^{d-\frac{3}{2}} (1 - z)^{m-\frac{1}{2}} dz
= \frac{B(d - \frac{1}{2}, m + \frac{1}{2})}{B(d,m)} \sqrt{\frac{\delta(\mathbf{X})}{k}}.$$
(18)

Similarly, it can be verified that, under the absolute error loss (AEL) function and zero-one loss function, the Bayes point predictors of $U_{m(k)}$ are

$$\hat{U}_{m(k)}^* = \operatorname{Med}(U_{m(k)}|\mathbf{x}) = \sqrt{\frac{(1 - \operatorname{Med}(d, m))[\delta(\mathbf{X})]}{k\operatorname{Med}(d, m)}},$$

and

$$\widetilde{U}_{m(k)} = \operatorname{Mod}(U_{m(k)}|\mathbf{x}) = \sqrt{\frac{(2m-1)[\delta(\mathbf{X})]}{k(2d+1)}},$$

respectively, where Med(d, m) denotes the median of Beta distribution with parameters d and m.

3.2 Results for the two parameter Rayleigh distribution

To facilitate the Bayesian approach under the two parameter Rayleigh distribution, we assume independent prior distributions for the model parameters, that is

$$\pi(\mu,\sigma) \propto \pi_1(\sigma)\pi_2(\mu),\tag{19}$$

where $\pi_1(\sigma)$ is the non-informative conjugate prior in (7) and $\pi_2(\mu)$ is a normal density with mean ξ and variance $1/2\tau$, that is

$$\pi_2(\mu) \propto \exp\left\{-\tau(\mu-\xi)^2\right\}, \quad \mu \in \mathbb{R}, \quad \xi \in \mathbb{R}, \quad \tau > 0.$$
(20)

Therefore, the joint prior density is

$$\pi(\mu,\sigma) \propto \frac{1}{\sigma} \exp\left\{-\tau(\mu-\xi)^2\right\}, \quad \sigma > 0, \quad \mu \in \mathbb{R}, \quad \xi \in \mathbb{R}, \quad \tau > 0,$$
(21)

and the posterior density function of μ and σ , given $\mathbf{X} = \mathbf{x}$, is obtained as

$$\pi^*(\mu, \sigma | \mathbf{x}) = \frac{A_1(\mathbf{x}) \exp\left\{-\tau(\mu - \xi)^2\right\}}{\Gamma(d) 2^d \sigma^{d+1}} \left[\prod_{i=1}^d (x_i - \mu)\right] \exp\left\{\frac{-1}{2\sigma} [\delta^*(\mu | \mathbf{x})]\right\},$$
$$\sigma > 0, \quad \mu < x_1, \tag{22}$$

where

$$\delta^*(\mu|\mathbf{x}) = \sum_{i=1}^d (x_i - \mu)^2 + (n - d)(T_0 - \mu)^2$$
(23)

and

$$A_1(\mathbf{x})^{-1} = \int_{-\infty}^{x_1} \frac{\exp\left\{-\tau(\mu-\xi)^2\right\} \prod_{i=1}^d (x_i-\mu)}{[\delta^*(\mu|\mathbf{x})]^d} d\mu.$$
 (24)

The predictive posterior density of $U_{m(k)}$, given **x**, is obtained as follows

$$h_{U_{m(k)}}^{*}(u|\mathbf{x}) = \int_{-\infty}^{\min(u,x_{1})} \int_{0}^{\infty} f_{U_{m(k)}}(u|\mu,\sigma)\pi^{*}(\mu,\sigma|\mathbf{x})\mathrm{d}\sigma\mathrm{d}\mu$$
$$= \frac{2A_{1}(\mathbf{x})}{B(d,m)} \int_{-\infty}^{\min(u,x_{1})} \frac{g(t,u,m;\mathbf{x},\boldsymbol{\eta})}{u-t} \mathrm{d}t, \quad u \in \mathbb{R},$$
(25)

where $\boldsymbol{\eta} = (\tau, \xi, k, d)$ and

$$g(t, u, m; \mathbf{x}, \boldsymbol{\eta}) = \frac{k^m \exp\left\{-\tau (t - \xi)^2\right\} (u - t)^{2m} \prod_{i=1}^d (x_i - t)}{[k(u - t)^2 + \delta^*(t|\mathbf{x})]^{d+m}}.$$
(26)

The predictive posterior survival function of $U_{m(k)}$ is, for $z \ge x_1$,

$$\bar{H}_{U_{m(k)}}^{*}(z|\mathbf{x}) = \int_{-\infty}^{x_{1}} \int_{0}^{\infty} \int_{z}^{\infty} f_{U_{m(k)}}(u|\mu,\sigma)\pi_{2}^{*}(\mu,\sigma)\mathrm{d}u\mathrm{d}\sigma\mathrm{d}\mu$$

$$= A_{1}(\mathbf{x}) \sum_{j=0}^{m-1} \frac{\Gamma(d+j)}{\Gamma(d)j!} \int_{-\infty}^{x_{1}} g(t,z,j;\mathbf{x},\boldsymbol{\eta})\mathrm{d}t,$$
(27)

where $g(t, z, j; \mathbf{x}, \boldsymbol{\eta})$ is given in (26); and for $z < x_1$,

$$\bar{H}_{U_{m(k)}}^{*}(z|\mathbf{x}) = A_{1}(\mathbf{x}) \left[\sum_{j=0}^{m-1} \frac{\Gamma(d+j)}{\Gamma(d)j!} \int_{-\infty}^{z} g(t,z,j;\mathbf{x},\boldsymbol{\eta}) \, \mathrm{d}t + \int_{z}^{x_{1}} g(t,t,0;\mathbf{x},\boldsymbol{\eta}) \, \mathrm{d}t \right],$$
(28)

wherein 0^0 is defined to be 1 and g is given in (26).

3.2.1 Interval prediction of a repair time

The equi-tailed $100(1 - \alpha)$ % Bayesian prediction interval for $U_{m(k)}$ can be obtained numerically, using (27) and (28).

Since $h_{U_{m(k)}}^*(u|\mathbf{x})$ is unimodal, then the HPD PI, (w_1, w_2) , for $U_{m(k)}$, with coverage probability $1 - \alpha$, satisfies

$$\int_{w_1}^{w_2} h_{U_m(k)}^*(u|\mathbf{x}) du = 1 - \alpha$$

and

$$h_{U_{m(k)}}^*(w_1|\mathbf{x}) = h_{U_{m(k)}}^*(w_2|\mathbf{x}),$$

where $h^*_{U_{m(k)}}(u|\mathbf{x})$ is given in (25).

3.2.2 Point prediction of a repair time

Under the SEL function, the point predictor of $U_{m(k)}$ is given by

$$\begin{aligned}
\hat{U}_{m(k)} &= E(U_{m(k)}|\mathbf{x}) \\
&= A_1(\mathbf{x}) \left[\frac{\Gamma(m+1/2)\Gamma(d-1/2)}{\Gamma(m)\Gamma(d)\sqrt{k}} \int_{-\infty}^{x_1} \sqrt{\delta^*(t|\mathbf{x})} g(t,t,0;\mathbf{x},\boldsymbol{\eta}) \, \mathrm{d}t \\
&+ \int_{-\infty}^{x_1} t g(t,t,0;\mathbf{x},\boldsymbol{\eta}) \, \mathrm{d}t \right],
\end{aligned}$$
(29)

where g is given in (26).

For the AEL function, $U^*_{m(k)}$ can be obtained as

$$U^*_{m(k)} = \bar{H^*}_{U_{m(k)}}^{-1} \left(\frac{1}{2}\right)$$

Also, the point predictor $\tilde{U}_{m(k)}$, under the zero-one loss function is the unique mode of the pdf $h^*_{U_{m(k)}}(w|\mathbf{x})$ in (25).

3.3 Model checking

The assumption of independence of $\pi_1(\sigma)$ and $\pi_2(\mu)$ in (19) may affect on the performance of the predictors. Furthermore, as τ tends to zero, the prior $\pi_2(\mu)$ tends to a noninformative prior, while the mean square error of prediction,

$$\mathcal{E}(\widehat{U}_{m(k)} - U_{m(k)})^2,$$

increases. Hence, choosing a suitable value for τ is an important issue. It should be kept in mind that $\hat{U}_{m(k)}$ minimizes

$$\mathrm{E}[(g(\mathbf{x}) - U_{m(k)})^2 | \mathbf{x}),$$

over all functions g, while $E(\hat{U}_{m(k)} - U_{m(k)})^2$ can be greater or less than $E(U'_{m(k)} - U_{m(k)})^2 = 2Var(U_{m(k)})$, in which $U_{m(k)}$ and $U'_{m(k)}$ are iid random variables from the distribution (6). Hence, for the prior distribution in (19) to be sufficiently low informative, and for the mean square error of prediction not to be very large, one may choose τ such that

$$\frac{\mathrm{E}(U_{m(k)} - U_{m(k)})^2}{\mathrm{E}(U'_{m(k)} - U_{m(k)})^2}$$

takes its largest value less than or equal to 1.

To check the suitableness of the prior distribution in (19) and to choose a suitable value for τ , we perform a simulation study as follows. This study is based on the general method for model checking, described by Gelman et al. (2004).

The algorithm for model checking is as follows:

Algorithm:

(i) Generate x_1, \dots, x_n independently from Rayleigh distribution and extract the hybrid censored sample (x_1, \dots, x_d) from x_1, \dots, x_n .

- (ii) Generate $u_{m(k)}$ and $u'_{m(k)}$ independently from (6).
- (iii) Predict $u_{m(k)}^*$ using (29).
- (iv) Replicate (i)-(iii), N = 10000 times, independently, to obtain samples $u_{m(k)}^{(1)}, \ldots, u_{m(k)}^{(N)}$ and $u'_{m(k)}^{(1)}, \ldots, u'_{m(k)}^{(N)}$ as well as predicted values $u_{m(k)}^{*(1)}, \ldots, u_{m(k)}^{*(N)}$.
- (v) Compute

$$SS_1 = \frac{1}{N} \sum_{i=1}^{N} (u_{m(k)}^{(i)} - u_{m(k)}^{*(i)})^2$$

and

$$SS_2 = \frac{1}{N} \sum_{i=1}^{N} (u_{m(k)}^{(i)} - u'_{m(k)}^{(i)})^2.$$

- (vi) Set $\xi = 0$ and choose l^* from the set $\{-2, -1, \dots, 2\}$, such that, for $\tau^* = 0.5 \times 10^{-l^*}$, $D_1 = SS_1/SS_2$ takes its largest value less than or equal to 1.
- (vii) For $\xi = 0$ and $\tau = \tau^*$, compute

$$D_2 = \frac{\frac{1}{N} \sum_{i=1}^{N} (u_{m(k)}^{(i)} - \mu)}{\frac{1}{N} \sum_{i=1}^{N} (u_{m(k)}^{*(i)} - \mu)}$$

and

$$D_{3} = \frac{\frac{1}{N} \sum_{i=1}^{N} (u_{m(k)}^{(i)})^{2} - \left(\frac{1}{N} \sum_{i=1}^{N} u_{m(k)}^{(i)}\right)^{2}}{\frac{1}{N} \sum_{i=1}^{N} (u_{m(k)}^{*(i)})^{2} - \left(\frac{1}{N} \sum_{i=1}^{N} u_{m(k)}^{*(i)}\right)^{2}}.$$

Table 1 presents the values of τ^* , D_1 , D_2 and D_3 , for m = 3, k = 2, $\mu = 0$, $\sigma = 1$, $\xi = 0$ and $\tau = \tau^*$. Also, empirical cdfs of the simulated values, $u_{m(k)}^{(1)}, \ldots, u_{m(k)}^{(N)}$, and the predicted values, $u_{m(k)}^{*(1)}, \ldots, u_{m(k)}^{*(N)}$, are shown in Figure 1, for m = 3, k = 2, $\mu = 0$, $\sigma = 1$, $\xi = 0$, $\tau = \tau^*$ and different values of n and (r, T). As one can see from Table 1 and Figure 1, for a sufficiently low informative prior, the predicted values have smaller variance and mean square error of prediction than the simulated values. The ignorable bias of the predicted values decreases as n and/or r get large. Hence, the prior (19) results in efficient predictors.



Figure 1: Empirical cdfs of the simulated values, $u_{m(k)}^{(1)}, \ldots, u_{m(k)}^{(N)}$ (solid line), and the predicted values, $u_{m(k)}^{*(1)}, \ldots, u_{m(k)}^{*(N)}$ (dashed line), for $m = 3, k = 2, \mu = 0, \sigma = 1, \xi = 0, \tau = \tau^*$ and different values of n and (r, T). 14

Table 1: The values of τ^* , D_1 , D_2 and D_3 , for m = 3, k = 2, $\mu = 0$, $\sigma = 1$, $\xi = 0$ and $\tau = \tau^*$.

n	(r,T)	$ au^*$	D_1	D_2	D_3
10	(5,2)	0.5	0.9426	0.9330	1.2006
	(5, 2.5)	0.5	0.9417	0.9348	1.2513
	(8,2)	0.005	0.8605	0.9441	1.5197
	(8, 2.5)	0.005	0.7295	0.9508	2.2776
20	(10,2)	0.05	0.7160	0.9577	2.5605
	(10, 2.5)	0.005	0.7143	0.9561	2.4767
	(16, 2)	0.005	0.6188	0.9750	4.3192
	(16, 2.5)	0.005	0.6125	0.9806	5.1078
30	(15,2)	0.05	0.6302	0.9740	4.2603
	(15, 2.5)	0.005	0.6262	0.9758	4.1887
	(24,2)	0.005	0.5595	0.9852	6.9719
	(24, 2.5)	0.005	0.5714	0.9858	7.8098

4 Illustrative example: groove ball bearings data set

In this section, we illustrate the proposed procedures in the previous section, using the following real data example.

Example 4.1 Consider the endurance test of deep groove ball bearings, discussed by Leiblein and Zelen (1956), which includes the number of revolutions (in hundreds of millions) to failure, for each of n = 23 ball bearings, as follows:

```
0.1788 0.2892 0.3300 0.4152 0.4212 0.4560 0.4880 0.5184 0.5196 0.5412
0.5556 0.6780 0.6864 0.6864 0.6888 0.8412 0.9312 0.9864 1.0512 1.0584
1.2792 1.2804 1.7340.
```

The adequacy of the fitness of the two parameter Rayleigh distribution with $\hat{\mu} = 0.1788$ and $\hat{\sigma} = 0.2149$ to the data is tested using the Kolmogorov-Smirnov (K-S) test. The value of K-S test statistic is obtained as D = 0.1982 with a corresponding *p*-value=0.3269. Hence, the two parameter Rayleigh distribution fits the data quite well.

Consider the following two sampling schemes:

• Scheme 1: r = 20 and T = 1.25. We have, d = r = 20, $T_0 = \min\{x_{r:n}, T\} = 1.0584$, and the hybrid censored sample is

0.1788 0.2892 0.3300 0.4152 0.4212 0.4560 0.4880 0.5184 0.5196 0.5412 0.5556 0.6780 0.6864 0.6864 0.6888 0.8412 0.9312 0.9864 1.0512 1.0584.

• Scheme 2: r = 20 and T = 1.

We have, in this case, d = 18, $T_0 = 1$ and the hybrid censored sample is

0.1788 0.2892 0.3300 0.4152 0.4212 0.4560 0.4880 0.5184 0.5196 0.5412 0.5556 0.6780 0.6864 0.6864 0.6888 0.8412 0.9312 0.9864.

To obtain stable Bayesian predictors, we need to choose suitable values for the hyperparameters ξ and τ , which ensures that the prior distribution is sufficiently low-informative. This is performed through a sensitivity analysis in the next subsection.

4.1 Sensitivity analysis

In order to check the effect of hyper-parameters ξ and τ on Bayesian predictors, we consider a pilot run on the prediction procedure, for various values of ξ and τ . As $\tau \to 0$, the variance of the normal prior for the parameter μ tends to infinity, which is the noninformative case. As the variance of the normal prior increases, the effect of the hyperparameter ξ on the predictors decreases. Therefore, many authors perform the sensitivity analysis on the hyper-parameter τ , assuming ξ to be fixed as $\xi = 0$. So, we take $\xi = 0$ and focus on a sequence of values of τ , tending to 0. Figure 2 shows the plot of $\hat{U}_{m(k)}$ versus values of l, for $\tau = 0.5 \times 10^{-l}$, and different values of m and k, when $\xi = 0$. Figure 2 shows that for $\tau \geq 0.5$, the values of $\hat{U}_{m(k)}$ tend to be very close to each other. Therefore, $\tau = 0.5$ and $\xi = 0$ are suitable hyper-parameters for obtaining stable Bayesian predictors.

4.2 Bayesian prediction

Here, for the sake of comparison of the performance of the predictors, we take k = 1, 2, 3and $m = 1, \ldots, 4$.



Figure 2: Sensitivity analysis for different values of m and k. Plot of the posterior mean versus values of l for $\tau = 0.5 \times 10^{-l}$.

			Scheme 1			
	m	Equi-tailed PI [width]	HPD PI [width]	$\widehat{U}_{m(k)}$	$\hat{U}^*_{m(k)}$	$\tilde{U}_{m(k)}$
	1	(0.1575, 1.5235) $[1.3660]$	(0.1004, 1.4219) $[1.3215]$	0.7111	0.6663	0.5692
	2	(0.4070, 1.8904) $[1.4834]$	(0.3468, 1.7975) $[1.4507]$	1.0402	1.0027	0.9302
k = 1	3	(0.6175, 2.1717) $[1.5542]$	(0.5567, 2.0811) $[1.5244]$	1.2870	1.2498	1.1796
	4	(0.7965, 2.4113) [1.6148]	(0.7337, 2.3184) [1.5847]	1.4928	1.4542	1.3825
	1	(0.1105, 1.0894) $[0.9789]$	(0.0736, 1.0329) $[0.9593]$	0.5183	0.4895	0.4260
	2	(0.2966, 1.3448) $[1.0482]$	(0.2580, 1.2885) $[1.0305]$	0.7510	0.7268	0.6798
k = 2	3	(0.4495, 1.5408) $[1.0913]$	(0.4099, 1.4839) $[1.0740]$	0.9255	0.9014	0.8556
	4	(0.5790, 1.7078) [1.1288]	(0.5377, 1.6485) $[1.1108]$	1.0710	1.0459	0.9989
	1	(0.0851, 0.8988) $[0.8137]$	(0.0584, 0.8616) $[0.8032]$	0.4329	0.4114	0.3632
	2	(0.2445, 1.1051) $[0.8606]$	(0.2160, 1.0656) $[0.8496]$	0.6229	0.6048	0.5693
k = 3	3	(0.3724, 1.2633) $[0.8909]$	(0.3424, 1.2219) $[0.8795]$	0.7654	0.7472	0.7124
	4	(0.4801, 1.3982) $[0.9181]$	(0.4485, 1.3542) $[0.9057]$	0.8842	0.8650	0.8291
			Scheme 2			
	m	Equi-tailed PI [width]	HPD PI [width]	$\widehat{U}_{m(k)}$	$\hat{U}^*_{m(k)}$	$\tilde{U}_{m(k)}$
	m 1	Equi-tailed PI [width] (0.1487,1.5871) [1.4384]	HPD PI [width] (0.0880,1.4792) [1.3912]	$ \widehat{U}_{m(k)} 0.7291 $	$\hat{U}^*_{m(k)}$ 0.6811	$\frac{\tilde{U}_{m(k)}}{0.5785}$
	m 1 2	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310]	$ \widehat{U}_{m(k)} $ 0.7291 1.0737	$ \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 $	$\tilde{U}_{m(k)}$ 0.5785 0.9526
k = 1	m 1 2 3	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155]	$ \hat{U}_{m(k)} 0.7291 1.0737 1.3322 $	$ \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 $	$\begin{array}{c} \tilde{U}_{m(k)} \\ 0.5785 \\ 0.9526 \\ 1.2112 \end{array}$
k = 1	m 1 2 3 4	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517] (0.8143,2.5383) [1.7240]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864]	$ \hat{U}_{m(k)} 0.7291 1.0737 1.3322 1.5476 $	$ \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 \\ 1.5031 $	$\begin{array}{c} \tilde{U}_{m(k)} \\ 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \end{array}$
k = 1	m 1 2 3 4 1	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517] (0.8143,2.5383) [1.7240] (0.0980,1.1290) [1.0310]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864] (0.0592,1.0700) [1.0108]	$\begin{array}{c} \widehat{U}_{m(k)} \\ 0.7291 \\ 1.0737 \\ 1.3322 \\ 1.5476 \\ 0.5272 \end{array}$	$\hat{U}^*_{m(k)}$ 0.6811 1.0320 1.2898 1.5031 0.4967	$\begin{array}{c} \tilde{U}_{m(k)} \\ \hline 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \\ \hline 0.4302 \end{array}$
k = 1	m 1 2 3 4 1 2	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517] (0.8143,2.5383) [1.7240] (0.0980,1.1290) [1.0310] (0.2947,1.4011) [1.1064]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864] (0.0592,1.0700) [1.0108] (0.2527,1.3390) [1.0863]	$\begin{array}{c} \widehat{U}_{m(k)} \\ 0.7291 \\ 1.0737 \\ 1.3322 \\ 1.5476 \\ 0.5272 \\ 0.7709 \end{array}$	$\begin{array}{c} \hat{U}^{*}_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 \\ 1.5031 \\ 0.4967 \\ 0.7442 \end{array}$	$\begin{array}{c} \tilde{U}_{m(k)} \\ \hline 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \\ \hline 0.4302 \\ 0.6931 \end{array}$
k = 1 k = 2	$egin{array}{c} m & & \\ 1 & 2 & \\ 3 & 4 & \\ 1 & 2 & \\ 3 & & \\ \end{array}$	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517] (0.8143,2.5383) [1.7240] (0.0980,1.1290) [1.0310] (0.2947,1.4011) [1.1064] (0.4543,1.6108) [1.1565]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864] (0.0592,1.0700) [1.0108] (0.2527,1.3390) [1.0863] (0.4102,1.5461) [1.1359]	$\begin{array}{c} \widehat{U}_{m(k)} \\ 0.7291 \\ 1.0737 \\ 1.3322 \\ 1.5476 \\ 0.5272 \\ 0.7709 \\ 0.9536 \end{array}$	$\begin{array}{c} \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 \\ 1.5031 \\ 0.4967 \\ 0.7442 \\ 0.9263 \end{array}$	$\begin{array}{c} \tilde{U}_{m(k)} \\ 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \\ \hline 0.4302 \\ 0.6931 \\ 0.8754 \end{array}$
k = 1 k = 2	$egin{array}{c} m & & \ 1 & \ 2 & \ 3 & \ 4 & \ 1 & \ 2 & \ 3 & \ 4 & \ 3 & \ 4 & \ 3 & \ 4 & \ 1 & \ 2 & \ 3 & \ 4 & \ 1 & \ 1 & \ 2 & \ 3 & \ 4 & \ 1 & $	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517] (0.8143,2.5383) [1.7240] (0.0980,1.1290) [1.0310] (0.2947,1.4011) [1.1064] (0.4543,1.6108) [1.1565] (0.5888,1.7901) [1.2013]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864] (0.0592,1.0700) [1.0108] (0.2527,1.3390) [1.0863] (0.4102,1.5461) [1.1359] (0.5422,1.7212) [1.1790]	$\begin{array}{c} \widehat{U}_{m(k)} \\ 0.7291 \\ 1.0737 \\ 1.3322 \\ 1.5476 \\ 0.5272 \\ 0.7709 \\ 0.9536 \\ 1.1060 \end{array}$	$\begin{array}{c} \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 \\ 1.5031 \\ 0.4967 \\ 0.7442 \\ 0.9263 \\ 1.0771 \end{array}$	$\begin{array}{c} \tilde{U}_{m(k)} \\ 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \\ 0.4302 \\ 0.6931 \\ 0.8754 \\ 1.0238 \end{array}$
k = 1 k = 2	$egin{array}{cccc} m & & & \ 1 & & \ 2 & & \ 3 & & \ 4 & & \ 1 & & \ 2 & & \ 3 & & \ 4 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \ 1 & & \ 1 & \$	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517] (0.8143,2.5383) [1.7240] (0.0980,1.1290) [1.0310] (0.2947,1.4011) [1.1064] (0.4543,1.6108) [1.1565] (0.5888,1.7901) [1.2013] (0.0706,0.9282) [0.8576]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864] (0.0592,1.0700) [1.0108] (0.2527,1.3390) [1.0863] (0.4102,1.5461) [1.1359] (0.5422,1.7212) [1.1790] (0.0427,0.8900) [0.8473]	$\begin{array}{c} \widehat{U}_{m(k)} \\ 0.7291 \\ 1.0737 \\ 1.3322 \\ 1.5476 \\ 0.5272 \\ 0.7709 \\ 0.9536 \\ 1.1060 \\ 0.4377 \end{array}$	$\begin{array}{c} \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 \\ 1.5031 \\ 0.4967 \\ 0.7442 \\ 0.9263 \\ 1.0771 \\ 0.4153 \end{array}$	$\begin{array}{c} \tilde{U}_{m(k)} \\ 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \\ \hline 0.4302 \\ 0.6931 \\ 0.8754 \\ 1.0238 \\ \hline 0.3653 \end{array}$
k = 1 k = 2	$egin{array}{cccc} m & & & \\ 1 & 2 & & \\ 3 & 4 & & \\ 1 & 2 & & \\ 3 & 4 & & \\ 1 & 2 & & \\ 1 & 2 & & \\ \end{array}$	Equi-tailed PI [width] (0.1487,1.5871) [1.4384] (0.4101,1.9789) [1.5688] (0.6290,2.2807) [1.6517] (0.8143,2.5383) [1.7240] (0.0980,1.1290) [1.0310] (0.2947,1.4011) [1.1064] (0.4543,1.6108) [1.1565] (0.5888,1.7901) [1.2013] (0.0706,0.9282) [0.8576] (0.2398,1.1474) [0.9076]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864] (0.0592,1.0700) [1.0108] (0.2527,1.3390) [1.0863] (0.4102,1.5461) [1.1359] (0.5422,1.7212) [1.1790] (0.0427,0.8900) [0.8473] (0.2090,1.1045) [0.8955]	$\begin{array}{c} \widehat{U}_{m(k)} \\ 0.7291 \\ 1.0737 \\ 1.3322 \\ 1.5476 \\ 0.5272 \\ 0.7709 \\ 0.9536 \\ 1.1060 \\ 0.4377 \\ 0.6367 \end{array}$	$\begin{array}{c} \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 \\ 1.5031 \\ 0.4967 \\ 0.7442 \\ 0.9263 \\ 1.0771 \\ 0.4153 \\ 0.6169 \end{array}$	$\begin{array}{c} \tilde{U}_{m(k)} \\ 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \\ \hline 0.4302 \\ 0.6931 \\ 0.8754 \\ 1.0238 \\ \hline 0.3653 \\ 0.5786 \end{array}$
k = 1 k = 2 k = 3	$egin{array}{cccc} m & & & \ 1 & & \ 2 & & \ 3 & & \ 1 & & \ 2 & & \ 3 & & \ 4 & & \ 1 & & \ 2 & & \ 3 & & \ 1 & & \ 2 & & \ 3 & & \ 3 & & \ \end{array}$	Equi-tailed PI [width] ($0.1487,1.5871$) [1.4384] ($0.4101,1.9789$) [1.5688] ($0.6290,2.2807$) [1.6517] ($0.8143,2.5383$) [1.7240] ($0.0980,1.1290$) [1.0310] ($0.2947,1.4011$) [1.1064] ($0.4543,1.6108$) [1.1565] ($0.5888,1.7901$) [1.2013] ($0.0706,0.9282$) [0.8576] ($0.2398,1.1474$) [0.9076] ($0.3737,1.3164$) [0.9427]	HPD PI [width] (0.0880,1.4792) [1.3912] (0.3444,1.8754) [1.5310] (0.5612,2.1767) [1.6155] (0.7435,2.4299) [1.6864] (0.0592,1.0700) [1.0108] (0.2527,1.3390) [1.0863] (0.4102,1.5461) [1.1359] (0.5422,1.7212) [1.1790] (0.0427,0.8900) [0.8473] (0.2090,1.1045) [0.8955] (0.3405,1.2697) [0.9292]	$\begin{array}{c} \widehat{U}_{m(k)} \\ 0.7291 \\ 1.0737 \\ 1.3322 \\ 1.5476 \\ 0.5272 \\ 0.7709 \\ 0.9536 \\ 1.1060 \\ 0.4377 \\ 0.6367 \\ 0.7860 \end{array}$	$\begin{array}{c} \hat{U}^*_{m(k)} \\ 0.6811 \\ 1.0320 \\ 1.2898 \\ 1.5031 \\ 0.4967 \\ 0.7442 \\ 0.9263 \\ 1.0771 \\ 0.4153 \\ 0.6169 \\ 0.7655 \end{array}$	$\begin{array}{c} \tilde{U}_{m(k)} \\ 0.5785 \\ 0.9526 \\ 1.2112 \\ 1.4215 \\ \hline 0.4302 \\ 0.6931 \\ 0.8754 \\ 1.0238 \\ \hline 0.3653 \\ 0.5786 \\ 0.7269 \end{array}$

Table 2: 95% Bayesian prediction intervals and point predictors for $U_{m(k)}$, based on the hybrid censored sample in Example 4.1.



Figure 3: Predictive density of m^{th} repair time of a series machine with k ball bearings (in hundreds of millions revolutions) given the censored sample of Example 4.1 (Scheme 1) for k = 1, 2, 3 (rows from top to bottom) and m = 1, 2, 3 (columns from left to right).

We shall construct equi-tailed 95% PIs, as well as 95% HPD PIs, for the first four repair times (in hundreds of millions revolutions to failure), based on a minimal repair strategy, of a series system with k = 1, 2, 3 ball bearings, i.e. for $U_{m(k)}$, $m = 1, \ldots, 4$ and k = 1, 2, 3. The intervals and the corresponding widths, as well as the point predictors $\hat{U}_{m(k)}$, $\hat{U}_{m(k)}^*$ and $\tilde{U}_{m(k)}$ are calculated and presented in Table 2, for each of the two sampling schemes. For example, for k = 3 and m = 4, the point predictor $\hat{U}_{4(3)} = 0.9103$ means that, when a minimal repair strategy is used, on average a series system with 3 ball bearings fails and needs to be repaired for the fourth time after 91.03 million revolutions. One can see from Table 2 that HPD PIs are more precise than their corresponding equi-tailed PIs. We also provide the predictive density plots of $U_{m(k)}$, for k = 1, 2, 3 and m = 1, 2, 3, based on Scheme 1 in Figure 3.

5 Simulation study

In this section, we wish to compare the performance of the interval and point predictors through a simulation study. As the Rayleigh distribution belongs to location-scale family, it would be reasonable to take $\mu = 0$ and $\sigma = 1$ in the simulation. To examine the effect of hyper-parameters on the predictors, the informative prior is considered by setting $\xi = -1, 1$ and $\tau = 0.25, 5$. Moreover, we consider the low-informative case by setting $\xi = 0$ and $\tau = 0.005$ in (21). We take n = 20, r = 17 T = 2, k = 1, 2, 3 and m = 1, 2, 3. The following algorithm is used to perform the simulation:

- 1. Generate x_1, \dots, x_n independently from Rayleigh distribution and extract the hybrid censored sample (x_1, \dots, x_d) from x_1, \dots, x_n .
- 2. Generate the repair time $u_{m(k)}$ from (6).
- 3. Obtain 95% PIs as well as the point predictors $\hat{u}_{m(k)}$, $\hat{u}_{m(k)}^*(i)$ and $\tilde{u}_{m(k)}(i)$ based on the values of (x_1, \dots, x_d) .
- 4. Repeat Steps 1-3 N = 10000 times, to obtain $u_{m(k)}(i)$, $\hat{u}_{m(k)}(i)$, $\hat{u}_{m(k)}^{*}(i)$ and $\tilde{u}_{m(k)}(i)$, i = 1, ..., N.

5. Calculate the estimated risk (ER) of the point predictors as follows

$$ER(\hat{u}_{m(k)}) = \frac{1}{N} \sum_{i=1}^{N} \left[\hat{u}_{m(k)}(i) - u_{m(k)}(i) \right]^{2},$$
$$ER(\hat{U}_{m(k)}^{*}) = \frac{1}{N} \sum_{i=1}^{N} \left| \hat{u}_{m(k)}^{*}(i) - u_{m(k)}(i) \right|$$

and

$$ER(\widetilde{u}_{m(k)}) = \frac{1}{N} \sum_{i=1}^{N} \delta\left(\widetilde{u}_{m(k)}(i) - u_{m(k)}(i)\right),$$

where

$$\delta(t) = \begin{cases} 1, & t = 0\\ 0, & t \neq 0 \end{cases}$$

6. Calculate the average width (AW) and coverage probability (CP) of the PIs.

In order to compare the Bayesian predicts with the classical (frequentist) ones, we also consider a classical method, due to Wald (1942), to obtain prediction intervals. To this end, we have to plug in the maximum likelihood estimators (MLEs) of the parameters μ and σ based on the hybrid censored sample in the conditional (predictive) density $f_{U_{m(k)}|\mathbf{X}}(u|\mathbf{x})$ to estimate it and then use it to obtain the PI for $U_{m(k)}$. Using the likelihood function (5), the maximum likelihood estimates $\hat{\mu}$ and $\hat{\sigma}$ are obtained by solving the likelihood equations

$$\sum_{i=1}^{d} \frac{-1}{x_i - \mu} x_i^2 + \frac{1}{\sigma} \left[\sum_{i=1}^{d} (x_i - \mu) + (n - d)(T_0 - \mu) \right] = 0$$

and

$$-\frac{d}{\sigma} + \frac{1}{2\sigma^2}\delta^*(\mu|\mathbf{x}) = 0,$$

where $\delta^*(\mu | \mathbf{x})$ is given in (23).

Since the hybrid censored sample **X** and $U_{m(k)}$ are independent, we have $f_{U_{m(k)}|\mathbf{X}}(u|\mathbf{x}) = f_{U_{m(k)}}(u)$ and thus the estimated predictive density is obtained as

$$\widehat{f}_{U_{m(k)}}(u) = \frac{k^m (u - \hat{\mu})^{2m-1}}{\Gamma(m)\hat{\sigma}^m 2^{m-1}} \exp\left\{-\frac{k(u - \hat{\mu})^2}{2\hat{\sigma}}\right\}, \quad u > \hat{\mu}.$$
(30)

Letting, $U_{m(k)}^* = k(U_{m(k)} - \hat{\mu})^2 / \hat{\sigma}$, we have

$$\widehat{f}_{U_{m(k)}^{*}|\mathbf{X}}(u|\mathbf{x}) = \frac{u^{m-1}e^{-u/2}}{\Gamma(m)2^{m-1}},$$

that is the pdf of chi-square distribution with 2m degrees of freedom. Thus, a two-sided equi-tailed $100(1 - \alpha)\%$ Wald's prediction interval for $U_{m(k)}$, given the hybrid censored sample is

$$\left(\hat{\mu} + \sqrt{\frac{\hat{\sigma}\chi_{1-\alpha/2}^2(2m)}{k}}, \hat{\mu} + \sqrt{\frac{\hat{\sigma}\chi_{\alpha/2}^2(2m)}{k}}\right),$$

where $\chi^2_{\gamma}(2m)$ denotes the upper γ^{th} quantile of the chi-square distribution with 2m degrees of freedom, i.e., $P(T > \chi^2_{\gamma}(2m)) = \gamma$, with $T \sim \chi^2(2m)$.

The simulated AWs, as well as CPs, of the Wald's PIs for $U_{m(k)}$ are given in Table 8, for k = 1, 2, 3 and m = 1, 2, 3. Also, the simulated AWs and CPs of the equi-tailed Bayesian and HPD PIs for $U_{m(k)}$ are given in Tables 3-7, for different values of the hyperparameters ξ and τ , k = 1, 2, 3 and m = 1, 2, 3. As one can see from Tables 3-7, the ERs of the point predicts and AWs of the PIs are increasing with respect to m, when other parameters are kept fixed, while they are decreasing with respect to k. Also we observe that although HPD PIs have smaller AWs in comparison with equi-tailed PIs, their CPs are very close and even in most cases larger than the CPs of equi-tailed PIs, revealing the superiority of HPD PIs. For $\xi = -1$ and $\tau = 5$, the largest CPs and AWs are obtained, while for $\xi = 1$ and $\tau = 5$, we obtain the smallest CPs and AWs. However, the ERs of all cases are almost equal. From Table 8, we see that the Wald's PIs have smaller AWs and CPs in comparison with their corresponding Bayesian PIs.

6 Concluding Remarks

In this paper, we have studied the marginal Bayesian prediction of repair times of a series system based on a minimal repair strategy, using the information contained in an observed hybrid censored sample of the lifetimes of the components of the system. The results can be extended to non-parametric prediction procedures and also the joint prediction of repair times. The problem of predicting repair times of other types of coherent systems, such as parallel systems and k-out-of-n systems, on the basis of a censored sample of their

		Equi-tailed	PI	H	PD	PI			
	m	AW	CP	A	W	CP	$ER(\widehat{U}_{m(k)})$	$ER(\hat{U}_{m(k)}^{*})$	$ER(\widetilde{U}_{m(k)})$
	1	3.5841	0.9930	3.4	763	0.9875	0.4502	0.5360	1.0000
k = 1	2	3.8944	0.9890	3.7	825	0.9889	0.5946	0.5970	1.0000
	3	4.1232	0.9790	3.9	736	0.9886	0.7854	0.6697	1.0000
	1	2.5732	0.9858	2.5	323	0.9795	0.2396	0.3894	1.0000
k = 2	2	2.7572	0.9920	2.6	778	0.9876	0.2736	0.4129	1.0000
	3	2.8789	0.9482	2.8	524	0.9741	0.5328	0.5600	1.0000
	1	2.1586	0.9831	2.1	301	0.9750	0.1800	0.3407	1.0000
k = 3	2	2.2668	0.9909	2.2	410	0.9858	0.1807	0.3399	1.0000
	3	2.3508	0.9913	2.3	073	0.9879	0.2029	0.3542	1.0000

Table 3: The simulated AWs and CPs of the Bayesian PIs for $U_{m(k)}$, for $\xi = -1$ and $\tau = 5$.

Table 4: The simulated AWs and CPs of the Bayesian PIs for $U_{m(k)}$, for $\xi = 1$ and $\tau = 5$.

		Equi-tailed	\mathbf{PI}	HPD	PI			
	m	AW	CP	AW	CP	$ER(\hat{U}_{m(k)})$	$ER(\hat{U}^*_{m(k)})$	$ER(\tilde{U}_{m(k)})$
	1	2.4006	0.9036	2.2932	0.9108	0.4687	0.5423	1.0000
k = 1	2	2.6305	0.9204	2.5956	0.9278	0.5263	0.5771	1.0000
	3	2.7528	0.9222	2.6601	0.9195	0.5698	0.6023	1.0000
	1	1.7006	0.8899	1.6687	0.9094	0.2369	0.3865	1.0000
k = 2	2	1.8560	0.9094	1.8047	0.9172	0.2686	0.4127	1.0000
	3	1.9450	0.9223	1.9250	0.9578	0.2848	0.4241	1.0000
	1	1.4001	0.8804	1.3587	0.9010	0.1622	0.3195	1.0000
k = 3	2	1.5176	0.9084	1.5041	0.9218	0.1772	0.3344	1.0000
	3	1.5873	0.9187	1.5257	0.9249	0.1926	0.3471	1.0000

		Equi-tailed	PI	HPD	PI			
	m	AW	CP	AW	CP	$ER(\widehat{U}_{m(k)})$	$ER(\hat{U}_{m(k)}^{*})$	$ER(\widetilde{U}_{m(k)})$
	1	2.8046	0.9634	 2.7415	0.9654	0.4619	0.5429	1.0000
k = 1	2	3.0324	0.9507	2.9718	0.9561	0.5473	0.5845	1.0000
	3	3.2103	0.9491	3.1510	0.9593	0.6153	0.6157	1.0000
	1	1.9971	0.9570	1.9859	0.9582	0.2256	0.3784	1.0000
k = 2	2	2.1387	0.9523	2.0747	0.9524	0.2657	0.4101	1.0000
	3	2.2313	0.9519	2.1790	0.9590	0.2935	0.4252	1.0000
	1	1.6724	0.9541	1.6606	0.9575	0.1598	0.3170	1.0000
k = 3	2	1.7622	0.9571	1.7524	0.9585	0.1764	0.3341	1.0000
	3	1.8334	0.9489	1.8074	0.9541	0.1997	0.3532	1.0000

Table 5: The simulated AWs and CPs of the Bayesian PIs for $U_{m(k)}$, for $\xi = -1$ and $\tau = 0.25$.

Table 6: The simulated AWs and CPs of the Bayesian PIs for $U_{m(k)}$, for $\xi = 1$ and $\tau = 0.25$.

		Equi-tailed	PI	HPD	PI			
	m	AW	CP	AW	CP	$ER(\widehat{U}_{m(k)})$	$ER(\hat{U}_{m(k)}^{*})$	$ER(\tilde{U}_{m(k)})$
	1	2.7305	0.9587	2.5025	0.9584	0.4628	0.5431	1.0000
k = 1	2	2.9582	0.9428	2.8333	0.9485	0.5474	0.5795	1.0000
	3	3.1104	0.9498	3.0390	0.9563	0.6083	0.6163	1.0000
	1	1.9378	0.9467	1.9217	0.9516	0.2313	0.3827	1.0000
k = 2	2	2.0774	0.9492	2.0129	0.9474	0.2632	0.4070	1.0000
	3	2.1777	0.9465	2.1290	0.9525	0.2942	0.4286	1.0000
	1	1.6144	0.9482	1.5954	0.9483	0.1582	0.3173	1.0000
k = 3	2	1.7069	0.9466	1.6974	0.9527	0.1754	0.3332	1.0000
	3	1.8085	0.9633	1.7874	0.9678	0.1986	0.3577	1.0000

		Equi-tailed	PI		HPD	PI			
	m	AW	CP	_	AW	CP	$ER(\widehat{U}_{m(k)})$	$ER(\hat{U}^*_{m(k)})$	$ER(\tilde{U}_{m(k)})$
	1	2.7430	0.9471		2.6487	0.9486	0.4661	0.5379	1.0000
k = 1	2	2.9953	0.9489		2.9414	0.9539	0.5421	0.5791	0.9999
	3	3.1791	0.9538		3.1284	0.9594	0.6086	0.6118	0.9997
	1	1.9735	0.9494		1.9649	0.9548	0.2317	0.3832	1.0000
k = 2	2	2.1178	0.9452		2.0502	0.9470	0.2696	0.4107	1.0000
	3	2.2232	0.9513		2.1658	0.9559	0.2960	0.4293	1.0000
	1	1.6489	0.9493		1.6334	0.9525	0.1590	0.3173	1.0000
k = 3	2	1.7390	0.9526		1.7301	0.9571	0.1733	0.3313	1.0000
	3	1.8103	0.9503		1.7897	0.9538	0.1974	0.3482	1.0000

Table 7: The simulated AWs and CPs of the Bayesian PIs for $U_{m(k)}$, for $\xi = 0$ and $\tau = 0.005$.

Table 8: The simulated AWs and CPs of the Wald's PIs for $U_{m(k)}$.

	m	AW	CP
	1	2.3382	0.9059
k = 1	2	2.4778	0.9091
	3	2.5293	0.8943
	1	1.6496	0.8964
k = 2	2	1.7597	0.9027
	3	1.7807	0.8978
	1	1.3463	0.8801
k = 3	2	1.4294	0.8994
	3	1.4734	0.9022

components is of interest. Work on these problems is under progress and we hope to report the new results in the near future.

Acknowledgements

We would like to thank the associate editor and the anonymous referees for their valuable comments and suggestions on an earlier version of this manuscript, which resulted in this improved version. We also thank Prof. N. Balakrishnan for his useful comments.

References

- Abdel-Hamid, A.H. and AL-Hussaini, E.K. (2014). Bayesian prediction for Type-II progressive-censored data from the Rayleigh distribution under progressive-stress model. *Journal of Statistical Computation and Simulation.*, 84, 1297–1312.
- Ahmadi, J. and Balakrishnan, N. (2010). Prediction of order statistics and record values from two independent sequences, *Statistics*, 44, 417–430.
- Ahmadi, J. and MirMostafaee, S. M. T. K. (2009). Prediction intervals for future records and order statistics coming from two parameter exponential distribution, *Statistics and Probability Letters*, **79**, 977–983.
- Ahmadi, J. and MirMostafaee, S. M. T. K. and Balakrishnan, N. (2010). Nonparametric prediction intervals for future record intervals based on order statistics, *Statistics and Probability Letters*, 80, 1663–1672.
- Ali Mousa, M. A. M., Al-Sagheer, S. A. (2006). Statistical inference for the Rayleigh model based on progressively Type-II censored data. *Statistics*, 40, 149–157.
- Arnold, B. C., Balakrishnan, N., and Nagaraja, H. N. (1998). *Records*, John Wiley & Sons, New York.
- Balakrishnan, N. (1989). Approximate MLE of the scale parameter of the Rayleigh distribution with censoring. *IEEE Transactions on Reliability*, 38, 355–357.
- Balakrishnan, N. and Kundu, D. (2012). Hybrid censoring: models, inferential results and applications (with discussion). *Computational Statistics and Data Anal*ysis, 57, 166–209.

- Barlow, R. E. and Hunter, L. (1960). Optimum preventive maintenance policies. Operations Research, 8, 90–100.
- Childs, A., Chandrasekhar, B., Balakrishnan, N. and Kundu, D. (2003). Exact likelihood inference based on type-I and type-II hybrid censored samples from the exponential distribution. Annals of the Institute of Statistical Mathematics, 55, 319–30.
- Dey, S. and Das, M.K. (2007). A Note on prediction interval for a Rayleigh distribution: Bayesian approach. American Journal of Mathematical and Management Sciences, 27, 43–48.
- Dey, S. and Dey, T. (2012). Bayesian estimation and prediction intervals for a Rayleigh distribution under a conjugate prior. *Journal of Statistical Computation* and Simulation., 82, 1651–1660.
- Dey, S. and Dey, T. (2014). Statistical inference for the Rayleigh distribution under Type II progressive censoring with binomial removal. *Applied Mathematical Modelling*, 38, 974–982.
- Draper, N. and Guttman, I. (1987). Bayesian analysis of hybrid life tests with exponential failure times, Annals of the Institute of Statistical Mathematics, 39, 219–225.
- Dyer, D.D. and Whisenand, C.W. (1973). Best linear unbiased estimator of the parameter of the Rayleigh distribution-Part I: small sample theory for censored order statistics. *IEEE Transactions on Reliability*, 22, 27–34.
- Ebrahimi, N. (1992). Prediction intervals for future failures in exponential distribution under hybrid censoring, *IEEE Transactions on Reliability*, 41, 127–132.
- Epstein, B. (1954). Truncated life tests in the exponential case. Annals of Mathematical Statistics, 25, 555–564.
- Fernandez, A. J. (2000). Bayesian inference from Type-II doubly censored Rayleigh data. *Statistics and Probability Letters*, 48, 393–399.
- Gelman, A., Carlin, J. B., Stern, H. S. and Rubin, D. B. (2004). Bayesian Data Analysis, Second Edition, Chapman & Hall/CRC, New York, USA.

- Gross, A.J. and Clark, V.A. (1976). Survival Distributions, Reliability Applications in Biomedical Sciences (Probability and Mathematical Statistics), John Wiley & Sons, New York.
- Howlader, H.A. (1985). HPD prediction intervals for the Rayleigh distribution. IEEE Transactions on Reliability, 34, 121–123.
- Howlader, H.A. and Hossain, A. (1995). On bayesian estimation and prediction from rayleigh based on Type II censored data. *Communications in Statistics- Theory and Methods*, 24, 2251–2259.
- Johnson, N.L., Kotz, S. and Balakrishnan, N. (1994). Continuous Univariate Distributions, Vol. 1, 2nd Ed., John Wiley & Sons, New York.
- Khan, H. M. R., Provost, S. B. and Singh, A. (2010). Predictive inference from a two-Parameter Rayleigh life model given a doubly censored sample. *Communications in Statistics- Theory and Methods*, **39**, 1237–1246.
- Kundu, D. (2007). On hybrid censoring Weibull distribution., Journal of Statistical Planning and Inference, 137, 2127–2142.
- Kundu, D. and Banerjee, A. (2008). Inference Based on Type-II Hybrid Censored Data From a Weibull Distribution. *IEEE Transactions on Reliability*, 57(2), 369– 378.
- Kundu, D. and Gupta, R. D. (1988). Hybrid censoring schemes with exponential failure distribution. *Communications in Statistics- Theory and Methods*, 27, 3065– 3083.
- Lawless, J.F. (2003). Statistical Models and Methods for Lifetime Data, John Wiley & Sons, New York.
- Leiblein, J. and Zelen, M. (1956). Statistical investigation of the fatigue life of deepgroove ball bearings, *Journal of Research of the National Bureau of Standards*, 57, 273–316.
- MirMostafaee, S. M. T. K. and Ahmadi, J. (2011). Point prediction of future order statistics from exponential distribution, *Statistics and Probability Letters*, 81, 360– 370.

- Nevzorov, V. (2001). Records: Mathematical Theory, Translation of Mathematical Monographs No. 194, American Mathematical Society, Providence, Rhode Island, USA.
- Polovko, A. M. (1968). Fundamentals of Reliability Theory, Academic Press, San Diego.
- Raqab, M. Z. and Madi, M. T. (2002). Bayesian prediction of the total time on test using doubly censored Rayleigh data. *Journal of Statistical Computation and Simulation.*, 72, 781–789.
- 34. Rayleigh, J.W.S. (1880). On the resultant of a large number of vibrations of the same pitch and of arbitrary phase. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 5th Series, **10**, 73–78.
- 35. Rayleigh, J.W.S. (1919). On the problem of random variations, and of random flights in one, two or three dimensions. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 6th Series, **37**, 321–347.
- Soliman, A. A. and Al-Aboud, F. M. (2008). Bayesian inference using record values from Rayleigh model with application. *European Journal of Operational Research*, 185, 659–672.
- Wald, A. (1942). Setting of tolerance limits when the sample is large. Annals of Mathematical Statistics, 13, 389–399.