# Sequence Graph Transform (SGT): A Feature Extraction Function for Sequence Data Mining

Chitta Ranjan Georgia Institute of Technology Atlanta, U.S.A. nk.chitta.ranjan@gatech.edu Samaneh Ebrahimi Georgia Institute of Technology Atlanta, U.S.A. samaneh.ebrahimi@gatech.edu Kamran Paynabar Georgia Institute of Technology Atlanta, U.S.A. kamran.paynabar@gatech.edu

# ABSTRACT

The ubiquitous presence of sequence data across fields such as the web, healthcare, bioinformatics, and text mining has made sequence mining a vital research area. However, sequence mining is particularly challenging because of the absence of an accurate and fast approach to find (dis)similarity between sequences. As a measure of (dis)similarity, mainstream data mining methods such as k-means, kNN and regression have proved *distance* between data points in a Euclidean space to be most effective. But a distance measure between sequences is not obvious due to their unstructuredness—arbitrary strings of arbitrary length. We, therefore, propose a new function, Sequence Graph Transform (SGT), that extracts sequence features and embeds them in a finitedimensional Euclidean space. SGT is scalable due to a low computation and has a universal applicability to most sequence problems. We theoretically show that SGT can capture both short and long patterns in sequences and provides an accurate distance-based measure of (dis)similarity between them. This is also validated experimentally. Finally, we show its real world application for clustering, classification, search and visualization on different sequence problems.

# **CCS** Concepts

 $\bullet {\bf Computing methodologies} \to {\bf Machine learning algorithms;}$ 

## Keywords

sequence data mining; feature map; short- and long-term patterns

# 1. INTRODUCTION.

A sequence can be defined as a contiguous chain of discrete *alphabets*, where an alphabet can be an event, a value or a symbol, sequentially tied together in a certain order, e.g., BAABCCADECDBBA. Sequences are one of the most common data types found in diverse fields such as social science, web, healthcare, bioinformatics, marketing and text mining. Some examples of sequences are: web logs, music listening histories, patient movements through hospital wards, DNA, RNA and protein sequences in bioinformatics.

The ubiquitous presence of sequence data has made development of new sequence analysis methods important. Some examples of its applications include: a) understanding users' behavior from their web surfing and buying sequences data to serve them better advertisements, product placements, promotions, and so on, b) assessing process flows (sequences) in a hospital to find the expected patient movement based on diagnostic profiles to better optimize the hospital resource and service, and c) analysis of biological sequences to understand human evolution, physiology and diseases.

However, existing sequence data mining methods lack in their effectiveness due to absence of good measures of (dis)similarity between sequences. For a (dis)similarity measure, almost all mainstream data mining methods use *distance* between objects in a Euclidean space. For example, in *k*-means clustering, the *distances* between objects within a cluster are minimized while *distances* between clusters are maximized; in classification models like SVM or logistic regression, the *distance* of a boundary is minimized or maximized from the objects. In the deep learning realm as well, objects are transformed into Euclidean vectors for comparisons. It is now commonly accepted that the *distance* between objects in a Euclidean space is one of the best measures of (dis)similarity.

But, since sequences are unstructured data—made of arbitrarily placed alphabets for any arbitrary length—their representation in a Euclidean space is not obvious. Unfortunately, the lack of a Euclidean space representation devoids sequence data analysis of mainstream data mining methods. As a result, sequence mining methods have been developed separately, which are often less effective in terms of accuracy, complexity and interpretability.

To that end, feature extraction of a sequence in a finitedimensional Euclidean feature space is necessary. This can also be viewed as an embedding space, where the objective is to transform a sequence into a feature vector such that the features capture the sequence's characteristics. This facilitates computation of (dis)similarity between two sequences by measuring the *distance* between their embeddings.

Several researchers have proposed feature sets or functions (see references in [10]) based on a fundamental premise: *a* sequence is characterized by the patterns formed due to the alphabets' positions relative to others. However, to work with this premise, some of them make strong assumptions, e.g. Markov model and n-grams.

We, therefore, develop a new feature extraction approach, Sequence Graph Transform (SGT), that works on the same fundamental premise but without any restrictive assumptions. Importantly, it effectively captures the sequence features and embeds them into a finite-dimensional Euclidean space that leads to an accurate comparison of sequences by measuring the *distance* between them in the feature space.

### **1.1 Related Work.**

Early research works used *edit*-distances between sequences after alignment. Methods for global alignment and local alignment, with or without overlapping, were developed by [11, 15]. Based on them, heuristic approaches were proposed for larger datasets [3, 4, 5]. These methods mainly focus on bioinformatics sequence problems and lack in their general applicability due to difficulty in tuning, high computational complexity, and inability to work on sequences with significantly varying lengths. Besides, these methods do not provide any feature representation of sequences.

More universally applicable and relatively powerful methods broadly work on one of the following assumptions: a) the sequence process has an underlying parametric distribution, b) similar sequences have common substrings, and c) a sequence evolves from hidden strings.

The parametric methods typically make Markovian distribution assumptions (more specifically a first-order Markovian) on the sequence process [1, 12]. However, such distributional assumptions are not always valid. General *n*-order Markov models were also proposed but not popular in practice due to high computation. Beyond them, Hidden Markov model-based approaches are popular in both bioinformatics and general sequence problems [13, 9]. This assumes a hidden layer of latent states that results in the observed sequence. These hidden states have a first-order Markov transition assumption, but due to the multi-layer setting, the first-order assumption is not transmitted to the observed sequence. However, tuning HMM (finding optimal hidden states) is difficult and computationally intensive, thus effecting HMM's generality and scalability.

N-gram methods (also known as k-mer methods in the bioinformatics area) are the most popular approaches that work on the second assumption [8, 16]. Although the pretext of this assumption seems appropriate, the optimal selection of substring length, i.e. n in n-gram or k in k-mer, is difficult. In sequence mining, selection of a small value for n can lead to inclusion of noise, but increasing it severely increases the computation. Some other variants, such as *spaced-words* and adaptive n, are more difficult to optimize [2].

Another class of methods hypothesizes that sequences are generated from some evolutionary process in which a sequence is produced by reproducing complex strings from simpler substrings ([14] and references therein). This method solves an NP-hard optimization problem to identify the underlying evolution hierarchy and corresponding substrings. These substrings can also be used as features for sequence data mining. However, the estimation algorithms for this and similar methods are heuristics that usually do not guarantee optimality. The algorithms can also lead to several solutions that will cause identifiability and ambiguity issues. Moreover, the evolutionary assumption may not be always true. The above methods either limit the extent of sequence pattern extraction due to restrictive assumptions or search for (hidden) states or strings in an unobservable universe. This causes limited accuracy and/or computational issues.

Besides these methods, Prefixspan [7] is another sequence pattern mining approach, but it works on a different type of sequence in which the sequence is a list of elements and each element consists of a set of items, e.g.  $\langle a(abc)(ac)d(cf) \rangle$ . For the sequence problems addressed here, Prefixspan's performance will be similar to n-grams.

Sequence mining problems have also been given attention by the deep learning research community. Embedding spaces for sequences have been proposed using Recurrent Neural Networks (RNN) and Long Short Term Memory [6]. However, the dimension of these embeddings is typically large, and finding the optimal dimension and embeddings requires the use of rigorous optimization problems in a deep learning network. Training such models is computationally intensive, sometimes not interpretable and requires a large amount of training data.

### **1.2 Problem Specification.**

The related methods discussed above fail to address at least one of the following challenges: a) feature mapping: effective extraction of sequence characteristics into a finitedimensional Euclidean space (a vector), b) universal applicability: which mainly requires the absence of any distributional or a domain specific assumption and a small number of tuning hyper-parameters, and c) scalability: which relies on the computational complexity, which should be small with respect to sequence length, size of the database and size of alphabets set.

We propose a new sequence feature extraction function, Sequence Graph Transform (SGT), that addresses all of the above challenges and is shown to outperform existing stateof-the-art methods in sequence data mining. SGT works by quantifying the pattern in a sequence by scanning the positions of all alphabets relative to each other. We call it a graph transform because of its inherent property of interpretation as a graph, where the alphabets form the nodes and a directed connection between two nodes shows their "association." These "associations" between all alphabets represent the signature features of a sequence. A Markov model transition matrix can be compared analogously with the SGT's feature space; however, among other differences (explored further in the paper), the associations (graph edges) do not represent a probability, and SGT is non-parametric. The non-parametric property also makes it robust to any underlying sequence generation distribution.

Regardless, sequence analysis problems can be broadly divided into: a) *length-sensitive*: the inherent patterns as well as the sequence lengths should match to render two sequences as similar, e.g., in protein sequence clustering; and b) *length-insensitive*: the inherent patterns should be similar, irrespective of the lengths, e.g., weblog comparisons. In contrast with the existing literature, SGT provides a solution for both scenarios. The advantage of this property becomes more pronounced when we have to perform both types of analysis on the same data and implementing different methods for each becomes cumbersome.

In this paper, our major contribution is the development of a new feature extraction function, SGT, for sequences. We support SGT's efficacy theoretically, as well as perform an



Figure 1: Showing "effect" of elements on each other.

extensive experimental evaluation. Furthermore, we show that SGT bridges the gap between sequence mining and mainstream data mining through implementation of fundamental methods, viz. PCA, k-means, SVM and graph visualization via SGT on real sequence data analysis.

# 2. SEQUENCE GRAPH TRANSFORM (SGT)

### 2.1 Overview and Intuition

By definition, a sequence can be either feed-forward or "undirected." In a feed-forward sequence, events (alphabet instances) occur in succession; e.g. in a clickstream sequence, the click events occur one after another in a "forward direction." On the other hand, in an "undirected" sequence, the directional or chronological order of alphabet instances is not present or not important, e.g. text documents.

For either of these sequence types, the developed Sequence Graph Transform works on the same fundamental premise—the relative positions of alphabets in a sequence characterize the sequence—to extract the pattern features of the sequence. This premise holds true for most sequence mining problems because similarity in sequences is often measured based on the similarities in their pattern from the alphabet positions.

In the following, we illustrate and develop the SGT's feature extraction approach for a feed-forward sequence and later extend it to "undirected" sequences.

Fig. 1 shows an illustrative example of a feed-forward sequence. In this example, the presence of alphabet B at positions 5 and 8 should be seen in context with or as a result of all other predecessors. To extract the sequence features, we take the relative positions of one alphabet pair at a time. For example, the relative positions for pair (A,B) are  $\{(2,3),5\}$  and  $\{(2,3,6),8\}$ , where the values in the position set for A are the ones preceding B. In the SGT procedure defined and developed in the following sections (§2.3-2.4), the sequence features are shown to be extracted from these positions information.

These extracted features are "association" between A and B, which can be interpreted as a connection feature representing "A leading to B." We should note that "A leading to B" will be different from "B leading to A." The associations between all alphabets in the alphabet set, denoted as  $\mathcal{V}$ , can be extracted similarly to obtain sequence features in a  $|\mathcal{V}|^2$ -dimensional feature space.

This is similar to the Markov probabilistic models, in which the transition probability of going from A to B is estimated. However, SGT is different because the connection feature 1) is not a probability, and 2) takes into account all orders of relationship without any increase in computation.

Besides, the SGT features also make it easy to visualize the sequence as a directed graph, with sequence alphabets in  $\mathcal{V}$  as graph nodes and the edge weights equal to the directional association between nodes. Hence, we call it a sequence graph transform. Moreover, we show that under certain conditions, the SGT also allows node (alphabet)



(a) Feature extracted as a vector with a graph interpretation.



(b) Use of sequences' SGT features for data mining.



clustering.

A high level overview of our approach is given in Fig. 2a-2b. In Fig. 2a, we show that applying SGT on a sequence, s, yields a finite-dimensional SGT feature vector,  $\Psi^{(s)}$ , for the sequence, also interpreted and visualized as a directed graph. For a general sequence data analysis, SGT can be applied on each sequence in a data corpus, as shown in Fig. 2b, to yield a finite and equal dimensional representation for each sequence. This facilitates a direct distance-based comparison between sequences and thus makes application of mainstream data mining methods for sequence analysis rather straightforward.

### 2.2 Notations

Suppose we have a dataset of sequences denoted by S. Any sequence in the dataset, denoted by  $s \in S$ , is made of alphabets in set V. A sequence can have instances of one or many alphabets from V. For example, sequences from a dataset, S, made of alphabets in,  $V = \{A, B, C, D, E\}$ (suppose), can be  $S = \{AABAAABCC, DEEDE, ABBDECCABB, ...\}$ . The length of a sequence, s, denoted by,  $L^{(s)}$ , is equal to the number of events (in this paper, the term "event" is used for an alphabet instance) in it. In the sequence,  $s_l$  will denote the alphabet at position l, where  $l = 1, \ldots, L^{(s)}$  and  $s_l \in V$ .

As mentioned in the previous section, we extract sequence features in the form of "associations" between the alphabets, represented as  $\psi_{uv}^{(s)}$ , where  $u, v \in \mathcal{V}$ , are the corresponding alphabets and  $\psi$  is a function of  $\phi$ .  $\phi$  is also a function that takes a "distance," d, as an input and  $\kappa$  as a tuning hyper-parameter, represented as  $\phi_{\kappa}(d)$ .

### 2.3 SGT Definition

As also explained in §2.1, the Sequence Graph Transform extracts the features from the relative positions of events. A quantification for an "effect" from the relative positions of two events in a sequence is given by  $\phi(d(l, m))$ , where l, m are the positions of the events and d(l, m) is a distance measure. This quantification is an effect of the preceding



Figure 3: Visual illustration of the effect of alphabets' relative positions.

event on the later event. For example, see Fig. 3a, where u and v are at positions l and m, and the directed arc denotes the effect of u on v.

For developing SGT, we require the following conditions on  $\phi$ : a) strictly greater than 0:  $\phi_{\kappa}(d) > 0$ ;  $\forall \kappa > 0, d > 0$ ; b) strictly decreasing with d:  $\frac{\partial}{\partial d}\phi_{\kappa}(d) < 0$ ; and c) strictly decreasing with  $\kappa$ :  $\frac{\partial}{\partial \kappa}\phi_{\kappa}(d) < 0$ .

The first condition is to keep the extracted SGT feature,  $\psi = f(\phi)$ , easy to analyze and interpret. The second condition strengthens the effect of closer neighbors. The last condition helps in tuning the procedure, allowing us to change the effect of neighbors.

There are several functions that satisfy the above conditions: e.g., Gaussian, Inverse and Exponential. We take  $\phi$ as an exponential function because it will yield interpretable results for the SGT properties (§2.4) and d(l,m) = |m-l|.  $\phi_{\kappa}(d(l,m)) = e^{-\kappa |m-l|}, \ \forall \kappa > 0, \ d > 0$  (1)

In a general sequence, we will have several instances of an alphabet pair. For example, see Fig. 3b, where there are five (u, v) pairs, and an arc for each pair shows an effect of u on v. Therefore, the first step is to find the number of instances of each alphabet pair. The instances of alphabet pairs are stored in a  $|\mathcal{V}| \times |\mathcal{V}|$  asymmetric matrix,  $\Lambda$ . Here,  $\Lambda_{uv}$  will have all instances of alphabet pairs (u, v), such that in each pair instance, v's position is after u.

$$\Lambda_{uv}(s) = \{(l,m) : s_l = u, s_m = v, \\ l < m, (l,m) \in 1, \dots, L^{(s)}\}$$
(2)

In the sequence,  $\phi$  from each (u, v) pair instance will contribute to the "association" feature,  $\psi_{uv}$ . Thus, we aggregate individual contributions from each pair instance and normalize the aggregate, as shown below in Eq. 3a-3b, to give  $\psi_{uv}$ . Here,  $|\Lambda_{uv}|$  is the size of the set  $\Lambda_{uv}$ , which is equal to the number of (u, v) pair instances. Eq. 3a gives the feature expression for a *length-sensitive* sequence analysis problem because it also contains the sequence length information within it (proved with a closed-form expression under certain conditions in §2.4). In Eq. 3b, the length effect is removed by standardizing  $|\Lambda_{uv}|$  with the sequence length  $L^{(s)}$  for *length-insensitive* problems.

$$\psi_{uv}(s) = \frac{\sum_{\forall (l,m) \in \Lambda_{uv}(s)} e^{-\kappa |m-l|}}{|\Lambda_{uv}(s)|}; \text{ length sensitive} \quad (3a)$$
$$= \frac{\sum_{\forall (l,m) \in \Lambda_{uv}(s)} e^{-\kappa |m-l|}}{|\Lambda_{uv}(s)|/L^{(s)}}; \text{ length insensitive} \quad (3b)$$

and  $\Psi(s) = [\psi_{uv}(s)], u, v \in \mathcal{V}$  is the SGT feature representation of sequence s.

For illustration, the SGT feature for alphabet pair (**A**, **B**) in sequence in Fig. 1 can be computed as (for  $\kappa = 1$  in length-sensitive SGT):  $\Lambda_{AB} = \{(2,5); (3,5); (2,8); (3,8); (6,8)\}$ and  $\psi_{AB} = \frac{\sum_{\forall (l,m) \in \Lambda_{AB}} e^{-|m-l|}}{|\Lambda_{AB}|} = \frac{e^{-|5-2|} + e^{-|5-3|} + e^{-|8-2|} + e^{-|8-3|} + e^{-|8-6|}}{5} = 0.066.$ 



# Figure 4: Representation of short- and long-term pattern.

The features,  $\Psi^{(s)}$ , can be either interpreted as a directed "graph," with edge weights,  $\psi$ , and nodes in  $\mathcal{V}$ , or vectorized to a  $|\mathcal{V}|^2$ -vector denoting the sequence s in the feature space.

### 2.4 SGT properties

In this section, we show SGT's property of capturing both short- and long-term sequence pattern features. This is shown by a closed-form expression for the SGT feature,  $\psi_{uv}$ , under some defined scenario. Note that the scenario defined below is only for showing an interpretable expression and is not required in practice.

Definition 1. A sequence of length L with an inherent pattern: u,v occurs closely together with a stochastic gap in between,  $X \sim N(\mu_{\alpha}, \sigma_{\alpha}^2)$ , and the intermittent stochastic gap between the pairs as,  $Y \sim N(\mu_{\beta}, \sigma_{\beta}^2)$ , such that,  $\mu_{\alpha} < \mu_{\beta}$  (See Fig. 4). X and Y characterize the short- and long-term patterns, respectively.

THEOREM 1. SGT feature has a closed-form expression which shows that it captures both short- and long-term patterns present in a sequence in both length-sensitive and insensitive SGT variants.

$$E[\psi_{uv}] = \begin{cases} \frac{2}{pL+1}\gamma & ; length \ sensitive\\ \frac{2L}{pL+1}\gamma & ; length \ insensitive \end{cases}$$
(4)

 $\lim_{L \to \infty} var(\psi_{uv}) \quad \to \quad 0$ 

where,

$$\gamma = \frac{e^{-\tilde{\mu}_{\alpha}}}{\left| \left( 1 - e^{-\tilde{\mu}_{\beta}} \right) \left[ 1 - \frac{1 - e^{-pL\tilde{\mu}_{\beta}}}{pL(e^{\tilde{\mu}_{\beta}} - 1)} \right] \right|}$$
(6)

(5)

and,  $\tilde{\mu}_{\alpha} = \kappa \mu_{\alpha} - \frac{\kappa^2}{2} \sigma_{\alpha}^2$ ;  $\tilde{\mu}_{\beta} = \kappa \mu_{\beta} - \frac{\kappa^2}{2} \sigma_{\beta}^2$ ,  $p \to constant$ . PROOF. See Appendix B.  $\Box$ 

As we can see in Eq. 4, the expected value of the SGT feature is proportional to the term  $\gamma$ . The numerator of  $\gamma$ contains the information about the short-term pattern, and its denominator has the long-term pattern information.

In Eq. 6, we can observe that if either of  $\mu_{\alpha}$  (the closeness of u and v in the short-term) and/or  $\mu_{\beta}$  (the closeness of uand v in the long-term) decreases,  $\gamma$  will increase, and vice versa. This emphasizes two properties: a) the SGT feature,  $\psi_{uv}$ , is affected by changes in both short- and long-term patterns, and b)  $\psi_{uv}$  increases when u, v becomes closer in the short or long range in the sequence, providing an analytical connection between the observed pattern and the extracted feature. Besides, it also proves the graph interpretation of SGT:  $\psi_{uv}$  that denotes the edge weight for nodes u and v (in the SGT-graph) increases if closeness between u, v increases in the sequence, meaning that the nodes becoming closer in the graph space (and vice versa).

Furthermore, the length-sensitive SGT feature expectation in Eq. 4 contains the sequence length, L. This shows that the SGT feature has the information of the sequence pattern, as well as the sequence length. This enables an effective length-sensitive sequence analysis because sequence comparisons via SGT will require both patterns and sequence lengths to be similar.

In the length-insensitive SGT feature expectation in Eq. 4, it is straightforward to show that it becomes independent of the sequence length as the length increases. Therefore, as sequence length, L, increases, the (u, v) "association" feature

approaches a constant,  $\lim_{L\to\infty} E[\psi_{uv}] \to \frac{2}{p} \left| \frac{e^{-\tilde{\mu}_{\alpha}}}{1 - e^{-\tilde{\mu}_{\beta}}} \right|$ . Besides, it is shown in Appendix B,  $\lim_{L\to\infty} \operatorname{var}(\psi_{uv}) \to \frac{1}{1/L}$ 

0. Thus, the expected value of the SGT feature becomes independent of the sequence length at a rate of inverse to the length. In our experiments, we observe that the SGT feature approaches a length-invariant constant when L > 30.

$$\lim_{L \to \infty} \Pr\left\{ \psi_{uv} = \frac{2}{p} \left| \frac{e^{-\tilde{\mu}_{\alpha}}}{1 - e^{-\tilde{\mu}_{\beta}}} \right| \right\} \xrightarrow[1/L]{} 1$$
(7)

Furthermore, if the pattern variances,  $\sigma_{\alpha}^2$  and  $\sigma_{\beta}^2$ , in the above scenario are small,  $\kappa$  allows regulating the feature extraction: higher  $\kappa$  reduces the effect from long-term patterns and vice versa.

The properties discussed above play an important role in SGT's effectiveness. Due to these properties, unlike the methods discussed in §1.1. SGT can capture higher orders of relationship without any increase in computation. Besides, SGT can effectively find sequence features without the need for any hidden string/state(s) search.

#### **Extensions of SGT** 2.5

#### 2.5.1 Undirected sequences

SGT can be extended to work on undirected sequences. In such sequences, the directional pattern or directional relationships (as in feed-forward) are not important. In other words, it is immaterial whether B occurs before or after A; occurring closely (or farther) is important. From SGT's operation standpoint, we have to remove the condition, l < m, from Eq. 2, denoted by  $\Lambda$ .

It is easy to show that  $\tilde{\Lambda} = \Lambda + \Lambda^T$  and

$$\tilde{\Psi} = \frac{|\Lambda|\Psi + |\Lambda^T|\Psi^T}{|\Lambda| + |\Lambda^T|} \tag{8}$$

where  $\Lambda$  and  $\Psi$  are given in Eq. 2 and Eq. 3a-3b, respectively (see Appendix C for proof).

Moreover, for sequences with a uniform marginal distribution of occurrence of elements,  $v \in \mathcal{V}$ ,  $\Lambda$  will be close to symmetric; thus, the undirected sequence graph can be approximated as,  $\tilde{\Psi} \approx \frac{\Psi + \Psi^T}{2}$ . In practice, this approximation is useful in most cases

#### 2.5.2 Alphabet clustering

Node clustering in graphs is a classical problem solved by various techniques, including spectral clustering, graph partitioning and others. SGT's graph interpretation facilitates grouping of alphabets that occur closely via any of these node clustering methods.

This is because SGT gives larger weights to the edges,  $\psi_{uv}$ , corresponding to alphabet pairs that occur closely. For instance, consider a sequence in Fig. 5a, in which v occurs



Figure 5: Illustrative sequence example for alphabet clustering.

Algorithm 1 Parsing a sequence to obtain its SGT				
<b>Input:</b> A sequence, $s \in S$ , alphabet set, $\mathcal{V}$ , and $\kappa$ .				
1: Initialize:				
$\mathbf{W}^{(0)}, \mathbf{W}^{(\kappa)} \leftarrow 0_{\mathcal{V} \times \mathcal{V}}, \text{ and length}, L \leftarrow 1$				
2: for $i \in \{1, \dots, (\text{length}(s) - 1)\}$ do				
3: for $j \in \{(i+1), \ldots, \operatorname{length}(s)\}$ do				
4: $\mathbf{W}_{s_i,s_j}^{(0)} \leftarrow \mathbf{W}_{s_i,s_j}^{(0)} + 1$				
5: $\mathbf{W}_{s_i,s_j}^{(\kappa)} \leftarrow \mathbf{W}_{s_i,s_j}^{(\kappa)} + \exp(-\kappa  j-i )$				
6: where, $s_i, s_j \in \mathcal{V}$				
7: end for				
8: $L \leftarrow L + 1$				
9: end for				
10: if length-sensitive is True then				
11: $\mathbf{W}^{(0)} \leftarrow \mathbf{W}^{(0)}/L$				
12: end if				
<b>Output</b> $\psi_{uv}(s) \leftarrow \left(\frac{W_{u,v}^{(\kappa)}}{W_{u,v}^{(0)}}\right)^{\frac{1}{\kappa}}; \Psi(s) = [\psi_{uv}(s)], \ u, v \in \mathcal{V}$				

closer to u than w, also implying E[X] < E[Y]. Therefore, in this sequence's SGT, the edge weight for  $u \rightarrow v$  should be greater than for  $u \rightarrow w$ , i.e.  $\psi_{uv} > \psi_{uw}$ .

From Def. 1 in §2.4, we will have,  $E[|\Lambda_{uv}|] = E[|\Lambda_{uw}|]$ . Therefore,  $\psi_{uv} \propto E[\phi(X)]$  and  $\psi_{uw} \propto E[\phi(Y)]$ , and due to Condition 2 on  $\phi$  given in §2.3, if E[X] < E[Y], then  $E[\psi_{uv}] > E[\psi_{uw}].$ 

Moreover, for an effective clustering, it is important to bring the "closer" alphabets in the sequence more close in the graph space. In the SGT's graph interpretation, it implies that  $\psi_{uv}$  should go as high as possible to bring v closer to u in the graph and vice versa for (u, w). Thus, effectively,  $\Delta = E[\psi_{uv} - \psi_{uw}]$  should be increased. It is proved in Appendix D that  $\Delta$  will increase with  $\kappa$ , if  $\kappa d > 1, \forall d$ , where we have  $d \in \mathbb{N}$ .

Thus, an SGT can represent a sequence as a graph with its alphabets connected with weighted edges, which enables clustering of associated alphabets.

#### 3. SGT ALGORITHM

In this section, two algorithms are provided for SGT for a feed-forward sequence defined in Eq. 3a-3b. The first algorithm is faster for  $L < |\mathcal{V}|^2$ , while the second is faster for  $L > |\mathcal{V}|^2.$ 

The outputted SGT for the sequence, s, will be a  $|\mathcal{V}| \times$  $|\mathcal{V}|$  matrix, which can be vectorized (size,  $|\mathcal{V}|^2$ ) for use in distance-based data mining methods, or it can be used as is for visualization and interpretation purposes. Note that we output the  $\kappa^{\rm th}~$  root as the final SGT features as it makes the SGTs easy to interpret and comparable for any value of κ.

The time complexity of Algorithm 1 is  $O(L^2)$ , where L is the average sequence length and  $O(|\mathcal{V}|(L+|V|))$  for AlgoAlgorithm 2 Extract SGT features by scanning alphabet positions of a sequence

**Input:** A sequence,  $s \in S$ , alphabet set,  $\mathcal{V}$ , and  $\kappa$ . 1: function GetAlphabetPositions $(s, \mathcal{V})$ positions  $\leftarrow \{\emptyset\}$ 2:3: for  $v \in \mathcal{V}$  do 4:  $positions(v) \leftarrow \{i : s_i = v, i = 1, \dots, length(s)\}$ 5:end for 6: return positions 7: end function 8: Initialize:  $\mathbf{W}^{(0)}, \mathbf{W}^{(\kappa)} \leftarrow \mathbf{0}_{\mathcal{V} \times \mathcal{V}}, \text{ and length, } L \leftarrow 0$ positions  $\leftarrow \text{GETALPHABETPOSITIONS}(s, \mathcal{V})$ 9: for  $u \in \mathcal{V}$  do 10: $U \leftarrow \text{positions}(u)$ 11: for  $v \in \mathcal{V}$  do 12: $V \leftarrow \text{positions}(v)$  $C \leftarrow (U \times V)^+ = \{(i, j) | i \in U, j \in V, \& j > i\}$ 13: $\mathbf{W}_{u,v}^{(0)} \leftarrow \text{length}(C)$ 14: $\mathbf{W}_{u,v}^{(\kappa)} \leftarrow \operatorname{sum}(\exp(-\kappa |C_{:,u} - C_{:,v}|))$ 15:end for 16:17: $L \leftarrow L + \text{length}(U)$ 18: end for 19: if length-sensitive is True then 20: $\mathbf{W}^{(0)} \leftarrow \mathbf{W}^{(0)}/L$ 21: end if **Output** SGT:  $\psi_{uv}(s) \leftarrow \left(\frac{W_{u,v}^{(\kappa)}}{W_{u,v}^{(0)}}\right)^{\frac{1}{\kappa}}; \Psi(s) = [\psi_{uv}(s)], u, v \in \mathcal{V}$ 

rithm 2. The space complexity for both is  $O(|\mathcal{V}|^2)$ . However, in most datasets, not all alphabets in  $\mathcal{V}$  are present in a sequence, resulting in a sparse SGT features representation. In such cases, the complexities reduce by a factor of the sparsity level. Moreover, for a sequence dataset,  $\mathcal{S}$ , the algorithm should be repeated for all sequences to obtain their feature representations. Fortunately, as also evident from Fig. 2b, the SGT operation on any sequence in a dataset is independent of the other. This means we can easily parallelize the SGT operation on sequences in dataset  $\mathcal{S}$ .

The optimal selection of the hyper-parameter  $\kappa$  will depend on the problem in hand. If the end objective is building a supervised learning model, methods such as cross-validation can be used. For unsupervised learning, any goodness-of-fit criteria can be used for the selection. In cases of multiple parameter optimization, e.g. the number of clusters (say,  $n_c$ ) and  $\kappa$  together in clustering, we can use a random search procedure. In such a procedure, we randomly initialize  $n_c$ , compute the best  $\kappa$  based on some goodness-of-fit measure, then fix  $\kappa$  to find the best  $n_c$ , and repeat until there is no change. From our experiments on real and synthesized data, the results of SGT-based data mining are not sensitive to minor differences in  $\kappa$ . In our implementations, we typically selected  $\kappa$  from  $\{1, 5, 10\}$ .

# 4. EXPERIMENTAL ANALYSIS

Here we perform an experimental analysis to assess the performance of the proposed SGT. The most important motivation behind SGT is the need for an accurate method to find (dis)similarity between sequences. Therefore, to test SGT's efficacy in finding sequence (dis)similarities, we built a sequence clustering experimental setup. A clustering operation requires accurate computation of (dis)similarity between objects and thus is a good choice for efficacy assess-

	Sequence length, $\mu, \sigma$	Noise	$\#$ clusters, $n_c$
Exp-1	424.6, 130.6	45-50%	5
Exp-2	116.4, 47.7	35-65%	5
Exp-3	98.2, 108.3	_	5
Exp-4	103.9, 33.6	30-50%	3

Table 1: Experimentation settings



Figure 6: Exp-1 results

 $\mathrm{ment.}$ 

We perform four types of experiments: a) Exp-1: lengthsensitive, b) Exp-2: length-insensitive with non-parametric sequence pattern, c) Exp-3: length-insensitive with parametric sequence pattern, and d) Exp-4: alphabet clustering. The settings for each are given in Table 1. Alphabet set is,  $\mathcal{V} = \{A, B, \dots, Z\}$ , for all sequences. Besides, except for Exp-3, clustered sequences were generated such that sequences within a cluster share common patterns. Here two sequences having a common pattern primarily means that the sequences have some common subsequences of any length, and these subsequences can be present anywhere in the sequence. The sequences also comprise of other events, which can be either *noise* or some other pattern. This setting is non-parametric; however, the subsequences can also bring some inherent parametric properties, such as a mixture of Markov distribution of different orders. In Exp-3, clustered sequences were generated from a mixture of parametric distributions. In all the experiments, k-means with manhattan distance was applied on the sequences' SGTs.

In Exp-1, we compare SGT with length-sensitive algorithms, viz. MUSCLE, UCLUST and CD-HIT, which are popular in bioinformatics. These methods are hierarchical in nature, and thus, themselves find the optimal number of clusters. For SGT-clustering, the number of clusters is found using the random search procedure recommended in §3.

Fig. 6 shows the results, where the y-axis is the ratio of the estimated optimal number of clusters,  $\hat{n}_c$ , and the true number of clusters,  $n_c$ . On the x-axis, it shows the clustering accuracy, i.e. the proportion of sequences assigned to a same cluster given that they were actually from the same cluster. For a best performing algorithm, both metrics should be close to 1. As shown in the figure, CD-HIT and UCLUST overestimated the number of clusters by about twice and five times, respectively. MUSCLE had a better  $n_c$  estimate but had about 95% accuracy. On the other hand, SGT could accurately estimate  $n_c$  and has a 100% clustering accuracy.

In Exp-2, we compare SGT with commonly used sequence analysis techniques, viz. n-gram, mixture Hidden Markov model (HMM), Markov model (MM) and semi-Markov model (SMM)-based clustering. For n-gram, we take  $n = \{1, 2, 3\}$ , and their combinations. Note that 1-gram is equivalent to



Figure 7: Exp-2 results.

the bag-of-words method. For these methods, we provided the known  $n_c$  to the algorithms. We use F1-score as the accuracy metric.

Besides, in this experiment, we set different scenarios such that the overlap of clusters' "centroid" is increased. A high overlap between clusters implies that the sequences belonging to these clusters have a higher number of common patterns. Thus, separating them for clustering becomes difficult, and clustering accuracy is expected to be lower.

The Exp-2's result in Fig. 7 shows the accuracy (F1-score) and the runtimes (with the legend) for each method, where SGT is seen to outperform all others in accuracy. MM and SMM have a poorer accuracy because of the first-order Markovian assumption. HMM is found to have a comparable accuracy, but its runtime is more than 6 times that of SGT, proving SGT's superiority. N-gram methods' accuracies lie in between. Low-order n-grams have smaller runtime than SGT but significantly lower accuracy. Interestingly, the 1-gram method is better when overlapping is high, showing the higher order n-grams' inability to distinguish between sequences when pattern overlap is high.

Furthermore, we did Exp-3 to see the performance of SGT in sequence datasets having an underlying mixture of parametric distributions, viz. mixture of HMM, MM and SMM. The objective of this experiment is to test SGT's efficacy on parametric datasets against parametric methods. In addition to obtaining datasets from mixed HMM and first-order mixed MM and SMM distributions, we also get second-order Markov (MM2) and third-order Markov (MM3) datasets. Fig. 8 shows the F1-score and the runtime (as bar labels). As expected, the mixture clustering method corresponding to the underlying distribution is performing the best. Note that SMM is slightly better than MM in the MM setting because of its over-representative formulation, i.e. a higher dimensional model to include a variable time distribution. However, the proposed SGT's accuracy is always close to the best. This shows SGT's robustness to underlying distribution and its universal applicability. Besides, again, its runtime is smaller than all others.

Finally, we validate the efficacy of the extensions of SGT given in §2.5 in Exp-4. Our main aim in this validation is to perform alphabet clustering (§2.5.2). We set up a test experiment such that across different sequence clusters some alphabets occur closer to each other. We create a dataset that has sequences from three clusters and alphabets belong-



Figure 8: Exp-3 results.



Figure 9: Heat map showing alphabets' association via SGT edge-weights.

ing to two clusters (alphabets A-H in one cluster and I-P in another).

This emulates a biclustering scenario in which sequences in different clusters have distinct patterns; however, the pattern of closely occurring alphabets is common across all sequences. This is a complex scenario in which clustering both sequences and alphabets can be challenging.

Upon clustering the sequences, the F1-score is found to be 1.0. For alphabet clustering, we applied spectral clustering on the aggregated SGT of all sequences, which yielded an accurate result with only one alphabet as mis-clustered. Moreover, a heat map in Fig. 9 clearly shows that alphabets within same underlying clusters have significantly higher associations. Thus, it validates that SGT can accurately cluster alphabets along with clustering the sequences.

### 5. APPLICATIONS

In this section, we show a few applications of SGT-based sequence mining on real-world datasets.

### 5.1 Clustering

Sequence clustering is an important application area across various fields. One important problem in this area is clustering user activity on the web (web log sequences) to understand user behavior. This analysis helps in better service, design, advertisements and promotions.

We take users' navigation data on msnbc.com collected during a 24-hour period. The navigation data are weblogs that correspond to the page views of each user. The alphabets of these sequences are the events corresponding to a user's page request. These requests are recorded at a higher abstract level of page category, e.g. frontpage, tech, which are representative of the structure of the website. The dataset has a random sample of 100,000 sequences



Figure 10: Frequency distribution of the number of members in msnbc.com user clusters.



Figure 11: Graphical visualization of cluster representatives showing user behaviors.

for our analysis. The sequences' average length is 6.9 and their standard deviation is 27.3, with the range between 2 and 7440 and a skewed distribution.

Our objective is to group the users with similar navigation patterns, irrespective of differences in their session lengths, into clusters. We, therefore, take the *length-insensitive* SGT and use the random search procedure for optimal clustering in §3. We performed k-means clustering with manhattan distance and the goodness-of-fit criterion as db-index, and found the optimality at  $n_c = 104$  for  $\kappa = 9$ .

The frequency distribution of the number of members in each cluster is shown in Fig. 10. The frequency distribution has a long-tail—the majority of users belong to a small set of clusters. Nevertheless, it is important to understand the distinct behaviors of both the majority and minority user types to provide better personalized services.

### 5.2 Visualization

Effective visualization is a critical need for easy interpretation of data and its underlying properties. For example, in the above msnbc.com navigation data analysis, interpreting behavior of different user clusters is quite important.

In the following (Fig. 11a-11b), we show a graph visualization of some clusters' centroids (which are in the SGT space), because a centroid represents the behavior of users present in the cluster. We have filtered edges with small weights for better visualization.

Fig. 11a shows the centroid for the first cluster that contains the highest membership ( $\sim$ 12%) and thus indicates the "most" general behavior. This cluster's users' behavior is centered around frontpage and misc, with users' tendency to navigate between frontpage, misc, weather, opinion, news, travel and business at different levels.

Fig. 11b shows another majority cluster with about 7.5% membership. This group of users seems to have a liking for sports. They primarily visit **sports**-related pages (the box around the **sports** node indicates a self-visiting edge), and also move back and forth from **sports** to **frontpage**,

	Protein	Network
Sample size	2113	115
Sequence length range	(289, 300)	(12, 1773)
Class distribution	46.4% +	11.3% +
Alphabet set size	20 (amino acids)	49 (log events)

Table 2: Dataset attributes

SVM on- $\{\gamma_{protein}; \gamma_{network}\}$	Protein	Network
$SGT\{0.0014; 0.1\}$	$99.61\%, \kappa = 1$	89.65%, $\kappa = 10$
$Bag-of-words\{0.05; 0.02\}$	88.45%	48.32%
$2$ -gram $\{0.0025; 0.00041\}$	93.87%	63.12%
$3$ -gram $\{0.00012; 8.4e - 6\}$	95.12%	49.09%
$1+2$ -gram $\{0.0012; 0.0004\}$	94.34%	64.39%
$1+2+3$ -gram $\{4.0e-5; 8.2e-6\}$	96.89%	49.74%

Table 3: Classification accuracy (F1-score) based on 10-fold cross-validation results.

travel, misc, msn-sports/news, etc.

### 5.3 Classification

At many occasions, we have labeled sequence data where it is required to build a classification model. SGT can be used for this, and is demonstrated on two datasets: a) protein sequences<sup>1</sup> having either of two known functions, which act as the labels, and b) network intrusion data<sup>2</sup> containing audit logs and any attack as a positive label.

The dataset details are given in Table 2. For both problems we use the *length-sensitive* SGT. For proteins, it is due to their nature, while for network logs, the lengths are important because sequences with similar patterns but different lengths can have different labels. Take a simple example of following two sessions: {login, password, login, password, mail,...} and {login, password,...(repeated several times)

..., login, password}. While the first session can be a regular user mistyping the password once, the other session is possibly an attack to guess the password. Thus, the sequence lengths are as important as the patterns.

For the network intrusion data, the sparsity of SGTs was high. Therefore, we performed principal component analysis (PCA) on it and kept the top 10 PCs as sequence features. We call it SGT-PC, for further modeling. However, for proteins, the SGTs are used directly.

After obtaining the SGT (-PC) features, we trained a SVM classifier on them. For comparison, we used popular n-gram sequence classifiers, viz. bag-of-words (1-gram), 2-, 3-, 1+2-, and 1+2+3-gram. The SVM was built with an RBF kernel. The cost parameter, c, is equal to 1, while the value for the kernel parameter,  $\gamma$ , is shown within braces in Table 3. The table reports the average test accuracy (F1-score) from a 10-fold cross-validation.

As we can see in Table 3, the F1-scores are high for all methods in the protein data, with SGT-based SVM surpassing all others. On the other hand, the accuracies are small for the network intrusion data. This is primarily due to: a) a small dataset but high dimension (related to the alphabet set size), leading to a weak predictive ability of models, and b) a few positive class examples (unbalanced data) causing a

<sup>&</sup>lt;sup>1</sup>www.uniprot.org

<sup>&</sup>lt;sup>2</sup>https://www.ll.mit.edu/ideval/data/1998data.html

Protein	SGT-PC	Identity
S9A4Q5	33.02	46.3%
S8TYW5	34.78	46.3%
A0A029UVD9	39.21	45.1%
A0A030I738	39.34	45.1%
A0A029UWE3	39.41	45.1%

Table 4: Protein search query (Q9ZIM1) result.

poor recall rate. Still, SGT outperformed other methods by a significant margin. Although the accuracies of the methods can be further increased using other classifiers such as Boosting and Random Forest, it is beyond the scope of this paper. Here our purpose is to make a simplistic comparison to highlight the superiority of SGT features in building a supervised learning model.

### 5.4 Search

Most sequence databases found in the real world are very large. For example, protein databases have billions of sequences and increasing. Here we show that SGT sequence features can lead to a fast and accurate sequence search.

We collected a random sample of 1000 protein sequences from the UniProtKB database on www.uniprot.org. We transformed them to Euclidean space using *length-sensitive* SGT (with  $\kappa = 1$ ) to incorporate their length informations. Thereafter, to reduce the dimension we applied principal component analysis and preserved the first 40 principal components (explaining ~83% of variance), denoted by SGT-PC. We arbitrarily chose a protein sequence, Q9ZIM1<sup>3</sup> (ID notation from UniProtKB), as the search query.

We compute the manhattan distance between the SGT-PCs of the query and each sequence in the dataset. The top 5 closest sequences are shown with their SGT-PC distances in Table 4. For a reference, we also find the *identity* between the query and all other sequences. An identity between two sequences is the edit-distance between them after alignment. Here we find identities after a global alignment, with cost of gap-opening as 0 and gap-extension as 1. Note that alignment algorithms are approximate heuristics; thus, the identities should be seen only as a guideline and not ground truth.

We find that the maximum pairwise identity (=46.3%) corresponds to the smallest SGT-PC distance (33.02) for {Q9ZIM1 (query), S9A4Q5}. Also, the identity level decreases with increasing SGT-PC differences. Importantly, the computation time for finding SGT-PC distances between the query and the entire dataset is found to be 0.0014 sec on a 2.2GHz Intel i7 processor, while identity computations took 194.4 sec. Although the current in-use methods for protein data-bases, such as BLAST, have a faster alignment and identity computation procedure than a pairwise, it will still be more than finding vector differences as in SGT-based search.

### 6. DISCUSSION AND CONCLUSION

As we showed in §2.4 and validated in §4-5, SGT's ability to capture the overall pattern—short- and long-range structures—of a sequence into a fixed finite-dimensional space with shorter computation time makes it stand out. The other methods were found to have lower performance than SGT for this reason.

To bring this into perspective, compare SGT with a firstorder Markov model. Suppose we are analyzing sequences in which "B occurs *closely* after A." Due to stochasticity, the observed sequences can be like: a) **ABCDEAB**, and b) ABCDEAXB, where (b) is same as (a) but a noise X, appearing in between A and B. While the transition probability in the Markov model will be significantly different for (a:1.0) and (b:0.5), SGT is robust to such noises, (a:0.50)and (b:0.45) for  $\kappa = 5$ . The effect of the intermittent noise can be easily regulated by changing  $\kappa$ : choose a high  $\kappa$  to reduce the noise effect, with a caution that sometimes it may be part of the pattern. Furthermore, a Markov model cannot easily distinguish between these two sequences: ABCDEAB and ABCDEFGHIJAB, from the (A,B) transition probabilities (=1 for both). Differently, the SGT feature for (A,B) changes from 1.72 to 2.94 ( $\kappa = 1$ ), because it looks at the overall pattern. On another note, although deep learning methods can capture such overall patterns, their representations are in an arbitrary and usually very high dimension.

In summary, SGT is a novel approach for effective feature extraction on a sequence to give it a finite-dimensional representation in a Euclidean space. This bridges an existing gap between sequence problems and powerful mainstream data mining methods. Moreover, it has been shown to have a universal applicability to many sequence problems with various applications. Importantly, due to its low computational complexity and ease of parallelization, it can be scaled to most big sequence data problem. For future research, we should attempt to use SGT to develop new methods for diverse sequence problems in speech recognition, text analysis, bioinformatics, etc., or use it as an embedding layer in deep learning architectures.

### 7. REFERENCES

- I. Cadez, D. Heckerman, C. Meek, P. Smyth, and S. White. Model-based clustering and visualization of navigation patterns on a web site. *Data Mining and Knowledge Discovery*, 7(4):399–424, 2003.
- [2] M. Comin and D. Verzotto. Alignment-free phylogeny of whole genomes using underlying subwords. *Algorithms for Molecular Biology*, 7(1):1, 2012.
- [3] R. C. Edgar. Muscle: a multiple sequence alignment method with reduced time and space complexity. *BMC bioinformatics*, 5(1):1, 2004.
- [4] R. C. Edgar. Search and clustering orders of magnitude faster than blast. *Bioinformatics*, 26(19):2460–2461, 2010.
- [5] L. Fu, B. Niu, Z. Zhu, S. Wu, and W. Li. Cd-hit: accelerated for clustering the next-generation sequencing data. *Bioinformatics*, 28(23):3150–3152, 2012.
- [6] A. Graves. Generating sequences with recurrent neural networks. arXiv preprint arXiv:1308.0850, 2013.
- [7] J. Han, J. Pei, B. Mortazavi-Asl, H. Pinto, Q. Chen, U. Dayal, and M. Hsu. Prefixspan: Mining sequential patterns efficiently by prefix-projected pattern growth. In proceedings of the 17th international conference on data engineering, pages 215–224, 2001.
- [8] M. Hauser, C. E. Mayer, and J. Söding. kclust: fast

<sup>&</sup>lt;sup>3</sup>The protein sequence of Q9ZIM1 is, MSYQQQQCKQPC-QPPPVCPTPKCPEPCPPPKCPEPYLPPPCPPEHCPPPPCQDKCP-PVQPYPPCQQKYPPKSK

and sensitive clustering of large protein sequence databases. *BMC bioinformatics*, 14(1):1, 2013.

- [9] S. Helske and J. Helske. Mixture hidden markov models for sequence data: the seqhmm package in r, 2016.
- [10] P. Kumar, P. R. Krishna, and S. B. Raju. Pattern discovery using sequence data mining: applications and studies. Information Science Reference, 2012.
- [11] S. B. Needleman and C. D. Wunsch. A general method applicable to the search for similarities in the amino acid sequence of two proteins. *Journal of molecular biology*, 48(3):443–453, 1970.
- [12] C. Ranjan, K. Paynabar, J. E. Helm, and J. Pan. The impact of estimation: A new method for clustering and trajectory estimation in patient flow modeling. arXiv preprint arXiv:1505.07752, 2015.
- [13] M. Remmert, A. Biegert, A. Hauser, and J. Söding. Hhblits: lightning-fast iterative protein sequence searching by hmm-hmm alignment. *Nature methods*, 9(2):173–175, 2012.
- [14] P. Siyari, B. Dilkina, and C. Dovrolis. Lexis: An optimization framework for discovering the hierarchical structure of sequential data. In *Proceedings of the 22nd ACM SIGKDD*, KDD '16, pages 1185–1194, New York, NY, USA, 2016. ACM.
- [15] T. F. Smith and M. S. Waterman. Identification of common molecular subsequences. *Journal of molecular biology*, 147(1):195–197, 1981.
- [16] A. Tomović, P. Janičić, and V. Kešelj. n-gram-based classification and unsupervised hierarchical clustering of genome sequences. *Computer methods and programs in biomedicine*, 81(2):137–153, 2006.

# APPENDIX

## A. MEAN AND VARIANCE OF $\psi_{UV}$

To easily denote various (u, v) pairs in Fig. 4, we use a term,  $m^{th}$  neighboring pair, where an  $m^{th}$  neighbor pair for (u, v) will have m - 1 other u's in between. A first neighbor is thus the immediate (u, v) neighboring pairs, while the  $2^{nd}$ -neighbor has one other u in between, and so on (see Fig. 4). The *immediate* neighbor mentioned in the assumption in Sec. 2.4 is the same as the first neighbor defined here.

The following derivation follows Def. 1. Based on it, the expected number of first-neighbor (u, v) pairs is given as M = pL. Consequently, it is easy to show that the expected number of  $m^{th}$  neighboring (u, v) pairs is (M - m + 1), i.e., the second neighboring (u, v) pairs will be (M - 1), (M - 2) for the third, so on and so forth, till one instance for the  $M^{th}$  neighbor (see Fig. 4). The gap distance for an  $m^{th}$  neighbor is given as  $Z_1 = X$ ;  $Z_m = X + \sum_{i=2}^m Y_i, m = 2, \ldots, M$ .

neighbor (see Fig. 4). The gap distance for an  $m^{th}$  neighbor is given as  $Z_1 = X; Z_m = X + \sum_{i=2}^m Y_i, m = 2, ..., M$ . Besides, the total number of (u, v) pair instances will be  $\sum_{m=1}^M m = \frac{M(M+1)}{2} (= |\Lambda_{uv}|, \text{ by definition})$ . Suppose we define a set that contains distances for each possible (u, v)pairs as  $\mathcal{Z} = \{Z_m^i, i = 1, ..., (M - m + 1); m = 1, ..., M\}$ . Also, since  $Z_m \sim N(\mu_\alpha + (m-1)\mu_\beta, \sigma_\alpha^2 + (m-1)\sigma_\beta^2), \phi_\kappa(Z_m)$ becomes a lognormal distribution. Thus,

$$E[\phi_{\kappa}(Z_m)] = e^{-\tilde{\mu}_{\alpha} - (m-1)\tilde{\mu}_{\beta}}$$
(9)

$$\operatorname{var}[\phi_{\kappa}(Z_m)] = e^{-2\tilde{\mu}'_{\alpha}-2(m-1)\tilde{\mu}'_{\beta}} - e^{-2\tilde{\mu}_{\alpha}-2(m-1)\tilde{\mu}_{\beta}} (10)$$

where,

$$\tilde{\mu}_{\alpha} = \kappa \mu_{\alpha} - \frac{\kappa^2}{2} \sigma_{\alpha}^2 \quad ; \quad \tilde{\mu}_{\alpha}' = \kappa \mu_{\alpha} - \kappa^2 \sigma_{\alpha}^2$$
$$\tilde{\mu}_{\beta} = \kappa \mu_{\beta} - \frac{\kappa^2}{2} \sigma_{\beta}^2 \quad ; \quad \tilde{\mu}_{\beta}' = \kappa \mu_{\beta} - \kappa^2 \sigma_{\beta}^2 \qquad (11)$$

Besides, the feature,  $\psi_{uv}$ , in Eq. 3a can be expressed as,  $\sum_{i=1}^{n} \frac{E[\phi_{ui}(Z)]}{E[\phi_{ui}(Z)]}$ 

$$E[\psi_{uv}] = \frac{\sum_{Z \in \mathcal{Z}} E[\psi_{\kappa}(Z)]}{M(M+1)/2} \\ = \frac{\sum_{m=1}^{M} (M - (m-1))e^{-\tilde{\mu}_{\alpha} - (m-1)\tilde{\mu}_{\beta}}}{M(M+1)/2} \\ = \frac{2}{pL+1} \underbrace{\frac{e^{-\tilde{\mu}_{\alpha}}}{\left\lfloor \left(1 - e^{-\tilde{\mu}_{\beta}}\right) \left[1 - \frac{1 - e^{-pL\tilde{\mu}_{\beta}}}{pL(e^{\tilde{\mu}_{\beta}} - 1)}\right]}_{\gamma}}_{\gamma} (12)$$

This yields to the expectation expression in Eq. 4. Besides, the variances will be

$$\operatorname{var}(\psi_{uv}) = \left(\frac{1}{pL(pL+1)/2}\right)^{2} \left[ \left\{ \frac{e^{-2\tilde{\mu}'_{\alpha}}}{1-e^{-2\tilde{\mu}'_{\beta}}} \left( pL - e^{-2\tilde{\mu}'_{\beta}} \left( \frac{1-e^{-2\tilde{\mu}'_{\beta}}}{1-e^{-2\tilde{\mu}'_{\beta}}} \right) \right) \right\} - \left\{ \frac{e^{-2\tilde{\mu}_{\alpha}}}{1-e^{-2\tilde{\mu}_{\beta}}} \left( pL - e^{-2\tilde{\mu}_{\beta}} \left( \frac{1-e^{-2pL\tilde{\mu}_{\beta}}}{1-e^{-2\tilde{\mu}_{\beta}}} \right) \right) \right\} \right]$$
$$\operatorname{var}(\psi_{uv}) = \left\{ \left( \frac{1}{pL(pL+1)/2} \right)^{2} \pi^{-\pi} ; \text{length sensitive} \right. \left( \frac{1}{p(pL+1)/2} \right)^{2} \pi^{-\pi} ; \text{length insensitive} \right\}$$

# **B. SGT FOR UNDIRECTED SEQUENCES**

$$\begin{split} \tilde{\Lambda}_{uv}(s) &= \{(l,m): x_l = u, x_m = v, (l,m) \in 1, \dots, L^{(s)}\} \\ &= \{(l,m): x_l = u, x_m = v, l < m, (l,m) \in 1, \dots, L^{(s)}\} \\ &+ \{(l,m): x_l = u, x_m = v, l > m, (l,m) \in 1, \dots, L^{(s)}\} \\ &= \Lambda_{uv}(s) + \Lambda_{uv}^T(s) \end{split}$$

Next, the SGT for the undirected sequence in Eq. 8 can be expressed as,

$$\begin{split} \tilde{\Psi}_{uv}(s) &= \frac{\sum_{\forall (l,m) \in \tilde{\Lambda}_{uv}(s)} \phi_{\kappa}(d(l,m))}{|\tilde{\Lambda}_{uv}(s)|} \\ &= \frac{\sum_{\forall (l,m) \in \Lambda_{uv}(s)} \phi_{\kappa}(d(l,m)) + \sum_{\forall (l,m) \in \Lambda_{uv}^T(s)} \phi_{\kappa}(d(l,m))}{|\Lambda_{uv}(s)| + |\Lambda_{uv}^T(s)|} \\ &= \frac{|\Lambda_{uv}(s)|\Psi_{uv}(s) + |\Lambda_{uv}^T(s)|\Psi_{uv}^T(s)}{|\Lambda_{uv}(s)| + |\Lambda_{uv}^T(s)|} \end{split}$$

# C. PROOF FOR ALPHABET CLUSTERING

We have,  $\frac{\partial \Delta}{\partial \kappa} = \frac{\partial}{\partial \kappa} E[\phi_{\kappa}(X) - \phi_{\kappa}(Y)] = E[\frac{\partial}{\partial \kappa}\phi_{\kappa}(X) - \frac{\partial}{\partial \kappa}\phi_{\kappa}(Y)]$ . For E[X] < E[Y], we want,  $\frac{\partial \Delta}{\partial \kappa} > 0$ , in turn,  $\frac{\partial}{\partial \kappa}\phi_{\kappa}(X) > \frac{\partial}{\partial \kappa}\phi_{\kappa}(Y)$ . This will hold if  $\frac{\partial^2}{\partial d \partial \kappa}\phi_{\kappa}(d) > 0$ , that is, slope,  $\frac{\partial}{\partial \kappa}\phi_{\kappa}(d)$  is increasing with d. For an exponential expression for  $\phi$  (Eq. 1), the above condition holds true if  $\kappa d > 1$ . Hence, under these conditions, the *separation* increases as we increase the tuning parameter,  $\kappa$ .