

RMPCDMD: Simulations of colloids with coarse-grained hydrodynamics, chemical reactions and external fields

Pierre de Buyl,¹ Mu-Jie Huang,² and Laurens Deprez¹

¹*Instituut voor Theoretische Fysica, KU Leuven B-3001, Belgium*

²*Chemical Physics Theory Group, Department of Chemistry, University of Toronto, Toronto, Ontario M5S 3H6, Canada*

The RMPCDMD software package performs hybrid Molecular Dynamics simulations, coupling Multiparticle Collision Dynamics to model the solvent and Molecular Dynamics to model suspended colloids, including hydrodynamics, thermal fluctuations, and chemically active solvent particles and catalytic colloids. The main usage of RMPCDMD is the simulation of chemically powered nanomotors, but other setups are considered: colloids in the presence of a thermal gradients or forced flows. RMPCDMD is developed in Fortran 2008 with OpenMP for multithreaded operation and uses the HDF5-based H5MD file format for storing data. RMPCDMD comes with documentation and a tutorial for the simulation of chemically powered nanomotors.

KEYWORDS

Molecular Dynamics ; Colloids ; Hydrodynamics ; Nanomotors ; Fortran ; Python

I. OVERVIEW

A. Introduction

Molecular Dynamics (MD) is a computational technique to study condensed matter systems by numerically solving Newton's equations of motion for a large number of particles [1]. Often, due to the number of constituents in a system, so-called *coarse-grained* or *multiscale* strategies are used to reduce the computational cost of a simulation.

One simulation strategy for modelling colloids embedded in a solvent is to couple the Multiparticle Collision Dynamics (MPCD) algorithm [2] for the solvent with MD for the colloids [3]. It differs from *traditional* MD by the use of a coarse-grained representation of the solvent's structure and dynamics and by the possible occurrence of chemical species transformations in the course of the simulation. In the latter case, the extension Reactive MPCD (RMPCD) provides bulk chemical kinetics that reduce to reaction-diffusion equations [4]. The name RMPCDMD results from the concatenation of the different algorithms' acronyms: Reactive Multiparticle Collision Dynamics and Molecular Dynamics.

The focus of RMPCDMD lies on the modeling of chemically active colloids (e.g. nanomotors [5]) or of colloids subjected to external gradients (e.g. flows [6] or temperature gradients [7]). A RMPCDMD simulation consists in N_{solvent} solvent particles and N_{colloids} colloidal particles with a mass, position, and velocity, placed in a cuboid domain. Colloid-solvent and colloid-colloid interactions follow Lennard-Jones type potentials, but there is no interaction potential acting among the solvent particles. As $N_{\text{solvent}} \gg N_{\text{colloids}}$, this considerably speeds up a simulation in comparison to a full MD simulation. The time evolution of colloidal and solvent particles follows Newton's equations of motion, which are solved iteratively using the velocity-Verlet algorithm [1, 8]. The output from a simulation is a trajectory representing the coordinates of all particles in the course of time. Typically, solvent data is preaveraged during the simulation as its storage requires significant amounts of space.

B. Implementation and architecture

1. Development

RMPCDMD is implemented in Fortran, following the 2008 version of the standard, and uses OpenMP for multi-core execution. Trajectories are stored in the H5MD file format [9], and Python programs are provided to illustrate data analysis. The module `fortran_h5md` [10] provides helper routines to write H5MD files from Fortran. H5MD files are HDF5 files (<https://www.hdfgroup.org/HDF5/>) with an internal organization tailored for molecular simulations [9].

In designing RMPCDMD, we tried to adopt practices for scientific computing that help to deliver reproducible results and facilitate the extension of the code and its maintenance. We also made special efforts on the usability of

the software. The design choices are the results of the authors’ experience on scientific programming, with further motivation by the article on “Best Practices for Scientific Computing” by Wilson *et al* [11]:

- The algorithms are implemented in Fortran modules in the `src/` directory and shared between the simulations found in `programs/`. Table I summarizes their content.
- Subroutines and functions are limited in size, so that understanding any single code unit remains reasonable.
- Data is encapsulated in *derived types*.
- No global variable is used, to clarify to the reader what data is passed to subroutines.
- The programming style strives for legibility, conciseness, and efficiency.
- All simulation parameters are given from a text configuration file, there is no hard-coded setting in the code that would require re-compilation between runs.
- The code is tracked with the git revision control software [12] and published on GitHub (<https://github.com/>).
- The build procedure and partial testing are automatically executed on the Travis CI platform (<https://travis-ci.org/>) for continuous integration.

Module name	Functionality
<code>common</code>	Routines of general use: histogramming, parsing of command-line arguments, timing and minimum-image convention function.
<code>hilbert</code>	Computation of the compact Hilbert index of a lattice cell and vice-versa.
<code>cell_system</code>	Cell data structure.
<code>particle_system</code>	Particles data structure and sorting routine.
<code>particle_system_io</code>	Data structures to facilitate the storage of thermodynamic and particle data.
<code>interaction</code>	Computation of Lennard-Jones force and energy.
<code>neighbor_list</code>	Data structure and routines to update the neighbor list.
<code>mpcd</code>	Algorithms for MPCD streaming and collision, and for bulk reactions.
<code>md</code>	Algorithms for velocity-Verlet and rigid body MD.

TABLE I. A summary of the functionality provided by the Fortran modules of RMPCDMD found in the `src/` directory.

Instead of building a generic program that could handle the logic of different geometries, boundary conditions, and colloid types, specific simulation programs have been implemented. Each program calls the algorithms from the modules and resembles a statically compiled “simulation script”. The amount of administrative code (reading parameters, defining storage, etc.) is however larger than what could be achieved in a higher-level language such as Python.

CMake is used to build RMPCDMD and run automated tests in `test/` that cover some of the base algorithms such as particle sorting or the histogram routine. The Fortran module `fortran_tester` [13] provide convenience routines for testing (e.g. equality assertions). Automated testing using actual simulations is difficult and very much time intensive, and we rely on it only for a small part of the code. In simulations without a thermostat or wall interactions, the total momentum and energy of the system must be conserved, which is verified for a short run of the `single_dimer_pbc` simulation as part of the continuous integration testing. Further validation of the code is done via comparison of physical results: the velocity distribution of particles in equilibrium, the viscosity of the fluid, etc.

2. User perspective

For the end-user, the interface comes as a single command-line tool, `rmpcdmd`, that drives the simulations and provides access to utility programs. A typical command is

```
rmpcdmd run single_dimer_pbc dimer.parameters dimer.h5 auto
```

where `single_dimer_pbc` is the simulation program, `dimer.parameters` is the configuration file, `dimer.h5` the output datafile, and `auto` is the setting for the random-number seed. While the individual programs can be run directly, the command-line tool `rmpcdmd` aims to provide a single file to place in the program “PATH” on the user’s computer and to automate some actions. The commands available are:

run: execute one of the simulation programs. The setting of the environment variable `OMP_NUM_THREADS`, and the start and end time of the run are shown. Bash’s `time` provides the “user time” actually used by the program.

seeder: print out a signed 64-bit integer value generated by the computer’s `/dev/urandom` device.

plot: display an observable from a simulation file.

timers: print out (or display) the timing information from a simulation file.

A benefit of using separate simulation programs is that the configuration file for a simulation only contains directly relevant parameters. All simulation programs share the same command-line syntax, read parameters from a text file using the ParseText Fortran library [14], read the seed for the RNG from the command line and output the trajectory to a H5MD file. An example configuration file for `single_dimer_pbc` is listed in Appendix A.

A generic plotting utility is provided and can be invoked as

```
rmpcdmd plot dimer.h5 --obs temperature
```

to plot the temperature, for instance. This plotting program and the other analysis programs that come with RMPCDMD are written in Python and rely on NumPy for storing and processing numerical data, SciPy [15] for numerical algorithms, Matplotlib [16] to produce 2D figures, h5py [17] to read HDF5 files and Mayavi [18] to visualize 3D data.

C. Documentation

A documentation is found in the directory `doc/`. It is published on the web, <http://lab.pdebuy1.be/rmpcdmd/> and also serves as the homepage of RMPCDMD. The documentation is built with the Sphinx documentation generator [19] and is written in reStructuredText. An extension to Sphinx is bundled with RMPCDMD to provide (i) automatic links from the documentation to the source code documentation that is annotated with Doxygen (<http://www.stack.nl/~dimitri/doxygen/>) and (ii) automatic inclusion of the Doxygen header of Fortran programs. Specific instructions for the installation and execution of RMPCDMD are provided, as well as general information on the algorithms are presented. The description of the simulation programs is generated automatically from the beginning of the corresponding `.f90` files and includes all parameters for the simulations.

A tutorial on the simulation of chemically powered nanomotors, based on RMPCDMD, was given at the recent workshop “Modeling of chemically powered nanomotors” held at the KU Leuven in April 2016 (<http://lab.pdebuy1.be/2016-nanomo>). This tutorial is reproduced in the documentation of RMPCDMD and represents a unique resource in the field of nanomotor simulation.

D. Algorithms

For completeness, we state here exactly what algorithms are implemented in RMPCDMD, with the corresponding reference to the literature.

RMPCDMD implements the original MPCD collision rule [2] and the Anderson thermostat [20]. Random shifting of the spatial grid is always performed [21] to ensure Galilean invariance. Flows are generated by applying a constant acceleration to solvent particles [22, 23]. Stick boundary conditions at the wall use the bounce-back rule and virtual particles during the collision step [24].

Molecular Dynamics is performed with the velocity-Verlet algorithm [1, 3, 8]. The interaction potential, both for solvent–colloid and colloid–colloid interactions, are purely repulsive cut-off 12–6 Lennard-Jones potentials of the form

$$V(r) = 4\epsilon \left(\left(\frac{\sigma}{r}\right)^{12} - \left(\frac{\sigma}{r}\right)^6 + \frac{1}{4} \right) \text{ for } r < 2^{1/6}\sigma$$

where the energy parameter ϵ and the scale parameter σ depend on the species considered. Verlet and cell lists are used to compute the solvent–colloid forces and energies [1]. The sorting of solvent particles in cells is the same as for the MPCD collision step. The rigid body dynamics uses RATTLE [25] in its iterative implementation for the Janus particle and exactly for the dimer motor.

Spatial sorting of the solvent particles is based on compact Hilbert indices [26]. Random numbers are generated with the Threefry 2x64 RNG [27], allowing each OpenMP thread to generate random numbers independently. The RNG is provided by the `random_module` library [28], where it is implemented in C99. The choices are inspired by the `nano-dimer` [29] simulation code, which implements these algorithms in OpenCL C for large-scale parallel processors.

To obtain a consistent measure of the temperature T even in the presence of flows, we compute T by averaging the center-of-mass reference frame temperature over all MPCD cells as

$$T = \frac{1}{3N_c} \sum_{\xi} \frac{1}{N_{\xi} - 1} \sum_i m_i (v_i - v_{\xi})^2$$

where N_c is the number of cells, the variable ξ represents a cell, N_{ξ} the number of particles in a cell, v_{ξ} the center-of-mass velocity of the cell, and m_i and v_i the mass and velocity of particle.

E. Applications of RMPCDMD

The prototypical use of the MPCD algorithm to study chemically active particles is the dimer nanomotor, whose model was introduced by Rückner and Kapral [5]. It consists of two rigidly linked spheres evolving in a solvent. Chemical reactions are catalyzed by one of the spheres and create a local concentration gradient, effectively propelling the dimer along its symmetry axis. This simulation is implemented in the program `single_dimer_pbc`.

To facilitate usage of RMPCDMD by newcomers, ready-made simulation “experiments” are provided in `experiments/`. There, makefiles allow the user to simply type

```
make simulation
```

to start a simulation. The terminology that we have chosen reflects our opinion that computer simulations can be viewed as numerical experiments in which one prepares a setup and conducts a study to understand a certain physical phenomenon. The ability to modify a given experimental choice (i.e. thermostating or not, surface properties, etc.) to assess its effect is therefore critical. By providing several chemical models and collision rules, RMPCDMD provides such a framework.

Four programs are provided to analyze the data of this experiment. `plot_velocity.py` displays the laboratory reference frame velocity or the directed velocity of the dimer (with the option `--directed`). `plot_histogram.py` displays the cylindrical shell histogram of the reaction product concentration. `plot_msd.py` displays the mean-squared displacement of the dimer’s center-of-mass position. This quantity is a practical interest in comparison to experimental studies [30]. `view_last_simulation_frame.py` displays a 3D representation of the dimer motor using the Mayavi visualization library [18], either with its full trajectory as a line (with option `--unwrap`) or with the product solvent particles B (with option `--show-B`). The two first analysis programs are modeled after the results by Rückner and Kapral [5].

While the aims of `single_dimer_pbc` are to reproduce Ref. [5] and to provide a starting point for other developments, the other simulation programs in RMPCDMD are related to forward-looking research projects that will benefit from a robust codebase. These other setups are: `poiseuille_flow` generates a Poiseuille flow between parallel plates, with no colloid. `chemotactic_cell` generates a Poiseuille flow with a two-species chemical gradient perpendicular to the flow and an embedded spherical colloid or a dimer nanomotor. `single_janus_pbc` implements a composite Janus nanomotor [31]. `single_sphere_thermo_trap` generates a thermal gradient between two plates, with an embedded spherical colloid.

II. AVAILABILITY

Operating System: RMPCDMD has been tested on Linux using the `gcc/gfortran` and `icc/ifort` compilers and on OS X (El Capitan) using `gcc/gfortran` (installed via MacPorts).

Programming Language: Fortran 2008 for the simulation code, C99 for the Random Number Generator, bash and make for the execution and Python (with NumPy, SciPy, matplotlib and h5py) for analysis.

Additional system requirements: The largest RAM usage in RMPCDMD comes from the solvent coordinates and requires about $N_{\text{solvent}} \times 250$ bytes of storage. The example simulations in the `experiments/` directory require between 100MB and 200MB of RAM.

Dependencies: The CMake and Make tools, and the HDF5 library. For data analysis, NumPy, SciPy, matplotlib and h5py.

LIST OF CONTRIBUTORS

Pierre de Buyl: Project creator, code, documentation, build system, tutorial.

Laurens Deprez: Code: RATTLE for the dimer, angle-dependent MPCD, boundary conditions and forcing for flows, Lennard-Jones 9-3 walls, chemotactic cell setup.

Mu-Jie Huang: Tutorial: Janus particle.

Peter Colberg: Initial OpenMP parallelization, continuous integration testing and build system.

SOFTWARE LOCATION

Archive

Name: Zenodo

Persistent identifier: DOI

Licence: BSD 3-clause

Publisher: Pierre de Buyl

Version published: 0.1

Date published: TODO

Code repository

Name: GitHub

Persistent identifier: <https://github.com/pdebuy1-lab/RMPCDMD>

Licence: BSD 3-clause

Date published: TODO

III. REUSE POTENTIAL

Besides `nano-dimer` [29] (by Peter Colberg, available under the MIT license), RMPCDMD is the only open-source software to provide support for chemically-powered nanomotor simulation. RMPCDMD has, in addition to `nano-dimer`, support for external fields or rigid-body dynamics for assemblies larger than the dimer. `nano-dimer`, on the other hand, is based on OpenCL C and on the Message Passing Interface for distributed parallel execution, and is able to handle many-motors simulations that are out of reach of RMPCDMD for performance reasons. Given the research activity on the topic of active colloids, we believe that providing a reference implementation of a chemically active MPCD fluid can serve as a starting point for further modeling, by us or by other groups.

RMPCMD has not been used for published work yet. It is in use for ongoing research projects at the *Instituut voor Theoretische Fysica* of the KU Leuven.

ACKNOWLEDGMENTS

The authors thank Raymond Kapral for discussions and for motivating this line of research, and Peter Colberg for his contributions to the code, his comments on the manuscript and for interesting discussions. The authors thank all authors of the open-source projects that they rely on for their research. PdB is a postdoctoral fellow of the Research Foundation-Flanders (FWO).

COMPETING INTERESTS

The authors declare that they have no competing interests.

-
- [1] Frenkel, D and Smit, B (2002). *Understanding molecular simulation: From algorithms to applications*. 2nd edition (Academic Press, San Diego, CA).
- [2] Malevanets, A and Kapral, R (1999). Mesoscopic model for solvent dynamics. *J. Chem. Phys.* 110: 8605. doi: 10.1063/1.478857.
- [3] Malevanets, A and Kapral, R (2000). Solute molecular dynamics in a mesoscale solvent. *J. Chem. Phys.* 112: 7260. doi:10.1063/1.481289.
- [4] Rohlf, K, Fraser, S and Kapral, R (2008). Reactive multiparticle collision dynamics. *Comput. Phys. Commun.* 179: 132. doi:10.1016/j.cpc.2008.01.027.
- [5] Rückner, G and Kapral, R (2007). Chemically powered nanodimers. *Phys. Rev. Lett.* 98: 150603. doi: 10.1103/PhysRevLett.98.150603.
- [6] Prohm, C, Gierlak, M and Stark, H (2012). Inertial microfluidics with multi-particle collision dynamics. *Eur. Phys. J. E* 35(8): 80. ISSN 1292-8941. doi:10.1140/epje/i2012-12080-3. URL <http://dx.doi.org/10.1140/epje/i2012-12080-3>.
- [7] Lüsebrink, D, Yang, M and Ripoll, M (2012). Thermophoresis of colloids by mesoscale simulations. *J. Phys. Cond. Matt.* 24(28): 284132. doi:10.1088/0953-8984/24/28/284132.
- [8] Allen, MP and Tildesley, DJ (1987). *Computer Simulation of Liquids* (Clarendon Press, Oxford).
- [9] de Buyl, P, Colberg, PH and Höfling, F (2014). H5MD: A structured, efficient, and portable file format for molecular data. *Comp. Phys. Commun.* 185: 1546–1553. doi:10.1016/j.cpc.2014.01.018.
- [10] de Buyl, P (2015-2016). `fortran_h5md`. https://github.com/pdebuyl/fortran_h5md.
- [11] Wilson, G, Aruliah, DA, Brown, CT, Hong, NPC, Davis, M, Guy, RT, Haddock, SHD, Huff, KD, Mitchell, IM, Plumbley, MD, White, BWE and Wilson, P (2014). Best practices for scientific computing. *PLoS Biol* 12: e1001745. doi: 10.1371/journal.pbio.1001745.
- [12] Git. URL <https://git-scm.com/>. <https://git-scm.com/>.
- [13] de Buyl, P (2015-2016). `fortran_tester`. https://github.com/pdebuyl/fortran_tester.
- [14] de Buyl, P (2011-2016). `ParseText`. <https://github.com/pdebuyl/ParseText>.
- [15] Jones, E, Oliphant, T, Peterson, P *et al.* (2001–). SciPy: Open source scientific tools for Python. URL <http://www.scipy.org/>.
- [16] Hunter, JD (2007). Matplotlib: A 2d graphics environment. *Computing In Science & Engineering* 9(3): 90–95. doi: 10.1109/MCSE.2007.55.
- [17] Collette, A (2013). *Python and HDF5* (O’Reilly).
- [18] Ramachandran, P and Varoquaux, G (2011). Mayavi: 3d visualization of scientific data. *Comput. Sci. Eng.* 13(2): 40–51. doi:10.1109/MCSE.2011.35.
- [19] Brandl, G (2007-2016). Sphinx. URL <http://www.sphinx-doc.org/>. <http://www.sphinx-doc.org/>.
- [20] Noguchi, H, Kikuchi, N and Gompper, G (2007). Particle-based mesoscale hydrodynamic techniques. *EPL (Europhysics Letters)* 78(1): 10005. doi:10.1209/0295-5075/78/10005.
- [21] Ihle, T and Kroll, DM (2001). Stochastic rotation dynamics: A galilean-invariant mesoscopic model for fluid flow. *Phys. Rev. E* 63: 20201. doi:10.1103/PhysRevE.63.020201.
- [22] Allahyarov, E and Gompper, G (2002). Mesoscopic solvent simulations: Multiparticle-collision dynamics of three-dimensional flows. *Phys. Rev. E* 66: 36702. doi:10.1103/PhysRevE.66.036702.
- [23] Whitmer, JK and Luijten, E (2010). Fluid–solid boundary conditions for multiparticle collision dynamics. *J. Phys. Condens. Matt.* 22(10): 104106. doi:10.1088/0953-8984/22/10/104106.
- [24] Lamura, A, Gompper, G, Ihle, T and Kroll, DM (2001). Multi-particle collision dynamics: Flow around a circular and a square cylinder. *EPL (Europhysics Letters)* 56: 319. doi:10.1209/epl/i2001-00522-9.
- [25] Andersen, HC (1983). Rattle: A "velocity" version of the shake algorithm for molecular dynamics calculations. *J. Comp. Phys.* 52: 24. doi:10.1016/0021-9991(83)90014-1.
- [26] Hamilton, CH (2006). Compact hilbert indices. Technical Report CS-2006-07, Dalhousie University. URL <https://www.cs.dal.ca/research/techreports/cs-2006-07>.
- [27] Salmon, JK, Moraes, MA, Dror, RO and Shaw, DE (2011). Parallel random numbers: As easy as 1, 2, 3. In *Proceedings of 2011 International Conference for High Performance Computing, Networking, Storage and Analysis, SC '11*, pages 16:1–16:12 (ACM, New York, NY, USA). ISBN 978-1-4503-0771-0. doi:10.1145/2063384.2063405. URL <http://doi.acm.org/10.1145/2063384.2063405>.
- [28] de Buyl, P (2015-2016). `random_module`. https://github.com/pdebuyl/random_module.
- [29] Colberg, PH (2013-2015). `nano-dimer`. URL <https://colberg.org/nano-dimer/>. <https://colberg.org/nano-dimer/>.
- [30] Howse, JR, Jones, RAL, Ryan, AJ, Gough, T, Vafabakhsh, R and Golestanian, R (2007). Self-motile colloidal particles: From directed propulsion to random walk. *Phys. Rev. Lett.* 99: 48102. doi:10.1103/PhysRevLett.99.048102.
- [31] de Buyl, P and Kapral, R (2013). Phoretic self-propulsion: a mesoscopic description of reaction dynamics that powers motion. *Nanoscale* 5: 1337–1344. doi:10.1039/c2nr33711h.

Appendix A: Example configuration file

An example configuration file for the program `single_dimer_pbc` is shown below.

```
# physical parameters
T = 1
L = 32 32 32
rho = 10
tau = 1
probability = 1.0
bulk_rmpcd = T
bulk_rate = 0.1

# simulation parameters
N_MD = 100
N_loop = 500

# interaction parameters
sigma_N = 3.0
sigma_C = 3.0

d = 6.5
epsilon_N = 1.0 0.2
epsilon_C = 1.0 1.0

epsilon_N_N = 1.0
epsilon_N_C = 1.0
epsilon_C_C = 1.0
```