

Bayesian Statistics in Software Engineering: Practical Guide and Case Studies

Carlo A. Furia

Chalmers University of Technology, Gothenburg, Sweden

furia@chalmers.se bugcounting.net

Abstract—Statistics comes in two flavors: frequentist and Bayesian. For a variety of historical and technical reasons, frequentist statistics has dominated data analysis in the past; but Bayesian statistics is making a comeback at the forefront of science. In this paper, we give a practical overview of Bayesian statistics for the kinds of analyses that are common in empirical software engineering, and illustrate its main advantages over frequentist statistics. We also practically demonstrate Bayesian statistics by applying it to empirical data from previous research investigating the performance of programming languages, agile vs. structured development processes, and random testing of object-oriented programs. In addition to being three case studies of how Bayesian analysis can be applied in practice, the analyses provide new insights beyond the results in the original publications (which used frequentist statistics), thus showing the practical value brought by Bayesian statistics.

I. INTRODUCTION

A towering figure in evolutionary biology and statistics, Ronald Fisher has exerted a tremendous influence on pretty much all of experimental science since the early decades of the 20th century. The statistical techniques he developed constitute the customary data analysis toolset of *frequentist statistics*, in direct contrast to the other school of statistics—known as *Bayesian statistics* since it is ultimately based on Bayes theorem of conditional probabilities. The overwhelming prevalence of frequentist statistics in all the sciences was due partly to Fisher’s keen efforts of promotion, partly to its claim of being “more objective”, and partly to its techniques being less computationally demanding than Bayesian ones—a crucial concern with the limited computational resources available in the first part of the past century.

In the last couple of decades, however, the scientific community has begun a critical re-examination of the toolset of frequentist statistics, with particular focus on the widespread technique of statistical hypothesis testing using p -values. The critics, who include prominent statisticians such as Cohen [13], have observed methodological shortcomings—which may have warped the picture drawn by empirical studies that claimed “significant” results based on hypothesis testing [14], [27]—and, more generally, limitations of the frequentist’s rigid view. On the other hand, the difficulties of applying Bayesian analysis due to its higher computational demands have become moot with the vast computing power available nowadays. As a result, Bayesian techniques are becoming increasingly popular in science, and have buttressed spectacular advances

in automation and machine learning such as the deep neural networks that powered Google’s AlphaGo [21].

As we argue in Sect. II, frequentist statistics is still dominant in empirical software engineering research, whose best practices have been perfected only relatively recently compared to other sciences. The main contribution of this paper is thus casting the usage of Bayesian statistics as an alternative and as a supplement to frequentist statistics in the context of the data analyses that are common in software engineering.

To make the presentation self contained, in Sect. III we briefly recall some fundamental notions of probability, and then introduce Bayes theorem—the cornerstone of Bayesian analysis. In Sect. III-B we explain the shortcomings of frequentist statistical hypothesis testing, and suggest Bayes factors as an alternative techniques. We also present other analyses that are fueled by Bayes theorem, and argue about the significant advantages of taking a Bayesian point of view.

In Sect. IV we then proceed to “eat our own dog food” and demonstrate Bayesian analysis on three case studies whose main data is taken from previous work of ours on the performance of programming languages [38], agile vs. structured development processes [19], [20], and random testing with specifications [43]. We focused on some of our own publications both because their data was (obviously) more readily available to us, and to show that we too used to rely entirely on the toolset of frequentist analysis. In each case, we take the same data that we analyzed using frequentist statistics in the original publications, and perform a new analysis that refines the original results or increases the confidence we have in them. In two case studies we even supplement the original experiments with additional data obtained by other researchers in comparable conditions. This turns on its head the criticism that Bayesian analysis is “less objective” than frequentist one because it depends on prior information: incorporating independently obtained information can be, in fact, conducive to richer and more robust analyses—provided it is done sensibly following justifiable modeling choices.

Sect. V discusses threats to validity, emphasizing where Bayesian statistics can help mitigate them. Sect. VI concludes with a list of practical guidelines to applying Bayesian analysis in empirical software engineering. Software engineering researchers should be aware of all the possibilities offered by statistics and be able to deploy the best tools of the trade pragmatically in each situation. Since frequentist techniques are already well understood, it is time to make some room for

Bayesian analysis.

Availability. The case study description focuses on the analysis design and its main results; the appendix includes more details about measures, statistics, and plots.

II. RELATED WORK

Empirical research in software engineering. Statistical analysis of empirical data has become commonplace in software engineering research [54], and it is even making its way into software development practices [32]. As a result of this popularity, *best practices* of using statistics in software engineering have been formulated [3], [54], [29] that have been widely adopted. The near entirety of statistical techniques that are being used in software engineering empirical research are, however, of the frequentist kind, with Bayesian statistics hardly even mentioned. Of course, Bayesian statistics are a fundamental component of many machine learning techniques [26], [7]; as such, they are used in software engineering research indirectly whenever machine learning is used. In this paper, however, we are concerned with the direct usage of statistics on empirical data, which is where the state of the art in software engineering seems mainly confined to frequentist techniques. As we argue in the rest of the paper, this is a lost opportunity because Bayesian techniques do not suffer from some technical limitations of frequentist ones, and can support rich, robust analyses in several situations.

Bayesian analysis in software engineering. To validate the perception that Bayesian statistics are not normally used in empirical software engineering, we carried out a small literature review of ICSE papers.¹ We selected all papers from the latest four editions of the International Conference on Software Engineering (ICSE 2013 to ICSE 2016) that mention “empirical” in their title or in their section’s name in the proceedings. This gave 22 papers,² from which we discarded one [49] that is actually not an empirical study. The experimental data in the remaining 21 papers come from various sources: the output of analyzers and other programs [12], [37], [41], [11], the mining of repositories of software and other artifacts [57], [10], [58], [35], [45], the outcome of controlled experiments involving human subjects [55], [51], [40], interviews and surveys [42], [6], [8], [46], [16], [34], [33], and a literature review [48].

As one would expect from a top-tier venue like ICSE, the papers follow the recommended practices in reporting and analyzing data at least to some extent, using significance testing (5 papers), effect sizes (3 papers), correlation coefficients (4 papers), frequentist regression (2 papers), and visualization in charts or tables (20 papers). None of the papers, however, uses Bayesian statistics. In fact, no paper but [57], [16] even mentions the terms “Bayes” or “Bayesian”. One exception [57] only cites Bayesian machine-learning techniques used in related work to which it compares. The

other exception [16] includes a presentation of the two views of frequentist and Bayesian statistics—with a critique of p -values similar to the one we make in Sect. III-B—but does not show how the latter can be used in practice. [16]’s main aim is investigating the relationship between empirical findings in software engineering and the actual beliefs of programmers about the same topics. To this end, it is based on a survey of programmers whose responses are analyzed using frequentist statistics; Bayesian statistics is mentioned only to frame the discussion about the relationship between evidence and beliefs (but it is not mentioned after the introductory second section). Our paper has a more direct aim: concretely showing how Bayesian analysis can be applied in practice in empirical software engineering research, as an alternative to frequentist statistics; thus, its scope is largely complementary to [16]’s.

Criticism of the p -value. Statistical hypothesis testing—and its summary outcome, the p -value—has been customary in experimental science for many decades, both for the influence of his proponents Fisher, Neyman, and Pearson, and because it offers a straightforward, ready-made procedure that is computationally simple. More recently criticism of frequentist hypothesis testing has been voiced in many experimental sciences, such as psychology [47], [14] and medicine [24], that used to rely on it heavily, as well as in statistics research itself [53], [22]. The criticism, which we articulate in Sect. III-B, concludes that p -value-based hypothesis testing should be abandoned. There has been no similar explicit criticism of p -values in software engineering research, and in fact statistical hypothesis testing is still regularly used.

Guidelines for using statistics. Best practices of using (frequentist) statistics in empirical software engineering are described in a few books [54], [36] and articles [3], [4], [29]. Given their focus on frequentist statistics, they all are complementary to the present paper, whose main goal is showing how Bayesian techniques can add to, or replace, frequentist ones, and how they can be applied in practice.

III. A PRACTICAL OVERVIEW OF BAYESIAN STATISTICS

Statistics provides models of *events*, such as the output of a randomized algorithm; the probability function \mathbb{P} assigns probabilities—values in the real unit interval $[0, 1]$, or equivalently percentages in $[0, 100]$ —to events. Often, events are values taken by *random variables* that follow a certain probability *distribution*. For example, if X is a random variable modeling the throwing of a six-face dice, it means that $\mathbb{P}[x] = 1/6$ for $x \in [1..6]$, and $\mathbb{P}[x] = 0$ for $x \notin [1..6]$ —where $\mathbb{P}[x]$ is a shorthand for $\mathbb{P}[X = x]$, and $[m..n]$ is the set of integers between m and n .

The probability of variables over discrete domains is described by *probability mass functions* (p.m.f. for short); their counterparts over continuous domains are probability density functions (p.d.f.), whose integrals give probabilities. In this paper we mostly deal with discrete domains and p.m.f., or p.m.f. approximating p.d.f., although most notions apply to continuous-domain variables as well with a few technical differences. For convenience, we may denote a distribution and

¹[46] has a much more extensive literature survey of empirical publications in software engineering.

²By the way, 7 of them were only available behind a paywall, which is regrettable.

its p.m.f. with the same symbol; for example, random variable X has a p.m.f. also denoted X , such that $X[x] = \mathbb{P}[x] = \mathbb{P}[X = x]$.

Conditional probability. The *conditional* probability $\mathbb{P}[h | d]$ is the probability of h given that d has occurred. When modeling experiments, d is the empirical data that has been recorded, and h is a hypothesis that is being tested. Consider a static analyzer that outputs \top (resp. \perp) to indicate that the input program never overflows (resp. may overflow); $\mathbb{P}[\text{OK} | \top]$ is the probability that, when the algorithm outputs \top , the input is indeed free from overflows—the data is the output and the hypothesis is “the input does not overflow”.

A. Bayes Theorem

Bayes theorem connects the conditional probabilities $\mathbb{P}[h | d]$ and $\mathbb{P}[d | h]$:

$$\mathbb{P}[h | d] = \frac{\mathbb{P}[d | h] \cdot \mathbb{P}[h]}{\mathbb{P}[d]}. \quad (1)$$

Suppose the static analyzer gives true positives and true negatives with high probability ($\mathbb{P}[\top | \text{OK}] = \mathbb{P}[\perp | \text{ERR}] = 0.99$), and that many programs are affected by some overflow errors ($\mathbb{P}[\text{OK}] = 0.01$). Whenever the analyzer outputs \top , what is the chance that the input is indeed free from overflows? Using Bayes theorem, $\mathbb{P}[\text{OK} | \top] = (\mathbb{P}[\top | \text{OK}] \mathbb{P}[\text{OK}]) / \mathbb{P}[\top] = (\mathbb{P}[\top | \text{OK}] \mathbb{P}[\text{OK}]) / (\mathbb{P}[\top | \text{OK}] \mathbb{P}[\text{OK}] + \mathbb{P}[\top | \text{ERR}] \mathbb{P}[\text{ERR}]) = (0.99 \cdot 0.01) / (0.99 \cdot 0.01 + 0.01 \cdot 0.99) = 0.5$, we conclude that we can have a mere 50% confidence in the response.

Priors, likelihoods, and posteriors. In Bayesian analysis [18], each factor of (1) has a special name: 1) $\mathbb{P}[h]$ is the *prior*—the probability of the hypothesis before having data—written $\pi[h]$; 2) $\mathbb{P}[d | h]$ is the *likelihood* of the data under the hypothesis—written $\mathcal{L}[d; h]$; 3) $\mathbb{P}[d]$ is the *normalizing constant*; 4) and $\mathbb{P}[h | d]$ is the *posterior*—the probability of the hypothesis after taking the data into account—written $\mathcal{P}_d[h]$. With this jargon, we say that the posterior is proportional to the likelihood times the prior.

The only role of the normalizing constant is to ensure that the posterior defines a correct probability distribution when evaluated over all hypotheses. In most cases we deal with hypotheses $h \in H$ that are mutually exclusive and exhaustive; then, the normalizing constant is simply $\mathbb{P}[d] = \sum_{h \in H} \mathbb{P}[d | h] \mathbb{P}[h]$, which can be computed from the rest of the information—we *update* the prior to get the posterior. Thus, it normally suffices to define likelihoods that are *proportional to a probability*, and rely on the update rule to normalize them to get a proper probability distribution as posterior.

In case of repeated experiments, the data is a set D that collects the outcomes of all experiments. Bayes’ update can be *iterated*: update the prior to get the posterior $\mathcal{P}_{d_1}[h]$ using some $d_1 \in D$; then the posterior becomes the new prior $\pi[h]$, which is updated using $d_2 \in D$ to get a new posterior $\mathcal{P}_{d_2}[h]$; and so on for all $d \in D$.

B. Frequentist vs. Bayesian Statistics

Despite being a simple theorem about an elementary fact in probability, Bayes theorem has significant implications

in the way we can reason about probabilities. We do not discuss the philosophical differences between how frequentist and Bayesian statistics interpret their results. Instead, we focus on describing how some features of Bayesian statistics support new ways of analyzing data. We start by criticizing statistical hypothesis testing since it is a customary technique in frequentist statistics that is widely applied in experimental science, and suggest how Bayesian techniques could provide more reliable analyses. Sect. IV will then demonstrate them in practice on significant case studies.

Hypothesis testing vs. model comparison. A primary goal of experimental science is validating models of behavior based on empirical data. This often takes the form of choosing between alternative hypotheses, such as deciding whether a programming language is faster than another (Sect. IV-A), or whether agile development methods lead to more successful projects (Sect. IV-B). *Hypothesis testing* is the customary framework offered by frequentist statistics to choose between hypotheses. A null hypothesis h_0 corresponds to “no significant difference” between two *treatments* A and B (such as two static analysis algorithms whose effectiveness we want to compare); an alternative hypothesis h_1 is the null hypothesis’s negation, namely corresponds to a significant difference between applying A and applying B . A *statistical significance test*, such as the t -test or the U -test, is a procedure that inputs two datasets D_A and D_B , respectively recording the outcome of applying A and B , and outputs a probability called the p -value. The p -value is the likelihood of the data under the null hypothesis; namely, it is the conditional probability $\mathbb{P}[D | h_0]$ that the outcomes in $D = D_A \cup D_B$ would occur assuming that the treatments A and B are equivalent (or, in more precise statistical terms, determine outcomes with the same distribution). If the p -value is sufficiently small—typically $p \leq 0.05$ or $p \leq 0.01$ —we *reject* the null hypothesis, which corresponds to leaning towards preferring the alternative hypothesis h_1 over h_0 : we have confidence that A and B differ.

Unfortunately, this widely used approach to testing hypotheses suffers from serious shortcomings. The most glaring problem is that, in order to decide whether h_0 is a plausible explanation of the data, we need the conditional probability $\mathbb{P}[h_0 | D]$ of the hypothesis given the data, not the p -value $\mathbb{P}[D | h_0]$. The two conditionals probabilities are related by Bayes theorem (1), so knowing only $\mathbb{P}[D | h_0]$ is not enough to determine $\mathbb{P}[h_0 | D]$; ³ in fact, Sect. III’s example of the static analyzer showed a case where one conditional probability is 99% while the other is only 50%. Other problems come from how hypothesis testing pits the null hypothesis against the alternative hypothesis: as the number of observations grows, it becomes increasingly likely that *some* effect is detectable (or, conversely, it becomes increasingly unlikely that *no effects* are), which leads to rejecting the null hypothesis, independent of the alternative hypothesis, just because it is unreasonably restrictive. This problem may result both in suggesting that some negligible effect is significant just because we reject the

³Assuming that they are equal is the “confusion of the inverse” [15].

null hypothesis, and, conversely, in discarding some interesting experimental results just because they fail to trigger the $p \leq 0.05$ threshold of significance. This is part of the more general problem with insisting on binary decisions between two alternatives: a better approach would be based on richer statistics than one or few summary values (such as the p -value) and would combine quantitative and qualitative data to get richer pictures.

In Bayesian statistics, the closest alternative to statistical significance testing is model comparison based on *Bayes factors*.⁴ To evaluate whether a model M_1 is a better explanation of the data D than another model M_2 , we compute the factor $K(D) = \mathbb{P}[D | M_1] / \mathbb{P}[D | M_2]$, which corresponds to a ratio of likelihoods. In Bayesian analysis, M_1 and M_2 normally are not two fixed hypotheses like h_0 and h_1 , but two families of models with associated probability distributions, so that we can compute the Bayes factor as the ratio of weighted sums:

$$K(D) = \frac{\sum_{m \in M_1} \mathbb{P}[m] \cdot \mathbb{P}[D | m]}{\sum_{n \in M_2} \mathbb{P}[n] \cdot \mathbb{P}[D | n]}.$$

The ratio of posteriors equals the Bayes factor times the ratio of priors, $\mathcal{P}_D(M_1) / \mathcal{P}_D(M_2) = K(D) \cdot \pi(M_1) / \pi(M_2)$; thus, $K(D)$ indicates how much the data is likely to shift the prior belief towards M_1 over M_2 . Choosing between hypotheses based on the Bayes factor avoids the main pitfalls of the p -value—which captures information that is not conclusive. Jeffreys [30] suggests the following scale to interpreting $K(D)$:

EVIDENCE FOR M_1	
$K(D) < 1$	negative (supports M_2)
$1 < K(D) \leq 3$	barely worth mentioning
$3 < K(D) \leq 10$	substantial
$10 < K(D) \leq 32$	strong
$32 < K(D) \leq 100$	very strong
$100 < K(D)$	decisive

Scalar summaries vs. posterior distributions. Decisions based on Bayes factors still reduce statistical modeling to binary choice, but a distinctive advantage of full-fledged Bayesian statistics is that it supports deriving a complete *distribution* of posterior probabilities, by applying (1) for all h 's in their domain, rather than just scalar summaries, such as estimators of mean, median, and standard deviation, or standardized measures of effect size. Given a distribution we can still compute scalar summaries, but we retain additional advantages of being able to visualize the distribution, as well as to derive other distributions by iterative application of Bayes theorem. This supports decisions based on a variety of criteria and on a richer understanding of the experimental data, as we demonstrate in the case studies of Sect. IV. In Sect. IV-A, for example, we visually inspect the posterior distribution to get an idea of whether some borderline differences in performance between programming languages can be considered significant; in Sect. IV-C, we derive the distribution of all bugs in a module from the posterior of the bugs found by random testing in one module.

The role of prior information. The other distinguishing feature of Bayesian analysis is that it *starts from a prior*

probability which models the initial knowledge about the hypotheses. The prior can record previous results in a way that is congenial to the way science is supposed to work—not as completely independent experiments in a metaphorical vacuum, but by constantly scrutinizing previous results and updating our models based on new evidence. A kind of canned criticism observes that using a prior is a potential source of bias. However, explicitly taking into account this very fact helps analyses being more rigorous. In particular, we can often consider several different alternative priors to perform Bayesian analysis. Priors that do not reflect any strong assumptions are called *uninformative*; a uniform distribution over hypotheses is the most common example. If it turns out that the posterior distribution is largely independent of the chosen prior, we say that the data *swamps* the prior, and hence the experimental evidence is quite strong. If, conversely, choosing a suitable prior is necessary to get sensible results, it means that the evidence is not overwhelming, and hence any additional reliable source of information should be vetted and used to sharpen the analysis results. Bayesian analysis stresses the importance of careful *modeling* of assumptions and hypotheses, which is more conducive to accurate analyses than the formulaic application of ready-made statistics.

IV. CASE STUDIES

We present three case studies of applying Bayesian analysis to interpret empirical data in software engineering research. Every case study: 1) presents the main data; 2) summarizes the analysis we carried out in previous research based on those data; 3) introduces additional data that provides complementary information; 4) describes a Bayesian analysis; 5) summarizes its results in terms of the case study; 6) suggests remaining aspects that deserve further investigation. The data analysis has been done in Python using the libraries `numpy`, `scipy`, `matplotlib`, and `thinkbayes` [18].⁵

A. Programming Languages Performance Comparison

The Rosetta code study [38] (for brevity, *Rosetta*) compares eight programming languages for features such as conciseness and performance, based on experiments with a curated selection of programs available in the Rosetta Code repository [44]. Here, we target Rosetta's running time performance analysis. Sect. A also discusses the analysis of memory usage.

Original data. For each language ℓ among C, C#, F#, Go, Haskell, Java, Python, and Ruby, Rosetta's *performance* experiments determine a $|T(\ell)|$ -element vector $\mathbf{S}(\ell) = S(\ell, 1) \cdots S(\ell, |T(\ell)|)$ of running time measures. Each element $t \in T(\ell)$ identifies a programming *task*; examples of tasks include sorting algorithms, combinatorial puzzles, and NP-complete problems. For each task t , $S(\ell, t)$ is the running time of the *best* (that is, the fastest) implementation in language ℓ among those available in Rosetta Code that run without errors or timeout on the same input. For each pair ℓ_1, ℓ_2 of languages, we define the vector $\mathbf{S}(\ell_1, \ell_2)$ elementwise as

⁵To support replication studies, the data and analysis scripts are available online at <https://bitbucket.org/caf/bayesstats-se>.

⁴Popularized by Jeffreys [30], who developed it independent of Turing [23].

$S(\ell_1, \ell_2, t) = \rho(S(\ell_1, t), S(\ell_2, t))$, for $t \in T(\ell_1) \cap T(\ell_2)$, where

$$\rho(a, b) = \text{sgn}(a - b) \frac{\max(a, b)}{\min(a, b)}, \quad (2)$$

and $\text{sgn}(z) = 1$ for $z > 0$ and $\text{sgn}(z) = -1$ for $z \leq 0$. Note that $|S(\ell_1, \ell_2, t)| \geq 1$; thus, $S(\ell_1, \ell_2, t)$ represents the *speedup* of one language over the other in task t : a positive value indicates that language ℓ_2 was $|S(\ell_1, \ell_2, t)|$ times faster than language ℓ_1 on task t ; a negative value indicates that language ℓ_1 was $|S(\ell_1, \ell_2, t)|$ times faster than ℓ_2 .

Previous results. For each pair ℓ_1, ℓ_2 of languages, Rosetta compares $\mathbf{S}(\ell_1)$ to $\mathbf{S}(\ell_2)$ using three statistics: 1) a Wilcoxon signed-rank test—a frequentist hypothesis test giving a p -value; 2) Cohen’s d effect size—a standardized mean difference between $\mathbf{S}(\ell_1)$ and $\mathbf{S}(\ell_2)$; 3) a signed ratio R —an unstandardized mean speedup between $\mathbf{S}(\ell_1)$ and $\mathbf{S}(\ell_2)$ (similar to $\mathbf{S}(\ell_1, \ell_2)$ but using the median running time across all tasks). The statistics for all comparisons are summarized in a language relationship graph: nodes are languages; the horizontal distance between two nodes ℓ_1, ℓ_2 is roughly proportional to the absolute value of R for those nodes; an arrow from ℓ_1 to ℓ_2 denotes that the corresponding p -value is small ($p < 0.05$), the effect size d is not negligible ($d \geq 0.05$), and ℓ_2 is faster on average ($R > 0$); if the p -value is $0.01 \leq p < 0.05$ the arrow is dotted to indicate lower confidence. Fig. 3a, copied from [38], shows the graph.⁶

New questions. Rosetta’s reliance on scalar statistics on top of the p -values of hypothesis testing gives confidence about the overall soundness of its results; however, many language comparisons remain inconclusive. For example, it is surprising that we could not ascertain that a compiled highly-optimized language like Haskell is faster than the dynamic scripting languages Python and Ruby. We would also like to track down the impact of experimental choices that somewhat depended on factors we could not fully control for, such as which implementations were available in Rosetta Code.

RQ₁: Which programming languages have better running time performance, taking into account the potential sources of bias in Rosetta’s experimental data [38]?

Additional data (benchmarks). As additional data on performance and memory usage we consider the Computer Language Benchmarks Game [50] (for brevity, *Bench*). The data from Bench are comparable to those from Rosetta as they both consist of curated selections of carefully written solutions to well-defined programming tasks running on the same input and refined over a significant stretch of time;⁷ on the other hand, Bench was developed independently of Rosetta, which makes it a complementary source of data.

For each language ℓ , Bench’s *performance* experiments determine a vector $\bar{\mathbf{S}}(\ell)$ with elements $\bar{S}(\ell, t, n, v)$ for t ranging over the set $\bar{T}(\ell)$ of Bench’s tasks, n ranging over the set $\bar{N}(\ell, t)$ of input sizes of task t in ℓ , and v ranging over the

set $\bar{V}(\ell, t)$ of different implementations of the same task t in ℓ . Examples of Bench’s tasks include numerical algorithms, regular expression matching, and algorithms on trees. Bench’s performance data include experiments with different solutions for the same task and inputs of different sizes; we avail this to model the possible variability in performance measurements.

For each pair ℓ_1, ℓ_2 of languages, we define the vector $\bar{\mathbf{S}}(\ell_1, \ell_2)$ elementwise as

$$\bar{S}(\ell_1, \ell_2, t) = \rho\left(\min_{v \in \bar{V}(\ell_1, t)} \bar{S}(\ell_1, t, \bar{m}, v), \min_{v \in \bar{V}(\ell_2, t)} \bar{S}(\ell_2, t, \bar{m}, v)\right),$$

for $\bar{m} = \max(\bar{N}(\ell_1, t) \cap \bar{N}(\ell_2, t))$; that is, $\bar{S}(\ell_1, \ell_2, t)$ is the speedup (2) of the fastest solution in ℓ_1 over the fastest solution in ℓ_2 for the same task t and running over the largest input that both languages can handle. Thus, $\bar{\mathbf{S}}(\ell_1, \ell_2)$ is directly comparable to $\mathbf{S}(\ell_1, \ell_2)$ as the similar notation suggests.

We also define the set $\bar{\mathbf{S}}_{\Delta}(\ell_1, \ell_2, t)$ of all values $\rho(\bar{\mathbf{S}}(\ell_1, t, n, v_1), \bar{\mathbf{S}}(\ell_2, t, n, v_2)) - \bar{S}(\ell_1, \ell_2, t)$, for n ranging over $\bar{N}(\ell_1, t) \cap \bar{N}(\ell_2, t)$, v_1 ranging over $\bar{V}(\ell_1, t)$, and v_2 ranging over $\bar{V}(\ell_2, t)$; intuitively, $\bar{\mathbf{S}}_{\Delta}(\ell_1, \ell_2, t)$ is the distribution of all differences in speedup measurements for task t between any two programs (on input of any size) and the two fastest programs (on the largest input). $\bar{\mathbf{S}}_{\Delta}(\ell_1, \ell_2, t)$ provides data about how measuring the performance of programs other than the fastest ones would have reported different speedups.

Bayesian analysis. For every pair ℓ_1, ℓ_2 of languages, the *prior* distribution $\pi^{\mathbf{S}}(\ell_1, \ell_2)$ gives the probability $\pi^{\mathbf{S}}(\ell_1, \ell_2)[r]$ of observing a program in ℓ_1 and a program in ℓ_2 —solving the same problem and input—respectively running for t_1 and t_2 time units such that $\rho(t_1, t_2) = r$. Informally, the prior models the initial expectations on the performance difference between languages—which one will be faster and how much. We base our initial expectations on the results of Bench; hence, $\pi^{\mathbf{S}}(\ell_1, \ell_2)$ follows the distribution of $\bar{\mathbf{S}}(\ell_1, \ell_2)$. Precisely, $\bar{\mathbf{S}}(\ell_1, \ell_2)$ is based on a finite number of discrete observations, and hence it excludes values that are perfectly acceptable but did not happen to occur in the experiments. But, if ℓ_2 is twice as fast as ℓ_1 in an experiment and three times as fast in another experiment, we expect speedup values between 2 and 3 to be possible even if they were not observed in any performed experiment. Thus, $\pi^{\mathbf{S}}(\ell_1, \ell_2)$ is the kernel density estimation (KDE [52] using a normal kernel function⁸) of $\bar{\mathbf{S}}(\ell_1, \ell_2)$; furthermore, we rework the smooth distribution obtained by KDE to exclude values in the open interval $(-1, 1)$ since these are impossible given the definition of ρ in (2).

The *likelihood* $\mathcal{L}^{\mathbf{S}}(\ell_1, \ell_2)[d; h]$ expresses how likely observing a speedup d is, under the hypothesis that the actual speedup is h . We base it on Bench’s extended experiments following this line of reasoning. The outcome of performance experiments also depends on some parameters, such as the input size and specific implementation choices, that are somewhat accidental; for example, Rosetta’s experiments use inputs of significant size that are still approachable by the slower languages; this choice seems reasonable, but it

⁶Unlike [38], we do not consider arrow thickness to indicate effect size.

⁷Some details of the performance measures are also similar, such as the choice of including the Java VM startup time in the running time measures.

⁸We used Python’s `scipy.stats.gaussian_kde` function.

does not exclude that, if input sizes had been chosen with a different criterion, the performance results could have been quantitatively different. In order to assess this experimental uncertainty due to effects that cannot be entirely controlled, we base the likelihood on the values $\bar{S}_\Delta(\ell_1, \ell_2, t)$, which span the differences between the reported data $\bar{S}(\ell_1, \ell_2)$ and the same metric for different choices of input size or program variant. Similarly to what we did for the prior, we smooth the distribution of values $\bigcup_t \bar{S}_\Delta(\ell_1, \ell_2, t)$ using KDE⁹, which yields a probability density function $\Delta(\ell_1, \ell_2)$. Then, the likelihood $\mathcal{L}^S(\ell_1, \ell_2)[d; h] \propto \Delta(\ell_1, \ell_2)[d - h]$ is a value proportional to the probability of observing the difference $d - h$ of speedups.

The posterior distribution $\mathcal{P}_S^S(\ell_1, \ell_2)$ is obtained by updating the prior (Sect. III-B) with Rosetta’s data \mathbf{S} ; $\mathcal{P}_S^S(\ell_1, \ell_2)[r]$ is the probability that the speedup of ℓ_1 over ℓ_2 is r . Tab. 2 summarizes the posteriors using two statistics: *CI* is the 95% credible interval¹⁰ (that is, there is a 95% chance that the real speedup falls in the interval), and *m* is the median of the posterior.¹¹ Credible intervals that include 0 may indicate an inconclusive comparison (one or the other language may be faster) One advantage of Bayesian analysis is that it provides *distributions* (rather than just scalar summaries), so that we can sort out borderline cases by visually inspecting them. For example, Fig. 1 suggests that the Java vs. Python comparison is indeed inconclusive (there’s significant probability on both sides of the origin), whereas the F# vs. Ruby comparison has a very sharp peak next to 1, which suggests that Ruby was consistently faster than F#—albeit not *much* faster. We summarize the results of the posteriors’ analysis in the language relationship graph in Fig. 3b. It conveys the same general information as the graph in Fig. 3a from [38], but it is based on Bayesian analysis; in particular, a dotted arrow indicates a speedup relationship that is weak or borderline but still sufficiently clear (such as F# vs. Ruby).

LANGUAGE		C	C#	F#	Go	Haskell	Java	Python
C#	CI	(-10.1, -8.7)						
	<i>m</i>	-9.22						
F#	CI	(-76.0, -64.5)	(-8.9, -4.6)					
	<i>m</i>	-72.61	-5.29					
Go	CI	(-2.3, -1.3)	(1.0, 2.5)	(16.9, 20.6)				
	<i>m</i>	-1.67	1.15	18.21				
Haskell	CI	(-5.9, -5.7)	(1.2, 1.7)	(3.2, 15.5)	(2.4, 2.5)			
	<i>m</i>	-5.76	1.23	6.77	2.49			
Java	CI	(-3.2, -3.1)	(-2.0, -1.3)	(5.7, 7.5)	(-8.5, -7.6)	(-8.6, -8.3)		
	<i>m</i>	-3.18	-1.77	6.94	-8.02	-8.63		
Python	CI	(-54.2, -32.3)	(-1.4, 1.8)	(2.1, 12.7)	(-27.2, -17.7)	(-5.0, -1.2)	(-2.1, 2.2)	
	<i>m</i>	-52.47	1.3	7.93	-23.01	-1.82	1.76	
Ruby	CI	(-124.0, -90.9)	(-21.1, -11.6)	(1.0, 1.1)	(-142.2, -36.9)	(-22.0, -19.9)	(-17.0, -8.6)	(-19.7, -14.0)
	<i>m</i>	-100.69	-16.96	1.05	-141.92	-21.85	-15.32	-15.03

TABLE 2: Comparison of running time: 95% credible intervals CI and medians *m* of posterior distributions.

New results. Compared with Rosetta’s frequentist analysis [38], the overall picture emerging from Bayesian analysis is richer and somewhat more nuanced. C remains the king of speed, but Go cannot claim to stand out as runner up: Haskell is faster than Go on average (it was slower in the previous analysis), even though the performance advantage of

⁹We take the union over all tasks in Bench because Bench’s and Rosetta’s tasks are all different.

¹⁰Credible intervals are Bayesian analogues of confidence intervals.

¹¹The means are generally close to the medians.

C over Haskell is still greater than its advantage over Go. On the other hand, several comparisons that were surprisingly inconclusive in Rosetta are now more clearly defined. Haskell emerges as faster than the scripting languages (Python and Ruby) and than the bytecode object-oriented languages (C# and Java). In the opposite direction, F# has shown a generally poor performance—in particular, quite slower than C# even if they both run on the same .NET platform. These differences indicate that a few results of Rosetta hinged on contingent experimental details; Bayesian analysis has lessened the bias by incorporating an independent data source.

AN₁: C is the king of performance. Go and Haskell (which compile to native) are the runner-ups. Object-oriented languages (C#, Java) retain a competitive performance on several tasks even if they compile to bytecode. Interpreted scripting languages (Python, Ruby) tend to be the slowest.

Further analyses. Since Bayesian analysis relies on the data from Bench, further analysis could try different sources for the prior and likelihood distributions, in order to understand the sensitivity of the analysis on the particular choice that was done. Bench, however, was chosen because it is the only data we could find that is publicly available, described in detail, and sufficiently similar to Rosetta to be comparable to it; thus getting more data may require to perform new experiments.

Another natural continuation of this work would collect additional data specifically for the comparisons where significant uncertainty remains. More data about C is probably redundant as its role as performance king is largely undisputed. In contrast, F#’s data are unsatisfactory because they often show a large variability and disappointing results for a language that compiles to the same .NET platform as C#; more data would help explain whether F#’s performance gap is real, or due to less mature language support or program implementations.

B. Agile vs. Structured Development

The Agile vs. Structured study [19], [20] (for brevity, *AvsS*) compares agile and heavyweight/structured software development processes based on a survey of IT companies worldwide involved in distributed and outsourced development. Here, we target *AvsS*’s analysis of overall project success. Sect. B also discusses the project importance for customers.

Original data. *AvsS* surveyed 47 projects P , partitioned according to whether they followed an agile process (29 projects P_A) or a more heavyweight, structured process (18 projects P_S).¹² For each project $p \in P$, the survey’s respondents assessed its *outcome* $O(p)$ on a scale 1–10, where 1 denotes complete failure and 10 denotes full success. We introduce the multisets $O_A = \{O(p) \mid p \in P_A\}$ of outcome of all agile projects, $O_S = \{O(p) \mid p \in P_S\}$ of outcome of all structured projects, and $O = O_A \cup O_S$ of outcome of all projects.

Previous results. *AvsS* compares O_A to O_S using a U test—a frequentist statistics testing the hypothesis that there is no significant difference between projects carried out using agile

¹²A binary classification of development processes is a simplification, but we took care [20, Sec. 7] of limiting its impact on the validity of data.




Fig. 1: Posterior distributions \mathcal{P}^S of running time ratios of Java vs. Python (left) and F# vs. Ruby (right).




Fig. 3: Comparison of running time: qualitative summaries.

or using structured processes. The p -value turned out to be quite *large*: $p = 0.571$. Indeed, pretty much all the analyses of AvsS—including many aspects other than success—failed to reject the null hypotheses that projects following agile processes and projects following structured processes behave differently. AvsS concluded that there is no a priori reason to prefer agile over structured; different projects may require different approaches, and each development process can be effective in a certain domain.

New questions. AvsS’s analysis does not comply with frequentist orthodoxy, according to which you can never “accept” a null hypothesis but only “fail to reject it”. From a Bayesian point of view, we cannot conclude from a large p -value that the null hypothesis is likely to hold (Sect. III-B). Independent of this shortcoming, AvsS’s results go against the overwhelming opinion that agile processes are more effective than traditional, structured ones. Can we validate AvsS’s analysis in a more general context with data coming from other sources?

RQ₂ What is the *typical* impact of adopting agile rather than structured processes on the overall outcome of software development projects?

Additional data (Ambysoft study). As additional data on software project outcome we consider Ambysoft’s IT Project Success Rates Survey [1] (for brevity, *ITP*). The data from ITP are comparable to those from AvsS as they both consist of the results from surveys of a substantial number of IT professionals, explicitly classify projects into agile and structured, and target overlapping aspects. Specifically, ITP collected data about the “success” of “software delivery teams”, which directly relates to project *outcome*.

ITP’s data is organized a bit differently than AvsS’s. The 173 survey respondents R assessed project outcome in four categories of development processes: ad-hoc H , agile A , traditional T , iterative I , and lean L . For each category

$c \in \{A, H, I, L, T\}$, each respondent $r \in R$ gave $p_c^0(r)$, $p_c^1(r)$, and $p_c^2(r)$ respectively estimating the percentage of projects in category c that were failures (score 0), challenges (score 1), and successful (score 2).¹³

Bayesian analysis. To make the data in AvsS and in ITP quantitatively comparable, we adjust scales and formats, and match categories of processes. In AvsS, we introduce primed versions O'_A, O'_S, O' of O_A, O_S, O by uniformly rescaling the data in the unprimed sets (ranging over $[1..10]$) over the range $[0..2]$ used in ITP’s data. Then, $\bar{d}_A(k) = |\{o \in O'_A \mid o = k\}|$ is the number of projects in A with outcome $0 \leq k \leq 2$; $\bar{d}_S(k)$ and $\bar{d}(k)$ are defined similarly for structured and for all projects.

In ITP, for every non-empty subset $C \subseteq \{A, H, I, L, T\}$, we define a distribution \mathfrak{o}_C over values in the range $[0..2]$ as follows. If C is a singleton set $\{c\}$ with $c \in \{A, H, I, L, T\}$, $\mathfrak{o}_c[k]$ is the probability $\sum_{r \in R} p_c^k(r) / |R|$ that a project in category c has outcome k . If C is a non-empty subset of $\{A, H, I, L, T\}$, $\mathfrak{o}_C[k]$ is the weighted average $\mathfrak{o}_C[k] = \sum_{c \in C} \mathfrak{o}_c[k] / |C|$. Tab. 4 shows the distributions \mathfrak{o}_C for the nine subsets C of process categories we analyze.

	A	AIL	$AILT$	AIT	AL	ALT	AT	IT	T
$\mathfrak{o}_C[0]$	7%	8%	10%	11%	7%	11%	12%	12%	18%
$\mathfrak{o}_C[1]$	30%	27%	28%	29%	27%	29%	31%	29%	32%
$\mathfrak{o}_C[2]$	63%	65%	62%	60%	66%	60%	57%	59%	50%

TABLE 4: For C one of the subsets of $\{A, I, L, T\}$ in the column headers, $\mathfrak{o}_C[k]$ is the probability that the outcome of projects following processes in categories C is $k \in [0..2]$.

Since we are comparing project outcomes, we need a notion of outcome distribution being *better* than another: p is better than q , written $p > q$, iff $\mu(p) > \mu(q)$,¹⁴ that is if p leads

¹³We discarded the p_c s of respondents who declared no experience in projects of category c .

¹⁴The mean $\mu(p)$ of p is $\sum_k k \cdot p[k]$.

to higher quality outcomes than q on average; otherwise we write $p \leq q$. For example, $o_A > o_T$ and $o_A \leq o_{AL}$ in Tab. 4.

Let p be a distribution of probabilities over project outcomes in $[0..2]$. Out of a total of n projects following p , the probability that d_0 projects have outcome 0, d_1 have outcome 1, and d_2 have outcome 2 is given by the multinomial p.m.f.

$$M(d_0, d_1, d_2; p) = \frac{(d_0 + d_1 + d_2)!}{d_0! d_1! d_2!} p[0]^{d_0} p[1]^{d_1} p[2]^{d_2}.$$

The goal of Bayesian analysis is assessing whether the data from AvsS supports the hypothesis “agile leads to more successful projects” (h_A) more than the hypothesis “agile is as good as structured” ($h_=-$). To this end, the *likelihood* function $\mathcal{L}_C[D; h]$ should weigh the same data D differently according to whether $h = h_A$ or $h = h_=-$.

Let $D = D_A \cup D_S$ be partitioned in data D_A about agile projects and data D_S about structured projects. Then, $\mathcal{L}_C[D; h_A]$ should assign a different weight to D_A with respect to D_S , whereas $\mathcal{L}_C[D; h_=-]$ should assign the same weight to D for all projects regardless of their kinds (agile or structured). If we knew accurate distributions of outcome p_A for agile projects, p_S for structured projects, and p_{AS} for all projects, we could just compute the likelihood as $\mathcal{L}_C[D; h_A] = M(D_A; p_A) \cdot M(D_S; p_S)$ and $\mathcal{L}_C[D; h_=-] = M(D_A; p_{AS}) \cdot M(D_S; p_{AS})$. However, getting accurate distributions is the whole point of the analysis! Whatever the choice of fixed p_A , p_S , and p_{AS} (for example, we could base it on data in Tab. 4), the results of the analysis would hinge on the choice, and hence risk overfitting.

Bayesian analysis, however, can average out over all possible distributions in a certain family. The data from ITP only provides a *baseline* distribution o_C . To test whether agile projects are better than structured, we assign to the former all outcome distributions that are better than the baseline (first product term in (3)), and to the latter all outcome distributions that are worse or as good as the baseline (second term in (3)):

$$\mathcal{L}_C[D; h_A] = \left(\sum_{p > o_C} w_p \cdot M(D_A; p) \right) \cdot \left(\sum_{p \leq o_C} w_p \cdot M(D_S; p) \right). \quad (3)$$

The w_p s are weights giving the prior probability of each distribution, which we define below. The likelihood for hypothesis $h_=-$ is similar but sums over all outcome distributions, modeling the hypothesis that a project’s outcome is independent of the development process:

$$\mathcal{L}_C[D; h_=-] = \left(\sum_p w_p \cdot M(D_A; p) \right) \cdot \left(\sum_p w_p \cdot M(D_S; p) \right). \quad (4)$$

Tab. 5 shows the Bayes factors $K_C(\bar{D}) = \mathcal{L}_C[\bar{D}; h_A] / \mathcal{L}_C[\bar{D}; h_=-]$ for the data $\bar{D} = (\bar{d}_A(0), \bar{d}_A(1), \bar{d}_A(2)) \cup (\bar{d}_S(0), \bar{d}_S(1), \bar{d}_S(2))$ from AvsS, for every distribution C in Tab. 4 as baseline. Each row uses different weights w_p s in (3) and (4): *uniform* weighs all distributions equally; *triangle* decreases the weigh linearly with the difference δ between $\mu(p)$ and the baseline $\mu(o_C)$; *power* decreases it like $(1 + \delta)^{-1}$; and *exp* like $\exp(-\delta)$.

New results. Regardless of the choice of weights and baseline distribution, the Bayes factors in Tab. 5 are not

	A	AIL	AILT	AIT	AL	ALT	AT	IT	T
uniform	0.25	0.26	0.17	0.14	0.29	0.12	0.08	0.10	0.01
triangle	0.25	0.26	0.17	0.14	0.29	0.13	0.08	0.10	0.02
power	0.25	0.26	0.17	0.14	0.29	0.13	0.09	0.11	0.02
exp	0.25	0.26	0.19	0.16	0.29	0.15	0.10	0.12	0.02

TABLE 5: Bayes factors $K_C(\bar{D})$ estimating whether the data \bar{D} supports hypothesis h_A (agile leads to more successful projects) more than hypothesis $h_=-$ (agile is no more successful), for different baseline project outcome distributions.

significant (see Sect. III-B); in fact, factors less than one suggest that the data supports hypothesis $h_=-$ more than h_A . We do not report variants of this analysis, where we rescaled the data in O differently (to account for the fact that the values in O do not span the entire available range $[1..10]$); in all cases factors do not significantly change. Thus, Bayesian analysis confirms the results of [19] with a stronger degree of confidence.

AN₂: Software projects developed following an agile process do not have consistently better outcomes than projects developed following a structured process.

In passing, we also largely agree with [2]’s conclusions that the claims of a “software crisis” are not supported by the evidence that software projects seem to be successful to a large degree.

Further analyses. Since the Bayesian analysis confirms AvsS’s results, further improvements should look into whether the data can be made more rigorous. A recurring threat follows from the observation that different IT professionals may have different views of what an “agile process” is. The data in ITP, which distinguish between categories such as “agile” and “lean” that would be natural to lump together, suggests that a sharp classification may be hard to obtain. Future work could collect data by inspecting individual processes to ensure that a uniform classification criterion is applied. Note, however, that results are unlikely to change dramatically for the aspects that we analyzed: respondents already tend to give higher ranks to agile projects, but this is not enough to show any significant overall difference, indicating that there are probably factors as or more important than the development process that determine a project’s success.

C. Testing with Specifications

The Testing with Strong Specifications paper [43] (for brevity, *SpecTesting*) assesses the effectiveness of random testing using as oracles functional specifications in the form of assertions embedded in the code (contracts).

Original data. SpecTesting’s experiments target the EiffelBase data-structure library, comprising 21 classes implementing data structures—such as arrays, lists, hash tables, and trees—and iterators. SpecTesting tested EiffelBase twice using the same random test-case generator AutoTest: once using the simple specifications that come with EiffelBase’s code, and once using stronger specifications that we wrote as part of [43]’s research. For each class C_k , $k = 1, \dots, 21$, testing using simple specifications detected t_k bugs, whereas

testing using strong specifications detected T_k bugs. These are actual specification violations that expose genuinely incorrect behavior. Let $\mathbf{t} = t_1, \dots, t_{21}$ and $\mathbf{T} = T_1, \dots, T_{21}$ be the sets of all bugs found using simple and using strong specifications.

Previous results. SpecTesting compares \mathbf{t} to \mathbf{T} using a Wilcoxon signed-rank test—a frequentist hypothesis test giving a p -value $p = 0.006$, which leads to rejecting the hypothesis that using simple specifications and using strong specifications makes no difference in testing effectiveness. Also based on other data—such as the effort spent writing strong specifications—SpecTesting argued that strong specifications bring significant benefits to random testing and achieve an interesting trade-off between effort and bug-detection effectiveness.

New questions. SpecTesting’s analysis is quite convincing as it stands; rather than confirming its results using Bayesian statistics, we extend its analysis into a different direction: studying the distribution of bugs in classes.

RQ₃: What is the distribution of bugs in classes? Does it satisfy the Pareto principle: “80% of the bugs are located in only 20% of the classes”, or, conversely, “80% of the classes are affected by only 20% of the bugs”?

Additional data. Zhang suggests [56] that bug distributions in modules follow a Weibull—a continuous distributions with positive parameters α and β , p.d.f. $w_{\alpha,\beta}[x] = (\beta/\alpha)(x/\alpha)^{\beta-1} \exp(-(x/\alpha)^\beta)$ and c.d.f.¹⁵

$$W_{\alpha,\beta}[x] = 1 - \exp\left(-\left(\frac{x}{\alpha}\right)^\beta\right). \quad (5)$$

Saying that the bug distribution in modules follows a Weibull with c.d.f. (5) means that a fraction $W_{\alpha,\beta}[x]$ of the modules has x or fewer bugs; or, equivalently, that a random module has x or fewer bugs with probability $W_{\alpha,\beta}[x]$. Under these conditions, the Pareto principle would hold only for certain values of α and β : while β determines the distribution’s *shape*, and hence qualitative properties such as the Pareto principle, α determines the distribution’s *scale*, and hence only specific quantitative properties.

Bayesian analysis: Pareto principle. We assume classes are modules in object-oriented programs; thus, we use Bayes theorem to estimate α and β such that a Weibull with c.d.f. $W_{\alpha,\beta}$ fits the distribution of bugs \mathbf{T} detected using strong specifications. Since Bayesian analysis computes distribution of parameters, we build a *multivariate* distribution m of values for parameters α and β . Since we have no inkling of plausible values for α and β , we use an uninformative uniform prior $\pi[\alpha, \beta] \propto 1$ for all α, β within a broad range. The likelihood $\mathcal{L}[d; \alpha, \beta]$ reflects the probability that d is drawn from a Weibull with parameters α and β ; thus $\mathcal{L}[d; \alpha, \beta] \propto w_{\alpha,\beta}[d+1]$, where we shift the p.d.f. by one unit to account for classes with no bugs. By applying Bayes theorem, the joint posterior distribution is:

$$m[\alpha, \beta] = \mathcal{P}_{\mathbf{T}}[\alpha, \beta] = \nu \prod_{d \in \mathbf{T}} w_{\alpha,\beta}[d+1],$$

¹⁵A cumulative distribution function (c.d.f.) $X[x]$ gives $\mathbb{P}[X \leq x]$.




Fig. 6: Marginals $m[\alpha]$ and $m[\beta]$ of the posterior distribution $m[\alpha, \beta]$ of parameters α and β . The graph indicates maxima $\hat{\alpha}$ and $\hat{\beta}$ and 90% credible intervals $(\alpha_{90}^l, \alpha_{90}^h)$ and $(\beta_{90}^l, \beta_{90}^h)$.




Fig. 7: Cumulative distribution function $W_{\alpha,\beta}$ (5) for the different values of α and β highlighted in Fig. 6.

where ν is a normalization factor obtained by the, by now familiar, update rule (Sect. III-B). Fig. 6 shows m ’s marginals $m[\alpha]$ and $m[\beta]$.¹⁶ The plot indicates that there is limited uncertainty about the value of β , whereas the uncertainty about α is significant. In terms of the resulting Weibull distributions, this means that the uncertainty is mainly on the scale of the distribution (parameter α) but not so much on its shape (parameter β). Fig. 7 shows this by plotting the Weibull’s c.d.f. $W_{\alpha,\beta}$ for parameters in the 90% credible intervals highlighted in Fig. 6. The picture suggests that the Pareto principle holds: the number b of bugs such that $W_{\alpha,\beta}[b] = 0.8$ is 8%, 10%, and 13% of the total number of possible bugs—one percentage for each choice of α, β in Fig. 7—which is close to Pareto’s 80–20 proportion.

AN_{3-A}: The distribution across classes of bugs found by random testing is modeled accurately by a Weibull distribution that satisfies the Pareto principle.

A significant advantage of Bayesian analysis over using frequentist statistics is that we have *distributions* of likely

¹⁶The maxima are close to means ($\mu(m[\alpha]) = 8.53$, $\mu(m[\beta]) = 0.88$) and medians ($m(m[\alpha]) = 6.86$ and $m(m[\beta]) = 0.81$).

parameter values, not just pointwise estimates. This entails that we can derive distributions of related variables. For example, we could plot how the probability of finding a class with at most N bugs—for any given N —varies with α and β . See Sect. C for an example of this.

Bayesian analysis: total bugs. This analysis modeled the number of bugs found by random testing (with strong specifications); what about the *total* number of bugs present in a class? Can we use Bayesian analysis to estimate it as well?

As a first step, suppose that the *effectiveness* of random testing with strong specifications is E : if testing finds N bugs—a fraction E of the total—there are actually N/E bugs in the class. Similarly, let e be the effectiveness of random testing with simple specifications. Given E and e , we can estimate the distribution B of real bugs using Bayesian analysis. The prior distribution has p.d.f. $\pi^b(\alpha, \beta, E)$ such that $\pi^b(\alpha, \beta, E)[x] = w_{\alpha, \beta}[x \cdot E]$, corresponding to a Weibull scaled so as to follow the expected actual bugs. The likelihood $\mathcal{L}^b(e)[d; h]$ is proportional to the probability that testing with effectiveness e finds d bugs in a class with h total bugs; thus, $\mathcal{L}^b(e)[d; h] \propto \mathcal{B}(h, e)[d]$, where $\mathcal{B}(h, e)$ is the binomial distribution’s p.m.f. giving the probability of d successes (d bugs found) out of h attempts when each attempt has probability e of success. With these prior and likelihood, the posterior distribution $\mathcal{P}_d^b(\alpha, \beta, e, E)[x] = B_{\alpha, \beta}(d, e, E)[x]$ gives the probability that a class has a total of x bugs given that testing with simple specifications found d bugs.

This analysis requires knowing plausible values for α and β —which we can obtain from the previous analysis summarized in Fig. 6—as well as for e and E —which is instead the rub of the analysis. Fortunately, we can add one layer of Bayesian inference to abstract over the unknown effectiveness values. The uninformative prior $\pi_{\alpha, \beta}^n(d)$ is now a uniform distribution over distributions such that $\pi_{\alpha, \beta}^n(d)[e, E]$ is the probability associated with $B_{\alpha, \beta}(d, e, E)$ defined in the previous analysis. The likelihood $\mathcal{L}^n[d; e, E]$ measures the probability that testing modeled by a distribution with parameters e, E finds d bugs in a class: $\mathcal{L}^n[d; e, E] \propto \sum_h \mathcal{L}^b(e)[d; h] \cdot B_{\alpha, \beta}(d, e, E)[h]$. With the usual update rule, compute the posterior $\mathcal{P}_d^{\alpha, \beta}[e, E]$ given values for α, β , and a number of bugs d detected in some class. Finally, $N_m^{\alpha, \beta}[n]$, which gives the probability that class m has n bugs, is a mixture that interpolates posteriors:

$$N_d^{\alpha, \beta}[n] = \sum_{e, E} B_{\alpha, \beta}(d, e, E)[n] \cdot \mathcal{P}_d^{\alpha, \beta}[e, E],$$

where d is the number of bugs found in a class by testing with effectiveness e .

Tab. 8 shows statistics about $N_{d_m}^{\hat{\alpha}, \hat{\beta}}$ for all 21 classes analyzed in SpecTesting. The parameters $\alpha = \hat{\alpha}$ and $\beta = \hat{\beta}$ are the maximum likelihood values in Fig. 6; prior effectiveness ranges over $0.15 \leq e \leq 0.5$ for testing with simple specifications and over $0.7 \leq E \leq 0.95$ for testing with strong specifications; and $d_m = t_m$, for $m = 1, \dots, 21$, is the number of bugs found in class C_m by testing with simple specifications in SpecTesting’s

	C ₁	C ₂	C ₃	C ₄	C ₅	C ₆	C ₇	C ₈	C ₉	C ₁₀	C ₁₁	C ₁₂	C ₁₃	C ₁₄	C ₁₅	C ₁₆	C ₁₇	C ₁₈	C ₁₉	C ₂₀	C ₂₁
$m/ M $	0.27	0.03	0.20	0.38	0.52	0.17	0.15	0.15	0.39	0.23	0.11	0.15	0.43	0.15	1.04	0.08	0.15	0.51	0.15	1.21	0.67
$m(N)$	14	3	5	19	38	5	10	2	31	20	5	3	22	13	22	8	1	71	3	67	2
N_{90}^l	5	0	2	18	20	2	2	0	2	2	2	0	22	0	4	4	0	25	0	49	0
N_{90}^h	26	7	17	54	57	17	17	7	17	17	17	7	60	7	22	22	7	66	7	100	7

TABLE 8: Median per public method $m/|M|$, median $m(N)$, and 90% credible interval (N_{90}^l, N_{90}^h) of $N_d^{\hat{\alpha}, \hat{\beta}}$ —estimating the total number of bugs in class C_m .

experiments. The median bugs per public method—similar to bugs per function point [31]—is an indicator of bug proneness considered more robust than bugs per line of code. According to this metric, trees (class C₂₀) and linked stacks (class C₁₅) data structures are the faultiest, while arrayed lists (class C₂) and linked lists (class C₁₁) are the least faulty. The difference can be explained in terms of which structures are the most used in Eiffel programs: lists are widely used, and hence their implementations have been heavily tested and fixed.

AN_{3-B}: The number of total bugs in a class can be estimated by Bayesian analysis from the distribution of bugs found by random testing.

Further analyses. Using Bayesian analysis we obtained a reliable estimate of the real bugs present in a data structure library; there remains a significant margin of uncertainty, given that we abstracted over several unknown details, but the uncertainty is quantified and upheld by precise modeling choices. Generalizing the analysis to include other testing techniques (possibly including manual testing) or, conversely, specialize it to other domains and conditions to make it more precise are natural extensions of this work. We used a very simple model of testing effectiveness based on detection effectiveness; using more detailed models of random testing [5] may provide additional insights and more accurate estimates.

V. THREATS TO VALIDITY

Do Bayesian techniques help with mitigating *threats to validity*? To answer this question, we consider each of the usual kinds of threats (construct, conclusion, internal, and external), and we assess them for the case studies in Sect. IV.

Bayesian analysis is unlikely to affect *construct* validity, which has to do with whether we measured what the study was supposed to measure, and hence mainly depends on how measurements were taken. This threat is very limited for the programming language and testing studies (Sect. IV-A and Sect. IV-C), which target well-defined and understood measures (running time, number of bugs). It is potentially more significant for the agile vs. structured study, because classifying processes in only two categories (agile and structured) may be partly fuzzy and subjective; however, Sect. IV-B discusses how the analysis is quite robust w.r.t. how this classification is done, which gives us confidence in its results.

Conclusion validity depends on the application of appropriate statistical tests. As we discuss in Sect. III-B, frequentist hypothesis testing techniques are questionable because they do not properly assess significance; switching to Bayesian analysis can certainly help in this respect. Thus, conclusion

validity threats are lower in our three case studies than in the original studies that provided the data.

Internal validity is mainly concerned with whether causality is correctly evaluated. This depends on several details of experimental design that are generally independent of whether frequentist or Bayesian statistics are used. One important aspect of internal validity pertains to the avoidance of *bias*; this is where Bayesian statistics can help, thanks to its ability of weighting out many different competing models rather than restricting the analysis to two predefined hypotheses (null vs. alternative hypothesis). This aspect is particularly relevant for the agile vs. structured study in the way we use Bayes factors as an alternative to hypothesis testing.

Since it integrates previous, or otherwise independently obtained, information in the form of priors, Bayesian analysis can help mitigate threats to *external validity*, which concern the generalizability of findings. Using an informative prior makes the statistics reflect not just the current experimental data but also prior knowledge and assumptions on the subject; conversely, being able to get to the same conclusions using different, uninformative priors indicates that the experimental evidence is strong over initial assumptions. In both cases, Bayesian statistics support analyses where generalizability is more explicitly taken into account instead of being just an afterthought. This applies to all three case studies, and in particular to the programming language performance analysis (Sect. IV-A) which integrated independent information to boost the confidence in the results.

VI. PRACTICAL GUIDELINES

We conclude by summarizing practical guidelines to perform Bayesian analysis on empirical data from diverse software-engineering research.

- If previous studies on the same subject are available, consider incorporating their data into the analysis in the form of prior—if only to estimate to what extent the interpretation of the new results changes according to what prior is used.
- To allow other researchers to do the same with your data, make it available in machine-readable form in addition to statistics and visualizations.
- Try to compute distributions of estimates rather than only single-point estimates. Visualize data as well as the computed distributions, and use the visual information to direct and refine your analysis.
- Consider alternatives to statistical hypothesis testing, for example the computation of Bayes factors; in any case, do not rely solely on the p -value to draw conclusions.
- More generally, avoid phrasing your analysis in terms of binary antithetical choices. No statistical tests can substitute careful, informed modeling of assumptions and data.

REFERENCES

- [1] Scott W. Ambler. Ambysoft's IT project success rates survey results. <http://www.ambysoft.com/surveys/success2013.html>, December 2013.
- [2] Scott W. Ambler. The non-existent software crisis: Debunking the chaos report. *Dr. Dobbs's*, February 2014. <http://www.drdobbs.com/architecture-and-design/the-non-existent-software-crisis-debunk/240165910>.
- [3] Andrea Arcuri and Lionel C. Briand. A practical guide for using statistical tests to assess randomized algorithms in software engineering. In *Proceedings of the 33rd International Conference on Software Engineering (ICSE 2011)*, pages 1–10. ACM, 2011.
- [4] Andrea Arcuri and Lionel C. Briand. A hitchhiker's guide to statistical tests for assessing randomized algorithms in software engineering. *Softw. Test., Verif. Reliab.*, 24(3):219–250, 2014.
- [5] Andrea Arcuri, Muhammad Zohaib Z. Iqbal, and Lionel C. Briand. Random testing: Theoretical results and practical implications. *IEEE Trans. Software Eng.*, 38(2):258–277, 2012.
- [6] Alberto Bacchelli and Christian Bird. Expectations, outcomes, and challenges of modern code review. In Notkin et al. [39], pages 712–721.
- [7] David Barber. *Bayesian Reasoning and Machine Learning*. Cambridge University Press, 2012.
- [8] Gabriele Bavota, Bogdan Dit, Rocco Oliveto, Massimiliano Di Penta, Denys Poshyvanyk, and Andrea De Lucia. An empirical study on the developers' perception of software coupling. In Notkin et al. [39], pages 692–701.
- [9] Antonia Bertolino, Gerardo Canfora, and Sebastian G. Elbaum, editors. *37th IEEE/ACM International Conference on Software Engineering, ICSE 2015, Volume 1*. IEEE Computer Society, 2015.
- [10] Nélio Cacho, Thiago César, Thomas Filipe, Eliezio Soares, Arthur Cassio, Rafael Souza, Israel Garcia, Eiji Adachi Barbosa, and Alessandro Garcia. Trading robustness for maintainability: an empirical study of evolving C# programs. In Jalote et al. [28], pages 584–595.
- [11] Junjie Chen, Wenxiang Hu, Dan Hao, Yingfei Xiong, Hongyu Zhang, Lu Zhang, and Bing Xie. An empirical comparison of compiler testing techniques. In Dillon et al. [17], pages 180–190.
- [12] Shaunik Roy Choudhary, Mukul R. Prasad, and Alessandro Orso. XPERT: accurate identification of cross-browser issues in web applications. In Notkin et al. [39], pages 702–711.
- [13] Jacob Cohen. *Statistical power analysis for the behavioral sciences*. Academic Press, 1969.
- [14] Jacob Cohen. The earth is round ($p < .05$). *American Psychologist*, 49(12):997–1003, 1994.
- [15] Confusion of the inverse. http://rationalwiki.org/wiki/Confusion_of_the_inverse, February 2016.
- [16] Premkumar T. Devanbu, Thomas Zimmermann, and Christian Bird. Belief & evidence in empirical software engineering. In Dillon et al. [17], pages 108–119.
- [17] Laura K. Dillon, Willem Visser, and Laurie Williams, editors. *Proceedings of the 38th International Conference on Software Engineering, ICSE 2016*. ACM, 2016.
- [18] Allen B. Downey. *Think Bayes*. O'Reilly Media, 2013.
- [19] H.-Christian Estler, Martin Nordio, Carlo A. Furia, Bertrand Meyer, and Johannes Schneider. Agile vs. structured distributed software development: A case study. In *Proceedings of the 7th International Conference on Global Software Engineering (ICGSE'12)*, pages 11–20. IEEE, 2012.
- [20] Hans-Christian Estler, Martin Nordio, Carlo A. Furia, Bertrand Meyer, and Johannes Schneider. Agile vs. structured distributed software development: A case study. *Empirical Software Engineering*, 19(5):1197–1224, 2014.
- [21] David Silver et al. Mastering the game of Go with deep neural networks and tree search. *Nature*, 429:484–489, 2016.
- [22] Andrew Gelman. The problems with p -values are not just with p -values. *The American Statistician*, 2016. Online discussion: http://www.stat.columbia.edu/~gelman/research/published/asa_pvalues.pdf.
- [23] Irving John Good. Explicativity, corroboration, and the relative odds of hypotheses. *Synthese*, 30(1/2):39–73, 1975.
- [24] Steven N. Goodman. Toward evidence-based medical statistics. 1: The p value fallacy. *Annals of Internal Medicine*, 130(12):995–1004, 1999.
- [25] Chris Bambey Guure, Noor Akma Ibrahim, and Al Omari Mohammed Ahmed. Bayesian estimation of two-parameter Weibull distribution using extension of Jeffreys' prior information with three loss functions. *Mathematical Problems in Engineering*, 2012. <http://dx.doi.org/10.1155/2012/589640>.
- [26] Trevor Hastie, Robert Tibshirani, and Jerome Friedman. *The Elements of Statistical Learning: Data Mining, Inference, and Prediction*. Springer, 2nd edition, 2009.
- [27] John P. A. Ioannidis. Why most published research findings are false. *PLoS Med*, 2(8), 2005.
- [28] Pankaj Jalote, Lionel C. Briand, and André van der Hoek, editors. *36th International Conference on Software Engineering, ICSE '14*. ACM, 2014.
- [29] Andreas Jedlitschka, Natalia Juristo Juzgado, and H. Dieter Rombach. Reporting experiments to satisfy professionals' information needs. *Empirical Software Engineering*, 19(6):1921–1955, 2014.
- [30] Harold Jeffreys. *Theory of Probability*. Oxford Classic Texts in the Physical Sciences. Oxford University Press, 3rd edition, 1998.
- [31] Capers Jones. Function points as a universal software metric. *ACM SIGSOFT Software Engineering Notes*, 38(4):1–27, 2013.
- [32] Miryung Kim, Thomas Zimmermann, Robert DeLine, and Andrew Begel. The emerging role of data scientists on software development teams. In Dillon et al. [17], pages 96–107.
- [33] Miryung Kim, Thomas Zimmermann, Robert DeLine, and Andrew Begel. The emerging role of data scientists on software development teams. In Dillon et al. [17], pages 96–107.
- [34] Irene Manotas, Christian Bird, Rui Zhang, David C. Shepherd, Ciera Japan, Caitlin Sadowski, Lori L. Pollock, and James Clause. An empirical study of practitioners' perspectives on green software engineering. In Dillon et al. [17], pages 237–248.
- [35] Daniel Matichuk, Toby C. Murray, June Andronick, D. Ross Jeffery, Gerwin Klein, and Mark Staples. Empirical study towards a leading indicator for cost of formal software verification. In Bertolino et al. [9], pages 722–732.
- [36] Tim Menzies, Laurie Williams, and Thomas Zimmermann, editors. *Perspectives on Data Science for Software Engineering*. Morgan Kaufmann, 2016.
- [37] Sarah Nadi, Thorsten Berger, Christian Kästner, and Krzysztof Czarnecki. Mining configuration constraints: static analyses and empirical results. In Jalote et al. [28], pages 140–151.
- [38] Sebastian Nanz and Carlo A. Furia. A comparative study of programming languages in Rosetta Code. In *Proceedings of the 37th International Conference on Software Engineering (ICSE)*, pages 778–788. ACM, 2015.
- [39] David Notkin, Betty H. C. Cheng, and Klaus Pohl, editors. *35th International Conference on Software Engineering, ICSE '13*. IEEE Computer Society, 2013.
- [40] Sebastiano Panichella, Annibale Panichella, Moritz Beller, Andy Zaidman, and Harald C. Gall. The impact of test case summaries on bug fixing performance: an empirical investigation. In Dillon et al. [17], pages 547–558.
- [41] Mike Papadakis, Yue Jia, Mark Harman, and Yves Le Traon. Trivial compiler equivalence: A large scale empirical study of a simple, fast and effective equivalent mutant detection technique. In Bertolino et al. [9], pages 936–946.
- [42] Marian Petre. UML in practice. In Notkin et al. [39], pages 722–731.
- [43] Nadia Polikarpova, Carlo A. Furia, Yu Pei, Yi Wei, and Bertrand Meyer. What good are strong specifications? In *Proceedings of the 35th International Conference on Software Engineering (ICSE)*, pages 257–266. ACM, May 2013.
- [44] Rosetta code. <http://rosettacode.org/>, Aug 2016.
- [45] Marija Selakovic and Michael Pradel. Performance issues and optimizations in JavaScript: an empirical study. In Dillon et al. [17], pages 61–72.
- [46] Janet Siegmund, Norbert Siegmund, and Sven Apel. Views on internal and external validity in empirical software engineering. In Bertolino et al. [9], pages 9–19.
- [47] Joseph P. Simmons, Leif D. Nelson, and Uri Simonsohn. False-positive psychology. *Psychological Science*, 22(11):1359–1366, 2011.
- [48] Klaas-Jan Stol, Paul Ralph, and Brian Fitzgerald. Grounded theory in software engineering research: a critical review and guidelines. In Dillon et al. [17], pages 120–131.
- [49] Guoxin Su and David S. Rosenblum. Perturbation analysis of stochastic systems with empirical distribution parameters. In Jalote et al. [28], pages 311–321.
- [50] The computer language benchmarks game. <http://benchmarksgame.alioth.debian.org/>, Aug 2016.

- [51] Phillip Merlin Uesbeck, Andreas Stefik, Stefan Hanenberg, Jan Pedersen, and Patrick Daleiden. An empirical study on the impact of C++ lambdas and programmer experience. In Dillon et al. [17], pages 760–771.
- [52] M. P. Wand and M. C. Jones. *Kernel Smoothing*, volume 60 of *Monographs on Statistics and Applied Probability*. Chapman & Hall/CRC, 1994.
- [53] Ronald L. Wasserstein and Nicole A. Lazar. The ASA’s statement on p -values: Context, process, and purpose. *The American Statistician*, 70(2):129–133, 2016.
- [54] Claes Wohlin, Per Runeson, Martin Höst, Magnus C. Ohlsson, and Björn Regnell. *Experimentation in Software Engineering*. Springer, 2012.
- [55] Aiko Fallas Yamashita and Leon Moonen. Exploring the impact of inter-smell relations on software maintainability: an empirical study. In Notkin et al. [39], pages 682–691.
- [56] Hongyu Zhang. On the distribution of software faults. *IEEE Transactions on Software Engineering*, 34(2):301–302, 2008.
- [57] Hongyu Zhang, Liang Gong, and Steven Versteeg. Predicting bug-fixing time: an empirical study of commercial software projects. In Notkin et al. [39], pages 1042–1051.
- [58] Hao Zhong and Zhendong Su. An empirical study on real bug fixes. In Bertolino et al. [9], pages 913–923.

APPENDIX
CONTENTS

I	Introduction	1
II	Related Work	2
III	A Practical Overview of Bayesian Statistics	2
III-A	Bayes Theorem	3
III-B	Frequentist vs. Bayesian Statistics	3
IV	Case Studies	4
IV-A	Programming Languages Performance Comparison	4
IV-B	Agile vs. Structured Development	6
IV-C	Testing with Specifications	8
V	Threats to Validity	10
VI	Practical Guidelines	11
	References	12
	Appendix	14
A	Rosetta Code Study	16
A1	Running time	16
A2	Memory usage	23
B	Agile vs. Structured Study	30
B1	Success	30
B2	Importance for customers	30
C	Testing Study	32

LIST OF FIGURES

1	Posterior distributions \mathcal{P}^S of running time ratios of Java vs. Python (left) and F# vs. Ruby (right).	7
3	Comparison of running time: qualitative summaries.	7
6	Marginals $m[\alpha]$ and $m[\beta]$ of the posterior distribution $m[\alpha, \beta]$ of parameters α and β . The graph indicates maxima $\hat{\alpha}$ and $\hat{\beta}$ and 90% credible intervals $(\alpha_{90}^l, \alpha_{90}^h)$ and $(\beta_{90}^l, \beta_{90}^h)$	9
7	Cumulative distribution function $W_{\alpha, \beta}$ (5) for the different values of α and β highlighted in Fig. 6.	9
10	Running time	16
11	Running time (C vs. other languages)	17
12	Running time (C# vs. other languages)	18
13	Running time (F# vs. other languages)	19
14	Running time (Go vs. other languages)	20
15	Running time (Haskell vs. other languages)	21
16	Running time (Java vs. other languages)	21
17	Running time (Python vs. other languages)	22
18	Comparison of used memory: qualitative summaries.	23
20	Maximum RAM usage	23
21	Maximum RAM usage (C vs. other languages)	24
22	Maximum RAM usage (C# vs. other languages)	25
23	Maximum RAM usage (F# vs. other languages)	26
24	Maximum RAM usage (Go vs. other languages)	27
25	Maximum RAM usage (Haskell vs. other languages)	28
26	Maximum RAM usage (Java vs. other languages)	28
27	Maximum RAM usage (Python vs. other languages)	29
34	Marginals $m[\alpha]$ and $m[\beta]$ of the posterior distribution $m[\alpha, \beta]$ of parameters α and β for uniform priors (left) and for Jeffreys prior (right).	32

35	Cumulative distribution function $W_{\alpha,\beta}$ for the values of α and β in Fig. 34 for uniform priors (left) and for Jeffreys prior (right).	33
36	Marginals of the probability distribution for a module having zero bugs detected by random testing with strong specifications for the values of α and β in a 90% credible interval for uniform priors (left) and for Jeffreys prior (right).	33
37	Marginals of the probability distribution for a module having at most five bugs detected by random testing with strong specifications for the values of α and β in a 90% credible interval for uniform priors (left) and for Jeffreys prior (right).	34
38	Distributions N_m of total bugs in module C_m (starting with uniform priors to get values of $\hat{\alpha}, \hat{\beta}$ for prior Weibull).	35
39	Distributions N_m of total bugs in module C_m (starting with uniform priors to get values of $\hat{\alpha}, \hat{\beta}$ for prior Weibull).	36
40	Distributions N_m of total bugs in module C_m (starting with uniform priors to get values of $\hat{\alpha}, \hat{\beta}$ for prior Weibull).	37

LIST OF TABLES

2	Comparison of running time: 95% credible intervals CI and medians m of posterior distributions.	6
4	For C one of the subsets of $\{A, I, L, T\}$ in the column headers, $o_C[k]$ is the probability that the outcome of projects following processes in categories C is $k \in [0..2]$	7
5	Bayes factors $K_C(\bar{D})$ estimating whether the data \bar{D} supports hypothesis h_A (agile leads to more successful projects) more than hypothesis h_+ (agile is no more successful), for different baseline project outcome distributions.	8
8	Median per public method $m/ M $, median $m(N)$, and 90% credible interval (N_{90}^l, N_{90}^h) of $N_d^{\hat{\alpha}, \hat{\beta}}$ —estimating the total number of bugs in class C_m	10
9	Comparison of running times	16
19	Comparison of maximum RAM usage	23
28	Different distributions for the baseline probability of <i>outcome</i> for software projects: for C one of the subsets of $\{A, I, L, T\}$ in the column headers, $o_C[k]$ is the probability that outcome is $k \in \{0, 1, 2\}$ in processes of category C	30
29	Bayes factors K estimating to what extent the hypothesis “agile leads to more successful projects” is supported over the other hypothesis “agile is no better than structured”.	30
30	Different distributions for the baseline probability of <i>customer importance</i> for software projects: for C one of the subsets of $\{A, I, L, T\}$ in the column headers, $i_C[k]$ is the probability that customer importance is $k \in \{0, 1, 2\}$ in processes of category C	30
31	Bayes factors K estimating to what extent the hypothesis “agile is used for projects that are more important for customers” is supported over the other hypothesis “agile is no better than structured”.	31
32	For every class C_m , $m = 1, \dots, 21$, the mean $\mu(N)$, median $m(N)$, maximum likelihood \hat{N} , 90% credible interval (N_{90}^l, N_{90}^h) , ratio $m(N)/LOC$ median to lines of code, and ratio $m(N)/\#R$ median to number of methods of the distribution of total bugs in the class. The analysis started with $\hat{\alpha}, \hat{\beta}$ given by the maximum likelihood for α, β in $m[\alpha, \beta]$ computed from a <i>uniform</i> prior.	32
33	For every class C_m , $m = 1, \dots, 21$, the mean $\mu(N)$, median $m(N)$, maximum likelihood \hat{N} , 90% credible interval (N_{90}^l, N_{90}^h) , ratio $m(N)/LOC$ median to lines of code, and ratio $m(N)/\#R$ median to number of methods of the distribution of total bugs in the class. The analysis started with $\hat{\alpha}, \hat{\beta}$ given by the maximum likelihood for α, β in $m[\alpha, \beta]$ computed from <i>Jeffreys</i> prior.	32

A. Rosetta Code Study

The tables comparing programming languages gray out cells corresponding to values that may provide lower confidence. Given a confidence intervals (c, C) , mean μ , and median m , let $\delta = C - c \geq 0$ be the interval size and $s = \min(|c|, |C|)$ be the absolute value of the endpoint closer to the origin. If $c < 0 < C$ or $-1.1 < \mu < 1.1$ the comparison may be not significant (dark gray background); if the comparison is significant and $\delta \geq s$, $s \leq 2$, and $|m| \leq 2$ the comparison may be only weakly significant (light gray background); in all other cases it is significant (no gray background).

LANGUAGE	MEASURE	C	C#	F#	Go	Haskell	Java	Python
C#	CI	(-10.1, -8.7)						
	m	-9.22						
	μ	-9.57						
F#	CI	(-76.0, -64.5)	(-8.9, -4.6)					
	m	-72.61	-5.29					
	μ	-70.58	-6.83					
Go	CI	(-2.3, -1.3)	(1.0, 2.5)	(16.9, 20.6)				
	m	-1.67	1.15	18.21				
	μ	-1.77	1.52	18.78				
Haskell	CI	(-5.9, -5.7)	(1.2, 1.7)	(3.2, 15.5)	(2.4, 2.5)			
	m	-5.76	1.23	6.77	2.49			
	μ	-5.82	1.35	7.03	2.47			
Java	CI	(-3.2, -3.1)	(-2.0, -1.3)	(5.7, 7.5)	(-8.5, -7.6)	(-8.6, -8.3)		
	m	-3.18	-1.77	6.94	-8.02	-8.63		
	μ	-3.18	-1.68	6.71	-8.06	-8.39		
Python	CI	(-54.2, -32.3)	(-1.4, 1.8)	(2.1, 12.7)	(-27.2, -17.7)	(-5.0, -1.2)	(-2.1, 2.2)	
	m	-52.47	1.3	7.93	-23.01	-1.82	1.76	
	μ	-44.23	1.31	7	-22.78	-2.58	1.31	
Ruby	CI	(-124.0, -90.9)	(-21.1, -11.6)	(1.0, 1.1)	(-142.2, -36.9)	(-22.0, -19.9)	(-17.0, -8.6)	(-19.7, -14.0)
	m	-100.69	-16.96	1.05	-141.92	-21.85	-15.32	-15.03
	μ	-105.99	-16.42	1.05	-105.32	-20.51	-12.76	-16.8

TABLE 9: Comparison of running times




Fig. 10: Running time

1) Running time:




Fig. 11: Running time (C vs. other languages)




Fig. 12: Running time (C# vs. other languages)




Fig. 13: Running time (F# vs. other languages)




Fig. 14: Running time (Go vs. other languages)




Fig. 15: Running time (Haskell vs. other languages)




Fig. 16: Running time (Java vs. other languages)




Fig. 17: Running time (Python vs. other languages)




Fig. 18: Comparison of used memory: qualitative summaries.

2) *Memory usage*: Rosetta’s *memory* experiments measure the maximum RAM usage of programs implementing the same tasks: $M(\ell, t)$ is the maximum RAM used by the *best* (that is, using the least amount of memory) implementation of t in language ℓ ; and $\mathbf{M}(\ell_1, \ell_2)$ is the vector of elementwise ratios (2), defined like $\mathbf{S}(\ell_1, \ell_2)$ but with respect to $\mathbf{M}(\ell_1)$ and $\mathbf{M}(\ell_2)$. Bench also includes *memory* experiments that determine vectors $\bar{\mathbf{M}}(\ell_1, \ell_2)$ and sets $\bar{\mathbf{M}}_{\Delta}(\ell_1, \ell_2, t)$, defined just like their counterparts for running time but measuring the maximum RAM used in each case. The following graphs, tables, and plots are the counterpart of the analysis of running time S with respect to the data M on memory usage.

LANGUAGE	MEASURE	C	C#	F#	Go	Haskell	Java	Python
C#	CI	(-12.9, 9.6)						
	m	9.83						
	μ	1.67						
F#	CI	(-65.3, -22.1)	(-9.2, -1.4)					
	m	-35.28	-6.32					
	μ	-39.51	-5.19					
Go	CI	(-3.2, -1.9)	(-7.0, 8.8)	(61.6, 63.2)				
	m	-1.84	-2.96	62.74				
	μ	-2.39	0.68	62.72				
Haskell	CI	(-12.8, -8.5)	(-5.0, -1.0)	(46.1, 49.3)	(-3.6, -3.4)			
	m	-11.11	-4.14	48.76	-3.56			
	μ	-10.71	-2.74	48.05	-3.56			
Java	CI	(-7.8, 1.7)	(-4.2, -1.2)	(1.4, 4.1)	(-33.5, -31.8)	(-2.7, 1.2)		
	m	-1.06	-2.34	2.26	-32.9	-2.07		
	μ	-3.4	-2.52	2.3	-32.89	-1.44		
Python	CI	(-18.0, -2.1)	(-15.5, 24.8)	(-4.3, 7.1)	(-7.0, -1.5)	(-2.2, 4.6)	(-10.6, -1.6)	
	m	-11.1	-7.58	-2.62	-6.82	2.35	-3.51	
	μ	-9.73	0.68	1.83	-4.49	2.23	-5.73	
Ruby	CI	(-229.5, -157.0)	(-36.5, -6.2)	(-23.6, -2.9)	(-194.8, -174.3)	(-60.7, -10.6)	(-25.6, -5.3)	(-12.2, -4.3)
	m	-154.78	-15.95	-18.33	-190.44	-43.66	-13	-10.82
	μ	-195.45	-17.16	-9.92	-184.58	-35.02	-12.07	-7.18

TABLE 19: Comparison of maximum RAM usage




Fig. 20: Maximum RAM usage




Fig. 21: Maximum RAM usage (C vs. other languages)




Fig. 22: Maximum RAM usage (C# vs. other languages)




Fig. 23: Maximum RAM usage (F# vs. other languages)




Fig. 24: Maximum RAM usage (Go vs. other languages)




Fig. 25: Maximum RAM usage (Haskell vs. other languages)




Fig. 26: Maximum RAM usage (Java vs. other languages)




Fig. 27: Maximum RAM usage (Python vs. other languages)

B. Agile vs. Structured Study

1) *Success*: Tab. 28 shows the distributions o_C for the nine combinations of process categories we analyze: A , AIL , $AILT$, AIT , AL , ALT , AT , IT , and T . These are used as baseline distributions in computing the Bayes factors. Tab. 28 is like Tab. 4 in the main paper.

Tab. 29 shows the Bayes factors $K_C(\bar{D})$ from AvsS, for each choice of baseline distribution C in Tab. 28. Each row uses different weights w_{ps} for the likelihoods (3) and (4). The table is partitioned in four parts separated by horizontal lines; they correspond, from top to bottom, to the analysis using different choices of lower bound $b = 1, 3, 4, 5$ for the scaling of data (row header). The scaling of data translates a project outcome $1 \leq x \leq 10$ into an outcome $0 \leq x' \leq r$ using lower bound b as follows. For $0 \leq k \leq r$, let $\sigma_r(k) = b + k(10 - b)/r$ be a uniformly spaced point over $[b, 10]$; then $x' = \text{argmin}_k |\sigma_r(k) - x|$. In the main paper, Tab. 5 shows the data for $b = 1$.

	A	AIL	$AILT$	AIT	AL	ALT	AT	IT	T
$\text{o}_C[0]$	7%	8%	10%	11%	7%	11%	12%	12%	18%
$\text{o}_C[1]$	30%	27%	28%	29%	27%	29%	31%	29%	32%
$\text{o}_C[2]$	63%	65%	62%	60%	66%	60%	57%	59%	50%

TABLE 28: Different distributions for the baseline probability of *outcome* for software projects: for C one of the subsets of $\{A, I, L, T\}$ in the column headers, $\text{o}_C[k]$ is the probability that outcome is $k \in \{0, 1, 2\}$ in processes of category C .

	A	AIL	$AILT$	AIT	AL	ALT	AT	IT	T
uniform	0.2456	0.2609	0.1655	0.1362	0.2881	0.1228	0.0780	0.0986	0.0131
triangle	0.2472	0.2614	0.1704	0.1411	0.2883	0.1284	0.0827	0.1037	0.0151
power	0.2484	0.2618	0.1735	0.1441	0.2885	0.1320	0.0855	0.1069	0.0162
exp	0.2525	0.2633	0.1860	0.1567	0.2891	0.1471	0.0986	0.1208	0.0229
uniform	0.0329	0.0277	0.0625	0.0735	0.0188	0.0782	0.0888	0.0853	0.0424
triangle	0.0348	0.0295	0.0648	0.0760	0.0201	0.0807	0.0915	0.0879	0.0460
power	0.0361	0.0307	0.0665	0.0777	0.0210	0.0824	0.0933	0.0897	0.0480
exp	0.0414	0.0358	0.0726	0.0843	0.0248	0.0888	0.1003	0.0965	0.0583
uniform	0.0406	0.0336	0.0854	0.1055	0.0220	0.1151	0.1461	0.1325	0.1102
triangle	0.0427	0.0356	0.0877	0.1077	0.0235	0.1170	0.1478	0.1344	0.1156
power	0.0442	0.0370	0.0894	0.1094	0.0245	0.1185	0.1491	0.1358	0.1187
exp	0.0501	0.0427	0.0953	0.1152	0.0287	0.1235	0.1537	0.1406	0.1330
uniform	0.0406	0.0336	0.0854	0.1055	0.0220	0.1151	0.1461	0.1325	0.1102
triangle	0.0427	0.0356	0.0877	0.1077	0.0235	0.1170	0.1478	0.1344	0.1156
power	0.0442	0.0370	0.0894	0.1094	0.0245	0.1185	0.1491	0.1358	0.1187
exp	0.0501	0.0427	0.0953	0.1152	0.0287	0.1235	0.1537	0.1406	0.1330

TABLE 29: Bayes factors K estimating to what extent the hypothesis “agile leads to more successful projects” is supported over the other hypothesis “agile is no better than structured”.

2) *Importance for customers*: The data in AvsS also reports, for each project $p \in P$, its *importance* for customers $I(p)$ on a scale 1–10, where 1 denotes an unimportant project and 10 denotes a very critical one. The multisets I_A , I_S , and I are defined similarly to O_A , O_S , and O but for importance assessments.

The data in ITP also assesses “stakeholder value”, which we can assimilate to *importance* for customers—a most significant group of stakeholders. For each category $c \in \{A, H, I, L, T\}$, each respondent $r \in R$ assesses the projects in category c according to their stakeholder value $v_c(r)$ on a scale 0–4, where 0 denotes no value and 4 denotes very high value.¹⁷ For every non-empty subset $C \subseteq \{A, H, I, L, T\}$, we define a distribution ι_C over values in the range $[0, 4]$ as follows. If C is a singleton set $\{c\}$ with $c \in \{A, H, I, L, T\}$, $\iota_c[k]$ is the probability $|\{r \in R \mid v_c(r) = k\}|/|R|$ that a project in category c has value k . If C is any non-empty subset of $\{A, H, I, L, T\}$, $\iota_C[k]$ is the weighted average $\iota_C[k] = \sum_{c \in C} \iota_c[k]/|C|$. Tab. 30 shows the distributions ι_C for the nine combinations of process categories we analyze.

	A	AIL	$AILT$	AIT	AL	ALT	AT	IT	T
$\iota_C[0]$	0%	1%	2%	2%	0%	3%	3%	3%	7%
$\iota_C[1]$	4%	3%	9%	9%	6%	14%	15%	11%	26%
$\iota_C[2]$	15%	18%	20%	21%	13%	19%	21%	24%	28%
$\iota_C[3]$	30%	35%	35%	35%	33%	34%	32%	37%	35%
$\iota_C[4]$	51%	43%	34%	33%	48%	30%	29%	25%	4%

TABLE 30: Different distributions for the baseline probability of *customer importance* for software projects: for C one of the subsets of $\{A, I, L, T\}$ in the column headers, $\iota_C[k]$ is the probability that customer importance is $k \in \{0, 1, 2, 3, 4\}$ in processes of category C .

¹⁷Respondents could also mark this question as “not applicable”, in which case we ignored their answer.

The Bayes factors are computed just like the analysis of success mutatis mutandis. Tab. 5 shows the Bayes factors for the data $I_A \cup I_S$ from AvsS, using the same conventions as Tab. 29 and using ι_C as baseline distributions, for C one of the nine distributions in Tab. 30.

	A	AIL	$AILT$	AIT	AL	ALT	AT	IT	T
uniform	0.0395	0.0494	0.0087	0.0087	0.0395	0.0038	0.0019	0.0019	0.0000
triangle	0.0429	0.0549	0.0114	0.0116	0.0435	0.0057	0.0029	0.0030	0.0000
power	0.0449	0.0570	0.0118	0.0121	0.0452	0.0058	0.0029	0.0030	0.0000
exp	0.0547	0.0728	0.0217	0.0238	0.0566	0.0140	0.0074	0.0078	0.0001
uniform	0.0003	0.0152	0.0800	0.0800	0.0003	0.0418	0.0205	0.0205	0.0001
triangle	0.0003	0.0162	0.0839	0.0854	0.0003	0.0477	0.0238	0.0241	0.0002
power	0.0004	0.0168	0.0855	0.0877	0.0004	0.0499	0.0248	0.0252	0.0001
exp	0.0005	0.0196	0.0954	0.1024	0.0004	0.0679	0.0348	0.0365	0.0007
uniform	0.0000	0.0000	0.0002	0.0002	0.0000	0.0053	0.0129	0.0129	0.0001
triangle	0.0000	0.0000	0.0003	0.0003	0.0000	0.0063	0.0154	0.0155	0.0002
power	0.0000	0.0000	0.0003	0.0003	0.0000	0.0067	0.0163	0.0164	0.0001
exp	0.0000	0.0000	0.0004	0.0004	0.0000	0.0099	0.0242	0.0250	0.0007
uniform	0.0000	0.0000	0.0010	0.0010	0.0000	0.0035	0.0203	0.0203	0.0007
triangle	0.0000	0.0000	0.0012	0.0012	0.0000	0.0040	0.0231	0.0232	0.0011
power	0.0000	0.0000	0.0014	0.0013	0.0000	0.0042	0.0247	0.0247	0.0011
exp	0.0000	0.0000	0.0021	0.0020	0.0000	0.0057	0.0330	0.0331	0.0037

TABLE 31: Bayes factors K estimating to what extent the hypothesis “agile is used for projects that are more important for customers” is supported over the other hypothesis “agile is no better than structured”.

C. Testing Study

The uniform prior assigns constant probability to every pair α, β ; Jeffreys prior [25] assigns it probability proportional to $(\alpha\beta)^{-1}$.

	C_1	C_2	C_3	C_4	C_5	C_6	C_7	C_8	C_9	C_{10}	C_{11}	C_{12}	C_{13}	C_{14}	C_{15}	C_{16}	C_{17}	C_{18}	C_{19}	C_{20}	C_{21}
$\mu(N)$	13	2	7	31	34	7	7	2	7	7	7	2	36	2	10	10	2	40	2	68	2
$m(N)$	10	2	8	17	36	5	14	2	7	4	3	2	30	1	8	10	2	19	3	66	2
\hat{N}	9	0	4	26	26	4	4	0	4	4	4	0	26	0	6	6	0	40	0	60	0
N_{90}^l	5	0	2	18	20	2	2	0	2	2	2	0	22	0	4	4	0	25	0	49	0
N_{90}^h	26	7	17	54	57	17	17	7	17	17	17	7	60	7	22	22	7	66	7	100	7
$m(N)/\text{LOC}$	1.2E-02	1.2E-03	1.5E-02	8.6E-03	3.2E-02	9.4E-03	1.0E-02	1.0E-02	3.8E-02	7.7E-03	1.6E-03	7.2E-03	1.4E-02	3.4E-03	7.3E-03	5.1E-03	5.4E-03	6.9E-03	6.9E-03	2.6E-02	5.4E-03
$m(N)/\#\text{R}$	0.19	0.03	0.24	0.34	0.56	0.16	0.27	0.15	0.51	0.09	0.04	0.15	0.37	0.07	0.29	0.14	0.15	0.20	0.19	0.73	0.15

TABLE 32: For every class C_m , $m = 1, \dots, 21$, the mean $\mu(N)$, median $m(N)$, maximum likelihood \hat{N} , 90% credible interval (N_{90}^l, N_{90}^h) , ratio $m(N)/\text{LOC}$ median to lines of code, and ratio $m(N)/\#\text{R}$ median to number of methods of the distribution of total bugs in the class. The analysis started with $\hat{\alpha}, \hat{\beta}$ given by the maximum likelihood for α, β in $m[\alpha, \beta]$ computed from a *uniform* prior.

	C_1	C_2	C_3	C_4	C_5	C_6	C_7	C_8	C_9	C_{10}	C_{11}	C_{12}	C_{13}	C_{14}	C_{15}	C_{16}	C_{17}	C_{18}	C_{19}	C_{20}	C_{21}
$\mu(N)$	13	1	7	32	34	7	7	1	7	7	7	1	36	1	10	10	1	41	1	70	1
$m(N)$	14	0	11	28	28	5	5	0	12	10	4	0	34	0	11	8	0	46	0	66	0
\hat{N}	9	0	4	26	26	4	4	0	4	4	4	0	26	0	6	6	0	40	0	60	0
N_{90}^l	5	0	2	18	20	2	2	0	2	2	2	0	22	0	4	4	0	25	0	50	0
N_{90}^h	26	6	17	56	59	17	17	6	17	17	17	6	62	6	21	21	6	68	6	105	6
$m(N)/\text{LOC}$	1.7E-02	0.0E+00	2.0E-02	1.4E-02	2.5E-02	8.3E-03	3.4E-03	0.0E+00	6.6E-02	2.0E-02	2.4E-03	0.0E+00	1.6E-02	0.0E+00	9.8E-03	3.9E-03	0.0E+00	1.7E-02	0.0E+00	2.6E-02	0.0E+00
$m(N)/\#\text{R}$	0.27	0.00	0.34	0.57	0.43	0.14	0.09	0.00	0.88	0.24	0.06	0.00	0.40	0.00	0.39	0.11	0.00	0.51	0.00	0.73	0.00

TABLE 33: For every class C_m , $m = 1, \dots, 21$, the mean $\mu(N)$, median $m(N)$, maximum likelihood \hat{N} , 90% credible interval (N_{90}^l, N_{90}^h) , ratio $m(N)/\text{LOC}$ median to lines of code, and ratio $m(N)/\#\text{R}$ median to number of methods of the distribution of total bugs in the class. The analysis started with $\hat{\alpha}, \hat{\beta}$ given by the maximum likelihood for α, β in $m[\alpha, \beta]$ computed from *Jeffreys* prior.




Fig. 34: Marginals $m[\alpha]$ and $m[\beta]$ of the posterior distribution $m[\alpha, \beta]$ of parameters α and β for uniform priors (left) and for Jeffreys prior (right).




Fig. 35: Cumulative distribution function $W_{\alpha,\beta}$ for the values of α and β in Fig. 34 for uniform priors (left) and for Jeffreys prior (right).




Fig. 36: Marginals of the probability distribution for a module having zero bugs detected by random testing with strong specifications for the values of α and β in a 90% credible interval for uniform priors (left) and for Jeffreys prior (right).





Fig. 37: Marginals of the probability distribution for a module having at most five bugs detected by random testing with strong specifications for the values of α and β in a 90% credible interval for uniform priors (left) and for Jeffreys prior (right).




Fig. 38: Distributions N_m of total bugs in module C_m (starting with uniform priors to get values of $\hat{\alpha}, \hat{\beta}$ for prior Weibull).




Fig. 39: Distributions N_m of total bugs in module C_m (starting with uniform priors to get values of $\hat{\alpha}, \hat{\beta}$ for prior Weibull).




Fig. 40: Distributions N_m of total bugs in module C_m (starting with uniform priors to get values of $\hat{\alpha}, \hat{\beta}$ for prior Weibull).