

FUZZY LOGIC IN NARROW SENSE WITH HEDGES

Van-Hung Le

Faculty of Information Technology
Hanoi University of Mining and Geology, Vietnam
levanhung@humg.edu.vn

ABSTRACT

Classical logic has a serious limitation in that it cannot cope with the issues of vagueness and uncertainty into which fall most modes of human reasoning. In order to provide a foundation for human knowledge representation and reasoning in the presence of vagueness, imprecision, and uncertainty, fuzzy logic should have the ability to deal with linguistic hedges, which play a very important role in the modification of fuzzy predicates. In this paper, we extend fuzzy logic in narrow sense with graded syntax, introduced by Novák *et al.*, with many hedge connectives. In one case, each hedge does not have any dual one. In the other case, each hedge can have its own dual one. The resulting logics are shown to also have the Pavelka-style completeness.

KEYWORDS

Fuzzy Logic in Narrow Sense, Hedge Connective, First-Order Logic, Pavelka-Style Completeness

1. INTRODUCTION

Extending logical systems of mathematical fuzzy logic (MFL) with hedges is axiomatized by Hájek [1], Vychodil [2], Esteva *et al.* [3], among others. Hedges are called *truth-stressing* or *truth-depressing* if they, respectively, strengthen or weaken the meaning of the applied proposition. Intuitively, on a chain of truth values, the truth function of a truth-depressing (resp., truth-stressing) hedge (connective) is a superdiagonal (resp., subdiagonal) non-decreasing function preserving 0 and 1. In [1, 2, 3], logical systems of MFL are extended by a truth-stressing hedge and/or a truth-depressing one.

Nevertheless, in the real world, humans often use many hedges, e.g., *very*, *highly*, *rather*, and *slightly*, simultaneously to express different levels of emphasis. Furthermore, a hedge may or may not have a dual one, e.g., *slightly* (resp., *rather*) can be seen as a dual hedge of *very* (resp., *highly*). Therefore, in [4, 5], Le *et al.* propose two axiomatizations for propositional logical systems of MFL with many hedges. In the axiomatization in [5], each hedge does not have any dual one whereas in the axiomatization in [4], each hedge can have its own dual one. In [5, 6], logical systems with many hedges for representing and reasoning with linguistically-expressed human knowledge are also proposed.

Fuzzy logic in narrow sense with graded syntax (FLn) is introduced by Novák *et al.* in [7]. In FLn, both syntax and semantics are evaluated by degrees. The graded approach to syntax can be seen as an elegant and natural generalization of classical logic for inference under vagueness since it allows one to explicitly represent and reason with partial truth, i.e., proving partially true conclusions from partially true premises, and it enjoys the Pavelka-style completeness. In this paper, we extend FLn with many hedges in order to provide a foundation for human knowledge representation and reasoning in the presence of vagueness since linguistic hedges are very often used by humans and play a very important

role in the modification of fuzzy predicates. FLn is extended in two cases: (i) each hedge does not have a dual one, and (ii) each hedge can have its own dual one. We show that the resulting logics also have the Pavelka-style completeness.

The remainder of the paper is organized as follows. Section 2 gives an overview of notions and results of FLn. Section 3 presents two extensions of FLn with many hedges. In one case, each hedge does not have any dual one, and in the other, each hedge can have its own dual one. The resulting logics are also shown to have the Pavelka-style completeness. Section 4 concludes the paper.

2. FUZZY LOGIC IN NARROW SENSE

FLn [7] is *truth functional*. A compound formula is built from its constituents using a logical connective. The truth value of a compound formula is a function of the truth values of its constituents. The function is called the *truth function* of the connective.

The set of truth values forms a residuated lattice, and more precisely, a Łukasiewicz algebra (or MV-algebra) $\mathcal{L} = \langle L, \vee, \wedge, \otimes, \Rightarrow, 0, 1 \rangle$, where $L = [0, 1]$, in which:

- (i) $\langle L, \vee, \wedge, 0, 1 \rangle$ is a lattice with the ordering \leq defined using the operations \vee (supremum), \wedge (infimum) as usual, and $0, 1$ are its least and the greatest elements, respectively;
- (ii) The operations \otimes and \Rightarrow are Łukasiewicz conjunction and implication defined by $a \otimes b = 0 \vee (a + b - 1)$ and $a \Rightarrow b = 1 \wedge (1 - a + b)$, respectively. Thus, $a \leq b$ iff $a \Rightarrow b = 1$. They satisfy the *residuation property* [8]: $a \otimes b \leq c$ iff $a \leq b \Rightarrow c$.

The language J of FLn consists of: (a) a countable set Var of object variables x, y, \dots ; (b) a finite or countable set of object constants $\mathbf{u}_1, \mathbf{u}_2, \dots$; (c) a finite or countable set $Func$ of functional symbols f, g, \dots ; (d) a nonempty finite or countable set $Pred$ of predicate symbols P, Q, \dots ; (e) logical constants \bar{a} for all $a \in L$; (f) implication connective \rightarrow ; (g) general quantifier \forall ; and (h) various types of brackets as auxiliary symbols.

Terms are defined as follows: (i) a variable x or constant u is a (atomic) term; (ii) if f be an n -ary functional symbol and t_1, \dots, t_n terms, then $f(t_1, \dots, t_n)$ is a term.

Formulae are defined as follows: (a) logical constants \bar{a} are a formula; (b) if P is an n -ary predicate symbol, and t_1, \dots, t_n are terms, then $P(t_1, \dots, t_n)$ is a formula; (c) if A, B are formulae, then $A \rightarrow B$ is a formula; and (d) if x is a variable, and A is a formula, then $(\forall x)A$ is a formula. Other connectives and formulae are defined as follows:

$$\begin{aligned} \neg A &\equiv A \rightarrow \bar{0} \text{ (negation); } A \& B \equiv \neg(A \rightarrow \neg B) \text{ (Łukasiewicz conjunction);} \\ A \vee B &\equiv (B \rightarrow A) \rightarrow A \text{ (disjunction); } A \nabla B \equiv \neg(\neg A \& \neg B) \text{ (Łukasiewicz disjunction);} \\ A \wedge B &\equiv \neg((B \rightarrow A) \rightarrow \neg B) \text{ (conjunction); } A \leftrightarrow B \equiv (A \rightarrow B) \wedge (B \rightarrow A) \text{ (equivalence);} \\ A^n &\equiv \underbrace{A \& A \& \dots \& A}_{n\text{-times}} \text{ (n-fold conjunction); } nA \equiv \underbrace{A \nabla A \nabla \dots \nabla A}_{n\text{-times}} \text{ (n-fold disjunction);} \\ (\exists x)A &\equiv \neg(\forall x)\neg A \text{ (existential quantifier).} \end{aligned}$$

The set of all formulae of J is denoted by F_J .

An *evaluated formula* is a pair a/A , where $A \in F_J$ and $a \in L$ is its syntactic evaluation. *Axioms* are sets of evaluated formulae. Since the evaluations can be interpreted as membership degrees in the fuzzy set, axioms can be seen as fuzzy sets of formulae.

$A \Subset U$ denotes that A is a fuzzy set on a universe U . The set of all fuzzy sets on U is denoted by $\mathcal{F}(U) = \{A | A \Subset U\}$. $\mathcal{F}(U)$ also contains all ordinary subsets of U .

Since a fuzzy set can be considered as a function, if we have a function $V : F_J \Rightarrow L$ and a fuzzy set $W \in F_J$, then $V \leq W$ means the ordering of functions.

Definition 1 [7] An n -ary inference rule r in FL_n is of the form:

$$r : \frac{a_1/A_1, \dots, a_n/A_n}{r^{evl}(a_1, \dots, a_n)/r^{syn}(A_1, \dots, A_n)} \quad (1)$$

which means from $a_1/A_1, \dots, a_n/A_n$ infer $r^{evl}(a_1, \dots, a_n)/r^{syn}(A_1, \dots, A_n)$, where r^{syn} is a partial n -ary syntactic operation on F_J , and r^{evl} is an n -ary lower semicontinuous evaluation operation on L (i.e., it preserves arbitrary suprema in all variables).

A fuzzy set $V \in F_J$ is closed w.r.t. r if $V(r^{syn}(A_1, \dots, A_n)) \geq r^{evl}(V(A_1), \dots, V(A_n))$ holds for all formulae $A_1, \dots, A_n \in Dom(r^{syn})$.

The set R of inference rules of FL_n consists of the following:

$$\begin{aligned} \text{Modus ponens: } r_{MP} : & \frac{a/A, b/A \rightarrow B}{a \otimes b/B}; & \text{Generalization: } r_G : & \frac{a/A}{a/(\forall x)A} \\ \text{Logical constant introduction: } r_{LC} : & \frac{a/A}{a \Rightarrow a/\bar{a} \rightarrow A} \end{aligned}$$

Note that the evaluation operation $r_{LC}^{evl}(x)$ of r_{LC} is $a \Rightarrow x$.

An *proof* of $A \in F_J$ from a fuzzy set $X \in F_J$ is a finite sequence of evaluated formulae $w := a_0/A_0, a_1/A_1, \dots, a_n/A_n$, whose each member is either a member of X , i.e., $a_i/A_i := X(A_i)/A_i$, or follows from some preceding members of the sequence using an inference rule of FL_n , and the last member is $a_n/A_n := a/A$. The evaluation a is called the *value* of the proof w , denoted $Val(w)$. A proof w of a formula A can be denoted w_A .

A *graded consequence operation* is a closure operation $\mathcal{C} : \mathcal{F}(F_J) \Rightarrow \mathcal{F}(F_J)$ assigning to a fuzzy set $X \in F_J$ a fuzzy set $\mathcal{C}(X) \in F_J$ and fulfilling $\mathcal{C}(X) = \mathcal{C}(\mathcal{C}(X))$.

Definition 2 [7] Let R be the set of inference rules. The fuzzy set of syntactic consequences of a fuzzy set $X \in F_J$ is the following membership function, for all $A \in F_J$:

$$\mathcal{C}^{syn}(X)(A) = \bigwedge \{V(A) \mid V \in F_J, X \leq V \text{ and } V \text{ is closed w.r.t. all } r \in R\} \quad (2)$$

Theorem 1 [7] Let $X \in F_J$. Then, $\mathcal{C}^{syn}(X)(A) = \bigvee \{Val(w) \mid w \text{ is a proof of } A \text{ from } X\}$.

A *structure* for the language J of FL_n is $\mathcal{D} = \langle D, (P_D)_{P \in Pred}, (f_D)_{f \in Func}, u_1, u_2, \dots \rangle$, where D is a non-empty domain (set); $(P_D) \in D$ assigns to each n -ary predicate symbol $P \in Pred$ an n -ary fuzzy relation P_D on D ; (f_D) assigns to each n -ary functional symbol $f \in Func$ an n -ary function f_D on D ; $u_1, u_2, \dots \in D$ are designated elements which are assigned to each constant $\mathbf{u}_1, \mathbf{u}_2, \dots$ of the language J , respectively.

A *truth valuation* of formulae in a structure \mathcal{D} is a function (also denoted by) $\mathcal{D} : F_J \rightarrow \mathcal{L}$ defined by means of *interpretation*. Let \mathcal{D} be a structure for the language J . The language $J(\mathcal{D})$ is obtained from J by adding new constants being names for all elements from D , i.e., $J(\mathcal{D}) = J \cup \{\mathbf{d} \mid d \in D\}$.

Let $A(x)$ be a formula and t a term. $A_x[t]$ denotes a formula obtained from A by replacing all free occurrences of the variable x with t .

Interpretations of closed terms and formulae are defined as follows:

(i) *Interpretation* of closed terms: $\mathcal{D}(\mathbf{u}_i) = u_i$ if $\mathbf{u}_i \in J$ and $u_i \in D$; $\mathcal{D}(\mathbf{d}) = d$ if $d \in D$; $\mathcal{D}(f(t_1, \dots, t_n)) = f_D(\mathcal{D}(t_1), \dots, \mathcal{D}(t_n))$.

(ii) *Interpretation* of closed formulae (where t_1, \dots, t_n are closed terms): $\mathcal{D}(\bar{a}) = a$ for all $a \in L$; $\mathcal{D}(P(t_1, \dots, t_n)) = P_D(\mathcal{D}(t_1), \dots, \mathcal{D}(t_n))$; $\mathcal{D}((\forall x)A) = \bigwedge\{\mathcal{D}(A_x[\mathbf{d}]) \mid \mathbf{d} \in D\}$.

(iii) *Interpretation* of the derived connectives:

$$\begin{aligned} \mathcal{D}(\neg A) &= \neg \mathcal{D}(A) & \mathcal{D}(A \wedge B) &= \mathcal{D}(A) \wedge \mathcal{D}(B) \\ \mathcal{D}(A \& B) &= \mathcal{D}(A) \otimes \mathcal{D}(B) & \mathcal{D}(A \vee B) &= \mathcal{D}(A) \vee \mathcal{D}(B) \\ \mathcal{D}(A \oplus B) &= \mathcal{D}(A) \oplus \mathcal{D}(B) & \mathcal{D}(A \leftrightarrow B) &= \mathcal{D}(A) \leftrightarrow \mathcal{D}(B) \\ \mathcal{D}((\exists x)A) &= \bigvee\{\mathcal{D}(A_x[\mathbf{d}]) \mid \mathbf{d} \in D\} \end{aligned}$$

where \neg and \oplus are Łukasiewicz negation and disjunction defined by $\neg a = 1 - a$ and $a \oplus b = 1 \wedge (a + b)$, respectively.

If $A(x_1, \dots, x_n)$ is not a closed formula, an *evaluation* of its free variables x_1, \dots, x_n is first defined such that $e(x_1) = d_1, \dots, e(x_n) = d_n$. Then, the interpretation of A is the interpretation of $A_{x_1, \dots, x_n}[\mathbf{d}_1, \dots, \mathbf{d}_n]$, which is a closed formula.

Definition 3 [7] *Let $X \in F_J$ be a fuzzy set of formulae. Then the fuzzy set of its semantic consequences is the following membership function:*

$$\mathcal{C}^{sem}(X)(A) = \bigwedge\{\mathcal{D}(A) \mid \text{for all structure } \mathcal{D}, X \leq \mathcal{D}\}. \quad (3)$$

A formula A is an *a-tautology* (tautology in the degree a) if $a = \mathcal{C}^{sem}(\emptyset)(A)$, and it is denoted by $\models_a A$. If $a = 1$, it is simply written by $\models A$, and A is called a *tautology*.

The following lemma gives simple rules how to verify tautologies in FLn.

Lemma 1 [7] *Let A, B be formulae in the language J .*

- (a) $\models A \rightarrow B$ iff $\mathcal{D}(A) \leq \mathcal{D}(B)$ holds for every structure \mathcal{D} for the language J .
- (b) $\models A \leftrightarrow B$ iff $\mathcal{D}(A) = \mathcal{D}(B)$ holds for every structure \mathcal{D} for the language J .

Definition 4 [7] *Let (R1) $A \rightarrow (B \rightarrow A)$; (R2) $(A \rightarrow B) \rightarrow ((B \rightarrow C) \rightarrow (A \rightarrow C))$;*

(R3) $(\neg B \rightarrow \neg A) \rightarrow (A \rightarrow B)$; (R4) $((A \rightarrow B) \rightarrow B) \rightarrow ((B \rightarrow A) \rightarrow A)$;

(B1) $(\bar{a} \rightarrow \bar{b}) \leftrightarrow \overline{(a \Rightarrow b)}$, where $\overline{(a \Rightarrow b)}$ denotes the logical constant for the value $a \Rightarrow b$ when a and b are given. This is called book-keeping axiom;

(T1) $(\forall x)A \rightarrow A_x[t]$ for any substitutable term t . This is called substitution axiom;

(T2) $(\forall x)(A \rightarrow B) \rightarrow (A \rightarrow (\forall x)B)$ provided that x is not free in A .

Using Lemma 1, it can be verified that (R1)-(R4), (B1) and (T1)-(T2) are (1-)tautologies.

The fuzzy set LAx of *logical axioms* of FLn is as follows: $LAx(F) = 1$ if F is one of the forms (R1)-(R4), (B1) and (T1)-(T2); $LAx(F) = a$ if $F = \bar{a}$; and $LAx(F) = 0$ otherwise.

Definition 5 [7] *A fuzzy theory (or theory for short) T in the language J of FLn is a triple $T = \langle LAx, SAx, R \rangle$, where LAx is the fuzzy set of logical axioms, $SAx \in F_J$ is a fuzzy set of special axioms, and R is the set of inference rules.*

A theory can be viewed as a fuzzy set $T = \mathcal{C}^{syn}(LAx \cup SAx) \in F_J$.

Definition 6 [7] *Let T be a theory and $A \in F_J$ a formula.*

(i) *If $\mathcal{C}^{syn}(LAx \cup SAx)(A) = a$, it is denoted by $T \vdash_a A$, and A is said to be a theorem or provable in the degree a in T . The value a is called the provability degree of A over T .*

(ii) *If $\mathcal{C}^{sem}(LAx \cup SAx)(A) = a$, it is denoted by $T \models_a A$, and A is said to be true in the degree a in T . The value a is called the truth degree of A over T .*

(iii) Let \mathcal{D} be a truth valuation of formulae. Then, it is a model of T , denoted $\mathcal{D} \models T$, if $Sax(A) \leq \mathcal{D}(A)$ holds for all formulae $A \in F_J$.

Therefore, Theorem 1 can be restated as follows:

$$T \vdash_a A \text{ iff } a = \bigvee \{Val(w) \mid w \text{ is a proof of } A \text{ from } LAx \cup Sax\} \quad (4)$$

Also, due to the assumption made on LAx, we have $LAx(A) \leq \mathcal{D}(A)$ holds for every truth valuation \mathcal{D} of formulae. Thus,

$$T \models_a A \text{ iff } a = \bigwedge \{\mathcal{D}(A) \mid \mathcal{D} \models T\}. \quad (5)$$

Definition 7 [7] *A theory T is contradictory if there exists a formula A , and there are proofs w_A and $w_{\neg A}$ of A and $\neg A$ from T , respectively, such that $Val(w_A) \otimes Val(w_{\neg A}) > 0$. Otherwise, it is consistent.*

Theorem 2 [7] *A fuzzy theory T is consistent iff it has a model.*

Theorem 3 (Completeness) [7] *$T \vdash_a A$ iff $T \models_a A$ holds for every formula $A \in F_J$ and every consistent fuzzy theory T .*

This means that the provability degree of A in T coincides with its truth degree over T . This is usually referred to as the *Pavelka-style completeness* [9, 8].

3. FUZZY LOGIC IN NARROW SENSE WITH HEDGES

In order to provide a foundation for a computational approach to human reasoning in the presence of vagueness, imprecision, and uncertainty, fuzzy logic should have the ability to deal with linguistic hedges, which play a very important role in the modification of fuzzy predicates. Therefore, in this section, we will extend FLn with hedges connectives in order to model human knowledge and reasoning. In addition to extending the language and the definition of formulae, new logical axioms characterizing properties of the new connectives are added. One of the most important properties should be preservation of the logical equivalence.

Definition 8 [7] *Let $\diamond : L^n \rightarrow L$ be an n -ary operation. It is called logically fitting if it satisfies the following condition: there are natural numbers $k_1 > 0, \dots, k_n > 0$ such that*

$$(a_1 \Leftrightarrow b_1)^{k_1} \otimes \dots \otimes (a_n \Leftrightarrow b_n)^{k_n} \leq \diamond(a_1, \dots, a_n) \Leftrightarrow \diamond(b_1, \dots, b_n)$$

holds for all $a_1, \dots, a_n, b_1, \dots, b_n \in L$, and the power is taken w.r.t. the operation \otimes , e.g.,

$$(a_1 \Leftrightarrow b_1)^{k_1} = \underbrace{(a_1 \Leftrightarrow b_1) \otimes \dots \otimes (a_1 \Leftrightarrow b_1)}_{k_1\text{-times}}$$

Hence, logically fitting operations preserve the logical equivalence. It can be proved that all the basic operations $\vee, \wedge, \otimes, \Rightarrow$ are logically fitting, and any composite operation obtained from logically fitting operations is also logically fitting.

A connective is *logically fitting* if it is assigned a logically fitting truth function (operation).

3.1. FLN WITH MANY HEDGES

In this subsection, FLn is extended with many hedges, in which each hedge does not have any dual one. To ease the presentation, we let s_0, d_0 denote the identity connective, i.e., for all formula A , $A \equiv s_0 A \equiv d_0 A$, and their truth functions s_0^\bullet and d_0^\bullet are the identity.

Definition 9 (FLn with many hedges) *On the syntactic aspect, FLn is extended as follows (where p, q are positive integers):*

(i) *The language J is extended into a language J_h by a finite set $\mathcal{H} = \{s_1, \dots, s_p, d_1, \dots, d_q\}$ of additional unary connectives, where s_i 's are truth-stressing hedges, and d_j 's are truth-depressing ones.*

(ii) *The definition of formulae is extended by adding the following: If A is a formula and $h \in \mathcal{H}$, hA is a formula.*

(iii) *The fuzzy set LAx of logical axioms is extended by the following axioms:*

$$1/(A \rightarrow B) \rightarrow (hA \rightarrow hB), \text{ for all } h \in \mathcal{H} \quad (6)$$

$$1/s_i A \rightarrow s_{i-1} A, \text{ for } i = 1, \dots, p \quad (7)$$

$$1/s_p \bar{1} \quad (8)$$

$$1/d_{j-1} A \rightarrow d_j A, \text{ for } j = 1, \dots, q \quad (9)$$

$$1/\neg d_q \bar{0} \quad (10)$$

Axiom (6) states that if A implies B , then *very* (resp., *slightly*) A implies *very* (resp., *slightly*) B . Axiom (8) (resp., (10)) says that the truth function s_p^\bullet (resp., d_q^\bullet) preserves 1 (resp., 0). Axiom (7) (resp., (9)) expresses that s_i (resp., d_j) modifies truth more than s_{i-1} (resp., d_{j-1}), for $i = 2, \dots, p$ (resp., $j = 2, \dots, q$). For example, *slightly* (resp., *very*) modifies truth more than *rather* (resp., *highly*) since *slightly true* < *rather true* < *true* (resp., *true* < *highly true* < *very true*). Also, for instance, let $A = \text{young}(x)$, $s_1 = \text{highly}$, $s_2 = \text{very}$, $d_1 = \text{rather}$, $d_2 = \text{slightly}$, by (7), we have *very young*(x) \rightarrow *highly young*(x) and *highly young*(x) \rightarrow *young*(x). Moreover, by (9), we have *young*(x) \rightarrow *rather young*(x) and *rather young*(x) \rightarrow *slightly young*(x). Therefore, we have:

$$\text{very young}(x) \rightarrow \text{highly young}(x) \rightarrow \text{young}(x) \rightarrow \text{rather young}(x) \rightarrow \text{slightly young}(x)$$

This is also in accordance with fuzzy-set-based interpretations of hedges [10, 11, 12], in which *very* and *highly* are called *intensifying modifiers* while *rather* and *slightly* are called *weakening modifiers*, and they satisfy the so-called *semantic entailment* property:

$$x \text{ is } \text{very } A \Rightarrow x \text{ is } \text{highly } A \Rightarrow x \text{ is } A \Rightarrow x \text{ is } \text{rather } A \Rightarrow x \text{ is } \text{slightly } A$$

where A is a fuzzy predicate. Note that, according to [10], if A is represented by a fuzzy set with a membership function $\mu_A(x)$, the membership function of *very* A can be $\mu_{\text{very } A}(x) = \mu_A^2(x)$. Since for all x , $0 \leq \mu_A(x) \leq 1$, we have for all x , $\mu_{\text{very } A}(x) \leq \mu_A(x)$. By fuzzy set inclusion, it is said that *very* A is included by A , denoted *very* $A \subseteq A$. Since the degree of membership of x to A is regarded as the truth value of “ x is A ”, the truth value of “ x is *very* A ” is less than or equal to that of “ x is A ”.

Theorem 4 *For every hedge connective $h \in \mathcal{H}$, its truth function h^\bullet is non-decreasing and preserves 0 and 1.*

Proof. By (6), for all structure \mathcal{D} of the language J_h , we have $\mathcal{D}(A \rightarrow B) \leq \mathcal{D}(hA \rightarrow hB)$. Hence, $\mathcal{D}(A) \Rightarrow \mathcal{D}(B) \leq h^\bullet(\mathcal{D}(A)) \Rightarrow h^\bullet(\mathcal{D}(B))$. Let $a, b \in L$ and $a \leq b$. Since $\mathcal{D}(\bar{a}) \Rightarrow \mathcal{D}(\bar{b}) = a \Rightarrow b = 1$, we have $h^\bullet(\mathcal{D}(\bar{a})) \Rightarrow h^\bullet(\mathcal{D}(\bar{b})) = 1$, i.e., $h^\bullet(a) \leq h^\bullet(b)$. Therefore, the truth function h^\bullet of any hedge connective $h \in \mathcal{H}$ is non-decreasing.

By (8), we have $s_p^\bullet(1) = 1$. Using (7) and taking $A = \bar{1}$, $i = p$, we have, for all structure \mathcal{D} of the language J_h , $\mathcal{D}(s_p \bar{1}) \leq \mathcal{D}(s_{p-1} \bar{1})$, i.e., $1 = s_p^\bullet(1) \leq s_{p-1}^\bullet(1)$. Hence, $s_{p-1}^\bullet(1) = 1$.

Similarly, we have $s_i^\bullet(1) = 1$ for all $i = p-2, \dots, 1$. Also, using (7) and taking $A = \bar{0}, i = 1$, we have, for all structure \mathcal{D} of the language J_h , $\mathcal{D}(s_1\bar{0}) \leq \mathcal{D}(s_0\bar{0})$, i.e., $s_1^\bullet(0) \leq s_0^\bullet(0) = 0$. Hence, $s_1^\bullet(0) = 0$. Similarly, we have $s_i^\bullet(0) = 0$ for all $i = 2, \dots, p$. Therefore, all s_i^\bullet preserve 0 and 1.

By (10), we have $d_q^\bullet(0) = 0$. Using (9) and taking $A = \bar{0}, j = q$, we have, for all structure \mathcal{D} of the language J_h , $\mathcal{D}(d_{q-1}\bar{0}) \leq \mathcal{D}(d_q\bar{0})$, i.e., $d_{q-1}^\bullet(0) \leq d_q^\bullet(0) = 0$. Hence, $d_{q-1}^\bullet(0) = 0$. Similarly, we have $d_j^\bullet(0) = 0$ for all $j = q-2, \dots, 1$. Also, using (9) and taking $A = \bar{1}, j = 1$, we have, for all structure \mathcal{D} of the language J_h , $\mathcal{D}(d_0\bar{1}) \leq \mathcal{D}(d_1\bar{1})$, i.e., $1 = d_0^\bullet(1) \leq d_1^\bullet(1)$. Hence, $d_1^\bullet(1) = 1$. Similarly, we have $d_j^\bullet(1) = 1$ for all $j = 2, \dots, q$. Therefore, all d_j^\bullet preserve 0 and 1. \square

Theorem 5 For every truth-stresser $s_i \in \mathcal{H}, i = \overline{1, p}$, its truth function s_i^\bullet is subdiagonal.

Proof. For any $a \in L$, using (7) and taking $A = \bar{a}, i = 1$, we have, for all structure \mathcal{D} of the language J_h , $s_1^\bullet(a) = \mathcal{D}(s_1\bar{a}) \leq \mathcal{D}(s_0\bar{a}) = s_0^\bullet(a) = a$. Thus, $s_1^\bullet(a) \leq a$ for all $a \in L$, i.e., s_1^\bullet is subdiagonal. Again, using (7) and taking $A = \bar{a}, i = 2$, we have $s_2^\bullet(a) = \mathcal{D}(s_2\bar{a}) \leq \mathcal{D}(s_1\bar{a}) = s_1^\bullet(a) \leq a$. Similarly, s_i^\bullet is subdiagonal for all $i = 3, \dots, p$. \square

Theorem 6 For every truth-depresser $d_j \in \mathcal{H}, j = \overline{1, q}$, its truth function d_j^\bullet is superdiagonal.

Proof. For any $a \in L$, using (9) and taking $A = \bar{a}, j = 1$, we have, for all structure \mathcal{D} of the language J_h , $a = d_0^\bullet(a) = \mathcal{D}(d_0\bar{a}) \leq \mathcal{D}(d_1\bar{a}) = d_1^\bullet(a)$. Thus, $d_1^\bullet(a) \geq a$ for all $a \in L$, i.e., d_1^\bullet is superdiagonal. Again, using (9) and taking $A = \bar{a}, j = 2$, we have $a \leq d_1^\bullet(a) = \mathcal{D}(d_1\bar{a}) \leq \mathcal{D}(d_2\bar{a}) = d_2^\bullet(a)$. Similarly, d_j^\bullet is superdiagonal for all $j = 3, \dots, q$. \square

The following theorem shows that the additional hedge connectives are logically fitting.

Theorem 7 For every hedge connective $h \in \mathcal{H}$, its truth function h^\bullet is logically fitting.

Proof. Given $a, b \in L$, using (6) and taking $A = \bar{a}, B = \bar{b}$, we have, for all structure \mathcal{D} of the language J_h , $\mathcal{D}(\bar{a} \rightarrow \bar{b}) \leq \mathcal{D}(h\bar{a} \rightarrow h\bar{b})$. Hence, $a \Rightarrow b \leq h^\bullet(a) \Rightarrow h^\bullet(b)$. Again, using (6) and taking $A = \bar{b}, B = \bar{a}$, we have $b \Rightarrow a \leq h^\bullet(b) \Rightarrow h^\bullet(a)$. Therefore, $a \Leftrightarrow b = (a \Rightarrow b) \wedge (a \Leftarrow b) \leq (h^\bullet(a) \Rightarrow h^\bullet(b)) \wedge (h^\bullet(a) \Leftarrow h^\bullet(b)) = h^\bullet(a) \Leftrightarrow h^\bullet(b)$, i.e., h^\bullet is logically fitting according to Definition 8. \square

We can also say that all the hedge connectives $h \in \mathcal{H}$ are logically fitting.

Since it is shown in [7] that introducing logically fitting operations have no influence on the algebraic proof of the completeness theorem of FLn (Theorem 3), we have the following completeness theorem for FLn with many hedges.

Theorem 8 Let T be a consistent fuzzy theory in the extended language J_h . Then

$$T \vdash_a A \text{ iff } T \models_a A$$

holds for every formula $A \in F_{J_h}$.

That means FLn with many hedges also has the Pavelka-style completeness.

3.2. FLN WITH MANY DUAL HEDGES

It can be observed that each hedge can have a dual one, e.g., *slightly* and *rather* can be seen as a dual hedge of *very* and *highly*, respectively. Thus, there might be axioms expressing dual relations of hedges in addition to axioms expressing their comparative truth modification strength.

In this subsection, FLn is extended with many dual hedges, in which each hedge has its own dual one.

Definition 10 (FLn with many dual hedges) *On the syntactic aspect, FLn is extended as follows (where n is a positive integer):*

(i) *The language J is extended into a language J_{dh} by a finite set $\mathcal{H} = \{s_1, \dots, s_n, d_1, \dots, d_n\}$ of additional unary connectives, where s_i 's are truth-stressing hedges, and d_i 's are truth-depressing ones.*

(ii) *The definition of formulae is extended by adding the following: If A is a formula and $h \in \mathcal{H}$, hA is a formula.*

(iii) *The fuzzy set LAx of logical axioms is extended by the following axioms:*

$$1/(A \rightarrow B) \rightarrow (hA \rightarrow hB), \text{ for all } h \in \mathcal{H} \quad (11)$$

$$1/s_i A \rightarrow s_{i-1} A, \text{ for } i = 1, \dots, n \quad (12)$$

$$1/s_n \bar{1} \quad (13)$$

$$1/d_{i-1} A \rightarrow d_i A, \text{ for } i = 1, \dots, n \quad (14)$$

$$1/d_i A \rightarrow \neg s_i \neg A \quad (15)$$

The main differences between the fuzzy set LAx of FLn with many dual hedges and that of FLn with many hedges are that we have the axiom (15) expressing the duality between hedges s_i and d_i , and we do not need an axiom similar to (10).

Concerning Axiom (15), for instance, let $A = \text{young}(x)$, $s_i = \text{very}$, $d_i = \text{slightly}$, then it means “*slightly young* implies not *very old*”. Using (15) and taking $A = \bar{a}$ for any $a \in L$, we have $\mathcal{D}(d_i \bar{a}) \leq \mathcal{D}(\neg s_i \neg \bar{a})$ for all structure \mathcal{D} of the language J_{dh} . Thus, $d_i^\bullet(a) \leq 1 - s_i^\bullet(1 - a)$, then $s_i^\bullet(1 - a) \leq 1 - d_i^\bullet(a)$. Let $b = 1 - a = \neg a$, hence $a = 1 - b = \neg b$. We have $s_i^\bullet(b) \leq 1 - d_i^\bullet(\neg b)$. Let B be a formula whose truth valuation is b , i.e., $\mathcal{D}(B) = b$. We have $\mathcal{D}(s_i B) = s_i^\bullet(b) \leq 1 - d_i^\bullet(\neg b) = \mathcal{D}(\neg d_i \neg B)$. Therefore, we have a tautology $1/s_i B \rightarrow \neg d_i \neg B$. This means, for instance, “*very old* implies not *slightly young*” as well.

Since axioms (12) and (13) are respectively similar to (7) and (8), we also have that all $s_i^\bullet, i = \overline{1, n}$, preserve 1. Using (15) and taking $A = \bar{0}$, we have $\mathcal{D}(d_i \bar{0}) \leq \mathcal{D}(\neg s_i \neg \bar{0})$ for all structure \mathcal{D} of the language J_{dh} . Hence, $d_i^\bullet(0) \leq 1 - s_i^\bullet(1) = 0$. Therefore, $d_i^\bullet(0) = 0$ for all $i = \overline{1, n}$. That means we do not need an axiom similar to (10).

Now, given a hedge function s_n^\bullet , which is non-decreasing, subdiagonal, and preserves 0 and 1, the boundaries for the other hedge functions are one by one determined as follows. Using (12) and taking $A = \bar{a}$ for any $a \in L$ and $i = n$, we have $s_n^\bullet(a) \leq s_{n-1}^\bullet(a)$. Thus, the lower boundary of $s_{n-1}^\bullet(a)$ is $s_n^\bullet(a)$, and its upper boundary is a . Similarly, we have $s_{n-1}^\bullet(a) \leq s_{n-2}^\bullet(a) \leq a$, and finally, $s_2^\bullet(a) \leq s_1^\bullet(a) \leq a$. Then, by (15), we have $a \leq d_i^\bullet(a) \leq \neg s_i^\bullet(\neg a)$ for all $i = \overline{1, n}$, thus, a and $\neg s_1^\bullet(\neg a)$ are the lower boundary and upper boundary of $d_1^\bullet(a)$, respectively (note that since $s_1^\bullet(1 - a) \leq 1 - a$, we have $\neg s_1^\bullet(\neg a) = 1 - s_1^\bullet(1 - a) \geq 1 - (1 - a) = a$). Using (14) and taking $A = \bar{a}, i = 2$, we have $d_1^\bullet(a) \leq d_2^\bullet(a)$, thus, $d_1^\bullet(a)$ and $\neg s_2^\bullet(\neg a)$ are the lower boundary and upper boundary of $d_2^\bullet(a)$, respectively. Similarly, we have $d_{i-1}^\bullet(a)$ and $\neg s_i^\bullet(\neg a)$ are the lower boundary and upper boundary of $d_i^\bullet(a)$, respectively, for all $i = \overline{3, n}$. In summary, the boundaries are shown in Table 1.

We also have the following completeness theorem for FLn with many dual hedges.

Theorem 9 *Let T be a consistent fuzzy theory in the extended language J_{dh} . Then*

$$T \vdash_a A \text{ iff } T \models_a A$$

Table 1: Boundaries of hedge functions

Hedge function	Lower boundary	Upper boundary
$s_{n-1}^\bullet(x)$	$s_n^\bullet(x)$	x
\dots		
$s_1^\bullet(x)$	$s_2^\bullet(x)$	x
$d_1^\bullet(x)$	x	$-s_1^\bullet(-x)$
$d_2^\bullet(x)$	$d_1^\bullet(x)$	$-s_2^\bullet(-x)$
\dots		
$d_n^\bullet(x)$	$d_{n-1}^\bullet(x)$	$-s_n^\bullet(-x)$

holds for every formula $A \in F_{J_{dh}}$.

It can be seen that in a case when we want to extend the above logic with one truth-stressing (resp., truth-depressing) hedge without a dual one, we only need to add axioms expressing its relations to the existing truth-stressing (resp., truth-depressing) hedges according to their comparative truth modification strength.

4. CONCLUSION

In this paper, we extend fuzzy logic in narrow sense with many hedge connectives in order to provide a foundation for human knowledge representation and reasoning. In fuzzy logic in narrow sense, both syntax and semantics are evaluated by degrees in $[0,1]$. The graded approach to syntax can be seen as an elegant and natural generalization of classical logic for inference under vagueness since it allows one to explicitly represent and reason with partial truth, i.e., proving partially true conclusions from partially true premises, and it enjoys the Pavelka-style completeness. FLn is extended in two cases: (i) each hedge does not have a dual one, and (ii) each hedge can have its own dual one. In addition to extending the language and the definition of formulae, new logical axioms characterizing properties of the hedge connectives are added. The truth function of a truth-depressing (resp., truth-stressing) hedge connective is a superdiagonal (resp., subdiagonal) non-decreasing function preserving 0 and 1. The resulting logics are shown to have the Pavelka-style completeness.

5. ACKNOWLEDGMENTS

Funding from HUMG under grant number T16-02 is acknowledged.

6. REFERENCES

- [1] P. Hájek, “On very true,” *Fuzzy Sets and Systems*, vol. 124, no. 3, pp. 329–333, 2001.
- [2] V. Vychodil, “Truth-depressing hedges and bl-logic,” *Fuzzy Sets and Systems*, vol. 157, no. 15, pp. 2074–2090, 2006.
- [3] F. Esteva, L. Godo, and C. Noguera, “A logical approach to fuzzy truth hedges,” *Inf. Sci.*, vol. 232, pp. 366–385, 2013.
- [4] V. H. Le, F. Liu, and D. K. Tran, “Mathematical fuzzy logic with many dual hedges,” in *Proceedings of the Fifth Symposium on Information and Communication Technology (SoICT 2014)*, Hanoi, Vietnam, pp. 7–13, 2014.
- [5] V. H. Le and D. K. Tran, “Linguistic logics with hedges,” in *Proceedings of the 2nd International Workshop on Semantic Technologies (IWOST2)*, Bangkok, Thailand, 2015.
- [6] V. H. Le and F. Liu, “Tabulation proof procedures for fuzzy linguistic logic programming,” *Int. J. Approx. Reasoning*, vol. 63, pp. 62–88, 2015.

- [7] V. Novák, I. Perfilieva, and J. Mockor, *Mathematical Principles of Fuzzy Logic*. Dordrecht: Kluwer, 2000.
- [8] P. Hájek, *Metamathematics of Fuzzy Logic*. Dordrecht, The Netherlands: Kluwer, 1998.
- [9] J. Pavelka, “On fuzzy logic i, ii, iii,” *Zeitschrift fur Mathematische Logik Grundlagen Math*, vol. 25, pp. 45–52, 119–134, 447–464, 1979.
- [10] L. A. Zadeh, “A fuzzy-set-theoretic interpretation of linguistic hedges,” *Journal of Cybernetics*, vol. 2, no. 3, pp. 4–34, 1972.
- [11] V.-N. Huynh, T. B. Ho, and Y. Nakamori, “A parametric representation of linguistic hedges in zadeh’s fuzzy logic,” *Int. J. Approx. Reasoning*, vol. 30, no. 3, pp. 203–223, 2002.
- [12] M. D. Cock and E. E. Kerre, “Fuzzy modifiers based on fuzzy relations,” *Inf. Sci.*, vol. 160, no. 1-4, pp. 173–199, 2004.

AUTHOR

Van-Hung Le received a B.Eng. degree in Information Technology from Hanoi University of Science and Technology (formerly, Hanoi University of Technology) in 1995, an M.Sc. degree in Information Technology from Vietnam National University, Hanoi in 2001, and a PhD degree in Computer Science from La Trobe University, Australia in 2010. He is a lecturer in the Faculty of Information Technology at Hanoi University of Mining and Geology. His research interests include Fuzzy Logic, Logic Programming, Soft Computing, and Computational Intelligence.

