Bergm: Bayesian exponential random graph models in R

Alberto Caimo¹ and Nial Friel²

¹Dublin Institute of Technology, Ireland; ²University College Dublin, Ireland

November 27, 2021

1 Introduction

Networks are relational data that can be defined as a collection of nodes interacting with each other and connected in a pairwise fashion. From a statistical point of view, networks are relational data represented as mathematical graphs. A graph consists of a set of n nodes and a set of m edges which define some sort of relationships between pair of nodes called dyads. The connectivity pattern of a graph can be described by an $n \times n$ adjacency matrix y encoding the presence or absence of an edge between node i and j:

$$y_{ij} = \begin{cases} 1, & \text{if } (i,j) \text{ are connected} \\ 0, & \text{otherwise.} \end{cases}$$

Two nodes are adjacent or neighbours if there is an edge between them. If $y_{ij} = y_{ji}, \forall i, j$ then the adjacency matrix is symmetric and the graph is undirected, otherwise the graph is directed and it is often called a digraph. Edges connecting a node to itself (self-loops) are generally not allowed in many applications and will not be considered in this context.

2 Exponential random graph models

Introduced by Holland and Leinhardt (1981) to model individual heterogeneity of nodes and reciprocity of their edges, the family of exponential random graph models (ERGMs) was generalised by Frank and Strauss (1986), Wasserman and Pattison (1996) and Snijders et al. (2006). ERGMs constitute a broad class of network models (see (Robins et al., 2007) for an introduction) that assume that the observed network y can be explained in terms of the relative prevalence of a set of network statistics s(y):

$$p(y|\theta) = \frac{\exp\{\theta^t s(y)\}}{z(\theta)} \tag{1}$$

where the normalising constant $z(\theta)$ is intractable for non trivially-small networks.

Due to the complexity of networks, it is necessary to reduce the information to describe essential properties of the network. Usually this is done via network statistics, a series of counts of sub-graph configurations (e.g., the number of edges, stars, triangles, functions of degree distributions, edgewise shared parters, etc.), catching the relevant information (Snijders et al., 2006).

3 Bayesian inference

In the ERGM context (see (Wasserman and Pattison, 1996) and (Robins et al., 2007)), the posterior distribution of model parameters θ given an observed network y on n nodes maybe written as:

$$p(\theta|y) = \frac{p(y|\theta) \ p(\theta)}{p(y)} = \frac{\exp\{\theta^t s(y)\}}{z(\theta)} \ \frac{p(\theta)}{p(y)},\tag{2}$$

where s(y) is a known vector of sufficient network statistics (Morris et al., 2008), $p(\theta)$ is a prior distribution placed on θ , $z(\theta)$ is the intractable likelihood normalising constant, and p(y) is the model evidence. The presence of the intractable ERGM likelihood implies that the usual suite of standard Bayesian inferential methods, especially standard MCMC tools are not possible in this context. However recent work has shown that the ERGM can be given the full Bayesian treatment as we now outline.

4 The Bergm package for R

The Bergm package (Caimo and Friel, 2014) for R (R Development Core Team, 2011) implements Bayesian analysis for ERGMs (Caimo and Friel, 2011, 2013; Caimo and Mira, 2015; Thiemichen et al., 2016; Bouranis et al., 2015). The package provides a comprehensive framework for Bayesian inference using Markov chain Monte Carlo (MCMC) algorithms. It can also supply graphical Bayesian goodness-of-fit procedures that address the issue of model adequacy.

The package is simple to use and represents an attractive way of analysing network data as it offers the advantage of a complete probabilistic treatment of uncertainty. Bergm is based on the ergm package (Hunter et al., 2008) which is part of the statnet suite of packages (Handcock et al., 2007) and therefore it makes use of the same model set-up and network simulation algorithms. The ergm and Bergm packages complement each other in the sense that ergm implements maximum likelihood-based inference whereas Bergm implements Bayesian inference. The Bergm package has been continually improved in terms of speed performance over the last years and we feel that this package now offers the end-user a feasible option for carrying out Bayesian inference for networks with several thousands of nodes.

5 Approximate exchange algorithm

In order to approximate the posterior distribution $p(\theta|y)$, the Bergm package uses the exchange algorithm described in Section 4.1 of (Caimo and Friel, 2011) to sample from the following distribution:

$$p(\theta', y', \theta|y) \propto p(y|\theta)p(\theta)\epsilon(\theta'|\theta)p(y'|\theta')$$

where $p(y'|\theta')$ is the likelihood on which the simulated data y' are defined and belongs to the same exponential family of densities as $p(y|\theta)$, $\epsilon(\theta'|\theta)$ is any arbitrary proposal distribution for the augmented variable θ' . As we will see in the next section, this proposal distribution is set to be a normal centred at θ .

At each MCMC iteration, the exchange algorithm consists of a Gibbs update of θ' followed by a Gibbs update of y', which is drawn from $p(\cdot|\theta')$ via an MCMC algorithm (Hunter et al., 2008). Then a deterministic exchange or swap from the current state θ to the proposed new parameter θ' . This deterministic proposal is accepted with probability:

$$\min\left(1, \frac{q_{\theta}(y')p(\theta')\epsilon(\theta|\theta')q_{\theta'}(y)}{q_{\theta}(y)p(\theta)\epsilon(\theta'|\theta)q_{\theta'}(y')} \times \frac{z(\theta)z(\theta')}{z(\theta)z(\theta')}\right),$$

where q_{θ} and $q_{\theta'}$ indicate the unnormalised likelihoods with parameter θ and θ' , respectively. Notice that all the normalising constants cancel above and below in the fraction above, in this way avoiding the need to calculate the intractable normalising constant.

The approximate exchange algorithm is implemented by the **bergm** function in the following way:

for
$$i = 1, \ldots, N$$

- 1. generate θ' from $\epsilon(\cdot|\theta)$
- 2. simulate $y' \ \text{from} \ p(\cdot | \theta')$
- 3. update heta
 ightarrow heta' (log) probability:

$$\min\left(0, \left[\theta - \theta'\right]^t \left[s(y') - s(y)\right] + \log\left[\frac{p(\theta')}{p(\theta)}\right]\right)$$

end for

where s(y) is the observed vector of network statistics and s(y') is the simulated vector of network statistics. Step 2. above requires a draw from the ERGM likelihood and perfect sampling in principle is a possibility, however practically this is out of reach as no such sampler has yet been developed. Therefore the pragmatic approach we take is to run a Gibbs sampler for **aux.iters** iterations targetting $p(\cdot|\theta')$. In order to improve mixing a parallel adaptive direction sampler (ADS) approach (Gilks et al., 1994; Roberts and Gilks, 1994) is considered as the default procedure.

To illustrate the inferential procedure, we fit a 4-dimensional ERGM to the Faux Mesa High School network data (Resnick et al., 1997) including uniform homophily between students with the same 'grade' (nodematch('Grade')), and statistics capturing the degree distribution (gwdegree) and transitivity effect (gwesp):



+ nodematch('Grade') + + gwdegree(0.2, fixed = TRUE) + + gwesp(0.2, fixed = TRUE)	>	model	<- y î	~	edges +	
+ gwdegree(0.2, fixed = TRUE) + + gwesp(0.2, fixed = TRUE)	+				<pre>nodematch('Grade') +</pre>	
+ gwesp(0.2, fixed = TRUE)	+				<pre>gwdegree(0.2, fixed = TRUE) +</pre>	
	+				<pre>gwesp(0.2, fixed = TRUE)</pre>	

and we use the **bergm** function with 20,000 auxiliary iterations for network simulation and 6 MCMC chains for the ADS procedure consisting of 2,000 main iterations each:

The estimation took about 200 seconds. A summary of the MCMC results is available via the bergm.output command:

> bergm.output(post)

 Mean
 SD
 Naive
 SE

 theta1 (edges)
 -6.4539945
 0.2269798
 0.002072032

theta2	(nodematch.Grade)	2.0653066	0.1562896	0.001426723		
theta3	(gwdegree)	0.1555102	0.2156994	0.001969057		
theta4	(gwesp.fixed.0.2)	1.6045295	0.1624254	0.001482734		
		Time-series	s SE			
theta1	(edges)	0.013682	2987			
theta2	(nodematch.Grade)	0.009303	3603			
theta3	(gwdegree)	0.013919	9679			
theta4	(gwesp.fixed.0.2)	0.009959682				
		2.5%	25%	50%		
theta1	(edges)	-6.8988256	-6.6003492	2 -6.4532048		
theta2	(nodematch.Grade)	1.7879473	1.9557575	5 2.0537140		
theta3	(gwdegree)	-0.2825274	0.0158655	0.1618899		
theta4	(gwesp.fixed.0.2)	1.2841624	1.4983524	1.6031113		
		75%	97.5%	0		
theta1	(edges)	-6.3043630	-6.0255210)		
theta2	(nodematch.Grade)	2.1665645	2.3952768	3		
theta3	(gwdegree)	0.3118872	0.5568012	2		
theta4	(gwesp.fixed.0.2)	1.7099524	1.9425482	2		

Acceptance rate: 0.1965833

Density and trace plots are produced automatically by the bergm.output function:



Posterior predictive goodness-of-fit diagnostics plots are available via the bgof command, as shown in the figure below.

```
> bgof(bergm.post,
+ aux.iters = 20000,
+ n.deg = 14,
+ n.dist = 15,
+ n.esp = 10)
```

Bayesian goodness-of-fit diagnostics



The plots in the figure indicate a very good fit of the model in terms of a higher-level network statistics in the data.

6 Pseudo-posterior calibration

An alternative approach to Bayesian inference for ERGMs has been proposed by Bouranis et al. (2015) based on replacing the intractable ERGM likelihood with a tractable pseudo-likelihood approximation. This results in a so-called pseudo-posterior distribution for which it is straightforward to sample from using the usual MCMC toolbox, for example. However it is well understood that Bayesian inference based on the pseudolikelihood can yield poor estimation and this motivated (Bouranis et al., 2015) to develop an approach which allows one to correct or calibrate a sample from such a pseudo-posterior distribution so that it is approximately distributed from the target posterior distribution. This is achieved by estimating the maximum a posteriori (MAP) of the posterior distribution and also estimating the Hessian of the posterior distribution at the MAP. Both of these quantites can then be used to define an affine transformation of the pseudo-posterior distribution to one that is approximately distributed as the posterior distribution.

The pseudo-posterior calibration approach can be carried out using the calibrate.bergm function:

```
> cbergm.post <- calibrate.bergm(model,
+ iters = 1000,
+ aux.iters = 20000,
+ noisy.nsim = 100,
+ noisy.thin = 1000,
+ mcmc = 10000)
```

The estimation took about 80 seconds and the MCMC output can be analysed by using the bergm.output function.

In the plots below, we see that the posterior estimates from the calibrate.bergm function is in good agreement with that corresponding to the bergm function:



7 More information

The Bergm package is available on the CRAN at: https://CRAN.R-project.org/package=Bergm, and also on GitHub at: https://github.com/acaimo/Bergm.

References

- Bouranis, L., Friel, N., and Maire, F. (2015), "Bayesian inference for misspecified exponential random graph models," arXiv preprint arXiv:1510.00934.
- Caimo, A. and Friel, N. (2011), "Bayesian Inference for Exponential Random Graph Models," Social Networks, 33, 41 55.
- Caimo, A. and Friel, N. (2013), "Bayesian model selection for exponential random graph models," Social Networks, 35, 11 – 24.
- Caimo, A. and Friel, N. (2014), "Bergm: Bayesian Exponential Random Graphs in R," Journal of Statistical Software, 61, 1–25.
- Caimo, A. and Mira, A. (2015), "Efficient computational strategies for doubly intractable problems with applications to Bayesian social networks," *Statistics and Computing*, 25, 113–125.
- Frank, O. and Strauss, D. (1986), "Markov Graphs," Journal of the American Statistical Association, 81, 832–842.
- Gilks, W. R., Roberts, G. O., and George, E. I. (1994), "Adaptive Direction Sampling," *Statistician*, 43, 179–189.

- Handcock, M. S., Hunter, D. R., Butts, C. T., Goodreau, S. M., and Morris, M. (2007), "statnet: Software Tools for the Representation, Visualization, Analysis and Simulation of Network Data," *Journal of Statistical Software*, 24, 1–11.
- Holland, P. W. and Leinhardt, S. (1981), "An exponential family of probability distributions for directed graphs (with discussion)," *Journal of the American Statistical Association*, 76, 33–65.
- Hunter, D. R., Handcock, M. S., Butts, C. T., Goodreau, S. M., and Morris, M. (2008), "ergm: A Package to Fit, Simulate and Diagnose Exponential-Family Models for Networks," *Journal of Statistical Software*, 24, 1–29.
- Morris, M., Handcock, M. S., and Hunter, D. R. (2008), "Specification of exponential-family random graph models: terms and computational aspects," *Journal of statistical software*, 24, 15–48.
- R Development Core Team (2011), R: A Language and Environment for Statistical Computing, R Foundation for Statistical Computing, Vienna, Austria.
- Resnick, M. D., Bearman, P. S., Blum, R. W., Bauman, K. E., Harris, K. M., Jones, J., Tabor, J., Beuhring, T., Sieving, R. E., and Shew, M. (1997), "Protecting adolescents from harm: findings from the National Longitudinal Study on Adolescent Health," Jama, 278, 823–832.
- Roberts, G. O. and Gilks, W. R. (1994), "Convergence of Adaptive Direction Sampling," Journal of Multivariate Analysis, 49, 287–298.
- Robins, G., Pattison, P., Kalish, Y., and Lusher, D. (2007), "An Introduction to Exponential Random Graph Models for Social Networks," Social Networks, 29, 169–348.
- Snijders, T. A. B., Pattison, P. E., Robins, G. L., and S., H. M. (2006), "New Specifications for Exponential Random Graph Models," *Sociological Methodology*, 36, 99–153.
- Thiemichen, S., Friel, N., Caimo, A., and Kauermann, G. (2016), "Bayesian exponential random graph models with nodal random effects," *Social Networks*, 46, 11–28.
- Wasserman, S. and Pattison, P. (1996), "Logit Models and Logistic Regression for Social Networks: I. An Introduction to Markov graphs and p^{*}," *Psycometrica*, 61, 401–425.