

RESEARCH ARTICLE**Vertex Nomination via Seeded Graph Matching**Heather G. Patsolic¹ | Youngser Park² | Vince Lyzinski³ | Carey E. Priebe^{*1,2}¹Dept. of Applied Mathematics and Statistics, The Johns Hopkins University, Maryland, USA²Center for Imaging Science, The Johns Hopkins University, Maryland, USA³Dept. of Mathematics, University of Maryland, College Park, Maryland, USA**Correspondence***Carey E. Priebe,
Whitehead Hall, 3400 N Charles St.
Baltimore, MD 21218
Email: cep@jhu.edu**Summary**

Consider two networks on overlapping, non-identical vertex sets. Given vertices of interest in the first network, we seek to identify the corresponding vertices, if any exist, in the second network. While in moderately sized networks graph matching methods can be applied directly to recover the missing correspondences, herein we present a principled methodology appropriate for situations in which the networks are too large/noisy for brute-force graph matching. Our methodology identifies vertices in a local neighborhood of the vertices of interest in the first network that have verifiable corresponding vertices in the second network. Leveraging these known correspondences, referred to as seeds, we match the induced subgraphs in each network generated by the neighborhoods of these verified seeds, and rank the vertices of the second network in terms of the most likely matches to the original vertices of interest. We demonstrate the applicability of our methodology through simulations and real data examples.

KEYWORDS:

vertex nomination, graph matching, seeded graph matching, graph inference, graph mining, stochastic block model

1 | INTRODUCTION AND BACKGROUND

In this paper, we address the problem of nominating vertices across a pair of networks: Given vertices of interest (VOIs) in a network $G = (V, E)$, our task is to identify the corresponding vertices of interest, if they exist, in a second network $G' = (V', E')$. Our methods will leverage vertices in the neighborhood of the VOIs in G that have verifiable matches in G' to (ideally) create local neighborhoods of the VOIs in both G and G' . These neighborhoods are then soft-matched (see Algorithm 1, adapted here from [11]) across networks, yielding a nomination list for each VOI in G ; i.e., a ranking of the vertices in the local neighborhood of the seeds in G' , ideally with the corresponding VOI's in G' concentrating at the top of the list. While global methods can (and have been) applied to identify the VOI's in G' directly, performance of these methods can suffer from the noise induced by vertices without correspondences across networks [28]. Localization is a prominent tool used across various fields such as machine learning (see for example [41, 53] on using locality based anomaly detection in time series of graphs and [16] on localized multiple kernel learning), pattern recognition (this includes clustering algorithms which have been using localization for many years — for example k -nearest neighbor based classification rules — see for example [47, 15, 23, 37, 8]), and object recognition (see for example [46] on using convolutional networks for localization and object boundary detection and [4] on local algorithms for geometric object recognition). Inspired by the many successes localization has seen in other fields of research, we bring the concept of localization to the fore-front of network alignment. Our methods are inherently local, leveraging recent

⁰Abbreviations: VN, vertex nomination; SGM, seeded graph matching; VOI, vertex of interest

advancements in both graph matching [11, 29] and vertex nomination [7, 12] to nominate across essentially arbitrarily large networks.

Formally, suppose we are given two networks $G = (V, E)$ and $G' = (V', E')$ on overlapping but not necessarily identical vertex sets V and V' respectively. For simplicity, we will presently restrict our attention to the case of a single VOI in G (as the case of multiple VOIs is an immediate extension of our methodology for a single VOI), and we write

$$V = \{x\} \cup S \cup W \cup J, \quad V' = \{x'\} \cup S' \cup W' \cup J',$$

where x and x' represent the VOI in G and G' resp.; S and S' represent the seeded vertices across networks—those vertices that appear in both vertex sets whose correspondence across networks (i.e., the seeding $S \leftrightarrow S'$) is known a priori—and necessarily satisfy $s := |S| = |S'|$; W and W' are the shared non-seed vertices—those vertices that appear in both vertex sets whose correspondence across networks is unknown a priori—with $|W| = |W'| = n$; and J and J' are the unshared vertices—those vertices that appear in only one or the other vertex set without correspondences across networks—with $|J| = m$ and $|J'| = m'$. Thus, we can write

$$\eta := |V| = 1 + s + n + m, \quad \text{and} \quad \eta' = |V'| = 1 + s + n + m'.$$

While the correspondence between vertices in W and W' is unknown a priori, we will further assume that it is unknown which vertices in $G \setminus \{x, S\}$ are in W versus J , as are the values of n, m and m' . Our inference task is to identify $x' \in V' \setminus S'$ (i.e., the corresponding VOI in G') using only the knowledge of the graph structures and the correspondence $S \leftrightarrow S'$. For the purposes of this paper, we will assume that the corresponding vertex x' *does* exist in G' , else our task is impossible. Our goal will be to nominate vertices in G' in a principled manner so that the true match is high in the nomination list, thus saving the end-user time in searching for this true match. While this core-junk network framework has appeared often in the literature (see, for example, [22]), herein we will consider a more general random graph model that allows for heterogeneity in vertex degree and behavior (see, Section 3).

Our approach to this inference task lies on the boundary between *Graph Matching* and *Vertex Nomination*. Stated simply, the formulation of the graph matching problem (GMP) considered herein seeks to align the vertices in two networks so as to minimize the number of induced edge disagreements between the aligned networks. Graph matching has been extensively studied in the literature (for an excellent survey of the literature, see [5, 13]) with applications across various fields including pattern recognition (see, for example, [2, 54, 60]), computer vision (see, for example, [59, 26, 55]), and biology (see, for example, [57, 36, 24]), among others. The seeded graph matching SGM algorithm on which we base our primary algorithm has run-time $O(n^3)$ at worst, which has been shown to be reasonable in comparison to other state-of-the-art algorithms (such as the PATH algorithm of [58] – see [52] and [11] for more information on the computational complexity of this algorithm). Furthermore, the authors of [30, 29] show that it has theoretical guarantees for converging to the correct solution under reasonable model assumptions.

The classical formulation of the vertex nomination (VN) inference task [34, 6, 48, 50, 12, 31] can be stated as follows: given a network with latent community structure in which one of the communities is of particular interest and given a few vertices from the community of interest, the task in vertex nomination is to order the remaining vertices in the network into a nomination list, with the aim of having vertices from the community of interest concentrate at the top of the list. Thus, vertex nomination can also be thought of as a method for inferring missing vertex labels, and is related to the class/labeled instances acquisition task and collective classification methods of [3, 51, 45]. The goal of vertex nomination is similar in spirit to popular network-based information retrieval (IR) procedures such as PageRank [39] and personalized recommender systems on graphs [19]. However, this formulation of VN is distinguished from other supervised network mining tasks in both the generality of what defines a vertex of interest [43, 32] and the (often) limited nature of the available training data (i.e., known vertices of interest) in G . Our present task can be viewed as vertex nomination *across* networks: for a vertex of interest in G , we use graph matching methodologies to order the vertices in G' into a nomination list, with the aim of having the corresponding vertex of interest in G' near the top of the list.

Our contributions:

In summary, our contributions are as follows:

- Leveraging the idea of principled sub-sampling of a graph, we reduce time-complexity for matching two graphs via *localization*.
- Combining the task of vertex nomination to across graph nomination tasks.

- Extending the `SoftSGM` algorithm of [11] to the task of vertex nomination.
- Demonstrating via two real world graph data-sets, we conduct an out-of-the-box large-scale evaluation of our `VNmatch` algorithm.

The remainder of the paper is laid out as follows: In Section 2, we give an overview of some related work, after which, in Section 3, we introduce a formal definition of what we mean by "corresponding vertices." Following, in Section 4, we introduce our across graph VN scheme, `VNmatch`, along with a brief mathematical description of the utilized subroutines including the soft seeded graph matching algorithm (`SoftSGM`, Algorithm 1), introduced in [11]. In Sections 5.1 and 5.2, we explore applications of `VNmatch` on both synthetic and real data, including a pair of high school friendship networks and a pair of online social networks. We conclude with an overview of our findings and a discussion of potential extensions in Section 6.

We employ the `SoftSGM` Algorithm of [11] as a means by which to nominate vertices in the `VNmatch` algorithm so as to introduce this algorithm as a useful tool in the across graph vertex nomination task. However, other vertex nomination schemes exist which could also be adapted and utilized in the `VNmatch` algorithm (in particular Steps 3 and 4). For example, the use of spectral methods, which tend to work well for matching larger graphs, may be desirable when the original graphs are on the order of millions of vertices and localization trims the networks down to only thousands of vertices. For details regarding adjacency or Laplacian spectral embedding, see [42].

Notation:

To aid the reader, we have collected the frequently used notation introduced in this manuscript into a table for ease of reference; see Table 1. Also, in what follows, we assume for simplicity that all graphs are simple (that is, edges are undirected, there are no multi-edges, and there are no loops).

TABLE 1 Table of frequently used notation

Symbol	Description
$G = (V, E)$	A graph with vertex set, V , and edge set, E
$G[T]$	For $T \subset V$, this is the induced subgraph of G on T
η (resp., η')	Number of vertices in V (resp., V')
S (resp., S')	Set of s seed vertices in G (resp., G')
x (resp., x')	Vertex of interest in G (resp., G')
W (resp., W')	Set of all n shared non-seed and non-VOI vertices in G (resp., G')
U (resp., U')	Set of all shared vertices, including seeds and VOI in G (resp., G')
J (resp., J')	Set of m (resp., m') unshared vertices in G (resp., G')
H (resp., H')	$G[U]$ (resp., $G'[U']$)
$N_t(T)$,	Set of all vertices within t -length path of $T \subset V$ (including T)
$I_n(0_n)$	The $n \times n$ identity (zeroes) matrix
$\mathbb{1}$	Appropriately sized vector of all ones
Π_k	Set of all $k \times k$ permutation matrices
D_k	Set of all $k \times k$ doubly stochastic matrices
h	Maximum considered path length from seeds to VOI, $x \in G$
S_x and S'_x	$S_x = S \cap N_h(x)$ with corresponding seeds S'_x in V'
ℓ	Maximum path length for neighborhood around S_x
$G_x = (V_x, E_x)$ (resp., $G'_x = (V'_x, E'_x)$)	$G[N_\ell(S_x)]$ (resp., $G'[N_\ell(S'_x)]$)
C'_x	The set of candidate matches for x in V'_x , namely $C'_x = V'_x \setminus S'_x$
Φ_x	Nomination list output from Algorithm 2
$\tau(x')$	Normalized expected location of x' in Φ_x
$ T $	Cardinality of set T
$\ A\ _F$	Frobenius norm of matrix A
\oplus	direct sum

2 | RELATED WORK

A number of inexact graph matching algorithms have been extended/developed recently to match graphs with overlapping, non-identical vertex sets. Two such algorithms include percolation based algorithms (see for example [22, 9, 21]) and Bayesian based algorithms (see for example [40]).

In [22] and [21], the authors focus their efforts on proving that under the independent-edge-sampling model $G(n, p; t, s)$, where a graph, G , is generated from an Erdős-Renyi (n, p) model and two subgraphs of G , namely G_1 and G_2 , are generated so that the probability of a node from G belonging to G_i is s , independently for $i = 1, 2$, and similarly for edges (with probability t). Under the independent-edge-sampling model, it is shown in [22] that for sufficiently large p the true partial matching is recoverable under particular model assumptions and for some formulation of their objective; however, as the authors admit, the optimization formulation proposed is not scalable, and there is no mention of how the correct formulation of the objective is to be obtained.

Using the same independent-edge-sampling model, the authors of [21] introduce an iterative percolation based graph matching method for seed-based graph matching, demonstrating that their method (under this model and particular assumptions) matches nearly all overlapping nodes correctly. In [9], the authors introduce a degree-driven percolation based graph matching algorithm which uses an iterative approach to match nodes with higher degree to lower degree using percolation based graph matching. For scale-free networks, the authors show that, under particular model assumptions, their method, which does not aim to match all nodes, but to match subsets of nodes from the two graphs, matches nearly all vertices which have a match correctly and that the algorithm does not match any nodes incorrectly. While this works well for scale-free networks, the advantages of this method would be more limited on graphs with more block structure and without having higher-degree nodes which help seed the rest of the algorithm. The authors point out that when seeds are chosen uniformly at random $o(n^{1/2+\epsilon})$ seeds are needed to match most vertices correctly, but allowing for more intelligent seed-selection based on vertex degree, as few as n^ϵ seeds may be sufficient, for some arbitrarily small ϵ .

Each of the above approaches is theoretically based in relatively simple random graph models (ER for [22] and the Chung-Lu model in [9]), while also demonstrating good performance in more complex real data settings. Our present approach is naturally situated in the more general Random Dot Product Graph setting of [56]. While still not able to capture all the intricacies of real network data, the random dot product graph is quite flexible and encompasses numerous other common random graph models (ER, Chung-Lu, positive definite stochastic blockmodel, etc.). In addition, we also demonstrate the effectiveness of our method on more complex real data networks as well.

Percolation based algorithms could certainly be used for vertex nomination in a similar way that we present vertex nomination based on the seeded graph matching algorithm of [11] (which is based on a fast approximate quadratic programming algorithm of [52]). One of the advantages of the present optimization based approach is the ability to efficiently explore the space of locally optimal solutions near the global optimum. Practically, the graphs to be matched in real data are much more messy than theory would allow, and the variations that can be obtained from these local optima provide a degree of robustness to model misspecification. Furthermore, the SGM algorithm itself runs quickly on modestly sized networks and has asymptotic guarantees for particular models and conditions (see for example [52, 11] and [30, 29]).

In [20] the authors focus on the task of de-anonymizability, and explore a method for matching nodes based on node-degree; that is, the authors consider two graphs drawn in some manner from a larger graph and attempt to de-anonymize (match) the vertices in the two graphs which have the highest degrees. We are not concerned with matching vertices based on their degree, since a vertex of interest is based on an external characteristic that is not necessarily related to the degree distribution of the two graphs.

Another technique for approximate graph matching relies on Bayesian methods [40]. The authors of [40] introduce a method which relies on estimating the posterior probability that two nodes should be matched based on a particular prior. In the aforementioned paper, the authors rely on node attributes, such as vertex degree, mapping a few nodes at a time in an iterative manner until all nodes are matched; any nodes matched in one iteration will be used as seeds (referred to as *anchors*) in the next iteration. In the end, the authors seek to obtain a hard matching of the nodes that maximizes the sum of the log-posteriors for all node pairs. While the idea of a posterior probability that two nodes should be matched is a similar idea to what we present, the purpose of our more frequentist method is to utilize a *soft matching* of the nodes in order to rank them in order from most to least likely matches to the vertex (or vertices) of interest.

3 | CORRESPONDING VERTICES

Consider two social networks in which vertices represent users/accounts and edges represent whether or not two accounts are linked in some way. An individual may have an account on one network or the other or both. We would say that two accounts across the platforms correspond to each other if the same individual runs both accounts; that is, both nodes correspond to the same individual although with possibly different node labels. Arguably an individual who has an account on both networks will have similar, though not identical, behavior across the two networks. Consider an email network in which nodes are email addresses and two email addresses share an edge (directed or not) if they send correspondence to one another, and a phone network in which nodes are phone numbers and edges represent whether or not one of the numbers calls the other. In this example, a vertex in the email network will correspond to a vertex in the call network if the email and phone number belong to the same individual. An individual who uses both email and phone correspondence may communicate with individuals in the two networks in a similar, though not identical, manner. Thus, if there is a connection between two individuals in one network and those same individuals exist in the second network, one would think that it is more likely that there exists a connection between these individuals in the second network, i.e. there is a positive correlation between the edges between these vertices across the networks. To model this correspondence, we proceed as follows.

With notation as above, let $U = \{x\} \cup S \cup W$ and $U' = \{x'\} \cup S' \cup W'$ denote the set of shared vertices between G and G' with $|U| = |U'| = 1 + s + n$. Define $H := G[U]$ (resp., $H' = G'[U']$), the induced subgraph of G (resp., G') on the vertex set U (resp., U'). As H and H' are graphs on the same (though potentially differently labeled) vertex sets, we model a shared structure present across H and H' as $(H, H') \sim \rho\text{-RDPG}(X)$. Before defining the $\rho\text{-RDPG}$ model, we first recall the definition of a *random dot product graph* (RDPG); see [56].

Definition 1. Consider $X = [X_1, \dots, X_n]^\top \in \mathbb{R}^{n \times d}$ satisfying $XX^\top \in [0, 1]^{n \times n}$. We say that graph G with adjacency matrix A is distributed as a random dot product graph with parameter X (abbreviated $G \sim \text{RDPG}(X)$) if given X ,

$$A_{i,j} \stackrel{\text{ind.}}{\sim} \text{Bernoulli}(X_i^\top X_j),$$

i.e.,

$$P(A|X) = \prod_{i < j} (X_i^\top X_j)^{A_{i,j}} (1 - X_i^\top X_j)^{1 - A_{i,j}}.$$

Conditioning on X , this is an independent-edge random graph model where vertex v_i is associated with a latent position vector $X_i \in \mathbb{R}^d$, and the probability of an edge between any two vertices is determined by the dot product of their associated latent position vectors.

To imbue multiple random dot product graphs with a notion of vertex correspondence, we correlate the behavior of nodes across networks. We call this new model the $\rho\text{-RDPG}$ model, which is defined as follows.

Definition 2. Consider $X = [X_1, \dots, X_n]^\top \in \mathbb{R}^{n \times d}$ satisfying $XX^\top \in [0, 1]^{n \times n}$. The bivariate graph valued random variables (G, G') —with respective adjacency matrices A and A' —are said to be distributed as a pair of ρ -correlated random dot product graphs with parameter X (abbreviated $(G, G') \sim \rho\text{-RDPG}(X)$) if

1. Marginally, $G, G' \sim \text{RDPG}(X)$, and
2. $\{A_{i,j}, A'_{k,l}\}_{\{i,j\}, \{k,l\} \in \binom{[n]}{2}}$ are collectively independent except that for each $\{i, j\} \in \binom{[n]}{2}$, $\text{correlation}(A_{i,j}, A'_{i,j}) = \rho$.

Our framework posits $(H, H') \sim \rho\text{-RDPG}(X)$ for a latent position matrix $X \in \mathbb{R}^{(1+s+n) \times d}$. In order to generate the full graphs G and G' which also have unshared vertices, we generate $G \sim \text{RDPG}([X, Y])$ and $G' \sim \text{RDPG}([X, Y'])$, so that the induced subgraphs $(H, H') \sim \rho\text{-RDPG}(X)$ and the remaining edges of G and G' are formed independently as in the case for the general RDPG. Thus, the first $1 + s + n$ vertices in the two graphs correspond to one another via the identity map and the remaining m and m' vertices of G and G' , respectively, represent the unshared vertices J and J' . Here, $Y \in \mathbb{R}^{m \times d}$ and $Y' \in \mathbb{R}^{m' \times d}$ represent the respective latent positions for the unshared vertices in G and G' . For ease of notation, we will write $(G, G') \sim \rho\text{-RDPG}(X, Y, Y')$, where (G, G') is realized as two graphs: G on $\eta = 1 + s + n + m$ vertices $\{x\} \cup S \cup W \cup J$ and G' on $\eta' = 1 + s + n + m'$ vertices $\{x'\} \cup S' \cup W' \cup J'$.

If G and G' exhibit latent community structure, it can be fruitful to model them as Stochastic block model (SBM) random graphs [18]. SBMs have been extensively studied in the literature and have been shown to provide a useful and theoretically tractable model for more complex graphs with underlying community structure [44, 49, 1, 38]. We define the stochastic block model as follows.

Definition 3. We say that graph $G = (V, E)$ with adjacency matrix A is distributed as a stochastic block model random graph with parameters k, b and Λ (abbreviated $G \sim \text{SBM}(k, b, \Lambda)$) if

1. V is partitioned into k blocks $V = V_1 \cup V_2 \cup \dots \cup V_k$;
2. $b : V \rightarrow \{1, \dots, k\}$ is a map such that $b(i)$ denotes the block label of the i^{th} vertex;
3. $\Lambda \in [0, 1]^{k \times k}$ is a matrix such that $A_{i,j} \stackrel{\text{ind}}{\sim} \text{Bernoulli}(\Lambda_{b(i), b(j)})$ for distinct $\{i, j\} \in \binom{V}{2}$.

Recall that the edge probability matrix for a random dot product graph model, with parameter $X \in \mathbb{R}^{n \times d}$, is equal to XX^T , which is positive semi-definite. If X consists of precisely k distinct rows, then a graph generated via $\text{RDPG}(X)$ can also be said to be generated from a stochastic block model having k blocks, block assignment vector b assigning vertices with the same latent position to the same block, and probability matrix $\Lambda = X^{(k)}(X^{(k)})^T$ where $X^{(k)}$ here refers to the $k \times d$ matrix of distinct rows of X . Moreover, if Λ is positive semidefinite, then $G \sim \text{SBM}(k, b, \Lambda)$ can be realized as a RDPG with appropriately defined X . Thus, there is an overlap in the set of random dot product graph models and stochastic block models.

We can then define the ρ -SBM model as follows.

Definition 4. The bivariate graph valued random variables (G, G') —with respective adjacency matrices A and A' —are said to be distributed as a pair of ρ -correlated stochastic block model graphs with parameter k, b , and Λ (abbreviated $(G, G') \sim \rho\text{-SBM}(k, b, \Lambda)$) if

1. Marginally, $G, G' \sim \text{SBM}(k, b, \Lambda)$, and
2. $\{A_{i,j}, A'_{k,l}\}_{\{i,j\}, \{k,l\} \in \binom{V}{2}}$ are collectively independent except that for each $\{i, j\} \in \binom{V}{2}$,

$$\text{correlation}(A_{i,j}, A'_{i,j}) = \rho.$$

Note that if we generate H and H' from a ρ -SBM(k, b, Λ), G and G' can be constructed so that

$$G \sim \rho\text{-SBM}(k_1, b_1, \Lambda_1) \text{ and } G' \sim \rho\text{-SBM}(k_2, b_2, \Lambda_2),$$

where $k \leq \min(k_1, k_2)$, $b_1(j) = b_2(j) = b(j)$ for all $j \in \{1, 2, \dots, 1 + s + n\}$, and the upper left $k \times k$ submatrix of Λ_i is Λ (for $i = 1, 2$). We write this formally as

$$(G, G') \sim \rho\text{-SBM}(k_1, k_2, b_1, b_2, \Lambda_1, \Lambda_2).$$

4 | VERTEX NOMINATION VIA SEEDED GRAPH MATCHING

With this notion of corresponding vertices, we next introduce our proposed algorithm for finding the corresponding vertex $x' \in V'$ to a particular vertex of interest $x \in V$. Again, we assume a single vertex of interest for simplicity, as the extension to multiple vertices of interest follows immediately. Before presenting our main algorithm, VNmatch (Algorithm 2), we first provide the necessary details for the subroutine of Algorithm 2 we employ, namely the SoftSGM algorithm of [11]. The easy interpretability and simple extension of the SoftSGM algorithm to generating nomination lists for vertices of interest make it a natural candidate for the vertex nomination subroutine task of Algorithm 2; however, other methods of graph matching, such as spectral-based methods, for which extension to vertex nomination is possible could also be used during this step of the algorithm.

4.1 | Soft seeded graph matching

Given A and A' in $\mathbb{R}^{n \times n}$, the respective adjacency matrices of two n -vertex graphs G and G' , the *graph matching problem* (GMP) is

$$\min_{P \in \Pi_n} \|AP - PA'\|_F, \quad (1)$$

where Π_n is the set of $n \times n$ permutation matrices, and $\|M\|_F$ denotes the Frobenius norm of the matrix M . While the formulation in Eq. (1) seems restrictive, it is easily adapted to handle the case where the graphs are weighted, directed, loopy and on potentially different sized vertex sets (using, for example, the padding methods introduced in [11]).

In our present setting, where we have known seeded vertices $S \leftrightarrow S'$, we consider the closely related *seeded graph matching problem* (SGMP) (see, for example, [11, 30, 29, 17, 13, 28, 33]). We have $G = (V, E)$ and $G' = (V', E')$ with vertex sets

Algorithm 1 SoftSGM

Input: $G \in \mathcal{G}_\eta$, $G' \in \mathcal{G}_{\eta'}$ with respective adjacency matrices A and A' ; number of seeds s (assumed to be first s vertices of G and G'); number of random restarts $R \in \mathbb{N}$; random initialization parameter $\gamma \in [0, 1]$; stopping criterion ϵ ;

Step 0: if $\eta \neq \eta'$ set $A = (2A - (\mathbb{1}\mathbb{1}^T - I_\eta)) \oplus 0_{\min(0, \eta' - \eta)}$ and $A' = (2A' - (\mathbb{1}\mathbb{1}^T - I_{\eta'})) \oplus 0_{\min(0, \eta - \eta')}$;

for $i=1:R$ **do**

Step 1: Generate Q_i Uniformly from the set of permutation matrices, Π_{n-s} ;

Step 2: Generate β_i Uniformly from $(0, \gamma)$ and set $P_i^{(0)} = \beta_i Q_i + (1 - \beta_i) \frac{1}{n-s} (\mathbb{1}\mathbb{1}^T)$;

Step 3:

while $\|f(P^{(j)}) - f(P^{(j-1)})\|_F > \epsilon$ **do**

Step a: Compute $\nabla f(P^{(j)}) = A_{21} B_{21}^T + A_{12}^T B_{12} + A_{22} P^{(j)} B_{22}^T + A_{22}^T P^{(j)} B_{22}$;

Step b: Compute $Q^{(j)} \in \arg \max \{\text{trace}(Q^T \nabla f(P^{(j)}))\}$ over $Q \in \mathcal{D}_{n-s}$ via the Hungarian Algorithm [25];

Step c: Compute $\alpha^{(j)} = \arg \max \{f(\alpha P^{(j)} + (1 - \alpha) Q^{(j)})\}$ over $\alpha \in [0, 1]$;

Step d: Set $P^{(j+1)} = \alpha^{(j)} P^{(j)} + (1 - \alpha^{(j)}) Q^{(j)}$;

end while

Step 5: Compute $P_i \in \arg \max \{\text{trace}(Q^T P^{(\text{final})})\}$ over $Q \in \Pi_{n-s}$ via the Hungarian Algorithm, where $P^{(\text{final})}$ is output from the while loop;

end for

Step 6: Define p via $p(\ell, k) = \left[\sum_{i=1}^R \frac{1}{R} P_i \right]_{\ell, k}$;

Output: p

$V = \{x\} \cup S \cup W \cup J$ and $V' = \{x'\} \cup S' \cup W' \cup J'$, with $|V| = \eta = 1 + s + n + m$, $|V'| = \eta' = 1 + s + n + m'$, and seeding $S \leftrightarrow S'$. Without loss of generality, suppose $S = S' = \{1, 2, \dots, s\}$ (if no seeds are used, $s = 0$ and $S = S' = \emptyset$), and suppose for the moment that $\eta = \eta'$. The seeded graph matching problem aims to solve

$$\min_{P \in \Pi_{\eta-s}} \|A(I_s \oplus P) - (I_s \oplus P)A'\|_F^2, \quad (2)$$

where, $\Pi_{\eta-s}$ denotes the set of $(\eta - s) \times (\eta - s)$ permutation matrices, and \oplus denotes the direct sum of matrices. Note that decomposing A and A' via

$$A = \begin{pmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{pmatrix}, \text{ and } A' = \begin{pmatrix} A'_{11} & A'_{12} \\ A'_{21} & A'_{22} \end{pmatrix} \quad (3)$$

where $A_{11}, A'_{11} \in \mathbb{R}^{s \times s}$, $A_{21}^T, (A'_{21})^T, A_{12}, A'_{12} \in \mathbb{R}^{(\eta-s) \times s}$, and $A_{22}, A'_{22} \in \mathbb{R}^{(\eta-s) \times (\eta-s)}$, the SGMP is equivalent to

$$\max_{P \in \Pi_{\eta-s}} f(P) = \max_{P \in \Pi_{\eta-s}} \left[\text{trace}(P^T A_{21} (A'_{21})^T) + \text{trace}(P^T A_{12}^T A'_{12}) + \text{trace}(A_{22}^T P A'_{22} P^T) \right]. \quad (4)$$

The SGMP, in general, is NP-hard, and many (seeded) graph matching algorithms begin by relaxing the feasible region of Eq. (2) or (4) from the discrete $\Pi_{\eta-s}$ to the convex hull of $\Pi_{\eta-s}$ [58, 10, 52, 11], which, by the Birkoff-vonNeumann theorem, is the set of $(\eta - s) \times (\eta - s)$ doubly stochastic matrices, denoted $\mathcal{D}_{\eta-s}$. This relaxation enables the machinery of continuous optimization (gradient descent, ADMM, etc.) to be employed on the relaxed SGMP. Note that while the solutions of Eq. (2) and (4) are equivalent, the solutions of the relaxations of Eq. (2) and (4) are not equivalent in general, with the indefinite relaxation, Eq. (4), preferable under the model assumptions we will consider in this paper [29].

The SGM algorithm of [11] approximately solves this indefinite SGMP relaxation using the Frank-Wolfe algorithm [14], and then projects the obtained doubly stochastic solution onto $\Pi_{\eta-s}$. The algorithm performs excellently in practice in both synthetic and real data settings, with a $O((\eta - s)^3)$ runtime allowing for its efficient implementation on modestly sized networks. Since we ultimately aim to create a nomination list (and not a 1-to-1 correspondence necessarily) for the VOI of likely matches in $V' \setminus S'$, we use the SoftSGM algorithm of [11]—a stochastic averaging of the original SGM procedure over multiple random restarts—in order to softly match the graphs. Rather than the 1-to-1 correspondence output from SGM, SoftSGM (pseudocode provided in Algorithm 1 for completeness) outputs a function $p(\cdot, \cdot) : V \times V' \mapsto [0, 1]$, where $p(i, j)$ represents the likelihood vertex j in G' matches to vertex i in G . As noted in Table 1, $A \oplus B$ denotes the direct sum between two matrices A and B , and 0_n denotes the $n \times n$ all zeroes matrix. Also, the function f in Algorithm 1 refers to f as in Equation 4.

Algorithm 2 VNmatch: vertex nomination via seeded graph matching

Input: $G, G'; S, S'$ – the seed sets, with $S \leftrightarrow S'$; $\ell \geq h$

Step 1: find $S_x = s \cap N_h(x)$, and matching vertices $S_x \leftrightarrow S'_x$ in G' , if $|S_x| = 0$, stop;

Step 2: create $G_x = G[N_\ell(S_x)]$ and $G'_x = G[N_\ell(S'_x)]$;

Step 3: use graph matching (we use SoftSGM Algorithm 1) to match $G_x = (V_x, E_x)$ and $G'_x = (V'_x, E'_x)$, yielding $p(\cdot, \cdot) : V_x \times V'_x \mapsto [0, 1]$;

Step 4: create nomination list ϕ_x for x by ranking the vertices in V'_x by decreasing value of $p(x, \cdot)$;

Output: ϕ_x

4.2 | VNmatch

We consider two graphs G and G' with vertex sets $V = \{x\} \cup S \cup W \cup J$ and $V' = \{x'\} \cup S' \cup W' \cup J'$, where the vertices in $V \setminus J$ and $V' \setminus J'$ are shared between the two graphs. As stated previously, our task is to leverage an observed one-to-one correspondence $S \leftrightarrow S'$ to find the vertex $x' \in V'$ corresponding to a particular vertex of interest $x \in V$. If G and G' are modestly sized (on the order of thousands of vertices), we could use Algorithm 1, the SoftSGM algorithm of [11], to soft match G and G' , padding V or V' as necessary when $\eta \neq \eta'$. As the purpose of matching the graphs in this inference task is to identify the vertex $x' \in V'$; we create a ranked nomination list, which we denote by ψ_x , for x by ordering the vertices in G' by decreasing value of $p(x, \cdot)$: (with ties broken uniformly at random)

$$\begin{aligned} \psi_x(1) &\in \arg \max_{r \in V'} p(x, r), \\ \psi_x(2) &\in \arg \max_{r \in (V' \setminus \{\psi_x(1)\})} p(x, r), \\ &\vdots \\ \psi_x(\eta') &\in \arg \max_{r \in (V' \setminus \{\psi_x(1), \dots, \psi_x(\eta'-1)\})} p(x, r). \end{aligned}$$

In practice, however, the networks under consideration may be too large to directly apply SoftSGM or similar global graph matching procedures. For example, many of the partially crawled social networks found at [27] contain tens-of-millions of vertices or more. Therefore, rather than applying SoftSGM globally, we reduce the size of the problem through localization. In our underlying network model, the local structure around a vertex in one graph will be similar to the local structure around a vertex in the second graph. With this in mind, given $h \in \mathbb{N}$ and a set $Y \subset V$, we define the h -neighborhood of Y in G via

$$N_h(Y) := \{v \in V : \text{there exists a path of length} \\ \leq h \text{ in } G \text{ from } v \text{ to a vertex in } Y\}.$$

Note, by convention $Y \subset N_h(Y)$. We denote by $S_x = S_{x,h} := S \cap N_h(x)$ the set of seeded vertices in G with shortest path distance to x less than or equal to h , and we define S'_x to be the corresponding seeds in G' with $|S_x| = s_x = |S'_x|$. Notionally, as $h \rightarrow \infty$, $N_h(x)$ tends towards the connected component of G containing x , and we say that $h = \infty$ yields $N_h(x)$ to be the entire vertex set V of G .

For $\ell \geq h$, we define $G_x = (V_x, E_x) := G[N_\ell(S_x)]$ and $G'_x = (V'_x, E'_x) := G[N_\ell(S'_x)]$ to be the respective induced subgraphs of G and G' generated by $N_\ell(S_x)$ and $N_\ell(S'_x)$. Ideally, $N_\ell(S'_x)$ —which is a local ℓ -neighborhood of those seeds in G' whose distance to x in G is at most $h \leq \ell$ —will contain x' , the corresponding VOI in G' . If so, we propose to uncover the correspondence $x \leftrightarrow x'$ by using SoftSGM to soft match G_x and G'_x rather than all of G and G' . The output of SoftSGM is then $p(\cdot, \cdot) : V_x \times V'_x \mapsto [0, 1]$, and we create the nomination list for x , denoted Φ_x , by ranking the vertices in V'_x based on decreasing value of $p(x, \cdot)$; i.e., if $|V'_x| = \xi$ then

$$\begin{aligned} \Phi_x(1) &\in \arg \max_{r \in V'_x} p(x, r), \\ \Phi_x(2) &\in \arg \max_{r \in (V'_x \setminus \{\Phi_x(1)\})} p(x, r), \\ &\vdots \\ \Phi_x(\xi) &\in \arg \max_{r \in (V'_x \setminus \{\Phi_x(1), \dots, \Phi_x(\xi-1)\})} p(x, r), \end{aligned}$$




FIGURE 1 Average size of S_x over 50 Monte Carlo simulations as a function of (h, s) ; seed sets and vertex of interest selected randomly. As h increases, more vertices in the graph are within an h -path of the randomly chosen VOI, and therefore more of the seed vertices are in $N_h(x)$.

where ties are broken uniformly at random.

Remark 1. Figure 1 demonstrates how $|S_x|$ depends on $|S|$ and h for graphs generated from a stochastic blockmodel (Figure 1a, model described in Definition 3) and for the Facebook network of [35] which we consider in detail in Section 5.2.1. In both cases, the seed sets and VOI are chosen uniformly at random. As expected, as h increases, $|S_x|$ approaches $|S|$. It is important to keep in mind that increasing h also increases ℓ and, consequently, the sizes of $N_\ell(S_x)$ and $N_\ell(S'_x)$, increasing computational complexity. In both the simulated and Facebook examples, $h = 2$ seems an appropriate choice, and is the value we use for the networks in further exploration (see Section 5).

5 | SIMULATIONS AND REAL DATA EXPERIMENTS

Note here that all necessary code and data needed to produce the figures in this section can be found at <http://www.cis.jhu.edu/~parky/D3M/VNSGM/>.

We will measure the performance of VNmatch via $\text{rank}(x')$, the expected rank of x' in Φ_x when ties are broken uniformly at random. Since the size of the set of candidate matches $C'_x := V'_x \setminus S'_x$ (seeds in G' will never be matched to x by SoftSGM) varies greatly in each experiment, we will compare across experiments by computing the normalized rank of x'

$$\tau(x') = \left(\frac{\text{rank}(x') - 1}{|C'_x| - 1} \right) \vee 0 \in [0, 1]. \quad (5)$$

Note that $\tau(x') = 0$ (resp., $\tau(x') = 0.5$ or $\tau(x') = 1$) implies that the $\Phi_x(1) = x'$ (resp., $\Phi_x(|C'_x|/2) = x'$ or $\Phi_x(\alpha) = x'$ for $\alpha \geq |C'_x|$); i.e., the VOI was first, half-way down, or effectively last in the nomination list. A low value of $\tau(x')$ corresponds to a low ranking of x' in the nomination list output from the VNmatch algorithm and corresponds to a measure of how much time is saved (versus a uniformly random search) by the end-user when searching through the candidate set of vertices for the true match x' . We view a score of $\tau(x') = 5/100$ as better than a score of $\tau(x') = 5/10$ since the amount of time saved by the end-user is greater in the first case.


(a) We plot $\tau(x')$ as a function of the number of seeds, s_x for various ρ .(b) $\tau(x')$ as a function of r , the ratio of the vertex sizes of the two graphs, using $s_x = 4$ and $\rho = 0.6$.

FIGURE 2 For pairs of 300-node graphs generated from a ρ -RDPG(X) model, we plot the average normalized rank, $\tau(x')$, as a function of s_x , ρ , and r .


(a) We plot $\tau(x')$ as a function of s_x for various ρ .(b) $\tau(x')$ as a function of r , the ratio of the vertex sizes of the two graphs, using $s_x = 4$ and $\rho = 0.6$.

FIGURE 3 For pairs of 300-node graphs generated from a ρ -SBM($3, b, \Lambda$), we the average normalized rank, $\tau(x')$, as a function of s_x , ρ , and r .

5.1 | Simulation experiments

We first explore the performance of Algorithm 2 in the ρ -RDPG setting, followed by the ρ -SBM setting (see Section 3 for descriptions of these models). To wit, we first generate pairs of graphs from a ρ -RDPG(X), where the latent positions of X are uniformly chosen so that each row of X is a unit vector and for any two rows of X , namely X_i and X_j , $X_i X_j^T \in (0, 1)$. In Figure 2 we explore how $\tau(x')$ is affected by the number of seeds used in the matching as compared against various correlation values $\rho = 0, 0.3, 0.5, 0.7, 1$ (2a) and disparities in the sizes of the graphs to be matched when $\rho = 0.6$ (2b).

Next, we generate pairs of graphs from a ρ -SBM($3, b, \Lambda$), where b is such that $1/3$ of the vertices are in each block and

$$\Lambda = \begin{bmatrix} 0.7 & 0.3 & 0.4 \\ 0.3 & 0.7 & 0.3 \\ 0.4 & 0.3 & 0.7 \end{bmatrix}. \quad (6)$$

In Figure 3, we explore how $\tau(x')$ is affected by the number of seeds used in the matching as compared against correlation values $\rho = 0, 0.3, 0.5, 0.7, 1$ (3a) and disparities in the sizes of the graphs to be matched when $\rho = 0.6$ (3b).

In order to explore how the number of seeds used in matching, s_x , affects the location of the VOI in the nomination list, in both the RDPG and SBM setting, we vary s_x from 1 to 9, and run 100 Monte Carlo replicates using `VNmatch`, with both the VOI and the seeds chosen uniformly at random in each Monte Carlo replicate. In Figures 2a and 3a, we record the average normalized rank of the VOI in the nomination list (± 2 s.e.) for the RDPG and SBM settings, respectively. It is apparent that for




FIGURE 4 The induced subgraphs for the High School Facebook and Survey networks generated by the shared vertices [35].

sufficiently correlated networks, as the number of seeds increases, our proposed nomination scheme becomes more accurate; i.e., the location of the VOI in the nomination list is closer to the top of the list. For graphs with very low correlation, the uniformly poor performance can be attributed to both the lack of much common structure between G_x and G'_x and the failure of `SoftSGM` to tease out this common structure. Since both G and G' are dense networks, $N_\ell(S_x)$ and $N_\ell(S'_x)$ generally contained between 250 and 300 vertices each. Thus, the proportion of shared vertices in G_x and G'_x is rather high for this example.

To explore how the normalized rank of the VOI is influenced by matching graphs which differ in size, we next consider pairs of graphs on different sized vertex sets. We will set the number of vertices in the smaller graph, G' , to be $|V'| = r|V| = 300r$, for $r = 0.25, 0.30, \dots, 1$. Let $H' = G'$ and suppose there exists an induced subgraph H of G so that $(H, G') \sim 0.6\text{-RDPG}(X)$ for Figure 2b and $(H, G') \sim 0.6\text{-SBM}(3, b, \Lambda)$ for Figure 3b. For each r , we plot the average $\tau(x')$ ($\pm 2\text{s.e.}$) over 100 Monte Carlo replicates for fixed $s_x = 4$. As can be seen, under this model when the original networks G and G' have a large discrepancy between the sizes of their vertex sets there is less accuracy in the `VNmatch` algorithm. Furthermore, the more obvious community structure present in the SBM setting contributes to better performance of the `VNmatch` algorithm. Although we are not matching graphs G_x and G'_x with vertex size difference ratio r at every iteration, since the connectivity of the vertices is high, G_x and G'_x do not deviate much from being the full graphs.

Li and Campbell explore the effects of utilizing seeds in graph matching problems in [28]. They found that although a small number of seeds can greatly increase the number of correctly matched vertices, as the number of shared users decreases so does the ability to find a good match. As might be expected, since the number of potential mismatches increases as the number of shared users decreases, Figures 2b and 3b are consistent with Li and Campbell's results.

5.2 | Real data experiments

In this section, we explore two applications of `VNmatch` on real data. Section 5.2.1 explores a pair of high-school networks obtained from [35] in which the first graph is created based on student responses to a 'who-knows-who' survey and the second is a Facebook friendship network involving some of the same students. In Section 5.2.2, we consider Instagram and Twitter networks having over-lapping vertex sets in which we would like to identify which Instagram profile corresponds to a particular Twitter profile.

5.2.1 | Finding friends in high school networks

We consider two High School friendship networks on over-lapping vertex sets published in [35]. The first network, having 156 vertices, represents a Facebook network of profiles in which two vertices are adjacent if the pair of individuals were friends on Facebook. The second network consists of 134 vertices, each representing a particular student, and two vertices are adjacent if one of the students reported that they are friends with the other student. There are 82 shared vertices across the two networks for which we know the bijection between the two vertex sets, and the remaining vertices are known to have no such correspondence. In the language of Section 1, $\eta = 156$, $\eta' = 134$, $n + s = 81$, $m = 74$, and $m' = 52$.

Due to the large number of unshared vertices (nearly 40% and 50% for the Survey and Facebook networks, respectively), for illustrative purposes we perform our analysis of this data set by looking at the induced subgraphs generated by the shared




FIGURE 5 Consider each $x \in V$ as the VOI ($|V| = 82$). For each $v \in N_2(x)$ match the induced subgraphs of H and H' generated by $N_2(v)$ and $N_2(v')$, considering $\{v\}$ and $\{v'\}$ to be seed-sets of size 1. For each x , plot how often $\tau(x') \in \{0, (0, 0.5), [0.5, 1], NA\}$ in light green, dark green, light purple, and dark purple, respectively (colors here listed in order as they appear in the plot from bottom to top). The height of the stack represents the total number of vertices in $N_2(x)$.

vertices. A brief glimpse into the effects of the unshared vertices can be found in the supplemental material accompanying this article. This step is purely for exploratory analysis and would not be feasible in practice, as we would not have prior knowledge about which vertices in the networks are shared as opposed to unshared. At the same time, immediate success of `VNmatch` is still not guaranteed since the structure of the two graphs is very different, see Figure 4. Furthermore, we can see that there appears to be a 2-block structure for each of the (shared) networks, although, if we were to model these networks the block probability matrices for the two networks appears to differ (unlike our simulation examples).

We first explore how `VNmatch` performs when finding the VOI using a single seed. Let H and H' denote, respectively, the induced subgraphs of the High School Facebook and Friendship-Survey networks generated by the 82 shared vertices. We run 82 experiments, one for considering each $x \in V$ as the VOI, and for each VOI we consider using each $v \in N_2(x)$ as our single seed for `VNmatch`. In Figure 5, for each x , we plot how often $\tau(x') \in \{0, (0, 0.5), [0.5, 1], NA\}$ in light green, dark green, light purple, and dark purple, respectively (colors listed in order as they appear in Figure 5 from bottom to top): When $\tau(x') = 0$, the true match x' is at the top of the nomination list – this is the best case possible; when $\tau(x') \in (0, 0.5)$, x' is somewhere between the top of the nomination list and half-way down (i.e. better than chance, but not first); when $\tau(x') \in [0.5, 1]$ the nomination list from `VNmatch` is worse than a uniformly random nomination list; and finally $\tau(x') = NA$ means that $x' \notin V'_x$ and our algorithm cannot hope to nominate the correct vertex. The height of the stack represents the total number of vertices in $N_2(x)$. While beyond the scope of this work, this figure points to the impact of seed-selection as well-chosen seeds can be the difference between perfect algorithmic performance and performance worse than chance. Note also that for vertices 6, 31, 36, and 49, $x' \notin V'_x$ for all $v \in N_2(x)$, so, matching the two neighborhoods for these vertices would never be successful for $\ell = h = 2$.

We next consider the effects of increasing s_x . For simplicity, we present our findings while considering vertex 27 to be the VOI. Vertex 27 shows moderately good performance using 1 seed in Figure 5, although not the best. We expect `VNmatch` to work equally well on any other vertex with similar (or better) performance to vertex 27 as noted in Figure 5.

With vertex $x = v_{27}$ as the VOI in G , for each s_x increasing from 2 to 9 we uniformly at random generate 100 seed sets from $N_2(x)$ and apply `VNmatch` to match G_x and G'_x using these seed sets. For $s_x = 1$, rather than having 100 Monte Carlo replicates, we consider only the 47 possible seed sets of size 1 in $N_2(27)$. Figure 6, displays $\tau(x')$ as a function of s_x , with Figure 6a showing the general performance of $\tau(x')$ with respect to s_x and Figure 6b displaying a frequency histogram (conditioned on $\tau(x') \neq NA$) of $\tau(x')$ for each $s_x \in \{1, \dots, 9\}$.




FIGURE 6 Using $x = v_{27}$ as the VOI, vary s_x from 1 to 9 in VNmatch. For $s_x > 1$, uniformly at random generate 100 seed sets from $N_2(x)$. For $s_x = 1$, consider all 47 possible seed sets of size 1.




FIGURE 7 Graphs of a particular friend of the VOI for both Twitter and Instagram; VOI in red and seeds in pink.

5.2.2 | Finding Friends on Instagram from Twitter

We next consider nominating across two publicly available social network datasets, one derived from Twitter and one derived from Instagram, where there is an edge between two vertices if one vertex is following the other vertex in the respective social network. We consider a single vertex present on both the Twitter and Instagram networks and construct the two-hop neighborhoods of this vertex in each network, yielding a 163 vertex Twitter graph (Figure 7a) and a 28 vertex Instagram graph (Figure 7b). After identifying a VOI in each network, a simple metadata analysis of vertex features yields 10 potential seeds. In Figure 8, we plot the average value of $\tau(x') (\pm 2s.e.)$ when using a seed set of size $s_x = 2, 4, 6, 8, 10$. To avoid pathologies arising from $x' \notin V'_x$, we use vertex 8 as a seed in each experiment. As there are few seeds here, we average τ over all possible sets of seeds of size s_x in each example.

There are a few takeaways from this figure. First note that as the number of seeds increases, the performance of VNmatch increases significantly (i.e., the rank of x' in Φ_x is closer to the top). In fact, we find that there are two vertices (including the central vertex in both graphs) whose presence in the seed sets are crucial in that if they are in the seed set then $\tau(x') = 0$ every time, and if not then $\tau(x') > 0.5$. Thus, the improvement upon $\tau(x')$ in Figure 8 is due to the increased proportion of seed sets




FIGURE 8 Plot the average value of $\tau(x)$ (Equation 5), along with a confidence bound, for $s_x = 2, 4, 6, 8, 10$, always using the center vertex (8) as a seed.

which contain the two crucial seeds for identifying the true match. Furthermore, these are the only two seeds which are adjacent to the vertex of interest. This indicates that in the future it may be beneficial to focus on what vertex-properties impact seed-usefulness in terms of assistance with matchability. Also note that these graphs are quite local—the full Twitter and Instagram networks would have $\gg 10^7$ vertices—yet our algorithm still performed quite well only considering $\approx 10^2$ vertices. Indeed, by whittling the networks down into local neighborhoods, we are able to leverage the rich local signal present across networks without the computational burden induced by working with the full, often massive, networks themselves.

6 | CONCLUSIONS

In this paper, we introduce an across-graph vertex nomination scheme based on local neighborhood alignment for identifying a vertex of interest. Our algorithm operates locally within much larger networks, and can scale to be implemented in the very large networks ubiquitous in this age of big data. We demonstrated the efficacy of our principled methodology on both simulated and real data networks, including an application to networks from Twitter and Instagram.

In this paper we have focused on finding a corresponding vertex in a second network to the VOI in the first network with a notion of correspondence in our real-data examples meaning that two nodes across the networks represent the same individual. Another application of this algorithm would be finding vertices, either across two networks or across two subnetworks of one larger network, that have *similar structural role* across the two networks. Since the resulting nomination list of the VNmatch algorithm already outputs nodes in an ordering that is based on which vertices in a localized version of the second network have similar localized structural role to the VOI in the first network, this extension follows immediately.

In the future, we would like to theoretically and empirically explore the impacts of network correlation and errors on VNmatch for various random graph models. We are also actively seeking to understand the effects of different types of seeds and what makes a “good” seed. The impact of unshared vertices and their connections on the performance of the VNmatch algorithm is still an open area of investigation. Applying VNmatch to multiple VOI could be done either iteratively or simultaneously. Other questions to explore include the addition of attributes and how to apply VNmatch simultaneously across multiple (more than 2) networks.

ACKNOWLEDGMENTS

This work is partially supported by the XDATA and D3M and SIMPLEX programs of the Defense Advanced Research Projects Agency (DARPA), the Acheson J. Duncan Fund for the Advancement of Research in Statistics (Awards 16-20 and 16-23 and 18-3), and by EPSRC grant no. EP/K032208/1. This material is also based on research sponsored by the Air Force Research Laboratory and DARPA, under agreement number FA8750-18-2-0035. The U.S. Government is authorized to reproduce and distribute reprints for Governmental purposes notwithstanding any copyright notation thereon. The views and conclusions

contained herein are those of the authors and should not be interpreted as necessarily representing the official policies or endorsements, either expressed or implied, of the Air Force Research Laboratory and DARPA, or the U.S. Government. The authors would also like to thank the Isaac Newton Institute for Mathematical Sciences, Cambridge, UK, for support and hospitality during the program for Theoretical Foundations for Statistical Network Analysis where a portion of work on this paper was undertaken. The authors would also like to thank Jason Matterer for his helpful comments and suggestions.

Author contributions

Conceived and designed the methodology: HP VL CP. Performed the experiments: HP YP. Analyzed the data: HP YP. Wrote the paper: HP VL CP.

Financial disclosure

None reported.

Conflict of interest

The authors declare no potential conflict of interests.

SUPPORTING INFORMATION

Relevant code and data for all simulations and experiments can be found at <http://www.cis.jhu.edu/~parky/D3M/VNSGM/>.

The high school friendship and Facebook network data was originally published in [35] as data sets three and four, respectively. A detailed description of the data sets can also be found at <http://www.sociopatterns.org/datasets/high-school-contact-and-friendship-networks/>.

References

- [1] Airoldi, E. M., D. M. Blei, S. E. Fienberg, and E. P. Xing, 2008: Mixed membership stochastic blockmodels. *The Journal of Machine Learning Research*, **9**, 1981–2014.
- [2] Berg, A., T. Berg, and M. J., 2005: Shape matching and object recognition using low distortion correspondences. *2005 IEEE Conference on Computer Vision and Pattern Recognition*, 26–33.
- [3] Bergsma, S. and B. Van Durme, 2013: Using conceptual class attributes to characterize social media users. *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 710–720.
- [4] Beveridge, J. R., 1994: Local search algorithms for geometric object recognition: Optimal correspondence and pose.
- [5] Conte, D., P. Foggia, C. Sansone, and M. Vento, 2004: Thirty years of graph matching in pattern recognition. *International Journal of Pattern Recognition and Artificial Intelligence*, **18**, no. 3, 265–298.
- [6] Coppersmith, G., 2014: Vertex nomination. *Wiley Interdisciplinary Reviews: Computational Statistics*, **6**, no. 2, 144–153.
- [7] Coppersmith, G. and C. Priebe, 2012: Vertex nomination via content and context. *arXiv preprint arXiv:1201.4118*.
- [8] Devroye, L., L. Györfi, and G. Lugosi, 2013: *A probabilistic theory of pattern recognition*, volume 31. Springer Science & Business Media.
- [9] Fabiana, C., M. Garetto, and E. Leonardi, 2015: De-anonymizing scale-free social networks by percolation graph matching. *Computer Communications (INFOCOM), 2015 IEEE Conference on*, IEEE, 1571–1579.

- [10] Fiori, M., P. Sprechmann, J. Vogelstein, P. Musé, and G. Sapiro, 2013: Robust multimodal graph matching: Sparse coding meets graph matching. *Advances in Neural Information Processing Systems*, 127–135.
- [11] Fishkind, D., S. Adali, H. Patsolic, L. Meng, D. Singh, V. Lyzinski, and C. Priebe, 2019: Seeded graph matching. *Pattern Recognition*, **87**, 203–215.
- [12] Fishkind, D., V. Lyzinski, H. Pao, L. Chen, and C. Priebe, 2015: Vertex nomination schemes for membership prediction. *The Annals of Applied Statistics*, **9**, no. 3, 1510–1532.
- [13] Foggia, P., G. Percannella, and M. Vento, 2014: Graph matching and learning in pattern recognition in the last 10 years. *International Journal of Pattern Recognition and Artificial Intelligence*, **28**, no. 1.
- [14] Frank, M. and P. Wolfe, 1956: An algorithm for quadratic programming. *Naval Research Logistics Quarterly*, **3**, 95–110, doi:10.1002/nav.3800030109.
- [15] Fukunage, K. and P. M. Narendra, 1975: A branch and bound algorithm for computing k-nearest neighbors. *IEEE transactions on computers*, no. 7, 750–753.
- [16] Gönen, M. and E. Alpaydin, 2008: Localized multiple kernel learning. *Proceedings of the 25th International Conference on Machine Learning*, ACM, New York, NY, USA, ICML '08, 352–359. URL <http://doi.acm.org/10.1145/1390156.1390201>
- [17] Ham, J., D. D. Lee, and L. K. Saul, 2005: Semisupervised alignment of manifolds. *AISTATS*, 120–127.
- [18] Holland, P. W., K. Laskey, and S. Leinhardt, 1983: Stochastic blockmodels: First steps. *Social Networks*, **5**, no. 2, 109–137.
- [19] Huang, Z., W. Chung, and H. Chen, 2004: A graph model for e-commerce recommender systems. *Journal of the American Society for information science and technology*, **55**, no. 3, 259–274.
- [20] Ji, S., W. Li, S. Yang, P. Mittal, and R. Beyah, 2016: On the relative de-anonymizability of graph data: Quantification and evaluation. *Computer Communications, IEEE INFOCOM 2016-The 35th Annual IEEE International Conference on*, IEEE, 1–9.
- [21] Kazemi, E., S. H. Hassani, and M. Grossglauser, 2015: Growing a graph matching from a handful of seeds. *Proceedings of the VLDB Endowment*, **8**, no. 10, 1010–1021.
- [22] Kazemi, E., L. Yartseva, and M. Grossglauser, 2015: When can two unlabeled networks be aligned under partial overlap? *Communication, Control, and Computing (Allerton), 2015 53rd Annual Allerton Conference on*, IEEE, 33–42.
- [23] Keller, J. M., M. R. Gray, and J. A. Givens, 1985: A fuzzy k-nearest neighbor algorithm. *IEEE transactions on systems, man, and cybernetics*, no. 4, 580–585.
- [24] Kuchaiev, O. and N. Pržulj, 2011: Integrative network alignment reveals large regions of global network similarity in yeast and human. *Bioinformatics*, **27**, no. 10, 1390–1396.
- [25] Kuhn, H., 1955: The hungarian method for the assignment problem. *Naval Research Logistics Quarterly*, **2**, 83–97, doi:10.1002/nav.3800020109.
- [26] Leordeanu, M., R. Sukthankar, and M. Hebert, 2012: Unsupervised learning for graph matching. *International Journal of Computer Vision*, **96**, no. 1, 28–45.
- [27] Leskovec, J. and A. Krevl, 2014: *SNAP Datasets: Stanford large network dataset collection*. <http://snap.stanford.edu/data>.
- [28] Li, L. and W. Campbell, 2015: Matching community structure across online social networks. *Networks NIPS*.
- [29] Lyzinski, V., D. Fishkind, M. Fiori, J. Vogelstein, C. Priebe, and G. Sapiro, 2016: Graph matching: Relax at your own risk. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, **38**, no. 1, 60–73.
- [30] Lyzinski, V., D. Fishkind, and C. Priebe, 2014: Seeded graph matching for correlated Erdős-Rényi graphs. *Journal of Machine Learning Research*, **15**, no. Nov, 3693–3720.

- [31] Lyzinski, V., K. Levin, D. E. Fishkind, and C. E. Priebe, 2016: On the consistency of the likelihood maximization vertex nomination scheme: Bridging the gap between maximum likelihood estimation and graph matching. *Journal of Machine Learning Research*, **17**, no. 179, 1–34.
- [32] Lyzinski, V., K. Levin, and C. E. Priebe, 2019: On consistent vertex nomination schemes. *Journal of Machine Learning Research*, **20**, no. 69, 1–39.
- [33] Lyzinski, V., D. L. Sussman, D. E. Fishkind, H. Pao, L. Chen, J. T. Vogelstein, Y. Park, and C. E. Priebe, 2015: Spectral clustering for divide-and-conquer graph matching. *Parallel Computing*, **47**, 70–87.
- [34] Marchette, D., C. E. Priebe, and G. Coppersmith, 2011: Vertex nomination via attributed random dot product graphs. *Proceedings of the 57th ISI World Statistics Congress*, volume 6, 16.
- [35] Mastrandrea, R., J. Fournet, and A. Barrat, 2015: Contact patterns in a high school: a comparison between data collected using wearable sensors, contact diaries and friendship surveys. *PLoS ONE*, doi:10.1371/journal.pone.0136497.
- [36] Milenkovic, T., W. Ng, W. Hayes, and N. Pržulj, 2010: Optimal network alignment with graphlet degree vectors. *Cancer Informatics*, **9**, 121.
- [37] Muja, M. and D. G. Lowe, 2009: Fast approximate nearest neighbors with automatic algorithm configuration. *VISAPP (1)*, **2**, no. 331-340, 2.
- [38] Olhede, S. C. and P. J. Wolfe, 2014: Network histograms and universality of block model approximation. *Proceedings of the National Academy of Sciences*, **111**, 14722–14727.
- [39] Page, L., S. Brin, R. Motwani, and T. Winograd, 1999: The pagerank citation ranking: Bringing order to the web. Stanford InfoLab.
- [40] Pedarsani, P., D. R. Figueiredo, and M. Grossglauser, 2013: A bayesian method for matching two similar graphs without seeds. *Communication, Control, and Computing (Allerton), 2013 51st Annual Allerton Conference on*, IEEE, 1598–1607.
- [41] Priebe, C. E., J. M. Conroy, D. J. Marchette, and Y. Park, 2005: Scan statistics on enron graphs. *Computational & Mathematical Organization Theory*, **11**, no. 3, 229–247.
- [42] Priebe, C. E., Y. Park, J. T. Vogelstein, J. M. Conroy, V. Lyzinski, M. Tang, A. Athreya, J. Cape, and E. Bridgeford, 2019: On a two-truths phenomenon in spectral graph clustering. **116**, no. 13, 5995–6000, doi:10.1073/pnas.1814462116.
- [43] Rastogi, P., V. Lyzinski, and B. Van Durme, 2017: Vertex nomination on the cold start knowledge graph. *Human Language Technology Center of Excellence: Technical report*.
- [44] Rohe, K., S. Chatterjee, and B. Yu, 2011: Spectral clustering and the high-dimensional stochastic blockmodel. *Annals of Statistics*, **39**, 1878–1915.
- [45] Sen, P., G. Namata, M. Bilgic, L. Getoor, B. Galligher, and T. Eliassi-Rad, 2008: Collective classification in network data. *AI magazine*, **29**, no. 3, 93–93.
- [46] Sermanet, P., D. Eigen, X. Zhang, M. Mathieu, R. Fergus, and Y. LeCun, 2013: Overfeat: Integrated recognition, localization and detection using convolutional networks. *arXiv preprint arXiv:1312.6229*.
- [47] Stone, C. J., 1977: Consistent nonparametric regression. *The annals of statistics*, 595–620.
- [48] Sun, M., M. Tang, and C. E. Priebe, 2012: A comparison of graph embedding methods for vertex nomination. *2012 IEEE ICMLA*, volume 1, 398–403.
- [49] Sussman, D. L., M. Tang, D. E. Fishkind, and C. E. Priebe, 2012: A consistent adjacency spectral embedding for stochastic blockmodel graphs. *Journal of the American Statistical Association*, **107**, no. 499, 1119–1128.
- [50] Suwan, S., D. S. Lee, and C. E. Priebe, 2015: Bayesian vertex nomination using content and context. *Wiley Interdisciplinary Reviews: Computational Statistics*, **7**, no. 6, 400–416.

- [51] Talukdar, P. P. and F. Pereira, 2010: Experiments in graph-based semi-supervised learning methods for class-instance acquisition. *Proceedings of the 48th annual meeting of the association for computational linguistics*, Association for Computational Linguistics, 1473–1481.
- [52] Vogelstein, J., J. Conroy, V. Lyzinski, L. Podrazik, S. Kratzer, E. Harley, D. Fishkind, R. Vogelstein, and C. Priebe, 2015: Fast approximate quadratic programming for graph matching. *PLOS one*, **10**, no. 4, e0121002.
- [53] Wang, H., M. Tang, Y. Park, and C. E. Priebe, 2013: Locality statistics for anomaly detection in time series of graphs. *IEEE Transactions on Signal Processing*, **62**, no. 3, 703–717.
- [54] Wiskott, L., N. Fellous, J-M. and Krüger, and C. Malsburg, 1997: Face recognition by elastic bunch graph matching. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, **19**, no. 7, 775–779.
- [55] Yan, J., Y. Tian, H. Zha, X. Yang, Y. Zhang, and S. Chu, 2013: Joint optimization for consistent multiple graph matching. *Proceedings of the IEEE International Conference on Computer Vision*, 1649–1656.
- [56] Young, S. J. and E. R. Scheinerman, 2007: Random dot product graph models for social networks. *International Workshop on Algorithms and Models for the Web-Graph*, Springer, 138–149.
- [57] Zaslavskiy, M., F. Bach, and J.-P. Vert, 2009: Global alignment of protein–protein interaction networks by graph matching methods. *Bioinformatics*, **25**, no. 12, i259–1267.
- [58] — 2009: A path following algorithm for the graph matching problem. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, **31**, no. 12, 2227–2242.
- [59] Zass, R. and A. Shashua, 2008: Probabilistic graph and hypergraph matching. *Computer Vision and Pattern Recognition, 2008. CVPR 2008. IEEE Conference on*, IEEE, 1–8.
- [60] Zhou, F. and F. De la Torre, 2012: Factorized graph matching. *2012 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 127–134.

AUTHOR BIOGRAPHY



Heather G. Patsolic received the BS degree in mathematics from Wingate University, in 2012, and the MA degree in mathematics from Wake Forest University, in 2014. She is currently a doctoral candidate in the Applied Mathematics and Statistics Department at Johns Hopkins University (JHU). Her research interests include statistical inference for high-dimensional and graph data, model selection, and pattern recognition.



Youngser Park received the BE degree in electrical engineering from Inha University, Seoul, Korea, in 1985, and the MS and PhD degrees in computer science from George Washington University, in 1991 and 2011, respectively. From 1998 to 2000, he worked in the Johns Hopkins Medical Institutes as a senior research engineer. From 2003 until 2011, he worked as a senior research analyst, and has been an associate research scientist since 2011 in the Center for Imaging Science, Johns Hopkins University (JHU). At JHU, he holds joint appointments in the Institute for Computational Medicine and the Human Language Technology Center of Excellence. His current research interests include clustering algorithms, pattern classification, and data mining for high-dimensional and graph

data.



Vince Lyzinski received the BSc degree in mathematics from the University of Notre Dame in 2006, the MSc degree in mathematics from Johns Hopkins University (JHU) in 2007, the MSE degree in applied mathematics and statistics from JHU in 2011, and the PhD degree in applied mathematics and statistics from JHU, in 2013. From 2013 to 2014, he was a postdoctoral fellow in the Applied Mathematics and Statistics (AMS) Department, JHU, and from 2014 to 2017, he was a senior research scientist in the JHU Human Language Technology Center of Excellence and an assistant research professor in the AMS Department, JHU. From 2017 to 2019 he was an assistant professor in the Department of Mathematics and Statistics at the University of Massachusetts,

Amherst. Since 2019 he has been an assistant professor in the Department of Mathematics at the University of Maryland, College Park. His research interests include graph matching, statistical inference on random graphs, pattern recognition, dimensionality reduction, stochastic processes, and high-dimensional data analysis.



Carey E. Priebe received the BS degree in mathematics from Purdue University in 1984, the MS degree in computer science from San Diego State University, in 1988, and the PhD degree in information technology (computational statistics) from George Mason University, in 1993. From 1985 to 1994, he worked as a mathematician and scientist in the US Navy research and development laboratory system. Since 1994, he has been a professor in the Department of Applied Mathematics and Statistics, Johns Hopkins University (JHU). At JHU, he holds joint appointments in the Department of Computer Science, Department of Electrical and Computer Engineering, Center for Imaging Science, Human Language Technology Center of Excellence, and Whitaker Biomedical Engineering Institute. His research interests include computational statistics, kernel and mixture estimates, statistical pattern recognition, statistical image analysis, dimensionality reduction, model selection, and statistical inference for high-dimensional and graph data. He is a lifetime member of the IMS, an elected member of the ISI, and a fellow of the ASA.

How to cite this article: H.G. Patsolic, Y. Park, V. Lyzinski, and C.E. Priebe (2019), Vertex Nomination via Seeded Graph Matching, *Statistical Analysis and Data Science*