

Global solvability of 1D equations of viscous compressible multi-fluids

Alexander Mamontov, Dmitriy Prokudin¹

August 25, 2017

Lavrentyev Institute of Hydrodynamics,
Siberian Branch of the Russian Academy of Sciences
pr. Lavrent'eva 15, Novosibirsk 630090, Russia

Abstract

We consider the model of viscous compressible multi-fluids with multiple velocities. We review different formulations of the model and the existence results for boundary value problems. We analyze crucial mathematical difficulties which arise during the proof of the global existence theorems in 1D case.

Keywords: existence theorem, uniqueness, unsteady boundary value problem, viscous compressible fluid, homogeneous mixture with multiple velocities

¹The research was supported by the Ministry of Education and Science of the Russian Federation (grant 14.Z50.31.0037).

Contents

1	Introduction	2
2	Mathematical model of multi-fluids	2
3	Statement of the 1D problem, formulation of the result, Lagrangian coordinates	5
4	Review of 1D viscous gas theory, strict positiveness and boundedness of the densities in the complete model (1), (2)	7
5	Open problems	9

1 Introduction

The description of the motion of multi-component media is an interesting and rather little-studied problem both in physics/mechanics and in mathematics. There is no standard approach to simulating these motions, nor is there any developed mathematical theory concerning the existence, uniqueness and properties of solutions of initial-boundary value problems arising in this simulation.

In the present paper, we choose one of the numerous versions of simulating the motion of multi-component fluid mixtures, namely, a homogeneous mixture of viscous compressible fluids and a multi-velocity model. This means that all components (constituents) of the mixture are present at any point of the space and with the same phase, and each of them has its own local velocity. The interaction between the components occurs via the viscous friction and the exchange between momenta, and also using the heat exchange (in heat-conducting models). This kind of mixtures is also called a multi-fluid, see [1] for the details.

2 Mathematical model of multi-fluids

The mathematical model of a multi-fluid which consists of $N \geq 2$ components, includes (see [2] and [3]) the continuity equations for each constituent

$$\partial_t \rho_i + \operatorname{div}(\rho_i \mathbf{u}_i) = 0, \quad i = 1, \dots, N, \quad (1)$$

the momentum equations for each constituent

$$\partial_t(\rho_i \mathbf{u}_i) + \operatorname{div}(\rho_i \mathbf{u}_i \otimes \mathbf{u}_i) + \nabla p_i - \operatorname{div} \mathbb{S}_i = \rho_i \mathbf{f}_i + \mathbf{J}_i, \quad i = 1, \dots, N, \quad (2)$$

and the energy equations. Here ρ_i is the density of the i -th constituent of the multi-fluid, \mathbf{u}_i is the velocity field, p_i is the pressure, \mathbb{S}_i is the viscous part of the stress tensor $\mathbb{P}_i = -p_i\mathbb{I} + \mathbb{S}_i$:

$$\mathbb{S}_i = \sum_{j=1}^N (\lambda_{ij}(\operatorname{div} \mathbf{u}_j)\mathbb{I} + 2\mu_{ij}\mathbb{D}(\mathbf{u}_j)), \quad i = 1, \dots, N,$$

where λ_{ij} and μ_{ij} are the viscosity coefficients, \mathbb{D} is the rate of deformation tensor, and \mathbb{I} is the identity tensor. The viscosity coefficients λ_{ij} and μ_{ij} compose the matrices $\mathbf{\Lambda} = \{\lambda_{ij}\}_{i,j=1}^N$ and $\mathbf{M} = \{\mu_{ij}\}_{i,j=1}^N$. Finally, $\mathbf{f}_i = (f_{i1}, \dots, f_{in})$ denotes the external body force (n is the dimension of the flow), and

$$\mathbf{J}_i = \sum_{j=1}^N a_{ij}(\mathbf{u}_j - \mathbf{u}_i), \quad i = 1, \dots, N, \quad a_{ij} = a_{ji}, \quad i, j = 1, \dots, N$$

stands for the momentum exchange between the constituents (the momentum supply).

The viscosity matrices in real multi-fluids take non-trivial forms and, generally speaking (see [4] for the details), they depend on the concentrations $\xi_i = \frac{\rho_i}{\rho}$, where $\rho = \sum_{i=1}^N \rho_i$ is the total density of the multi-fluid. The dependence of the viscosity matrices on the concentrations constitutes serious difficulties. We accept the simplifying assumption of constant viscosities, but with the preservation of necessary properties of positiveness. The thing is that it is very important (physically and mathematically) to validate Second law of thermodynamics which means

$$\sum_{i=1}^N \mathbb{S}_i : \mathbb{D}(\mathbf{u}_i) \geq 0. \quad (3)$$

Besides, in order to provide important mathematical property of ellipticity, it is necessary to validate the condition

$$\sum_{i=1}^N \int_{\Omega} \mathbb{S}_i : \mathbb{D}(\mathbf{u}_i) d\mathbf{x} \geq C \sum_{i=1}^N \int_{\Omega} |\nabla \otimes \mathbf{u}_i|^2 d\mathbf{x}, \quad (4)$$

where Ω is the flow domain, and $\mathbf{u}_i|_{\partial\Omega} = 0$, $i = 1, \dots, N$. The formulated positiveness or coercivity can be provided by the following properties of viscosity matrices: the properties $n\mathbf{\Lambda} + 2\mathbf{M} \geq 0$, $\mathbf{M} \geq 0$ provide (3), and the properties $\mathbf{\Lambda} + 2\mathbf{M} > 0$, $\mathbf{M} > 0$ provide (4).

A very important observation is that the viscosity matrices should not be diagonal. Momentum supply \mathbf{J}_i in the momentum equations gives lower order terms (physically important, but mathematically causing no difficulties), and if the matrices are diagonal then \mathbf{J}_i is the only connection between the constituents, so we have N Navier–Stokes systems connected only via lower order terms. Earlier such problems were relevant (even in 1D) (see, e. g., [5], [6] and [7]), but nowadays such results almost automatically come from the theory of mono-fluid systems governed by the compressible Navier–Stokes equations. If viscosity matrices are “complete” (general) then we have interesting mathematical problems (see the reviews in [1], [8] and the citations there).

The crucial problem in the multi-D flows is that an automatic extension of the theory of compressible Navier–Stokes equations to the theory of multi-fluids requires

$$\operatorname{div} \operatorname{div} \mathbb{S}_i = \operatorname{const}_i \cdot \Delta \operatorname{div} \mathbf{u}_i, \quad i = 1, \dots, N,$$

but we have

$$\begin{pmatrix} \operatorname{div} \operatorname{div} \mathbb{S}_1 \\ \dots \\ \operatorname{div} \operatorname{div} \mathbb{S}_N \end{pmatrix} = \mathbf{N} \begin{pmatrix} \Delta \operatorname{div} \mathbf{u}_1 \\ \dots \\ \Delta \operatorname{div} \mathbf{u}_N \end{pmatrix},$$

where $\mathbf{N} = \{\nu_{ij}\}_{i,j=1}^N = \{\lambda_{ij} + 2\mu_{ij}\}_{i,j=1}^N$ is the matrix of total viscosities. It is possible to obtain results in the case of triangular matrices \mathbf{N} (see, e. g., [9] and [10]). However, for a general \mathbf{N} , it is important to radically review the existing techniques developed for the compressible Navier–Stokes system. If $n = 1$ then interesting problems also appear (see below).

The authors found a way to overcome the crucial problem of total viscosity matrix structure, that is to introduce the assumptions that

- the pressures in all constituents are equal to each other,
- the velocities of the constituents in the material derivative operators are replaced by the average velocity.

Both assumptions are physically realistic in many situations (see [4] for the details), and the main mathematical effect is that the model does not lose richness inherent to the multi-fluid models (different densities and velocities of the constituent are preserved), moreover, the variety of the model grows because this trick allows to eliminate the restrictions of the viscosity matrix, and hence to admit all possible viscous terms.

As a result, we come (see [4] and [8]) to the following system of equations:

$$\partial_t \rho_i + \operatorname{div} (\rho_i \mathbf{v}) = 0, \quad i = 1, \dots, N, \quad (5)$$

$$\partial_t(\rho_i \mathbf{u}_i) + \operatorname{div}(\rho_i \mathbf{v} \otimes \mathbf{u}_i) + \alpha_i \nabla p = \operatorname{div} \mathbb{S}_i + \rho_i \mathbf{f}_i, \quad i = 1, \dots, N. \quad (6)$$

Here $\mathbf{v} = \sum_{i=1}^N \alpha_i \mathbf{u}_i$ is the average velocity of the multi-fluid, and the coef-

ficients $\alpha_i(\{\xi_j\}_{j=1}^N) > 0$ are such that $\sum_{i=1}^N \alpha_i = 1$ (for instance, $\alpha_i = \xi_i$).

Thus, the values α_i , due to their dependence on the concentrations, satisfy the equations

$$\frac{\partial \alpha_i}{\partial t} + \mathbf{v} \cdot \nabla \alpha_i = 0, \quad i = 1, \dots, N.$$

In the simplest version, α_i may be regarded as constants. The main existence results for the model (5), (6) are obtained in [11], [12], [13], [14] and [15].

To conclude the Section, let us note that the multidimensional existence theorems concern only weak solutions, whose regularity is not sufficient even for the uniqueness; smoothness increase is hindered by serious obstacles. Moreover, the difficulty of multidimensional problems eclipses the study of many qualitative properties of solutions, as well as related problems including modeling; this gives researchers the right to consider the corresponding questions first in the one-dimensional case. Hence, whereas in the solvability theory for the main boundary value problems of the viscous gas there was a shift of emphasis from the one-dimensional case to the multidimensional one already two decades ago, in many other domains of the theory, the one-dimensional problems stay at the forefront.

On the other hand, as well as in the multidimensional case, the classical one-dimensional results for mono-fluids cannot be reproduced for multi-fluids automatically, in particular, due to essentially different structure of the viscous terms, namely, the presence of non-diagonal viscosity matrices; this difference in difficulty *does not depend on the dimension of the flow*.

3 Statement of the 1D problem, formulation of the result, Lagrangian coordinates

Consider the rectangular Q_T (here and below $Q_t = (0, 1) \times (0, t)$) with an arbitrary finite height $T > 0$, and the system of equations ($i = 1, \dots, N$)

$$\partial_t \rho_i + \partial_x(\rho_i v) = 0, \quad v = \frac{1}{N} \sum_{i=1}^N u_i, \quad (7)$$

$$\rho_i (\partial_t u_i + v \partial_x u_i) + K \partial_x \rho^\gamma = \sum_{j=1}^N \mu_{ij} \partial_{xx} u_j, \quad \rho = \sum_{i=1}^N \rho_i, \quad (8)$$

with the following initial and boundary conditions ($i = 1, \dots, N$):

$$\rho_i|_{t=0} = \rho_{0i}(x), \quad u_i|_{t=0} = u_{0i}(x), \quad x \in [0, 1], \quad (9)$$

$$u_i|_{x=0} = u_i|_{x=1} = 0, \quad t \in [0, T]. \quad (10)$$

Definition 1. Refer as a *strong solution* to the problem (7)–(10) a collection of $2N$ functions $(\rho_1, \dots, \rho_N, u_1, \dots, u_N)$ such that the equations (7), (8) are valid a. e. in Q_T , the initial conditions (9) are satisfied for a. a. $x \in (0, 1)$, the boundary conditions (10) hold for a. a. $t \in (0, T)$, and the following inequalities and inclusions hold ($i = 1, \dots, N$)

$$\rho_i > 0, \quad \rho_i \in L_\infty(0, T; W_2^1(0, 1)), \quad \partial_t \rho_i \in L_\infty(0, T; L_2(0, 1)),$$

$$u_i \in L_\infty(0, T; W_2^1(0, 1)) \cap L_2(0, T; W_2^2(0, 1)), \quad \partial_t u_i \in L_2(Q_T).$$

The result is formulated as the following Theorem.

Theorem 2. *Let the initial conditions in (9) satisfy the assumptions*

$$\rho_{0i} \in W_2^1(0, 1), \quad \rho_{0i} > 0, \quad u_{0i} \in \overset{\circ}{W}_2^1(0, 1), \quad i = 1, \dots, N,$$

the symmetric viscosity matrix \mathbf{M} be positive, the adiabatic index $\gamma > 1$, the constants $K, T > 0$. Then there exists the unique strong solution to the problem (7)–(10) in the sense of Definition 1.

In the model case (when all densities are equal to each other), the proof of Theorem 2 is given in [16] and [17]. Let us comment the scheme of the proof of Theorem 2. First of all, we prove the local in time solvability of the initial boundary value problem which is obtained from (7)–(10) via the Galerkin method (with respect to the spacial variable x) in the momentum equations (8). The proof is made via the Leray–Schauder Fixed Point Theorem. Then, basing on the uniform estimates, we pass to the limit and establish the local solvability of the problem (7)–(10), i. e. on a small time interval $[0, t_0]$. In order to continue the solution over the whole interval $[0, T]$, we prove estimates in which the constants depend on the input data of the problem and on T , but not on t_0 . In conclusion, we prove the uniqueness in a standard way. The key problem in the proof of Theorem 2 is the verification of the strict positiveness and boundedness of the densities (note that this problem is the key one for the complete model (1), (2) as well). We consider this problem in more detail in Section 4.

During the study of the problem (7)–(10), the parallel use of the Lagrangian coordinates is convenient. Let us accept $y(x, t) = \int_0^x \rho(s, t) ds$ and t as new independent variables. Then the system (7), (8) takes the form

$$\partial_t \rho_i + \rho \rho_i \partial_y v = 0, \quad v = \frac{1}{N} \sum_{i=1}^N u_i,$$

$$\frac{\rho_i}{\rho} \partial_t u_i + K \partial_y \rho^\gamma = \sum_{j=1}^N \mu_{ij} \partial_y (\rho \partial_y u_j), \quad i = 1, \dots, N, \quad \rho = \sum_{i=1}^N \rho_i.$$

The domain Q_T is transformed into the rectangular $\Pi_T = (0, d) \times (0, T)$, where $d = \int_0^1 \rho_0 dx > 0$, $\rho_0 = \sum_{i=1}^N \rho_{0i}$, and the initial and boundary conditions take the form ($i = 1, \dots, N$)

$$\rho_i|_{t=0} = \tilde{\rho}_{0i}(y), \quad u_i|_{t=0} = \tilde{u}_{0i}(y), \quad y \in [0, d],$$

$$u_i|_{y=0} = u_i|_{y=d} = 0, \quad t \in [0, T].$$

4 Review of 1D viscous gas theory, strict positivity and boundedness of the densities in the complete model (1), (2)

Consider the initial boundary value problem for the 1D Navier–Stokes equations (in the Lagrangian coordinates):

$$\partial_t \rho + \rho^2 \partial_y v = 0, \tag{11}$$

$$\partial_t v + K \partial_y \rho^\gamma = \mu \partial_y (\rho \partial_y v), \tag{12}$$

$$\rho|_{t=0} = \tilde{\rho}_0, \quad v|_{t=0} = \tilde{v}_0, \quad y \in [0, d], \tag{13}$$

$$v|_{y=0} = v|_{y=d} = 0, \quad t \in [0, T]. \tag{14}$$

The first a priori estimate is obtained via the standard arguments and takes the form:

$$\|v\|_{L_\infty(0, T; L_2(0, d))} + \|\sqrt{\rho} \partial_y v\|_{L_2(\Pi_T)} + \|\rho\|_{L_\infty(0, T; L_{\gamma-1}(0, d))} \leq C. \tag{15}$$

The equation (11) allows to express $\rho \partial_y v = -\partial_t \ln \rho$ and to substitute it into (12):

$$\partial_{ty} \ln \rho + K \partial_y \rho^\gamma = -\partial_t v. \quad (16)$$

Let us multiply this equality by $\partial_y \ln \rho =: w$ and integrate over $y \in (0, d)$, then we obtain

$$\frac{1}{2} \frac{d}{dt} \left(\int_0^d w^2 dy \right) + K \gamma \int_0^d \rho^\gamma w^2 dy = - \int_0^d (\partial_t v) w dy. \quad (17)$$

The right-hand side may be transformed via integration by parts due to (16):

$$- \int_0^d (\partial_t v) w dy = - \frac{d}{dt} \left(\int_0^d v w dy \right) + \int_0^d \rho |\partial_y v|^2 dy. \quad (18)$$

Thus, after integration of (17) in t , using (18), we find that

$$\begin{aligned} & \|w\|_{L_2(0,d)}^2 + 2K\gamma \int_0^t \int_0^d \rho^\gamma w^2 dy d\tau \leq \\ & \leq \|w_0\|_{L_2(0,d)}^2 - 2 \int_0^d v w dy + 2 \int_0^d v_0 w_0 dy + 2 \int_0^t \|\sqrt{\rho} \partial_y v\|_{L_2(0,d)} d\tau, \end{aligned}$$

where $w_0 = w(0, t)$. Using Cauchy's inequality and the estimate (15), we derive

$$\|w(t)\|_{L_2(0,d)} \leq C \quad \forall t \in [0, T],$$

i. e. the norm of the derivative $\partial_y \ln \rho$ in $L_2(0, d)$ is bounded uniformly in $t \in [0, T]$.

The equation (11) and the conditions (13), (14) obviously imply that for every $t \in [0, T]$ the equality $\rho(z(t), t) = d$ holds with some $z(t) \in [0, d]$. Hence, we can use the presentation

$$\ln \rho(y, t) = \ln \rho(z(t), t) + \int_{z(t)}^y \partial_s \ln \rho(s, t) ds.$$

This leads to the fact that $|\ln \rho(y, t)| \leq |\ln d| + \sqrt{d} \|w\|_{L_2(0,d)} \leq C$, and hence

$$0 < C^{-1} \leq \rho(y, t) \leq C.$$

For the complete multi-fluid model (1), (2), difficulties appear even on the stage of introducing the Lagrangian coordinates. In fact, if the Lagrangian coordinates are related to the velocity of one constituent (as it was made in [5]), say, with the number m , then we come to the following system of equations ($i = 1, \dots, N$):

$$\partial_t \rho_i + \rho_m (u_i - u_m) \partial_y \rho_i + \rho_i \rho_m \partial_y u_i = 0,$$

$$\frac{\rho_i}{\rho_m} \partial_t u_i + \rho_i (u_i - u_m) \partial_y u_i + K \partial_y \rho^\gamma = \sum_{j=1}^N \mu_{ij} \partial_y (\rho_m \partial_y u_j) + \frac{1}{\rho_m} \sum_{j=1}^N a_{ij} (u_j - u_i).$$

The analysis of this system via 1D viscous gas technique is possible only in the case of the diagonal viscosity matrix.

For the modified multi-fluid model (7), (8), the direct application of the technique also fails. However, as we have seen, it is possible to overcome all difficulties and to obtain all necessary estimates.

5 Open problems

Let us identify several open problems in the 1D theory of viscous compressible multi-fluids:

- General model with complete viscosity matrix.
- Heat-conductive models.
- Asymptotics as $t \rightarrow +\infty$.
- Other boundary value problems.

References

- [1] A. E. Mamontov, D. A. Prokudin, *Viscous compressible multi-fluids: modeling and multi-D existence*, Methods and applications of analysis, **20**:2 (2013), 179–195.
- [2] R. I. Nigmatulin, *Dynamics of multiphase media, vol. 1*, Hemisphere, New York, 1990.
- [3] K. L. Rajagopal, L. Tao, *Mechanics of mixtures*, World Scientific Publishing, Singapore, 1995.
- [4] A. E. Mamontov, D. A. Prokudin, *Modeling viscous compressible barotropic multi-fluid flows*, arXiv:1708.07319 [math.AP], 24 Aug 2017, 13 P.
- [5] A. V. Kazhikhov, A. N. Petrov, *Well-posedness of the initial-boundary value problem for a model system of equations of a multicomponent mixture*, Dinamika sploshnoy sredy, **35** (1978), 61–73 (in Russian).
- [6] A. N. Petrov, *Well-posedness of initial-boundary value problems for one-dimensional equations of interpenetrating motion of perfect gases*, Dinamika sploshnoy sredy, **56** (1982), 105–121 (in Russian).
- [7] A. A. Zlotnik, *Uniform estimates and stabilization of solutions to equations of one-dimensional motion of a multicomponent barotropic mixture*, Mathematical notes, **58**:2 (1995), 885–889.
- [8] A. E. Mamontov, D. A. Prokudin, *Viscous compressible homogeneous multi-fluids with multiple velocities: barotropic existence theory*, arXiv:1610.05536 [math.AP], 18 Oct 2016, 14 P.
- [9] N. A. Kucher, A. E. Mamontov, D. A. Prokudin, *Stationary solutions to the equations of dynamics of mixtures of heat-conductive compressible viscous fluids*, Siberian Math. J., **53**:6 (2012), 1075–1088.
- [10] A. E. Mamontov, D. A. Prokudin, *Solubility of a stationary boundary-value problem for the equations of motion of a one-temperature mixture of viscous compressible heat-conducting fluids*, Izvestiya: Mathematics, **78**:3 (2014), 554–579.
- [11] A. E. Mamontov, D. A. Prokudin, *Solubility of initial boundary value problem for the equations of polytropic motion of multicomponent viscous compressible fluids*, Siberian Electr. Math. Reports, **13** (2016), 541–583 (in Russian).

- [12] A. E. Mamontov, D. A. Prokudin, *Solubility of steady boundary value problem for the equations of polytropic motion of multicomponent viscous compressible fluids*, Siberian Electr. Math. Reports, **13** (2016), 664–693 (in Russian).
- [13] A. E. Mamontov, D. A. Prokudin, *Solvability of the regularized steady problem of the spatial motions of multicomponent viscous compressible fluids*, Siberian Math. J., **57**:6 (2016), 1044–1054.
- [14] A. E. Mamontov, D. A. Prokudin, *Existence of weak solutions to the three-dimensional problem of steady barotropic motions of mixtures of viscous compressible fluids*, Siberian Math. J., **58**:1 (2017), 113–127.
- [15] D. A. Prokudin, M. V. Krayushkina, *Solvability of a stationary boundary value problem for a model system of the equations of barotropic motion of a mixture of compressible viscous fluids*, Journal of Applied and Industrial Mathematics, **10**:3 (2016), 417–428.
- [16] D. A. Prokudin, *Unique solvability of initial-boundary value problem for a model system of equations for the polytropic motion of a mixture of viscous compressible fluids*, Siberian Electr. Math. Reports, **14** (2017), 568–585 (in Russian).
- [17] D. A. Prokudin, *Global solvability of the initial boundary value problem for a model system of one-dimensional equations of polytropic flows of viscous compressible fluid mixtures*, Journal of Physics: Conference Series, To appear (2017).