

# Measuring the Complexity of Consciousness

Xerxes D. Arsiwalla<sup>1,2,3</sup> and Paul Verschure<sup>1,2,3,4</sup>

<sup>1</sup> Institute for Bioengineering of Catalonia, Barcelona, Spain.

<sup>2</sup> Barcelona Institute for Science and Technology, Barcelona, Spain.

<sup>3</sup> Universitat Pompeu Fabra, Barcelona, Spain.

<sup>4</sup> Institució Catalana de Recerca i Estudis Avançats (ICREA),  
Barcelona, Spain.

{x.d.arsiwalla@gmail.com}

**Abstract.** The quest for a scientific description of consciousness has given rise to new theoretical and empirical paradigms for the investigation of phenomenological contents as well as clinical disorders of consciousness. An outstanding challenge in the field is to develop measures that uniquely quantify global brain states tied to consciousness. In particular, information-theoretic complexity measures such as integrated information have recently been proposed as measures of conscious awareness. This suggests a new framework to quantitatively classify states of consciousness. However, it has proven increasingly difficult to apply these complexity measures to realistic brain networks. In part, this is due to high computational costs incurred when implementing these measures on realistically large network dimensions. Nonetheless, complexity measures for quantifying states of consciousness are important for assisting clinical diagnosis and therapy. This article is meant to serve as a lookup table of measures of consciousness, with particular emphasis on clinical applicability of these measures. We consider both, principle-based complexity measures as well as empirical measures tested on patients. We address challenges facing these measures with regard to realistic brain networks, and where necessary, suggest possible resolutions.

**Keywords:** Consciousness in the Clinic, Computational Neuroscience, Complexity Measures.

## 1 Introduction

In patients with disorders of consciousness, such as coma, locked-in syndrome or vegetative state, levels of consciousness are assessed in the clinic through a battery of behavioral tests and neurophysiological recordings. In particular, these methods are used to assess levels of wakefulness (arousal) and awareness in patients [28], [27]. Such assessments have led to a two dimensional operational definition of consciousness for clinical purposes. Assessments of awareness use behavioral and neurophysiological (fMRI or EEG) protocols in order to gauge how patients perform on various cognitive functions. Assessments of wakefulness are based on metabolic markers (if reporting is not possible) such as glucose

uptake in the brain, captured using PET scans [17]. As such a clinically-oriented definition of consciousness enables classification of closely associated states and disorders of consciousness into clusters on a bivariate scale with awareness and wakefulness on orthogonal axes. Under healthy conditions, these two levels are almost linearly correlated, as in conscious wakefulness (high arousal and high awareness) or in deep sleep (low arousal and low awareness). However, in pathological states, wakefulness without awareness can be observed in the vegetative state [28], while transiently reduced awareness is observed following seizures [16]. Patients in the minimally conscious state show intermittent and limited non-reflexive and purposeful behavior [20], [19], whereas patients with hemi-spatial neglect display reduced awareness of stimuli contralateral to the side where brain damage has occurred [30]. Given the aforementioned scales for labeling states and disorders of consciousness, the crucial question is how should one quantify awareness and wakefulness from neurophysiological data? This is particularly useful for non-communicative patients such as those in coma or states of minimal wakefulness. For this reason, several dynamical complexity measures have been developed. In this article, we first describe theoretically-grounded complexity measures and the challenges one faces when applying these measures to realistic brain data. We then outline alternative empirical approaches to classify states and disorders of consciousness. We end with a discussion on how these two approaches might inform each other.

## 2 Measures of Integrated Information

Dynamical complexity measures are designed to capture both, network topology as well as causal dynamics. The most prominent among these is integrated information, denoted as  $\Phi$ . This was first introduced in [37] and is defined as the quantity of information generated by a network as a whole, over and above that of its parts, taking into account the system's causal dynamical interactions. This reflects the intuition going back to William James that conscious states are integrated, yet diverse.  $\Phi$  seeks to operationalize this intuition in terms of complexity, stating that complexity arises from simultaneous integration and differentiation of the network's structure as well as dynamics. Differentiation refers to functional specialization of neural populations, while integration, as a complementary design principle, results in distributed coordination among neural populations. This interplay generates integrated yet diversified information believed to support cognitive and behavioral states. The earliest proposals defining integrated information were made in [37], [36] and [34]. Since then, considerable progress has been made towards the development of a normative theory as well as applications of integrated information [12], [14], [35], [1], [29], [7], [8], [26], [33], [5]. The core idea of integrated information as a whole versus parts quantity has been formalized in several distinct information measures such as neural complexity [37], causal density [32],  $\Phi$  from integrated information theory: IIT 1.0, 2.0 & 3.0 [34], [12], [29], stochastic interaction [39], [11], stochastic integrated information [14], [1], [9] and synergistic  $\Phi$  [23], [22]. **Table 1** summarizes these

measures along with corresponding information metrics upon which they have been based.

**Table 1.** Theoretical complexity measures alongside their corresponding information metrics.

<b>Integrated Information Measures</b>	<b>Information Metrics</b>
Neural Complexity	Mutual Information (MI)
Causal Density	Granger Causality (GC)
Stochastic Interaction	Kullback-Leibler Divergence (KLD)
IIT 1.0 & 2.0	KLD
Stochastic Integrated Information	MI or KLD
IIT 3.0	Earth Mover’s Distance
Synergistic $\Phi$	Synergistic Information

However, computing integrated information for large neurophysiological datasets has been challenging due to both, computational difficulties and limits on domains where these measures can be implemented. For instance, many of these measures use the minimum information partition of the network. This involves evaluating a large number of network configurations (more precisely, the Bell number), which makes their computational cost extremely high for large networks. As for domains of applicability, the measure of [12] has been formulated for discrete-state, deterministic, Markovian systems with the maximum entropy distribution. On the other hand, the measure of [14] has been devised to continuous-state, stochastic, non-Markovian systems and in principle, admits dynamics with any empirical distribution (although in practice, it is easier to use assuming Gaussian distributions). The formulation in [14] is based on mutual information, whereas [12] uses a measure based on the Kullback-Leibler divergence. Note however, that in some cases the measure of [14] can take negative values and that complicates its interpretation. The Kullback-Leibler based definition computes the information generated during state transitions and remains positive in the regime of stable dynamics. This gives it a natural interpretation as an integrated information measure. Both measures [12], [14] make use of a normalization scheme in their formulations. Normalization inadvertently introduces ambiguities in computations. The normalization is actually used for the purpose of determining the partition of the network that minimizes the integrated information, but a normalization dependent choice of partition ends up influencing the value and interpretation of  $\Phi$ . An alternate measure based on the Earth Mover’s distance was proposed in [29]. This does away with the normalization problem (though the current version is not formulated for continuous-state variables). However, the formulation of [29] lies outside the scope of standard information theory and is still difficult for performing computations on large networks.

More recently, these issues have been addressed in [9], using a formulation of stochastic integrated information based on the Kullback-Leibler divergence

between the conditional multivariate distribution on the set of network states versus the corresponding factorized distribution over its parts, while implementing the maximum information partition instead of the minimum information partition. Using this formulation,  $\Phi$  can be computed for large-scale networks with linear stochastic dynamics, for both, attractor as well as non-stationary states [9] (for network simulations see [2], [3], [10]). This work also demonstrated the first computation of  $\Phi$  for the resting-state human brain connectome. The connectome network is estimated from cortical white matter tractography data, comprising 998 voxels (nodes) with approximately 28,000 weighted symmetric connections [24]. [9] show that the dynamics and topology of the healthy resting-state brain generates greater information complexity than a (weight-preserving) random rewiring of the same network. Even though this formulation of stochastic integrated information was successfully implemented for the human cerebral connectome, a network of 998 nodes and about 28,000 edges, it was limited to linearized dynamics. This is well-defined in the vicinity of attractor states such as the resting-state, however, it would be desirable to extend this formulation to include non-linearities existing in brain dynamics.

### 3 Empirical Measures

Ideally, integrated information was intended as a measure of awareness, one that could account for informational differences between states and also disorders of consciousness. However, as described above, for realistic brain dynamics and physiological data that task has in fact proven difficult. On the other hand, the basic conceptualization of consciousness in terms of integration and differentiation of causal information has motivated several empirical measures that seek to classify consciousness-related disorders from patient data. For example, [13] investigated changes in conscious levels using Granger Causality (GC) as a causal connectivity measure. Given two stationary time-series signals, Granger Causality measures the extent to which the past of one assists in predicting the future of the other, over and above the extent to which the past of the latter already predicts its own future [21], thus quantifying causal relations between two signaling sources. This was tested using electroencephalographic (EEG) data from subjects undergoing propofol-induced anesthesia, with signals source-localized to the anterior and posterior cingulate cortices. [13] found a significant increases in bidirectional GC in most subjects during loss of consciousness, especially in the beta and gamma frequency ranges. Another useful measure of causal connectivity is transfer entropy, which extends Granger causality to the non-Gaussian case. However, so far this has only been implemented on neuronal cultures by [40] and holds future potential as a clinically relevant measure. Yet another measure that has already proven useful as a clinical classifier of conscious levels is the Perturbational Complexity Index (PCI), which was introduced by [18] and tested on TMS-evoked potentials measured with EEG. PCI is calculated by perturbing the cortex with transcranial magnetic stimulation (TMS) in order to engage distributed interactions in the brain and then compressing the

resulting spatiotemporal EEG responses to measure their algorithmic complexity, based on the Lempel-Ziv compression. For a given segment of EEG data, the Lempel-Ziv algorithm quantifies complexity by counting the number of distinct patterns in the data. For example, this can be proportional to the size of a computer file after applying a data compression algorithm. Computing the Lempel-Ziv compressibility requires binarizing the time-series data, based either on event-related potentials or with respect to a given threshold. Using PCI, [18] were able to discriminate levels of consciousness during wakefulness, sleep, and anesthesia, as well as in patients who had emerged from coma and recovered a minimal level of consciousness. Later, the Lempel-Ziv complexity was also used by [31] on spontaneous high-density EEG data recorded from subjects undergoing propofol-induced anesthesia. Once again, a robust decline in complexity was observed during anesthesia. These are complexity measures based on data compression algorithms. A qualitative comparison between a data compression measure inspired by PCI and  $\Phi$  was made in [38]. While compression-based measures do seem to capture certain aspects of  $\Phi$ , the exact relationship between the two is not completely clear. Nonetheless, these empirical measures have been useful for clinical purposes, in terms of broadly discriminating disorders of consciousness. Another relevant complexity measure is the weighted symbolic mutual information (wSMI), introduced by [25]. This is a measure of global information sharing across brain areas. It evaluates the extent to which two EEG channels present nonrandom joint fluctuations, suggesting that they share common sources. This is done by first transforming continuous signals into discrete symbols, and subsequently computing the joint probabilities of symbol pairs between two EEG channels. Before computing the symbolic mutual information between two time-series signals, a weighting is introduced to disregard conjunctions of identical or opposite-sign symbols from the two signal trains as that could potentially arise from common-source artifacts. In [25] wSMI was estimated for 181 EEG recordings from awake but noncommunicating patients diagnosed in various disorders of consciousness (including 143 from patients in vegetative and minimally conscious states). This measure of information sharing was found to systematically increase with consciousness. In particular, it was able to distinguish patients in the vegetative state, minimally conscious state, and fully conscious state. In **Table 2** we summarize the above empirical measures along with their domains of application.

## 4 Discussion

The paradigm-shifting proposal that consciousness might be measurable in terms of the information generated by causal dynamics of the brain as a whole, over the sum of its parts, has led to precise quantitative formulations of information-theoretic complexity measures. These measures seek to operationalize the intuition that the complexity associated to consciousness arises from simultaneous integration and differentiation of the brain's structural and dynamical hierarchies. However, progress in this direction has faced practical challenges such

**Table 2.** Empirical complexity measures alongside their tested domains of application.

Empirical Measures	Tested Application Domains
Granger Causality	Wakefulness vs propofol-induced anesthesia using EEG
Perturbational Complexity Index	Wakefulness, sleep, anesthesia, coma & minimal consciousness using TMS-evoked EEG
Lempel-Ziv Complexity	Wakefulness vs propofol-induced anesthesia using EEG
Weighted Symbolic Mutual Information	Vegetative, minimally conscious & fully conscious states using EEG

as high computational cost upon scaling with network size. This is especially true with regard to realistic neuroimaging or physiological datasets. Even in the approach of [9], where both, the scaling and normalization problem have been solved, the formulation is still applicable only to linear dynamical systems. A possible way to extend this formulation to non-linear systems such as the brain might be to first solve the Fokker-Planck equations for these systems (as probability distributions will no longer remain Gaussian) and subsequently estimate entropies and conditional entropies numerically to compute  $\Phi$ . Another solution to the problem might be to construct statistical estimators for the covariance matrices from data and then compute  $\Phi$ .

In the meanwhile, for clinical purposes, it has been useful to consider empirical complexity measures, which serve as classifiers that very broadly discriminate states of consciousness, such as between wakefulness and anesthesia or broadly between disorders of consciousness. However, these measures do not strictly correspond to integrated information. Some of them are based on signal compression, which does capture differentiation, though not directly integration. So far these methods have been applied on the scale of EEG datasets. One has yet to demonstrate their computational feasibility for larger datasets (which might only be a matter of time though). All in all, bottom-up approaches suggest important features that might help inform or constrain implementations of principle-based approaches. However, the latter are indispensable for ultimately understanding causal aspects of information generation and flow in the brain.

This article is intended as a lookup table spanning the landscape of both, theoretically-motivated as well as empirically-based complexity measures used in current consciousness research. Even though, for the purpose of this article, we have treated complexity as a global correlate of consciousness, there are indications that multiple complexity types, based on cognitive and behavioral control, might be important for a more precise classification of various states of consciousness [15], [6]. This latter observation alludes to the need for an integrative systems approach to consciousness research, one that is grounded in cognitive architectures and helps understand control mechanisms underlying systems level neural information processing [4].

**Acknowledgments.** This work has been supported by the European Research Council’s CDAC project: ”The Role of Consciousness in Adaptive Behavior: A Combined Empirical, Computational and Robot based Approach” (ERC-2013-ADG 341196).

## References

1. Arsiwalla, X.D., Verschure, P.F.M.J.: Integrated information for large complex networks. In: The 2013 International Joint Conference on Neural Networks (IJCNN). pp. 1–7 (Aug 2013)
2. Arsiwalla, X.D., Betella, A., Bueno, E.M., Omedas, P., Zucca, R., Verschure, P.F.: The dynamic connectome: A tool for large-scale 3d reconstruction of brain activity in real-time. In: ECMS. pp. 865–869 (2013)
3. Arsiwalla, X.D., Dalmazzo, D., Zucca, R., Betella, A., Brandi, S., Martinez, E., Omedas, P., Verschure, P.: Connectomics to semantomics: Addressing the brain’s big data challenge. *Procedia Computer Science* 53, 48–55 (2015)
4. Arsiwalla, X.D., Herreros, I., Moulin-Frier, C., Sanchez, M., Verschure, P.F.: Is Consciousness a Control Process?, pp. 233–238. IOS Press, Amsterdam (2016)
5. Arsiwalla, X.D., Mediano, P.A., Verschure, P.F.: Spectral modes of network dynamics reveal increased informational complexity near criticality. *Procedia Computer Science* 108, 119–128 (2017)
6. Arsiwalla, X.D., Moulin-Frier, C., Herreros, I., Sanchez-Fibla, M., Verschure, P.F.: The morphospace of consciousness. *arXiv preprint arXiv:1705.11190* (2017)
7. Arsiwalla, X.D., Verschure, P.: *Computing Information Integration in Brain Networks*, pp. 136–146. Springer International Publishing, Cham, Switzerland (2016)
8. Arsiwalla, X.D., Verschure, P.F.M.J.: High Integrated Information in Complex Networks Near Criticality, pp. 184–191. Springer International Publishing, Cham, Switzerland (2016)
9. Arsiwalla, X.D., Verschure, P.F.: The global dynamical complexity of the human brain network. *Applied Network Science* 1(1), 16 (2016)
10. Arsiwalla, X.D., Zucca, R., Betella, A., Martinez, E., Dalmazzo, D., Omedas, P., Deco, G., Verschure, P.: Network dynamics with brainx3: A large-scale simulation of the human brain network with real-time interaction. *Frontiers in Neuroinformatics* 9(2) (2015)
11. Ay, N.: Information geometry on complexity and stochastic interaction. *Entropy* 17(4), 2432–2458 (2015)
12. Balduzzi, D., Tononi, G.: Integrated information in discrete dynamical systems: motivation and theoretical framework. *PLoS Comput Biol* 4(6), e1000091 (2008)
13. Barrett, A.B., Murphy, M., Bruno, M.A., Noirhomme, Q., Boly, M., Laureys, S., Seth, A.K.: Granger causality analysis of steady-state electroencephalographic signals during propofol-induced anaesthesia. *PloS one* 7(1), e29072 (2012)
14. Barrett, A.B., Seth, A.K.: Practical measures of integrated information for time-series data. *PLoS Comput Biol* 7(1), e1001052 (2011)
15. Bayne, T., Hohwy, J., Owen, A.M.: Are there levels of consciousness? *Trends in cognitive sciences* 20(6), 405–413 (2016)
16. Blumenfeld, H.: Impaired consciousness in epilepsy. *The Lancet Neurology* 11(9), 814–826 (2012)

17. Bodart, O., Gosseries, O., Wannez, S., Thibaut, A., Annen, J., Boly, M., Rosanova, M., Casali, A.G., Casarotto, S., Tononi, G., et al.: Measures of metabolism and complexity in the brain of patients with disorders of consciousness. *NeuroImage: Clinical* 14, 354–362 (2017)
18. Casali, A.G., Gosseries, O., Rosanova, M., Boly, M., Sarasso, S., Casali, K.R., Casarotto, S., Bruno, M.A., Laureys, S., Tononi, G., et al.: A theoretically based index of consciousness independent of sensory processing and behavior. *Science translational medicine* 5(198), 198ra105–198ra105 (2013)
19. Giacino, J.T.: The vegetative and minimally conscious states: consensus-based criteria for establishing diagnosis and prognosis. *NeuroRehabilitation* 19(4), 293–298 (2004)
20. Giacino, J.T., Ashwal, S., Childs, N., Cranford, R., Jennett, B., Katz, D.I., Kelly, J.P., Rosenberg, J.H., Whyte, J., Zafonte, R., et al.: The minimally conscious state definition and diagnostic criteria. *Neurology* 58(3), 349–353 (2002)
21. Granger, C.W.: Investigating causal relations by econometric models and cross-spectral methods. *Econometrica: Journal of the Econometric Society* pp. 424–438 (1969)
22. Griffith, V.: A principled infotheoretic  $\phi$ -like measure. arXiv preprint arXiv:1401.0978 (2014)
23. Griffith, V., Koch, C.: Quantifying Synergistic Mutual Information, pp. 159–190. Springer Berlin Heidelberg, Berlin, Heidelberg (2014), [http://dx.doi.org/10.1007/978-3-642-53734-9\\_6](http://dx.doi.org/10.1007/978-3-642-53734-9_6)
24. Hagmann, P., Cammoun, L., Gigandet, X., Meuli, R., Honey, C.J., Wedeen, V.J., Sporns, O.: Mapping the Structural Core of Human Cerebral Cortex. *PLoS Biology* 6(7), 15 (2008)
25. King, J.R., Sitt, J.D., Faugeras, F., Rohaut, B., El Karoui, I., Cohen, L., Naccache, L., Dehaene, S.: Information sharing in the brain indexes consciousness in noncommunicative patients. *Current Biology* 23(19), 1914–1919 (2013)
26. Krohn, S., Ostwald, D.: Computing integrated information. arXiv preprint arXiv:1610.03627 (2016)
27. Laureys, S.: The neural correlate of (un) awareness: lessons from the vegetative state. *Trends in cognitive sciences* 9(12), 556–559 (2005)
28. Laureys, S., Owen, A.M., Schiff, N.D.: Brain function in coma, vegetative state, and related disorders. *The Lancet Neurology* 3(9), 537–546 (2004)
29. Oizumi, M., Albantakis, L., Tononi, G.: From the phenomenology to the mechanisms of consciousness: integrated information theory 3.0. *PLoS Comput Biol* 10(5), e1003588 (2014)
30. Parton, A., Malhotra, P., Husain, M.: Hemispatial neglect. *Journal of Neurology, Neurosurgery & Psychiatry* 75(1), 13–21 (2004)
31. Schartner, M., Seth, A., Noirhomme, Q., Boly, M., Bruno, M.A., Laureys, S., Barrett, A.: Complexity of multi-dimensional spontaneous eeg decreases during propofol induced general anaesthesia. *PloS one* 10(8), e0133532 (2015)
32. Seth, A.K.: Causal connectivity of evolved neural networks during behavior. *Network: Computation in Neural Systems* 16(1), 35–54 (2005)
33. Tegmark, M.: Improved measures of integrated information. arXiv preprint arXiv:1601.02626 (2016)
34. Tononi, G.: An information integration theory of consciousness. *BMC neuroscience* 5(1), 42 (2004)
35. Tononi, G.: Integrated information theory of consciousness: an updated account. *Arch Ital Biol* 150(2-3), 56–90 (2012)



36. Tononi, G., Sporns, O.: Measuring information integration. *BMC neuroscience* 4(1), 31 (2003)
37. Tononi, G., Sporns, O., Edelman, G.M.: A measure for brain complexity: relating functional segregation and integration in the nervous system. *Proceedings of the National Academy of Sciences* 91(11), 5033–5037 (1994)
38. Virmani, M., Nagaraj, N.: A compression-complexity measure of integrated information. *arXiv preprint arXiv:1608.08450* (2016)
39. Wennekers, T., Ay, N.: Stochastic interaction in associative nets. *Neurocomputing* 65, 387–392 (2005)
40. Wibral, M., Vicente, R., Lindner, M.: *Transfer Entropy in Neuroscience*, pp. 3–36. Springer Berlin Heidelberg, Berlin, Heidelberg (2014)