A simulation comparison of tournament designs for the World Men's Handball Championships

László Csató*

Institute for Computer Science and Control, Hungarian Academy of Sciences (MTA SZTAKI) Laboratory on Engineering and Management Intelligence, Research Group of Operations Research and Decision Systems

> Corvinus University of Budapest (BCE) Department of Operations Research and Actuarial Sciences

> > Budapest, Hungary

17th July 2022

Wo es auch kein System, keinen Wahrheitsapparat gibt, da gibt es doch eine Wahrheit, und diese wird dann meistens nur durch ein geübtes Urteil und den Takt einer langen Erfahrung gefunden. Gibt also die Geschichte hier keine Formeln, so gibt sie doch hier wie überall Übung des Urteils.¹

(Carl von Clausewitz: Vom Kriege)

Abstract

The study aims to compare different designs for World Men's Handball Championships. This event, organised in every two years, has adopted four hybrid formats consisting of knockout and round-robin stages in recent decades, including a change of design between the two recent championships in 2017 and 2019. They are evaluated under two seeding policies with respect to various outcome measures through Monte-Carlo simulations. We find that the ability to select the strongest competitors as the winner is not necessarily a monotonic function of the number of matches played, the most frugal format is the second best with respect to efficacy, making it a good compromise in this unavoidable trade-off. A possible error is identified in a particular design. The relative performance of the formats is independent of the

^{*} e-mail: laszlo.csato@uni-corvinus.hu

¹ "Where neither system nor any dogmatic apparatus can be found, there may still be truth, and this truth will then, in most cases, only be discovered by a practised judgment and the tact of long experience. Therefore, even if history does not here furnish any formula, we may be certain that here as well as everywhere else, it will give us *exercise for the judgment*." (Source: Carl von Clausewitz: *On War*, Book 6, Chapter 30 – Defence of a Theatre of War (continued): When no Decision is Sought for. Translated by Colonel James John Graham, London, N. Trübner, 1873. http://clausewitz.com/readings/OnWar1873/TOC.htm)

seeding rules and the competitive balance of the teams. It is shown that the recent reform has increased the probability of winning for the top teams. Our results have useful implications for organisers of hybrid tournaments.

JEL classification number: C44, C63, Z20

MSC class: 62F07, 68U20

Keywords: OR in sports; tournament design; simulation; handball

Contents

1	Intr	oduction	4
2	Met	thodology	6
	2.1	Tournament designs	6
		2.1.1 One group stage with 6 teams per group (KO)	7
		2.1.2 Two group stages with 6 and 4 teams per group $(G64)$	7
		2.1.3 Two group stages with 6 and 6 teams per group $(G66)$	7
		2.1.4 Two group stages with 4 and 6 teams per group $(G46)$	8
		2.1.5 Round-robin (RR)	8
		2.1.6 Seeding	8
	2.2	Tournament metrics	8
	2.3	Simulation procedure	9
		2.3.1 Playing abilities	9
		2.3.2 Technical details	9
3	The	e comparison of tournament designs	10
	3.1	Match distribution	11
	3.2	Main results	12
	3.3	Sensitivity analysis	14
4	Disc	cussion	16
Ac	cknow	wledgements	19
Re	eferei	nces	19
A	ppen	dix	23

List of Tables

1	Tournament designs of the recent IHF World Men's Handball Championships	
	with 24 teams	7
2	Estimates of some tournament metrics for all designs (baseline model)	15
3	Sensitivity analysis for parameter α – Estimates of some tournament metrics	15
4	Sensitivity analysis for parameter β – Estimates of some tournament metrics	16

List of Figures

1	The probability that team i beats its opponent \ldots \ldots \ldots \ldots \ldots \ldots	10
2	The distribution of matches played in different tournament designs	11
3	Dependence of some tournament metrics on the number of iterations	12
4	The probability that one of the best p teams wins the tournament $\ldots \ldots \ldots$	13
5	The probability difference that one of the best p teams wins the tournament,	
	compared to a round-robin tournament with 24 teams	14
6	The probability that at least one of the best p teams plays in the final	14
7	Winning percentage for certain teams	18
A.1	Format KO , which was used in the 2017 World Men's Handball Championship .	23
A.2	Format $G64$, which was used in the 2003 World Men's Handball Championship .	24
A.3	Format G66, which was used in the 2011 World Men's Handball Championship,	
	and again in the 2019 World Men's Handball Championship	25
A.4	Format $G46$, which was used in the 2007 World Men's Handball Championship .	26
A.5	Sensitivity analysis – The probability difference that one of the best p teams wins	
	the tournament, compared to a round-robin tournament with 24 teams	27
A.6	Sensitivity analysis – The probability that at least one of the best p teams $plays$	
	in the final	28

1 Introduction

Finding the optimal design of sports tournaments is an important question of scientific research (Szymanski, 2003). Ignoring the assignment of referees (Alarcón et al., 2014; Atan and Hüseyinoğlu, 2017) – who may be biased, for example, towards the home team (Garicano et al., 2005) –, organisers and sport governing bodies have supposedly no influence on match outcomes. However, they can certainly choose other characteristics of a tournament, including its format (Scarf et al., 2009; Scarf and Yusof, 2011; Guyon, 2017), the schedule of individual matches (Ribeiro, 2012; Atan and Hüseyinoğlu, 2017; Durán et al., 2017), the seeding policy (Guyon, 2015; Laliena and López, 2018), and the progression rules (Dagaev and Sonin, 2017; Vong, 2017; Csató, 2018b,d,c,e).

The current paper considers tournament designs as probabilistic mechanisms that select high-quality alternatives (players or teams) in a noisy environment (Ryvkin, 2010). Operational Research (OR) can play a prominent role here by analysing the effects of competition structures on particular aspects of the sporting event: given a particular metric as an objective, and respecting design constraints, it becomes possible to choose the most favourable version.

In sports involving pairwise matches, there are two fundamental tournament formats (Scarf et al., 2009). The first is the *knockout* tournament where matches are played in rounds such that the winners play against each other in the next round, while the losers are immediately eliminated from the tournament. The sole remaining player, the winner of the final gets the first prize. The second basic design is the *round-robin* tournament where every competitor plays every other such that they earn points based on their number of wins, draws, and losses. The winner is the team with the greatest point score. All other designs can be considered as variations, such as the *double elimination* (McGarry and Schutz, 1997; Stanton and Williams, 2013), the *Swiss system* (Appleton, 1995; Csató, 2013, 2017), and hybrids like the FIFA World Cup or the UEFA Champions League in association football.

Tournament success measures can be defined in a relatively straightforward way. On the other hand, the identification of design constraints is usually more difficult because they are rarely communicated by the administrators. The only plausible assumption seems to be that a format already used for a given tournament remains feasible in the future. However, it does not help much when the tournament receives a modification to its structure only in parallel with the number of competitors changes. For example, FIFA World Cup was expanded to 24 teams in 1982, then to 32 in 1998, while the 2026 World Cup will have 48 finalist teams, but its format has remained the same for the same number of teams in these years. Similarly, the biannual European Men's and Women's Handball Championships started with 12 teams in 1994, and were expanded to 16 teams in 2002, but were organised according to the same format for a given number of competitors. It means that suggesting a new design has not much practical value unless it dominates the one applied in the real-world in (almost) every respect.

In contrast, a number of high profile events have received a regular modification to their structure. We will analyse here a probably unique example, the IHF World Men's Handball Championship. This event is held in every two years since 1993 and is one of the most important and prestigious championships for men's handball national teams along Olympic games and EHF European Men's Handball Championship: handball is most popular in the countries of continental Europe, which have won all medals but one in the World Men's Championships. Attendance of the Championship in 2017, hosted by France, was over 500,000, or more than 6,500 per match.

The number of qualified teams is fixed at 24 since 1995, but the tournament format has changed several times over the last two decades. Between 1995 and 2001 (four events), there were group games in the preliminary round, followed by a knockout stage. This format was used again between 2013 and 2017 (three events). However, there were two subsequent group stages between 2003 and 2011 (five events), in three different variants, one of them returning in 2019. Consequently, there are four tournament structures that have been implemented in recent years, including a change between the two recent tournaments, which indicates that the organisers experiment with finding the best design, and gives an extraordinary opportunity to compare them with the tools of OR.

It is clear that such complex designs, consisting of knock-out and round-robin stages, can be analysed only via Monte-Carlo simulations. Academic literature has made several attempts to address similar problems. Scarf et al. (2009) propose a number of tournament metrics and describe how they may be evaluated for a particular design. The authors use the UEFA Champions League to illustrate their methodology. Scarf and Yusof (2011) extend this investigation by considering the effect of the seeding policy on outcome uncertainty while taking competitive balance into account. Goossens et al. (2012) examine four league formats that have been considered by the Royal Belgian Football Association. Lasek and Gagolewski (2015) compare the recently introduced competition format for the top association football division in Poland to the standard double round-robin structure. Yusof et al. (2016) develop a system called as 'E-compare of Soccer Tournament Structures' to assist decision makers in determining the fairest design for association football tournaments. Dagaev and Rudyak (2016) assess a recent reform of the seeding system in the UEFA Champions League. Csató (2018a) evaluates an alternative of the traditional multi-stage tournament design through the example of the EHF Champions League, the most prestigious men's handball club competition in Europe. Lasek and Gagolewski (2018) examine the efficacy of league formats in ranking football teams and find that the performance of formats consisting of round-robin stages mainly depends on the total number of matches played.

Most of these papers use specific models for simulating match results, however, we want to avoid the use of such sophisticated assumptions to compare the different tournament formats for a number of reasons. First, we follow general works on the efficacy of sports tournaments applying this choice (Appleton, 1995; McGarry and Schutz, 1997). Second, at least according to our knowledge, there exists no particular prediction model fitted to handball results, contrary to the variety of methods making a good prediction on the outcome of a single match between two football teams (Maher, 1982; Dixon and Coles, 1997; Koning et al., 2003). The main difficulty is probably that handball is a fast, dynamic and high-scoring game, where professional teams now typically score between 20 and 35 goals each, therefore the technical analysis of a handball match poses a serious challenge (Bilge, 2012; Gruić et al., 2007). According to Dumangane et al. (2009), the dynamics of handball matches violate both independence and identical distribution, in some cases having a non-stationary behaviour. Furthermore, some tournament designs analysed here have been applied only once, so the lack of historical data prevents fitting a specific prediction model. Third, Krumer et al. (2017) prove that in round-robin tournaments among three or four symmetric contestants, there is a first-mover advantage driven by strategic effects arising from the subgame perfect equilibrium, while Krumer and Lechner (2017) give an empirical proof of this finding. Since all of our designs contain at least one group stage, even the schedule of the matches may influence the outcome of the tournament.

To summarize, exact modelling of handball matches organised in such complicated hybrid designs seems to be beyond the current knowledge of the academic community. However, our intention is only to compare the tournament formats, and not to estimate the chance of winning, hence a number of models within reason could be taken to determine the winners (Appleton, 1995). Nonetheless, this implies that all calculations are for comparative purposes only.

The main contribution and novelty of our research is the analysis of a particular – but by no means marginal – handball tournament by simulations, which has received several modifications to its format recently, so the organisers are probably uncertain on its appropriate design. While the choice of tournament format is driven by a number of factors (Szymanski, 2003; Wright, 2009, 2014), we focus on its 'fairness' in the sense of its accuracy in ranking competitors according to their true abilities. Consequently, a design will be said being more *efficacious* if it is better in reproducing the pre-tournament ranking of the teams, and guarantees a higher probability of winning for the best team, furthermore, the expected quality and outcome uncertainty of the final is higher.

We have some surprising findings, for example, the ability to select the strongest competitors as the winner is not a monotonic function of the number of matches played: the most frugal design is the second best with respect to efficacy, hence it seems to be a good compromise in the unavoidable trade-off. This is mainly caused by the smaller groups of four teams instead of six in the first round-robin stage, a suggestion is worth further consideration. Our calculations also reveal that the recent format change of the World Men's Handball Championship has increased the probability of winning for the top teams.

In short, the results will have useful implications for hybrid tournaments that are applied in several sports such as basketball, handball, and volleyball, some of them are presented at the end of the paper.

The paper is structured as follows. Section 2 describes the tournament designs, the metrics used for the comparison of different formats, and the simulation experiment. The results and their sensitivity analysis are detailed in Section 3. Finally, Section 4 discusses our main findings and concludes.

2 Methodology

For the comparison of different tournament designs, it is necessary to use simulation as historical data are limited: it will turn out that some formats were applied only once.

2.1 Tournament designs

The IHF World Men's Handball Championships have been organised with 24 participating teams in four fundamentally different designs in recent decades. Our investigation is restricted to these tournament formats in order to avoid the question of whether the suggested design can be implemented in practice.

Each format contains one or two group stages. Groups are round-robin tournaments with all teams playing once against any other teams in their group. In the case of two group stages, results of the matches played in the preliminary round between teams of the same main round groups are carried over to the main round (Csató, 2018c).

Organisers provide a strict final ranking at the end of the tournament, meaning that usually there are some further matches played by the teams already eliminated. We focus on the first four places, our stylized model contains only a third-place game played between the two losers of the semifinals, similarly to the actual tournaments. Note that there were no playoffs for the 5-8th place in the 2013 and 2017 World Men's Handball Championships.

		Prel	iminary r	ound	Μ	ain round	ł
Format	Year(s) of application	Gr.	Teams	Q	Gr.	Teams	Q
KO	1995-2001, 2013-2017	4	6	4	k	Knockout	
G64	2003	4	6	4	4	4	1
G66	2005, 2009-2011, 2019-	4	6	3	2	6	2
G46	2007	6	4	2	2	6	4

Table 1: Tournament designs of the recent IHF WorldMen's Handball Championships with 24 teams

Notes: Gr. = Number of groups in the preliminary and main round, respectively; Teams = Number of teams in each group of the preliminary and main round, respectively; Q = Number of teams qualified from each group of the preliminary and main round, respectively

In the following, we present the designs that have been used recently in the World Men's Handball Championships. Table 1 and Figures A.1-A.4 of the Appendix provide an overview of them.

2.1.1 One group stage with 6 teams per group (KO)

This design, presented in Figure A.1, has been used in the World Men's Handball Championships between 1995 and 2001 as well as between 2013 and 2017. It contains one group stage with four groups of six teams each such that the top four teams qualify for the round of 16 (see Figure A.1a), where a standard knockout stage starts (see Figure A.1b).

2.1.2 Two group stages with 6 and 4 teams per group (G64)

This design, presented in Figure A.2, has been used in the 2003 World Men's Handball Championship, hosted by Portugal. It contains two group stages (see Figure A.2a). The preliminary round consists of four groups of six teams each such that the top four teams qualify for the main round. The main round consists of four groups of four teams each such that two teams in each main round group are from the same preliminary round group, the first and the third, or the second and the fourth. Therefore, all teams play two further matches in the main round. Only the top team of main round groups qualifies for the semifinals in the knockout stage (see Figure A.2b).

2.1.3 Two group stages with 6 and 6 teams per group (G66)

This design, presented in Figure A.3, has been used first in the 2005 World Men's Handball Championship and has been applied in 2009, 2011, and 2019. It contains two group stages (see Figure A.3a). The preliminary round consists of four groups of six teams each such that the top three teams qualify for the main round. The main round consists of two groups of six teams, each created from two preliminary round groups. Therefore, all teams play three further matches in the main round. The top two teams of every main round group advance to the semifinals in the knockout stage (see Figure A.3b).

2.1.4 Two group stages with 4 and 6 teams per group (G46)

This design, presented in Figure A.4, has been used in the 2007 World Men's Handball Championship, hosted by Germany. It contains two group stages (see Figure A.4a). Teams are drawn into six groups of four teams each in the preliminary round such that the top two teams proceed to the main round. The main round consists of two groups, each created from three preliminary round groups. Therefore, all teams play four further matches in the main round. Four teams of every main round group advance to the quarterfinals in the knockout stage (see Figure A.4b).

2.1.5 Round-robin (RR)

While the 24 competitors have never played a round-robin tournament, we use this basic format as a reference.

2.1.6 Seeding

Seeding plays an important role in knockout tournaments (Hwang, 1982; Schwenk, 2000; Marchand, 2002; Groh et al., 2012; Karpov, 2016; Dagaev and Suzdaltsev, 2018). It is not an issue in our case since the knockout stage of all formats is immediately determined by the previous group stage (see Figures A.1-A.4). However, all participants should be drawn into groups before the start of the tournament, and this policy may influence the outcome, too (Guyon, 2015; Dagaev and Rudyak, 2016; Guyon, 2017; Laliena and López, 2018).

In the recent World Men's Handball Championships, the pots were determined on the basis of geography and other aspects such as qualification results. For example, in the 2009 tournament, Pot 1 contained the host (Croatia), the defending World Champions (Germany), the champions of Europe (Denmark), and the third-placed team of the recent European Championship (France), where Croatia and Germany were the second- and fourth-placed teams, respectively.

We consider two variants of each tournament design called *seeded* and *unseeded*. In the seeded version, the preliminary round groups are seeded such that in the case of k groups (k = 6 for design G46 and k = 4 otherwise), the strongest k teams are placed in Pot 1, the next strongest k teams in Pot 2, and so on. Unseeded version applies fully random seeding. In this case, some strong teams, allocated in a harsh group, may have more difficulties in qualifying than other weaker teams, allocated in an easier group, which can be regarded as unfair. Naturally, there is no need to seed the teams in the reference format RR.

2.2 Tournament metrics

Following the literature (Horen and Riezman, 1985; Scarf et al., 2009; Dagaev and Rudyak, 2016), we have chosen the following tournament success measures:

- the probability that one of the best *p* teams wins the tournament;
- the probability that at least one of the best p teams plays in the final;
- the average pre-tournament rank of the winner, the second-, the third- and the fourth-placed teams;
- the expected quality of the final (the sum of the finalists' pre-tournament ranks);

• the expected competitive balance of the final (the difference between the finalists' pre-tournament ranks).

We have focused only on the first four places because there was a third place game in all World Men's Handball Championships since 1995, however, other placement matches were organised arbitrarily.

2.3 Simulation procedure

Given the design and a prediction model for match results, we are able to simulate a complete tournament repeatedly and obtain estimates of any metrics of interest.

2.3.1 Playing abilities

The probability with which a given team would beat another team is fixed *a priori*. We have chosen a generalised version of Jackson (1993)'s model for this purpose:

$$p_{ij} = \frac{1}{1 + [(i+\beta)/(j+\beta)]^{\alpha}},$$
(1)

where p_{ij} is the probability that team *i* defeats team *j*, $\alpha, \beta \geq 0$ are parameters and $1 \leq i, j \leq 24$ is the *identifier* of the teams. The model was used by Jackson (1993) and Marchand (2002) with $\beta = 0$. The role of this novel parameter β is a to lessen the sharp increase of winning probabilities for the strongest teams. The function of α is similar to the original model, its smaller or larger values reflect situations where there is a smaller or larger dispersion in the teams' strengths, respectively.

Stationarity and independence of the probability that team i beats team j is assumed, they do not change throughout the tournament and are independent of the previous results. While in practice they are dynamic and changing probabilities are expected to alter the outcome of the tournament on a single occasion, it seems to be reasonable that stationary probabilities are good approximations of long-run averages (McGarry and Schutz, 1997).

Baseline results are obtained with $\alpha = 4$ and $\beta = 24$, and a robustness check will be provided for both parameters. Figure 1 shows the probabilities of beating the opponents for certain teams as derived from formula (1). Our choice somewhat follows the idea behind Matrix I of McGarry and Schutz (1997): adjacent teams are closely matched (team k-1 defeats team k with a probability of no more than 0.54), but the difference between a top team and an underdog is significant (the strongest team has greater than 90% chance to win against the last five teams).

2.3.2 Technical details

A handball game may be tied at the end of the regular playing time. If a winner has to be determined, namely, in the knockout stage of a tournament, it is followed by the first and (if it is necessary) the second overtime of 10 minutes, and the match is finally decided with penalty throws. It is a less frequent event than a draw in football, for example, in the 2017 World Men's Handball Championship, which was organised according to format KO, there were three draws from the 60 group matches, and one draw from the 16 matches of the knockout stage. Thus, following McGarry and Schutz (1997), draws are not allowed in the simulation. This is not to be confused with ties in the ranking of round-robin groups, resolved in our simulations with an equal-odds 'coin toss'.



Figure 1: The probability that team *i* beats its opponent (baseline, $\alpha = 4$, $\beta = 24$)

Every simulation has been run one million times (N = 1,000,000) such that two matrices with match outcomes have been generated for each possible pair of opponents in every run because some teams may play two matches against each other (but it is not possible before the semifinals). After that, these outcomes have been plugged into the competition formats analysed to study the outcome of the tournament: we have recorded the identifier of the first four teams and the teams which play the final in each run. Thus any differences in tournament metrics are solely caused by the designs.

The validity of the simulation procedure has been tested in several ways. First, a matrix representing equality among all teams $(p_{ij} = 0.5 \text{ for all combinations of } i \text{ and } j)$ has led to, as expected, an outcome where all teams are placed first to fourth equally often. Second, simulations with a fully deterministic matrix $(p_{ij} = 1 \text{ if } i < j)$ have been analysed. Note that it still shows the differences between our tournament designs. For example, in the seeded versions of G66 and G46, the four best teams are guaranteed to occupy the first four places in their natural order. However, in the seeded KO and G64, the two strongest teams can meet in a semifinal with a probability of 1/3. Regarding the unseeded variants, the worst team that may qualify for the semifinals is the sixth in G46, the seventh in KO, and the fourteenth in G64 and G66. Finally, some values have been changed in the fully deterministic matrix in order to see whether they function in an expected way.

We have concluded from these checks that the simulation procedure is valid.

3 The comparison of tournament designs

In the following, our findings on the four tournament designs, that have been used in the recent World Men's Handball Championships, are reviewed.

3.1 Match distribution

By looking at the tournament formats, one can realize that two teams may play at most two times against each other, and this number could be two only if one of these matches is a semifinal, the final or the third-place game.

Each design requires a different number of matches:

- A round-robin tournament with 24 teams contains $24 \times 23/2 = 276$ games.
- Format KO contains $4 \times 6 \times 5/2 = 60$ games in the group stage, and 8+4+2+2 = 16 games in the knockout stage, that is, 76 in total.
- Format G64 contains $4 \times 6 \times 5/2 = 60$ games in the preliminary round, $4 \times 4 \times 2/2 = 16$ games in the main round, and 2 + 2 = 4 games in the knockout stage, that is, 80 in total.
- Format G66 contains $4 \times 6 \times 5/2 = 60$ games in the preliminary round, $2 \times 6 \times 3/2 = 18$ games in the main round, and 2 + 2 = 4 games in the knockout stage, that is, 82 in total.
- Format G46 contains $6 \times 4 \times 3/2 = 36$ games in the preliminary round, $2 \times 6 \times 4/2 = 24$ games in the main round, and 4 + 2 + 2 = 8 games in the knockout stage, that is, 68 in total.



Figure 2: The distribution of matches played in different tournament designs

Besides the total number of matches, its distribution, presented in Figure 2, is also interesting. It presents the number of teams with a given number of matches, for example, under the design KO, eight teams play five matches. In G46, half of the teams play only three matches, however, the others play at least seven. For the three remaining designs, the minimum number of games to be played by a team is five. The maximum is nine in KO and G64, while ten in G66 and G46.

3.2 Main results

Figure 3: Dependence of some tournament metrics on the number of iterations Competition design unseeded KO; $\alpha = 4$; $\beta = 24$



We have tested simulations with the unseeded variant of tournament design KO for various number of independent runs (Figure 3). Since two success measures, the proportion of tournament wins for the highest ranked team, and the proportion of tournament finals between the two highest ranked teams are stable after one million (10⁶) runs, we have decided to implement all of our following simulations with one million runs.

The first tournament metric to be analysed, the probability that one of the best p teams wins the tournament is shown in Figure 4 for some tournament designs. As expected from the number of matches played in each design (Section 3.1), the round-robin is the format that maximises the probability of winning for the best teams.

Furthermore, the four designs of the World Men's Handball Championships are almost indistinguishable, therefore it is worth calculating the difference between these formats compared to the reference RR, as presented in Figure 5. It reveals that design G66 is the best from the perspective of its ability to select the strongest teams, followed by G46, while KO and G64 perform similarly. Furthermore, seeding has not much effect, with the possible exception of format KO: while the seeded variants of KO and G64 are almost indistinguishable, KO becomes marginally better with random seeding.

The same pattern is attested for our second tournament metric, the probability that at least one of the best p teams plays in the final (Figure 6).

The remaining outcome characteristics for the nine tournament designs are summarised in Table 2. A format is said to be *more efficacious* if the average pre-tournament rank of the team finishing in the *p*th place (p = 1, 2, 3, 4) is smaller, the proportion of wins for the highest ranked team is higher, as well as the expected quality and the expected competitive balance of the final is lower. The round-robin design shows the best performance in selecting the highest pre-tournament ranked teams as the winner. However, it requires an especially high number of matches, only the other formats can be applied in practice. Among the seeded variants, *G*66 is the best, followed by *G*46, while the order of *KO* and *G*64 remains undecided, although the former has a marginal advantage.

Eliminating the seeding procedure changes the metrics according to our expectations, for example, the unseeded G66 is approximately at the same level as the seeded G46, whereas the unseeded G46 is still more efficacious than the KO. An interesting observation



Figure 4: The probability that one of the best p teams wins the tournament Seeded competition designs; $\alpha = 4$; $\beta = 24$

- perhaps a kind of puzzle – is that the performance of the design KO, where the knockout stage plays the greatest role, is not influenced by seeding.

The metrics of seeded G64 may refer to a flaw of this format because the average pre-tournament ranking of the bronze medallist is not substantially greater than the average ranking of the silver medallist. The unexpected phenomenon is perhaps caused by its strange knockout stage, where only the group winners of the main round compete.

It is reasonable to assume that if a given design is more efficacious than another in both its seeded and unseeded variants, then it is more efficacious in practice when the actual allocation of the teams into pots is somewhere between these two extreme cases.

All results should be considered with respect to the number of games played. It is the smallest, 68 for the design G46, so its second-place according to efficacy has a favourable message for the organisers: there exists no clear trade-off between efficacy and the number of matches. This is in contrast to the intuition as well as the conclusions of most tournament design papers. For example, Lasek and Gagolewski (2018) find that the performance of a given soccer league format highly depends on the total number of matches played. The reason is that half of the participating teams play only three games in G46, which seems to be enough to determine the competitors with the greatest chance to win the tournament, furthermore, this is the only design containing quarterfinals after two group stages. The remaining three formats are closer to each other from this point of view, all teams play at least five matches, and the total number of games is between 76 and 82. This fact also shows that G64 is a misaligned design because the relatively high number of matches does not reduce outcome uncertainty.

Figure 5: The probability difference that one of the best p teams wins the tournament, compared to a round-robin tournament with 24 teams (RR)



Figure 6: The probability that at least one of the best p teams plays in the final



3.3 Sensitivity analysis

Following Scarf et al. (2009), the robustness of the results is addressed by calculating our metrics for more and less competitive tournaments than the baseline version. It is achieved in two ways, by changing: the parameter α in (1) from its original value of 4 to 3 (more competitive) and 5 (less competitive); and the parameter β in (1) from its original value of 24 to 18 (less competitive) and 36 (more competitive).

Figure A.5 reproduces Figure 5 for these cases. It can be seen that the ranking of the competition designs by efficacy remains unchanged as G66 is better than G46, which outperforms KO and G64. The seeded KO and G64 formats are almost indistinguishable, but the former is more efficacious than the latter if there is no seeding. The advantage of an ideal round-robin tournament becomes more significant if competitive balance is smaller, that is, results are more difficult to forecast.

Figure A.6 reinforces that seeding has not much influence on tournament outcomes, and, while the actual differences among the four designs are modest (at least compared to a round-robin format), they are robust with respect to the distribution of teams' strength.

Table 2: Estimates of some tournament metrics for all designs (baseline model) 1 million simulations for each version; $\alpha = 4$; $\beta = 24$ S = seeded version of the design; R = unseeded (random) version of the design

	RR	KO/S	KO/R	G64/S	G64/R	G66/S	G66/R	G46/S	G46/R
Min. games	23	5	5	5	5	5	5	3	3
Max. games	23	9	9	9	9	10	10	10	10
Total games	276	76	76	80	80	82	82	68	68
Average rank of $\#1$	2.56	3.90	3.88	3.90	3.96	3.48	3.58	3.60	3.70
Average rank of $\#2$	3.31	5.70	5.69	5.75	5.86	4.88	5.11	5.07	5.31
Average rank of $#3$	4.03	5.81	5.86	5.74	6.11	4.94	5.37	5.19	5.45
Average rank of $#4$	4.79	8.63	8.74	8.63	9.19	7.16	7.87	7.47	8.01
Proportion of wins for the highest ranked	0.36	0.24	0.24	0.24	0.24	0.27	0.26	0.25	0.25
Expected quality of the final		9.60	9.57	9.65	9.82	8.35	8.69	8.68	9.01
Expected competitive balance of the final		4.40	4.37	4.45	4.51	3.78	3.94	3.87	4.09

Table 3: Sensitivity analysis for parameter α – Estimates of some tournament metrics 1 million simulations for each version

 $\mathbf{S}=\mathbf{seeded}$ version of the design; $\mathbf{R}=\mathbf{unseeded}$ (random) version of the design

(a)) $\alpha = 3; \beta = 24$ ((more competitive)
-----	------------------------------	--------------------

	RR	KO/S	KO/R	G64/S	G64/R	G66/S	G66/R	G46/S	G46/R
Average rank of $\#1$	3.00	4.78	4.78	4.81	4.89	4.26	4.40	4.41	4.55
Average rank of $\#2$	3.82	6.73	6.77	6.82	6.96	5.87	6.11	6.05	6.36
Average rank of $\#3$	4.58	6.84	6.89	6.78	7.16	5.90	6.33	6.15	6.48
Average rank of $#4$	5.35	9.58	9.72	9.61	10.08	8.24	8.86	8.53	9.08
Proportion of wins for the highest ranked	0.31	0.20	0.20	0.20	0.19	0.22	0.22	0.21	0.21
Expected quality of the final		11.51	11.55	11.63	11.86	10.13	10.51	10.46	10.91
Expected competitive balance of the final		5.29	5.30	5.38	5.45	4.65	4.84	4.75	5.00

(b) $\alpha = 5; \beta = 24$ (less competitive)

	RR	KO/S	KO/R	G64/S	G64/R	G66/S	G66/R	G46/S	G46/R
Average rank of $\#1$	2.31	3.34	3.33	3.34	3.38	3.00	3.08	3.13	3.18
Average rank of $\#2$	3.02	5.02	4.98	5.04	5.12	4.26	4.46	4.48	4.63
Average rank of $\#3$	3.73	5.11	5.17	5.03	5.40	4.34	4.77	4.60	4.78
Average rank of $#4$	4.50	7.85	7.96	7.82	8.44	6.38	7.16	6.73	7.21
Proportion of wins for the highest ranked	0.40	0.28	0.28	0.28	0.28	0.31	0.30	0.29	0.29
Expected quality of the final		8.36	8.30	8.38	8.50	7.27	7.55	7.61	7.81
Expected competitive balance of the final		3.80	3.75	3.82	3.86	3.22	3.37	3.35	3.49

Further tournament characteristics are summarised in Tables 3 and 4. Our conclusions do not change significantly, although the unseeded KO is clearly worse than its seeded variant if $\alpha = 3$ or $\beta = 36$, that is when the teams' abilities are more similar. The final of

the seeded KO is more exciting with higher quality and outcome uncertainty than the final of the seeded G64 fin these cases, too. A possible flaw of design G64 under seeding (the average pre-tournament rank of the third-placed team is close to the average rank of the second-placed) can be observed as before, too.

Table 4: Sensitivity analysis for parameter β – Estimates of some tournament metrics 1 million simulations for each version S = seeded version of the design; R = unseeded (random) version of the design

KO/SG64/SRRKO/RG64/RG66/SG66/RG46/SG46/RAverage rank of #12.273.33 3.31 3.323.362.983.06 3.11 3.16Average rank of #25.055.015.075.174.662.994.274.484.48Average rank of #33.725.155.215.075.444.364.794.614.82Average rank of #44.517.95 8.07 7.93 8.57 6.457.266.827.30 Proportion of wins for 0.280.290.28 0.280.310.310.300.300.41the highest ranked Expected quality 8.37 8.32 8.40 8.53 7.257.547.597.82of the final Expected competitive 3.843.803.873.923.243.403.373.52balance of the final

(a) $\alpha = 4$; $\beta = 18$ (less competitive)

(b) $\alpha = 4$; $\beta = 36$ (more competitive)

	RR	KO/S	KO/R	G64/S	G64/R	G66/S	G66/R	G46/S	G46/R
Average rank of $\#1$	3.13	4.90	4.91	4.94	5.02	4.41	4.54	4.54	4.69
Average rank of $\#2$	3.94	6.82	6.85	6.90	7.04	5.96	6.21	6.14	6.45
Average rank of $\#3$	4.68	6.92	6.97	6.86	7.21	5.99	6.40	6.23	6.56
Average rank of $#4$	5.42	9.59	9.72	9.62	10.07	8.27	8.88	8.55	9.09
Proportion of wins for the highest ranked	0.30	0.19	0.19	0.19	0.19	0.21	0.21	0.20	0.20
Expected quality of the final		11.72	11.76	11.84	12.06	10.37	10.75	10.68	11.14
Expected competitive balance of the final		5.34	5.34	5.42	5.49	4.72	4.89	4.80	5.06

4 Discussion

We have compared four tournament formats of recent World Men's Handball Championships. They have been evaluated by Monte-Carlo simulations under two seeding policies: allocating teams perfectly into pots on the basis of their strength, and a fully random draw of groups. Our main findings are the following:

- KO (applied from 1995 to 2001 and between 2013 and 2017, see Section 2.1.1): it is almost insensitive to the seeding rule. While it seems to be a somewhat surprising fact as the knockout phase plays the greatest role in this format, Marchand (2002) provides evidence that the outcomes of the standard and random knockout tournaments may not vary as much as one might expect.
- G64 (applied in 2003, see Section 2.1.2): it seems to be a questionable design because of its weak ability to select the best teams despite the relatively high

number of matches as well as the average pre-tournament rank of the third-placed team is not substantially higher than the average pre-tournament rank of the second-placed team in the seeded variant.

- G66 (the actual design in 2019, applied in 2005, 2009 and 2011, see Section 2.1.3): it maximises the association between teams' strength and final position, partially due to the highest number of matches played among our designs.
- G46 (applied in 2007, see Section 2.1.4): it means a good compromise between efficacy and compactness as the only format with better performance (G66) requires a 20% increase in the number of matches.

The analysis clearly shows that no single best tournament design exists. For example, format G46 allows only three matches for certain teams before they are eliminated, which may be regarded as the price for an appropriate selection of top teams. On the other hand, format KO is insensitive to the drawing of groups, therefore this competition structure minimizes randomness in a sense by being independent of the seeding policy. In short, we can agree with Scarf et al. (2009): one cannot come up with a single definition of fairness that all would accept. However, the obvious conclusion from the intuition and the principle of statistics that a bigger sample lead to better estimates does not necessarily hold in the case of such complex designs as the comparison of formats G64 and G46 reveals.

It should be noted that all results are based on a particular probabilistic model, which implies certain limitations. However, we have made great effort to minimize this sensitivity by studying a variety of robustness check, and it seems that a wide range of model assumptions are appropriate for comparative purposes (Appleton, 1995).

These competition designs have also been used in other team tournaments with 24 participants. IHF World Women's Handball Championship is organised in every two years since 1993, with 24 teams since 1997. Its format has followed the World Men's Handball Championship taken place in the same year, except for 2003 – when women handball teams competed under design G66, while men played in format G64, thus no women tournament was organised according to this dubious design –, and for 2011 – when women national teams competed under design KO, while men played in format G66. Similarly to the Men's Championship, the next Women's Championship to be held in 2019, hosted by Japan, will also use the format G66 instead of KO (IHF, 2018).

In basketball, the 2006 and the 2010 FIBA World Championships as well as 2014 FIBA Basketball World Cup (the tournament previously known as the FIBA World Championship), the EuroBasket 2015, and the EuroBasket 2017 applied the design KO. However, format G66 was used in the 1986 FIBA World Championship, while the EuroBasket 2011 and the EuroBasket 2013 applied G66 with a slight modification that four teams advanced from each of the two main round groups to the quarterfinals (instead of only two to the semifinals). Finally, the 1978 and 1982 FIVB Volleyball Men's World Championships were organised in a structure similar to G46, but only the two top teams from the two main round groups qualified for the semifinals – while in handball, the second group stage was followed by quarterfinals (see Figure A.4). In the view of our findings, perhaps it is not a coincidence that no further use of the strange design G64 has been found in practice.

To conclude, our results can have a significant impact on practice, and organisers of team championships may consider them when deciding on the design of future tournaments. For example, the recent change of the World Men's Handball Championship format (from

Figure 7: Winning percentage for certain teams



Seeded designs

KO to G66 between 2017 and 2019) has increased the probability of winning for the best teams as revealed by Figure 7. Thus the choice of format offers perhaps the only way to influence the expected value of certain tournament metrics for sports administrators.

There is a great scope for future research. First, one can implement a more extensive sensitivity analysis. Second, as discussed in the Introduction, the method of allocating wins in the simulation is not based on data from real tournaments since it is far from trivial to model them. Third, other tournament designs or simple modifications of the formats analysed by us (recall that a slightly modified variant of structure G46 was used in volleyball) can be investigated with the methodology presented here. Finally, further properties of the competition formats can be examined. For example, it is almost obvious to check that design KO satisfies strategy-proofness, but structures G64, G66, and G46 are incentive incompatible (Csató, 2018c).

Acknowledgements

This paper could not be written without my father, who has coded the simulations in Python during a Christmas break.

We are grateful to *Tamás Halm* for reading the manuscript.

Four anonymous reviewers provided valuable comments and suggestions on earlier drafts. We are indebted to the Wikipedia community for contributing to our research by collecting and structuring some information used in the paper.

The research was supported by OTKA grant K 111797 and by the MTA Premium Post Doctorate Research Program.

References

- Alarcón, F., Durán, G., and Guajardo, M. (2014). Referee assignment in the Chilean football league using integer programming and patterns. *International Transactions in Operational Research*, 21(3):415–438.
- Appleton, D. R. (1995). May the best man win? The Statistician, 44(4):529–538.
- Atan, T. and Hüseyinoğlu, O. P. (2017). Simultaneous scheduling of football games and referees using Turkish league data. *International Transactions in Operational Research*, 24(3):465–484.
- Bilge, M. (2012). Game analysis of Olympic, World and European Championships in men's handball. *Journal of Human Kinetics*, 35(1):109–118.
- Csató, L. (2013). Ranking by pairwise comparisons for Swiss-system tournaments. *Central European Journal of Operations Research*, 21(4):783–803.
- Csató, L. (2017). On the ranking of a Swiss system chess team tournament. Annals of Operations Research, 254(1-2):17–36.
- Csató, L. (2018a). How to design a tournament: lessons from the EHF men's handball Champions League. Manuscript. arXiv: 1811.11850.
- Csató, L. (2018b). Incentive compatible designs for tournament qualifiers with round-robin groups and repechage. Manuscript. arXiv: 1804.04422.
- Csató, L. (2018c). Overcoming the incentive incompatibility of tournaments with multiple group stages. Manuscript. arXiv: 1712.04183.
- Csató, L. (2018d). UEFA Champions League entry has not satisfied strategy-proofness in three seasons. Manuscript. arXiv: 1801.06644.
- Csató, L. (2018e). Was Zidane honest or well-informed? How UEFA barely avoided a serious scandal. *Economics Bulletin*, 38(1):152–158.
- Dagaev, D. and Rudyak, V. (2016). Seeding the UEFA Champions League participants: Evaluation of the reform. Manuscript. DOI: 10.2139/ssrn.2754127.
- Dagaev, D. and Sonin, K. (2017). Winning by losing: Incentive incompatibility in multiple qualifiers. *Journal of Sports Economics*, in press. DOI: 10.1177/1527002517704022.

- Dagaev, D. and Suzdaltsev, A. (2018). Competitive intensity and quality maximizing seedings in knock-out tournaments. *Journal of Combinatorial Optimization*, 35(1):170–188.
- Dixon, M. J. and Coles, S. G. (1997). Modelling association football scores and inefficiencies in the football betting market. *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, 46(2):265–280.
- Dumangane, M., Rosati, N., and Volossovitch, A. (2009). Departure from independence and stationarity in a handball match. *Journal of Applied Statistics*, 36(7):723–741.
- Durán, G., Guajardo, M., and Sauré, D. (2017). Scheduling the South American Qualifiers to the 2018 FIFA World Cup by integer programming. *European Journal of Operational Research*, 262(3):1109–1115.
- Garicano, L., Palacios-Huerta, I., and Prendergast, C. (2005). Favoritism under social pressure. *Review of Economics and Statistics*, 87(2):208–216.
- Goossens, D. R., Beliën, J., and Spieksma, F. C. R. (2012). Comparing league formats with respect to match importance in Belgian football. *Annals of Operations Research*, 194(1):223–240.
- Groh, C., Moldovanu, B., Sela, A., and Sunde, U. (2012). Optimal seedings in elimination tournaments. *Economic Theory*, 49(1):59–80.
- Gruić, I., Vuleta, D., and Milanović, D. (2007). Performance indicators of teams at the 2003 Men's World Handball Championship in Portugal. *Kinesiology: International Journal of Fundamental and Applied Kinesiology*, 38(2):164–175.
- Guyon, J. (2015). Rethinking the FIFA World Cup^{TM} final draw. Journal of Quantitative Analysis in Sports, 11(3):169–182.
- Guyon, J. (2017). What a fairer 24 team UEFA Euro could look like. Manuscript. DOI: 10.2139/ssrn.2714199.
- Horen, J. and Riezman, R. (1985). Comparing draws for single elimination tournaments. *Operations Research*, 33(2):249–262.
- Hwang, F. K. (1982). New concepts in seeding knockout tournaments. *The American Mathematical Monthly*, 89(4):235–239.
- IHF (2018). Regulations for IHF Competitions. International Handball Federation. Edition: 14 January 2018. http://ihf.info/files/Uploads/NewsAttachments/0_ Regulations%20for%20IHF%20Competitions_GB.pdf.
- Jackson, D. A. (1993). Independent trials are a model for disaster. *Applied Statistics*, 42(1):211–220.
- Karpov, A. (2016). A new knockout tournament seeding method and its axiomatic justification. Operations Research Letters, 44(6):706–711.
- Koning, R. H., Koolhaas, M., Renes, G., and Ridder, G. (2003). A simulation model for football championships. *European Journal of Operational Research*, 148(2):268–276.

- Krumer, A. and Lechner, M. (2017). First in first win: Evidence on schedule effects in round-robin tournaments in mega-events. *European Economic Review*, 100:412–427.
- Krumer, A., Megidish, R., and Sela, A. (2017). First-mover advantage in round-robin tournaments. Social Choice and Welfare, 48(3):633–658.
- Laliena, P. and López, F. J. (2018). Fair draws for group rounds in sport tournaments. International Transactions in Operational Research, in press. DOI: 10.1111/itor.12565.
- Lasek, J. and Gagolewski, M. (2015). Predictive efficacy of a new association football league format in Polish Ekstraklasa. In *Machine Learning and Data Mining for Sports Analytics Workshop at ECML/PPKD*.
- Lasek, J. and Gagolewski, M. (2018). The efficacy of league formats in ranking teams. *Statistical Modelling*, 18(5-6):411–435.
- Maher, M. J. (1982). Modelling association football scores. *Statistica Neerlandica*, 36(3):109–118.
- Marchand, É. (2002). On the comparison between standard and random knockout tournaments. Journal of the Royal Statistical Society: Series D (The Statistician), 51(2):169–178.
- McGarry, T. and Schutz, R. W. (1997). Efficacy of traditional sport tournament structures. Journal of the Operational Research Society, 48(1):65–74.
- Ribeiro, C. C. (2012). Sports scheduling: Problems and applications. International Transactions in Operational Research, 19(1-2):201–226.
- Ryvkin, D. (2010). The selection efficiency of tournaments. European Journal of Operational Research, 206(3):667–675.
- Scarf, P., Yusof, M. M., and Bilbao, M. (2009). A numerical study of designs for sporting contests. *European Journal of Operational Research*, 198(1):190–198.
- Scarf, P. A. and Yusof, M. M. (2011). A numerical study of tournament structure and seeding policy for the soccer World Cup Finals. *Statistica Neerlandica*, 65(1):43–57.
- Schwenk, A. J. (2000). What is the correct way to seed a knockout tournament? *The American Mathematical Monthly*, 107(2):140–150.
- Stanton, I. and Williams, V. V. (2013). The structure, efficacy, and manipulation of double-elimination tournaments. *Journal of Quantitative Analysis in Sports*, 9(4):319– 335.
- Szymanski, S. (2003). The economic design of sporting contests. *Journal of Economic Literature*, 41(4):1137–1187.
- Vong, A. I. K. (2017). Strategic manipulation in tournament games. Games and Economic Behavior, 102:562–567.
- Wright, M. (2009). 50 years of OR in sport. Journal of the Operational Research Society, 60(Supplement 1):S161–S168.

- Wright, M. (2014). OR analysis of sporting rules A survey. European Journal of Operational Research, 232(1):1–8.
- Yusof, M. M., Khalid, R., Sulaiman, T., Hamid, M. S. A., Mansor, R., and Rosli, N. C. (2016). E-compare of soccer tournament structures. *International Review of Management* and Marketing, 6(8S):294–298.

Appendix

Figure A.1: Format KO, which was used in the 2017 World Men's Handball Championship

Group A	Group B	Group C	Group D
A1	B1	C1	D1
A2	B2	C2	D2
A3	B3	C3	D3
A4	B4	C4	D4
A5	B5	C5	D5
A6	B6	C6	D6

(a) Group stage: preliminary round



(b) Knockout stage

Figure A.2: Format G64, which was used in the 2003 World Men's Handball Championship



(a) Group stages: preliminary and main rounds





Figure A.3: Format G66, which was used in the 2011 World Men's Handball Championship, and again in the 2019 World Men's Handball Championship

Group A		Group X	•	Group B
A1 -		X1		- B1
A2 -		X2		- B2
A3 ~		X3		<u>B3</u>
A4		X4		B4
A5		X5		B5
A6		X6		B6
	•			
Group C		Group Y		Group D
C1 -		Y1		- D1
C2 -		Y2		- D2
<u>C3</u>		Y3		D3
C4		Y4		D4
C5		Y5		D5
$\bigcirc 5$		- •		20

(a) Group stages: preliminary and main rounds

(b)	Knockout	stage
(D)	mochout	Stage



Figure A.4: Format G46, which was used in the 2007 World Men's Handball Championship

(a) Group stages: preliminary and main rounds







Figure A.5: Sensitivity analysis – The probability difference that one of the best p teams wins the tournament, compared to a round-robin tournament with 24 teams (RR)



Figure A.6: Sensitivity analysis – The probability that at least one of the best p teams *plays in the final*