Better Fixed-Arity Unbiased Black-Box Algorithms^{*}

Nina Bulanova Maxim Buzdalov

July 11, 2018

Abstract

In their GECCO'12 paper, Doerr and Doerr proved that the k-ary unbiased black-box complexity of ONEMAX on n bits is O(n/k) for $2 \le k \le O(\log n)$. We propose an alternative strategy for achieving this unbiased black-box complexity when $3 \le k \le \log_2 n$. While it is based on the same idea of block-wise optimization, it uses k-ary unbiased operators in a different way.

For each block of size $2^{k-1} - 1$ we set up, in O(k) queries, a virtual coordinate system, which enables us to use an arbitrary unrestricted algorithm to optimize this block. This is possible because this coordinate system introduces a bijection between unrestricted queries and a subset of k-ary unbiased operators. We note that this technique does not depend on ONEMAX being solved and can be used in more general contexts.

This together constitutes an algorithm which is conceptually simpler than the one by Doerr and Doerr, and at the same time achieves better constant factors in the asymptotic notation. Our algorithm works in $(2 + o(1)) \cdot n/(k-1)$, where o(1) relates to k. Our experimental evaluation of this algorithm shows its efficiency already for $3 \le k \le 6$.

1 Introduction

Unbiased black-box complexity of a problem is one of the measures for how complex this problem is for solving it by evolutionary algorithms and other randomized

^{*}An extended abstract of this work will appear in proceedings of Genetic and Evolutionary Computation Conference 2018. The paper is accompanied with the source code, which is available on GitHub: https://github.com/mbuzdalov/unbiased-bbc.

heuristics. Often, complexities of rather simple problems are studied, such as the famous ONEMAX problem, defined on bit strings of length n as follows:

ONEMAX_z :
$$\{0, 1\}^n \to \mathbb{R}; x \mapsto |\{i \in [1..n] \mid x_i = z_i\}|.$$

The notion of unbiased black-box complexity was introduced in [16] for pseudo-Boolean problems (see also the journal version [17]) partially as a response to unrealistically low black-box complexities of various NP-hard problems [13]. Since evolutionary algorithms and other randomized search heuristics are designed as general-purpose solvers, they shall not prefer one instance of a problem over another one. This means that unbiased black-box algorithms are a better model of randomized search heuristics, since the unbiased model does not allow certain ways of being "too fast". Unfortunately, the ways were found to perform most of the work without making queries in the unbiased model too [5,8]. In fact, it was shown that, with a proper notion of unbiasedness for the given type of individuals, the unbiased black-box complexity coincides to the unrestricted one [18]. Several alternative restricted models of black-box algorithms were subsequently introduced as a reaction, namely ranking-based algorithms [11], limited-memory algorithms [10], and elitist algorithms [12].

One of possible restrictions to the unbiased black-box search model is the use of unbiased operators with restricted arity. The original paper [16] studied mostly unary unbiased black-box complexity, e.g. the class of algorithms allowing only unbiased operators taking one individual and producing another one, or mutationbased algorithms. This model appeared to be quite restrictive, e.g. the unary unbiased black-box complexity of ONEMAX was proven to be $\Theta(n \log n)$ [6, 16]. Together with the rather old question, whether crossover is useful in evolutionary algorithms (which was previously positively, but only in artificial settings [15]), this inspired a number of works on higher-arity unbiased algorithms, since many crossovers are binary unbiased operators.

The theorem that for $k \ge 2$ the k-ary unbiased black-box complexity of ONE-MAX is $O(n/\log k)$, which was proven in [7], was the first signal that higher arities are useful. Among others, an elegant crossover-based algorithm with the expected running time of 2n - O(1) was presented, which works for all linear functions. Several particular properties of this algorithm inspired the researchers to look deeper for faster general-purpose algorithms that use crossover. The first reported progress of algorithms using crossover on simple problems like ONEMAX was made in [20,21], where an algorithm was presented with the same $O(n \log n)$ asymptotic but with a better constant factor. An algorithm, called the $(1 + (\lambda, \lambda))$ genetic algorithm, was presented in [3] along with the proof of the $O(n\sqrt{\log n})$ runtime on ONEMAX, which was faster than any evolutionary algorithm before, and improved performance on some other problems. With the use of self-adaptation for its parameter λ , the O(n) bound was proven for the runtime on ONEMAX [2], and similar improvements were shown later on a more realistic problem, MAX-SAT [1]. Experiments show that the constant in O(n) is rather small.

After such a great success already for binary unbiased operators, what can we expect from higher arity algorithms? Some of the existing algorithms already feature as much as quaternary (k = 4) operators, the notable example of which is differential evolution [19]. The $O(n/\log k)$ result on ONEMAX does not look very inspiring in this aspect, since it suggests that the arity should grow exponentially to get noticeable runtime improvements. However, soon a better result appeared in [9], which shows that the k-ary unbiased black-box complexity of ONEMAX is O(n/k) for $2 \le k \le O(\log n)$. While there are still no matching lower bounds for arities greater than one, this result suggests that higher arities generally pay off.

The result presented in [9] is rather complicated and non-trivial to use for two reasons. First, it has to use, as a building block, a derandomized unrestricted algorithm to solve ONEMAX, proposed in [14], which runs in $(1 + \delta) \log_2(9) \cdot n/\log_2 n$ for δ decreasing with n. The corresponding sequence is only proven to exist, but no way to construct it has ever been proposed. Second, this algorithm needs 4ℓ bits to optimize a piece of ℓ bits and encodes the fitness values of several queried strings into some of these bits to make the final choice. This not only complicates the algorithm but also increases the arity needed to find the optimum within the given number of fitness queries.

In this paper we aim to improve this situation. We propose an algorithm which, like the one from [9], optimizes ONEMAX by blocks of ℓ bits but does it in a simpler and more explicit manner and performs fewer queries. For k-ary operators, $k \geq 3$, we set $\ell = 2^{k-1} - 1$ and initialize a "virtual coordinate system" in k queries very similar to "storage initialization" in [9]. However, subsequently we use the opportunities offered by this coordinate system in a different manner. We notice that it introduces a bijection between bit strings of length ℓ and 2^{ℓ} different k-ary unbiased operators. We use this fact to optimize these ℓ bits by simulating an arbitrary algorithm for solving ONEMAX of length ℓ , regardless of unbiasedness or arity of this algorithm.

Note that this algorithm operates not on the individuals of the enclosing k-ary unbiased algorithm, and even not on their parts, but in fact on the subset of k-ary unbiased operators, where each operator is unambiguously defined by a bit string of length ℓ . This subset is isomorphic to a set of bit strings of length ℓ , and the abovementioned bijection effectively introduces an instance of the ONEMAX problem defined on this subset. In simple words, each such k-ary unbiased operator has an associated "fitness value". It is computed by applying this operator to a predefined sequence of already queried strings, computing the fitness of the resulting string and translating it back using a simple linear transformation which is detailed later. While the k-ary unbiased algorithm cannot access the particular bits of the bit string, the definition of a k-ary unbiased algorithm does not prevent it from setting the parameters of the k-ary unbiased operators, which it uses, in an arbitrary way depending on the preceding query history. Our algorithm is thus able to run an arbitrary optimizer on its k-ary unbiased operators, while the fitness values of these operators are computed in a completely unbiased way with the use of at most k-ary unbiased operators.

In particular, we can use the random sampling algorithm from [14] which works in expected $(2 + o(1)) \cdot \ell / \log \ell$ time. Thus, the overall number of queries needed by the proposed algorithm to solve the ONEMAX problem sums up from expected $(2 + o(1)) \cdot n/(k - 1)$ queries from solving each block and $O(n \cdot k/2^k)$ additional work coming from the initialization of coordinate systems and the aggregation of answers found for each block. Note that the second addend is negligibly small in k compared to the first one, so it hides entirely in o(1) inside the first addend.

The rest of the paper is structured as follows. Section 2 introduces the general form of unbiased operators, which is used afterwards to describe the used operators in the concise way without the need to prove their unbiasedness. Section 3 gives a short overview of the existing O(n/k) algorithm from [9] so that one can clearly see the differences between this algorithm and the proposed one. Section 4 describes the "virtual coordinate system" that we use to optimize blocks. In Section 5 the proposed algorithm is described in the general form, along with a faster custom version for k = 3. Section 6 presents the empirical study of the proposed algorithms for $3 \le k \le 6$, which shows that the improvements from higher arities are clearly seen already for these values of k. This empirical study also suggests that a simple modification to the $(2+o(1)) \cdot n/\log n$ random sampling algorithm from [14] might reduce its running time, which seems to be interesting on its own. Section 7 concludes.

2 Unbiased Operators: General Form

In this section we give the formal definition of k-ary unbiased operators, and then we show how to define every possible k-ary unbiased operator in a concise form, which additionally enables to implement this operator in a constructive way. We also introduce a convenient notation for k-ary unbiased operators, which we will use in subsequent sections. In what follows we consider only operators which take and produce bit strings of length n.

Note that most of this section seems to belong to a common sense in theory of evolutionary computation. However, no literature seems to cover this fact. In particular, the paper [9] still uses the explicit distribution notation, and the authors still have to prove that certain distributions are unbiased. **Definition 1.** A k-ary operator \mathcal{X} , which produces a search point y from the given k search points $x^{(1)}, \ldots, x^{(k)}$ with probability $P_{\mathcal{X}}(y \mid x^{(1)}, \ldots, x^{(k)})$, is unbiased if the following relations hold for all search points $x^{(1)}, \ldots, x^{(k)}, y, z$ and all permutations π over [1..n]:

$$P_{\mathcal{X}}(y \mid x^{(1)}, \dots, x^{(k)}) = P_{\mathcal{X}}(y \oplus z \mid x^{(1)} \oplus z, \dots, x^{(k)} \oplus z),$$
(1)

$$P_{\mathcal{X}}(y \mid x^{(1)}, \dots, x^{(k)}) = P_{\mathcal{X}}(\pi(y) \mid \pi(x^{(1)}), \dots, \pi(x^{(k)})),$$
(2)

where $a \oplus b$ is the bitwise exclusive-or operation applied to a and b, and $\pi(a)$ is an application of permutation π to a.

This definition is equivalent to Definition 1 in [9]. In simple words, (1) declares that \mathcal{X} is invariant under flipping the *i*-th bits, for any *i*, in every argument and in the result simultaneously, and (2) declares that \mathcal{X} is invariant under permuting bits in the same way in arguments and the result.

It is clear that the only 0-ary unbiased operator is the operator that produces a bit string with every bit set with probability 0.5. The standard bit mutation is an example of the 1-ary, or *unary*, unbiased operator, while the uniform crossover operator, as well as the crossover operator from the $(1 + (\lambda, \lambda))$ algorithm [3]¹ are 2-ary, or *binary*, unbiased operators.

We are going to characterize all unbiased operators for $k \ge 1$. To do this, we note that the set of bit indices, $\{1, 2, \ldots, n\}$, can be split into 2^{k-1} disjoint sets according to whether the *i*-th bit is same in the first argument $x^{(1)}$ and each of other arguments, $x^{(2)}$ to $x^{(k)}$. More formally, we introduce sets $S_0, S_1, \ldots, S_{2^{k-1}-1}$, such that $S_i \cap S_j = \emptyset$ if $i \ne j$ and $\bigcup S_i = \{1, 2, \ldots, n\}$. It is easier to construct these sets by defining the index of the set, to which a particular bit index *i* belongs, as follows:

$$i \in S_j \leftrightarrow j = \sum_{t=2}^k 2^{t-2} \cdot \left[x_i^{(1)} \neq x_i^{(t)} \right],$$

where [P] is the Iverson bracket, which yields 1 if P is true and 0 otherwise. For instance, S_0 is the set of bit indices at which bits are equal in all arguments, while $S_{2^{k-1}-1}$ contains indices at which $x^{(1)}$ differs from all other arguments.

Note that the sets S_i do not change if all arguments $x^{(i)}$ are replaced with $x^{(i)} \oplus z$ for an arbitrary bit string z same to all arguments. In the same time, it holds for an arbitrary permutation π that whenever $i \in S_j$, then $\pi(i) \in S_j^*$, where the set S_j^* is built from $\pi(x^{(1)}), \pi(x^{(2)}), \ldots, \pi(x^{(k)})$. We may define $\pi(S_j) = {\pi(i) \mid i \in S_j}$, which is the same as S_j^* . Note also that $|S_j| = |\pi(S_j)|$ for an arbitrary π .

¹This crossover is called "biased" in that paper, which can cause confusion. In fact, the "biasedness" of this crossover is about choosing the bits from the parent with much greater probability than from the child. However, in the terms of the current paper, this crossover is unbiased.

The following lemma states that a certain kind of k-ary operator is unbiased. We will show later that *every* k-ary unbiased operator can be described as an operator of this kind.

Lemma 1. Consider a k-ary operator \mathcal{X} on bit strings of length n which, given k arguments $x^{(1)}, \ldots, x^{(k)}$:

- 1. Computes sets of bit indices $S_0, \ldots, S_{2^{k-1}-1}$ as above.
- 2. Computes sizes of these sets $n_i = |S_i|$.
- 3. Based only on the values of n_j , chooses values $d_0, \ldots, d_{2^{k-1}-1}$ such that $0 \leq d_j \leq n_j$. These values can heavily depend on the n_j values and need not be random.
- 4. Chooses uniformly at random subsets $F_j \subseteq S_j$, such that $|F_j| = d_j$, for all $0 \le j < 2^{k-1}$, and computes $F = \bigcup F_j$.
- 5. Returns a bit string y which differs from $x^{(1)}$ exactly at indices from the set F.

The operator \mathcal{X} is unbiased.

Proof. To prove unbiasedness of \mathcal{X} , one needs to show that (1) and (2) hold. The first holds trivially since, as shown above, applying the $(z \oplus \cdot)$ operation, for an arbitrary bit string z, to all arguments does not change the sets S_i , which, in turn, leaves intact the distribution of the indices which are going to be flipped.

To prove the second property, consider $P_{\mathcal{X}}(y \mid x^{(1)}, \ldots, x^{(k)})$. This is exactly the probability that $F = \{i \mid x_i^{(1)} \neq y_i\}$ is chosen at step 4, given the arguments $x^{(1)}, \ldots, x^{(k)}$. This event is equivalent to the event that $F_j \subseteq S_j$ for all j are chosen. The probability of this event depends only on n_j and d_j , since every possible subset of S_j of size d_j is chosen with the same probability. We also note that $F_j = \{i \mid y_i \neq x_i^{(1)}\} \cap S_j$.

Now consider $P_{\mathcal{X}}(\pi(y) \mid \pi(x^{(1)}), \dots, \pi(x^{(k)}))$. As shown above, the sizes of the index sets do not change, that is, $|\pi(S_j)| = |S_j| = n_j$. One can see that $|\pi(F_j)| = |F_j| = d_j$ as well. This means that this new probability is exactly the same as the probability in the previous case, which proves the second property and the entire lemma.

We prove now that every k-ary unbiased operator can be represented in the way described in Lemma 1. We do not need this fact in the subsequent sections, since both the algorithm from [9] and the proposed algorithm use only operators which can be explicitly represented as Lemma 1 requires. However, we feel that this fact deserves a proof.

Lemma 2. Assume \mathcal{X} is a k-ary unbiased operator which operates on bit strings of length n. Then for any $y, x^{(1)}, \ldots, x^{(k)}, \tilde{y}, \tilde{x}^{(1)}, \ldots, \tilde{x}^{(k)}$ such that, for all $j \in \{0, \ldots, 2^{k-1}-1\}$:

- 1. The index sets S_j generated from $x^{(1)}, \ldots, x^{(k)}$ and the index sets \tilde{S}_j generated from $\tilde{x}^{(1)}, \ldots, \tilde{x}^{(k)}$ satisfy $|S_j| = |\tilde{S}_j|$.
- 2. $|\{i \mid y_i \neq x^{(1)}\} \cap S_j| = |\{i \mid \tilde{y}_i \neq \tilde{x}^{(1)}\} \cap \tilde{S}_j|;$

it holds that $P_{\mathcal{X}}(y \mid x^{(1)}, \dots, x^{(k)}) = P_{\mathcal{X}}(\tilde{y} \mid \tilde{x}^{(1)}, \dots, \tilde{x}^{(k)}).$

Proof. Let $U = \{1, ..., n\}$, $F = \{i \mid y_i \neq x_i^{(1)}\}$ and $\tilde{F} = \{i \mid \tilde{y}_i \neq \tilde{x}_i^{(1)}\}$. We define $S_j^0 = S_j \cap (U \setminus F)$, $S_j^1 = S_j \cap F$, $\tilde{S}_j^0 = \tilde{S}_j \cap (U \setminus \tilde{F})$, $\tilde{S}_j^1 = \tilde{S}_j \cap \tilde{F}$.

By part 2 of the lemma statement, $|S_j^0| = |\tilde{S}_j^0|$ and $|S_j^1| = |\tilde{S}_j^1|$. This means that there exists a bijection between each such pair. Since $\bigcup S_j = U$ and $\bigcup \tilde{S}_j = U$, there exists a permutation π such that $\pi(S_j^0) = \tilde{S}_j^0$ and $\pi(S_j^1) = \tilde{S}_j^1$ for all jsimultaneously.

Define $z = \pi(y) \oplus \tilde{y}$. Since bits in every S_j^0 coincide in $x^{(1)}$ and y, bits in $\pi(S_j^0) = \tilde{S}_j^0$ will also coincide in $\pi(x^{(1)})$ and $\pi(y)$, so they will also coincide in $\pi(x^{(1)}) \oplus z$ and $\pi(y) \oplus z = \tilde{y}$. This means that $\tilde{x}^{(1)}$ coincides with $\pi(x^{(1)}) \oplus z$ in bits \tilde{S}_j^0 for every j. The same logic shows that $\tilde{x}^{(1)}$ coincides with $\pi(x^{(1)}) \oplus z$ in bits \tilde{S}_j^1 for every j, so $\tilde{x}^{(1)} = \pi(x^{(1)}) \oplus z$.

By construction of sets S_j and \tilde{S}_j , it also holds that $\tilde{x}^{(i)} = \pi(x^{(i)}) \oplus z$ for all $1 \leq i \leq k$. This means that, in the statement to be proven, the arguments of $P_{\mathcal{X}}(y \mid x^{(1)}, \ldots, x^{(k)})$ are translated into the arguments of $P_{\mathcal{X}}(\tilde{y} \mid \tilde{x}^{(1)}, \ldots, \tilde{x}^{(k)})$ by applying the permutation π first, and then $(z \oplus \cdot)$. Since the operator \mathcal{X} is unbiased, these two probabilities are equal.

To represent an arbitrary k-ary unbiased operator in the form which Lemma 1 specifies, it is enough to iterate over all possible values of n_j , to generate an arbitrary set of arguments such that $|S_j| = n_j$, and to measure, for every possible combination of values d_j , the probability of sampling an arbitrarily chosen bit string which matches these values of d_j . By Lemma 2, the probabilities for all the remaining cases will be automatically determined.

The only part of the unbiased operator, which is done at will, is the stage 3 of the form required by Lemma 1. This, together with Lemma 2, proves the following theorem.

Theorem 1. Every k-ary unbiased operator defined on its arguments $x^{(1)}, \ldots, x^{(k)}$ is uniquely described by the following, possibly non-deterministic, mapping:

$$\langle n_0, n_1, \dots, n_{2^{k-1}-1} \rangle \rightarrow \langle d_0, d_1, \dots, d_{2^{k-1}-1} \rangle,$$

where n_j is the size of the subset of bit indices S_j such that:

$$S_{j} = \left\{ i \mid j = \sum_{t=2}^{k} 2^{t-2} \cdot \left[x_{i}^{(1)} \neq x_{i}^{(t)} \right] \right\},\$$

and d_j indicates how many bits, chosen uniformly at random from S_j , to flip in $x^{(1)}$ to achieve the result.

We give a few examples of the notation introduced in this theorem.

- Single bit mutation: $\langle n \rangle \rightarrow \langle 1 \rangle$.
- Unary inversion operator: $\langle n \rangle \rightarrow \langle n \rangle$.
- Standard bit mutation: $\langle n \rangle \rightarrow \langle \text{Bin}(n, 1/n) \rangle$.
- Uniform crossover: $\langle n_0, n_1 \rangle \rightarrow \langle \operatorname{Bin}(n_0, 1/2), \operatorname{Bin}(n_1, 1/2) \rangle$.
- Crossover from [7] for the binary case: $\langle n_0, n_1 \rangle \rightarrow \langle 0, 1 \rangle$.

The result presented in this section essentially means that a k-ary unbiased operator can distinguish at most 2^{k-1} groups of bits, determined by which arguments have a certain bit different to that of the first argument, and it is able to choose different numbers of bits to flip in each of these groups.

3 The Existing Algorithm: Overview

In this section we cover the k-ary unbiased algorithm for solving ONEMAX on bit strings of length n, which was proposed in [9].

This algorithm uses operators with arity at most $k \ge 7$. For convenience, denote $\kappa = k - 7$. The algorithm maintains two strings x and y, which coincide in precisely those bits that are guessed right and differ in all other bits. Initially x is random, and y is the inverse of x. Unless x = y, the algorithm wants to choose at most $\ell = 2^{\kappa}$ bit indices among those which differ in x and y at random and optimizes bits at these indices.

To optimize these bits, the algorithm uses the "derandomized random sampling" technique: before it starts its work, it precomputes a string-distinguishing sequence r_1, \ldots, r_t for $t = (1 + o(1)) \log_2(9) \cdot \ell / \log_2 \ell$. However, since the algorithm is unbiased, it cannot directly place the strings from this sequence into the ℓ chosen bits. What is more, the algorithm requires some additional space to store the fitness values, received from the "bigger" ONEMAX of length n and recoded to be understood by a solver of the "smaller" ONEMAX of length ℓ . Since a fitness in the latter cannot be greater than ℓ , it cannot occupy more than $\kappa + 1$ bits. All fitness values corresponding to the queries from the sequence r_1, \ldots, r_t cannot occupy more than 4ℓ bits in total.

To accomodate them, the algorithm initializes the so-called *storage* of length 4ℓ , of which ℓ' bits ($\ell' \leq \ell$, where the inequality can be strict in the last run) are those which it intends to optimize. First, a string y_0 is queried by a binary operator $\langle n_0, n_1 \rangle \rightarrow \langle 4\ell - \ell' - q, \ell' + q \rangle$, where $\max(0, 4\ell - \ell' - n_0) \leq q \leq n_1 - \ell'$ and

$$P(q = q_0) = \frac{\binom{n_0}{4\ell - \ell' - q_0} \binom{n_1 - \ell'}{q_0}}{\binom{n_0 + n_1 - \ell'}{4\ell - \ell'}}$$

in order to distribute $4\ell - \ell'$ bits of storage uniformly at random, applied to x and y. In this way, the bits in which it differs from x define the bits allocated for the storage, and the ℓ bits to optimize are among them.

In order to address the individual bits of the storage, the strings y_i are generated, the *i*-th one by an (i + 2)-ary unbiased operator $\langle 0, n_1, \ldots, n_j, \ldots \rangle \rightarrow \langle 0, 0, \ldots, [j \mod 2 = 0] \cdot n_j/2, \ldots \rangle$ applied to $x, y, y_0, \ldots, y_{i-1}$. The only exception is the string y_1 , where it is additionally ensured that y_1 coincides with x in the ℓ' bits which are to be optimized. Our construction, described in detail in Section 4, is very similar to this one, so we will discuss its working principles later. Now we only state that the strings $x, y, y_0, \ldots, y_{\kappa+2}$ introduce a bijection between all bit strings of length 4ℓ and all bit strings which are different from x only in those 4ℓ bits in which x and y_0 differ. What is more, this bijection can be expressed as a composition of some permutation and an application of the operation \oplus with some bit string. Note that this bijection, which is Hamming-preserving, is not explicitly mentioned in [9], where one of its directions is called the write procedure. The bijection σ , which was mentioned in this paper, is a bijection between the indices of these strings.

The algorithm proceeds with morphing the strings r_1 to r_t by the above mentioned bijection (using $(\kappa + 5)$ -ary operators applied each to x, y, y_i), and querying them. To morph these fitnesses back, another string, y_B , must be queried beforehand by the 4-ary operator $\langle n_0, n_1, n_2, \ldots, n_7 \rangle \rightarrow \langle 0, n_1, 0, \ldots, 0 \rangle$ applied to strings x, y_0, y_1, y_2 . These morphed fitnesses, each of $\kappa + 1$ bits, are then written to the storage using $(\kappa + 6)$ -ary operators with the help of the same bijection. Finally, a $(\kappa + 7)$ -ary operator chooses the bits consistent with the stored fitness values and the pre-computed values r_1, \ldots, r_t and writes them to the ℓ' bits which they should occupy.

Since every ℓ bits, chosen in this way, are optimized in $O(\ell/\log \ell)$ queries, the entire running time of the algorithm is $O(n/\log \ell) = O(n/\kappa) = O(n/k)$.

In our opinion, all the major complications in this algorithm arise solely from the fact that the authors of [9] accidentally missed the fact that the system of strings $x, y, y_0, \ldots, y^{\kappa+2}$ actually introduced a Hamming-preserving bijection between the $2^{4\ell}$ bit strings which are the candidates for an optimum in 4ℓ bits and the same number of $(\kappa+5)$ -ary unbiased operators which take all uninteresting bits from the first argument but can change every single bit among the 4ℓ interesting bits, compared to its value in the first argument, in arbitrary way independently of all other $4\ell - 1$ bits. With this weapon in hand, we can run an arbitrary unrestricted algorithm for solving ONEMAX through the prism of this bijection, since the unbiased setting does not restrict us which k-ary unbiased operators to apply. We develop this idea in next two sections.

4 The Virtual Coordinate System

In this section, we assume that we have two strings x and y_0 , such that they differ in ℓ bits. We need to establish a way to set each of these bits in either the same value as in x, or in a different value than in x, independently of other bits, in a single query, while leaving all other $n - \ell$ bits in the same state as in x. Since for $\ell = 1$ this problem is trivial, we consider $\ell \geq 2$. We show a way to do this with the help of k-ary unbiased operators such that $2^{k-1} - 1 \geq \ell$.

Recall that a k-ary unbiased operator can distinguish 2^{k-1} groups of bits. One of these groups has to be dedicated to "unrelated" bits, i.e. the $n-\ell$ bits outside of the interesting region. For simplicity, we allocate the 0-th group for this purpose, that is, the group of bits which are equal throughout all arguments. Our aim is to design auxiliary queries in such a way that each of the remaining $2^{k-1} - 1$ groups consists of at most a single bit, which enables subsequent fine manipulations with them.

We illustrate this technique on $\ell = 2^{k-1} - 1$. It will also work with only minor changes for any $2^{k-2} \leq \ell < 2^{k-1}$, whereas smaller ℓ will only require a smaller k. It can also be modified to work slightly better in the case of $2^{k-1} \geq n$, in which we do not need to care about the unrelated bits since there are none of them.

To create the next k - 1 bit strings y_1, \ldots, y_{k-1} , we use a set of very similar unbiased operators of arity $2, \ldots, k$ correspondingly, which can be described by a single phrase: in each bit group except the 0-th one, flip half of the bits *rounded* up. The formal notation for these operators is as follows:

$$\langle n_0, n_1, \ldots, n_j, \ldots \rangle \rightarrow \langle 0, \lceil n_1/2 \rceil, \ldots, \lceil n_j/2 \rceil, \ldots \rangle$$

Each time such an operator is applied, a new string is created which, if used together with the previous ones, divides every bit group with the size greater than one (except the 0-th one) into two parts of (almost) equal size. When y_{k-1} is created, every group of $2^{k-1} - 1$ such groups contains a single element (at most one element if $\ell < 2^{k-1} - 1$). The algorithm for constructing strings y_1, \ldots, y_{k-1}

Algorithm 1 Construction of the virtual coordinate system

function BUILDCOORDINATES $(x, y_0; k)$ – x and y_0 are strings which differ in ℓ bits, $2^{k-2} \leq \ell < 2^{k-1}$ – k is the maximum allowed arity FLIPUPPERHALF := $\langle n_0, \ldots, n_j, \ldots \rangle \rightarrow \langle 0, \ldots, \lceil n_j/2 \rceil, \ldots \rangle$ for $i \in [1; k - 1]$ do $y_i \leftarrow \text{FLIPUPPERHALF}(x, y_0, \ldots, y_{i-1});$ QUERY (y_i) end for return (y_1, \ldots, y_{k-1}) end function

00	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1	y_4
$0\dots 0$	0	1	1	0	0	1	1	0	0	1	1	0	0	1	1	y_3
$0\dots 0$	0	0	0	1	1	1	1	0	0	0	0	1	1	1	1	y_2
$0\dots 0$	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	y_1
$0\dots 0$	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	y_0
$0\dots 0$	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	x
0	8	4	12	2	10	6	14	1	9	5	13	3	11	$\overline{7}$	15	Group No.

Figure 1: Example of the virtual coordinate system for k = 5 and $\ell = 15$. The bit value 0 means that this value is the same as the value of x at this position, 1 means this value negated. Group numbers are given for subsequent calls of k-ary unbiased operators on strings x, y_1, y_2, y_3, y_4 . A group number is formed by reading the column top to bottom from y_4 to y_1 as a binary number. The example for $11 = 1011_2$ is highlighted.

from x and y_0 is outlined as Algorithm 1. Figure 1 illustrates it for k = 5 and $\ell = 15$.

Rounding up, in the case of odd size of a group, ensures² that in no such group bits in x, y_1, \ldots, y_{k-1} coincide (note the absence of y_0). This means that, in the subsequent queries, we can exclude y_0 from the arguments, which means that we can still use operators of arity k to query arbitrary strings.

Now we establish a Hamming-preserving bijection between arbitrary strings of length ℓ and k-ary unbiased operators called on x, y_1, \ldots, y_{k-1} . There are exactly ℓ groups among $1 \leq j < 2^{k-1}$ for which $n_j = 1$. Based on this, we define an

²Strictly speaking, rounding up is necessary only in the group 1, since this ensures that this group will have the size one already when querying y_{k-1} . This means that the group 1 will be empty if a (k + 1)-ary operator is called on $x, y_0, y_1, \ldots, y_{k-1}$, from which it follows that the group 0 on x, y_1, \ldots, y_{k-1} consists only of "unrelated" bits. In all other groups rounding can be arbitrary: either up or down.

Algorithm 2 The way to query arbitrary strings

```
function QUERYVIRTUAL(x, y_1, \ldots, y_{k-1}; w)
    -x, y_1, \ldots, y_{k-1} are the virtual coordinate system
    -w is a bit string of length \ell
    OP := \langle n_0, n_1, \ldots \rangle \rightarrow \langle 0, MAKEOPERATOR(n_1, \ldots; w) \rangle
    z \leftarrow \operatorname{OP}(x, y_1, \dots, y_{k-1}); \operatorname{QUERY}(z)
    return z
end function
function MAKEOPERATOR(n_1, \ldots, n_z; w)
    d \leftarrow []; t \leftarrow 1
    for i \in [1; z] do
         if n_i = 1 then
              d \leftarrow \text{APPEND}(d, w_t); t \leftarrow t + 1
         else
              d \leftarrow \operatorname{APPEND}(d, 0)
         end if
    end for
    return d
end function
```

arbitrary injection $g : \{1, \ldots, \ell\} \to \{1, \ldots, 2^{k-1} - 1\}$ such that $n_{g_i} = 1$ for all $1 \leq i \leq \ell$. Since g is an injection, $h = g^{-1}$ exists. We additionally define h(i) = 0 in the case $n_i = 0$. An arbitrary bit string $r = r_1 \ldots r_\ell$ of length ℓ is mapped to the following k-ary unbiased operator:

$$\langle n_0, n_1, \dots, n_i, \dots, n_{2^{k-1}-1} \rangle \to \langle 0, r_{h(1)}, \dots, r_{h(i)}, \dots, r_{h(2^{k-1}-1)} \rangle,$$

where we additionally define $r_0 = 0$ for convenience. On the other hand, when we are given an operator of this sort, we can remove the identity zero positions at index 0 and at indices where h(i) = 0 and unambiguously restore the original string r using the injection g and the remaining positions. This means that this mapping is actually a bijection. Finally, it is Hamming-preserving, since it can be achieved by applying a permutation (which is a composition of g and the permutation of the chosen ℓ indices which appeared as a result of querying strings y_i) and then an $(x \oplus \cdot)$ operation. The algorithm to query arbitrary strings through this bijection is outlined in Algorithm 2.

A k-ary unbiased algorithm cannot access or manipulate the particular bits of the bit strings from the optimization domain, neither can it access or set their particular values. However, it is free to apply arbitrary k-ary unbiased operators. Through the prism of the just introduced bijection, our algorithm is also able to manipulate individual bits by deciding which exactly k-ary unbiased operators to use. At the first sight, this looks like a violation of the definition of a k-ary unbiased algorithm, however, all these operations are still all performed using only k-ary unbiased operators without any access to representations of individuals. In particular, the following statements hold.

- Our algorithm never accesses a bit at the specified index, since the identity of a particular bit is determined by the k bit strings created earlier by unbiased operators, so the bit in question is never fixed in advance and can be any particular bit in different runs of the algorithm.
- Our algorithm also does not know whether the bit value is 1 or 0. In each query made through the bijection described above, the algorithm defines whether this bit (whose position, as said above, is also defined by where exactly and how exactly the k arguments of the corresponding k-ary unbiased operator differ from each other) will have the same or the opposite value as in a certain existing query x.

5 The Proposed Algorithm

In this section we outline the proposed k-ary unbiased algorithm for solving ONE-MAX in $(2 + o(1)) \cdot n/(k-1) = O(n/k)$ queries. We explain the general scheme first (Section 5.1), then give a number of ideas for how to further speed up the algorithm (Section 5.2), and finally give somewhat faster algorithms specialized for k = 3 and 4 (Section 5.3).

In the text below, as well as in algorithm listings, we make a difference between the query procedure QUERY and the call to fitness function FITNESS. We always assume that QUERY must immediately follow the creation of the individual, which associates the fitness value with this individual. The subsequent calls to FITNESS return this computed value and do not count towards the number of queries. We also assume that whenever QUERY is called on a bit string which is the optimum, the algorithm immediately terminates, so we do not have to check this condition.

5.1 The General Form

Similarly to the algorithm from [9], we maintain two bit strings, x and y, to encode which bits are already guessed right. The only difference is that we change the meaning to the opposite one: the bits that differ between x and y are guessed right in x. Initially, x is generated uniformly at random and y = x.

We optimize bits in blocks of size at most $\ell = 2^{k-1} - 1$, where all blocks except for possibly the last one have the maximum possible size ℓ . For every block, we first determine which bits to optimize by querying $y_0 = \text{FLIPELLSAME}(x, y)$, where FLIPELLSAME = $\langle n_0, n_1 \rangle \rightarrow \langle \min(\ell, n_0), 0 \rangle$ is a binary unbiased operator. Then we build the virtual coordinate system as explained in Section 4 and Algorithm 1:

$$(y_1,\ldots,y_{k-1}) = \text{BUILDCOORDINATES}(x,y_0;k).$$

After that we use this coordinate system to forward queries of an unrestricted algorithm solving ONEMAX of length ℓ to the ℓ bits of the original ONEMAX problem of length n using only k-ary unbiased operators.

More formally, we generate random bit strings w_i , $i \ge 1$, of length ℓ and compute their fitness values f_i as follows:

$$f_i = \text{FITNESS}(\text{QUERYVIRTUAL}(x, y_1, \dots, y_{k-1}; w_i)) - \Delta,$$

where $\Delta = (\text{FITNESS}(x) + \text{FITNESS}(y_0) - \ell)/2$ is the term that captures how many ones the bits unrelated to the ℓ chosen bits contribute to the raw fitness value. We repeat this until, for some $i = i_0$, there remains only one string w_{opt} of length ℓ which, according to $(w_1, f_1), (w_2, f_2), \ldots, (w_{i_0}, f_{i_0})$, can be the optimum. Note that this is essentially the same random sampling technique used to solve ONEMAX in an unrestricted manner, however, this particular version does not perform restarts and terminates once the optimum is unambiguously determined.

We should explicitly note here that the random bit strings w_i are not the bit strings in the search space of the original ONEMAX problem, but rather the descriptions of the k-ary unbiased operators.

Yet another concern is that the w_i strings need to be stored somewhere between the queries, which is not explicitly allowed by a definition of a k-ary unbiased blackbox algorithm. However, since any randomized algorithm can be thought of as a deterministic algorithm which uses a long enough precomputed sequence of random numbers as a source of its randomized decisions, the choice of these strings is in fact deterministic, and all these strings can be recomputed from scratch at any convenient moment from the number of already performed queries only. It is also possible to prove a more general version of this idea to allow an arbitrarily large auxiliary storage, accessible in an arbitrary way, available to any k-ary unbiased algorithm, while the only information used to populate this storage is the list of fitness values.

When the optimum string w_{opt} is found, we use the same mechanism to set the ℓ bits to their optimal values while other bits preserve their values. This will be the new value for x, and we update y accordingly:

$$x_{\text{new}} = \text{QUERYVIRTUAL}(x, y_1, \dots, y_{k-1}; w_{\text{opt}}),$$

$$y_{\text{new}} = \text{XOR3}(y, x, x_{\text{new}}),$$

where XOR3 = $\langle n_0, n_1, n_2, n_3 \rangle \rightarrow \langle 0, n_1, n_2, 0 \rangle$ is a ternary unbiased operator essentially performing an exclusive-or operation over its three arguments, also known in the literature as selectBits [4].

We outline the entire algorithm as Algorithm 3. For every block of length ℓ , it spends one query to determine which ℓ bits to optimize, k - 1 queries to build the virtual coordinate system, $(2 + o(1)) \cdot \ell / \log_2 \ell$ queries in expectation to find the optimum and two queries to set the next x and y. Since $k + 2 = O(\log_2 \ell) = o(\ell / \log_2 \ell)$, the entire expected number of queries made by the algorithm is $(2 + o(1)) \cdot n / \log_2 \ell = (2 + o(1)) \cdot n / (k - 1)$, where o(1) is taken relative to k.

We note that the functions COUNTCONSISTENT and GETCONSISTENT in Algorithm 3, operate not on the bit strings in the domain of the original problem, but on the bit strings of length ℓ which define the k-ary unbiased operators (which are stored in W) and on their effective fitness values (which are stored in F). Since their first arguments are lists not of the original bit strings, but rather of the parameters of the k-ary unbiased operators, these functions are free to manipulate with their arguments in an arbitrary, unrestricted way.

5.2 Performance Improvements

There are two main sources for performance improvement of the general algorithm. The first of them is especially significant when k is relatively small. While this issue seems to be not so important when talking about the unbiased black-box complexity questions "in the large", we shall note, however, that the majority of evolutionary algorithms used in practice feature small arities of their operators. For instance, differential evolution [19] typically samples one individual as a linear combination of three different individuals, however it does not sample this individual directly but crosses it over with another individual and only then queries its fitness. This constitutes an operator of arity k = 4. Finding efficient unbiased algorithms even with small constant arities may still shed some light on how powerful such operators are compared to mutations and crossovers.

What we note first is that we can use the fitness values of individuals y_1, \ldots, y_{k-1} , which constitute the virtual coordinate system, to seed the unrestricted algorithm for solving ONEMAX. Although these individuals are not sampled independently, they still limit the number of consistent optima. This effect is expected to, and indeed does, reduce the number of subsequent queries for small constant k. Even one such individual reduces the number of potential optima from 2^{ℓ} to $O(2^{\ell}/\sqrt{\ell})$, and more individuals perform an even better reduction. In fact, for very small k even the chance of hitting the optimum inside Algorithm 1, or immediately after it, is quite noticeable, so in a practical implementation we should check whether a currently sampled string corresponds to the optimum in ℓ bits.

Our second potential improvement comes from an unexpected side, and its impact is experimentally measured but not yet proven for arbitrary n and k. This is a modification in the random sampling unrestricted algorithm to solve ONEMAX, which samples a new bit string to test not uniformly at random among all possible Algorithm 3 The generic k-ary unbiased algorithm for ONEMAX procedure SOLVEONEMAX(n, k) $x \leftarrow \text{UNIFORMRANDOMBITSTRINGOFLENGTH}(n)$ QUERY(x) $y \leftarrow x$ \triangleright Bits different in x and y are guessed right $b \leftarrow 0$ \triangleright The number of bits guessed right while true do if b = 1 then FLIPONEWHERESAME := $\langle n_0, n_1 \rangle \rightarrow \langle 1, 0 \rangle$ FLIPONEWHERESAME(x, y) \triangleright Will terminate there else $\ell \leftarrow \min(b, 2^{k-1} - 1)$ $k \leftarrow 1 + \left\lceil \log_2(\ell + 1) \right\rceil$ \triangleright Can change at the end FLIPELLSAME := $\langle n_0, n_1 \rangle \rightarrow \langle \ell, 0 \rangle$ $y_0 \leftarrow \text{FLIPELLSAME}(x, y)$ $(y_1, \ldots, y_{k-1}) \leftarrow \text{BUILDCOORDINATES}(x, y_0; k)$ $\Delta \leftarrow (\text{FITNESS}(x) + \text{FITNESS}(y_0) - \ell)/2$ W = []; F = []while COUNTCONSISTENT(W, F) > 1 do $w \leftarrow \text{UNIFORMRANDOMBITSTRINGOFLENGTH}(\ell)$ $q \leftarrow \text{QUERYVIRTUAL}(x, y_1, \dots, y_{k-1}; w)$ $f \leftarrow \text{FITNESS}(q) - \Delta$ $W \leftarrow \operatorname{APPEND}(W, w); F \leftarrow \operatorname{APPEND}(F, f)$ end while $w_{\text{opt}} \leftarrow \text{GetConsistent}(W, F)$ $x_{\text{new}} \leftarrow \text{QUERYVIRTUAL}(x, y_1, \dots, y_{k-1}; w_{\text{opt}})$ $XOR3 := \langle n_0, n_1, n_2, n_3 \rangle \rightarrow \langle 0, n_1, n_2, 0 \rangle$ $y \leftarrow \text{XOR3}(y, x, x_{\text{new}})$ $x \leftarrow x_{\text{new}}; b \leftarrow b - \ell$ end if end while end procedure

bit strings, but uniformly at random among all *potential optima*, that is, among strings consistent with the previous samples and measurements.

From now on, we call the original algorithm the *pure*, and this modification the *hack*. Currently we have no proof for the runtime of the *hack*, hence the name. In particular, we do not known whether it is $O(n/\log n)$ and whether it is better or worse than the *pure* algorithm. However, experimental measurements for $2 \le n \le 32$ suggest that the *hack* performs generally better than the *pure*



Figure 2: Experiment results for unrestricted algorithms. 10^4 independent runs were performed for each n. Means and standard deviations are plotted.

algorithm for these values (see Figure 2). In subsequent experiments with the unbiased algorithms, we will evaluate both versions.

5.3 Algorithms for k = 3 and 4

In this section, we describe a custom implementation of the block-wise optimization of ONEMAX using ternary unbiased operators (k = 3). However, since the block size $\ell = 3$, we simply perform the fitness-dependent case analysis instead of explicit construction of the virtual coordinate system and subsequent random sampling.

The algorithm is presented in Algorithm 5, and the operators it uses are given in Algorithm 4. By following its branches and computing the probabilities of their execution, one can prove the expected running time of $9n/8 \pm O(1)$. Note that this is faster than the best known binary unbiased algorithm, whose expected running time is $2n \pm O(1)$ [7]. In a similar way, we designed an algorithm with k = 4 and $\ell = 7$, whose expected running time is $765/896n \pm O(1)$.

Algorithm 4 The operators for Algorithm 5

$$\begin{split} & \text{SAMEX} := \langle n_0, n_1 \rangle \to \langle x, 0 \rangle \\ & \text{ONEWHEREEQUAL} := \langle n_0, n_1, n_2, n_3 \rangle \to \langle 1, 0, 0, 0 \rangle \\ & \text{ONEWHERE2NDDIFFERS} := \langle n_0, n_1, n_2, n_3 \rangle \to \langle 0, 1, 0, 0 \rangle \\ & \text{ONEWHERE3RDDIFFERS} := \langle n_0, n_1, n_2, n_3 \rangle \to \langle 0, 0, 1, 0 \rangle \\ & \text{TWOWHERE3RDDIFFERS} := \langle n_0, n_1, n_2, n_3 \rangle \to \langle 0, 0, 2, 0 \rangle \\ & \text{COMPLICATED} := \langle n_0, n_1, n_2, n_3 \rangle \to \langle 0, n_1, 0, 1 \rangle \\ & \text{XOR3} := \langle n_0, n_1, n_2, n_3 \rangle \to \langle 0, n_1, n_2, 0 \rangle \end{split}$$



Figure 3: Experiment results for k-ary unbiased algorithms on ONEMAX. 100 independent runs were made for each point.

6 Experiments

We have implemented a small programming platform for experimenting with unbiased algorithms of fixed arity. In this platform, the bit strings of individuals are encapsulated in a so-called "unbiased processor", and the individuals are accessed through handles, which reveal only their fitness. Unbiased operators are naturally encoded as functions which map one integer array, $\langle n_0, n_1, \ldots \rangle$, to another one, $\langle d_0, d_1, \ldots \rangle$. With these precautions, the platform ensures that one implements only unbiased algorithms. The source code is available on GitHub.³

By the means of this platform, we have implemented the well-known binary algorithm, Algorithm 5 for k = 3 and 4, as well as the *pure* and *hack* flavors

³https://github.com/mbuzdalov/unbiased-bbc

Algorithm 5 The custom unbiased algorithm for k = 3

```
procedure SOLVEONEMAX3(n)
    x \leftarrow \text{UNIFORMRANDOMBITSTRINGOFLENGTH}(n); y \leftarrow x
    b \leftarrow n
                                                                                            \triangleright How many bits left to be optimized
    while true do
        if b = 1 then
             o \leftarrow \text{SAME1}(x, y); \text{QUERY}(o)
                                                                                                                              ▷ Optimum
         else if b = 2 then
             if FITNESS(x) = n - 2 then
                 o \leftarrow \text{SAME2}(x, y); \text{QUERY}(o)
                                                                                                                              \triangleright Optimum
             else
                 z \leftarrow \text{SAME1}(x, y); \text{QUERY}(z)
                 if FITNESS(z) = n - 2 then
                     o \leftarrow \text{OneWhereEQUAL}(x, y, z); \text{QUERY}(o)
                 end if
                                                                                                  \triangleright Either z or o was the optimum
             end if
        else
             m \leftarrow \text{SAME3}(x, y); \text{QUERY}(m)
             if FITNESS(m) = FITNESS(x) + 3 then
                                                                                                                     \triangleright y is already OK
                 x \leftarrow m
             else if FITNESS(m) = FITNESS(x) - 3 then
                 y \leftarrow \text{XOR3}(x, y, m); \text{QUERY}(y)
                                                                                                                     \triangleright x is already OK
             else if FITNESS(m) = FITNESS(x) + 1 then
                 p \leftarrow \text{TwoWhere3rdDiffers}(x, y, m); \text{Query}(p)
                 if FITNESS(p) = FITNESS(x) + 2 then
                     x \leftarrow p
                 else
                      r \leftarrow \text{COMPLICATED}(x, m, p); \text{QUERY}(r)
                      if FITNESS(r) = FITNESS(x) + 2 then
                          x \leftarrow r
                      else
                          x \leftarrow \operatorname{XOR3}(x, p, r); \operatorname{QUERY}(x)
                      end if
                 end if
                 y \leftarrow \text{XOR3}(x, y, m); \text{QUERY}(y)
             else
                 p \leftarrow \text{OneWhere3rdDiffers}(x, y, m); \text{Query}(p)
                 if FITNESS(p) = FITNESS(x) + 1 then
                     x \leftarrow p
                 else
                     r \leftarrow \text{OneWhere2ndDiffers}(x, m, p)
                      QUERY(r)
                      if FITNESS(r) = FITNESS(x) + 1 then
                         x \leftarrow r
                      else
                         x \leftarrow \text{XOR3}(m, p, r); \text{QUERY}(x)
                      end if
                 end if
                 y \leftarrow \text{XOR3}(x, y, m); \text{QUERY}(y)
             end if
             b \leftarrow b-3
         end if
    end while
end procedure
```

of the generic algorithm for arbitrary fixed arities. We could handle only arities $3 \le k \le 6$, since with k = 7 the block size becomes $\ell = 63$, the size which currently cannot be solved by neither *pure* nor *hack* random sampling in reasonable time.

The experimental results are presented in Figure 3.

For k = 3, both generic algorithms showed the performance of 1.29*n*, which is somewhat greater than 9n/8 = 1.125n by the custom algorithm. However, for k = 4 the runtimes of $\approx 0.958n$ was shown by the pure algorithm, and $\approx 0.934n$ by the hack, both smaller than *n*. The custom algorithm for k = 4 is still slightly faster with 765/896*n* $\approx 0.854n$. For k = 5 the pure and hack versions were $\approx 0.694n$ and $\approx 0.653n$ correspondingly. Finally, for k = 6 the results were close to half the size, with the pure algorithm being slightly above, $\approx 0.505n$, while the hack is slightly below, $\approx 0.476n$.

7 Conclusion

We presented a cleaner and more efficient way to prove that the k-ary unbiased black-box complexity of ONEMAX is O(n/k). Our approach enabled to define the explicit constants: the running time is shown to be $(2+o(1))\cdot n/(k-1)$, where o(1)relates to k. We also showed that unbiased operators are powerful enough to enable solving exponentially large parts of the original problem by arbitrary unrestricted algorithms. Finally, this approach is efficient enough even for the smallest arities $k \geq 3$. We hope that this paper will accelerate and simplify the research on higher-arity operators and their impact on the performance of randomized search heuristics.

8 Acknowledgments

This work was supported by Russian Science Foundation under the agreement No. 17-71-20178.

References

- [1] M. Buzdalov and B. Doerr. Runtime analysis of the $(1 + (\lambda, \lambda))$ genetic algorithm on random satisfiable 3-CNF formulas. In *Proceedings of Genetic and Evolutionary Computation Conference*, pages 1343–1350, 2017.
- [2] B. Doerr and C. Doerr. Optimal parameter choices through self-adjustment: Applying the 1/5-th rule in discrete settings. In *Proceedings of Genetic and Evolutionary Computation Conference*, pages 1335–1342, 2015.
- [3] B. Doerr, C. Doerr, and F. Ebel. From black-box complexity to designing new genetic algorithms. *Theoretical Computer Science*, 567:87–104, 2015.

- [4] B. Doerr, C. Doerr, and T. Kötzing. Unbiased black-box complexities of jump functions—how to cross large plateaus, 2014.
- [5] B. Doerr, C. Doerr, and T. Kötzing. The unbiased black-box complexity of Partition is polynomial. Artificial Intelligence, 216:275–286, 2014.
- [6] B. Doerr, C. Doerr, and J. Yang. Optimal parameter choices via precise black-box analysis. In *Proceedings of Genetic and Evolutionary Computation Conference*, pages 1123–1130, 2016.
- [7] B. Doerr, D. Johannsen, T. Kötzing, P. K. Lehre, M. Wagner, and C. Winzen. Faster black-box algorithms through higher arity operators. In *Proceedings of Foundations of Genetic Algorithms*, pages 163–172, 2011.
- [8] B. Doerr, T. Kötzing, and C. Winzen. Too fast unbiased black-box algorithms. In Proceedings of Genetic and Evolutionary Computation Conference, pages 2043–2050. ACM, 2011.
- B. Doerr and C. Winzen. Reducing the arity in unbiased black-box complexity. In *Proceedings Genetic and Evolutionary Computation*, pages 1309–1316, 2012.
- [10] B. Doerr and C. Winzen. Playing Mastermind with constant-size memory. *Theory of Computing Systems*, 55(4):658–684, 2014.
- [11] B. Doerr and C. Winzen. Ranking-based black-box complexity. Algorithmica, 68(3):571–609, 2014.
- [12] C. Doerr and J. Lengler. Elitist black-box models: Analyzing the impact of elitist selection on the performance of evolutionary algorithms. In *Proceedings* of Genetic and Evolutionary Computation Conference, pages 839–846. ACM, 2015.
- [13] S. Droste, T. Jansen, and I. Wegener. Upper and lower bounds for randomized search heuristics in black-box optimization. *Theory of Computing Systems*, 39(4):525–544, 2006.
- [14] P. Erdős and A. Rényi. On two problems of information theory. Magyar Tudományos Akadémia Matematikai Kutató Intézet Közleményei, 8:229–243, 1963.
- [15] T. Jansen and I. Wegener. The analysis of evolutionary algorithms a proof that crossover really can help. *Algorithmica*, 34:47–66, 2002.

- [16] P. K. Lehre and C. Witt. Black-box search by unbiased variation. In Proceedings of Genetic and Evolutionary Computation Conference, pages 1441–1448. ACM, 2010.
- [17] P. K. Lehre and C. Witt. Black-box search by unbiased variation. Algorithmica, 64:623-642, 2012.
- [18] J. Rowe and M. Vose. Unbiased black box search algorithms. In Proceedings of Genetic and Evolutionary Computation Conference, pages 2035–2042. ACM, 2011.
- [19] R. Storn and K. Price. Differential evolution a simple and efficient heuristic for global optimization over continuous spaces. *Journal of Global Optimization*, 11(4):341–359, 1997.
- [20] D. Sudholt. Crossover speeds up building-block assembly. In Proceedings of Genetic and Evolutionary Computation Conference, pages 689–696, 2012.
- [21] D. Sudholt. How crossover speeds up building block assembly in genetic algorithms. *Evolutionary Computation*, (2):237–274, 2017.