

# On the security of two-way quantum key distribution

Jesni Shamsul Shaari,<sup>1,2</sup> Stefano Mancini,<sup>3,4</sup> Stefano Pirandola,<sup>5</sup> and Marco Lucamarini<sup>6</sup>

<sup>1</sup>*Department of Physics, International Islamic University Malaysia (IIUM),  
Jalan Sultan Ahmad Shah, Bandar Indera Mahkota, 25200 Kuantan, Pahang, Malaysia*

<sup>2</sup>*Institute of Mathematical Research (INSPEM), University Putra Malaysia, 43400 UPM Serdang, Selangor, Malaysia.*

<sup>3</sup>*School of Science & Technology, University of Camerino, I-62032 Camerino, Italy*

<sup>4</sup>*INFN Sezione di Perugia, I-06123 Perugia, Italy*

<sup>5</sup>*Computer Science & York Centre for Quantum Technologies,  
University of York, Deramore Lane, York, YO10 5GH, UK*

<sup>6</sup>*Toshiba Research Europe, 208 Cambridge Science Park, Cambridge CB4 0GZ, UK*

In a recent article entitled “Can Two-Way Direct Communication Protocols Be Considered Secure?” [1], protocols for two-way Quantum Key Distribution (QKD) [2, 3], in particular the Ping-Pong protocol [4] and the LM05 protocol [5], were criticized under a specific well-known attack called “Quantum-Man-in-the-Middle” (QMM) [2, 6, 7]. However, not only such an attack does not disprove the security of two-way QKD, but it also represents one of the weakest strategies available to an eavesdropper.

Two-way QKD involves a bidirectional quantum channel between the users Alice and Bob. Bob sends qubits to Alice, who either encodes or measures them in a randomly chosen basis. The former case corresponds to the encoding or message mode (MM), which is used to define the key; the latter, to the control mode (CM), which is used to detect a potential eavesdropper (Eve). Alice subsequently resubmits the qubits to Bob for his final measurements. The quantum transmission is followed by a public discussion over an authenticated channel, where the users reconcile and distill the final keys.

Ref. [1] overlooked the importance of the CM and purported that two-way QKD becomes insecure when attacks do not induce errors in the MM. The QMM attack is used as a specific example. Here, Eve swaps Bob’s traveling qubit with her own, submits it to Alice and then upon learning Alice’s encoding operation, duplicates it onto Bob’s qubit before returning it to him. Such an attack can only be detected in CM. This is enough for the author of Ref. [1] to conclude that: (i) attacks which leave no errors in the MM do not allow for security to be established by standard methods; (ii) privacy amplification (PA) cannot be executed due to the absence of a ‘critical value’ similar to BB84’s famous 11%; (iii) the existing security proofs [8] are flawed as they do not consider this specific class of attacks.

We argue that the above claims are erroneous and stem from a fundamental misunderstanding of how two-way QKD works.

This can be seen by considering the secure key rate of a QKD protocol. In the asymptotic limit of many signals, we can simply write it as  $R = I_{AB} - I_E$ , with  $I_{AB}$  the mutual information between the users’ keys and  $I_E$  an upper bound on Eve’s information on the key. In two-way QKD,  $I_E$  is obtained from the CM whereas  $I_{AB}$  is estimated from the MM. Therefore, the CM makes it

possible to properly execute the PA whereas the MM enables a proper execution of the EC.

The fact that the QMM attack introduces no error in the MM is inconsequential. In fact, while this implies that  $I_{AB} = 1$ , it also causes an error rate equal to 50%, detected in the CM [2, 6, 7]. Hence, if Eve attacks a fraction  $f$  of the qubits, the resulting secret key rate will be given by  $R = 1 - f \geq 0$ , with equality when  $f = 1$ , i.e., when Eve attacks all the qubits. Therefore, the protocol is always secure against such an attack, for any value of  $f$ . The absence of errors in MM simply ensures the unity value for  $I_{AB}$ , to the legitimate parties’ benefit, and has no bearing in determining the PA rate, which is a function of  $I_E$  estimated from the error rate in CM. Obviously, differing values for errors in CM would translate into differing PA rates, hence differing  $R$ , effectively dismissing the notion of ‘critical value’. However, a similar argument applies even in the BB84 protocol, where the amount of PA executed depends on the actual error rate that has been detected, not on a predetermined critical value like the 11% quoted in Ref. [1].

Finally, Ref. [1] also argued that the analysis in existing security proofs [8], which is based on Eve’s ancillae interacting with Bob’s qubits via some unitary transformation, do not incorporate the QMM attacking strategy. This is clearly untrue as QMM can be described as a specific case of such proofs. It suffices to consider Eve’s ancilla as a qubit and the unitary transformation as the well known SWAP gate [9]. An attack in the backward path is not made explicit as an extremely pessimistic stand is taken where Eve is allowed to extract all possible information from the entire Bob-Eve system without specifying the actual mechanism.

Two-way QKD security proofs are quite complex and include many different aspects. Simple attacks like those described in Ref. [1] have been important to move the first steps in this field, but real progress demands new avenues and better criticism.

**Notes:** Let us remark we do not claim the security of direct communication by the above, rather that of two-way QKD, which is provably secure. It should be noted that despite its title, the commented paper [1] was in fact addressing two-way protocols within a QKD context.

- 
- [1] M. Pavičić, *Nanoscale Research Letters* **12**, 552 (2017) (arXiv:1709.09262 [quant-ph]).
- [2] M. Lucamarini & S. Mancini, *Theoretical Computer Science* **560**, 46 (2014).
- [3] S. Pirandola, S. Mancini, S. Lloyd, & S. L. Braunstein, *Nat. Phys.* **4**, 726 (2008).
- [4] K. Boström & T. Felbinger, *Phys. Rev. Lett.* **89**, 187902 (2002).
- [5] M. Lucamarini & S. Mancini, *Phys. Rev. Lett.* **94**, 140501 (2005).
- [6] B. A. Nguyen, *Phys. Lett. A* **328**, 610 (2004).
- [7] M. Lucamarini, Ph.D. thesis, University of Rome 'Sapienza' (2004).
- [8] H. Lu, C.-H. F. Fung, X. Ma, & Q.-Y. Cai, *Phys. Rev. A* **84**, 042344 (2011).
- [9] M. Nielsen & I. L. Chuang, *Quantum Computation and Quantum Information* (Cambridge Univ. Press 2000).