# Using Stastical and Semantic Models for Multi-Document Summarization

Divyanshu Daiya\*Anukarsh Singh\*Mukesh JadonLNM Institute of InformationLNM Institute of InformationLNM Institute of InformationTechnologyTechnologyTechnologyJaipur, Rajasthan 302031Jaipur, Rajasthan 302031Jaipur, Rajasthan 302031daiyadivyanshu@gmail.comanukarshsingh1@gmail.comjadonmukesh30@gmail.com

## Abstract

We report on series of experiments with different semantic models on top of various statistical models for extractive text summarization. Though statistical models may better capture word cooccurances and distribution around the text but fail to detect the context and the sense of sentences /words as a whole, Semantic models help us gain better insight into context of sentences. We show that how tuning weights between different models can help us achieve considerable results on various benchmarks. Learning pretrained vector's used in semantic models further on given corpus can give addition spike in performance. Using weighing techniques in between various statistical models too further refines our result. For Statstical models we have used TF/IDF, TextRAnk, Jaccard/Cosine Similarities for Semantic Models we have used WordNet based Model, and proposed two models based on Glove Vectors and Facebook's InferSent. We tested our approach on DUC 2004 dataset, generating 100-word summaries. We have discussed the system, algorithms, analysis and also proposed and tested possible improvements. ROUGUE scores were used to compare to other summarizers.

# 1 Introduction

Automatic Text sumarization deals with task to condense documents to a level of human coherant summaries. It's mostly distributed into two distinct domains i.e Abstractive Summarization Dejong, et al. (1978) it involves models to deduce the crux of the document and then presenting a summary with words and phrases that were not

there in the actual document and even paraphrasing Rocktschel, Tim, et al.(2015). A state of art method proposed by Zeng et al. (2016) produces such summaries with length restricted to 75. There have been many recent developments that produce optimistic results, but it is still in developing phase given it's high reliance on natural language processing techniques which is still evolving to match human standards, these shortcoming make abstractive summaries highly domain selective to the areas where NLP techniques have been superlative. While the other technique i.e. Extractive Summarization involves uses different methods to identify the most informative / dominant sentences through the text and present the result ranking them accordingly.

In this paper, we have proposed two novel stand-alone summarization methods based on Glove Model(), and other using Facebook's InferSent () and discussed how we can effectively subdue shortcomings of one model by using it in coalition with models which capture the view that other faintly held.

## 2 Related Work

Methods ranging from determining that length and positioning of sentences in the text can be useful to deduce the importance of sentence in the text (Radev et al. 2004) ,deducing centroid terms to find the importance of text (Radev et al. 2004) by setting a threshold on average TF-IDF scores, using bag-of-words approach i.e. making sentence/Word freq matrix, using signature set of words and assigning them weights to use them as importance measure (Lin and Hovy, 2000), using weights on high frequency words Nenkova et al. (2006) described high frequency terms can be used to deduce the core of document.

While semantic summarizers like Lexical similarity is based on the assumption that important sentences are identified by strong chains (Gupta et al., 2011; Barrera —& Verma, 2012 Murdock, 2006). In other words, it relates sentences that employ words with the same meaning (synonyms) or other semantic relation. It uses WordNet (Miller, George A., et al. 1990 ) to find similarity among words than applies Word Frequency algorithm.POS(Part of Speech) Tagging and WSD(Word Sense Disambiguation) are common among semantic summaizers. Graphical summarizeers like TextRank have also provided great benchmark results ,TextRank assigns weights to important keywords from document using graph based model and sentences which capture most of those concepts/keywords are ranked higher (Barrera, 2012; Mihalcea, 2004) TextRank uses Google's PageRank (Brin and Page, 1998) for graphical modelling. Though semantic and graphical models may better capture the sense of document but miss out on statistical view.

There is a void pertaining to hybrid summarizers, there haven't been many studies made in the area ,Wu et al. (2007) conducted some preliminary research bu there isn't much there on benchmark tests to our knowledge. We use a mixture of statistical and semantic models ,assign weights among them by training on field specific corpuses. As there is a significant variations in choices among different fields. We support our proposal with expectations that shortcomings posed by one model can be filled by positives from others. We deploy experimental analysis to test our proposition.

# **3** Proposed Approach

For Statistical analysis we use Similarity matrices, Word co-occurrence or n-gram model, TF/IDF matrix, for semantic analysis we use custom Glove based model, WordNet based Model, Facebook InferSent Conneau, Alexis, et al. (2017) based Model. For Multi-Document Summarization after training on corpus we assign weights among them .We store the sense vector for document along with weights for future reference. For Single document summarization firstly we calculate the sense vector for document and calculate the nearest vector from the stored Vectors, we use the weight's of nearest vector. We will describe the flow for semantic and statistical model separately.

# 3.1 Prepossessing

Steps that are common for both statistical and semantic models.

# 3.1.1 Sentence Tokenizer

We use NLTK sentence tokenizer sent\_tokenize() based on PUNKT tokenizer pre-trained on a corpus. It can differentiate between Mr., Mrs. and other abbreviations etc. and the normal sentence boundaries et al Kiss, Tibor and Strunk (2006).

Given a document D we tokenize it into sentences as  $\langle s_1, s_2, s_3, s_4...s_n \rangle$ .

#### 3.1.2 Cleaning

Replacing all the special characters with spaces for easier word-tagging and Tokenizing.

#### 3.1.3 Word Tokenizer

We use NLTK word tokenizer to tokenize words which is a Penn Treebankstyle tokenizer.We calculate the totla unique word in the Document and write any sentence,

 $s_i \rightarrow \langle \mathbf{w_I}, \mathbf{w_J}, \mathbf{w_K}, \mathbf{w_L}, .. \rangle, i \in (1, n)$ 

$$(\mathbf{I},\mathbf{J},\mathbf{K},\mathbf{L}...)\subset(1,..M)$$

 $n \rightarrow Total sentences, M \rightarrow Total unique words$ 

## 3.2 Using Stastical Models

#### 3.2.1 Similarity/Correlation Matrices

Frequency Matrix generation Our tokenized words contain redundancy due digits and transitional words such as and ,but etc which carry little information such words are termed stop words et al.Wilbur, W. John, and Karl Sirotkin (1992), we removed stop words and words occurring in <0.2% and >15% of the documents (considering the word frequency over all documents). After, the removal the no. of unique words left in the particular document be p where p<m.We now formulate a matrix  $F_{n\times p}$  where n is total number of sentences,p is total number of unique words left in the document. Element  $e_{ij}$  in the matrix  $F_{n\times p}$  denotes frequency of  $j^{th}$  unique word in the  $i^{th}$  sentence.

Similarity/Correlation Matrix generation We now have have sentence word frequency vector  $\mathbf{Sf_i}$  as  $\langle \mathbf{f_{1i}}, \mathbf{f_{2i}}, \mathbf{f_{3i}}, \dots \mathbf{f_{pi}} \rangle$  where  $f_{ai}$  denotes frequency of  $a^{th}$  unique word in the  $i^{th}$  sentence. We now compute,

Sentence\_similarity(Sf<sub>i</sub>, Sf<sub>j</sub>)

We use three similarity measures :

- 1. Jaccard Similarity
- 2. Cosine Similarity

We generate the similarity matrix  $Sim_{n\times n}^{j}$ for each of the similarity Measure ,where j indexes the similarity Measure. Element  $E_{ij}$ of  $Sim_{n\times n}^{j}$  denote similarity between i<sup>th</sup> and j<sup>th</sup> sentence. Consequeticely we will end with  $Sim_{n\times n}^{1}$ ,  $Sim_{n\times n}^{2}$ ,  $Sim_{n\times n}^{3}$  corresponding to each similarity measure.

**Jaccard Similarity** For some sets A and B, <abr/>a,b,c,... >and <x,y,z,... >respectively,

$$\texttt{Jaccard\_similarity}(\texttt{A},\texttt{B}) \leftarrow \frac{n(A \cap B)}{n(A \cup B)}$$

**Cosine Simmilarity** The Cosine distance between 'u' and 'v', is defined as

$$\texttt{Cosine\_similarity}(\texttt{A},\texttt{B}) \gets 1 - \frac{u \cdot v}{||u||_2 ||v||_2}$$

where  $u \cdot v$  is the dot product of u and v.

#### 3.2.2 PageRank

PageRank algorithm et al larry page devised to rank web-pages forms the core of Google Search, it roughly woks by ranking pages by number and quality of outsourcing links from the page. For NLP a PageRank based technique TextRank have been a major breakthrough in the field. TextRank based summarization have seeded exemplary results on benchmarks. We use a naive TextRank analogous for our task.

Given *n* sentences  $\langle s_1, s_2, s_3, ... s_n \rangle$ , we intent to generate PageRank or probability distribution matrix  $\mathbf{R}_{n \times 1}$ ,

$$\begin{bmatrix} Pr(s_1) \\ Pr(s_2) \\ \vdots \\ Pr(s_n) \end{bmatrix}$$

, where  $Pr(s_k)$  in original paper denoted probability with which randomly browsing user lands on a particular page, for summarization task they denote how strongly a sentence is connected with rest of document, or how well sentence captures multiple views/concepts. The steps are as:

1. Initialize **R** as,

$$\begin{bmatrix} Pr(s_1) \\ Pr(s_2) \\ \vdots \\ Pr(s_n) \end{bmatrix} = \begin{bmatrix} \frac{1}{n} \\ \frac{1}{n} \\ \vdots \\ \frac{1}{n} \end{bmatrix}$$

- 2. Define d, probability that randomly chosen sentence is in summary and  $\varepsilon$  as measure of change i.e. to stop computation when difference between to successive R computations recedes below  $\varepsilon$ .
- 3. Using cosine-similarity matrix  $Sim_{n \times n}^2$  generated in equation [—missing—], as a measure for relation between sentences.

$$\mathbf{R} = \begin{bmatrix} (1-d)/n \\ (1-d)/n \\ \vdots \\ (1-d)/n \end{bmatrix} + \mathbf{d} \times \mathbf{Sim}_{\mathbf{n} \times \mathbf{n}}^{2} \times \mathbf{R}$$

4. Repeat last step until  $|R(t+1) - R(t)| > \varepsilon$ .

5. Take top ranking sentences in **R** for summary.

# 3.2.3 TF/IDF

Term Frequency(TF)/Bag of words is count of how many times word occurs in the given document. Inverse Document Frequency(IDF) is a number of times word occurs in complete corpus. Infrequent words through corpus will have higher weights, while weights for more frequent words will be depreciated.

Underlying steps for TF/IDF summarization are:

1. Create a count vector

 $Doc_1 \leftarrow < fr_{Word_1}, fr_{Word_2}, fr_{Word_3}, .. >$ 

2. Build a tf-idf matrix  $W_{M \times N}$  with element  $w_{i,j}$  as,

$$w_{i,j} = tf_{i,j} \times \log(\frac{N}{df_i})$$

 Score each sentence, taking into consideration only nouns, we use NLTK POS-tagger for identifying nouns.

$$Score(S_{o,j}) \leftarrow \frac{\sum No_{i,j}}{\sum\limits_{p=1}^{N} N_{p,j}}$$

4. Applying positional weighing .

$$Scores[S_{o,j}] = Score(S_{o,j}) \times (\frac{\partial}{T})$$

 $\mathsf{o} \to \texttt{Sentence index}$ 

 $T \rightarrow \texttt{Total}$  sentences in document j

5. Summarize using top ranking sentences.

#### 3.3 Using Semantic Models

We proceed is the same way as we did for statistical model, all the pre-processing steps remain nearly same. We can make a little change by using lemmatizer instead of stemmer, stemming involved removing the derivational affixes/ end of words by heuristic analysis with hope to achieve base form, lemmatization on the other hand involves firstly POS tagging and after morphological and vocabulary analysis reducing the word to its base form. Stemmef output for 'goes' is 'goe' while lemmatized output with verb passed as POS tag is 'go'. Though lemmatization may have little time overhead over stemming it necessary provide better base word reductions. Since WordNet and Glove both require dictionary look-ups so we need better base word mappings, hence Lemmatization is preferred.

#### 3.3.1 Additional Pre-processing

- 1. **Part of Speech(POS) Tagging** We tag the words using NLTK POS-Tagger.
- 2. Lemmatization We use NTLK lemmatizer with POS tags passed as contexts..

#### 3.3.2 Using WordNet

We generated Similarity matrices in case of Statistical Model, we do the same here, but for sentence sentence similarity measure we use method devised by et al. Dao, T. N.,2005. The method is defined as:

- 1. Word Sense Disambiguation(WSD) We use adapted version of Michael Lesk algorithm as devised by et al. Dao, T. N.,2005 to derive the sense for each word.
- 2. Sentence pair Similarity For each pair of sentences we create semantic similarity matrix S, let A and B be two sentences of lengths m and n respectively then the resultant matrix S will of  $m \times n$ , with element  $s_{i,j}$  denoting semantic similarity between sense/synset of word at position i in sentence A and sense/synset of word at position j in sentence B, which is calculated by path length similarity using is-a(hypernym/hyponym) hierarchies, which uses the idea that shorter the path length higher the similarity. To calculate the path length in we proceed following manner.For

two words  $W_1$  and  $W_2$ , with synsets  $s_1$  and  $s_2$  respectively,

$$S_{m \times n} = \begin{bmatrix} sd(s_1, s_2) = 1/distance(s_1, s_2) \\ sd(s_1, s_1) & \dots & sd(s_1, s_n) \\ sd(s_2, s_1) & \ddots & \vdots \\ \vdots & sd(s_i, s_j) \\ sd(s_m, s_1) & \dots & sd(s_m, s_n) \end{bmatrix}$$

We formulate the problem of capturing semantic similarity between sentences as the problem of computing a maximum total matching weight of a bipartite graph, where X and Y are two sets of disjoint nodes. We use the Hungarian method to solve this problem. Finally we get bipartite matching matrix B with entry  $b_{i,j}$  denoting matching between A[i] and B[j]. To obtain the overall similarity we use Dice coefficient,

$$Sim(A,B) = \frac{|A \cap B|}{|A| + |B|}$$

with threshold set to 0.5, and |A|, |B| denoting lengths of sentence A and B respectively.

3. We perform the previous step over all pairs to generate the similarity matrix  $Sim_{N\times N}^4$ .

#### 3.3.3 Using Glove Model

Glove Model provides us with convenient method to represent words as vectors, using vectors representation for words, we generate vector representation for sentences. We work in following order,

- 1. Represent each tokenized word  $w_i$  in its vector form  $\langle a_i^1, a_i^2, a_i^3, \dots, a_i^{300} \rangle$ .
- 2. Represent each sentence into vector using following equation,

$$SVec(s_j) = \frac{1}{|s_j|} \sum_{w_i \in s_j} f_{i,j}(a_i^1, a_i^2, \dots a_i^{300})$$

where  $f_{i,j}$  being frequency of  $w_i$  in  $s_j$ .

- Calculate similarity between sentences using cosine distance between two sentence vectors.
- 4. Populate similarity matrix  $Sim_{N \times N}^5$  using previous step.

# 3.3.4 Using Facebook's InferSent

Infersent is a state of art supervised sentence encoding technique devised by Conneau, Alexis, et al. (2017), it outperformed another sentence encoder SkipThought on benchmark. The model is trained on Stanford Natural Language Inference (SNLI) dataset (Bowman et al., 2015) using seven architectures Long Short-Term Memory (LSTM), Gated Recurrent Units (GRU), forward and backward GRU with hidden states concatenated, Bidirectional LSTMs (BiLSTM) with min/max pooling, self-attentive network and (HCN's) Hierarchical convolutional networks. The network performances are task/corpus specific.

Steps to generate similarity matrix  $Sim_{N\times N}^{6}$  are:

- 1. Encode each sentence to generate its vector representation  $\langle l_i^1, l_i^2, l_i^3, \dots l_i^{4096} \rangle$ .
- 2. Calculate similarity between sentence pair using cosine distance.
- 3. Populate similarity matrix  $Sim_{N \times N}^{6}$  using previous step.

#### 3.4 Generating Summaries

TF-IDF scores and TextRank allows us directly rank sentences and choose k top sentences, where k is how many sentences user want in the summary. On the other hand the similarity matrix based approach as used in case of all Semantic Models, and Similarity/correlation based Statistical models. To rank sentences from Similarity matrix we can use following approaches.

#### 1. Ranking through Relevance score

For each sentence  $s_i$  in similarity matrix the Relevance Score is as,  $RScore(s_i) = \sum_{j=1}^{N} Sim[i, j]$  We can now choose k top ranking sentences by RScores, higher the RScore higher the rank of sentence.

#### 2. Hierarchical Clustering

Given a similarity matrix  $Sim_{N\times N}$ , let  $s_{a,b}$  denote an individual element, then Hierarchical clustering is performed as.

- (a) Initialize a empty list R.
- (b) Choose element with highest similarity value let it be  $s_{i,j}$  where,  $i \neq j, s_{i,j} \neq 0$
- (c) Replace values in column and row i in following manner.  $s_{d,i} = \frac{s_{d,i}+s_{d,j}}{2}, d \in (1, N)$   $[s_{i,d} = \frac{s_{i,d}+s_{j,d}}{2}, d \in (1, N)$

- (d) Replace entries corresponding to column and row *i* by zeros.
- (e) Add *i* and *j* to *R*, if they are not already there.
- (f) Repeat steps 2-5 until single single nonzero element remains, for remaining non-zero element apply Step 5 and terminate.
- (g) We will have rank list R in the end.

We can now choose k top ranking sentences by from R.

#### 3.5 Single Document Summarization

After generating summary from a particular model, our aim is to compute summaries through overlap of different models. Let us have g summarizes from g different models, for  $p_{th}$  summarization model the k sentences contained be,  $Sum_p \leftarrow (s_{(1,p)}, s_{(2,p)} \dots, s_{(k,p)})$  Now for our list of sentences  $\langle s_1, s_2, s_3, ...s_n \rangle$  we define **cWeight** as weight obtained for each sentence using g models.  $cWeight(s_i) = \sum_{j=1}^{g} W_i B(j, s_i)$ where,  $B(j, s_i)$  is a function which returns 1 if sentence is in summary of  $j_{th}$  model, otherwise zero.  $W_i$  is weight assigned to each model without training,  $W_i = \frac{1}{q}, i \in (1, g)$ 

#### 3.6 Multi-Document/Domain-Specific Summarization

We here use machine learning based approach to further increase quality of our summarization technique. The elemental concept here being we use training set of u domain specific documents, with gold standard/human-composed summaries provided we fine tune our weights  $W_i \forall i \in (1, g)$ for different models taking F1-score/F-measure Powers et. al (2011). as factor.

$$F1Score = \frac{2.precision.recall}{precision + recall}$$

We proceed in following manner.

- 1. For each document in training set generate summary using each model independently, compute the  $F_1Score$  w.r.t. gold summary.
- 2. For each model assign the weights using,

$$W_i = \frac{\sum_{j=1}^v f_1^{(j,i)}}{u}, i \in (1,g)$$

where,  $f_1^{(j,i)}$  denotes  $F_1Score$  for  $j_{th}$  model in  $i_{th}$  document.

We now obtain **cWeight** as we did previously, and formulate cumulative summary capturing consensus of different models. We hence used supervised learning algorithm to capture the mean performances of different models over the training data to fine tune our summary.

# 3.7 Domain-Specific Single Document Summarization

As we discussed earlier summarization models are field selective, some model tend to perform remarkably better than others in certain fields. So, instead of assigning uniform weights to all models we can go by following approach.

 For each set of documents we train on we generate document vector using bidirectional GRU (Bahdanau et al., 2014) as described by Yang, Zichao, et al. 2016. for each document. We then generate complete corpus vector as,

$$cDocs = \sum_{i=1}^{v} (a_i^1, a_i^1, a_i^1, \dots, a_i^p,)$$

where, v is total training set size, p is number of features in document vector.

- 2. We save *cDocs* and *weights* corresponding to each corpus.
- 3. For each single document summarization task, we generate given texts document vector, perform nearest vector search over all stored *cDocs*, apply weights corresponding to that corpus.

## 3.8 Experiments

# TABLE 1

AVERAGE ROUGE-2 SCORES FOR DIFFERENT COMBINATION OF MODELS.

Models						Score
А	В	C	D	Е	F	ROUGE2(95%)
		•	-	•	-	0.03172
•				•		0.03357
•		•		•		0.03384
-	•	•		•		0.03479
•	•	-		•		0.03572
•	•	•		•		0.03519
		•			•	0.03821
•		-			•	0.03912
•		•			•	0.03822
-	•	•			•	0.03986
•	•	-			•	0.04003
•	•	•			•	0.03846
-	-	•	•		-	0.03312
•		-	•			0.03339
•		•	•			0.03332
-	•	•	•			0.03532
•	•	-	•			0.03525
•	•	•	•			0.03519
•	•	•	•		•	0.03721
•		-	•		•	0.03689
•		•	•		•	0.03771
•	•	•	•		•	0.03812
•	•	-	•		•	0.03839
•	•	•	•		•	0.03782
-	-	•	-	•	•	0.03615
•		-		•	•	0.03598
•		•		•	•	0.03621
-	•	•		•	•	0.03803
•	•	-		•	•	0.03819
•	•	•		•	•	0.03784
-	-	•	•	•	-	0.03314
•		-	•	•		0.03212
•		•	•	•		0.03426
	•	•	•	•		0.03531
•	•		•	•		0.03544
•	•	•	•	•		0.03529
	-	•	•	•	•	0.03712
•			•	•	•	0.03713
•		•	•	•	•	0.03705
-	•	•	•	•	•	0.03821
•	•	-	•	•	•	0.03829
•	•	•		•	•	0.03772
•	-	-	-		•	0.00112

 $A \rightarrow$  Jaccard/Cosine Similarity Matrix

 $B \rightarrow TextRank$ 

 $C \rightarrow TFIDF$ 

 $D \rightarrow$  WordNet Based Model  $E \rightarrow$  Glove-vec Based Model

 $F \rightarrow$  InferSent Based Model

We evaluate our approaches on DUC(Document Understanding Conferences) 2004 data set. The Dataset have 5 Tasks in total, we work on Task 2. The Task contains 50 news documents cluster for multi-document summarization. Only 665character summaries are provided for each cluster.For evaluation, we use ROGUE an automatic summary evaluation metric, it was firstly used for DUC 2004 data-set, now have become benchmark technique for evaluation purpose. ROUGE is a correlation metric for fixed-length summaries populated using n-gram co-occurrence. For comparison between model summary and to-be evaluated summary separate scores for 1, 2, 3, and 4-gram matching are kept. We use ROUGE-2, a bi-gram based matching for our task.

# TABLE 2

AVERAGE ROUGE-2 SCORES FOR BASE METH-ODS.

Model	ROUGE - 2
Jaccard	0.03468
Cosine	0.02918
TextRank	0.03629
TFIDF	0.03371
WordNet Based Model	0.03354
Glove-vec Based Model	0.03054
InferSent Based Model	0.03812

In the *Table 1* we try different model pairs with weights trained on corpus for Task 2, we have displayed mean ROUGE-2 scores for base Models. We have calculated final scores taking into consideration all normalization's, stemming, lemmatizing and clustering techniques, the ones providing best results were used. We generally expected WordNet, Glove based semantic models to perform better given they better capture crux of sentence and compute similarity using the same, but instead they performed average. This is attributed to fact they assigned high similarity scores to not so semantically related sentences. We also observe that combinations with TFIDF and Similarity Matrices(Jaccard/Cosine) offer nearly same results. InfraSent based Summarizer performed exceptionally well, we initially used pre-trained features to generate sentence vectors through InfraSent, with some domain specific training on labeled data could give us even more spike in performance.

# 3.9 Conclusion/Future Work

We can see that using mixture of Semantic and Statistical models offers improvement over stand alone models. Given better training data results can be further improved. Using domain specific labeled data can povide further increase in performances of Glove and WordNet Model's.

Some esay additions that can be worked on are:

- 1. Unnecessary parts of sentence can be trimmed to improve summary further.
- 2. Using better algorithm to capture sentence vector through Glove Model can improve results.
- 3. Query specific summarizer can be implemented with little additions.
- 4. For generating summary through model overlap's we can also try Graph based methods or different Clustering techniques.