Peres-Style Recursive Algorithms

Sung-il Pae Hongik University Seoul, Korea email: pae@hongik.ac.kr

September 6, 2018

Abstract

Peres algorithm applies the famous von Neumann's trick recursively to produce unbiased random bits from biased coin tosses. Its recursive nature makes the algorithm simple and elegant, and yet its output rate approaches the information-theoretic upper bound. However, it is relatively hard to explain why it works, and it appears partly due to this difficulty that its generalization to many-valued source was discovered only recently. Binarization tree provides a new conceptual tool to understand the innerworkings of the original Peres algorithm and the recently-found generalizations in both aspects of the uniform random number generation and asymptotic optimality. Furthermore, it facilitates finding many new Peres-style recursive algorithms that have been arguably very hard to come by without this new tool.

1 Introduction

Given a coin that turns heads (denoted by 0) with probability p, thus the probability of turning tails (1) being q = 1 - p, the von Neumann's trick takes two coin flips and returns output by the following rule [12]:

$$00 \mapsto \lambda, \ 01 \mapsto 0, \ 10 \mapsto 1, \ 11 \mapsto \lambda, \tag{1}$$

where λ indicates "no output." Because Pr(01) = Pr(10) = pq, the resulting bit is unbiased. By repeating this process, we obtain a sequence of random bits, and the *output rate*, the average number of output per input, is $pq \leq 1/4$. (See, for example, exercise 5.1-3 in [11])

Formalizing this idea [2, 10, 9, 8], an extracting function $f: \{0,1\}^n \to \{0,1\}^*$ takes n independent dent bits of bias p, called Bernoulli source of bias p, and returns independent and unbiased random bits, and its output rate is bounded by the Shannon entropy $H(p) = -(p \lg p + q \lg q)$. When p = 1/3, the output rate of von Neumann's procedure is $pq = 2/9 \approx 0.22$ while the entropy bound $H(1/3) \approx 0.92$; the discrepancy is quite large. But there are asymptotically optimal extracting functions that achieve rates arbitrarily close to the entropy bound.

Consider the functions	defined on	$\{0,1\}^2$	as follows,	where Ψ	$_1$ is	the <i>i</i>	von	Neumann	function
defined by the rule (1) :									

x	$\Pr(x)$	$\Psi_1(x)$	u(x)	v(x)
00	p^2	λ	0	0
01	pq	0	1	λ
10	pq	1	1	λ
11	q^2	λ	0	1

Extend the three functions Ψ_1 , u, and v to $\{0,1\}^*$: for an empty string,

$$\Psi_1(\lambda) = u(\lambda) = v(\lambda) = \lambda$$

for a nonempty even-length input, define (and the same for u and v)

$$\Psi_1(x_1x_2\dots x_{2n}) = \Psi_1(x_1x_2) * \dots * \Psi_1(x_{2n-1}x_{2n}),$$
(3)

where * is concatenation, and for an odd-length input, drop the last bit and take the remaining even-length bits.

Now, define Peres function $\Psi:\{0,1\}^* \to \{0,1\}^*$ by a recursion

$$\begin{cases} \Psi(x) = \Psi_1(x) * \Psi(u(x)) * \Psi(v(x)), \\ \Psi(\lambda) = \lambda. \end{cases}$$
(4)

This simple recursive function is extracting for each input length, and, rather surprisingly, asymptotically optimal [10]. Its implementation is straightforward and runs very fast, in $O(n \log n)$ time for input length n, with a small footprint. Another superiority over other asymptotically optimal extracting algorithms, for example, Elias algorithm [2], is its uniformity. To achieve the asymptotic optimality, these algorithms need to take increasingly longer inputs. While Peres algorithm does this with the same simple fixed function Ψ , Elias algorithm need to compute separately for each input length with increasing complexity.

However, it appears harder to explain why Peres algorithm works than Elias algorithm, and it is quite tempting to say that the algorithm works almost like a magic because of its simplicity of definition and complexity of justification. So a natural question is whether we can find similar recursively defined extracting functions. But the question had remained elusive for a while and it was only recent that its generalizations to many-valued source were discovered [6].

By *Peres-style* recursion we mean a recursion of the style

$$\Psi(x) = \Psi_1(x) * \Psi(u_1(x)) * \cdots * \Psi(u_l(x)),$$

which defines an asymptotically optimal extracting function, where Ψ_1 is extracting and u_1, \ldots, u_l are auxiliary functions defined on a fixed finite-length inputs and extended to arbitrary-length inputs as in (3). If one or more auxiliary functions are omitted, then the resulting recursive function is still extracting but not asymptotically optimal anymore. We always call the base function of the recursion von Neumann function and write as Ψ_1 .

We report a new way to understand and justify Peres-style recursive algorithms using a recent development of *binarization tree* [7]. It provides a simple and unified viewpoint that explains innerworkings of the Peres algorithm and its recently-found generalizations. Furthermore, we report new Peres-style recursive algorithms that have been arguably hard to come by without this new tool.

2 Binarization Tree and Peres Algorithm

Summarized below are necessary backgrounds on extracting functions and binarization trees. In particular, for a binarization tree, we give "structure lemma" and "entropy lemma." The entropy lemma is also known as the "leaf entropy theorem," (see, for example, Section 6.2.2. of [3]) and it is mainly related to the asymptotic optimality of Peres-style recursive algorithms defined by a binarization tree. The structure lemma was first discussed in [7], and, in our context, it is used to show our algorithms are extracting. For more rigorous treatments on the subjects, see [9, 6, 7]. Then, using these new tools, we give a proof that the original Peres algorithm is extracting and asymptotically optimal.

2.1 Extracting Functions

Definition 1 ([10, 9]). A function $f: \{0, 1, ..., m-1\}^n \to \{0, 1\}^*$ is *m*-extracting if for each pair z_1, z_2 in $\{0, 1\}^*$ such that $|z_1| = |z_2|$, we have $\Pr(f(x) = z_1) = \Pr(f(x) = z_2)$, regardless of the distribution $\langle p_0, \ldots, p_{m-1} \rangle$.

Denote by $S_{(n_0,n_1,\ldots,n_{m-1})}$ the subset of $\{0,1,\ldots,m-1\}^n$ that consists of strings with n_i i's. Then

$$\{0, 1, \dots, m-1\}^n = \bigcup_{n_0+n_1+\dots+n_{m-1}=n} S_{(n_0, n_1, \dots, n_{m-1})},$$

and each $S_{(n_0,n_1,\ldots,n_{m-1})}$ is an *equiprobable* subset of elements whose probability of occurrence is $p_0^{n_0}p_1^{n_1}\cdots p_{m-1}^{n_{m-1}}$. When m=2, an equiprobable set $S_{(l,k)}$ is also written as $S_{n,k}$, where n=l+k, and its size can also be written as an equivalent binomial coefficient as well as the multinomial one:

$$\binom{n}{k} = \binom{n}{l,k}.$$

An equivalent condition for a function to be extracting is that it sends equiprobable sets to multiple copies of $\{0,1\}^N$, the exact full set of binary strings of various lengths N's. For example, Table 2.1 shows how von Neumann function and Peres function sends equiprobable sets to such sets.

Definition 2 ([6]). A multiset A of bit strings is extracting if, for each z that occurs in A, all the bit strings of length |z| occur in A the same time as z occurs in A.

$k \ (n=6)$	$\Pr(x)$	$ S_{n,k} $	von Neumann (Ψ_1)	bits	Peres (Ψ)	bits
k = 0	p^6	1	$\{\lambda\}$	0	$\{\lambda\}$	0
k = 1	p^5q	6	$3 \cdot \{0,1\}$	6	$\{0,1\},\{0,1\}^2$	10
k = 2	p^4q^2	15	$3 \cdot \{\lambda\}, 3 \cdot \{0,1\}^2$	24	$\{\lambda\}, \{0,1\}, \{0,1\}^2, \{0,1\}^2$	34
k = 3	p^3q^3	20	$6 \cdot \{0,1\}, \{0,1\}^3$	28	$\{0,1\}^2,3\cdot\{0,1\}^3$	56
k = 4	p^2q^4	15	$3 \cdot \{\lambda\}, 3 \cdot \{0,1\}^2$	24	$\{\lambda\}, \{0,1\}, \{0,1\}^2, \{0,1\}^2$	34
k = 5	pq^5	6	$3 \cdot \{0,1\}$	6	$\{0,1\},\{0,1\}^2$	10
k = 6	q^6	1	$\{\lambda\}$	0	$\{\lambda\}$	0

Table 1: Multiset images of equiprobable sets under extracting functions

Lemma 3 ([6]). A function $f: \{0, 1, ..., m-1\}^n \to \{0, 1\}^*$ is extracting if and only if its multiset image of each equiprobable set $S_{(n_0, n_1, ..., n_{m-1})}$ is extracting.

2.2 Binarization Tree

Let X be a random variable over $\{0, 1, \ldots, m-1\}$ (or, rather, a dice with m faces) with probability distribution $\langle p_0, \ldots, p_{m-1} \rangle$. A sequence $x = x_1 \ldots x_n \in \{0, 1, \ldots, m-1\}^n$ is considered to be taken n times from X.

Given a function $\phi: \{0, 1, \dots, m-1\} \to \{\lambda, 0, 1, \dots, k-1\}$, the random variable $\phi(X)$ has distribution $\langle \pi_0, \dots, \pi_{k-1} \rangle$, where

$$\pi_0 = \sum_{\phi(i)=0} p_i/s, \dots, \pi_{k-1} = \sum_{\Phi(i)=k-1} p_i/s, \text{ and } s = \sum_{\phi(i)\neq\lambda} p_i$$

Extend ϕ to $\{0, 1, \ldots, m-1\}^n$, by letting, for $x = x_1 \ldots x_n$, $\phi(x) = \phi(x_1) \ast \cdots \ast \phi(x_n)$. Then, for an equiprobable set $S = S_{(n_0, \ldots, n_{m-1})}$, its image under ϕ is equiprobable, that is,

$$\phi(S) = S_{(l_0, \dots, l_{k-1})},$$

where

$$l_0 = \sum_{\phi(i)=0} n_i, \dots, l_{k-1} = \sum_{\phi(i)=k-1} n_i.$$

Consider a tree with m external nodes labeled uniquely with $0, 1, \ldots, m-1$. For an internal node v of degree k, define a function $\phi_v : \{0, 1, \ldots, m-1\} \to \{\lambda, 0, 1, \ldots, k-1\}$ as follows:

$$\phi_v(x) = \begin{cases} i, & \text{if } x \in \text{leaf}_i(v), \text{ for } i = 0, \dots, k-1, \\ \lambda, & \text{otherwise.} \end{cases}$$

where $\text{leaf}_i(v)$ is the set of external nodes on the *i*th subtree of v. When X is also an *m*-valued source, call such a tree an *m*-binarization tree over X and ϕ_v its component function.

For example, the following tree with 10 external nodes



defines the following component functions:

x	$\Phi_1(x)$	$\Phi_2(x)$	$\Phi_3(x)$	$\Phi_4(x)$	$\Phi_5(x)$
0	2	λ	0	1	1
1	2	λ	0	0	λ
2	0	0	λ	λ	λ
3	2	λ	2	λ	λ
4	2	λ	0	1	0
5	0	1	λ	λ	λ
6	1	λ	λ	λ	λ
7	2	λ	1	λ	λ
8	2	λ	0	1	2
9	2	λ	0	1	3

(6)

For $S = S_{(n_0, n_1, ..., n_{m-1})}$, we have

$$\begin{split} \Phi_1(S) &= S_{(n_2+n_5,n_6,n_0+n_1+n_3+n_4+n_7+n_8+n_9)}, \\ \Phi_2(S) &= S_{(n_2,n_5)}, \\ \Phi_3(S) &= S_{(n_0+n_1+n_4+n_8+n_9,n_7,n_3)}, \\ \Phi_4(S) &= S_{(n_1,n_0,n_4,n_8,n_9)}, \\ \Phi_5(S) &= S_{(n_4,n_0,n_8,n_9)}, \end{split}$$

and the sizes |S| and $|\Phi_i(S)|$ satisfy

$$|S| = \binom{n}{n_0, \dots, n_9}$$

= $\binom{n}{n_2 + n_5, n_6, n_0 + n_1 + n_3 + n_4 + n_7 + n_8 + n_9} \binom{n_2 + n_5}{n_2, n_5} \dots \binom{n_4 + n_0 + n_8 + n_9}{n_4, n_0, n_8, n_9}$
= $\prod |\Phi_i(S)|.$

In fact, we have a stronger claim. A proof is given in Appendix.

Lemma 4 (Structure Lemma). Let $\Phi = \{\Phi_1, \ldots, \Phi_M\}$ be the set of component functions defined by an *m*-binarization tree. Then the mapping $\Phi: x \mapsto \Phi(x) = (\Phi_1(x), \ldots, \Phi_M(x))$ gives a one-toone correspondence between an equiprobable subset $S = S_{(n_0,n_1,\ldots,n_{m-1})}$ and $\Phi_1(S) \times \cdots \times \Phi_M(S)$, the Cartesian product of equiprobable sets $\Phi_j(S)$'s. For a node v of a binarization tree T and its degree is k, let

$$P(v) = \sum_{i \in \text{leaf}(v)} p_i,$$

where $\operatorname{leaf}(v) = \bigcup_{i=0,\dots,k-1} \operatorname{leaf}_i(v)$, and let

$$\pi_0(v) = \sum_{i \in \text{leaf}_0(v)} p_i / P(v),$$

$$\vdots$$

$$\pi_{k-1}(v) = \sum_{i \in \text{leaf}_{k-1}(v)} p_i / P(v)$$

so that $\phi_v(X)$ has the distribution $\pi(v) = \langle \pi_0(v), \dots, \pi_{k-1}(v) \rangle$. Then we have the following lemma that is also well-known as the leaf entropy theorem. See, for example, Lemma E in Section 6.2.2 of [3].

Lemma 5 (Entropy Lemma).

$$H(X) = \sum_{v \in T} P(v)H(\pi(v))$$

2.3 Peres Algorithm Revisited

Let Y be a Bernoulli random variable with distribution $\langle p, q \rangle$. Consider the following binarization tree over $X = Y^2$, the random variable with values $\{0, 1\}^2 = \{00, 01, 10, 11\}$ and distribution $\langle p^2, pq, pq, q^2 \rangle$, and:



Then the component functions $\{u, v, \Psi_1\}$ defined by this binarization tree are exactly the same as those of Peres algorithm given in (2)!

Theorem 6. Peres function Ψ is extracting.

Proof. Observe that, for an equiprobable set $S \subset \{0,1\}^{2n}$, $\Psi(S) = \Psi_1(S) * \Psi(u(S)) * \Psi(v(S))$. This does not hold in general. But, for equiprobable sets, we have one-to-one correspondence Φ given by the binarization tree (7) and $\Phi(S) = \Psi_1(S) \times u(S) \times v(S)$ by the structure lemma. Consider a function Ψ' on $\{0,1\}^* \times \{0,1\}^* \times \{0,1\}^*$ defined by $\Psi'(x,u,v) = x * \Psi(u) * \Psi(v)$. For sets A, B, and C, we have $\Psi'(A \times B \times C) = A * \Psi(B) * \Psi(C)$. Since $\Psi = \Psi' \circ \Phi$, we conclude that $\Psi(S) = \Psi_1(S) * \Psi(u(S)) * \Psi(v(S))$.

Note, here, that u(S) and v(S) are equiprobable. Now, by the induction on the length of strings, $\Psi(u(S))$ and $\Psi(v(S))$ are extracting. Since Ψ_1 is extracting, so is $\Psi_1(S)$. So, their concatenation $\Psi(S)$ is extracting, and thus Ψ is extracting. **Theorem 7.** Peres function Ψ is asymptotically optimal.

Proof. By the entropy lemma,

$$H(Y^2) = 2pqH(\Psi_1(Y^2)) + H(u(Y^2)) + (p^2 + q^2)H(v(Y^2)).$$

The nodes of our binarization tree have distributions

$$u(Y^{2}): \quad \langle p^{2} + q^{2}, 2pq \rangle,$$

$$v(Y^{2}): \quad \langle p^{2}/(p^{2} + q^{2}), q^{2}/(p^{2} + q^{2}) \rangle$$

$$\Psi_{1}(Y^{2}): \quad \langle \frac{1}{2}, \frac{1}{2} \rangle.$$

Since $H(Y^2) = 2H(p)$ and $H(\Psi_1(Y^2)) = 1$, we have

$$H(p) = pq + \frac{1}{2}H(p^2 + q^2) + \frac{1}{2}(p^2 + q^2)H(p^2/(p^2 + q^2)).$$
(8)

Consider the truncated versions of Peres function, whose recursion depths are bounded by ν , defined as follows:

$$\Psi_{\nu}(x) = \Psi_{1}(x) * \Psi_{\nu-1}(u(x)) * \Psi_{\nu-1}(v(x)),$$

$$\Psi_{0}(x) = \lambda.$$

So the von Neumann function Ψ_1 has recursion depth 1, and if $|x| \leq 2^{\nu}$, then $\Psi(x) = \Psi_{\nu}(x)$.

The output rate $r_{\nu}(p)$, for the source distribution $\langle p, q \rangle$, of Ψ_{ν} satisfies the recursion (See [10, 6, 5])

$$r_{\nu}(p) = r_1(p) + \frac{1}{2}r_{\nu-1}(p^2 + q^2) + \frac{1}{2}(p^2 + q^2)r_{\nu-1}(p^2/(p^2 + q^2)),$$
(9)

Note, here, that $u(Y^2)$ and $v(Y^2)$ has distributions $\langle p^2 + q^2, 2pq \rangle$ and $\langle p^2/(p^2 + q^2), q^2/(p^2 + q^2) \rangle$, respectively, and $r_1(p) = pq$, and $r_0(p) = 0$. Consider the operator T on $\{f : [0,1] \to \mathbf{R} \mid \lim_{t\to 0} f(t) = \lim_{t\to 1} f(t) = 0\}$ defined by

$$T(f)(p) = r_1(p) + \frac{1}{2}f(p^2 + q^2) + \frac{1}{2}(p^2 + q^2)f(p^2/(p^2 + q^2)).$$
(10)

Then $r_{\nu}(p) = T^{(\nu)}(r_0)(p)$ is increasing and bounded by H(p). By (8), H(p) is a fixed point of T and thus $\lim_{\nu\to\infty} r_{\nu}(p) = H(p)$.

In the rest of the paper, for each Peres-style recursion, we give a binarization tree whose component functions define the von Neumann function Ψ_1 and auxiliary functions u_1, \ldots, u_l . The resulting recursive function $\Psi(x) = \Psi_1(x) * \Psi(u_1(x)) * \cdots * \Psi(u_l(x))$ is extracting exactly in the same manner as in Theorem 6; an equiprobable set S is sent to an extracting multiset $\Psi_1(S)$ and the Cartesian product of equiprobable sets $u_1(S) \times \cdots \times u_l(S)$ which in turn becomes extracting multiset $\Psi(u_1(S)) * \cdots * \Psi(u_l(S))$ so that $\Psi(S)$ is extracting. For the asymptotical optimality, the operator T is again defined by the binarization tree to be

$$T(f)(\vec{p}) = r_1(\vec{p}) + P(u_1)f(\pi(u_1)) + \dots + P(u_l)f(\pi(u_l)),$$
(11)

where $r_1(\vec{p})$ is the output rate $P(\Psi_1)$ of the von Neumann function and $P(u_i)$ is the probability for the node corresponding to the component function u_i and $\pi(u_i)$ is the node's branching probability distribution. In the same manner as in Theorem 7, the output rates of the truncated recursive functions give rise to a monotone increasing sequence converging to the Shannon entropy because the entropy is the fixed point of the operator T by the entropy lemma since T is defined by the binarization tree.

3 Peres-Style Recursive Algorithms

Section 3.1 and 3.2 present the binarization trees for the recently-found generalizations of Peres algorithm in [6], and the rest of the paper discusses brand-new Peres-style recursive algorithms.

3.1 3-Face Peres Algorithm

Suppose that we want to find a generalization of Peres algorithm that works on a 3-faced source Y with a distribution $\langle p, q, r \rangle$. As in the original Peres algorithm, we take two samples and use the obvious generalization of von Neumann function which we use the same name Ψ_1 . We devise a binarization tree with $3^2 = 9$ external nodes, whose component function includes Ψ_1 :



Verify that the component functions are the same as the auxiliary functions of the 3-faced Peres function given in [6], except that the functions Ψ_{11} , Ψ_{12} and Ψ_{13} with disjoint supports are combined, which we denote by $\Psi_1 = \Psi_{11} \oplus \Psi_{12} \oplus \Psi_{13}$:

x	$\Pr(x)$	$\Psi_1(x)$	u(x)	v(x)	w(x)
00	p^2	λ	0	0	λ
01	pq	0	1	λ	1
02	pr	0	1	λ	2
10	pq	1	1	λ	1
11	q^2	λ	0	1	λ
12	qr	0	1	λ	0
20	pr	1	1	λ	2
21	qr	1	1	λ	0
22	r^2	λ	0	2	λ

Since Ψ_{11} , Ψ_{12} and Ψ_{13} are extracting and have disjoint supports, $\Psi_1(x) = \Psi_{11}(x) * \Psi_{12}(x) * \Psi_{13}(x)$, and thus Ψ_1 is extracting. Then the resulting recursive function $\Psi(x) = \Psi_1(x) * \Psi(u(x)) * \Psi(v(x)) * \Psi(w(x))$ is extracting and asymptotically optimal, where the entropy bound is H(p,q,r).

3.2 4-Face Peres Algorithm

A 4-Face Peres function is given in [6], and it is defined by the following binarization tree of $4^2 = 16$ external nodes:



whose component functions are as follows, where $\Psi_1 = \Psi_{11} \oplus \Psi_{12} \oplus \ldots \Psi_{16}$, again, as in [6]:

x	$\Psi_1(x)$	u(x)	v(x)	$w_1(x)$	$w_2(x)$
00	λ	0	0	λ	λ
01	0	1	λ	0	λ
02	0	1	λ	1	λ
03	0	1	λ	2	λ
10	1	1	λ	0	λ
11	λ	0	1	λ	λ
12	0	1	λ	3	λ
13	0	2	λ	λ	0
20	1	1	λ	1	λ
21	1	1	λ	3	λ
22	λ	0	2	λ	λ
23	0	2	λ	λ	1
30	1	1	λ	2	λ
31	1	2	λ	λ	0
32	1	2	λ	λ	1
33	λ	0	3	λ	λ

Alternatively, consider, for example,



and the corresponding component functions are as follows:

x	$\Psi_1(x)$	u(x)	v(x)	$w_1(x)$	$w_2(x)$
00	λ	0	0	λ	λ
01	0	1	λ	0	λ
02	0	1	λ	1	λ
03	0	1	λ	2	λ
10	1	1	λ	0	λ
11	λ	0	1	λ	λ
12	0	1	λ	3	λ
13	0	1	λ	λ	0
20	1	1	λ	1	λ
21	1	1	λ	3	λ
22	λ	0	2	λ	λ
23	0	1	λ	λ	1
30	1	1	λ	2	λ
31	1	1	λ	λ	0
32	1	1	λ	λ	1
33	λ	0	3	λ	λ

3.3 3-bit Peres Algorithm

Now consider a brand-new situation in which m = 2 but the component functions are defined on 3 bits instead of 2 bits as with all the examples given above:

v_1 $v_2 \Psi_{11}$ Ψ_{12} 000 111 100 110 001 010 011 101									
x	$\Pr(x)$	u(x)	v(x)	$v_1(x)$	$v_2(x)$	$\Psi_1(x)$	w(x)		
000	p^3	0	0	0	λ	λ	λ		
001	p^2q	1	λ	λ	λ	0	0		
010	p^2q	1	λ	λ	λ	1	0		
011	pq^2	1	λ	λ	λ	0	1		
100	p^2q	0	1	λ	0	λ	λ		
101	pq^2	1	λ	λ	λ	1	1		
110	pq^2	0	1	λ	1	λ	λ		
111	q^3	0	0	1	λ	λ	λ		

(12)

The three-bit von Neumann function $\Psi_1 = \Psi_{11} \oplus \Psi_{12}$ does not utilize inputs 100 and 110, and the output rate 2(p+q)pq/3 = 2pq/3 is strictly smaller than pq of the two-bit case. Therefore, even

though 3-bit Peres algorithm is asymptotically optimal, the convergence to the entropy bound must be slower.

3.4 4-bit Peres Algorithm

If we ever wanted to have a 4-bit Peres function in this fashion, then can we use E_4 , the Elias function of input size 4 as the base of the recursion? Note, in the three-bit case, Ψ_1 of (12) is actually E_3 . With E_4 , among 16 inputs, only 2 inputs, 0000 and 1111, are wasted. Consider the following binarization tree:



So we have the following recursion:

$$\Psi(x) = E_4(x) * \Psi(u(x)) * \Psi(v(x)) * \Psi(w(x)) * \Psi(w_1(x)) * \Psi(w_2(x))$$

The rate of E_4 is

$$\begin{aligned} \frac{1}{4} \left(2 \cdot 4p^3 q + (2 \cdot 4 + 2)p^2 q^2 + 2 \cdot 4pq^3 \right) &= \frac{1}{4} pq(8p^2 + 10pq + 8q^2) \\ &= pq(1 + p^2 + q^2 + \frac{1}{2}pq) \\ &> 1.65 \cdot pq. \end{aligned}$$

However, it seems that the convergence is slower than the original Peres function. For a fair comparison, we need to see how the original Peres function on $\{0,1\}^{4n}$. Consider, for $x \in \{0,1\}^4$,

$$\Psi^{2}(x) = \Psi_{1}(x) * \Psi_{1}(u(x)) * \Psi_{1}(v(x)) * \Psi^{2}(uu(x)) * \Psi^{2}(vu(x)) * \Psi^{2}(uv(x)) * \Psi^{2}(vv(x)).$$

The output rate of base part of this recursion is

$$pq + pq(p^{2} + q^{2}) + \frac{1}{2}p^{2}q^{2}/(p^{2} + q^{2}) = pq(1 + p^{2} + q^{2} + \frac{1}{2}pq/(p^{2} + q^{2}))$$

> $pq(1 + p^{2} + q^{2} + \frac{1}{2}pq).$

So the comparison favors the original Peres function. The following plot compares this rate with that of E_4 , where the red one being the rate of Ψ^2 :



3.5 Dijkstra's roulette

Dijkstra's one-page paper [1] describes an interesting algorithm that simulates a fair roulette from a biased coin: suppose m is a prime; take m flips of the coin, encoded as a binary string x in $\{0, 1\}^m$. If $x = 0 \dots 0$ or $x = 1 \dots 1$, then try again, otherwise, output y the number of cyclic shifts to obtain the lexicographic minimum. The virtues of this scheme are, as with Peres algorithm, simplicity and efficiency, although output rate is much lower than, for example, Elias's algorithm for m-faced dice using a coin, in which case again asymptotically optimal with output rate approaching $H_m(p)$, the Shannon entropy with base m. Using Dijkstra's scheme together with Peres-style recursion, we can reach out the both side of virtues.

Consider a simple case of m = 3 with a biased coin as a source. The Dijkstra's scheme enhanced with Peres-style recursion is described by the following binarization tree:



Note, here, that the base function has three branches while auxiliary functions are binary because we use a coin as the source and outputs are to be three-valued. The resulting recursion $\Psi(x) = \Psi_1(x) * \Psi(u(x)) * \Psi(v(x)) * \Psi(w(x))$ outputs a uniform three-valued random numbers with an output rate that approaches $H_3(p)$, the Shannon entropy with base 3, as the input size tends to infinity.

When m = 5, consider the following binarization tree:



where $\Psi_{11}, \ldots, \Psi_{16}$ are five-valued extracting functions, which gives the base function $\Psi_1 = \Psi_{11} \oplus \cdots \oplus \Psi_{16}$.

Now, as m increases, as we can see already in m = 5 case, the corresponding binarization tree grows complicated so much that the advantage of the simplicity disappears quickly. Note that, in (14), the supports of the functions $\Psi_{11}, \ldots, \Psi_{16}$ are exactly the orbits with respect to the group action by rotation on $\{0, 1\}^5$ [4]. For a prime number m, there are $(2^m - 2)/m$ such orbits, and Dijkstra's algorithm is based on this property. So the height of the binarization tree grows almost linearly and the number of nodes exponentially. However, observe that the subtree rooted at w in (14) can be regarded as a binary search tree whose search keys are $\Psi_{11}, \ldots, \Psi_{16}$. So we can make a compromise and keep only the nodes with high probability of output.

For example, for m = 11, consider the following binarization tree:



Here, we partition the orbits into four sets S_1, \ldots, S_4 appropriately, for example, by the number of 1's. Then, auxiliary functions w, w_1 and w_2 are easily computed by counting the number of 1's in the input $x \in \{0, 1\}^{11}$. The base function Ψ_1 is computed using the original Dijkstra algorithm. The corresponding Peres-style recursion is

$$\Psi(x) = \Psi_1(x) * \Psi(u(x)) * \Psi(v(x)) * \Psi(w_1(x)) * \Psi(w_2(x))$$

is still extracting but not asymptotically optimal.

Appendix: The Proof of Structure Lemma

Given a binarization tree, let T be a subtree and X_T be the restriction of X on the leaf set of T. The leaf entropy theorem is proved by induction using the following recursion,

$$H(X_T) = \begin{cases} 0, & \text{if } T \text{ is a leaf,} \\ H(\pi) + \pi_0 H(X_{T_0}) + \dots + \pi_{d-1} H(X_{T_{d-1}}), & \text{otherwise,} \end{cases}$$
(15)

where, for nonempty T whose root v has degree d, T_0, \ldots, T_{d-1} are the subtrees of v and $\pi = \langle \pi_0, \ldots, \pi_{d-1} \rangle$ is the branching distribution of v. The structure lemma holds for a similar reason.

Proof of Structure Lemma. For an equiprobable subset $S = S_{(n_0,...,n_{m-1})}$ and a subtree T of the given binarization tree, let S_T be the restriction of S on the leaf set of T. Then we have a similar recursion

$$S_T \cong \begin{cases} \{0\}, & \text{if } T \text{ is a leaf,} \\ S_{(l_0,\dots,l_{d-1})} \times S_{T_0} \times \dots \times S_{T_{d-1}}, & \text{otherwise,} \end{cases}$$
(16)

where, for nonempty T and its root v, T_0, \ldots, T_{d-1} are the subtrees of v and

$$l_0 = \sum_{\phi_v(i)=0} n_i, \dots, l_{d-1} = \sum_{\phi_v(i)=d-1} n_i$$

so that $\phi_v(S) = S_{(l_0,...,l_{d-1})}$.

First, if T is a leaf with label i, then S_T is a singleton set that consists of a single string of n_i i's, hence the first part of (16). When T is nonempty, the correspondence $S_T \to S_{(l_0,\ldots,l_{d-1})} \times S_{T_0} \times \cdots \times S_{T_{d-1}}$ is given by $x \mapsto (\phi_v(x), x_{T_0}, \ldots, x_{T_{d-1}})$, where $x_{T_0}, \ldots, x_{T_{d-1}}$ are restrictions of x. This correspondence is one-to-one because $\phi_v(x)$ encodes the branching with which x is recovered from $(x_{T_0}, \ldots, x_{T_{d-1}})$, giving an inverse mapping $S_{(l_0,\ldots,l_{d-1})} \times S_{T_0} \times \cdots \times S_{T_{d-1}} \to S_T$. For example, consider tree (5) and suppose that T is the subtree rooted at the node 3. For x = 207643590289787, the following shows the restrictions of x and $\Phi_i(x)$'s.



By taking symbols one by one from $x_{T_0} = 0490898$, $x_{T_1} = 777$, and $x_{T_2} = 3$, according to $\Phi_3(x) = 01020000101 = (b_i)_{i=1}^{11}$, if $b_i = j$, from x_{T_i} , we recover $x_T = 07439890787$.

Induction on subtrees proves the lemma.

References

- [1] Edsger W. Dijkstra. Making a fair roulette from a possibly biased coin. *Information Processing Letters*, 36:193, 1990.
- [2] Peter Elias. The efficient construction of an unbiased random sequence. The Annals of Mathematical Statistics, 43(3):865–870, 1972.
- [3] Donald E. Knuth. *The Art of Computer Programming, Sorting and Searching*, volume 3. Addison-Wesley, 2 edition, 1998.
- [4] Serge Lang. Algebra (3. ed.). Addison-Wesley, 1993.
- [5] Sung-il Pae. Exact output rate of Peres's algorithm for random number generation. Inf. Process. Lett., 113(5-6):160-164, 2013.
- [6] Sung-il Pae. A generalization of Peres's algorithm for generating random bits from loaded dice. *IEEE Transactions on Information Theory*, 61(2), 2015.
- [7] Sung-il Pae. Binarizations in random number generation. In *IEEE International Symposium* on Information Theory, ISIT 2016, Barcelona, Spain, July 10-15, 2016, pages 2923–2927, 2016.
- [8] Sung-il Pae and Michael C. Loui. Optimal random number generation from a biased coin. In Proceedings of the Sixteenth Annual ACM-SIAM Symposium on Discrete Algorithms, pages 1079–1088, January 2005.
- [9] Sung-il Pae and Michael C. Loui. Randomizing functions: Simulation of discrete probability distribution using a source of unknown distribution. *IEEE Transactions on Information Theory*, 52(11):4965–4976, November 2006.
- [10] Yuval Peres. Iterating von Neumann's procedure for extracting random bits. Annals of Statistics, 20(1):590–597, 1992.
- [11] C. Stein, T. H. Cormen, R. L. Rivest, and C. E. Leiserson. Introduction to Algorithms. MIT Press, second edition, 2001.
- [12] John von Neumann. Various techniques for use in connection with random digits. Notes by G. E. Forsythe. In *Monte Carlo Method, Applied Mathematics Series*, volume 12, pages 36–38. U.S. National Bureau of Standards, Washington D.C., 1951. Reprinted in von Neumann's *Collected Works* 5 (Pergammon Press, 1963), 768–770.