Adversarial Training of Word2Vec for Basket Completion

Ugo Tanielian Criteo Research UPMC Paris, France u.tanielian@criteo.com Mike Gartrell Criteo Research Paris, France m.gartrell@criteo.com Flavian Vasile Criteo Research Paris, France 43017-6221 f.vasile@criteo.com

ABSTRACT

In recent years, the Word2Vec model trained with the Negative Sampling loss function has shown state-of-the-art results in a number of machine learning tasks, including language modeling tasks, such as word analogy and word similarity, and in recommendation tasks, through Prod2Vec, an extension that applies to modeling user shopping activity and user preferences. Several methods that aim to improve upon the standard Negative Sampling loss have been proposed. In our paper we pursue more sophisticated Negative Sampling, by leveraging ideas from the field of Generative Adversarial Networks (GANs), and propose Adversarial Negative Sampling. We build upon the recent progress made in stabilizing the training objective of GANs in the discrete data setting, and introduce a new GAN-Word2Vec model. We evaluate our model on the task of basket completion, and show significant improvements in performance over Word2Vec trained using standard loss functions, including Noise Contrastive Estimation and Negative Sampling.

CCS CONCEPTS

•Theory of computation \rightarrow Structured prediction; Adversarial learning; •Computer systems organization \rightarrow Neural networks;

ACM Reference format:

Ugo Tanielian, Mike Gartrell, and Flavian Vasile. 2018. Adversarial Training of Word2Vec

for Basket Completion. In Proceedings of ACM Confernce on Recommender Systems, Vancouver, Canada, October 2018 (RecSys'18), 5 pages. DOI: 10.475/123_4

1 INTRODUCTION

The recommendation task of basket completion is a key part of many online retail applications. Basket completion involves computing predictions for the next item that should be added to a shopping basket, given a collection of items that the user has already added to the basket.

RecSys'18, Vancouver, Canada

© 2018 ACM. 123-4567-24-567/08/06...\$15.00 DOI: 10.475/123_4

In this context of basket completion, learning item embedding representations can lead to state-of-the-art results, as shown in [24]. Within this class of approaches, *Word2Vec* [15], and its item-based extension *Prod2Vec* [10], have become the de-facto standard approach, due to the conceptual simplicity, implementation simplicity, and state-of-the-art performance of these models.

In terms of training and the use of negatives, there have been many extensions of the classical Word2Vec model based on the Negative Sampling (NS) loss function [16], such as Swivel [21]. However, these approaches do not have a dynamic way of sampling the most informative negatives. This shortcoming was addressed by [4], which proposes an active sampling heuristic. In our paper we propose GAN-Word2Vec, an extension of Word2Vec that uses ideas from Generative Adversarial Networks (GANs) to create an adversarial negative sampling approach that places dynamic negative sampling on firmer theoretical grounds, and shows significant improvements in performance over the classical training approaches. In our current structure the generator is also trained adversarially and benefits from a better training signal coming from the discriminator. In terms of training stability, which becomes an issue in GAN-like settings, our algorithm builds upon recent advances that make GAN training stable for discrete input data. We evaluate the performance of our GAN-Word2Vec model on a basketcompletion task and show that it outperforms classical supervised approaches such as Word2Vec with Negative Sampling by a significant margin.

Overall, the main contributions of this paper are the following:

- We propose a new dynamic negative sampling scheme for Word2Vec based on ideas from GANs. To the best of our knowledge, we are the first to implement adversarial training for Word2Vec.
- We introduce a stable training algorithm that implements our adversarial sampling scheme.
- Through an experimental evaluation on two real-world datasets, we show that our GAN-Word2Vec model outperforms classical sampling schemes for Word2Vec.

We briefly discuss related work on sampling schemes for Word2Vec and the recent developments on GAN training in discrete settings in Section 2 of this paper. In Section 3, we formally introduce our *GAN-Word2Vec* model and describe the training algorithm. We highlight the performance of our method in Section 4, and conclude with main ideas and directions for future work in Section 5.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

RecSys'18, October 2018, Vancouver, Canada

2 RELATED WORK

2.1 Basket Completion with Embedding Representations

In the recent years, a substantial amount of work has focused on improving the performance of language modeling and text generation. In both tasks, Deep Neural Networks (DNNs) have proven to be extremely effective, and are now considered state-of-the-art. In this paper, we focus on the task of basket completion with learned embedding representations. For the task of basket completion, very little work has focused on applying DNNs, with the notable exception of [24]. In this paper, the authors introduced a new family of networks designed to work on sets, where the output is invariant to any permutation in the order of objects in the input set. As an alternative to a set-based interpretation, basket completion can be approached as a sequence generation task, where one seeks to predict the distribution of the next item conditioned on the items already present in the basket. First, one could use the Skip-Gram model proposed by [16], and use the average of the embeddings for the items within a basket to compute the next-item prediction for the basket. Second, building upon work on models for text generation, it is natural to leverage Recurrent Neural Networks (RNNs), particularly Long Short Term Memory cells, as proposed by [12], or bi-directional LSTMs [9, 20]. Convolutional neural networks could also be used, for example by using a Text-CNN like architecture as proposed by [13]. The authors of [13] empirically show on different tasks, such as point cloud classification, that their method outperforms state-of-the-art results with good generalization properties.

2.2 Negative sampling schemes for Word2Vec

When dealing with the training of multi-class models with thousands or millions of output classes, candidate sampling algorithms can speed up the training by considering a small randomly-chosen subset of contrastive candidates for each batch of training examples. Ref. [11] introduced Noise Contrastive Estimation (NCE) as an unbiased estimator of the softmax loss, and has been proven to be efficient for learning word embeddings [17]. In [16], the authors propose *negative sampling* and directly sample candidates from a noise distribution.

More recently, in [4], the authors provide an insightful analysis of negative sampling. They show that negative samples with high inner product scores with a context word are more informative in terms of gradients on the loss function. Leveraging this analysis, the authors propose a dynamic sampling method based on innerproduct rankings. This result can be intuitively interpreted by seeing that negative samples with a higher inner product will lead to a better approximation of the softmax.

In our setup, we simultaneously train two neural networks, and use the output distribution coming from one network to generate the negative samples for the second network. This *adversarial negative sampling* proves to be a dynamic and efficient way to improve the training of our system. This method echoes the recent work on Generative Adversarial Networks.

2.3 GANs

First proposed by [8] in 2014, Generative Adversarial Networks (GANs) have been quite successful at generating realistic images. GANs can be viewed as a framework for training generative models by posing the training procedure as a minimax game between the generative and discriminative models. This adversarial learning framework bypasses many of the difficulties associated with maximum likelihood estimation (MLE), and has demonstrated impressive results in natural image generation tasks.

Theoretical work [1, 14, 18, 25] and practical studies [2, 5, 19] have stabilized GAN training and enabled many improvements in continuous spaces. However, in discrete settings a number of important limitations have prevented major breakthroughs. A major issue involves the complexity of backpropagating the gradients for the generative model. To bypass this differentiation problem, [3, 23] proposed a cost function inspired by reinforcement learning. The discriminator is used as a reward function and the generator is trained via policy gradient [22]. Additionally, the authors propose the use of importance sampling and variance reduction techniques to stabilize the training.

3 OUR MODEL: GAN-WORD2VEC

We begin this section by formally defining the basket completion task. We denote \mathbb{Z} as all of the potential items, products, or words. \mathbb{Z}^d is the space of all baskets of size d, and $U = \bigcup_{d=1}^{\infty} \mathbb{Z}^d$ is the space of all possible baskets of any size.

The objective of GANs is to generate candidate, or synthetic, samples from a target data distribution p^* , from which only true samples – in our case baskets of products – are available. Therefore, the collection of true baskets *S* is a subset of *U*. We are given each basket $\{X\} \in S$, and an element $z \in Z$ randomly selected from $\{X\}$. Knowing $\{X \setminus z\}$, which denotes basket *X* with item *z* removed, we want to be able to predict the missing item *z*. We denote $\mathbb{P}(\mathbb{Z})$ as the space of probability distributions defined on \mathbb{Z} .

As in [16], we are working with embeddings. For a given target item z, we denote C_z as its context, where $C_z = \{X \setminus z\}$. The embeddings of z and C_z are w_z and w_{C_z} , respectively.

3.1 Notation

Both generators and discriminators as a whole have the form of a parametric family of functions from $\mathbb{Z}^{d'}$ to $\mathbb{P}(\mathbb{Z})$, where d' is the length of the prefix basket. We denote $\mathscr{G} = \{G_{\theta}\}_{\theta \in \Theta}$ as the family of generator functions, with parameters $\Theta \subset \mathbb{R}^{p}$, and $\{D_{\alpha}\}_{\alpha \in \Lambda}$ as the family of discriminator functions, with parameters $\Lambda \subset \mathbb{R}^{q}$. Each function G_{θ} and D_{α} is intended to be applied to a d'-long random input basket. Both the generator and the discriminator output probabilities that are conditioned on an input basket. In our setting, G and D may therefore be from the same class of models, and may be parametrized by the same class of functions. Given the context C_z , we denote $P_G(.|C_z)$ and $P_D(.|C_z)$ as the conditional probabilities output by G and D, respectively. The samples drawn from $P_G(.|C_z)$ are denoted as O.

Adversarial Training of Word2Vec for Basket Completion

3.2 Adversarial Negative Sampling Loss

In the usual GAN setting, D is trained with a binary cross-entropy loss function, with positives coming from p^* and negatives generated by G. In our setting, we modify the discriminator's loss using an extension of the standard approach to *Negative Sampling*, which has proven to be very efficient for language modeling. We define *Adversarial Negative Sampling Loss* by the following objective:

$$\log \sigma(w_z \ w_{C_z}^T) + \sum_{i=1}^k \mathbb{E}_{O_i \sim P_G(. \mid C_z)} \left[\log \sigma(-w_{O_i} \ w_{C_z}^T)\right] \quad (1)$$

where *k* is the number of negatives O_i sampled from $P_G(.|C_z)$.

As in the standard GAN setting, D's task is to learn to discriminate between true samples and synthetic samples coming from *G*. Compared to standard *negative sampling*, the main difference is that the negatives are now drawn from a dynamic distribution that is by design more informative than the fixed distribution used in standard negative sampling. Ref. [4] proposes a dynamic sampling strategy based on self-embedded features, but our approach is a fully adversarial sampling method that is not based on heuristics.

3.3 Training the Generator

In discrete settings, training *G* using the standard GAN architecture is not feasible, due to discontinuities in the space of discrete data that prevent updates of the generator. To address this issue, we sample potential outcomes from $P_G(.|C_z)$, and use *D* as a reward function on these outcomes.

In our case, the training of the generator has been inspired by [3]. In this paper, the authors define two main loss functions for training the generator. The first loss is called the *basic MALIGAN* and only uses signals from D. Adapted to our setting, we have the following formulation for the generator's loss:

$$L_G(\theta) = \sum_{i=1}^{m} \frac{r_D(O_i)}{\sum_i r_D(O_i)} \log P_G(O_i|C_z)$$
(2)

where

- O_i ~ P_G(.|C_z). That is, we draw negative samples in the form of "next-item" samples, where only the missing element z for each basket {X} is sampled. This missing element is sampled by conditioning P_G on the context, C_z, for z.
- $r_D(O_i) = \frac{p_D(O_i|C_z)}{1 p_D(O_i|C_z)}$. This term allows us to incorporate reward from the discriminator into updates for the generator. The expression for r_D comes from a property of the optimal *D* for a GAN; a full explanation is provided in [3].
- *m* is the number of negatives sampled from *P_G*(.|*C_z*) used to compute the gradients

Unlike [3], we do not use any *b* parameter in Eq. 2, as we did not observe the need for further variance reduction provided by this term in our applications. As both models output probability distributions, computing $P_G(O_i|C_z)$ and $r_D(O_i)$ is straightforward.

The second loss, *Mixed MLE-MALIGAN*, mixes adversarial loss and the standard maximum likelihood estimate (MLE) loss. In our

Algorithm I GAN-Word2Vec
Require: generator policy G_{θ} ; discriminator D_{α} ; a basket dataset S
Initialize G_{θ} , D_{α} with random weights θ , α .
Pre-train $G_ heta$ and D_lpha using sampled softmax on ${\cal S}$
repeat
for g-steps do
Get random true sub-baskets $\{X \setminus z\}$ and the targets z .
Generate negatives by sampling from $P_G(. \{X \setminus z\})$
Update generator parameters via policy gradient Eq. (3)
end for
for d-steps do
Get random true sub-baskets $\{X \setminus z\}$ and the targets <i>z</i> .
Generate adversarial samples for <i>D</i> from $P_G(. \{X \setminus z\})$
Train discriminator D_{α} by Eq. (1)
end for
until GAN-Word2Vec converges
-

4 CANTIN

case, this loss mixes the adversarial training loss and a standard sampled softmax loss (negative sampling loss):

$$\begin{split} L_{G}(\theta) &= 0.5 \ * \ \sum_{i=1}^{m} \ \frac{r_{D}(O_{i})}{\sum_{i} r_{D}(O_{i})} \ \log \ P_{G}(O_{i}|C_{z}) \ + \\ & 0.5 \left(\log \ \sigma(w_{z} \ w_{C_{z}}^{T}) + \sum_{i=1}^{k} \ \mathbb{E}_{N_{i} \sim U(Z)} \left[\log \ \sigma(-w_{N_{i}} \ w_{C_{z}}^{T}) \right] \right) \end{split}$$
(3)

where $N_i \sim U(Z)$ are negatives uniformly sampled among the potential next items. We empirically find that this mixed loss provides more stable gradients than the loss in Eq. 2, leading to faster convergence during training.

A description of our algorithm can be found in Algorithm 1. We pre-train both G and D using a standard negative sampling loss before training these components adversarially. We empirically show improvements with this procedure in the following section.

4 EXPERIMENTS

All our experiments have been ran on the task basket completion, which is a well-known Recommendation task.

4.1 Datasets

In [6] and [7], the authors present state-of-the-art results on basket completion datasets. We performed our experiments on two of the datasets used in this prior work: the *Amazon Baby Registries* and the *Belgian Retail* datasets.

- This public dataset consists of registries of baby products from 15 different categories (such as 'feeding', 'diapers', 'toys', etc.), where the item catalog and registries for each category are disjoint. Each category therefore provides a small dataset, with a maximum of 15,000 purchased baskets per category. We use a random split of 80% of the data for training and 20% for testing.
- Belgian Retail Supermarket This is a public dataset composed of shopping baskets purchased over three non-consecutive time periods from a Belgian retail supermarket store. There are 88,163 purchased baskets, with a catalog of 16,470 unique

RecSys'18, October 2018, Vancouver, Canada

items. We use a random split of 80% of the data for training and 20% for testing.

4.2 Task definition and associated metrics

In the following evaluation, we consider two metrics:

• Mean Percentile Rank (MPR) - For a basket {X} and one item *z* randomly removed from this basket, we rank all potential items *i* from set of candidates \mathbb{Z} according to their probabilities of completing {X\z}, which are $P_G(i|{X\backslashz})$ and $P_D(i|{X\backslashz})$. The Percentile Rank (PR) of the missing item *z* is defined by:

$$\mathrm{PR}_{j} = \frac{\sum_{j \neq \mathbb{Z}} \mathbb{I}(p_{j} \ge p_{j})}{|\mathbb{Z}|} \times 100\%$$

where $\mathbb I$ is the indicator function and $|\mathbb Z|$ is the number of items in the candidate set. The Mean Percentile Rank (MPR) is the average PR of all the instances in the test-set $\mathcal T$.

$$MPR = \frac{\sum_{t \in \mathcal{T}} PR_t}{|\mathcal{T}|}$$

MPR = 100 always places the held-out item for the test instance at the head of the ranked list of predictions, while MPR = 50 is equivalent to random selection.

• Precision@k - We define this metric as

precision@k =
$$\frac{\sum_{t \in \mathcal{T}} \mathbb{I}[\operatorname{rank}_t \le k]}{|\mathcal{T}|}$$

where $rank_t$ is the predicted rank of the held-out item for test instance *t*. In other words, precision@k is the fraction of instances in the test set for which the predicted rank of the held-out item falls within the top *k* predictions.

4.3 Experimental results

We compare our *GAN-Word2Vec* model with Word2Vec models training using classical loss funcitions, including *Noise Contrastive Estimation Loss* (NCE) [11, 17] and *Negative Sampling Loss* (NEG) [16]. We observe that we have better results with the *Mixed Loss*.

We find that pre-training both *G* and *D* with a *Negative Sampling Loss* leads to better predictive quality for *GAN-Word2Vec*.

After pre-training, we train G and D using Eq. 3 and Eq. 1, respectively. We observe that the discriminator initially benefits from adversarial sampling, and its performance on both MPR and precision@1 increases. However, after convergence, the generator ultimately provides better performance than the discriminator on both metrics. We conjecture that this may be explained by the fact that basket completion is a generative task.

From Table 1, we see that our GAN-Word2Vec model consistently provides statistically-significant improvements over the Word2Vec ^[5] baseline models on both the Precision@1 and MPR metrics. As confirmed by the experiments, we expect our method to be more effective on larger datasets. ^[6]

We also see that Word2Vec trained using Negative Sampling (W2V-NEG) is generally a stronger baseline than Word2Vec trained via NCE.

Ugo Tanielian, Mike Gartrell, and Flavian Vasile

Method	Precision@1	MPR
Amazon dataset		
W2V-NCE	14.80 ± 0.07	80.15 ± 0.05
W2V-NEG	15.40 ± 0.05	80.20 ± 0.07
W2V-GANs	16.30 ±0.08	80.50 ±0.1
		<u>-</u>
Belgian retail dataset		
W2V-NCE	29.50 ± 0.05	87.54 ± 0.04
W2V-NEG	34.35 ± 0.07	88.55 ± 0.05
W2V-GANs	35.82 ± 0.09	89 45 +0 1

Table 1: One item basket completion task on the Belgian retail dataset.

5 CONCLUSIONS

In this paper, we have proposed a new adversarial negative sampling algorithm suitable for models such as Word2Vec. Based on recent progress made on GANs in discrete data settings, our solution eliminates much of the complexity of implementing a generative adversarial structure for such models. In particular, our adversarial training approach can be easily applied to models that use standard sampled softmax training, where the generator and discriminator can be of the same family of models.

Regarding future work, we plan to investigate the effectiveness of this training procedure on other models. It is possible that models with more capacity than *Word2Vec* could benefit even more from using softmax with the adversarial negative sampling loss structure that we have proposed. Therefore, we plan to test this procedure on models such as TextCNN, RNNs, and determinantal point processes (DPPs) [6, 7], which are known to be effective in modeling discrete set structures.

GANs have proven to be quite effective in conjunction with deep neural networks when applied to image generation. In this work, we have showed that adversarial training can also be applied to simpler models, in discrete settings, and bring statistically significant improvements in predictive quality.

REFERENCES

- M. Arjovsky and L. Bottou. 2017. Towards principled methods for training generative adversarial networks. In *International Conference on Learning Represen*tations.
- [2] M. Arjovsky, S. Chintala, and L. Bottou. 2017. Wasserstein generative adversarial networks. In *Proceedings of the 34th International Conference on Machine Learning*, D. Precup and Y. Whye Teh (Eds.). Vol. 70. Proceedings of Machine Learning Research, 214–223.
- [3] Tong Che, Yanran Li, Ruixiang Zhang, R. Devon Hjelm, Wenjie Li, Yangqiu Song, and Yoshua Bengio. 2017. Maximum-Likelihood Augmented Discrete Generative Adversarial Networks. *CoRR* abs/1702.07983 (2017). arXiv:1702.07983 http://arxiv.org/abs/1702.07983
- [4] Long Chen, Fajie Yuan, Joemon M Jose, and Weinan Zhang. 2018. Improving Negative Sampling for Word Representation using Self-embedded Features. In Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining. ACM, 99–107.
- [5] G.K. Dziugaite, D.M. Roy, and Z. Ghahramani. 2015. Training generative neural networks via maximum mean discrepancy optimization. In *Proceedings of* the Thirty-First Conference on Uncertainty in Artificial Intelligence. AUAI Press, Arlington, 258–267.
- [6] Mike Gartrell, Ulrich Paquet, and Noam Koenigstein. 2016. Bayesian low-rank determinantal point processes. In Proceedings of the 10th ACM Conference on Recommender Systems. ACM, 349–356.
- [7] Mike Gartrell, Ulrich Paquet, and Noam Koenigstein. 2017. Low-Rank Factorization of Determinantal Point Processes.. In AAAI. 1912–1918.

Adversarial Training of Word2Vec for Basket Completion

- [8] I.J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and J. Bengio. 2014. Generative adversarial nets. In Advances in Neural Information Processing Systems 27, Z. Ghahramani, M. Welling, C. Cortes, N.D. Lawrence, and K.Q. Weinberger (Eds.). Curran Associates, Inc., Red Hook, 2672–2680.
- [9] Alex Graves, Santiago Fernández, and Jürgen Schmidhuber. 2005. Bidirectional LSTM networks for improved phoneme classification and recognition. In International Conference on Artificial Neural Networks. Springer, 799–804.
- [10] Mihajlo Grbovic, Vladan Radosavljevic, Nemanja Djuric, Narayan Bhamidipati, Jaikit Savla, Varun Bhagwan, and Doug Sharp. 2015. E-commerce in your inbox: Product recommendations at scale. In Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. ACM, 1809–1818.
- [11] M. Gutmann and A. Hyvrinen. 2010. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. JMLR WCP, Vol. 9. Journal of Machine Learning Research - Proceedings Track, 297–304.
- [12] Sepp Hochreiter and Jrgen Schmidhuber. 1997. Long Short-term Memory. 9 (12 1997), 1735–80.
- [13] Yoon Kim. 2014. Convolutional Neural Networks for Sentence Classification. CoRR abs/1408.5882 (2014). arXiv:1408.5882 http://arXiv.org/abs/1408.5882
- [14] S. Liu, O. Bousquet, and K. Chaudhuri. 2017. Approximation and convergence properties of generative adversarial learning. In Advances in Neural Information Processing Systems 30, I. Guyon, U.V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (Eds.). Curran Associates, Inc., Red Hook, 5551–5559.
- [15] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Efficient estimation of word representations in vector space. arXiv preprint arXiv:1301.3781 (2013).
- [16] Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. In Advances in neural information processing systems. 3111–3119.
- [17] Andriy Mnih and Yee Whye Teh. 2012. A fast and simple algorithm for training neural probabilistic language models. arXiv preprint arXiv:1206.6426 (2012).
- [18] S. Nowozin, B. Cseke, and R. Tomioka. 2016. f-GAN: Training generative neural samplers using variational divergence minimization. In Advances in Neural Information Processing Systems 29, D.D. Lee, M. Sugiyama, U.V. Luxburg, I. Guyon, and R. Garnett (Eds.). Curran Associates, Inc., Red Hook, 271–279.
- [19] T. Salimans, I. Goodfellow, W. Zaremba, V. Cheung, A. Radford, and X. Chen. 2016. Improved techniques for training GANs. In Advances in Neural Information Processing Systems 29, D.D. Lee, M. Sugiyama, U.V. Luxburg, I. Guyon, and R. Garnett (Eds.). Curran Associates, Inc., Red Hook, 2234–2242.
- [20] Mike Schuster and Kuldip K Paliwal. 1997. Bidirectional recurrent neural networks. *IEEE Transactions on Signal Processing* 45, 11 (1997), 2673–2681.
- [21] Noam Shazeer, Ryan Doherty, Colin Evans, and Chris Waterson. 2016. Swivel: Improving Embeddings by Noticing What's Missing. CoRR abs/1602.02215 (2016). arXiv:1602.02215 http://arxiv.org/abs/1602.02215
- [22] Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. 2000. Policy gradient methods for reinforcement learning with function approximation. In Advances in neural information processing systems. 1057–1063.
- [23] Lantao Yu, Weinan Zhang, Jun Wang, and Yong Yu. 2016. SeqGAN: Sequence Generative Adversarial Nets with Policy Gradient. *CoRR* abs/1609.05473 (2016). arXiv:1609.05473 http://arxiv.org/abs/1609.05473
- [24] Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabás Póczos, Ruslan Salakhutdinov, and Alexander J. Smola. 2017. Deep Sets. CoRR abs/1703.06114 (2017). arXiv:1703.06114 http://arxiv.org/abs/1703.06114
- [25] P. Zhang, Q. Liu, D. Zhou, T. Xu, and X. He. 2018. On the discriminativegeneralization tradeoff in GANs. In *International Conference on Learning Rep*resentations.