

Quantum generalizations of the polynomial hierarchy with applications to QMA(2)

Sevag Gharibian* Miklos Santha† Jamie Sikora‡ Aarthi Sundaram§
Justin Yirka¶

Abstract

The polynomial-time hierarchy (PH) has proven to be a powerful tool for providing separations in computational complexity theory (modulo standard conjectures such as PH does not collapse). Here, we study whether two quantum generalizations of PH can similarly prove separations in the quantum setting. The first generalization, QCPH, uses classical proofs, and the second, QPH, uses quantum proofs. For the former, we show quantum variants of the Karp-Lipton theorem and Toda’s theorem. For the latter, we place its third level, $Q\Sigma_3$, into NEXP using the Ellipsoid Method for efficiently solving semidefinite programs. These results yield two implications for QMA(2), the variant of Quantum Merlin-Arthur (QMA) with two unentangled proofs, a complexity class whose characterization has proven difficult. First, if $QCPH = QPH$ (i.e., alternating quantifiers are sufficiently powerful so as to make classical and quantum proofs “equivalent”), then QMA(2) is in the Counting Hierarchy (specifically, in P^{PPP}). Second, unless $QMA(2) = Q\Sigma_3$ (i.e., alternating quantifiers do not help in the presence of “unentanglement”), QMA(2) is strictly contained in NEXP.

1 Introduction

The polynomial-time hierarchy (PH) [MS72] is a staple of computational complexity theory, and generalizes P, NP and co-NP with the use of alternating existential (\exists) and universal (\forall) operators. Roughly, a language $L \subseteq \{0, 1\}^*$ is in Σ_i , the i th level of PH, if there exists a polynomial-time deterministic Turing machine M that acts as a verifier and accepts i proofs y_1, \dots, y_i , each polynomially bounded in the length of the input x , such that:

$$x \in L \Rightarrow \exists y_1 \forall y_2 \exists y_3 \cdots Q_i y_i \text{ such that } M \text{ accepts } (x, y_1, \dots, y_i), \quad (1)$$

$$x \notin L \Rightarrow \forall y_1 \exists y_2 \forall y_3 \cdots \overline{Q}_i y_i \text{ such that } M \text{ rejects } (x, y_1, \dots, y_i), \quad (2)$$

where $Q_i = \exists$ if i is odd and $Q_i = \forall$ if i is even, and \overline{Q} denotes the complement of Q . Then, PH is defined as the union over all Σ_i for all $i \in \mathbb{N}$. The study of PH has proven remarkably fruitful in the classical setting, from celebrated results such as Toda’s Theorem [Tod91], which shows that

*University of Paderborn, Paderborn, North Rhine-Westphalia, Germany, and Virginia Commonwealth University, Richmond, VA, USA.

†CNRS, IRIF, Université Paris Diderot, Paris, France and Centre for Quantum Technologies, National University of Singapore, Singapore.

‡Perimeter Institute for Theoretical Physics, Waterloo, Ontario, Canada.

§Joint Center for Quantum Information and Computer Science, University of Maryland, College Park, Maryland, USA.

¶Virginia Commonwealth University, Richmond, Virginia, USA.

PH is contained in $P^{\#P}$, to the Karp-Lipton Theorem [KL80], which says that unless PH collapses to its second level, NP does not have polynomial size non-uniform circuits.

As PH has played a role in separating complexity classes (assuming standard conjectures like “PH does not collapse”), it is natural to ask whether quantum generalizations of PH can be used to separate *quantum* complexity classes. Here, there is some flexibility in defining “quantum PH”, as there is more than one well-defined notion of “quantum NP”: The first, Quantum-Classical Merlin Arthur (QCMA) [AN02], is a quantum analogue of Merlin-Arthur (MA) with a classical proof but quantum verifier. The second, Quantum Merlin Arthur (QMA) [KSV02], is QCMA except with a quantum proof. Generalizing each of these definitions leads to (at least) two possible definitions for “quantum PH”, the first using classical proofs (denoted QCPH), and the second using quantum proofs (denoted QPH) (formal definitions in Section 2).

With these definitions in hand, our aim is to separate quantum classes whose complexity characterization has generally been difficult to pin down. A prime example is QMA(2), the variant of QMA with two “unentangled” quantum provers. While the classical analogue of QMA(2) (i.e. an MA proof system with two provers) trivially equals MA, in the quantum regime multiple unentangled provers are conjectured to yield a more powerful proof system (e.g. there exist problems in QMA(2) not known to be in QMA) [LCV07, BT09, Bei10, ABD⁺09]. For this reason, QMA(2) has received much attention, despite which the strongest bounds known on QMA(2) remain the trivial ones:

$$\text{QMA} \subseteq \text{QMA}(2) \subseteq \text{NEXP}.$$

(Note: $\text{QMA} \subseteq \text{PP}$ [KW00, Vya03, MW05, GY18].) In this work, we show that, indeed, results about the structure of QCPH or QPH yield implications about the power of QMA(2).

1.1 Results, techniques, and discussion

We begin by informally defining the two quantum generalizations of PH to be studied (formal definitions in Section 2).

How to define a “quantum PH”? The first definition, QCPH, has its i th level $\text{QC}\Sigma_i$ defined analogously to Σ_i , except we replace the Turing machine M with a polynomial-size uniformly generated quantum circuit V such that:

$$\begin{aligned} x \in A_{\text{yes}} &\Rightarrow \exists y_1 \forall y_2 \exists y_3 \cdots Q_i y_i \text{ such that } V \text{ accepts } (x, y_1, \dots, y_i) \text{ with probability } \geq 2/3, \\ x \in A_{\text{no}} &\Rightarrow \forall y_1 \exists y_2 \forall y_3 \cdots \overline{Q}_i y_i \text{ such that } V \text{ accepts } (x, y_1, \dots, y_i) \text{ with probability } \leq 1/3, \end{aligned}$$

where the use of a language L has been replaced with a *promise problem*¹ $A = (A_{\text{yes}}, A_{\text{no}})$ (since $\text{QC}\Sigma_i$ uses a bounded error verifier). The values $(2/3, 1/3)$ are *completeness* and *soundness* parameters for A . QCPH is a generalization of QCMA in that $\text{QC}\Sigma_1 = \text{QCMA}$.

We next define QPH using *quantum* proofs. Here, however, there are various possible definitions one might consider. Can the quantum proofs be entangled between alternating quantifiers? If not, we are enforcing “unentanglement” as in QMA(2). Allowing entanglement, on the other hand, might yield classes similar to QIP; however, note that $\text{QIP} = \text{QIP}(3)$ (i.e. QIP collapses to a 3-message proof system) [KW00, MW05], and so it is not clear that allowing entanglement leads to an interesting hierarchy. Assuming proofs are unentangled, should the proofs be pure or mixed

¹Recall that unlike a decision problem, for a promise problem $A = (A_{\text{yes}}, A_{\text{no}})$, it is not necessarily true that for all inputs $x \in \Sigma^*$, either $x \in A_{\text{yes}}$ or $x \in A_{\text{no}}$. In the case of proof systems such as QCPH, when $x \notin A_{\text{yes}} \cup A_{\text{no}}$, V can output an arbitrary answer. Additionally, $A_{\text{yes}} \cap A_{\text{no}} = \emptyset$.

quantum states? (For QMA and QMA(2), standard convexity arguments show both classes of proofs are equivalent, but such arguments fail when *alternating* quantifiers are allowed.)

Here, we define QPH to have its i th level, $Q\Sigma_i$, defined similarly to $QC\Sigma_i$, except each classical proof y_j is replaced with a mixed quantum state ρ_j on polynomially many qubits (for clarity, each ρ_j acts on a disjoint set of qubits). We say a promise problem $A = (A_{\text{yes}}, A_{\text{no}})$ is in $Q\Sigma_i$ if it satisfies the following conditions:

$$\begin{aligned} x \in A_{\text{yes}} &\Rightarrow \exists \rho_1 \forall \rho_2 \exists \rho_3 \cdots Q_i \rho_i \text{ such that } V \text{ accepts } (x, \rho_1, \dots, \rho_i) \text{ with probability } \geq 2/3, \\ x \in A_{\text{no}} &\Rightarrow \forall \rho_1 \exists \rho_2 \forall \rho_3 \cdots \overline{Q}_i \rho_i \text{ such that } V \text{ accepts } (x, \rho_1, \dots, \rho_i) \text{ with probability } \leq 1/3. \end{aligned}$$

Note that $QMA = Q\Sigma_1$ and $QMA(2) \subseteq Q\Sigma_3$ (simply ignore the second proof).

Our results are now stated as follows under three headings.

1. An analogue of Toda’s theorem for QCPH. As previously mentioned, PH is one way to generalize NP using alternations. Another approach is to count the number of solutions for an NP-complete problem such as SAT, as captured by #P. Surprisingly, these two notions are related, as shown by the following celebrated theorem of Toda.

Theorem 1.1 (Toda’s theorem [Tod91]). $PH \subseteq P^{\#P}$.

In the quantum setting, for QCPH, it can be shown using standard arguments involving enumeration over classical proofs that $QCPH \subseteq PSPACE$. However, here we show a stronger result.

Theorem 1.2 (A quantum-classical analogue of Toda’s theorem). $QCPH \subseteq P^{PPPP}$.

Thus, we almost recover the original bound of Toda’s theorem², except we require an oracle for the *second* level of the Counting Hierarchy (CH). CH can be defined with its first level as $C_1 = PP$ and its k th level for $k \geq 2$ as $C_k = PP^{C_{k-1}}$.

Why did we move up to the next level of CH? There are two difficulties in dealing with QCPH (see Section 3 for a detailed discussion). The first can be sketched as follows. Classically, many results involving PH, from basic ones implying the collapse of PH to more advanced statements such as Toda’s theorem, use the following recursive idea (demonstrated with Σ_2 for simplicity): By fixing the existentially quantified proof of Σ_2 the remnant reduces to a co-NP problem, i.e. we can recurse to a lower level of PH. In the quantum setting, however, this does not hold — fixing the existentially quantified proof for $QC\Sigma_2$ does *not* necessarily yield a co-QCMA problem. (This is due to the same phenomenon that has been an obstacle to resolving whether $\exists \cdot BPP$ equals MA (see Section 1.2 and Remark 3.7).) Thus, we cannot directly generalize recursive arguments from the classical setting to the quantum setting. The second difficulty is trickier to explain briefly (see Section 3.2 for details). Roughly, Toda’s proof that $PH \subseteq P^{\#P}$ crucially relies on the Valiant-Vazirani (VV) theorem [VV86], which has one-sided error (i.e. VV may map YES instances of SAT to NO instances of UNIQUE-SAT, but NO instances of SAT are always mapped to NO instances of UNIQUE-SAT). The VV theorem for QCMA [ABOBS08] also has this property, but in addition it can output instances which are “invalid”. Roughly, an “invalid” instance of a promise problem Π is an instance violating the promise of Π . The combination of invalid instances and alternating quantifiers makes it unclear how to extend the parity arguments used in Toda’s proof to the QCPH setting.

²PP captures all problems for which a majority of all possible answers is correct and it is known that $P^{PP} = P^{\#P}$.

To circumvent these difficulties, we exploit a high-level idea from [GY18], where an oracle for SPECTRAL GAP³ was used to detect “invalid” QMA instances⁴. In our setting, the “correct” choice of oracle turns out to be a Precise-BQP oracle, where Precise-BQP is roughly BQP with an inverse exponentially small promise gap. Using this, we are able to essentially “remove” the promise gap of QCPH altogether, thus recovering a “decision problem” which does not pose the difficulties above. Specifically, this mapping is achieved by Lemma 3.8 (Cleaning Lemma), which shows that $\forall i \in \mathbb{N}$, we have $\text{QC}\Sigma_i \subseteq \exists \cdot \forall \cdot \dots \cdot Q_i \cdot \text{P}^{\text{PP}}$. The latter expression applies the existential (\exists) and universal (\forall) operators to a complexity class \mathcal{C} . Informally, $\exists \cdot \mathcal{C}$ is the class of languages such that an input x is in the language if and only if there is a polynomial-sized witness y such that $\langle x, y \rangle$ is in a language in \mathcal{C} . Correspondingly, the $\forall \cdot \mathcal{C}$ class is defined when for every witness y , $\langle x, y \rangle$ is in some language in \mathcal{C} . (See Definition 3.6 for formal definitions of \exists and \forall .)

Notice that although we use a Precise-BQP oracle above, the Cleaning Lemma shows containment using a PP oracle. This is because, as shown in Lemma 3.3 and Corollary 3.4, $\text{Precise-BQP} \subseteq \text{PP}$. One may ask whether our proof technique also works with an oracle *weaker* than PP. We show in Theorem 3.15 that this is unlikely, since the problem of detecting proofs in promise gaps of quantum verifiers is PP-complete.

Finally, an immediate corollary of Theorem 1.2 and the fact that $\text{QMA}(2) \subseteq \text{QPH}$ is:

Corollary 1.3. *If $\text{QCPH} = \text{QPH}$, then $\text{QMA}(2) \subseteq \text{P}^{\text{PPPP}}$.*

In other words, if alternating quantifiers are so powerful so as to make classical and quantum proofs equivalent in power, then $\text{QMA}(2)$ is contained in CH (and thus in PSPACE). For comparison, $\text{QMA} \subseteq \text{P}^{\text{QMA}[\log]} \subseteq \text{PP}$ [KW00, Vya03, MW05, GY18].

2. QPH versus NEXP. We next turn to the study of *quantum* proofs, i.e. QPH. As mentioned above, the best known upper bound on $\text{QMA}(2)$ is NEXP — a non-deterministic verifier can simply guess an exponential-size description of the proof. When alternating quantifiers are present, however, this strategy seemingly no longer works. In other words, it is not even clear that $\text{QPH} \subseteq \text{NEXP}$! This is in stark contrast to the explicit $\text{P}^{\#\text{P}}$ upper bound for PH [Tod91]. In this part, our goal is to use semidefinite programming to give bounds on some levels of QPH. As we will see, this will yield the existence of a complexity class lying “between” $\text{QMA}(2)$ and NEXP.

Theorem 1.4 (Informal statement). *It holds that $\text{Q}\Sigma_2 \subseteq \text{EXP}$ and $\text{Q}\Pi_2 \subseteq \text{EXP}$, even when the completeness-soundness gap is inverse doubly-exponentially small.*

The proof idea is to map alternating quantifiers to an optimization problem with alternating minimizations and maximizations. Namely, to decide if $x \in A_{\text{yes}}$ or $x \in A_{\text{no}}$ for a $\text{Q}\Sigma_i$ promise problem $A = (A_{\text{yes}}, A_{\text{no}})$, where i is even, we can solve for α defined as the optimal value of the optimization problem:

$$\alpha := \max_{\rho_1} \min_{\rho_2} \max_{\rho_3} \dots \min_{\rho_i} \langle C, \rho_1 \otimes \rho_2 \otimes \dots \otimes \rho_i \rangle \quad (3)$$

where C is the POVM operator⁵ corresponding to the ACCEPT state of the verifier. This is a non-convex problem, and as such is (likely) hard to solve in general. Our approach is to cast the case of $i = 2$ as a semidefinite program (SDP), allowing us to efficiently approximate α .

³This problem determines whether the spectral gap of a given local Hamiltonian is “small” or “large”.

⁴This was used, in turn, to show in conjunction with [Amb14] that SPECTRAL GAP is $\text{P}^{\text{Unique-QMA}[\log]}$ -hard.

⁵A POVM is a set of Hermitian positive semidefinite operators that sum to the identity. In this case, the POVM has two operators — corresponding to the ACCEPT and REJECT states of the verifier.

The next natural question is whether a similar SDP reformulation might be used to show whether $Q\Sigma_3$ or $Q\Pi_3$ is also contained in EXP. Unfortunately, this is likely to be difficult — indeed, if there exists a “nice” SDP for the optimal success probability of $Q\Sigma_3$ protocols, then it would imply $QMA(2) \subseteq EXP$, resolving the longstanding open problem of separating $QMA(2)$ from NEXP (recall $QMA(2) \subseteq Q\Sigma_3$). Likewise, a “nice” SDP for $Q\Pi_3$ would place $co-QMA(2) \subseteq EXP$.

To overcome this, we resort to non-determinism by stepping up to NEXP. Namely, one can non-deterministically guess the first proof of a $Q\Sigma_3$ protocol, then approximately solve the SDP for the resulting $Q\Pi_2$ -flavoured computation. Hence, we have:

Theorem 1.5 (Informal statement). $QMA(2) \subseteq Q\Sigma_3 \subseteq NEXP$ and $co-QMA(2) \subseteq Q\Pi_3 \subseteq NEXP$, even when the completeness-soundness gap is inverse doubly-exponentially small. Moreover, the first two containments hold with equality in the inverse exponentially small completeness-soundness gap setting as $QMA(2) = NEXP$ in this case [Per12].

Two remarks are in order. First, in principle, it remains plausible that the *fourth* level of QPH already exceeds NEXP in power. Second, we have the following implication for $QMA(2)$. Classically, assuming PH does not collapse, alternating quantifiers strictly add power to NP proof systems. If alternating quantifiers similarly add power in the quantum setting, then it would separate $QMA(2)$ from NEXP via the following immediate corollary.

Corollary 1.6. $QMA(2) \neq NEXP$ unless $QMA(2) = Q\Sigma_3$, i.e. unless the second universally quantified proof of $Q\Sigma_3$ adds no proving power. Similarly, $co-QMA(2) \neq NEXP$ unless $co-QMA(2) = Q\Pi_3$.

3. A quantum generalization of the Karp-Lipton Theorem. Finally, our last result studies a topic which is unrelated to $QMA(2)$ — the well-known Karp-Lipton theorem [KL80]. The latter shows that if NP-complete problems can be solved by polynomial-size non-uniform Boolean circuits, then $\Sigma_2 = \Pi_2$ (formal definitions in Section 2), which in turn implies that PH collapses to its second level. Here, a poly-size “non-uniform” circuit receives, in addition to the input instance, a poly-size “advice string” y such that (1) y depends only on the input size n , and (2) given n , computing y need not be poly-time. The class of decision problems solved by such circuits is $P_{/poly}$.

Theorem 1.7 (Karp-Lipton [KL80]). *If $NP \subseteq P_{/poly}$ then $\Pi_2 = \Sigma_2$.*

Denote the bounded-error analogue of $P_{/poly}$ with polynomial-size non-uniform quantum circuits as $BQP_{/mpoly}$. In this work, we ask: Does $QCMA \subseteq BQP_{/mpoly}$ imply $QC\Pi_2 = QC\Sigma_2$? Unfortunately, generalizing the proof of the Karp-Lipton theorem is problematic for the same “ $\exists \cdot BPP$ versus MA phenomenon” encountered in extending Toda’s result. Namely, the proof of Karp-Lipton proceeds by fixing the outer, universally quantified, proof of a Π_2 machine, and applying the $NP \subseteq P_{/poly}$ hypothesis to the resulting NP computation. However, for $QC\Pi_2$, it is not clear that fixing the outer, universally quantified, proof yields a QCMA computation; thus, it is not obvious how to use the hypothesis $QCMA \subseteq BQP_{/mpoly}$.

To sidestep this, our approach is to strengthen the hypothesis. Specifically, using the results of [JKNN12] on perfect completeness for QCMA, fixing the outer proof of a $QC\Pi_2$ computation can be seen to yield a Precise-QCMA “decision problem”, where by “decision problem”, we mean no proofs for the Precise-QCMA verifier are accepted within the promise gap. Here, Precise-QCMA is QCMA with inverse exponentially small promise gap. We hence obtain the following.

Theorem 1.8 (A quantum-classical Karp-Lipton theorem). *If $Precise-QCMA \subseteq BQP_{/mpoly}$, then $QC\Pi_2 = QC\Sigma_2$.*

To give this result context, we also show that $\text{Precise-QCMA} \subseteq \text{NP}^{\text{PP}}$ (Lemma 5.6). However, whether $\text{QC}\Pi_2 = \text{QC}\Sigma_2$ collapses QCPH remains open due to the same “ $\exists \cdot \text{BPP}$ versus MA phenomenon”.

1.2 Related work

As far as we are aware, Yamakami [Yam02] was the first to consider a quantum version of PH. His version differs from our setting in that it considers quantum Turing machines (we use quantum circuits) and quantum inputs (we use classical inputs, like QMA). The next work, by Gharibian and Kempe [GK12], introduced and studied $\text{cq-}\Sigma_2$, defined as our $\text{QC}\Sigma_2$ except with a quantum universally quantified proof. [GK12] showed completeness and hardness of approximation results for $\text{cq-}\Sigma_2$ for (roughly) the following problem: What is the smallest number of terms required in a given local Hamiltonian for it to have a frustrated ground space? More recently, Lockhart and González-Guillén [LGG17] considered a hierarchy (denoted QCPH' here) which *a priori* appears identical to our QCPH , but is apparently not so due to the “ $\exists \cdot \text{BPP}$ versus MA phenomenon”, which we now discuss briefly (see also Remark 3.7).

In this work, the “ $\exists \cdot \text{BPP}$ versus MA phenomenon”, refers to the following discrepancy: Unlike with MA, *all* proofs in an $\exists \cdot \text{BPP}$ system must be accepted with probability at least $2/3$ or at most $1/3$ (i.e. no proof is accepted with probability in the gap $(1/3, 2/3)$). The quantum analogue of this phenomenon yields the open question: Is $\exists \cdot \text{BQP}$ (which equals NP^{BQP}) equal to QCMA? For this reason, it is not clear whether QCPH equals QCPH' , where QCPH' is defined recursively as $\text{QC}\Sigma'_1 = \exists \cdot \text{BQP}$, $\text{QC}\Pi'_1 = \forall \cdot \text{BQP}$, and

$$\forall i \geq 1, \text{QC}\Sigma'_i = \exists \cdot \text{QC}\Pi'_{i-1}; \quad \text{QC}\Pi'_i = \forall \cdot \text{QC}\Sigma'_{i-1}.$$

Thus, in our work $\text{QC}\Sigma_1 = \text{QCMA}$, but in [LGG17] $\text{QC}\Sigma'_1 = \exists \cdot \text{BQP}$. The advantage of the latter definition is that one avoids the recursion problems discussed earlier — e.g., fixing the first existential proof in $\text{QC}\Sigma'_2$ *does* reduce the problem to a co-QCMA computation, unlike the case with $\text{QC}\Sigma_2$. Hence, recursive arguments from the context of PH can be extended to show that, for instance, QCPH' collapses to $\text{QC}\Sigma'_2$ when $\text{QC}\Sigma'_2 = \text{QC}\Pi'_2$. On the other hand, the advantage of our definition of QCPH is that it generalizes the natural quantum complexity class QCMA.

Let us also remark on Toda’s theorem in the context of QCPH' (for clarity, Toda’s theorem is not studied in [LGG17]). The recursive definition of QCPH' allows one to obtain Toda’s P^{PP} upper bound for QCPH' with a simple argument:

$$\forall i, \text{QC}\Sigma'_i = \text{NP}^{\text{NP}^{\dots^{\text{BQP}}}} = \Sigma_i^{\text{BQP}} \implies \forall i, \text{QC}\Sigma'_i \subseteq (\text{P}^{\text{PP}})^{\text{BQP}} = \text{P}^{\text{PP}},$$

where the first equality

holds due to the recursive definition of $\text{QC}\Sigma'_i$ (but is not known to hold for our $\text{QC}\Sigma_i$), the implication arises by relativizing Toda’s theorem, and the last equality holds as BQP is low for PP [FR99]. In contrast, our Theorem 1.2 yields $\text{QCPH} \subseteq \text{P}^{\text{PPPP}}$, raising the question: is $\text{QCPH}' = \text{QCPH}$? A positive answer may help shed light on whether $\exists \cdot \text{BQP}$ equals QCMA; we leave this for future work.

Finally, a quantum version of the Karp-Lipton theorem was covered by Aaronson and Drucker in [AD14] and further improved by Aaronson, Cojocaru, Gheorghiu, and Kashefi [ACGK17], where the consequences of NP-complete problems being solved by small quantum circuits with polynomial sized quantum advice were considered. Their results differ from ours in that different hierarchies are studied, and in their use of quantum advice as opposed to our use of classical advice.

1.3 Open questions

As the study of quantum generalizations of alternating quantifiers is in its infancy, many open questions exist. For example, due to the “ $\exists \cdot$ BPP versus MA phenomenon”, we are not able to show “simple” collapse statements such as the following.

Conjecture 1.9. *For any $i \geq 1$, if $\text{QC}\Sigma_i = \text{QC}\Pi_i$, then QCPH collapses to the i^{th} level. Moreover, if $\text{QCMA} = \text{BQP}$, then $\text{QCPH} = \text{BQP}$.*

Next, can a non-trivial bound on QPH be shown? Here, we have shown that $\text{Q}\Sigma_3 \subseteq \text{NEXP}$; can the complexity of higher levels be bounded? Along these lines, our Theorem 1.4 shows $\text{Q}\Sigma_2 \subseteq \text{EXP}$; by applying alternative methods for approximating semidefinite programs arising in quantum complexity theory (see, e.g., [JJUW10]), we also conjecture the following.

Conjecture 1.10. $\text{Q}\Sigma_2 \subseteq \text{PSPACE}$.

Finally, determining where in the complexity zoo $\text{QMA}(2)$ lies remains an important open question; assuming alternating quantifiers *do* add proving power to QPH (the analogous assumption for PH is widely believed), our work shows $\text{QMA}(2)$ is strictly contained in NEXP. Can this statement be strengthened?

Organization: We begin in Section 2 by formally introducing relevant complexity classes. In Section 3 we show a quantum-classical analogue of Toda’s theorem. Section 4 gives upper bounds on levels of QPH, and Section 5 shows a Karp-Lipton-type theorem.

2 Definitions, preliminaries, and basic properties

We begin by recalling the definition of uniformly-generated families of quantum circuits.

Definition 2.1 (Polynomial-time uniform family of quantum circuits). *A family of quantum circuits $\{V_n\}_{n \in \mathbb{N}}$ is said to be uniformly generated in polynomial time if there exists a polynomially bounded function $t : \mathbb{N} \mapsto \mathbb{N}$ and a deterministic Turing machine M acting as follows. For every n -bit input x , M outputs in time $t(n)$ a description of a quantum circuit V_n (consisting of 1- and 2-qubit gates) that takes the all-zeros state as ancilla and outputs a single qubit. We say V_n accepts if measuring its output qubit in the computational basis yields 1.*

Throughout this paper, we study *promise problems*. A promise problem is a pair $A = (A_{\text{yes}}, A_{\text{no}})$ such that $A_{\text{yes}}, A_{\text{no}} \subseteq \{0, 1\}^*$, $A_{\text{yes}} \cup A_{\text{no}} \subseteq \{0, 1\}^*$ and $A_{\text{yes}} \cap A_{\text{no}} = \emptyset$. We now formally define each level of our quantum-classical polynomial hierarchy below.

Definition 2.2 ($\text{QC}\Sigma_i$). *Let $A = (A_{\text{yes}}, A_{\text{no}})$ be a promise problem. We say that A is in $\text{QC}\Sigma_i(c, s)$ for polynomial-time computable functions $c, s : \mathbb{N} \mapsto [0, 1]$ if there exists a polynomially bounded function $p : \mathbb{N} \mapsto \mathbb{N}$ and a polynomial-time uniform family of quantum circuits $\{V_n\}_{n \in \mathbb{N}}$ such that for every n -bit input x , V_n takes in classical proofs $y_1 \in \{0, 1\}^{p(n)}, \dots, y_i \in \{0, 1\}^{p(n)}$ and outputs a single qubit, such that:*

- *Completeness:* $x \in A_{\text{yes}} \Rightarrow \exists y_1 \forall y_2 \dots Q_i y_i$ s.t. $\text{Prob}[V_n \text{ accepts } (y_1, \dots, y_i)] \geq c$.
- *Soundness:* $x \in A_{\text{no}} \Rightarrow \forall y_1 \exists y_2 \dots \overline{Q}_i y_i$ s.t. $\text{Prob}[V_n \text{ accepts } (y_1, \dots, y_i)] \leq s$.

Here, Q_i equals \exists when m is odd and equals \forall otherwise and \bar{Q}_i is the complementary quantifier to Q_i .

$$\text{Define } \text{QC}\Sigma_i := \bigcup_{c-s \in \Omega(1/\text{poly}(n))} \text{QC}\Sigma_i(c, s). \quad (4)$$

Notice that the first level of this hierarchy corresponds to QCMA. The complement of the i^{th} level of the hierarchy, $\text{QC}\Sigma_i$, is the class $\text{QC}\Pi_i$ defined below.

Definition 2.3 ($\text{QC}\Pi_i$). Let $A = (A_{\text{yes}}, A_{\text{no}})$ be a promise problem. We say that $A \in \text{QC}\Pi_i(c, s)$ for polynomial-time computable functions $c, s : \mathbb{N} \mapsto [0, 1]$ if there exists a polynomially bounded function $p : \mathbb{N} \mapsto \mathbb{N}$ and a polynomial-time uniform family of quantum circuits $\{V_n\}_{n \in \mathbb{N}}$ such that for every n -bit input x , V_n takes in classical proofs $y_1 \in \{0, 1\}^{p(n)}, \dots, y_i \in \{0, 1\}^{p(n)}$ and outputs a single qubit, such that:

- *Completeness*: $x \in A_{\text{yes}} \Rightarrow \forall y_1 \exists y_2 \dots Q_i y_i$ s.t. $\text{Prob}[V_n \text{ accepts } (y_1, \dots, y_i)] \geq c$.
- *Soundness*: $x \in A_{\text{no}} \Rightarrow \exists y_1 \forall y_2 \dots \bar{Q}_i y_i$ s.t. $\text{Prob}[V_n \text{ accepts } (y_1, \dots, y_i)] \leq s$.

Here, Q_i equals \forall when m is odd and equals \exists otherwise and \bar{Q}_i is the complementary quantifier to Q_i .

$$\text{Define } \text{QC}\Pi_i := \bigcup_{c-s \in \Omega(1/\text{poly}(n))} \text{QC}\Pi_i(c, s). \quad (5)$$

Now the corresponding quantum-classical polynomial hierarchy is defined as below.

Definition 2.4 (Quantum-classical polynomial hierarchy).

$$\text{QCPH} = \bigcup_{m \in \mathbb{N}} \text{QC}\Sigma_m = \bigcup_{m \in \mathbb{N}} \text{QC}\Pi_m.$$

A few remarks are in order. First, by encoding a polynomial time predicate into a quantum verification circuit, one can see that (where Σ_i and Π_i refer to the i^{th} level of the corresponding classical polynomial hierarchy)

$$\forall i, \Sigma_i \subseteq \text{QC}\Sigma_i, \quad \Pi_i \subseteq \text{QC}\Pi_i \quad \text{and} \quad \text{PH} \subseteq \text{QCPH}.$$

Second, a natural question is to what extent the completeness and soundness parameters of $\text{QC}\Sigma_i$ and $\text{QC}\Pi_i$ can be improved. Towards achieving one-sided error, we apply known techniques to prove that “every other level” (see Theorem 2.6 for a formal statement) has *perfect completeness* (i.e. we can improve the completeness parameter to $c = 1$), in addition to every level having inverse exponentially small soundness. This is shown using techniques from the proof of the following theorem.

Theorem 2.5 (Jordan, Kobayashi, Nagaj, Nishimura [JKNN12]). *QCMA has perfect completeness i.e.*

$$\text{QCMA} = \text{QCMA}(1, 1 - 1/\text{poly}(n)). \quad (6)$$

The proof of the above result starts by choosing a suitable gate-set for the QCMA verifier, i.e., Hadamard, Toffoli and CNOT gates [Shi03, Aha03]. This ensures that the acceptance probability for any proof y can be expressed as $k/2^{\ell(|x|)}$ for an integer $k \in \{0, \dots, 2^{\ell(|x|)}\}$ and a polynomially bounded integer function $\ell(|x|)$. The verifier then asks the prover to send k (expressed as a polynomial-size bit string) along with the classical proof. When k is above a certain threshold,

the verifier chooses one of two tests with equal probability: (a) run the original verification circuit or (b) trivially accept with probability $> k/2^{\ell(|x|)}$. This allows for the completeness to be reduced to exactly $1/2$ while the soundness is strictly bounded below $1/2$. Then by using the quantum rewinding technique [Wat09c], c can be boosted to exactly 1. The ideas in this proof have been adapted to several similar scenarios (see, e.g., [KIGN15, GKS16]). We state our result below.

Theorem 2.6. *For polynomially bounded functions $r, q : \mathbb{N} \mapsto \mathbb{N}$ and polynomial-time computable functions $c, s : \mathbb{N} \mapsto [0, 1]$ such that for any n -bit input $c(n) - s(n) \geq 1/q(n)$, we have:*

$$\begin{aligned} \text{For } i \text{ even: } & \text{QC}\Sigma_i(c, s) = \text{QC}\Sigma_i(1 - 2^{-r}, 2^{-r}), \\ & \text{QC}\Pi_i(c, s) = \text{QC}\Pi_i(1, 2^{-r}), \\ \text{for } i \text{ odd: } & \text{QC}\Sigma_i(c, s) = \text{QC}\Sigma_i(1, 2^{-r}), \\ & \text{QC}\Pi_i(c, s) = \text{QC}\Pi_i(1 - 2^{-r}, 2^{-r}). \end{aligned}$$

Proof Sketch. To achieve perfect completeness (i.e. $c = 1$), the idea is to append to the register of the last proof (which must be an existential quantifier for this to work) a classical register containing the acceptance probability of the verification circuit C . Specifically, for level i , for any set of $i - 1$ proofs y_1, \dots, y_{i-1} , the final (existential) proof y_i is augmented with k , such that $\Pr[C(y_1, \dots, y_i) = 1] = k/2^{\ell(|x|)}$ (that this probability is rational is due solely to the use of an appropriate universal gate set, as done for Theorem 2.5, and is independent of how each y_i for $i \in \{1, \dots, i - 1\}$ is quantified). Then the proof of Theorem 2.5 in [JKNN12] proves the result. The error reduction follows from standard arguments. \square

Notice that by explicitly emulating the technique from [JKNN12] we are using it as a *white-box* and not a black box reduction. Hence, the issues discussed in Section 1 the arise from “fixing proofs” does not apply here. We leave as an open problem the question of obtaining perfect completeness for the remaining levels of the hierarchy. This seems like a considerably harder problem, with current proof techniques requiring the last quantifier to be existential.

Now, we move on to defining the fully quantum hierarchy.

Definition 2.7 ($\text{Q}\Sigma_i$). *A promise problem $A = (A_{\text{yes}}, A_{\text{no}})$ is in $\text{Q}\Sigma_i(c, s)$ for polynomial-time computable functions $c, s : \mathbb{N} \mapsto [0, 1]$ if there exists a polynomially bounded function $p : \mathbb{N} \mapsto \mathbb{N}$ and a polynomial-time uniform family of quantum circuits $\{V_n\}_{n \in \mathbb{N}}$ such that for every n -bit input x , V_n takes $p(n)$ -qubit density operators ρ_1, \dots, ρ_i as quantum proofs and outputs a single qubit, then:*

- *Completeness: If $x \in A_{\text{yes}}$, then $\exists \rho_1 \forall \rho_2 \dots Q_i \rho_i$ such that V_n accepts $(\rho_1 \otimes \rho_2 \otimes \dots \otimes \rho_i)$ with probability $\geq c$.*
- *Soundness: If $x \in A_{\text{no}}$, then $\forall \rho_1 \exists \rho_2 \dots \overline{Q}_i \rho_i$ such that V_n accepts $(\rho_1 \otimes \rho_2 \otimes \dots \otimes \rho_i)$ with probability $\leq s$.*

Here, Q_i equals \forall when m is even and equals \exists otherwise, and \overline{Q}_i is the complementary quantifier to Q_i .

$$\text{Define } \text{Q}\Sigma_i = \bigcup_{c-s \in \Omega(1/\text{poly}(n))} \text{Q}\Sigma_i(c, s). \quad (7)$$

A few comments are in order: (1) In contrast to the standard quantum circuit model, here we allow *mixed* states as inputs to V_n ; this can be formally modelled via the mixed state framework of [AKN98]. (2) Clearly, $\text{Q}\Sigma_1 = \text{QMA}$. (3) We recover the definition of $\text{QMA}(k)$ by ignoring the ρ_i proofs, for i even, in the definition of $\text{Q}\Sigma_{2k}$.

Definition 2.8 ($\text{Q}\Pi_i$). A promise problem $A = (A_{\text{yes}}, A_{\text{no}})$ is in $\text{Q}\Pi_i(c, s)$ for polynomial-time computable functions $c, s : \mathbb{N} \mapsto [0, 1]$ if there exists a polynomially bounded function $p : \mathbb{N} \mapsto \mathbb{N}$ and a polynomial-time uniform family of quantum circuits $\{V_n\}_{n \in \mathbb{N}}$ such that for every n -bit input x , V_n takes $p(n)$ -qubit density operators ρ_1, \dots, ρ_i as quantum proofs and outputs a single qubit, then:

- **Completeness:** If $x \in A_{\text{yes}}$, then $\forall \rho_1 \exists \rho_2 \dots \exists Q_i \rho_i$ such that V_n accepts $(\rho_1 \otimes \rho_2 \otimes \dots \otimes \rho_i)$ with probability $\geq c$.
- **Soundness:** If $x \in A_{\text{no}}$, then $\exists \rho_1 \forall \rho_2 \dots \forall \bar{Q}_i \rho_i$ such that V_n accepts $(\rho_1 \otimes \rho_2 \otimes \dots \otimes \rho_i)$ with probability $\leq s$.

Here, Q_i equals \exists when m is even and equals \forall otherwise, and \bar{Q}_i is the complementary quantifier to Q_i .

$$\text{Define } \text{Q}\Pi_i = \bigcup_{c-s \in \Omega(1/\text{poly}(n))} \text{Q}\Pi_i(c, s). \quad (8)$$

The fully quantum polynomial hierarchy can now be defined as follows.

Definition 2.9 (Quantum Polynomial-Hierarchy).

$$\text{QPH} = \bigcup_{m \in \mathbb{N}} \text{Q}\Sigma_i = \bigcup_{m \in \mathbb{N}} \text{Q}\Pi_i.$$

Next, we recall the definition of BQP circuits which take in poly-size classical advice.

Definition 2.10 ($\text{BQP}_{/\text{mpoly}}$). A promise problem $\Pi = (A_{\text{yes}}, A_{\text{no}})$ is in $\text{BQP}_{/\text{mpoly}}$ if there exists a polynomial-sized family of quantum circuits $\{C_n\}_{n \in \mathbb{N}}$ and a collection of binary advice strings $\{a_n\}_{n \in \mathbb{N}}$ with $|a_n| = \text{poly}(n)$, such that for all n and all strings x where $|x| = n$, $\Pr[C_n(|x\rangle, |a_n\rangle) = 1] \geq 2/3$ if $x \in A_{\text{yes}}$ and $\Pr[C_n(|x\rangle, |a_n\rangle) = 1] \leq 1/3$ if $x \in A_{\text{no}}$.

Equivalently, $\text{BQP}_{/\text{mpoly}}$ is the set of promise problems solvable by a *non-uniform* family of poly-sized bounded error quantum circuits.

Definition 2.11 (PP). A language \mathcal{L} is in PP if there exists a probabilistic polynomial time Turing machine M such that $x \in \mathcal{L} \iff \Pr[M(x) = 1] > 1/2$.

3 A quantum-classical analogue of Toda's theorem

In this section, we show an analogue of Toda's theorem to bound the power of QCPH (Theorem 1.2, Section 3.2), and give evidence that the bound of Theorem 1.2 is likely the best possible using our specific proof approach (Section 3.3, Theorem 3.15).

3.1 Precise-BQP

Our proof of a “quantum-classical Toda's theorem” requires us to define the Precise-BQP class, which we do now.

Definition 3.1 ($\text{Precise-BQP}(c, s)$). A promise problem $A = (A_{\text{yes}}, A_{\text{no}})$ is contained in $\text{Precise-BQP}(c, s)$ for polynomial-time computable functions $c, s : \mathbb{N} \mapsto [0, 1]$ if there exists a polynomially bounded function $p : \mathbb{N} \mapsto \mathbb{N}$ such that $\forall \ell \in \mathbb{N}$, $c(\ell) - s(\ell) \geq 2^{-p(\ell)}$, and a polynomial-time uniform family of quantum circuits $\{V_n\}_{n \in \mathbb{N}}$ whose input is the all zeroes state and output is a single qubit. Furthermore, for an n -bit input x :

- *Completeness:* If $x \in A_{\text{yes}}$, then V_n accepts with probability at least $c(n)$.
- *Soundness:* If $x \in A_{\text{no}}$, then V_n accepts with probability at most $s(n)$.

In contrast, BQP is defined such that the completeness and soundness parameters are $2/3$ and $1/3$, respectively (alternatively, the gap is least an inverse polynomial in n). We now give a useful observation and lemma.

Observation 3.2 (Rational acceptance probabilities). By fixing an appropriate universal gate set (e.g. Hadamard and Toffoli [Aha03]) for the description of V_n in Definition 3.1, we assume henceforth, without loss of generality, that the acceptance probability of V_n is a rational number that can be represented using at most $\text{poly}(n)$ bits (this observation was used in the proof that QCMA has perfect completeness i.e., $c = 1$ [JKNN12], stated as Theorem 2.5 here).

Lemma 3.3. For any polynomial p , if $c - s \geq 1/2^{p(n)}$, then

$$\text{Precise-BQP}(c, s) \subseteq \text{PP} \quad (9)$$

when c and s are computable in polynomial time in the size of the input, n .

Proof sketch. Recall that the complexity class QQP is defined as PP except with a uniform quantum circuit family $\{Q_n\}$ in place of a probabilistic Turing machine, i.e. for YES (NO) instances Q_n accepts with probability $> 1/2$ ($\leq 1/2$). Consider any $\text{Precise-BQP}(c, s)$ circuit V_x as in Definition 3.1. Then, by flipping a coin with appropriately chosen bias $\gamma \in \mathbb{Q}$ and choosing to either accept/reject with probability γ and run Q_n with probability $1 - \gamma$, one may map c, s to polynomial-time computable functions c', s' such that

$$c' > 1/2, \quad s' \leq 1/2, \quad \text{and} \quad c' - s' \in \Theta(c - s) \quad (10)$$

(roughly, one loses about a factor of at most approximately $1/2$ in the gap). Thus,

$$\text{Precise-BQP}(c, s) \subseteq \text{QPQ} = \text{PP}, \quad (11)$$

where the last equality is shown in [Wat09a]. □

As an aside, we remark the following.

Corollary 3.4. Let \mathbb{P} denote the set of all polynomials $p : \mathbb{N} \mapsto \mathbb{N}$. Then,

$$\bigcup_{p \in \mathbb{P}} \text{Precise-BQP} \left(\frac{1}{2} + \frac{1}{2^{p(n)}}, \frac{1}{2} \right) = \text{PP}.$$

To prove Corollary 3.4, we need the classical counterpart to Precise-BQP , denoted Precise-BPP . Accordingly, we define Precise-BPP analogous to Definition 3.1 except by replacing the quantum circuit family $\{V_n\}_{n \in \mathbb{N}}$ with a deterministic polynomial-time Turing machine which takes in polynomially many bits of randomness.

Proof. The direction \subseteq is given by Lemma 3.3. For the reverse containment, note that

$$\text{PP} = \bigcup_p \text{PreciseBPP} \left(\frac{1}{2} + \frac{1}{2^{p(n)}}, \frac{1}{2} \right), \quad (12)$$

since PP can be defined as the set of decision problems of the form: Given as input a polynomial-time non-deterministic Turing machine N , do more than half of N 's computational paths accept? The claim now follows, since for all c, s as in Definition 3.1, clearly $\text{PreciseBPP}(c, s) \subseteq \text{Precise-BQP}(c, s)$. □

Note that this proof does not go through as is (assuming $\text{PP} \neq \text{co-NP}$) when we fix (say) completeness $c = 1$ and soundness $s = 1 - 2^{-p(n)}$, for some polynomial p . This is because

$$\bigcup_p \text{PreciseBPP}(1, 1 - \frac{1}{2^{p(n)}}) = \text{co-NP}. \quad (13)$$

Similarly, setting $s = 0$ and $c = 2^{-p(n)}$ yields NP.

Finally, we define the promise problem $\text{QCIRCUIT}(c, s)$, which is trivially $\text{Precise-BQP}(c, s)$ -complete when $c - s$ is an inverse exponential.

Definition 3.5 ($\text{QCIRCUIT}(c, s)$). *Parameters $c, s : \mathbb{N} \mapsto [0, 1]$ are polynomial-time computable functions such that $c > s$.*

- (Input) A classical description of quantum circuit V_n (acting on n qubits, consisting of $\text{poly}(n)$ 1 and 2-qubit gates), taking in the all-zeroes state, and outputting a single qubit.
- (Output) Decide if $\Pr[V_n \text{ accepts}] \geq c$ or $\leq s$, assuming one of the two is the case.

3.2 Bounding the power of QCPH

Classically, PH can be defined in terms of the existential (\exists) and universal (\forall) operators; while it is not clear that one can also define QCPH using these operators, they nevertheless prove useful in bounding the power of QCPH.

Definition 3.6 (Existential and universal quantifiers [Wra76, AW93]). *For \mathcal{C} a class of languages, $\exists \cdot \mathcal{C}$ is defined as the set of languages L such that there is a polynomial p and set $A \in \mathcal{C}$ such that for input x , $x \in L \Leftrightarrow [\exists y (|y| \leq p(|x|)) \text{ and } \langle x, y \rangle \in A]$. The set $\forall \cdot \mathcal{C}$ is defined similarly with \exists replaced with \forall .*

Remark 3.7 (Languages versus promise problems). Directly extending Definition 3.6 to promise problems, gives rise to subtle issues. To demonstrate, recall that $\exists \cdot \text{P} = \text{NP}$. Then, let (L, A) for $L \in \exists \cdot \text{P} = \text{NP}$ and $A \in \text{P}$ be as in Definition 3.6, such that T_A is a polynomial-time Turing machine deciding A . If $x \in L$, there exists a bounded length witness y^* such that T_A accepts $\langle x, y^* \rangle$ and, for all $y' \neq y^*$, T_A by definition either accepts or rejects $\langle x, y' \rangle$. Now consider instead $\exists \cdot \text{BPP}$, which *a priori* seems equal to Merlin-Arthur (MA). Applying the same definition of \exists , we should obtain a BPP machine T_A such that if $x \in L$, then for all $y' \neq y^*$, T_A either accepts or rejects $\langle x, y' \rangle$. But this means, by definition of BPP, that $\langle x, y' \rangle$ is either accepted or rejected with probability at least $2/3$, respectively. (Equivalently, for any fixed y , the machine $T_{A,y}$ must be a BPP machine.) Unfortunately, the definition of MA *makes no such promise* — any $y' \neq y^*$ can be accepted with arbitrary probability when x is a YES instance. Indeed, whether $\exists \cdot \text{BPP} = \text{MA}$ remains an open question [FFKL03].

The following lemma is the main contribution of this section. To set context, adapting the ideas from Toda's proof of $\text{PH} \subseteq \text{P}^{\text{PP}}$ to QCPH is problematic for at least two reasons:

1. Remark 3.7 says that it is not necessarily true that by fixing a proof y to an MA (resp. QCMA) machine, the resulting machine is a BPP (resp. BQP) machine. This prevents the direct extension of recursive arguments, say from [Tod91], to this regime.
2. The ‘‘Quantum Valiant Vazirani (QVV)’’ theorem for QCMA (and MA) [ABOBS08] is not a many-one reduction, but a *Turing* reduction. Specifically, it produces a set of quantum circuits $\{Q_i\}$, at least one of which is guaranteed to be a YES instance of some Unique-QCMA

promise problem Γ if the input Π to the reduction was a YES instance. Unfortunately, some of the Q_i may violate the promise gap of Γ , which implies that when such Q_i are substituted into the Unique-QCMA oracle O , O returns an arbitrary answer. This does not pose a problem in [ABOBS08], as one-sided error suffices for that reduction — so long as O accepts at least one Q_i , one safely concludes Π was a YES instance. In the setting of Toda’s theorem, however, the use of *alternating* quantifiers turns this one-sided error into two-sided error. This renders the output of O useless, as one can no longer determine whether Π was a YES or NO instance.

To sidestep these issues, we adapt a high-level idea from [GY18]: With the help of an appropriate *oracle*, one can sometimes detect “invalid proofs” (i.e. proofs in promise gaps of bounded error verifiers) and “remove” them. Indeed, we show that using a PP oracle, one can eliminate the promise-gap of QCPH altogether, thus overcoming the limitations given above. This is accomplished by the following “Cleaning Lemma”. We also show subsequently that it is highly unlikely for an oracle weaker than PP to suffice for our particular proof technique (see Remark 3.9 and Section 3.3).

Lemma 3.8 (Cleaning Lemma). *For all $i \geq 0$,*

$$\text{QC}\Sigma_i \subseteq \exists \cdot \forall \cdot \dots \cdot Q_i \cdot \text{P}^{\text{Precise-BQP}} \subseteq \exists \cdot \forall \cdot \dots \cdot Q_i \cdot \text{P}^{\text{PP}},$$

where $Q_i = \exists$ ($Q_i = \forall$) if i is odd (even). An analogous statement holds for $\text{QC}\Pi_i$.

Proof. Let C be a $\text{QC}\Sigma_i$ verification circuit for a promise problem Π . Let $C_{y_1^*, \dots, y_i^*}$ denote the quantum circuit obtained from C by fixing values y_1^*, \dots, y_i^* of the i classical proofs. In general, nothing can be said about the acceptance probability $p_{y_1^*, \dots, y_i^*}$ of $C_{y_1^*, \dots, y_i^*}$, except that, by Observation 3.2, $p_{y_1^*, \dots, y_i^*}$ is a rational number representable using $p(n)$ bits for some fixed polynomial p . Let S denote the set of all rational numbers in $[0, 1]$ representable using $p(n)$ bits of precision. (Note $|S| \in \Theta(2^{p(n)})$.) Then, for any $a, b \in S$ with $a > b$, the triple $(C_{y_1^*, \dots, y_i^*}, a, b)$ is a valid $\text{QCIRCUIT}(a, b)$ instance, in that $C_{y_1^*, \dots, y_i^*}$ accepts with probability at least a or at most b for $a - b$ an inverse exponential. It follows that using binary search (by varying the values $a, b \in S$ with $a > b$) in conjunction with $\text{poly}(n)$ calls to a $\text{QCIRCUIT}(a, b)$ oracle, we may exactly and deterministically compute $p_{y_1^*, \dots, y_i^*}$. Moreover, since for all such $a > b$, $\text{QCIRCUIT}(a, b) \in \text{Precise-BQP}(a, b)$, Lemma 3.3 implies a $\text{QCIRCUIT}(a, b)$ oracle call can be simulated with a PP oracle. Denote the binary search subroutine using the PP oracle as B .

Using C and B , we now construct an oracle Turing machine C' as follows. Given any proofs y_1^*, \dots, y_i^* as input, C' uses B to compute $p_{y_1^*, \dots, y_i^*}$ for $C_{y_1^*, \dots, y_i^*}$. If $p_{y_1^*, \dots, y_i^*} \geq c$, C' accepts with certainty, and if $p_{y_1^*, \dots, y_i^*} < c$, C' rejects with certainty. Suppose that the circuits C and C' return 1 when they accept and 0 when they reject. Two observations: (1) Since by construction, for any fixed y_1^*, \dots, y_i^* , B makes only “valid” $\text{QCIRCUIT}(a, b)$ queries (i.e. satisfying the promise of $\text{QCIRCUIT}(a, b)$), C' is a P^{PP} machine (cf. Observation 3.10). (2) Since $C'_{y_1^*, \dots, y_i^*}$ accepts if $C_{y_1^*, \dots, y_i^*}$ accepts with probability at least c , and since $C'_{y_1^*, \dots, y_i^*}$ rejects if $C_{y_1^*, \dots, y_i^*}$ accepts with probability at most s , we conclude that

$$\exists y_1 \forall y_2 \dots Q_i y_i \text{Prob}[C(y_1, \dots, y_i) = 1] \geq c \Leftrightarrow \exists y_1 \forall y_2 \dots Q_i y_i C'(y_1, \dots, y_i) = 1 \quad (14)$$

$$\forall y_1 \exists y_2 \dots \overline{Q}_i y_i \text{Prob}[C(y_1, \dots, y_i) = 1] \leq s \Leftrightarrow \forall y_1 \exists y_2 \dots \overline{Q}_i y_i C'(y_1, \dots, y_i) = 0. \quad (15)$$

(14) and (15) imply that we can simulate Π with a $\exists \cdot \forall \cdot \dots \cdot Q_i \cdot \text{P}^{\text{PP}}$ computation. The proof for $\text{QC}\Pi_i$ is analogous. \square

Remark 3.9 (Possibility of a stronger containment). A key question is whether one may replace the Precise-BQP oracle in the proof of Lemma 3.8 with a weaker BQP oracle. For example, consider the following alternative definition for oracle Turing machine C' : Given proofs y_1^*, \dots, y_i^* , C' plugs $C_{y_1^*, \dots, y_i^*}$ into a BQP oracle and returns the oracle's answers. It is easy to see that in this case, Equations (14) and (15) hold. However, C' is *not* necessarily a P^{BQP} machine, since for some settings of y_1^*, \dots, y_i^* , its input to the BQP oracle may violate the BQP promise, hence making the output of C' ill-defined. To further illustrate this subtle point, consider Observation 3.10. Moreover, in Section 3.3 we show that the task the Precise-BQP oracle is used for in Lemma 3.8 is in fact PP-complete; thus, it is highly unlikely that one can substitute a weaker oracle into the proof above.

Observation 3.10 (When a P machine querying a BQP oracle is not a P^{BQP} machine). The proof of the Cleaning Lemma uses a $P^{\text{Precise-BQP}}$ machine. Let us highlight a subtle reason why using a weaker BQP oracle instead might be difficult (indeed, in Section 3.3 we show that the task we use the Precise-BQP oracle for is PP-complete). Let M denote the trivially BQP-complete problem of determining whether a given polynomial-sized quantum circuit Q accepts with probability at least $2/3$, or accepts with probability at most $1/3$, with the promise that one of the two is the case. Now consider the following polynomial time computation, Π , which is given access to an oracle O_M for M : Π inputs the Hadamard gate H into O_M and outputs O_M 's answer. Does it hold that $\Pi \in P^{\text{BQP}}$? No. Since H violates the promise of BQP, i.e. measuring the output of H yields 0 or 1 with equal probability, the oracle O_M can answer 0 or 1 arbitrarily, and so the output of Π is not well-defined. Having a well-defined output, however, is required for a P^{O_K} computation, where K is any promise class [Gol06].

Using standard techniques, we next show the following.

Lemma 3.11. *For all $i \geq 0$, the following holds true:*

$$\begin{aligned} \exists \cdot \forall \cdot \dots \cdot Q_i \cdot P^{\text{PP}} &\subseteq \Sigma_i^{\text{PP}}, \\ \forall \cdot \exists \cdot \dots \cdot Q_i \cdot P^{\text{PP}} &\subseteq \Pi_i^{\text{PP}}, \end{aligned}$$

where $Q_i = \exists$ (resp. $Q_i = \forall$) when i is odd (resp. even) in the first containment and vice versa for the second containment.

Proof. We show the first statement with containment in Σ_i^{PP} ; the second containment follows using an analogous proof. Let NP_i be defined recursively as $\text{NP}_i := \text{NP}^{\text{NP}_i}$ with $\text{NP}_1 := \text{NP}$. We show that $\exists \cdot \forall \cdot \dots \cdot Q_i \cdot P^{\text{PP}} \subseteq \text{NP}_i^{\text{PP}}$, and then use the fact that $\text{NP}_i = \Sigma_i$ using the oracular definition for Σ_i . Recall that MAJSAT is a PP-complete language, where, given a Boolean formula ϕ , one must decide if more than half of the possible assignments x satisfy $\phi(x) = 1$. For brevity, let A_i denote the (trivially) $\exists \cdot \forall \cdot \dots \cdot Q_i \cdot P^{\text{PP}}$ -complete language (under polynomial-time many-one reductions) — given as input a polynomial time oracle Turing machine T with access to a MAJSAT oracle, decide which of the two is the case:

$$\begin{aligned} \exists y_1 \forall y_2 \dots Q_i y_i &\text{ such that } T \text{ accepts } \langle y_1, \dots, y_i \rangle, \\ \forall y_1 \exists y_2 \dots \overline{Q}_i y_i &\text{ such that } T \text{ rejects } \langle y_1, \dots, y_i \rangle. \end{aligned}$$

Let B_i denote the analogous trivially complete problem for $\forall \cdot \exists \cdot \dots \cdot Q_i \cdot P^{\text{PP}}$. We proceed by induction. The base case $i = 0$ holds trivially since $\Sigma_0 = P$ by definition. For the inductive step $i \geq 1$, let L be a language in $\exists \cdot \forall \cdot \dots \cdot Q_i \cdot P^{\text{PP}}$. Then there exists a polynomial-time oracle Turing machine T , with access to a MAJSAT oracle, and such that $x \in L$ if and only if $\exists y_1$ such that

$$\forall y_2 \exists y_3 \dots Q_i y_i \text{ such that } T \text{ accepts } \langle x, y_1, y_2, \dots, y_i \rangle.$$

By non-deterministically guessing y_1 , it follows that $L \in \text{NP}^{B_{i-1}} = \text{NP}^{A_{i-1}}$. This equality holds since for all $i \geq 1$, $\text{NP}^{B_i} = \text{NP}^{A_i}$, as one can run the oracle for A_i instead of B_i and negate its answer. Since A_{i-1} is an oracle for $\exists \cdot \forall \cdot \dots \cdot Q_{i-1} \cdot \text{P}^{\text{PP}}$, the induction hypothesis now implies that

$$\exists \cdot \forall \cdot \dots \cdot Q_i \cdot \text{P}^{\text{PP}} \subseteq \text{NP}^{\text{NP}_{i-1}^{\text{PP}}} = \text{NP}_i^{\text{PP}} = \Sigma_i^{\text{PP}}.$$

□

We can now show the main theorem of this section.

Theorem 1.2. $\text{QCPH} \subseteq \text{P}^{\text{PPPP}}$.

Proof. The claim follows by combining the Cleaning Lemma (Lemma 3.8), Lemma 3.11, and Toda's theorem ($\text{PH} \subseteq \text{P}^{\text{PP}}$), whose proof relativizes (see, e.g., page 4 of [For94]). □

3.3 Detecting non-empty promise gaps is PP-complete

The technique behind the Cleaning Lemma (Lemma 3.8) can essentially be viewed as using a PP oracle to determine whether a given quantum circuit accepts some input with probability within the promise gap (s, c) , where $c - s$ is an inverse polynomial. One can ask whether this rather powerful PP oracle can be replaced with a weaker oracle (Remark 3.9)? We show that unless one deviates from our specific proof approach, the answer is negative. Specifically, we show that the problem of detecting non-empty promise gaps is PP-complete, even if the gap is *constant* in size. Let us begin by formalizing this problem.

Definition 3.12 ($\text{NON-EMPTY GAP}(c, s)$). *Let V_n be an input for $\text{QCIRCUIT}(c, s)$. Then, output YES if $\text{Prob}[V_n \text{ accepts}] \in (s, c)$, and NO otherwise.*

We now show that NON-EMPTY GAP is PP-complete.

Lemma 3.13. *For all c, s with the $c - s$ gap at least an inverse exponential in input size,*

$$\text{NON-EMPTY GAP}(c, s) \in \text{PP}.$$

Proof. Our approach to show containment in PP is to give a poly-time many-one reduction from $\text{NON-EMPTY GAP}(c, s)$ with $c - s$ at least an inverse exponential to $\text{QCIRCUIT}(P, Q)$ with $P - Q$ an inverse exponential. (Note that even if $c - s \in \Omega(1)$, we will still have $P - Q$ an inverse exponential.) Let V_n be an input to $\text{NON-EMPTY GAP}(c, s)$. We construct an instance V_n'' of $\text{QCIRCUIT}(P, Q)$ as follows.

The first step is to adjust the completeness and soundness parameters for NON-EMPTY GAP so that they “straddle” the midpoint $1/2$. Formally, map $c > s$ to $c' > s'$, respectively, so that $c'(n) - 1/2 = 1/2 - s'(n)$. For this, construct the following circuit V_n' , whose completeness and soundness parameters we denote by c' and s' , respectively.

If $c(n) + s(n) > 1$, then with probability

$$\alpha := (c(n) + s(n) - 1)/(c(n) + s(n)), \tag{16}$$

reject, and with probability $1 - \alpha$, run V_n and output its answer.

The case of $c(n) + s(n) < 1$ is analogous, except with

$$\alpha := (1 - c(n) - s(n))/(2 - c(n) - s(n)). \tag{17}$$

Finally, if $c(n) + s(n) = 1$, set $c' = c$ and $s' = s$. (Here, we use Observation 3.2, which allows us to assume $c, s \in \mathbb{Q}$ with $\text{poly}(n)$ bits of precision.)

Next, map V'_n to V''_n as follows: Given a proof $y \in \{0, 1\}^m$, (1) run two copies of V'_n in parallel on y , (2) negate the output of the second copy of V'_n via a Pauli X gate, (3) apply an AND gate to both output qubits, and (4) measure in the standard basis. Let p_y denote the probability that V'_n accepts y . Then, V''_n accepts y with probability $p_y(1 - p_y)$.

Correctness. Intuitively, since the function $f(x) = x(1 - x)$ is maximized over $x \in [0, 1]$ when $x = 1/2$, the acceptance probability of V''_n is maximized when y falls into the promise gap of V'_n , i.e. $p_y \approx 1/2$. Formally, let $c'(n) = 1/2 + \gamma$ and $s'(n) = 1/2 - \gamma$ for $\gamma \in (0, 1/2]$, and express $p_y = 1/2 + \delta$ for bias $\delta \in [-1/2, 1/2]$. Then, V''_n accepts y with probability

$$p_y(1 - p_y) = 1/4 - \delta^2. \quad (18)$$

It follows that if $p_y \geq c'(n)$ or $p_y \leq s'(n)$, then V''_n accepts y with probability $Q \leq 1/4 - \gamma^2$, and if $s'(n) < p_y < c'(n)$, then V''_n accepts y with probability $P > 1/4 - \gamma^2$. By Observation 3.2, we may assume

$$P - Q \in \Omega(1/\exp(n)), \quad (19)$$

thus yielding that a YES instance of $\text{NON-EMPTY GAP}(c, s)$ with at least inverse exponential $c - s$ is mapped to a NO instance of $\text{QCIRCUIT}(P, Q)$ and vice versa with inverse exponential $P - Q$. The claim now follows by Lemma 3.3, which says $\text{QCIRCUIT}(P, Q) \in \text{PP}$. \square

Lemma 3.14. *There exist $c, s \in \Theta(1)$ such that $\text{NON-EMPTY GAP}(c, s)$ is PP-hard.*

Proof. Let $\phi : \{0, 1\}^n \mapsto \{0, 1\}$ be an instance of the PP-complete problem MAJSAT (see proof of Lemma 3.11). We construct an instance V_n of $\text{NON-EMPTY GAP}(c, s)$ with $c - s \in \Theta(1)$ as follows. Let V'_n be a poly-size quantum circuit which prepares the state

$$2^{-n/2} \sum_{x \in \{0, 1\}^n} |x\rangle_A |\phi(x)\rangle_B \in (\mathbb{C}^2)^{\otimes n+1}, \quad (20)$$

then measures register B in the standard basis, and accepts if and only if it obtains result 1. If ϕ is a YES instance, then V'_n accepts with probability in range $[1/2 + 1/2^n, 1]$, and if ϕ is a NO instance, V'_n accepts with probability in range $[0, 1/2]$. Thus, setting (for example) $c = 3/4$, $s = 1/4$, and constructing circuit V_n which with probability $1/2$ rejects, and with probability $1/2$ runs V'_n and outputs its answer, yields the claim. \square

Lemmas 3.13 and 3.14 immediately yield the following.

Theorem 3.15. *There exist $c, s \in \Theta(1)$ such that $\text{NON-EMPTY GAP}(c, s)$ is PP-complete.*

4 Bounding the complexity of $\text{Q}\Sigma_2$ and $\text{Q}\Sigma_3$

In this section, we upper bound the complexity of the second and third levels of our fully quantum hierarchy. For brevity, we sometimes use shorthand $\text{Q}\Sigma_2$ and $\text{Q}\Pi_2$ to refer to $\text{Q}\Sigma_2(c, s)$ and $\text{Q}\Pi_2(c, s)$, respectively, for completeness and soundness parameters c and s , respectively. We begin by restating Theorem 1.4 as follows.

Theorem 4.1. *For any polynomial r , if $c - s \geq 1/2^{2^r(n)}$, then*

$$\text{Q}\Sigma_2(c, s) \subseteq \text{EXP} \quad \text{and} \quad \text{Q}\Pi_2(c, s) \subseteq \text{EXP} \quad (21)$$

when c and s are computable in exponential time in the size of the input, n .

Proof. We show the first containment for $\text{Q}\Sigma_2$. The proof for $\text{Q}\Pi_2$ is analogous. Given a $\text{Q}\Sigma_2$ instance, let its two proofs be denoted ρ_1 and ρ_2 , with the former existentially quantified and the latter universally quantified. Let α be the maximum acceptance probability of a $\text{Q}\Sigma_2(c, s)$ protocol, i.e. the special case of Equation (3) such that

$$\alpha := \max_{\rho_1} \min_{\rho_2} \langle C, \rho_1 \otimes \rho_2 \rangle \quad (22)$$

for accepting POVM operator C . We wish to decide in exponential time whether $\alpha \geq c$ or $\alpha \leq s$. Since the promise gap satisfies $c - s \geq 1/2^{2^{r(n)}}$, it suffices to approximate α within additive error (say) $\frac{1}{4}(c - s)$ in exponential time. Hence, we show how to compute $\gamma \in \mathbb{R}$ such that $|\gamma - \alpha| \leq 1/(4 \cdot 2^{2^{r(n)}})$ in exponential time.

Beginning with Equation (22), note that we can write C as

$$C = \text{Tr}_{\text{anc}} \left[(I \otimes |0 \cdots 0\rangle\langle 0 \cdots 0|_{\text{anc}}) V_n^\dagger (|1\rangle\langle 1|_{\text{out}} \otimes I) V_n (I \otimes |0 \cdots 0\rangle\langle 0 \cdots 0|_{\text{anc}}) \right] \quad (23)$$

for verification circuit V_n . By definition, V_n is generated by a polynomial-time Turing machine, which we assume specifies V_n via a sequence of gates from a universal gate set G (such as $\{\text{CNOT}, \text{H}, \text{T}\}$). Since we wish to proceed via numerical optimization techniques, we begin by computing a numerical approximation C' to C . Specifically, in exponential time, we can approximate each entry⁶ of C using $2^{q(n)}$ bits of precision, for some polynomial q . Therefore, we have

$$|\langle C - C', \sigma \rangle| \leq \|C - C'\|_2 \|\sigma\|_2 \leq \dim(C) \cdot 2^{-2^{q(n)}} = O(2^{2p(n) - 2^{q(n)}}) \quad (24)$$

for any density matrix σ (which satisfies $\|\sigma\|_2 \leq 1$). (Recall $p(n)$ is the size of the each proof, for some polynomial p .) Therefore, for sufficiently large polynomial q , we have that

$$\alpha' := \max_{\rho_1} \min_{\rho_2} \{ \langle C', \rho_1 \otimes \rho_2 \rangle : \text{Tr}(\rho_1) = \text{Tr}(\rho_2) = 1, \rho_1, \rho_2 \succeq 0 \}, \quad (25)$$

satisfies $|\alpha - \alpha'| \leq \frac{1}{4} \cdot 2^{-2^{r(n)}} \leq \frac{1}{4}(c - s)$.

We now use SDP duality (in a manner reminiscent of LP solutions for the Chebyshev approximation problem, p. 293 of [BV04]) to rephrase (25) as an SDP. Suppose we fix a feasible ρ_1 and solve the inner optimization problem in (25). Then:

$$\alpha'(\rho_1) := \min_{\rho_2} \{ \langle C', \rho_1 \otimes \rho_2 \rangle : \text{Tr}(\rho_2) = 1, \rho_2 \succeq 0 \}.$$

We can rewrite $\langle C', \rho_1 \otimes \rho_2 \rangle$ as $\langle \text{Tr}_1[(\rho_1 \otimes I)C'], \rho_2 \rangle$ where Tr_1 is the partial trace over the register that ρ_1 acts on. Additionally, as $\text{Tr}_1[(\rho_1 \otimes I)C'] = \text{Tr}_1[(\rho_1^{1/2} \otimes I)C(\rho_1^{1/2} \otimes I)]$, this term is Hermitian and positive semidefinite. This implies that the best choice for ρ_2 is a rank-1 projector onto the eigenspace corresponding to the least eigenvalue. In other words, $\alpha'(\rho_1) = \lambda_{\min}(\text{Tr}_1[(\rho_1 \otimes I)C'])$ where $\lambda_{\min}(X)$ denotes the least eigenvalue of operator X . For fixed ρ_1 , this minimum eigenvalue calculation can be rephrased via the dual optimization program for $\alpha'(\rho_1)$,

$$\alpha'(\rho_1) = \max_t \{ t : tI \preceq \text{Tr}_1[(\rho_1 \otimes I)C'] \}.$$

⁶This can be accomplished in exponential time as follows. Replace gate set G with G' by approximating each entry of each gate in G using $2^{s(n)}$ bits of precision, for some sufficiently large, fixed polynomial s . Define C' as C , except each use of a gate $U \in G$ is replaced with its approximation $U' \in G'$. Then, via the well-known bound $\|U_m \cdots U_1 - V_m \cdots V_1\|_\infty \leq \sum_{i=1}^m \|U_i - V_i\|_\infty$ (for unitary U_i, V_i), it follows that $\|C' - C\|_\infty \in O(\text{poly}(n)/(2^{2^{s(n)}}))$, since V_n contains $\text{poly}(n)$ gates. Here, $\|A\|_\infty = \max_{|\psi\rangle} \|A|\psi\rangle\|_2$ for unit vectors $|\psi\rangle$ denotes the spectral or operator norm. Finally, apply the fact that $\max_{i,j} |A(i,j)| \leq \|A\|_\infty$ (p. 314 of [HJ90]).

Re-introducing the maximization over ρ_1 , we hence obtain

$$\alpha' = \max_{\rho_1, t} \{t : tI \preceq \text{Tr}_1[(\rho_1 \otimes I)C'], \text{Tr}(\rho_1) = 1, \rho_1 \succeq 0\},$$

which is a semidefinite program.

With an SDP in hand, we now apply the Ellipsoid Method to obtain an estimate, γ , for α' . Note that not all SDPs can be solved in polynomial time, as the runtime of the Ellipsoid Method depends in part on two parameters, R and ϵ , where R is the radius of a ball (with respect to the Euclidean norm) containing the feasible region, and ϵ is the radius of a ball contained in the feasible region (see [GLS93] for details). For this reason, we give an equivalent SDP which allows us to bound R and ϵ as follows. First, relax the constraint $\text{Tr}(\rho) = 1$ to $\text{Tr}(\rho) \leq 1$. Second, replace t with $t_1 - t_2$ where $t_1, t_2 \geq 0$. From context, we know t is a probability, and so we have the implicit constraint $t \in [0, 1]$. Therefore, we add redundant constraints $t_1, t_2 \leq 100$ without changing α' . Thus, we have the following reformulation of α' .

$$\alpha' = \max_{\rho_1, t_1, t_2} \{t_1 - t_2 : (t_1 - t_2)I \preceq \text{Tr}_1[(\rho_1 \otimes I)C'], \text{Tr}(\rho_1) \leq 1, \rho_1 \succeq 0, t_1, t_2 \in [0, 100]\}. \quad (26)$$

We can now use the Ellipsoid Method to approximately solve this SDP in time that is exponential in n . We follow a similar analysis to [Wat09b] and find a γ such that $|\gamma - \alpha'| \leq \epsilon$ in time

$$\text{poly}(\log(R), \log(1/\epsilon), n', m, J), \quad (27)$$

for parameters R, ϵ, n', m , and J defined as:

- R : This is equal to the maximum of $\|\rho_1 \oplus t_1 \oplus t_2\|_2$ over all feasible (ρ_1, t_1, t_2) . Since we have

$$\|\rho_1 \oplus t_1 \oplus t_2\|_2 \leq \|\rho_1 \oplus t_1 \oplus t_2\|_1 = \text{Tr}(\rho_1 \oplus t_1 \oplus t_2) = \text{Tr}(\rho_1) + t_1 + t_2 \leq 201, \quad (28)$$

for feasible (ρ_1, t_1, t_2) , we can set $R = 201$.

- ϵ : This plays the role of a small radius ball contained in the feasible region. Specifically, ϵ is defined so that there exists feasible (ρ_1, t_1, t_2) such that $(\rho_1, t_1, t_2) + (\sigma, \tau_1, \tau_2)$ is feasible for all (σ, τ_1, τ_2) with $\|\sigma \oplus \tau_1 \oplus \tau_2\|_2 \leq \epsilon$. Since we have

$$\epsilon \geq \|\sigma \oplus \tau_1 \oplus \tau_2\|_2 = \|\sigma\|_2 + |\tau_1| + |\tau_2| \geq \max\{\|\sigma\|_2, |\tau_1|, |\tau_2|\}, \quad (29)$$

we will use the more convenient bound $\max\{\|\sigma\|_2, \tau_1, \tau_2\} \leq \epsilon$ for the analysis. We choose the interior point

$$\rho_1 = \frac{1}{\dim(\rho_1)^2} I, \quad t_1 = 10, \quad t_2 = 20, \quad (30)$$

and

$$\epsilon = \frac{1}{4} \cdot 2^{(-2^{r(n)})} \leq \frac{1}{4}(c - s). \quad (31)$$

Note that this has the sufficiently small accuracy we require.

We now prove that $(\rho_1, t_1, t_2) + (\sigma, \tau_1, \tau_2)$ is feasible so long as $\max\{\|\sigma\|_2, \tau_1, \tau_2\} \leq \epsilon$. One can check that for these values, we have

1. $\rho_1 + \sigma \succeq \rho_1 - \|\sigma\|_\infty I \succeq \rho_1 - \epsilon I \succeq 0$, (where we used $\|\sigma\|_2 \leq \epsilon$ implies $\|\sigma\|_\infty \leq \epsilon$),
2. $\text{Tr}(\rho_1 + \sigma) = \text{Tr}(\rho_1) + \text{Tr}(\sigma) \leq \text{Tr}(\rho_1) + \|\sigma\|_2 \|I\|_2 \leq \frac{1}{\dim(\rho_1)} + \epsilon \sqrt{\dim(\rho_1)} \leq 1$, (using the Cauchy-Schwarz inequality),

3. $t_1 + \tau_1 \in [0, 100]$ and $t_2 + \tau_2 \in [0, 100]$,
 4. $((t_1 + \tau_1) - (t_2 + \tau_2))I \prec 0 \preceq \text{Tr}_1[(\rho_1 - \sigma) \otimes I]C'$, (since $(t_1 + \tau_1) - (t_2 + \tau_2) < 0$ and $\rho_1 + \sigma \succeq 0$ as shown above).
- n' : The dimension of $\rho_1 \oplus t_1 \oplus t_2$, which is equal to the sum of the dimensions, i.e., $O(2^{p(n)})$.
 - m : The dimension of the operators appearing in the constraints. Note, from (26), that constraint $(t_1 - t_2)I \preceq \text{Tr}_1[(\rho_1 \otimes I)C]$ involves operators acting on a space of dimension $O(2^{p(n)})$. Moreover, there are only 3 other inequality constraints: $\text{Tr}(\rho) \leq 1$ and $t_1, t_2 \leq 100$. Thus, $m = O(2^{p(n)})$.
 - J : The maximum bit-length of the entries in C' , which is $2^{q(n)}$, by definition.

We conclude that the EXP protocol approximates α' via γ , which is correct up to an additive error of $\frac{1}{4}(c - s)$. Finally, if $\gamma \geq (c + s)/2$, we output YES (i.e. $x \in A_{\text{yes}}$). Otherwise, we output NO (i.e. $x \in A_{\text{no}}$).

As mentioned previously, a similar proof holds for the case of a QII₂ protocol, except that the check at the end is for the no-case instead of the yes-case. This is because the optimization in this case is to test whether there *exists* a proof ρ_1 making the verifier *reject* (as opposed to trying to make the verifier accept in QΣ₂). \square

Using the power of non-determinism, we can also bound the complexity of QΣ₃ and QΠ₃.

Theorem 4.2. *For any polynomial r and input size n , if $c - s \geq 1/r(n)$, then*

$$\text{QMA}(2) \subseteq \text{Q}\Sigma_3 \subseteq \text{NEXP} \quad \text{and} \quad \text{co-QMA}(2) \subseteq \text{Q}\Pi_3 \subseteq \text{NEXP}, \quad (32)$$

where all classes have completeness and soundness c and s , respectively. Moreover, if we allow smaller gaps (in principle, gaps which are at most inverse singly exponential in n suffice for the first claim below), such as $c - s \geq 1/2^{2^{t(n)}}$, then

$$\text{QMA}(2)(c, s) = \text{Q}\Sigma_3(c, s) = \text{NEXP} \quad \text{and} \quad \text{Q}\Pi_3(c, s) \subseteq \text{NEXP}. \quad (33)$$

Here, we assume c and s are computable in exponential time in the size of the input.

Proof. Consider the maximum acceptance probability of a QΣ₃ protocol,

$$\beta := \max_{\rho_1} \min_{\rho_2} \max_{\rho_3} \{ \langle C, \rho_1 \otimes \rho_2 \otimes \rho_3 \rangle : \text{Tr}(\rho_1) = \text{Tr}(\rho_2) = \text{Tr}(\rho_3) = 1, \rho_1, \rho_2, \rho_3 \succeq 0 \}$$

where C is the POVM element corresponding to the verifier accepting. As in the proof of Theorem 4.1, define C' to be equal to C where each entry is correct up to $2^{q(n)}$ bits of precision.

Now, suppose we non-deterministically guess a value for the optimal ρ_1 by a matrix, each of whose entries is specified up to $2^{t(n)}$ bits of precision for some polynomial t . Call this approximation ρ'_1 . Define $C'' := \text{Tr}_1[(\rho'_1 \otimes I \otimes I)C']$ to be the matrix which hardcodes ρ'_1 into C' . Define $D = \text{Tr}_1[(\rho_1 \otimes I \otimes I)C]$ and $D' = \text{Tr}_1[(\rho_1 \otimes I \otimes I)C']$. Now we have, for any density operator σ ,

$$| \langle C'' - D, \sigma \rangle | \leq \|C'' - D\|_2 \|\sigma\|_2 \leq \|C'' - D\|_2 \leq \|C'' - D' + D' - D\|_2 \leq \|C'' - D'\|_2 + \|D' - D\|_2. \quad (34)$$

Then, we can bound

$$\begin{aligned}
\|C'' - D\|_2 &= \|\text{Tr}_1 [((\rho'_1 - \rho_1) \otimes I \otimes I)C']\|_2 \\
&\leq \|((\rho'_1 - \rho_1) \otimes I \otimes I)C'\|_1 \\
&\leq \|((\rho'_1 - \rho_1) \otimes I \otimes I)\|_1 \|C + E\|_1 \\
&\leq 2 \|((\rho'_1 - \rho_1) \otimes I \otimes I)\|_1 \|C\|_1 \\
&\leq \|\rho'_1 - \rho_1\|_1 \cdot 2^{5p(n)} \\
&\leq \|\rho'_1 - \rho_1\|_2 \cdot 2^{11p(n)/2} \\
&\leq \frac{2^{13p(n)/2}}{2^{2t(n)}},
\end{aligned}$$

where the second and sixth statements follow from the bounds $\|A\|_2 \leq \|A\|_1 \leq \sqrt{d}\|A\|_2$ for A a linear operator on \mathbb{C}^d and $\|A\|_1 = \text{Tr}(\sqrt{A^\dagger A})$ the trace norm. The third inequality defines a perturbation matrix E with entries of absolute value at most $2^{-2q(n)}$ and the fourth comes from the sub-multiplicativity of the trace norm and the Gershgorin circle theorem. The fifth inequality holds since $C \succeq 0$, and the seventh since $\|A\|_2 \leq d \cdot \max_{i,j} |A(i,j)|$ for $n \times n$ matrix A . Similarly, one can show $\|D' - D\|_2 \in O((2^{O(p(n))})/(2^{-2q(n)}))$. Thus, we can choose q and t sufficiently large so that $|\langle C'' - D, \sigma \rangle| \leq \frac{1}{4}(c-s)$, as in the previous proof. Since C'' still has exponential bit-length, is positive semidefinite, and can be computed in non-deterministic exponential time, we can repeat the arguments from Theorem 4.1. This yields

$$\text{Q}\Sigma_3 \subseteq \text{NEXP}, \quad (35)$$

even when $\text{Q}\Sigma_3$ has small gap. A similar argument works for $\text{Q}\Pi_3$. The rest of the theorem holds by a result of Pereszlényi [Per12], who proved that the equality $\text{QMA}(2)(c,s) = \text{NEXP}$ holds when $c-s \geq 2^r$ for polynomial r . Combining this with the fact that $\text{QMA}(2) \subseteq \text{Q}\Sigma_3$ and (35) finishes the proof. \square

5 A Karp-Lipton type theorem

An early indication in favour of the conjecture that $\text{P} \neq \text{NP}$ was given by the Karp-Lipton [KL80] theorem, which showed that if $\text{NP} \subseteq \text{P}/\text{poly}$ (i.e. if NP can be solved by polynomial-size non-uniform circuits), then $\Sigma_2 = \Pi_2$ (which in turn collapses PH collapses to its second level). Here, we show that the proof technique used by Karp and Lipton carries over directly to the quantum setting, *provided* one uses the stronger hypothesis

$$\text{Precise-QCMA} \subseteq \text{BQP}/\text{mpoly} \quad (36)$$

(as opposed to $\text{QCMA} \subseteq \text{BQP}/\text{mpoly}$). Whether this causes QCPH to collapse to its second level, however, remains open (see Remark 5.5 below). We begin by defining Precise-QCMA.

Definition 5.1 (Precise-QCMA). *A promise problem $A = (A_{\text{yes}}, A_{\text{no}})$ is said to be in Precise-QCMA(c, s) for polynomial-time computable functions $c, s : \mathbb{N} \mapsto [0, 1]$ if there exists polynomially bounded functions $p, q : \mathbb{N} \mapsto \mathbb{N}$ such that $\forall \ell \in \mathbb{N}$, $c(\ell) - s(\ell) \geq 2^{-q(\ell)}$, and there exists a polynomial-time uniform family of quantum circuits $\{V_n\}_{n \in \mathbb{N}}$ that takes a classical proof $y \in \{0, 1\}^{p(n)}$ and outputs a single qubit. Moreover, for an n -bit input x :*

- *Completeness:* If $x \in A_{\text{yes}}$, then $\exists y$ such that V_n accepts y with probability at least $c(n)$.
- *Soundness:* If $x \in A_{\text{no}}$, then $\forall y$, V_x accepts y with probability at most $s(n)$.

Define $\text{Precise-QCMA} = \bigcup_{c,s} \text{Precise-QCMA}(c, s)$.

Observation 5.2. The proof of Theorem 2.5 and footnote 2 in [JKNN12] show that by choosing an appropriate universal gate set (e.g. Hadamard, Toffoli, NOT), one has that

$$\text{Precise-QCMA} = \text{Precise-QCMA}(1, 1 - 1/\exp(n)). \quad (37)$$

As an aside, note that QCMA is defined with $c - s \in \Omega(1/\text{poly}(n))$. Recall from the discussion in Section 1.1 that the main obstacle to the recursive arguments that work well for NP in [KL80] is the “promise problem” nature of QCMA_2 and QCMA. However, exploiting the perfect completeness of Precise-QCMA and the fact that $\forall s \leq s' < c$, $\text{Precise-QCMA}(c, s) \subseteq \text{Precise-QCMA}(c, s')$, we “recover” the notion of a decision problem in a rigorous sense by working with Precise-QCMA as demonstrated below.

Claim 5.3. For every promise problem $\Pi' = (A_{\text{yes}}, A_{\text{no}}) \in \text{Precise-QCMA}(c, s)$ with verifier V' , there exists a verifier V (a poly-time uniform quantum circuit family), a polynomial q and a decision problem $\Pi = (A_{\text{yes}}, \{0, 1\}^* \setminus A_{\text{yes}})$ such that $\Pi \in \text{Precise-QCMA}(1, 1 - 2^{-q(n)})$ with verifier V . Moreover, for all proofs y , V accepts y with probability either 1 or at most $1 - 2^{-q(n)}$.

Proof. By Observation 5.2, we may assume

$$\text{Precise-QCMA}(c, s) = \text{Precise-QCMA}(1, 1 - 2^{-p(n)}) \quad (38)$$

for some polynomial p . Let $\Pi = (A_{\text{yes}}, A_{\text{no}}) \in \text{Precise-QCMA}(1, 1 - 2^{-p(n)})$ be a promise problem with verifier V . The concern is that for $x \in A_{\text{yes}}$, there may exist a proof y accepted by V with probability in $(1, 1 - 2^{-p(n)})$. By Observation 3.2, we may assume the acceptance probabilities of V are integer multiples of $2^{-q(n)}$ for some polynomial q . Since p and q are polynomials, there exists $n_0 \geq 0$ such that $\forall n \geq n_0$, either $p(n) \geq q(n)$ or vice versa. Thus, updating the soundness parameter to $1 - 2^{-p(n)}$ in the former case and to $1 - 2^{-q(n)}$ in the latter case ensures that no proofs are accepted by V in the promise gap for sufficiently large n . This yields the second claim of the observation. The first claim now also follows, since if no proofs are accepted in the promise gap, then certainly the optimal proof is also not accepted in the gap. \square

Note that the same process fails to map a promise problem $\Pi' \in \text{QCMA}(1, s)$ to a corresponding decision problem $\Pi \in \text{QCMA}(1, s')$ where $1 < s' \leq s$. As shown above, s' could very well be exponentially close to 1, which would violate the requirement, by definition, for QCMA that the promise gap should be an inverse polynomial function in the input size.

Building on this “decision problem” flavour of Precise-QCMA, we first show:

Lemma 5.4. Suppose $\text{Precise-QCMA} \subseteq \text{BQP}_{/\text{mpoly}}$. Then, for every promise problem $\Pi = (A_{\text{yes}}, A_{\text{no}})$ in Precise-QCMA and every n -bit input x , there exists a polynomially bounded function $p : \mathbb{N} \mapsto \mathbb{N}$ and a bounded error polynomial time non-uniform quantum circuit family $\{C_n\}_{n \in \mathbb{N}}$ such that:

- if $x \in A_{\text{yes}}$, then C_n outputs valid proof $y \in \{0, 1\}^{p(n)}$ such that (x, y) is accepted by the corresponding Precise-QCMA verifier with probability 1;
- if $x \in A_{\text{no}}$, then C_n outputs a symbol \perp with probability exponentially close to 1 signifying that there is no $y \in \{0, 1\}^{p(n)}$, such that (x, y) is accepted by the corresponding Precise-QCMA verifier with probability 1.

Proof. To begin, recall from Claim 5.3 that we may assume that a given promise problem Π in Precise-QCMA has (a) completeness/soundness parameters $(1, 1 - 2^{-q(n)})$ for a polynomial q and (b) a verifier V_n for an n -bit input x which accepts no proofs with probability in the promise gap. Since Precise-QCMA \subseteq BQP/mpoly, by assumption, there exists a non-uniform polynomial-size quantum circuit family $\{C'_n\}_{n \in \mathbb{N}}$ that accepts x as advice such that for any $x \in A_{\text{yes}}$, C'_n accepts with probability at least $2/3$ and rejects with probability $2/3$ otherwise. By using standard parallel repetition, we may assume without loss of generality that C'_n accepts or rejects the corresponding cases with probability at least $1 - 2^{-p(n)}$ for some polynomial p . Now, we would like to construct a BQP/mpoly circuit C_n that uses the input x and a description of C'_n as polynomial-sized advice and outputs a valid proof y such that V_n accepts (x, y) with probability 1.

The construction of $\{C_n\}$ is now as follows. C_n first runs C'_n using x to check if $x \in A_{\text{yes}}$; if not, it rejects and outputs \perp . To find a proof y , we now use standard self-reducibility ideas from SAT, coupled with the crucial Claim 5.3. Specifically, fix $y_1 = 0$ (i.e. the first bit of y) to obtain a new circuit $C'_{n,1}$, run $C'_{n,1}$ on (x, y_1) and record its answer $z_1 \in \{0, 1\}$. Since no proofs are accepted in the gap as per Claim 5.3, $C'_{n,1}$ is a valid Precise-QCMA machine (i.e. satisfying the promise of the completeness/soundness parameters). Thus, with high probability, if $z_1 = 1$ there is an accepting proof for x whose first bit is 0 and if $z_1 = 0$, there is a proof with the first bit set to 1. Hence, we can fix y_1 's accordingly. Iterating this process successively for all remaining bits of y yields the claim. \square

We next give a quantum-classical analogue of the Karp-Lipton theorem.

Theorem 1.8 (A Quantum-Classical Karp-Lipton Theorem). *If Precise-QCMA \subseteq BQP/mpoly then QCII₂ = QCΣ₂.*

Proof. We essentially follow the proof of the original Karp-Lipton theorem, coupled with careful use of Observation 3.2. To show QCII₂ = QCΣ₂, it suffices to show that QCII₂ \subseteq QCΣ₂. To see this, consider promise problem $A \in \text{QC}\Sigma_2$. Now, \bar{A} (the complement of A) is in QCII₂ by definition. However, if QCII₂ \subseteq QCΣ₂, then $\bar{A} \in \text{QC}\Sigma_2$, which in turn implies by definition that $A \in \text{QCII}_2$, as desired.

To show QCII₂ \subseteq QCΣ₂, let $A = (A_{\text{yes}}, A_{\text{no}})$ be a QCII₂ problem. As QCII₂ has perfect completeness from Result 2.6, there exist polynomials p, r and a polynomial time uniform family of quantum circuits $\{V_i\}_{i \in \mathbb{N}}$ that take as input a string $x \in \{0, 1\}^n$ for some $n \in \mathbb{N}$, two classical proofs $u, v \in \{0, 1\}^{p(n)}$, and outputs a single qubit such that:

$$x \in A_{\text{yes}} \quad \Rightarrow \quad \forall u \exists v \Pr[V_n(x, u, v) = 1] = 1, \quad (39)$$

$$x \in A_{\text{no}} \quad \Rightarrow \quad \exists u \forall v \Pr[V_n(x, u, v) = 1] \leq \frac{1}{2^{r(n)}}. \quad (40)$$

Let us now highlight the difficulty in proving the claim for QCMA instead of Precise-QCMA. Specifically, if we fix the first proof u , what we would ideally require is that the resulting existentially quantified computation over v , denoted M_u ⁷, is in QCMA. Indeed, if $x \in A_{\text{yes}}$, then for any fixed u , there exists a v causing M_u to accept with certainty. The problem arises when $x \in A_{\text{no}}$, in which case, we require that for all v , M_u accepts with probability at most s for some soundness parameter s inverse polynomially gapped away from 1. Unfortunately, the definition of QCII₂ only ensures this holds for *some* u , and not necessarily *all* u . To circumvent this, we use Observation 3.2, which implies we may assume M_u 's acceptance probabilities are given by rational numbers with $\text{poly}(n)$ bits of precision (assuming an appropriate universal gate set is used).

⁷Notice that M_u is the remnant of the verifier circuit obtained from V_n when the first proof register is loaded with u . In a slight abuse of notation, M_u will be referred to both as a computation and as a circuit.

It follows that if M_u does not accept some v with probability 1, then it must reject v with probability at least $1 - 2^{-q(n)}$ for some efficiently computable polynomial q . Thus, by definition M_u is a Precise-QCMA($1, 1 - 2^{-q(n)}$) computation, to which we may now apply our hypothesis that $\text{Precise-QCMA} \subseteq \text{BQP}/_{\text{mpoly}}$. (Note: There is a subtle point here — the precise choice of q depends on the length of circuit M_u , which in turn depends on the Hamming weight of u , since we can simulate “fixing” u by adding appropriate Pauli X gates to our circuit. Nevertheless, it is trivial to choose a polynomial q which provides sufficient precision in our rational approximation in order to accommodate the fixing of proofs u of any Hamming weight.)

Since for any fixed u , M_u denotes a Precise-QCMA computation, our assumption says that there exists a non-uniform family of polynomial-sized bounded-error quantum circuits $\{Q'_n\}_{n \in \mathbb{N}}$ that accepts (x, u) and a description of M_u as advice and outputs a bit such that:

- if there exists a proof v such that M_u accepts (x, v) with probability 1, then Q'_n accepts (x, u, M_u) with probability at least $2/3$, and
- if for all proofs v , M_u accepts (x, v) with probability at most $1 - 2^{-q(n)}$, then Q'_n accepts (x, u, M_u) with probability at most $1/3$.

Crucially, the set $\{Q'_n\}$ is non-uniform, and thus Q'_n depends only on n , not the choice of x or u .

Continuing, from Lemma 5.4, we now conclude there exists a bounded-error polynomial time non-uniform quantum circuit family $\{Q_n\}_{n \in \mathbb{N}}$ which, whenever $x \in A_{\text{yes}}$, outputs a proof v which M_u accepts with certainty. For clarity, note that Q_n accepts (x, u) and a description of M_u as advice and outputs a string $v \in \{0, 1\}^{p(n)}$. Suppose Q_n outputs the correct answer with probability at least $1 - 2^{-s(n)}$ for some polynomial s , as per Lemma 5.4. Using the existence and non-uniformity of $\{Q_n\}$, as done in the proof of the classical Karp-Lipton theorem, we claim we may now swap the order of the quantifiers and write:

- If $x \in A_{\text{yes}}$, then $\exists Q_n \forall u \Pr[V_n(x, u, Q_n(x, u, M_u)) = 1] \geq 1 - 2^{-s(n)}$, and
- if $x \in A_{\text{no}}$, then $\forall Q_n \exists u \Pr[V_n(x, u, Q_n(x, u, M_u)) = 1] \leq \frac{1}{2^{r(n)}}$.

This would imply the desired claim that $\text{QC}\Pi_2 \subseteq \text{QC}\Sigma_2$.

To see that we may indeed swap quantifiers in this fashion, assume first that $x \in A_{\text{yes}}$. Then, choosing the non-uniform circuit family from Lemma 5.4 yields that for any fixed x and u , with probability at least $1 - 2^{-s(n)}$, Q_n outputs a proof v such that C_n accepts (x, u, v) with probability 1. Conversely, if $x \in A_{\text{no}}$, since for an appropriate choice of u , there are *no* proofs v such that C_n accepts (x, u, v) with probability more than $2^{-r(n)}$. Then, clearly no choice of Q_n is able to generate a proof $Q_n(x, u, M_u)$ such that C_n accepts $(x, u, Q_n(x, u, M_u))$ with probability more than $2^{-r(n)}$. \square

Remark 5.5 (Collapse of QCPH?). An appeal of the classical Karp-Lipton theorem is that it implies that if $\text{NP} \subseteq \text{P}/_{\text{poly}}$, then PH collapses to its second level; this is because if $\Pi_2 = \Sigma_2$, then PH collapses to Σ_2 . Does an analogous statement hold for QCPH as a result of Theorem 1.8? Unfortunately, the answer is not clear. The problem is similar to that outlined in Remark 3.7. Namely, classically $\Pi_2 = \Sigma_2$ collapses PH since for any Π_3 decision problem, fixing the first (universally) quantified proof yields a Σ_2 computation. But this can be replaced with a Π_2 computation by assumption, yielding a computation with quantifiers $\forall\forall\exists$, which trivially collapses to $\forall\exists$, i.e. $\Pi_3 \subseteq \Pi_2$. In contrast, for (say) $\text{QC}\Pi_3$, similar to the phenomenon in Remark 3.7, fixing the first (universally) quantified proof does *not* necessarily yield a $\text{QC}\Sigma_2$ computation. Thus, a recursive application of the assumption $\text{QC}\Sigma_2 = \text{QC}\Pi_2$ cannot straightforwardly be applied.

Since Precise-QCMA plays an important role in Theorem 1.8, we close with an upper bound on Precise-QCMA.

Lemma 5.6. $\text{Precise-QCMA} \subseteq \text{NP}^{\text{PP}}$.

Proof. Let V be a Precise-QCMA verifier. Using Claim 5.3, we may assume that for any proof y , V either accepts y with probability 1 or rejects with probability at most $1 - 2^{-q(n)}$. Thus, for any fixed y , the resulting computation V_y is a Precise-BQP computation. This implies $\text{Precise-QCMA} \subseteq \exists \cdot \text{Precise-BQP}$ (see also Remark 3.7). But by Definition 3.6, $\exists \cdot \text{Precise-BQP} \subseteq \text{NP}^{\text{Precise-BQP}}$. Combining this with Lemma 3.3, which says $\text{Precise-BQP} \subseteq \text{PP}$, yields the claim. \square

Acknowledgements

SG and AS thank the Centre for Quantum Technologies at the National University of Singapore for their support and hospitality, where part of this research was carried out. SG acknowledges support from NSF grants CCF-1526189 and CCF-1617710. AS is supported by the Department of Defense. Research at the Centre for Quantum Technologies is partially funded by the Singapore Ministry of Education and the National Research Foundation under grant R-710-000-012-135. This research was supported in part by the QuantERA ERA-NET Cofund project QuantAlgo. This research was supported in part by Perimeter Institute for Theoretical Physics. Research at Perimeter Institute is supported by the Government of Canada through the Department of Innovation, Science and Economic Development Canada and by the Province of Ontario through the Ministry of Research, Innovation and Science.

References

- [ABD⁺09] S. Aaronson, S. Beigi, A. Drucker, B. Fefferman, and P. Shor. The power of unentanglement. *Theory of Computing*, 5:1–42, 2009.
- [ABOBS08] D. Aharonov, M. Ben-Or, F. Brandão, and O. Sattath. The pursuit for uniqueness: Extending Valiant-Vazirani theorem to the probabilistic and quantum settings. Available at arXiv.org e-Print quant-ph/0810.4840v1, 2008.
- [ACGK17] S. Aaronson, A. Cojocaru, A. Gheorghiu, and E. Kashefi. On the implausibility of classical client blind quantum computing. Available at arXiv.org e-Print quant-ph/1704.08482, 2017.
- [AD14] S. Aaronson and A. Drucker. A full characterization of quantum advice. *SIAM Journal on Computing*, 43(3):1131–1183, 2014.
- [Aha03] D. Aharonov. A simple proof that Toffoli and Hadamard are quantum universal. Available at arXiv.org e-Print quant-ph/0301040, January 2003.
- [AKN98] D. Aharonov, A. Kitaev, and N. Nisan. Quantum circuits with mixed states. In *Proceedings of 13th ACM Symposium on Theory of Computing (STOC 1998)*, pages 20–30, 1998.
- [Amb14] A. Ambainis. On physical problems that are slightly more difficult than QMA. In *Proceedings of 29th IEEE Conference on Computational Complexity (CCC 2014)*, pages 32–43, 2014.

- [AN02] D. Aharonov and T. Naveh. Quantum NP - A survey. Available at arXiv.org e-Print quant-ph/0210077v1, 2002.
- [AW93] E. W. Allender and K. W. Wagner. *Counting hierarchies: Polynomial time and constant depth circuits*, pages 469–483. World Scientific, 1993.
- [Bei10] S. Beigi. NP vs $\text{QMA}_{\log}(2)$. *Quantum Information and Computation*, 10:0141–0151, 2010.
- [BT09] H. Blier and A. Tapp. All languages in NP have very short quantum proofs. In *Proceedings of the 3rd International Conference on Quantum, Nano and Micro Technologies*, pages 34–37, 2009.
- [BV04] S. Boyd and L. Vandenberghe. *Convex Optimization*. Cambridge University Press, 2004.
- [FFKL03] S. Fenner, L. Fortnow, S. A. Kurtz, and L. Li. An oracle builder’s toolkit. *Information and Computation*, 182(2):95 – 136, 2003.
- [For94] L. Fortnow. The role of relativization in complexity theory. *Bulletin of the European Association for Theoretical Computer Science*, 52:52–229, 1994.
- [FR99] L. Fortnow and J. Rogers. Complexity limitations on quantum computation. *Journal of Computer and System Sciences*, 59(2):240–252, 1999.
- [GK12] S. Gharibian and J. Kempe. Hardness of approximation for quantum problems. In *Proceedings of 39th International Colloquium on Automata, Languages and Programming (ICALP 2012)*, pages 387–398, 2012.
- [GKS16] A. B. Grilo, I. Kerenidis, and J. Sikora. QMA with subset state witnesses. *Chicago Journal of Theoretical Computer Science*, 4, 2016.
- [GLS93] M. Grötschel, L. Lovász, and A. Schrijver. *Geometric Algorithms and Combinatorial Optimization*. Springer-Verlag, 1993.
- [Gol06] O. Goldreich. On promise problems: A survey. *Theoretical Computer Science*, 3895:254–290, 2006.
- [GY18] S. Gharibian and J. Yirka. The complexity of simulating local measurements on quantum systems. In Mark M. Wilde, editor, *12th Conference on the Theory of Quantum Computation, Communication and Cryptography (TQC 2017)*, volume 73 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 2:1–2:17, Dagstuhl, Germany, 2018. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik.
- [HJ90] R. A. Horn and C. H. Johnson. *Matrix Analysis*. Cambridge University Press, 1990.
- [JJUW10] R. Jain, Z. Ji, S. Upadhyay, and J. Watrous. QIP = PSPACE. In *Proceedings of the 42nd Annual ACM Symposium on Theory of Computing*, pages 573–581, 2010.
- [JKNN12] S. P. Jordan, H. Kobayashi, D. Nagaj, and H. Nishimura. Achieving perfect completeness in classical-witness quantum Merlin–Arthur proof systems. *Quantum Information & Computation*, 12(5 & 6):461–471, 2012.

- [KL80] R. M. Karp and R. J. Lipton. Some connections between nonuniform and uniform complexity classes. In *Proceedings of the Twelfth Annual ACM Symposium on Theory of Computing*, STOC '80, pages 302–309, New York, NY, USA, 1980. ACM.
- [KIGN15] H. Kobayashi, F. le Gall, and H. Nishimura. Stronger methods of making quantum interactive proofs perfectly complete. *SIAM Journal on Computing*, 44(2):243–289, 2015.
- [KSV02] A. Kitaev, A. Shen, and M. Vyalyi. *Classical and Quantum Computation*. American Mathematical Society, 2002.
- [KW00] A. Kitaev and J. Watrous. Parallelization, amplification, and exponential time simulation of quantum interactive proof systems. In *Proceedings of the 32nd ACM Symposium on Theory of Computing (STOC 2000)*, pages 608–617, 2000.
- [LCV07] Y.-K. Liu, M. Christandl, and F. Verstraete. Quantum computational complexity of the N-representability problem: QMA complete. *Physical Review Letters*, 98:110503, 2007.
- [LGG17] J. Lockhart and C. E. González-Guillén. Quantum state isomorphism. *arXiv preprint arXiv:1709.09622*, 2017.
- [MS72] A. Meyer and L. Stockmeyer. The equivalence problem for regular expressions with squaring requires exponential time. In *Proceedings of the 13th Symposium on Foundations of Computer Science*, pages 125–129, 1972.
- [MW05] C. Marriott and J. Watrous. Quantum Arthur-Merlin games. *Computational Complexity*, 14(2):122–152, 2005.
- [Per12] A. Pereszlényi. Multi-prover quantum Merlin-Arthur proof systems with small gap. Available at arXiv.org e-Print quant-ph/1205.2761, 2012.
- [Shi03] Y. Shi. Both Toffoli and controlled-NOT need little help to do universal quantum computing. *Quantum Information and Computation*, 3(1):84–92, January 2003.
- [Tod91] S. Toda. PP is as hard as the Polynomial-Time Hierarchy. *SIAM Journal on Computing*, 20:865–877, 1991.
- [VV86] L. G. Valiant and V. V. Vazirani. NP is as easy as detecting unique solutions. *Theoretical Computer Science*, 47:85–93, 1986.
- [Vya03] M. Vyalyi. QMA=PP implies that PP contains PH. *Electronic Colloquium on Computational Complexity*, 2003.
- [Wat09a] J. Watrous. *Encyclopedia of Complexity and System Science*, chapter Quantum Computational Complexity. Springer, 2009.
- [Wat09b] J. Watrous. Semidefinite programs for completely bounded norms. *Theory of Computing*, 5:217–238, 2009.
- [Wat09c] J. Watrous. Zero-knowledge against quantum attacks. *SIAM Journal on Computing*, 39(1):25–58, 2009.
- [Wra76] C. Wrathall. Complete sets and the Polynomial-Time Hierarchy. *Theoretical Computer Science*, 3(1):23 – 33, 1976.

- [Yam02] T. Yamakami. Quantum NP and a quantum hierarchy. In *Proceedings of the 2nd IFIP International Conference on Theoretical Computer Science*, pages 323–336. Kluwer Academic Publishers, 2002.