Superensemble classifier for learning from imbalanced business school data set

Tanujit Chakraborty¹, Ashis Kumar Chakraborty²

 1 and 2 SQC and OR Unit, Indian Statistical Institute, 203, B. T. Road, Kolkata - 700108, India

Abstract

Private business schools in India face a common problem of selecting quality students for their MBA programs to achieve desired placement percentage. Business school data set is biased towards one class, i.e., imbalanced in nature. And learning from imbalanced data set is a difficult proposition. Most existing classification methods tend not to perform well on minority class examples when the data set is extremely imbalanced, because they aim to optimize the overall accuracy without considering the relative distribution of each class. The aim of the paper is twofold. We first propose an integrated sampling technique with an ensemble of classification tree (CT) and artificial neural network (ANN) model as one of the methodologies which works better compared to other similar methods. Further we propose a superensemble imbalanced classifier which works better on the original business school data set. Our proposed superensemble classifier not only handles the imbalance data set but also achieves higher accuracy in case of feature selection cum classification problems. The proposal has been compared with other stateof-the-art classifiers and found to be very competitive.

Keywords: Business School Problem, Imbalanced Data, Sampling Techniques, Hellinger Distance, Ensemble Classifier

1. Introduction

Out of the many reasons behind the closing down of many of the private business schools in India, the foremost one is the unemployment of Master

¹Corresponding author: Tanujit Chakraborty (tanujit_r@isical.ac.in)

of Business Administration (MBA) students passing out of these business schools. The most challenging job for administrations is to find the optimal set of parameters for choosing candidates in their MBA program which will ensure employability of the candidates. Attracting students in business schools are highly dependent on the schools' past placement records. If right set of students are not selected for a few years, the number of unplaced students will certainly accumulate, resulting in the damage of reputation for the business school. One needs to develop an appropriate model in such a way that the model ensures appropriate feature selection (selection of important student's characteristics) with decision on the optimal values or ranges of the features and higher prediction accuracy of the classifier as well. In our previous work, we proposed an ensemble classifier based on CT and ANN (we call it EnCT-ANN Model) to solve the business school problem [1] and it's asymptotic properties were also studied [2]. In this article, we observed a vital property of the business school data set, i.e., it's imbalanced nature. Usual classifiers including EnCT-ANN model makes a simple assumption that the classes to be discriminated should have a comparable number of instances. Many real-world data sets including the business school data set are skewed, in which most of the cases belong to a larger class and far fewer cases belong to a smaller, yet usually more interesting class. It is also the case where the cost of misclassifying minority examples is much higher in terms of the seriousness of the problem in hand [3]. Due to higher weightage given to the majority class, these systems tend to misclassify the minority class examples as majority, and lead to a high false negative rate. In this particular example of business school data set, it is clearly a two-class problem with class distribution of 80:20, a straight forward method of guessing all instances to be placed would achieve an accuracy of 80%.

There are broadly two ways of dealing with imbalanced data problems. One such way to deal with the imbalanced data problems is to modify the class distributions in the training data by applying sampling techniques. Sampling techniques include oversampling the minority class to match the size of the majority class [4] and undersampling the majority class to match the size of the minority class [5]. Sampling is a popular strategy to handle the data imbalance as it simply rebalances the data at the data preprocessing stage. Sampling approaches have obvious deficiencies like undersampling majority instances may lose potential useful information of the data set and oversampling increases the size of the training data set, which may increase computational cost. On the other hand, a very successful technique, the Synthetic Minority Oversampling Technique (SMOTE) [6] oversamples the minority class by generating artificially interpolated data. Hybrid sampling approaches, viz. SMOTE with data cleaning methods (for example, Tomek links (TL) and Edited Nearest Neighbor (ENN) rule) not only balances the data, but also removes noisy examples lying on the wrong side of the decision boundary [7]. Even different combinations of undersampling, oversampling and ensemble learning techniques are found useful to tackle the curse of imbalanced data sets [8]. Nonetheless, data sampling is not the only way for handling imbalanced data sets. There exists some specially designed imbalanced data oriented algorithms which perform well on unmodified original imbalanced data sets. One of the most celebrated paper in the literature is Hellinger Distance Decision Tree (HDDT) [9] which used Hellinger Distance (HD) as decision tree splitting criterion and it is insensitive towards the skewness of the class distribution [10]. An immediate extension to this work is HD based random forest (HDRF) [11]. Another breakthrough in the literature is the Class Confidence Proportion Decision Tree (CCPDT), a robust decision tree algorithm which can handle original imbalanced data sets [12]. It is to be noted that imbalanced data oriented classifiers are sometimes preferred since it can work with original data set.

The key contributions of this paper are as follows:

(1) We have extended the work of EnCT-ANN model in the context of imbalanced problems. We first proposed an integrated data processing approach combining data cleaning by TL, undersampling by bootstrap and oversampling by SMOTE. Through experimental evaluation we have found that the proposed integrated approach along with EnCT-ANN model outperforms other sampling techniques over different classifiers. Situations where computational cost is not an issue and somehow a few minority examples are lost, this proposed methodology is preferred.

(2) This paper also recommends a superensemble classifier for feature selection cum classification problems in imbalanced business school data sets. It has the advantages of both the HDDT and ANN algorithm and it is highly useful for high dimensional data sets. Numerical evidence based on business school data set shows the robustness of the proposed algorithm.

2. Background

In this section, we will briefly introduce EnCT-ANN model and various methods for handling imbalanced data sets.

2.1. Ensemble CT-ANN model

In EnCT-ANN model [1], we first split the feature space into areas by CT algorithm. Most important features are chosen using CT and redundant features are eliminated. Then we build ANN model using the important variables obtained through CT algorithm along with prediction results made by CT algorithm which is used as an additional input feature in the neural networks. Then ANN model is applied with one (hidden) layer to get the final classification results. Since, we have taken CT output as an input feature in ANN model, the number of hidden layer is chosen to be one. The informal work-flow of the proposed model is as follows:

- First, apply CT algorithm to train and build a decision tree and record important features. The prediction results of CT algorithm is also chosen as an additional feature for further modeling.
- Using important input variables obtained from CT along with an additional input variable (CT output), a neural network is generated.
- Run one hidden-layered ANN algorithm with sigmoid activation function and record the classification results. The optimum number of neurons in the hidden layer of the model to be chosen as $O\left(\sqrt{\frac{n}{dlog(n)}}\right)$ [2], where n, d are number of training samples and number of input

features in ANN model, respectively.

2.2. Pre-processing imbalanced data sets

The application of pre-processing step in order to balance the class distribution is one way to solve the imbalanced data set problem. The main advantage of these techniques is that they are independent of the classifier used [7]. Sampling techniques are classified into three groups: undersampling, oversampling and hybrid sampling. Undersampling methods create a subset of the original data set by eliminating some of the examples of the majority class. One-sided selection (OSS) [13] is an under-sampling method resulting from the application of TL followed by the application of Condensed Nearest Neighbor (CNN). TL is used as an undersampling method that removes noisy and borderline majority class examples. CNN aims to remove examples from the majority class that are distant from the decision border. The remaining examples (safe majority class examples) and all minority class examples are used for learning. Another popular method, namely the Neighborhood cleaning rule (NCL), uses the Wilson's ENN [14] to remove majority class examples. ENN removes any example whose class label differs from the class of at least two of its three nearest neighbors. Oversampling methods create a superset of the original database by creating new ones from the original minority class instances. The most used oversampling method is SMOTE [6] which forms new minority class examples by interpolating between several minority class examples that lie together. Thus, the over-fitting problem is avoided and causes the decision boundaries for the minority class to spread further into the majority class space. The algorithm starts with searching for the k-nearest neighbors for each minority instance, and then for each neighbor, it randomly selects a point from the line connecting the neighbor and the instance itself. Finally, these data points are included as minority examples. Several hybrid sampling methods including SMOTE with ENN and SMOTE with TL provided very good results in practice [7].

2.3. Hellinger distance decision tree

Chawla [9] proposed HDDT which uses HD as the splitting criterion to build decision tree. HD is used as a measure of distributional divergence and has the property of skew insensitivity [15]. Let (Θ, λ) denote a measurable space. For any binary classification problem, let us suppose that P and Qbe two continuous distributions with respect to the parameter λ having the densities p and q in a continuous space Ω , respectively. Define HD as follows:

$$d_H(P,Q) = \sqrt{\int_{\Omega} (\sqrt{p} - \sqrt{q})^2 d\lambda} = \sqrt{2\left(1 - \int_{\Omega} \sqrt{pq} d\lambda\right)}$$

where $\int_{\Omega} \sqrt{pq} d\lambda$ is the Hellinger integral. It is noted that HD doesn't depend on the choice of the parameter λ . Given a countable space Φ , HD can also be written as follows:

$$d_H(P,Q) = \sqrt{\sum_{\phi \in \Phi} \left(\sqrt{P(\phi)} - \sqrt{Q(\phi)}\right)^2}$$

The bigger the value of HD is, the better is the discrimination of the features. A feature is selected that carries the minimal affinity between the classes. For application of HD as a decision tree criterion, the final formulation can be given as follows:

$$d_H(X_+, X_-) = \sqrt{\sum_{j=1}^K \left(\frac{|X_{+j}|}{|X_+|} - \frac{|X_{-j}|}{|X_-|}\right)^2}$$
(1)

where $|X_+|$ indicates the number of examples that belong to the majority class in training set and $|X_{+j}|$ is the subset of training set with the majority class and the value j for the feature X. Similar explanation can be written for $|X_-|$ and $|X_{-j}|$ but for the minority class. Here K is the number of partitions of the feature space X. Since equation (1) is not influenced by prior probability, it is insensitive to the class distribution. Based on the experimental results, Chawla [9] concluded that unpruned HDDT is recommended for dealing with imbalanced problems as a better alternative to sampling approaches.

3. Major problems faced when the data set is imbalanced

In this section, we are going to investigate the effect of class imbalance on CT followed by the effect of class imbalance on the performance metrics. Since EnCT-ANN model uses CT in the first stage, let us first investigate how decision boundaries created by CT get affected by imbalance ratio (the ratio between the number of minority and majority examples). Let X be an attribute and Y be the response class. Here Y^+ denotes majority class, Y^- denotes minority class and n is the total number of instances. Also, let $X^{\geq} \longrightarrow Y^+$ and $X^{<} \longrightarrow Y^-$ be two rules generated by CT. Table 1 shows the number of instances based on the rules generated using CT.

Class & Attribute	X^{\geq}	$X^{<}$	Sum of instances
Y^+	a	b	a + b
Y^{-}	c	d	c+d
Sum of attributes	a + c	b+d	n

Table 1: An example of notions of classification rules

In case of imbalanced data set, since the size of the majority class is always much larger than the size of the minority class, we will always have a+b >> c+d. It is clear that the generation of rules based on confidence in CT is biased towards majority class. Various measures like information gain (IG), gini index (GI) and misclassification impurity (MI) are expressed as a function of confidence and these impurity measures are used to decide which variable to split in the important feature selection stage [16].

From Table 1, we can define $\operatorname{Confidence}(X^{\geq} \longrightarrow Y^{+}) = \frac{a}{a+c}$. Let us consider a binary classification problem with label set $\Omega = \{\omega_1, \omega_2\}$ and let P(j/t) be the probability for class ω_j at a certain node t of classification tree, where, j = 1, 2. These probabilities can be estimated as the proportion of points from the respective class within the data set that reached the node t. Using Table 1, the following can be computed:

$$P(Y^+/X^{\geq}) = \frac{a}{a+c} = \text{Confidence}(X^{\geq} \longrightarrow Y^+)$$
(2)

For an imbalanced data set, Y^+ will occur more frequently with $X^{\geq} \& X^{<}$ than to Y^- . So the concept of confidence is a fatal error in an imbalanced classification problem where minority class is of more interest and data is biased towards the majority class. In binary classification, information gain for splitting a node t is defined as:

$$IG = Entropy(t) - \sum_{i=1,2} \frac{n_i}{n} Entropy(i)$$
(3)

where *i* represents one of the sub-nodes after splitting (assuming we have two sub-nodes only), n_i is the number of instances in sub-node *i* and *n* is the total number of instances. Entropy at node *t* is defined as:

$$Entropy(t) = -\sum_{j=1,2} P(j/t) log(P(j/t))$$
(4)

The objective of classification using CT is to maximize IG which reduces to (assuming training set is fixed and so the first term in equation (3) is fixed as well):

$$\text{Maximize}\left\{-\sum_{i=1,2}\frac{n_i}{n}\text{Entropy}(i)\right\}$$
(5)

Using Table 1 and equation (4); the maximization problem in equation (5) reduces to:

$$\begin{aligned}
&\operatorname{Maximize} \left\{ \frac{n_1}{n} \Big[P(Y^+/X^{\geq}) log \big(P(Y^+/X^{\geq}) \big) + P(Y^-/X^{\geq}) log \big(P(Y^-/X^{\geq}) \big) \big] \\
&+ \frac{n_2}{n} \Big[P(Y^+/X^{<}) log \big(P(Y^+/X^{<}) \big) + P(Y^-/X^{<}) log \big(P(Y^-/X^{<}) \big) \Big] \right\} (6)
\end{aligned}$$

The task of selecting the best feature for node *i* is carried out by picking up the feature with maximum IG. As $P(Y^+/X^{\geq}) >> P(Y^-/X^{\geq})$, we face a problem while maximizing (6). It can be concluded from the above discussion that feature selection in CT based on the impurity measures is biased towards majority class.

The problem can be looked upon from the perspective of performance evaluation metrics as well. Standard notations of confusion matrix is given in Table 2. From Table 2 and using Equation (2), we can write $P(Y^+/X^{\geq}) = \frac{\text{TP}}{\text{TP}+\text{FP}} > P(Y^-/X^{\geq}) = \frac{\text{FP}}{\text{TP}+\text{FP}}$, etc. Since misclassification rate in the minority class is higher than the misclassification rate in the majority class, confusion matrix based on different classification algorithms will have a fatal error. As a consequence, prediction models with imbalanced data will lead to a high false negative rate.

Table 2: Confusion Matrix for Binary Classification Problem

All instances	Predicted majority class	Predicted minority class
Actual majority class	True Positive (TP)	False Negative(FN)
Actual minority class	False Positive (FP)	True Negative (TN)

4. Proposed methodology for handling imbalanced data set

4.1. Methodology 1: Integrated sampling with EnCT-ANN model

One way of solving the imbalanced class problem is to modify the class distribution in the training data by undersampling the majority class or oversampling the minority class or using a hybrid one. To avoid taking risks of inducing ambiguities along the decision boundaries, we choose to filter out the impure data first before sampling. TL [17] is defined as follows: given two examples Z_i and Z_j belonging to different classes with $d(Z_i, Z_j)$ as the distance between Z_i and Z_j , we call a pair (Z_i, Z_j) a Tomek link if there doesn't exist an example Z_k such that any of the following inequality holds: (a) $d(Z_i, Z_k) < d(Z_i, Z_j)$ and (b) $d(Z_j, Z_k) < d(Z_i, Z_j)$.

If a pair forms a TL, then either both the examples are border-line or any one of them is a noise. As a data cleaning method it is advised to remove examples of both the classes [7]. In our work, however, to further reduce the uncertainty from both the classes, such a filtering process is taken on each side. Now after data filtering, we address the imbalanced problem by combining both the under-sampling and the oversampling approaches together. We first oversample the minority instances with the SMOTE algorithm. SMOTE uses the idea of forming new minority class examples by interpolating between several minority class examples that lie together. Then we under-sample the majority class so that both sides have the same or similar amount of instances. To under-sample the majority class, we use the bootstrap sampling approach [18] with all available majority instances, provided that the size of the new majority class is the same as that of the minority class after running SMOTE. The benefit of doing so is that this approach inherits the strength of both the strategies, and alleviates the overfitting and information loss problems. Proposed integrated sampling or data pre-processing technique is abbreviated as SBT in rest of the paper. After the data set becomes balanced, we apply EnCT-ANN for further feature selection cum classification task. Figure 1 shows the workflow of balancing the data set using the proposed algorithm.

4.2. Methodology 2: Superensemble imbalance classifier

Methodology 1 has the major drawback of changing the original data set into a synthetic data set. The motivation behind designing superensemble classifier is when we would like to work with the original data set without taking recourse to sampling. For an imbalanced classification problem, we are going to create a superensemble classifier which will utilize the power of HDDT as mentioned in Section 2.3 as well as the superiority of neural networks. In the proposed superensemble classifier, we first split the feature space into areas by HDDT algorithm. Most important features are chosen using HDDT and redundant features are extracted. We then build ANN model using the important variables obtained through HDDT algorithm along with the prediction results obtained from HDDT are used as another input information in the input layer of neural networks. The effectiveness of the proposed classifier lies in the selection of important features and using prediction results of HDDT followed by the ANN model. The inclusion of HDDT output as an additional input feature not only improves the model accuracy but also increases class separability. This superensemble classifier not only handles imbalance through the implementation of HDDT in selecting features but also improves performance of the classifier by incorporating better classification results for the data set obtained from HDDT and the model gets improved using ANN algorithm. The informal workflow of our proposed superensemble model, shown in Figure 2 is as follows:



Figure 1: Workflow of Methodology 1

- Sort the feature value in ascending order and find the splits between adjacent different values of the feature. Calculate the binary conditional probability divergence at each split using HD (equation (6)).
- Record the highest divergence as the divergence of the whole feature. Choose the feature hat has maximum HD value and grow unpruned HDDT.
- Using HDDT algorithm, build a decision tree. Feature selection model is generated by HDDT takes into account the imbalance nature of the data set.

- The prediction result of HDDT algorithm is used as an additional feature in the input layer of ANN model.
- Export important input variables along with additional feature to the ANN model and a neural network is generated.
- Since the output results of HDDT has been incorporated as an additional feature along with other important features obtained by HDDT in input layer of ANN, so the number of hidden layer is chosen to be one.
- A one hidden layered ANN with sigmoid activation function having number of neurons in the hidden layer to be $O\left(\sqrt{\frac{n}{dlogn}}\right)$, where *n* is the number of training samples, *d* is the number of input features in ANN model which makes the classifier universally consistent [2]. And record the classification results.

This algorithm is a multi-step problem solving approach such as handling imbalanced class distribution, selecting important features and getting an improved classifier. The optimal characteristics of students which affect the placements can be chosen by our model and future predictions and modeling the imbalanced data set can also be done by the superensemble classifier. Now we will experimentally show that the proposed model works better compared with the state-of-the-art models for the business school data set.

5. Experimental evaluation

In this section, we first describe the business school data in brief and also discuss different evaluation measures that are used in this study. Subsequently, we are going to report the experimental results and compare our proposed methodologies with state-of-the-arts.

5.1. Description of data set

The data was provided by a private business school which receives applications for the MBA program from across the country and admits a prespecified number of students every year [1]. This data set comprises of several parameters of previous pass out student's profile along with their placement



Figure 2: An example of superensemble classifier with X_i ; i = 1, 2, 3, 4, 5 as Important features obtained by HDDT, L_i as leaf nodes and OP as HDDT output.

information. We divided the data into training set (80 percent of the records) for building the model and test set (20 percent of the records) to check accuracy of the models. The data set contains 24 explanatory variables out of which there are 7 categorical variables, 10 continuous variables and 7 dummy variables which represent the parameters of the students and one response variable, namely placement which indicates whether the student got placed or not. Sample data set is shown in Table 3.

Table 3: Sample business school data set.

ID	Gender	SSC	HSC	Degree	E.Test	SSC	HSC	HSC	Placement
		Percentage	Percentage	Percentage	Percentile	Board	Board	Stream	
1	Μ	68.4	85.6	72	70	ICSE	ISC	Commerce	Y
2	M	59	62	50	79	CBSE	CBSE	Commerce	Y
3	Μ	65.9	86	72	66	Others	Others	Commerce	Y
4	F	56	78	62.4	50.8	ICSE	ISC	Commerce	Y
5	F	64	68	61	24.3	Others	Others	Commerce	Ν
6	F	70	55	62	89	Others	Others	Science	Y
•		•		•					

5.2. Performance measures

The performance evaluation measures used in our experimental analysis are based on the confusion matrix (refer Table 2). Higher the value of performance metrics, the better the classifier is. The expressions for different performance measures as follows:

 $\begin{array}{l} \text{G-mean} = \sqrt{\text{Sensitivity} \times \text{Specificity}};\\ \text{AUC} = \frac{\text{Sensitivity} + \text{Specificity}}{2};\\ \text{F-measure} = 2\frac{\left(\text{PrecisionSensitivity}\right)}{\left(\text{Precision} + \text{Sensitivity}\right)};\\ \text{Accuracy} = \frac{(TP+TN)}{(TP+TN+FP+FN)};\\ \text{where, Precision} = \frac{TP}{TP+FP}; \text{Sensitivity} = \frac{TP}{TP+FN}; \text{Specificity} = \frac{TN}{FP+TN}. \end{array}$

5.3. Analysis of results

We aim to select the optimal set of features and the corresponding model for the selection of right set of students who will be fit for the MBA program of a business school and subsequently will be placed as well. Experimental evaluation is divided into two subparts:

- In the First stage, we compare our proposed integrated sampling approach with EnCT-ANN model (Methodology 1, refer to Section 4.1) with other sampling techniques applied on different classifiers. Different performance metrics are computed to draw the conclusion from the experimental results.
- In the next stage, we compare our proposed superensemble classifier (Methodology 2, refer to Section 4.2) with other similar types of imbalanced data oriented classifiers. Different performance metrics are computed to draw the conclusion from the experimental results.

All the methods were implemented in R Statistical package on a PC with 2.1 GHz processor and 8 GB memory.

5.3.1. Comparison with other data processing methods

As mentioned in Section 2.2., we first implemented SMOTE, SMOTE +ENN, SMOTE + TL on the imbalanced business school data set for balancing the data. As far as the recommendation of a few literatures [19], the value of the parameter for SMOTE implementation to be chosen as k = 5. Then we applied proposed integrated sampling technique, viz. SBT for data processing. In the first step, we applied TL on the original imbalanced business school data set to cut off the noise from the data set. It actually removes the border-line examples from both the class instances. After data cleaning is done, we applied SMOTE on the minority examples for oversampling and bootstrap on the majority examples for undersampling. Combining both the sampling techniques, we created a new balanced training data set which has equal class distribution. Further we implemented different supervised algorithms, such as CT, ANN, RF, EnCT-ANN, support vector machine (SVM), on the balanced data set. Results based on different algorithms are summarized in terms of performance metrics in Table 4. Values of different performance metrics, as mentioned in Section 5.2., are computed. It is clearly visible from Table 4 that our proposed Methodology 1 gives best performance across all the performance metrics. The important se of features that came out while applying EnCT-ANN model are as follows: SSC Percentage, HSC Percentage, Degree Percentage, Entrance Test Percentile, HSC Stream, Degree Stream. The conclusion of the experimental evaluation suggests SBT along with EnCT-ANN model gives higher accuracy over all other state-of-the-art methods.

5.3.2. Comparison with other imbalanced data oriented classifier

Due to the fact that the implementation of data pre-processing and sampling techniques in Section 5.3.1. changes the originality of the data set, so we require specially designed classifiers for imbalanced data sets. We started the experimentation with HDDT algorithm by using R Package 'CORElearn' for learning from imbalanced business school data set. HDDT achieved around 93% accuracy while CT based on IG achieved around 83% accuracy. This gives an indication that imbalanced based classifiers performs better than

Classifiers	Sampling Technique	AUC	F-measure	G-mean	Accuracy
	SMOTE	0.765	0.822	0.765	0.800
ANN	SMOTE+ENN	0.798	0.852	0.780	0.820
	SBT	0.803	0.876	0.798	0.833
	SMOTE	0.845	0.862	0.840	0.835
CT	SMOTE+ENN	0.850	0.870	0.842	0.849
	SBT	0.851	0.875	0.851	0.855
RF	SMOTE	0.859	0.870	0.869	0.845
	SMOTE+ENN	0.875	0.897	0.884	0.869
	SBT	0.928	0.922	0.925	0.904
SVM	SMOTE	0.720	0.765	0.713	0.710
	SMOTE+ENN	0.700	0.732	0.709	0.689
	SBT	0.714	0.768	0.714	0.714
	SMOTE	0.926	0.928	0.919	0.920
EnCT-ANN	SMOTE+ENN	0.939	0.942	0.925	0.928
	SBT	0.952	0.965	0.943	0.952

Table 4: Performance of classifiers using different sampling techniques

the usual supervised classifier designed for general purpose. Further we implemented HDRF, CCPDT which are among other imbalanced data oriented algorithms. Finally, we applied our proposed superensemble classifier which is a multi-step methodology. In the first stage, we select important features using HDDT and record it's classification outputs. Followings are the important features we obtained for business school data set by applying HDDT: SSC Percentage, HSC Percentage, Entrance Test Percentile, Degree Percentage and Work Experience. In the next step, we design a neural network with the above mentioned important features along with HDDT output as an additional feature vector. We reported the performance of different classifiers in terms of different performance metrics in Table 5. It is clear from Table 5 that our proposed Methodology 2, viz. superensemble classifier achieved an accuracy of over 96% for business school data set. It should also be noted that the prediction accuracy is better for Methodology 2 even when we compare with performance of classifiers on synthetic data set as reported in Table 4.

Different Classifiers	AUC	F-measure	G-mean	Accuracy
CT	0.810	0.822	0.815	0.833
ANN	0.768	0.781	0.758	0.771
HDCT	0.933	0.936	0.925	0.931
HDRF	0.939	0.941	0.932	0.938
CCPDT	0.912	0.918	0.902	0.915
Superensemble Classifier	0.964	0.969	0.951	0.964

Table 5: Quantitative measure of performance for different classifiers

6. Conclusion

It should be noted that allocating half of the training examples to the minority class doesn't provide optimal results in all the cases [20]. It is also important to note that "imbalanced data oriented" algorithms sometimes perform well on the original imbalanced data sets. Modifying the classifier and working with the original data sets are also addressed by this research. When computational cost is not a problem and minority data is somehow lost and artificial data generation for balancing the data is required Methodology 1 is preferred. The main motivation behind this methodology is not only to balance the training data, but also cleaning the data set before the study. However if we would like to work with the original data without taking recourse to sampling, our proposed methodology 2 will be quite handy. Methodology 2 proposed a superensemble classifier which takes into account data imbalance and used for feature selection cum classification problems. Through experimental evaluation we have shown our proposed methodology performed well as compared to other state-of-the-art models. We thereby conclude that for imbalanced business school data set it is sufficient to use superensemble classifier.

References

- T. Chakraborty, S. Chattopadhyay, and A. K. Chakraborty, "A novel hybridization of classification trees and artificial neural networks for selection of students in a business school," *OPSEARCH*, vol. 55, no. 2, pp. 434–446, 2018.
- [2] T. Chakraborty, A. K. Chakraborty, and C. Murthy, "A nonparametric

ensemble binary classifier and its statistical properties," *arXiv preprint* arXiv:1804.10928, 2018.

- [3] M. Rastgoo, G. Lemaitre, J. Massich, O. Morel, F. Marzani, R. Garcia, and F. Meriaudeau, "Tackling the problem of data imbalancing for melanoma classification," in *Bioimaging*, 2016.
- [4] H. Guo and H. L. Viktor, "Learning from imbalanced data sets with boosting and data generation: the databoost-im approach," ACM Sigkdd Explorations Newsletter, vol. 6, no. 1, pp. 30–39, 2004.
- [5] C. Chen, A. Liaw, and L. Breiman, "Using random forest to learn imbalanced data," University of California, Berkeley, vol. 110, pp. 1–12, 2004.
- [6] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "Smote: synthetic minority over-sampling technique," *Journal of artificial intelligence research*, vol. 16, pp. 321–357, 2002.
- [7] G. E. Batista, R. C. Prati, and M. C. Monard, "A study of the behavior of several methods for balancing machine learning training data," ACM SIGKDD explorations newsletter, vol. 6, no. 1, pp. 20–29, 2004.
- [8] G. Lemaître, F. Nogueira, and C. K. Aridas, "Imbalanced-learn: A python toolbox to tackle the curse of imbalanced datasets in machine learning," *Journal of Machine Learning Research*, vol. 18, no. 17, pp. 1–5, 2017.
- [9] D. A. Cieslak and N. V. Chawla, "Learning decision trees for unbalanced data," in *Joint European Conference on Machine Learning and Knowledge Discovery in Databases.* Springer, 2008, pp. 241–256.
- [10] D. A. Cieslak, T. R. Hoens, N. V. Chawla, and W. P. Kegelmeyer, "Hellinger distance decision trees are robust and skew-insensitive," *Data Mining and Knowledge Discovery*, vol. 24, no. 1, pp. 136–158, 2012.
- [11] C. Su, S. Ju, Y. Liu, and Z. Yu, "Improving random forest and rotation forest for highly imbalanced datasets," *Intelligent Data Analysis*, vol. 19, no. 6, pp. 1409–1432, 2015.

- [12] W. Liu, S. Chawla, D. A. Cieslak, and N. V. Chawla, "A robust decision tree algorithm for imbalanced data sets," in *Proceedings of the 2010 SIAM International Conference on Data Mining.* SIAM, 2010, pp. 766–777.
- [13] M. Kubat, S. Matwin *et al.*, "Addressing the curse of imbalanced training sets: one-sided selection," in *ICML*, vol. 97. Nashville, USA, 1997, pp. 179–186.
- [14] D. L. Wilson, "Asymptotic properties of nearest neighbor rules using edited data," *IEEE Transactions on Systems, Man, and Cybernetics*, no. 3, pp. 408–421, 1972.
- [15] C. R. Rao, "A review of canonical coordinates and an alternative to correspondence analysis using hellinger distance," *Qüestiió: quaderns* d'estadística i investigació operativa, vol. 19, no. 1, 1995.
- [16] P. A. Flach, "The geometry of roc space: understanding machine learning metrics through roc isometrics," in *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, 2003, pp. 194–201.
- [17] I. Tomek, "Two modifications of cnn," IEEE Trans. Systems, Man and Cybernetics, vol. 6, pp. 769–772, 1976.
- [18] B. Efron, "Bootstrap methods: another look at the jackknife," in Breakthroughs in statistics. Springer, 1992, pp. 569–593.
- [19] S. García, A. Fernández, and F. Herrera, "Enhancing the effectiveness and interpretability of decision tree and rule induction classifiers with evolutionary training set selection over imbalanced problems," *Applied Soft Computing*, vol. 9, no. 4, pp. 1304–1314, 2009.
- [20] G. M. Weiss and F. Provost, "Learning when training data are costly: The effect of class distribution on tree induction," *Journal of artificial intelligence research*, vol. 19, pp. 315–354, 2003.