Fast approximate inference for variable selection in Dirichlet process mixtures, with an application to pan-cancer proteomics

Oliver M. Crook^{1,2,3}, Laurent Gatto⁴ and Paul D. W. Kirk³

¹Department of Applied Mathematics and Theoretical Physics, University of Cambridge, U.K.

²Cambridge Centre for Proteomics, Department of Biochemistry, University of Cambridge, U.K.

³MRC Biostatistics Unit, School of Clinical Medicine, University of Cambridge, U.K.

⁴de Duve Institute, UCLouvain, Belgium

Preprint, October 15, 2018

Abstract. The Dirichlet Process (DP) mixture model has become a popular choice for model-based clustering, largely because it allows the number of clusters to be inferred. The sequential updating and greedy search (SUGS) algorithm (Wang and Dunson, 2011) was proposed as a fast method for performing approximate Bayesian inference in DP mixture models, by posing clustering as a Bayesian model selection (BMS) problem and avoiding the use of computationally costly Markov chain Monte Carlo methods. Here we consider how this approach may be extended to permit variable selection for clustering, and also demonstrate the benefits of Bayesian model averaging (BMA) in place of BMS. Through an array of simulation examples and well-studied examples from cancer transcriptomics, we show that our method performs competitively with the current state-of-the-art, while also offering computational benefits. We apply our approach to reverse-phase protein array (RPPA) data from The Cancer Genome Atlas (TCGA) in order to perform a pan-cancer proteomic characterisation of 5,157 tumour samples. We have implemented our approach, together with the original SUGS algorithm, in an open-source R package named sugsvarsel, which accelerates analysis by performing intensive computations in C++ and provides automated parallel processing. The R package is freely available from: https://github.com/occcrook/sugsvarsel

1 Introduction

Bayesian nonparametric methods have become commonplace in the statistics and machine learning literature due to their flexibility and wide applicability. For model-based clustering, Dirichlet process (Ferguson, 1973, 1974) mixture models have become particularly popular (Antoniak, 1974, Blei et al., 2006, Escobar, 1994, Escobar and West, 1995, Lo, 1984), partly because they allow the number of clusters supported by the data to be inferred. By introducing latent selection indicators, these models can be extended to perform variable selection for clustering (Kim et al., 2006), which is particularly relevant in highdimensional settings (Constantinopoulos et al., 2006, Law et al., 2004). There are now several approaches for model-based clustering and variable selection (see Fop and Murphy, 2017, for a recent review), but current Markov chain Monte Carlo (MCMC) algorithms for Bayesian inference in Dirichlet process (DP) mixture models (e.g. Jain and Neal, 2004, Neal, 2000) are computationally costly, and often infeasible for large datasets. Algorithms for fast approximate inference in DP mixture models, such as the use of fast search algorithms (Daume III, 2007), Bayesian hierarchical clustering (Cooke et al., 2011, Darkins et al., 2013, Heller and Ghahramani, 2005, Savage et al., 2009), or the sequential updating and greedy search (SUGS) algorithm (Wang and Dunson, 2011, Zhang et al., 2014), make possible the analysis of datasets with large numbers of observations. However, without variable selection such algorithms may be ill-suited to the high-dimensional setting. In the spirit of the original SUGS algorithm, here we pose clustering and variable selection as a Bayesian model selection (BMS) problem. We consider variable selection for clustering in terms of partitioning variables into those which are relevant and those which are irrelevant for defining the clustering structure, and thereby pose the problem as one of using BMS to select both a partition of the variables and a partition of the observations. We moreover consider the benefits of performing Bayesian model averaging (BMA) (Hoeting et al., 1999, Madigan and Raftery, 1994) for summarising the SUGS output. For ease of exposition, we focus on the case of DP Gaussian mixtures, but note that all of our methods extend straightforwardly to other distributions for which conjugate priors may be chosen.

We consider a range of simulation settings and well-studied examples from cancer transcriptomics to show that our methods perform competitively with the current state-of-the-art. Having established the utility of our approach, we consider an application to reverse-phase protein arrays (RPPA) datasets in order to characterise the pan-cancer functional proteome. Such datasets have the potential to provide a deeper understanding of the biomolecular processes at work in cancer cells, and have previously been shown to offer additional insights beyond what may be captured by genomics or transcriptomics datasets (Akbani et al., 2014). Here we consider RPPA data for 5,157 tumour samples obtained from The Cancer Genome Atlas (TCGA).

Section 2 recaps DP mixture models and the SUGS algorithm, then describes our extensions to SUGS including variable selection and BMA. Section 3 evaluates our method on simulated datasets and compares it with other approaches to clustering and variable selection. We then apply our method to a large proteomics dataset, highlighting its applicability. In the final section, we make some concluding remarks and discuss limitations and extensions. Our methods are implemented in an R package: https://github.com/ococrook/sugsvarsel.

2 Methods

2.1 Dirichlet process mixtures

We provide a very brief recap of DP mixture models, mainly to introduce notation, and refer to the overview provided in Section 3 of Teh et al. (2006) for further details. Let $G \sim DP(\beta P_0)$ where $\beta > 0$ is the DP concentration parameter, P_0 is the base probability measure, and G is a random probability measure. We consider a Pólya urn scheme in which we have independent and identically distributed (i.i.d.) random variables $\theta_1, \theta_2, ...$ distributed according to G. Computing the sequential conditional distributions of θ_i given $\theta_1, ..., \theta_{i-1}$, upon marginalising out the random G, we obtain (Blackwell and MacQueen, 1973):

$$\theta_i | \theta_1, ..., \theta_{i-1} \sim \frac{\beta}{\beta + i - 1} P_0 + \frac{1}{\beta + i - 1} \sum_{l=1}^{i-1} \delta_{\theta_l}, \ i = 1, ..., n,$$
(1)

where δ_{θ} is a probability measure with mass concentrated at θ . It is clear from this equation that for any r = 1, 2, ..., i-1, the probability that θ_i is equal to θ_r is given by $\sum_{l=1}^{i-1} \mathbb{I}(\theta_l = \theta_r)/(\beta + i - 1)$, where $\mathbb{I}(X) = 1$ if X is true and $\mathbb{I}(X) = 0$ otherwise. Thus θ_i has non-zero probability to be equal to one of the previous draws, and it is this clustering property that makes the DP a suitable prior for mixture models.

The DP mixture model is obtained by introducing an additional parametric probability distribution,

F. More precisely, let observations x_i be modelled according to the following hierarchical model:

$$G \sim DP(\beta P_0),$$

$$\theta_i | G \sim G,$$

$$x_i | \theta_i \sim F(\theta_i),$$

(2)

where F denotes the conditional distribution of the observation x_i given θ_i . For example, when F is chosen to be a Gaussian distribution we arrive at the DP Gaussian mixture model (also referred to as the infinite Gaussian mixture model; Rasmussen, 2000).

When performing inference for such models, it is common to introduce a set of latent variables (cluster labels) $z_1, ..., z_n$ associated with the observations, such that z_i is the cluster label for observation x_i . From the above specification of the DP mixture model, it follows that the conditional prior distribution of z_i given $z_{-i} = (z_1, ..., z_{i-1})$ is categorical with:

$$\pi_{ik} := P(z_i = k | z_{-i}, \beta) = \begin{cases} \frac{n_k}{\beta + i - 1}, & \text{for } k = 1, ..., K - 1\\ \frac{\beta}{\beta + i - 1}, & \text{for } k = K, \end{cases}$$
(3)

where $\beta > 0$ is the DP concentration parameter, $n_k := \sum_{l=1}^{i-1} \mathbb{I}(z_l = k)$ is the number of previous observations allocated to cluster k, and $K = \max\{z_{-i}\} + 1$. Larger values of β encourage observations to be allocated to new clusters, hence β plays a role in controlling the number of clusters.

Inference for DP mixture models can performed using computationally intensive MCMC methods (Jain and Neal, 2004, Neal, 2000). However, as we discuss, here we are interested in the SUGS algorithm for approximate inference, proposed by Wang and Dunson (2011).

2.2 Sequential Updating and Greedy Search (SUGS)

SUGS is a sequential approach for allocating observations to clusters, which (greedily) allocates the *i*-th observation to a cluster, given the allocations of the previous i-1 observations. Suppose that observations $x_{-i} = (x_1, ..., x_{i-1})$ have previously been allocated to clusters. As described in Wang and Dunson (2011), the posterior probability of allocating observation *i* to cluster *k* according to the DP mixture model formulation above is given by:

$$P(z_i = k | x_i, x_{-i}, z_{-i}, \beta) = \frac{\pi_{ik} L_{ik}(x_i)}{\sum_{l=1}^{K} \pi_{ik} L_{il}(x_i)},$$
(4)

where π_{ik} is defined as in Equation (3), and

$$L_{ik} = \int f(x_i|\theta_k) p(\theta_k|x_{-i}, z_{-i}) \, d\theta_k \tag{5}$$

is the conditional marginal likelihood associated with x_i given allocation to cluster k and the cluster allocations for observations 1, ..., i - 1, with $f(x_i|\theta_k)$ denoting the likelihood associated with x_i as a function of θ_k . If k is a cluster to which previous observations have already been allocated, then $p(\theta_k|x_{-i}, z_{-i})$ is the posterior distribution of θ_k given the observations previously allocated to cluster k; i.e. $p(\theta_k|x_{-i}, z_{-i}) \propto p_0(\theta_k) \prod_{j:z_j=k, 1 \le j \le i-1} f(x_j|\theta_k)$, where $p_0(\theta_k)$ is the prior on the cluster-specific parameters, θ_k . For a new cluster, i.e. for k = K, we have $p(\theta_k|x_{-i}, z_{-i}) = p_0(\theta_k)$. If p_0 is taken to be conjugate for the likelihood f, then the posterior and conditional marginal likelihood are available analytically.

Assuming that the concentration parameter β is given and that conjugate priors are taken, the above suggests a computationally efficient deterministic clustering algorithm (the SUGS algorithm). That is, z_1 is initialised as $z_1 = 1$, and then subsequent observations are sequentially allocated to clusters by setting $z_i = \arg \max_{k \in \{1,...,K\}} P(z_i = k | x_i, x_{-i}, z_{-i}, \beta)$, where we recall that $K = \max\{z_{-i}\} + 1$ may change after each sequential allocation.

2.2.1 Dealing with unknown β

The DP concentration parameter β directly influences the number of clusters, thus we treat this as a random variable to be inferred, in the same way as in Wang and Dunson (2011). In particular, let $\hat{\beta} = (\hat{\beta}_1, ..., \hat{\beta}_L)$ be a discrete grid of permissible values for β with a large range, and then define the prior for β to be discrete with the following form:

$$p_0(\beta|\kappa_1,\ldots,\kappa_L) = \sum_{l=1}^L \kappa_l \mathbb{I}(\beta = \hat{\beta}_l), \tag{6}$$

where $\kappa_l = p(\beta = \hat{\beta}_l)$. Further defining $\phi_l^{(i-1)} = p(\beta = \hat{\beta}_l | x_{-i}, z_{-i})$ and $\pi_{ikl} = p(z_i = k | \beta = \hat{\beta}_l, z_{-i})$, the β parameter may be marginalised in Equation (4) to obtain:

$$p(z_i = k | x_{-i}, x_i, z_{-i}) = \frac{\sum_{l=1}^{L} \phi_l^{(i-1)} \pi_{ikl} L_{ik}(x_i)}{\sum_{l=1}^{L} \phi_l^{(i-1)} \sum_{k=1}^{K} \pi_{ikl} L_{ik}(x_i)},$$
(7)

where $\pi_{ikl} := p(z_i = k | \beta = \hat{\beta}_l, z_{-i})$ is given by Equation (3); $\phi_l^{(0)} = \kappa_l$; and:

$$\phi_l^{(i)} = p(\beta = \hat{\beta}_l | x_{-i}, x_i, z_{-i}, z_i) = \frac{\phi_l^{(i-1)} \pi_{iz_i l}}{\sum_{s=1}^L \phi_s^{(i-1)} \pi_{iz_i s}}$$
(8)

may be calculated sequentially for i = 1, ..., n. The SUGS algorithm for allocating observations to clusters when β is unknown is then as presented in Algorithm 1.

Algorithm 1: The SUGS algorithm, when the DP precision parameter β is allowed to be unknown.

Input : Data $X = \{x_i\}_{i=1}^n$, Prior $p_0(\theta)$, Hyperparameters $\{\kappa_l\}_{l=1}^L$ **Output :** Cluster allocations $Z = \{z_i\}_{i=1}^n$ 1 Initialise $z_1 = 1$, K = 2, and $\{\phi_l^{(0)} = \kappa_l\}_{l=1}^L$; **2** Evaluate $p(\theta_1|z_1, x_1) \propto p_0(\theta_1) f(x_1|\theta_1);$ ${\bf 3}$ Calculate $\{\phi_l^{(1)}\}_{l=1}^L,$ according to Eq. (8); 4 for i = 2 to N do 5 for k = 1 to K do Calculate L_{ik} according to Eq. (5); 6 Evaluate $p(z_i = k | x_1, \dots, x_i, z_1, \dots, z_{i-1})$ according to Eq. (7); 7 8 end Set $z_i = \arg \max_{k=1,...,K} (p(z_i = k | x_1, ..., x_i, z_1, ..., z_{i-1}));$ 9 Set $K = \max\{z_1, ..., z_i\} + 1;$ 10 for l = 1 to L do $\mathbf{11}$ Calculate $\phi_I^{(i)}$, according to Eq. (8); 12 end $\mathbf{13}$ Evaluate $p(\theta_{z_i}|x_1,\ldots,x_i,z_1,\ldots,z_i) \propto p_0(\theta_{z_i}) \prod_{j:z_i=z_i,1\leq j\leq i} f(x_j|\theta_{z_i});$ $\mathbf{14}$ 15 end

2.2.2 Formulation of Bayesian Model Selection problem

A notable limitation of the (deterministic) SUGS algorithm as presented so far is that the clustering structure obtained is dependent upon the initial ordering of the observations. To remove this dependence, Wang and Dunson (2011) consider multiple permutations of this ordering, and pose SUGS as a Bayesian

model selection (BMS) problem. More concretely, the algorithm is repeated for many random orderings of the data and a final partition of the observations is then chosen by optimising an appropriate objective function for BMS, such as the marginal likelihood (ML):

$$L(X|Z) = \prod_{k=1}^{K} \int_{\theta_k} \left[\prod_{i:z_i=k} f(x_i|\theta_k) \right] p_0(\theta_k) d\theta_k.$$
(9)

In practice, Wang and Dunson (2011) advocate optimising the *pseudo*-marginal likelihood (PML), since they found that the marginal likelihood to often produce many small clusters. The PML is given by:

$$PML_{z}(X) = \prod_{i=1}^{N} p(x_{i}|X_{n\setminus -i}, z_{n\setminus -i})$$

$$= \prod_{i=1}^{N} \int_{\theta} p(x_{i}|\theta) p(\theta|X_{n\setminus -i}, z_{n\setminus -i}) d\theta$$

$$= \prod_{i=1}^{N} \sum_{k=1}^{K} P(z_{i} = k|X_{n\setminus -i}, z_{n\setminus -i}) \int_{\theta_{k}} f(x_{i}|\theta_{k}) p(\theta_{k}|X_{n\setminus -i}, z_{n\setminus -i}) d\theta_{k},$$

(10)

where, defining $X = \{x_1, ..., x_n\}$ and $Z = \{z_1, ..., z_n\}$, we have $X_{n \setminus -i} = X \setminus \{x_i\}$ is the set of all observations except the i^{th} , and similarly $z_{n \setminus -i} = Z \setminus \{z_i\}$. In addition, Wang and Dunson (2011) remark that that $p(x_i|X, Z)$ can be used to approximate $p(x_i|X_{n \setminus -i}, z_{n \setminus -i})$ to speed up computations and that this approximation is accurate for large sample sizes.

2.3 SUGS for variable selection

Irrelevant variables in high-dimensions can present a considerable challenge for clustering models and algorithms, because the number of variables with no clustering structure can overwhelm those where a clustering structure exists (Witten and Tibshirani, 2010). There have been many approaches to model-based clustering and variable selection (e.g. Maugis et al., 2009, Raftery and Dean, 2006), and we direct readers to Fop and Murphy (2017) for a recent review. However, many of these scale poorly with increasing dataset dimension, and/or require the number of clusters to be determined as a separate analysis step. To address these challenges, here we extend the SUGS algorithm to simultaneously perform clustering and variable selection, and refer to the resulting procedure as *SUGSVarSel*.

Since we are in the high-dimensional setting, we assume for simplicity that variables are independent given the cluster allocations (which, in the Gaussian case, is equivalent to assuming a diagonal structure for the covariance matrix). Let $x_{i,d}$ be the d^{th} element of the i^{th} observation vector, with $d = 1, \ldots, D$, and D the number of variables. Introducing indicator variables γ_d , which is 1 if the d^{th} variable is relevant for the clustering structure and 0 if not, we follow a common approach from the literature (Kim et al., 2006, Law et al., 2004, Tadesse et al., 2005) and assume that the cluster conditional likelihood can be factorised as follows:

$$f(x_i|\theta,\theta_0,z_i=k) = \prod_{d=1}^{D} f(x_{i,d}|\theta_{k,d})^{\mathbb{I}(\gamma_d=1)} f(x_{i,d}|\theta_{0,d})^{\mathbb{I}(\gamma_d=0)},$$
(11)

where θ_0 are "global" (i.e. not cluster-specific) parameters. In other words, the variables for which $\gamma_d = 1$ are modelled by a mixture distribution with cluster-specific parameters $\theta_{k,d}$, while the variables for which $\gamma_d = 0$ are modelled by a single component with (global, not cluster-specific) parameters $\theta_{0,d}$. Having introduced the D indicator variables γ_d , we now extend the SUGS algorithm in order to estimate them.

2.3.1 The SUGSVarSel algorithm

Given a realisation of the indicator variables, $\Gamma = \{\gamma_1, \ldots, \gamma_D\}$, we may plug the cluster conditional likelihood given in Equation (11) into Equation (5) and proceed as before in order to identify a clustering, Z.

Conversely, suppose we have a realisation, Z, of the set of component allocation variables, but that the indicator variables Γ are unknown. In this case, the posterior probabilities associated with the variable indicators are given by:

$$P(\gamma_d = 1|X, Z) = \frac{p_0(\gamma_d = 1)}{B} \prod_{k \in Z} \int_{\theta_{k,d}} \left(\prod_{i:z_i = k} f(x_{i,d}|\theta_{k,d}) \right) p_0(\theta_{k,d}) d\theta_{k,d}$$
(12)

$$P(\gamma_d = 0|X, Z) = \frac{p_0(\gamma_d = 0)}{B} \int_{\theta_{0,d}} \left(\prod_{i:z_i = k} f(X_d | \theta_{0,d}) \right) p_0(\theta_{0,d}) d\theta_{0,d},$$
(13)

where $p_0(\gamma_d = q)$ indicates the prior probability that $\gamma_d = q$, and B is a normalising constant that ensures that $p(\gamma_d = 0|X, Z)$ and $p(\gamma_d = 1|X, Z)$ sum to 1. Thus, given a realisation, Z, of the set of component allocation variables, a greedy approach to finding γ_d is to set $\gamma_d = \arg \max_{q \in \{0,1\}} P(\gamma_d = q|X, Z)$.

Given an initial realisation of the indicator variables, $\Gamma = \Gamma^{(0)}$, the above suggests an iterative strategy in which at each iteration we use the SUGS algorithm to find a partition $Z^{(t)}$ given $\Gamma^{(t-1)}$, and then greedily update the indicator variables according to Equations (12) and (13) above in order to obtain $\Gamma^{(t)}$ given $Z^{(t)}$. This algorithm, which we refer to as SUGSVarSel, is presented in Algorithm 2. Algorithm 2: The SUGSVarSel algorithm

: Data $X = \{x_i\}_{i=1}^n$, Priors $p_0(\theta)$ and $p_0(\gamma)$, Input Hyperparameters $\{\kappa_l\}_{l=1}^L$, Initial Indicator Switches $\Gamma^{(0)}$, Maximum Iterations T. **Output :** Cluster allocation $Z = \{z_i\}_{i=1}^n$ Variable switches $\Gamma = \{\gamma_d\}_{d=1}^{D}$ 1 Initialise $z_1 = 1$, K = 2, and $\{\phi_l^{(0)} = \kappa_l\}_{l=1}^L$; **2** Evaluate $p(\theta_1|z_1, x_1) \propto p_0(\theta_1) f(x_1|\theta_1)$; **3** Calculate $\{\phi_l^{(1)}\}_{l=1}^L$, according to Eq. (8); 4 while $t \leq T$ do for i = 2 to N do 5 for k = 1 to K do 6 Calculate L_{ik} given $\Gamma^{(t-1)}$, according to Eqs. (5) and (11); 7 Evaluate $p(z_i = k | x_1, \dots, x_i, z_1, \dots, z_{i-1})$ according to Eq. (7); 8 9 end Set $z_i = \arg \max_{k=1,...,K} (p(z_i = k | x_1, ..., x_i, z_1, ..., z_{i-1}));$ 10 Set $K = \max\{z_1, ..., z_i\} + 1;$ 11 for l = 1 to L do 12Calculate $\phi_{I}^{(i)}$, according to Eq. (8); $\mathbf{13}$ end $\mathbf{14}$ Evaluate, using the cluster conditional likelihood in Eq. (11), 15 $p(\theta_{z_i}|x_1,...,x_i,z_1,...,z_i) \propto p_0(\theta_{z_i}) \prod_{i:z_i=z_i,1 \le i \le i} f(x_i|\theta_{z_i});$ 16 end for d = 1 to D do $\mathbf{17}$ Calculate $p(\gamma_d = r | X, Z)$, according to Eqs. (12) and (13); $\mathbf{18}$ Set $\gamma_d = \arg \max_{r \in \{0,1\}} (p(\gamma_d = r | X, Z));$ 19 end $\mathbf{20}$ $t \leftarrow t + 1$ $\mathbf{21}$ 22 end

2.3.2 Initialisation strategies for SUGSVarSel

Like the SUGS algorithm, the output of SUGSVarSel depends upon the initial ordering of the observations. It moreover depends upon the initialisation of the variable selection switches, $\Gamma^{(0)}$. To address this latter issue, we propose a random sub-sampling initialisation strategy. This is as follows: first randomly select p_1 variables (with $1 < p_1 \le D$) and apply SUGSVarSel on this new dataset X of size $n \times p_1$ with a small number of random orderings of the observations (we find 10 works in practice). The initial indicator for the variables of \tilde{X} , which we write as $\tilde{\Gamma}^{(0)}$, are set as all-on ($\gamma_d = 1$ for these p_1 variables). $\tilde{\Gamma}^{(0)}$ is held the same for each of the random orderings. For each of the random orderings, this approach outputs \tilde{Z} for all observations but $\tilde{\Gamma}$ for only a subset of size p_1 of the variables. To obtain Γ for all D variables, we use the cluster allocations \tilde{Z} and the full data X to compute probabilities for the remaining variables using equations 12 and 13. We then greedily assign the indicator variables. A single best model generated by these random orderings is selected using the ML. This procedure returns a $\Gamma_1 \in \{0,1\}^D$; that is, variable selection switches with some variables switched on and other variables switched off. We repeat this process for a total of M random sub-samples of the variables to produce a set of clusterings $Z_1, ..., Z_M$ and a set of variables $\Gamma_1, ..., \Gamma_M$. These variable sets are then used as initial inputs $\Gamma^{(0)} = \Gamma_i$ for i = 1, ..., M for the SUGSVarSel algorithm (which is now run using all variables p = D) with Q new random orderings (again we find 10 is sufficient in practice). This SUGSVarSel with sub-sampling initialisation strategy returns Qmodels for each random sub-sample of the variables. Thus, we have QM models from which to choose. For each model obtained in this way, we calculate the marginal likelihood (see Section 2.2.2). We can then perform BMS to obtain a single "best" model, or we can use Bayesian model averaging (BMA; see next section).

2.4 Bayesian Model-Averaged Co-clustering Matrices

2.4.1 Bayesian model averaging

The output of our algorithm is a set of clusterings, associated variables and a marginal likelihood. One can select a single "best" model amongst these possible clustering, however we can also average over these models to capture the model uncertainty. The idea is called Bayesian model averaging (BMA) and we apply the method to clustering and variable selection (Hoeting et al., 1999, Madigan and Raftery, 1994, Russell et al., 2015).

For each model we form a co-clustering matrix S. S is defined in the following way:

$$S_{ij} = \begin{cases} 0, & \text{if } z_i \neq z_j \\ 1, & \text{if } z_i = z_j. \end{cases}$$
(14)

That is the ij^{th} entry of S is 1 if observation x_i and x_j are in the same cluster and 0 otherwise. We note that the S is invariant to relabelling and the number of clusters. Now, suppose we have M models $\mathcal{M}_1, ..., \mathcal{M}_M$, letting X be our observations and θ_m be the parameters associated with model \mathcal{M}_m . The posterior probability for \mathcal{M}_m is given by

$$p(\mathcal{M}_m|X) = \frac{p(X|\mathcal{M}_m)p_0(\mathcal{M})}{\sum_{l=1}^M p(X|\mathcal{M}_l)p_0(\mathcal{M}_l)},\tag{15}$$

where

$$P(X|\mathcal{M}_m) = \int P(X|\theta_m, \mathcal{M}_m) P(\theta_m|\mathcal{M}_m) \, d\theta_m.$$
(16)

The marginal likelihood (16) is the key quantity for model comparison and can be interpreted as the weight given to each proposed model. Further note the two sources of averaging: the averaging over the parameters in the ML and the averaging over the models in equation (15). We suppose that a priori all models are equally likely, choosing the prior on each model to be $p_0(\mathcal{M}_m) = 1/\mathcal{M}$. One computational challenge that (15) gives us is computing the summation, since it can involve evaluating possibly thousands of models. To overcome this, one can discount models that are poor at describing our observations comparatively to our best model. More precisely, let us form Occam's window (Hoeting et al., 1999):

$$\mathcal{W} = \left\{ M_k : \frac{\max_l(p(M_l|X))}{p(M_k|D)} \le K \right\},\tag{17}$$

where K is a tuning parameter. Occam's window is the set of all possible models within a reasonable Bayes factor from the best model under consideration. The summation in (15) is then replaced with a summation over the set \mathcal{W} .

2.4.2 Averaging the co-clustering matrices

We can form the Bayesian model-averaged co-clustering matrix (BMAC) by taking the set of co-clustering matrices S_W and averaging, weighting by their ML:

$$S_{BMAC} = \frac{p(X|\mathcal{M}_m)S_m}{\sum_{l \in \mathcal{W}} p(X|\mathcal{M}_l)}.$$
(18)

The BMA of the variable set can be found in the same way by averaging over the weighted variable sets for each model:

$$\mathcal{F}_{BMA} = \frac{p(X|\mathcal{M}_m)\mathcal{F}_m}{\sum_{l \in \mathcal{W}} p(X|\mathcal{M}_l)},\tag{19}$$

where we denote by \mathcal{F}_m the variable set associated with model \mathcal{M}_m .

3 Comparisons with the state-of-the-art

We compare SUGSVarSel to a number of alternative algorithms, and demonstrate the performance of our method in two situations. The first is the p > n paradigm, where the number of variables exceeds the number of observations. The second situation considers n > p for n = 1000, while simultaneously considering different proportions of variables being relevant. In both cases, we consider a variety of scenarios, for which different proportions of the variables are relevant.

3.1 Alternative methods for clustering and variable selection

We compare our method relative to the current state-of-the-art, including methods that do and do not peform variable selection. These include: mclust, a finite mixture model based clustering method (Fraley and Raftery, 2002, Fraley et al., 2012, Scrucca et al., 2016); clustvarsel, a finite mixture model method with variable selection (Maugis et al., 2009, Raftery and Dean, 2006, Scrucca and Raftery, 2014); the original sequential updating and greedy search algorithm (Wang and Dunson, 2011) as implemented in our sugsvarsel R package; and VarSelLCM, a model-based clustering and variable selection approach using the integrated complete-data likelihood (Marbac and Sedki, 2017).

3.2 High-dimensional example

In the first example, we simulate a mixture of 3 Gaussians with mixture proportions 0.5, 0.3, 0.2 centred at (0, 0, ..., 0), (2, 2, ..., 2), (-2, -2, ..., -2) respectively, each with variance-covariance matrix equal to the identity. The irrelevant variables are simulated from a standard Gaussian. First, we simulate 100 observations from this model with 200 variables and explore varying the number of relevant variables.

When running SUGS and SUGSVarSel we use the same prior specification for both methods and 30 random orderings of the data. Throughout this article, we always perform 2 iterations of variable selection in the SUGSVarSel algorithm. To initialise variable selection in SUGSVarSel, we subsample 10% of the variables 20 times to produce an initial variable selection set. For SUGS we choose the partition with maximal PML (as advised in the original SUGS paper by Wang and Dunson 2011), while for SUGSVarSel we select the result with maximal ML. Prior choices for SUGS and SUGSVarSel can be found in the appendix. For mclust and clustvarsel, we find the appropriate number of clusters using a sequential search up to a maximum of 9 possible clusters. We then use then Bayesian Information Criterion (BIC) to select an appropriate model (Schwarz, 1978). For VarSelLCM we run the algorithm up to a maximum of 9 possible clusters and select an appropriate model using the Maximum Integrated Complete-data Likelihood (MICL) (Marbac and Sedki, 2017, 2018). All methods are run in serial for fair comparison.

Results are presented in Tables 1 - 4. In all tables, we provide runtimes for each of the methods, indicate the proportion of relevant and irrelevant variables that each method correctly identified (for methods without variable selection this is reported as 1 for relevant and 0 for irrelevant variables), and report the adjusted Rand index (Hubert and Arabie, 1985, Rand, 1971) between the clustering produced and the truth. We repeat all methods for 10 different random realisation of the datasets to produce a distribution of scores. We report the median scores, along with the upper and lower quartiles.

Table 1. High-dimensional simulation example where 100 observations are simulated from a Gaussian mixture distribution with 3 components and 200 variables, in which 50% of variables are relevant.

Method	Time (secs)	Correct relevant variables	Correct irrelevant variables	ARI
mclust	< 1	1	0	$1 \ [1, 1]$
clustvarsel	6780	0.45	1	1
SUGS	$0.92 \ [0.90, \ 0.97]$	1	0	0.955[0.90,0.97]
SUGSVarSel	24.6 [23.8, 24.9]	1 [1, 1]	1 [1, 1]	$1 \ [1, 1]$
VarSelLCM	580.7 [574.8, 587.9]	$1 \ [1, 1]$	$1 \ [1, 1]$	1 [1, 1]

Table 2. High-dimensional simulation example where 100 observations are simulated from a Gaussian mixture distribution with 3 components and 200 variables, in which 25% of variables are relevant.

Method	Time $(secs)$	Correct Correct		ARI
		relevant	irrelevant	
		variables	variables	
mclust	< 1	1	0	$1 \ [1, \ 1]$
clustvarsel	3825.52	0.02	0.673	0
SUGS	$2.07 \ [1.89, \ 2.16]$	1	0	$0.78 \ [0.72, \ 0.84]$
SUGSVarSel	$21.9 \ [21.9, \ 22.1]$	$1 \ [1, \ 1]$	$1 \ [1, 1]$	$1 \ [1, 1]$
VarSelLCM	$508.0 \ [496.3, \ 517.0]$	$1 \ [1, 1]$	$1 \ [1, 1]$	$1 \ [1, 1]$

Table 3. High-dimensional simulation example where 100 observations are simulated from a Gaussian mixture distribution with 3 components and 200 variables, in which 10% of variables are relevant.

Method	Time $(secs)$	Correct	Correct	ARI
		relevant	irrelevant	
		variables	variables	
mclust	< 1	1	0	$0 \ [0, \ 0]$
clustvarsel	6459.88	0.1	0.772	0
SUGS	$5.02 \ [4.76, \ 5.23]$	1	0	$0.18\ [0.13,\ 0.21]$
SUGSVarSel	$19.7 \ [19.5, \ 19.9]$	1 [1, 1]	$1 \ [1, 1]$	1 [1, 1]
VarSelLCM	523.3 [521.3, 527.7]	1 [1, 1]	$1 \ [1, 1]$	$1 \ [1, 1]$

Table 4. High-dimensional simulation example where 100 observations are simulated from a Gaussian mixture distribution with 3 components and 200 variables, in which 5% of variables are relevant.

Method	Time $(secs)$	Correct	Correct	ARI
		relevant	irrelevant	
		variables	variables	
mclust	< 1	1	0	$0 \ [0, \ 0]$
clustvarsel	178.66	0.1	0.01	0
SUGS	$6.30 \ [6.07, \ 10.11]$	1	0	$0.04 \ [0.02, \ 0.05]$
SUGSVarSel	$19.9\ [19.7,\ 20.5]$	1 [1, 1]	$1 \ [1, \ 1]$	$1 \ [1, \ 1]$
VarSelLCM	996.8 [959.7, 1084.3]	$1 \ [1, 1]$	$1 \ [1, 1]$	$1 \ [1, 1]$

It is evident that methods that do not perform variable selection such as mclust and SUGS perform poorly when there are many irrelevant variables. The performance of clustvarsel here seems volatile and performs poorly at correctly selecting relevant features. VarSelLCM and SUGSVarSel are competitive in terms variable selection and clustering. However, VarSelLCM requires an exhaustive search over the number of clusters, which makes this method computationally costly to apply when the number of clusters is not known. SUGSVarSel outperforms all variable selection and clustering methods in terms of speed, while also automatically inferring the number of clusters in the data. We proceed to evaluate the performance of SUGSVarSel on large simulated datasets.

3.2.1 Increasing the number of observations

We simulate the same distribution as before, but instead sample 1000 observations and only 100 variables and the irrelevant variable are simulated from a standard Gaussian distribution. All priors are the same as in the previous analysis and we sub-sample 10% of the variables 10 times to produce an initial variable selection set. We repeat SUGS and SUGSVarSel for 10 random orderings of the data. We compare the scalable methods mclust, SUGS, SUGSVarSel and VarSelLCM, where 25%, 10%, 5% of the variable are relevant. For SUGS we choose the partition with maximal PML, while for SUGSVarSel we select the result with maximal ML. For VarSelLCM we run the algorithm for possible number of clusters 1 through 4 and select an appropriate model using the MICL, as previously. Results are presented in Tables 5–7.

Table 5. Simulation example where 1000 observations are simulated from a Gaussian mixture distribution with 3 components and 100 variables, in which 25% of variables are relevant.

Method	Time (secs)	Correct	Correct	ARI
		relevant	irrelevant	
		variables	variables	
mclust	11.2 [10.9, 11.6]	1	0	$0 \ [0, \ 0]$
SUGS	3.4 [3.1, 3.6]	1	0	$0.98 \ [0.97, \ 0.98]$
SUGSVarSel	$31.2 \ [30.7, \ 31.8]$	1 [1, 1]	$1 \ [1, \ 1]$	$1 \ [1, 1]$
VarSelLCM	$3596.8 \ [2639.5, \ 7537.7]$	1 [1, 1]	1 [1, 1]	$1 \ [1, 1]$

Table 6. Simulation example where 1000 observations are simulated from a Gaussian mixture distribution with 3 components and 100 variables, in which 10% of variables are relevant.

Method	Time (secs)	Correct relevant variables	Correct irrelevant variables	ARI
mclust	11.0 [10.7, 11.4]	1	0	0 [0, 0]
SUGS	$5.1 \ [4.9, \ 5.3]$	1	0	$0.01 \ [0.01, \ 0.04]$
SUGSVarSel	$33.3 \ [33.0, \ 33.8]$	1 [1, 1]	1 [1, 1]	$0.90 \ [0.80, \ 0.97]$
VarSelLCM	$1938.5 \ [1852.3, \ 1973.9]$	1 [1, 1]	1 [1, 1]	$0.997 \ [0.994 \ 0.997]$

Method	Time (secs)	Correct	Correct	ARI
	· · · ·	relevant	irrelevant	
		variables	variables	
mclust	11.4 [11.2, 15.7]	1	0	$0 \ [0, 0]$
SUGS	$6.3 \ [5.6, \ 11.1]$	1	0	$0 \ [0, \ 0]$
SUGSVarSel	60.8 [59.8, 64.2]	1 [1, 1]	$1 \ [0.99, 1]$	$0.78 \ [0.54, \ 0.92]$
VarSelLCM	2688.8 [2588.9, 2878.6]	1 [1, 1]	$1 \ [1, 1]$	$0.943 \ [0.931, \ 0.945]$

Table 7. Simulation example where 1000 observations are simulated from a Gaussian mixture distribution with 3 components and 100 variables, in which 5% of variables are relevant.

SUGSVarSel and VarSelLCM produce high quality answers in all situations but SUGSVarSel is 2 orders of magnitude faster. However, to alleviate the computational burden we searched up to a maximum of 4 clusters in VarSelLCM, providing it with an easier opportunity to produce high quality clusterings. In applications to real data this would have to be much larger, adding considerably to computational time, whereas the inference of the number of clusters is automatic in SUGSVarSel.

3.3 Advantages of Bayesian model averaging

As an example, we simulate a dataset with 30 observations from a mixture of 3 Gaussians, where two of the Gaussians are isotropic and centred (2,2) and (-3,-3) respectively, each with mixing weights 0.4. The third component has mixture weight 0.2 and is centered at (-3,4) but the covariance matrix is 2 on the diagonals and 1 on the off diagonals, violating our independence assumption. We additionally include 2 components of irrelevant variables generated from standard Gaussians. Our prior specifications are set as in the previous section. Simply using the ML to pick a partition results in an ARI of 0.635 between the clustering produced and the truth. However, we can also perform BMA and then summarise our co-clustering. We applied hierarchical clustering with average linkage to compute a clustering, which has previously be applied to posterior similarity matrices (Fritsch and Ickstadt, 2009, Liverani et al., 2015, Medvedovic et al., 2004) (see appendix for complete details). This clustering then produces an ARI of 0.875. The heatmap of the co-clustering matrix is Figure 1, providing a visualisation of the uncertainty in the clustering.



Figure 1. A heatmap of the BMA co-clustering matrix, where dark blue indicates the probability of being in the same cluster is 1 and white indicates a probability of 0 of belonging to the same cluster. The component annotation bar indicates the true component labels and the cluster annotation bar indicates the clustering obtained from summarising the BMA co-clustering matrix.

4 Applications to cancer subtyping

4.1 Application to Leukaemia Dataset

In this section, we apply SUGSVarSel to real biological datasets. The first is a well-studied genomic clustering problem: the separation of acute myeloid leukaemia (AML) and the B/T-cell subtypes of acute lymphoblastic leukemia (ALL) samples on the basis of microarray transcriptomic data. We use the dataset described by Golub et al. (1999), which comprises 38 samples, 27 of which are ALL (8 T-cell and 19 B-cell related), and 11 of which are AML cases. Initial preprocessing is performed as in Dudoit et al. (2002), which reduces the dimension of the dataset from 6,817 to 3,051 genes. In Dudoit et al. (2002), a further dimension reduction step is performed that makes use of the AML and ALL class labels, so that only those genes that have a high ratio of their between-class to within-class sums of squares are retained. Here we instead wish to adopt a completely unsupervised approach, so that we may use the known ALL-AML class label in order to validate our results.

We select the 200 most variable genes and then normalise, so the expression values for each gene are mean-centred at 0 with variance 1. 200 genes were chosen because this led to good predictive performance in previous analysis of these data (Dudoit et al., 2002, Golub et al., 1999). We then apply SUGSVarSel to the resultant dataset. We sub-sample 10% of the variables 20 times to produce an initial variable selection set, and run the algorithm for 100 random orderings. We adopt our default priors and summarise the output using BMA. A final summary clustering is obtained by performing hierarchical clustering with average linkage (Fritsch and Ickstadt, 2009). We use the ARI to compare our results to the truth (of 3 classes) and repeat the process 10 times and report the average results.

Results are illustrated in Figure 2. The final clustering result provides an ARI of 0.831, which is in line with previous analyses preformed on this dataset (Dudoit et al., 2002, Golub et al., 1999). The algorithm selects a total of 92 genes, including TCL1, TCRB, IL8, EPB72, IL7R, TCRG, NFIL6, which are all known to be associated with leukaemia (Chen et al., 2010, Kuett et al., 2015, Natsuka et al., 1992, Pekarsky et al., 2001, Shochat et al., 2011, Van der Velden et al., 2004). A full list of the selected genes (including their descriptions) can be found in the appendix. The advantage of our analysis over other methods is that we did not need to specify the number clusters - the algorithm automatically inferred 3 clusters in the data, which have excellent correspondence to the known classes of AML and ALL, as well as the 2 ALL subgroups.



Figure 2. A PCA plot of the microarray expression data of 38 patients from the Golub et al. (1999) dataset, using the 200 most variable genes. The different symbols indicate the clustering produced by the SUGSVarSel algorithm after summarising the BMA co-clustering matrix using hierarchical clustering with average linkage. The colours indicate the annotated sub-types.

To assess the importance of variable selection, we also apply mclust and the original SUGS algorithm to the data. We run the mclust algorithm performing a systematic search to select the number of clusters, up to a maximum of 9, and select the number of cluster which maximises the BIC. This criterion selects 3 clusters and clustering produced gives an adjusted Rand index of 0.627 - the inclusion of irrelevant variables has led to reduced cluster quality. We run SUGS using our default prior choices and using the PML criterion to select a clustering. The algorithm was run for 100 random ordering and we repeated the process 10 times, reporting an average ARI of 0. The lack of variable selection renders SUGS unable to produce a meaningful clustering. In Figure 3, we visualise the BMA co-clustering matrix for these data when applying the SUGSVarSel algorithm.



Figure 3. A heatmap of the BMA co-clustering matrix for the 38 patients, when applying SUGSVarSel, demonstrating the added benefit of visualising uncertainty. The annotation bars of the left indicate the correspondence between the clusters and the subtypes.

4.2 Application to TCGA breast cancer dataset

We demonstrate SUGSVarSel on a further genomics dataset. We analyse an expression dataset for breast cancer tumour data from The Cancer Genome Atlas (TCGA)(Network, 2012), which we pre-process in the same way as in Lock and Dunson (2013). The processed expression dataset comprises 348 tumours with 645 genes, of which 14 belong to the PAM50 (Prediction Analysis of Microarray) group of genes (Parker et al., 2009).

Analysis was performed in the following way. We first standardise our data so that each column is mean-centred with variance 1. We then subsample 10% of the variables 64 times to produce an initial variable set. We then apply the SUGSVarSel algorithm with default settings. We summarise our output by performing BMA and then hierarchical clustering with average linkage.

SUGSVarSel reveals two clusters in the dataset, the second of which is significantly associated with Basal-like tumours (Fisher test, p < 0.0001). The algorithm selects 245 variables to discriminate between the groups. We perform PCA before and after variable selection to demonstrate that the reduced variable set produces more separable and therefore more interpretable clusters (Figure 4).



Figure 4. PCA plot of the TCGA breast cancer data, where clusters identified by SUGSVarSel are indicated by shape and subtypes by colour. The left PCA plot demonstrates smaller and tighter clusters using only the variables that remained after variable selection. In the right hand plot all variable were used to produce the plot.

Furthermore, the algorithm selected 13 out of a total of 14 of the PAM50 genes, which is significantly better than random (Fisher Test, p < 0.0001).

There is perhaps concern that variable selection could remove relevant genes for clustering, in the situation where we have a highly informative set of variables. We consider the following task to cluster the breast cancer genes using the PAM50 genes from the total unprocessed dataset (that is without the filtering of Lock and Dunson (2013)), of which there are 48. We apply the SUGSVarSel algorithm in identical fashion to before, sub-sampling 10% of the variables 4 time to produce an initial variable set. We obtain 5 clusters which correspond well to the different breast cancer subgroups.



Figure 5. PCA plot of the TCGA breast cancer data using 48 of the PAM50 genes, where clusters produced by SUGSVarSel are indicated by shape and subtypes by colour.

Cluster A is associated with Luminal A cancers, cluster B is associated with Luminal cancers, cluster C with basal-like tumours, cluster D contains mostly HER2 type breast cancers (chi-squared p < 0.0001). Thus, hardly surprisingly, the cluster produce on the PAM50 data coincide well with the PAM50 subgroups. Furthermore, 87.5% of the genes were selected which is more than we expect given our prior, telling us this was a highly informative set of genes.

The clusterings shown in Figures 4 and 5 demonstrate that the variables we use for clustering are critically important. The two different pre-filtering choices led to results of varying quality and biological meaning. This is strong evidence in support of model-based variable selection rather than ad-hoc preprocessing.

5 Pan-cancer proteomic characterisation

In this section we apply our method to The Cancer Proteome Atlas (TCPA) datasets (Akbani et al., 2014, Li et al., 2013, Städler et al., 2017). The dataset contains a large number of tumours and cell line samples with protein expression levels generated using reverse-phase protein arrays (RPPAs). Our method allows us to perform a number of tasks on this data; in particular, for each cancer we can detect possible subgroups and the relevant proteins which discriminate these subgroups. We can also perform a pan-cancer analysis to explore the differences and similarities between cancers. Pan-cancer studies can unravel inter-cancer relationships which are important for developing new clinical targets (Berger et al., 2018, Hoadley et al., 2018, Uhlen et al., 2017, Weinstein et al., 2013). Recent pan-cancer analyses have suggested that cancers should be classified based on their molecular signatures rather than tissue of origin (Berger et al., 2018, Hoadley et al., 2018) and this motivates our analysis.

As is usual with this data there are irrelevant variables so methods that do not perform variable se-

lection such as mclust and SUGS are ill-suited. Furthermore, there is little *a priori* knowledge about the number of clusters and so methods such as VarSelLCM and clustvarsel which require an exhaustive search of the number of clusters are inappropriate. To perform the analysis on all cancer sets would be prohibitively slow for the slowest of analysis methods.

The TCPA datasets contain data on 19 cancer types and the description of these cancers can be found in the appendix. The total dataset consists of over 5000 tumour samples with only a few samples for some cancers and hundreds of samples for others and several hundreds of proteins. The merged PAN-Can 19 level 4 dataset is used in the following analysis, since it is appropriate for multiple disease analysis. More information about the data can be found here http://tcpaportal.org/tcpa/, where the data itself can also be downloaded. In addition, we standardise the expression levels for each protein so that they are zero-centred with unit variance.

Table 8 demonstrates the number of cases for each cancer type:

Table 8. A table indicating the different cancer types and the number of observations from each of those cancers.

ACC	BLCA	BRCA	COAD	GBM	HNSC	KIRC	KIRP	LGG	LUAD
46	127	820	327	205	203	445	208	257	234
LUSC	OV	PAAD	PRAD	READ	SKCM	STAD	THCA	UCEC	
192	411	105	164	129	207	299	374	404	

We only keep proteins which have been measured on all cancers, which total 217 and so our dataset has a total of 5157 tumour samples with 217 variables. We apply SUGSVarSel to this data by first subsampling 10% of the variables 43 (a fifth of the total number of variables) times. Using the same priors as in previous analysis we analyses this data using the SUGSVarSel algorithm, running the algorithm for 50 random orderings, thus exploring a total of 2150 models. We summarise the BMA clustering using hierarchical clustering with average linkage. The summarised clustering contains 60 clusters, however many of these clusters contain only a few observations. Reassuringly there are 18 clusters with more than 20 observations and we focus on these for our analysis. A table summarising the clusters can be found in the appendix. Figure 6 summarises the relationship between the cancer types and SUGSVarSel clusterings.



Figure 6. A heatmap indicating the correspondence between clusters produced by the SUGSVarSel algorithm and the different cancer types.

In addition, in Figure 7 we plot a heatmap of the data with the clustering identified by SUGSVarSel, using only the proteins selected by the algorithm.



Figure 7. A heatmap of the expression data using the clustering produced by the SUGSVarSel algorithm applied to the pan-cancer TCPA dataset. The annotation bars on the top of plot indicate the different cancers and clusters.

It is rare that a cancer associates with a single cluster, however there are evident relationships between cancers and clusters. Cluster A contains predominately womens' cancers (OV, UCEC, BRCA), while cluster B contains a large spread of cancers. Clusters C, E and F contain the cancers of the digestive tract (STAD, COAD and READ). Cluster D contains a subgroups of breast cancers (BRCA), while cluster G contains solely kidney cancer (KIRC). Clusters H and I contain cancers of the brain (LGG, GBM). Cluster J and P contain aero-digestive cancers (HNSC, LUAD LUSC). Thyroid cancer (THCA) is spread across clusters K, L and B, whilst KIRP is predominately found in cluster M. Pancreatic cancer (PAAD) is split across clusters N and B. Cluster O contains the majority of breast cancer patients. Prostate cancer (PRAD) is dominantly found in Q, while R forms a small cluster of stomach cancers. This is in line with other analyses performed on these data (Akbani et al., 2014, Hoadley et al., 2014, Şenbabaoğlu et al., 2016). A total of 147 proteins were selected as relevant for clustering.

We now consider an illustrative example. Figure 6 indicates that clusters K and L contain only thyroid cancers. It is of biological interest to see what drives the differences between these clusters, as they could define clinically relevant thyroid cancer subtypes. Considering only the 147 selected proteins, in Figure 8 we plot the expression profile for the 20 proteins, with smallest p-value, which are significantly different between clusters K and L (T-test (Welch, 1947), p < 0.00001, using Benjamini-Hochberg correction (Benjamini and Hochberg, 1995))



Figure 8. A heatmap of the expression TCPA data for the thyroid subgroups. We have plotted the expression for only the top 20 proteins which are significantly different between clusters K and L.

We do not observe an over representation of known thyroid cancers subtypes within each of these clusters (see Table 9).

Table 9. A table showing the distribution of 3 different THCA subtypes across the clusters K and L produce from the SUGSVarSel algorithm. Note that this information was not available for all patients.

	Κ	\mathbf{L}
Thyroid Papillary Carcinoma - Classical/usual	31	72
Thyroid Papillary Carcinoma - Follicular ($>= 99\%$ follicular patterned)	17	25
Thyroid Papillary Carcinoma - Tall Cell ($>= 50\%$ tall cell features)	2	6

6 Conclusion

In this article we presented SUGSVarSel, an extension to the SUGS algorithm of Wang and Dunson (2011) to allow variable selection. We demonstrated that when irrelevant variables are present the quality of the clustering can be degraded and clusters become more challenging to interpret. SUGSVarSel allows the flexibility of a Bayesian nonparametric approach but inference is considerably faster than using MCMC. Indeed, the SUGSVarSel algorithm infers the number of clusters automatically and performs inference for the Dirichlet process hyperparameter. This is in contrast to most clustering with variable selection methods which require a systematic search over the number of clusters.

Whilst our method is approximate it performs competitively with other commonly used approaches. Furthermore, we take advantage of exploring many models by performing Bayesian model averaging, which is important for exploring uncertainty in our clustering. We remark that model uncertainty and the application of BMA is rarely explored in clustering tasks. We have provided an R package to facilitate dissemination of our method utilising C++ to accelerate intensive computations and parallel processing features to make further computational gains

Application to two cancer transcriptomic datasets show the clear benefit of simultaneously performing variable selection and clustering. We demonstrate that variable selection improves interpretation of these datasets, providing the genes that drive the clustering structure of the data, as well as identifying those that are irrelevant for clustering. We further applied our method to a pan-cancer proteomic dataset for which none of the current model-based clustering and variable selection methods are suitable. SUGSVarSel is able to provide a characterisation of 5, 157 tumour samples, demonstrating clustering relationships across cancer types based on their molecular signature rather than tissue of origin.

There are a number of ways in which our proposed method could be extended. Firstly, our assumption that variables are conditionally independent given the cluster allocations might be unrealistic for some datasets. In such cases, more elaborate variable selection methods might be desirable, although this is likely to come at increased computational cost. Furthermore, we have assumed conjugacy throughout, so that the marginal likelihood in Equation (5) may be evaluated analytically. As noted in the original SUGS paper of Wang and Dunson (2011), one possible way to extend to non-conjugate cases would be to approximate this marginal likelihood, e.g. using a Laplace approximation.

Acknowledgements

O.M.C. is a Wellcome Trust Mathematical Genomics and Medicine student supported financially by the School of Clinical Medicine, University of Cambridge. L.G. was supported by a BBSRC Strategic Longer and Larger grant (Award BB/L002817/1). P.D.W.K. was supported by the Medical Research Council grant number MC_UU_00002/10. No conflict of interest declared.

7 Appendix

DP Gaussian mixture with variable selection

In this appendix, we give specific details for our algorithm in the case of Gaussian mixtures. We note that whenever conjugate priors are chosen all the formulas presented here are available analytically. We specify the mean and covariance matrix associated cluster k by $\theta_k = (m_k, \Sigma_k)$, where $m_k = (m_{k,1}, ..., m_{k,d})$ and Σ_k is diagonal under our independence assumption. The prior on the parameters $p_0(\theta_{k,d})$ is chosen as conjugate normal inverse-chi-squared $(NI\chi^2)$ prior, which is a simple reparameterisation of the normal inverse-gamma prior and is the special case of normal inverse-Wishart prior in one dimension. The specification is as follows:

$$p_0(\theta_{k,d}) \sim N\left(m_{k,d}|\mu_0, \frac{\Sigma_{k,d}}{\lambda_0}\right) I\chi^2\left(\Sigma_{k,d}|\nu_0, S_0\right),\tag{20}$$

with known hyperparameters $\mu_0, \lambda_0, \nu_0, S_0$. Updating the prior (20) with the data from observations 1, ..., (i-1) results in

$$p(\theta_{k,d}|x_{-i}, z_{-i}) \sim N\left(m_{k,d}|m^{(i-1)}, \frac{\Sigma_{k,d}}{\lambda^{(i-1)}}\right) I\chi^2\left(\Sigma_{k,d}|\nu^{(i-1)}, S^{(i-1)}\right),\tag{21}$$

where the parameter updates are obtained sequentially, through the following equations (dropping the subscript d for clarity) (Murphy, 2007):

$$m_{k}^{(i)} = \frac{\lambda_{k}^{(i-1)}m_{k}^{(i-1)} + x_{i}}{\lambda^{(i)}}$$

$$\lambda_{k}^{(i)} = \lambda_{k}^{(i-1)} + 1$$

$$v_{k}^{(i)} = v_{k}^{(i-1)} + 1$$

$$T_{k}^{(i)} = T_{k}^{(i-1)} + x_{i}^{2}$$

$$v_{k}^{(i)}S_{k}^{(i)} = T_{k}^{(i)} - \lambda_{k}^{(i)} \left(m_{k}^{(i)}\right)^{2},$$
(22)

where in the case i = 0 the parameters are given by their specified prior values, except we set $T_k^{(0)} = v_0 S_0 + \lambda_0 \mu_0^2$. The required conditional likelihood is given by a non-central \mathcal{T} -distribution. Remembering at the i^{th} iteration we compute with the updated parameters from the previous iteration; that is, at the $(i - 1)^{th}$ iteration, the required distribution is

$$\mathcal{T}\left(\cdot|m_{k}^{(i-1)},v_{k}^{(i-1)},\frac{(1+\lambda_{k}^{(i-1)})S_{k}^{(i-1)}}{\lambda_{k}^{(i-1)}}\right).$$

For a $NI\chi^2$ prior the marginal likelihood is given by the following equation, (dropping the subscript d for clarity)

$$\int_{\theta_k} f(X_k | \theta_k) p_0(\theta_k) d\theta_k = \frac{1}{\pi^{n_k/2}} \frac{\Gamma(\nu_k/2)}{\Gamma(\nu_0/2)} \left(\frac{\lambda_0(\nu_0 S_0)^{\nu_0}}{\lambda_k (\nu_k S_k)^{\nu_k}} \right)^{1/2}.$$
(23)

The other required equations have already been given and require simple substitutions.

Prior Settings for the SUGS and SUGSVarSel high-dimensional example

Here we state the prior specification for the SUGS and SUGSVarSel algorithms. We let μ_0 be the mean of the observations' data for each variable, $\lambda_0 = 0.01$, ν_0 be the number of variables, $S_0 = 0.2$ for all variables. We let $\hat{\beta} = (0.01, 0.1, 1, 5, 10, 15, 30, 50, 100)^T$ and set the prior to be $\mathcal{G}(1, 1)$. In addition, for SUGSVarSel we suppose that a priori variables are equally likely to be relevant or irrelevant.

Summarising the Bayesian model averaged co-clustering matricies

Fritsch and Ickstadt (2009) propose a method to summarise the posterior similarity matrix of a Bayesian clustering method. We apply their methodology to summarise our Bayesian model averaged co-clustering matrix. They present several method to obtain a clustering by maximising the posterior expected adjusted Rand index. We use the proposed method which obtains clusterings from applying hierarchical clustering with average linkage. An optimal clustering is then obtain by cutting the dendrogram at 0.5 (Fritsch and Ickstadt, 2009).

Gene selection table Genes selected in the SUGSVarSel algorithm applied to the Golub dataset

1 "TCL1 gene (T cell leukemia) extracted from H.sapiens mRNA for Tcell leukemia/lymphoma 1"	28 "Mac25"	55 "LYZ Lysozyme"
2 "TCRB T-cell receptor, beta cluster"	29 "PSAP Sulfated glycoprotein 1"	56 "Fc-epsilon-receptor gamma-chain mRNA"
3 "INTERLEUKIN-8 PRECURSOR"	30 "Terminal transferase mRNA"	57 "HLA-DRB1 Major histocompatibility complex, class II, DR beta 5"
4 "TCRB T-cell receptor, beta cluster"	31 "CALGRANULIN A"	58 "Lysozyme gene (EC 3.2.1.17)"
5 "GB DEF = MAL gene exon 4"	32 "CLASS II HISTOCOMPATIBILITY ANTIGEN, M ALPHA CHAIN PRECURSOR"	59 "LYZ Lysozyme"
6 "Interleukin 8 (IL8) gene"	33 "SELL Leukocyte adhesion protein beta subunit"	60 "Pre-B cell enhancing factor (PBEF) mRNA"
7 "GB DEF = (lambda) DNA for immunoglobin light chain"	34 "GB DEF = T-lymphocyte specific protein tyrosine kinase p56lck (lck) abberant mRNA"	61 "LPAP gene"
8 "CST3 Cystatin C (amyloid angiopathy and cerebral hemorrhage)"	35 "MEF2C MADS box transcription enhancer factor 2, polypeptide C (myocyte enhancer factor 2C)"	62 "CHIT1 Chitinase 1"
9 "CD24 signal transducer mRNA and 3' region"	36 "PRG1 Proteoglycan 1, secretory granule"	63 "TCRG T cell receptor gamma chain"
10 "IGHM Immunoglobulin mu"	37 "CD2 CD2 antigen (p50), sheep red blood cell receptor"	64 "MXS1 Membrane component, X chromosome, surface marker 1"
11 "MPO Myeloperoxidase"	38 "CTGF Connective tissue growth factor"	65 "FLN1 Filamin 1 (actin-binding protein-280)"
12 "MHC class II HLA-DP light chain mRNA"	39 "Lymphoid-restricted membrane protein (Jaw1) mRNA"	66 "BLK Protein-tyrosine kinase blk"
13 "GB DEF = Cystic fibrosis antigen mRNA"	40 "GRO2 GRO2 oncogene"	67 "DP2 (Humdp2) mRNA"
14 "LTB Lymphotoxin-beta"	41 "SEF2-1A protein (SEF2-1A) mRNA, 5' end"	68 "HLA CLASS II HISTOCOMPATIBILITY ANTIGEN, DR ALPHA CHAIN PRECURSOR"
15 "Major Histocompatibility Complex, Class Ii Beta W52"	42 "GB DEF = T-cell antigen receptor gene T3-delta"	69 "Quiescin (Q6) mRNA, partial cds"
16 "CD9 CD9 antigen"	43 "CYSTATIN A"	70 "GB DEF = Immunoglobulin mu, part of exon 8"
17 "MB-1 gene"	44 "NPY Neuropeptide Y"	71 "ICAM3 Intercellular adhesion molecule 3"
18 "DF D component of complement (adipsin)"	45 "Amphiregulin (AR) gene"	72 "NF-IL6-beta protein mRNA"
19 "PROBABLE PROTEIN DISULFIDE ISOMERASE ER-60 PRECURSOR"	46 "ELA2 Elastatse 2, neutrophil"	73 "Nuclear Factor Nf-II6"
20 "LGALS3 Lectin, galactoside-binding, soluble, 3 (galectin 3) (NOTE: redefinition of symbol)"	47 "SNRPN Small nuclear ribonucleoprotein polypeptide N"	74 "Protein-tyrosine-phosphatase (tissue type: foreskin)"
21 "LYZ Lysozyme"	48 "Adenosine triphosphatase, calcium"	75 "DAGK1 Diacylglycerol kinase, alpha (80kD)"
22 "ANX1 Annexin I (lipocortin I)"	49 "MHC cell surface glycoprotein (HLA-DQA) mRNA, 3'end"	76 "CD72 CD72 antigen"
23 "IGB Immunoglobulin-associated beta (B29)"	50 "Zyxin"	77 "GB DEF = Selenoprotein W (selW) mRNA"
24 "Azurocidin gene"	51 "HU-K4 mRNA"	78 "PROBABLE G PROTEIN-COUPLED RECEPTOR LCR1 HOMOLOG"
25 "Na,K-ATPase gamma subunit mRNA"	52 "GLUTATHIONE S-TRANSFERASE, MICROSOMAL"	79 "ARHG Ras homolog gene family, member G (rho G)"
26 "CD1B CD1b antigen (thymocyte antigen)"	53 "GB DEF = CD1 R2 gene for MHC-related antigen"	80 "CA2 Carbonic anhydrase II"
27 "TCF7 Transcription factor 7 (T-cell specific)"	54 "GB DEF = Neutrophil elastase gene, exon 5"	81 "APLP2 Amyloid beta (A4) precursor-like protein 2"

82 "CD22 CD22 antigen"
83 "No cluster in current Unigene and no Genbank entry for U77396 (qualifier U77396_at)"
84 "Epb72 gene exon 1"
85 "GB DEF = Fork head domain protein (FKHR) mRNA, 3' end"
86 "PFC Properdin P factor, complement"
87 "Inducible protein mRNA"
88 "PLECKSTRIN"
89 "C-myb gene extracted from Human (c-myb) gene, complete primary cds, and five complete alternatively spliced cds"
90 "IL7R Interleukin 7 receptor"
91 "Cytoplasmic dynein light chain 1 (hdlc1) mRNA"
92 "FOS-RELATED ANTIGEN 2"

Pan-cancer proteomics cancer types

The cancers used in the pan-cancer proteomic analysis are Uterine Corpus Endometrial Carcinoma (UCEC), Ovarian (OV), Kidney Renal Clear Cell Carcinoma (KIRC), Colon Adenocarcinoma (COAD), glioblastoma multiforme (GBM), Rectum adenocarcinoma (READ), Thyroid carcinoma (THCA), Kidney renal papillary cell carcinoma (KIRP), Pancreas adenocarcinoma (PAAD), Adenoid cystic carcinoma (ACC), Urothelial Bladder Carcinoma (BLCA), breast cancer (BRCA), Head and neck squamous cell carcinoma (HNSC), Lower grade glioma (LGG), Lung adenocarcinoma (LUAD), Lung Squamous Cell Carcinoma (LUSC), Prostate Adenocarcinoma (PRAD), skin cutaneous melanoma (metastatic and primary) (SKCM) and Stomach Adenocarcinoma (STAD).

Cancer clustering table In Table 10, we summarise the correspondence between the 18 largest SUGSVarSel clusters (which omits clusters with fewer than 20 members) and the cancer types.

	А	В	С	D	Ε	F	G	Η	Ι	J	Κ	L	М	Ν	0	Р	Q	R
UCEC	325	43	1	1	11	2	0	0	0	0	0	0	0	0	0	0	0	0
OV	363	42	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0
KIRC	3	25	0	2	0	0	405	0	0	0	0	0	0	0	0	0	0	0
COAD	18	33	229	0	28	17	0	0	0	1	0	0	0	0	0	0	0	0
READ	8	13	92	1	10	4	0	0	0	0	0	0	0	0	0	0	0	0
GBM	5	6	0	4	0	0	0	170	2	0	0	0	0	0	0	0	0	0
THCA	0	177	0	3	0	0	0	0	0	0	64	128	0	0	0	0	0	0
KIRP	7	40	0	2	0	0	0	0	0	0	0	0	158	0	0	0	0	0
PAAD	5	72	0	2	3	0	0	0	0	0	0	0	0	23	0	0	0	0
ACC	6	6	0	0	1	0	0	0	0	0	0	0	33	0	0	0	0	0
BLCA	66	46	1	0	3	0	0	0	0	6	0	0	0	0	0	0	0	0
BRCA	151	192	0	34	0	0	0	0	0	1	0	0	0	0	415	0	0	0
HNSC	24	49	0	1	16	3	0	0	0	104	0	0	0	0	0	1	0	0
LGG	0	1	0	0	0	0	0	128	124	0	0	0	0	0	0	0	0	0
LUAD	12	19	0	0	1	11	0	0	0	164	0	0	0	0	0	16	0	0
LUSC	20	5	0	0	10	3	0	0	0	146	0	0	0	0	0	5	0	0
PRAD	3	5	0	1	0	0	0	0	0	0	0	0	0	0	0	0	155	0
SKCM	149	46	0	4	6	0	0	0	0	0	0	0	0	0	0	0	0	0
STAD	8	66	99	2	25	45	0	0	0	0	0	0	0	0	0	0	0	38

Table 10. Number of tumours of each cancer type (rows) in each SUGSVarSel cluster (columns).

References

Akbani, R., Ng, P. K. S., Werner, H. M. J., Shahmoradgoli, M., Zhang, F., Ju, Z., Liu, W., Yang, J.-Y., Yoshihara, K., Li, J., Ling, S., Seviour, E. G., Ram, P. T., Minna, J. D., Diao, L., Tong, P., Heymach, J. V., Hill, S. M., Dondelinger, F., Städler, N., Byers, L. A., Meric-Bernstam, F., Weinstein, J. N., Broom, B. M., Verhaak, R. G. W., Liang, H., Mukherjee, S., Lu, Y., and Mills, G. B. (2014). A pancancer proteomic perspective on The Cancer Genome Atlas. *Nature communications*, 5:3887. *Referred* to on pages 2, 16, and 18.

Antoniak, C. E. (1974). Mixtures of dirichlet processes with applications to bayesian nonparametric problems. Ann. Statist., 2(6):1152–1174. Referred to on page 1.

Benjamini, Y. and Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the royal statistical society. Series B (Methodological)*, pages 289–300. *Referred to on page 18.*

- Berger, A. C., Korkut, A., Kanchi, R. S., Hegde, A. M., Lenoir, W., Liu, W., Liu, Y., Fan, H., Shen, H., Ravikumar, V., et al. (2018). A comprehensive pan-cancer molecular study of gynecologic and breast cancers. *Cancer Cell. Referred to on page 16.*
- Blackwell, D. and MacQueen, J. B. (1973). Ferguson distributions via polya urn schemes. Ann. Statist., 1(2):353–355. Referred to on page 2.
- Blei, D. M., Jordan, M. I., et al. (2006). Variational inference for dirichlet process mixtures. Bayesian analysis, 1(1):121–143. Referred to on page 1.
- Chen, A. H., Tsau, Y.-W., and Lin, C.-H. (2010). Novel methods to identify biologically relevant genes for leukemia and prostate cancer from gene expression profiles. *BMC genomics*, 11(1):274. *Referred to on page 13.*
- Constantinopoulos, C., Titsias, M. K., and Likas, A. (2006). Bayesian feature and model selection for gaussian mixture models. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 28(6):1013–1018. *Referred to on page 1.*
- Cooke, E. J., Savage, R. S., Kirk, P. D. W., Darkins, R., and Wild, D. L. (2011). Bayesian hierarchical clustering for microarray time series data with replicates and outlier measurements. *BMC Bioinformatics*, 12:399. *Referred to on page 2*.
- Darkins, R., Cooke, E. J., Ghahramani, Z., Kirk, P. D. W., Wild, D. L., and Savage, R. S. (2013). Accelerating bayesian hierarchical clustering of time series data with a randomised algorithm. *PloS* one, 8(4):e59795. Referred to on page 2.
- Daume III, H. (2007). Fast search for dirichlet process mixture models. In Meila, M. and Shen, X., editors, *Proceedings of the Eleventh International Conference on Artificial Intelligence and Statistics*, volume 2 of *Proceedings of Machine Learning Research*, pages 83–90, San Juan, Puerto Rico. PMLR. *Referred to on page 2.*
- Dudoit, S., Fridlyand, J., and Speed, T. P. (2002). Comparison of discrimination methods for the classification of tumors using gene expression data. *Journal of the American statistical association*, 97(457):77–87. *Referred to on page 13.*
- Escobar, M. D. (1994). Estimating normal means with a dirichlet process prior. Journal of the American Statistical Association, 89(425):268–277. Referred to on page 1.
- Escobar, M. D. and West, M. (1995). Bayesian density estimation and inference using mixtures. *Journal* of the American Statistical Association, 90(430):577–588. Referred to on page 1.
- Ferguson, T. S. (1973). A bayesian analysis of some nonparametric problems. Ann. Statist., 1(2):209–230. Referred to on page 1.
- Ferguson, T. S. (1974). Prior distributions on spaces of probability measures. Ann. Statist., 2(4):615–629. Referred to on page 1.
- Fop, M. and Murphy, T. B. (2017). Variable selection methods for model-based clustering. arXiv preprint arXiv:1707.00306. Referred to on pages 1 and 5.
- Fraley, C. and Raftery, A. E. (2002). Model-based clustering, discriminant analysis and density estimation. Journal of the American Statistical Association, 97:611–631. Referred to on page 9.
- Fraley, C., Raftery, A. E., Murphy, T. B., and Scrucca, L. (2012). mclust Version 4 for R: Normal Mixture Modeling for Model-Based Clustering, Classification, and Density Estimation. Referred to on page 9.

- Fritsch, A. and Ickstadt, K. (2009). Improved criteria for clustering based on the posterior similarity matrix. *Bayesian Anal.*, 4(2):367–391. *Referred to on pages 12, 13, and 21.*
- Golub, T. R., Slonim, D. K., Tamayo, P., Huard, C., Gaasenbeek, M., Mesirov, J. P., Coller, H., Loh, M. L., Downing, J. R., Caligiuri, M. A., et al. (1999). Molecular classification of cancer: class discovery and class prediction by gene expression monitoring. *science*, 286(5439):531–537. *Referred to on page* 13.
- Heller, K. and Ghahramani, Z. (2005). Bayesian hierarchical clustering. Proceedings of the 22nd international conference on Machine learning. Referred to on page 2.
- Hoadley, K. A., Yau, C., Hinoue, T., Wolf, D. M., Lazar, A. J., Drill, E., Shen, R., Taylor, A. M., Cherniack, A. D., Thorsson, V., et al. (2018). Cell-of-origin patterns dominate the molecular classification of 10,000 tumors from 33 types of cancer. *Cell*, 173(2):291–304. *Referred to on page 16.*
- Hoadley, K. A., Yau, C., Wolf, D. M., Cherniack, A. D., Tamborero, D., Ng, S., Leiserson, M. D., Niu, B., McLellan, M. D., Uzunangelov, V., et al. (2014). Multiplatform analysis of 12 cancer types reveals molecular classification within and across tissues of origin. *Cell*, 158(4):929–944. *Referred to on page 18*.
- Hoeting, J. A., Madigan, D., Raftery, A. E., and Volinsky, C. T. (1999). Bayesian model averaging: a tutorial (with comments by m. clyde, david draper and e. i. george, and a rejoinder by the authors. *Statist. Sci.*, 14(4):382–417. *Referred to on pages 2 and 8.*
- Hubert, L. and Arabie, P. (1985). Comparing partitions. Journal of Classification, 2(1):193–218. Referred to on page 9.
- Jain, S. and Neal, R. M. (2004). A split-merge markov chain monte carlo procedure for the dirichlet process mixture model. *Journal of Computational and Graphical Statistics*, 13(1):158–182. *Referred to on pages 1 and 3.*
- Kim, S., Tadesse, M. G., and Vannucci, M. (2006). Variable selection in clustering via dirichlet process mixture models. *Biometrika*, 93(4):877–893. *Referred to on pages 1 and 5.*
- Kuett, A., Rieger, C., Perathoner, D., Herold, T., Wagner, M., Sironi, S., Sotlar, K., Horny, H.-P., Deniffel, C., Drolle, H., et al. (2015). Il-8 as mediator in the microenvironment-leukaemia network in acute myeloid leukaemia. *Scientific reports*, 5:18411. *Referred to on page 13.*
- Law, M. H. C., Figueiredo, M. A. T., and Jain, A. K. (2004). Simultaneous feature selection and clustering using mixture models. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 26(9):1154– 1166. *Referred to on pages 1 and 5.*
- Li, J., Lu, Y., Akbani, R., Ju, Z., Roebuck, P. L., Liu, W., Yang, J.-Y., Broom, B. M., Verhaak, R. G., Kane, D. W., et al. (2013). Tcpa: a resource for cancer functional proteomics data. *Nature methods*, 10(11):1046–1047. *Referred to on page 16*.
- Liverani, S., Hastie, D. I., Azizi, L., Papathomas, M., and Richardson, S. (2015). Premium: An r package for profile regression mixture models using dirichlet processes. *Journal of statistical software*, 64(7):1. *Referred to on page 12.*
- Lo, A. Y. (1984). On a class of bayesian nonparametric estimates: I. density estimates. Ann. Statist., 12(1):351–357. Referred to on page 1.
- Lock, E. F. and Dunson, D. B. (2013). Bayesian consensus clustering. Bioinformatics, 29(20):2610–2616. Referred to on pages 14 and 15.

- Madigan, D. and Raftery, A. E. (1994). Model selection and accounting for model uncertainty in graphical models using occam's window. Journal of the American Statistical Association, 89(428):1535–1546. Referred to on pages 2 and 8.
- Marbac, M. and Sedki, M. (2017). Variable selection for model-based clustering using the integrated complete-data likelihood. Statistics and Computing, 27(4):1049–1063. Referred to on page 9.
- Marbac, M. and Sedki, M. (2018). Varsellcm: an r/c++ package for variable selection in model-based clustering of mixed-data with missing values. *Bioinformatics*, page bty786. *Referred to on page 9*.
- Maugis, C., Celeux, G., and Martin-Magniette, M.-L. (2009). Variable selection for clustering with gaussian mixture models. *Biometrics*, 65(3):701–709. *Referred to on pages 5 and 9.*
- Medvedovic, M., Yeung, K. Y., and Bumgarner, R. E. (2004). Bayesian mixture model based clustering of replicated microarray data. *Bioinformatics*, 20(8):1222–1232. *Referred to on page 12.*
- Murphy, K. P. (2007). Conjugate bayesian analysis of the gaussian distribution. *def*, 1:16. *Referred to* on page 21.
- Natsuka, S., Akira, S., Nishio, Y., Hashimoto, S., Sugita, T., Isshiki, H., and Kishimoto, T. (1992). Macrophage differentiation-specific expression of nf-il6, a transcription factor for interleukin-6. Blood, 79(2):460–466. Referred to on page 13.
- Neal, R. M. (2000). Markov chain sampling methods for dirichlet process mixture models. Journal of Computational and Graphical Statistics, 9(2):249–265. Referred to on pages 1 and 3.
- Network, C. G. A. (2012). Comprehensive molecular portraits of human breast tumours. *Nature*, 490(7418):61–70. *Referred to on page 14.*
- Parker, J. S., Mullins, M., Cheang, M. C., Leung, S., Voduc, D., Vickery, T., Davies, S., Fauron, C., He, X., Hu, Z., et al. (2009). Supervised risk predictor of breast cancer based on intrinsic subtypes. *Journal* of clinical oncology, 27(8):1160–1167. *Referred to on page 14*.
- Pekarsky, Y., Hallas, C., and Croce, C. M. (2001). The role of tcl1 in human t-cell leukemia. Oncogene, 20(40):5638. Referred to on page 13.
- Raftery, A. E. and Dean, N. (2006). Variable selection for model-based clustering. Journal of the American Statistical Association, 101(473):168–178. Referred to on pages 5 and 9.
- Rand, W. M. (1971). Objective criteria for the evaluation of clustering methods. Journal of the American Statistical association, 66(336):846–850. Referred to on page 9.
- Rasmussen, C. E. (2000). The Infinite Gaussian Mixture Model. In In Advances in Neural Information Processing Systems 12, volume 12, pages 554–560. Referred to on page 3.
- Russell, N., Murphy, T. B., and Raftery, A. E. (2015). Bayesian model averaging in model-based clustering and density estimation. arXiv preprint arXiv:1506.09035. Referred to on page 8.
- Savage, R. S., Heller, K., Xu, Y., Ghahramani, Z., Truman, W. M., Grant, M., Denby, K. J., and Wild, D. L. (2009). R/BHC: fast Bayesian hierarchical clustering for microarray data. *BMC Bioinformatics*, 10:242. *Referred to on page 2.*
- Schwarz, G. (1978). Estimating the dimension of a model. The annals of statistics, 6(2):461–464. Referred to on page 9.

- Scrucca, L., Fop, M., Murphy, T. B., and Raftery, A. E. (2016). mclust 5: clustering, classification and density estimation using Gaussian finite mixture models. *The R Journal*, 8(1):205–233. *Referred to on* page 9.
- Scrucca, L. and Raftery, A. E. (2014). clustvarsel: A package implementing variable selection for modelbased clustering in r. arXiv preprint arXiv:1411.0606. Referred to on page 9.
- Şenbabaoğlu, Y., Sümer, S. O., Sánchez-Vega, F., Bemis, D., Ciriello, G., Schultz, N., and Sander, C. (2016). A multi-method approach for proteomic network inference in 11 human cancers. *PLoS computational biology*, 12(2):e1004765. *Referred to on page 18.*
- Shochat, C., Tal, N., Bandapalli, O. R., Palmi, C., Ganmore, I., te Kronnie, G., Cario, G., Cazzaniga, G., Kulozik, A. E., Stanulla, M., et al. (2011). Gain-of-function mutations in interleukin-7 receptor-α (il7r) in childhood acute lymphoblastic leukemias. Journal of Experimental Medicine, 208(5):901–908. Referred to on page 13.
- Städler, N., Dondelinger, F., Hill, S. M., Akbani, R., Lu, Y., Mills, G. B., and Mukherjee, S. (2017). Molecular heterogeneity at the network level: high-dimensional testing, clustering and a tcga case study. *Bioinformatics*, 33(18):2890–2896. *Referred to on page 16*.
- Tadesse, M. G., Sha, N., and Vannucci, M. (2005). Bayesian variable selection in clustering highdimensional data. Journal of the American Statistical Association, 100(470):602–617. Referred to on page 5.
- Teh, Y. W., Jordan, M. I., Beal, M. J., and Blei, D. M. (2006). Hierarchical dirichlet processes. Journal of the American Statistical Association, 101(476):1566–1581. Referred to on page 2.
- Uhlen, M., Zhang, C., Lee, S., Sjöstedt, E., Fagerberg, L., Bidkhori, G., Benfeitas, R., Arif, M., Liu, Z., Edfors, F., et al. (2017). A pathology atlas of the human cancer transcriptome. *Science*, 357(6352):eaan2507. *Referred to on page 16*.
- Van der Velden, V., Brüggemann, M., Hoogeveen, P., de Bie, M., Hart, P., Raff, T., Pfeifer, H., Lüschen, S., Szczepański, T., Van Wering, E., et al. (2004). Tcrb gene rearrangements in childhood and adult precursor-b-all: frequency, applicability as mrd-pcr target, and stability between diagnosis and relapse. *Leukemia*, 18(12):1971. *Referred to on page 13*.
- Wang, L. and Dunson, D. B. (2011). Fast Bayesian Inference in Dirichlet Process Mixture Models. Journal Of Computational And Graphical Statistics, 20(1):196–216. Referred to on pages 1, 2, 3, 4, 5, 9, 19, and 20.
- Weinstein, J. N., Collisson, E. A., Mills, G. B., Shaw, K. R. M., Ozenberger, B. A., Ellrott, K., Shmulevich, I., Sander, C., Stuart, J. M., Network, C. G. A. R., et al. (2013). The cancer genome atlas pan-cancer analysis project. *Nature genetics*, 45(10):1113–1120. *Referred to on page 16*.
- Welch, B. L. (1947). The generalization of student's problem when several different population variances are involved. *Biometrika*, 34(1-2):28–35. *Referred to on page 18.*
- Witten, D. M. and Tibshirani, R. (2010). A framework for feature selection in clustering. Journal of the American Statistical Association, 105(490):713–726. PMID: 20811510. Referred to on page 5.
- Zhang, X., Nott, D. J., Yau, C., and Jasra, A. (2014). A sequential algorithm for fast fitting of dirichlet process mixture models. *Journal of Computational and Graphical Statistics*, 23(4):1143–1162. *Referred* to on page 2.