Predictor-Corrector Policy Optimization

Ching-An Cheng¹² Xinyan Yan¹ Nathan Ratliff² Byron Boots¹²

Abstract

We present a predictor-corrector framework, called PICCOLO, that can transform a first-order model-free reinforcement or imitation learning algorithm into a new hybrid method that leverages predictive models to accelerate policy learning. The new "PICCOLOed" algorithm optimizes a policy by recursively repeating two steps: In the Prediction Step, the learner uses a model to predict the unseen future gradient and then applies the predicted estimate to update the policy; in the Correction Step, the learner runs the updated policy in the environment, receives the true gradient, and then corrects the policy using the gradient error. Unlike previous algorithms, PICCOLO corrects for the mistakes of using imperfect predicted gradients and hence does not suffer from model bias. The development of PICCOLO is made possible by a novel reduction from predictable online learning to adversarial online learning, which provides a systematic way to modify existing firstorder algorithms to achieve the optimal regret with respect to predictable information. We show, in both theory and simulation, that the convergence rate of several firs t-order model-free algorithms can be improved by PICCOLO.

1. Introduction

Reinforcement learning (RL) has recently solved a number of challenging problems (Mnih et al., 2013; Duan et al., 2016; Silver et al., 2018). However, many of these successes are confined to games and simulated environments, where a large number of agent-environment interactions can be cheaply performed. Therefore, they are often unrealistic in real-word applications (like robotics) where data collection is an expensive and time-consuming process. Improving sample efficiency still remains a critical challenge for RL. Model-based RL methods improve sample efficiency by leveraging an accurate model that can cheaply simulate interactions to compute policy updates in lieu of real-world interactions (Tan et al., 2018). A classical example of pure model-based methods is optimal control (Jacobson & Mayne, 1970; Todorov & Li, 2005; Deisenroth & Rasmussen, 2011; Pan & Theodorou, 2014), which has recently been extended to model abstract latent dynamics with neural networks (Silver et al., 2017; Oh et al., 2017). These methods use a (local) model of the dynamics and cost functions to predict cost-to-go functions, policy gradients, or promising improvement direction when updating policies (Levine & Koltun, 2013; Sun et al., 2018; Anthony et al., 2017). Another way to use model information is the hybrid DYNA framework (Sutton, 1991; Sutton et al., 2012), which interleaves model-based and model-free updates, ideally cutting learning time in half. However, all of these approaches, while potentially accelerating policy learning, suffer from a common drawback: when the model is inaccurate, the performance of the policy can become *biased* away from the best achievable in the policy class.

Several strategies have been proposed to remove this performance bias. Learning-to-plan attempts to train the planning process end-to-end (Pascanu et al., 2017; Srinivas et al., 2018; Amos et al., 2018), so the performance of a given planning structure is directly optimized. However, these algorithms are still optimized through standard model-free RL techniques; it is unclear as to whether they are more sample efficient. In parallel, another class of bias-free algorithms is control variate methods (Chebotar et al., 2017; Grathwohl et al., 2018; Papini et al., 2018), which use models to reduce the variance of sampled gradients to improve convergence.

In this paper, we provide a novel learning framework that can leverage models to improve sample efficiency while avoiding performance bias due to modeling errors. Our approach is built on techniques from online learning (Gordon, 1999; Zinkevich, 2003). The use of online learning to analyze policy optimization was pioneered by Ross et al. (2011), who proposed to reduce imitation learning (IL) to adversarial online learning problems. This reduction provides a framework for performance analysis, leading to algorithms such as DAGGER (Ross et al., 2011) and AG-GREVATE (Ross & Bagnell, 2014). However, it was recently shown that the naïve reduction to adversarial online learning

¹Georgia Tech ²NVIDIA. Correspondence to: Ching-An Cheng <cacheng@gatech.edu>.

Proceedings of the 36th International Conference on Machine Learning, Long Beach, California, PMLR 97, 2019. Copyright 2019 by the author(s).

loses information (Cheng & Boots, 2018): in practice, IL is *predictable* (Cheng et al., 2019) and can be thought of as a predictable online learning problem (Rakhlin & Sridharan, 2013a). Based on this insight, Cheng et al. (2019) recently proposed a two-step algorithm, MOBIL. The authors prove that, by leveraging predictive models to estimate future gradients, MOBIL can speed up the convergence of IL, without incurring performance bias due to imperfect models.

Given these theoretical advances in IL, it is natural to ask if similar ideas can be extended to RL. In this paper, we show that RL can also be formulated as a predictable online learning problem, and we propose a novel first-order learning framework, PICCOLO (PredICtor-COrrector poLicy Optimization), for general predictable online learning problems. PICCOLO is a meta-algorithm: it takes a standard online learning algorithm designed for adversarial problems (e.g. ADAGRAD (Duchi et al., 2011)) as input and returns a new hybrid algorithm that can use model information to accelerate convergence. This new "PICCOLOed" algorithm optimizes the policy by alternating between Prediction and Correction steps. In the Prediction Step, the learner uses a predictive model to estimate the gradient of the next loss function and then uses it to update the policy; in the Correction Step, the learner executes the updated policy in the environment, receives the true gradient, and then corrects the policy using the gradient error. We note that PICCOLO is orthogonal to control variate methods; it can still improve learning even in the noise-free setting (see Section 5.2).

Theoretically, we prove that PICCOLO can improve the convergence rate of *any* base algorithm that can be written as mirror descent (Beck & Teboulle, 2003) or Follow-the-Regularized-Leader (FTRL) (McMahan & Streeter, 2010). This family of algorithms is rich and covers most first-order algorithms used in RL and IL (Cheng et al., 2018). And, importantly, we show that PICCOLO does not suffer from performance bias due to model error, unlike previous model-based approaches. To validate the theory, we "PICCOLO" multiple algorithms in simulation. The experimental results show that the PICCOLOed versions consistently surpass the base algorithm and are robust to model errors.

The design of PICCOLO is made possible by a novel reduction that converts a given predictable online learning problem into a new adversarial problem, so that standard online learning algorithms can be applied optimally without referring to specialized algorithms. We show that PICCOLO includes and generalizes many existing algorithms, e.g., MOBIL, mirror-prox (Juditsky et al., 2011), and optimistic mirror descent (Rakhlin & Sridharan, 2013a) (Appendix A). Thus, we can treat PICCOLO as an automatic process for designing new algorithms that safely leverages imperfect predictive models (such as off-policy gradients or gradients simulated through dynamics models) to speed up learning.

2. Problem Definition

We consider solving policy optimization problems: given state and action spaces S and A, and a parametric policy class Π , we desire a stationary policy $\pi \in \Pi$ that solves

$$\min_{\pi \in \Pi} J(\pi), \quad J(\pi) \coloneqq \mathbb{E}_{(s,t) \sim d_{\pi}} \mathbb{E}_{a \sim \pi_s} \left[c_t(s,a) \right]$$
(1)

where $c_t(s, a)$ is the instantaneous cost at time t of state $s \in \mathbb{S}$ and $a \in \mathbb{A}$, π_s is the distribution of a at state s under policy π , and d_{π} is a generalized stationary distribution of states generated by running policy π in a Markov decision process (MDP); the notation $\mathbb{E}_{a \sim \pi_s}$ denotes evaluation when π is deterministic. The use of d_{π} in (1) abstracts different discrete-time RL/IL problems into a common setup. For example, an infinite-horizon γ -discounted problem with time-invariant cost c can be modeled by setting $c_t = c$ and $d_{\pi}(s,t) = (1-\gamma)\gamma^t d_{\pi,t}(s)$, where $d_{\pi,t}$ is the state distribution visited by policy π at time t starting from some *fixed* but unknown initial state distribution.

For convenience, we will usually omit the random variable in expectation notation (e.g. we will write (1) as $\mathbb{E}_{d_{\pi}}\mathbb{E}_{\pi}[c]$). For a policy π , we overload the notation π to also denote its parameter, and write $Q_{\pi,t}$ and $V_{\pi,t} := \mathbb{E}_{\pi}[Q_{\pi,t}]$ as its Q-function and value function at time t, respectively.

3. IL and RL as Predictable Online Learning

We study policy optimization through the lens of online learning (Hazan et al., 2016), by treating a policy optimization algorithm as the learner in online learning and *each intermediate policy* that it produces as an online decision. This identification recasts the iterative process of policy optimization into a standard online learning setup: in round n, the learner plays a decision $\pi_n \in \Pi$, a *per-round loss* l_n is then selected, and finally some information of l_n is revealed to the leaner for making the next decision. We note that the "rounds" considered here are the number of episodes that an algorithm interacts with the (unknown) MDP environment to obtain new information, not the time steps in the MDP. And we will suppose the learner receives an unbiased stochastic approximation \tilde{l}_n of l_n as feedback.

We show that, when the per-round losses $\{l_n\}$ are properly selected, the policy performance $\{J(\pi_n)\}$ in IL and RL can be upper bounded in terms the N-round weighted regret

$$\operatorname{Regret}_{N}(l) \coloneqq \sum_{n=1}^{N} w_{n} l_{n}(\pi_{n}) - \min_{\pi \in \Pi} \sum_{n=1}^{N} w_{n} l_{n}(\pi) \quad (2)$$

and an expressiveness measure of the policy class Π

$$\epsilon_{\Pi,N}(l) \coloneqq \frac{1}{w_{1:N}} \min_{\pi \in \Pi} \sum_{n=1}^{N} w_n l_n(\pi)$$
(3)

where $w_n > 0$ and $w_{1:n} \coloneqq \sum_{m=1}^n w_m$. Moreover, we show that these online learning problems are *predictable*:

that is, the per-round losses are not completely adversarial but can be estimated from past information. We will use these ideas to design PICCOLO in the next section.

3.1. IL as Online Learning

We start by reviewing the classical online learning approach to IL (online IL for short) (Ross et al., 2011) to highlight some key ideas. IL leverages domain knowledge about a policy optimization problem through expert demonstrations. Online IL, in particular, optimizes policies by letting the learner π query the expert π^* for desired actions, so that a policy can be quickly trained to perform as well as the expert. At its heart, online IL is based on the following lemma, which relates the performance between π and π^* .

Lemma 1. (Kakade & Langford, 2002) Let π and π' be two policies and $A_{\pi',t}(s,a) \coloneqq Q_{\pi',t}(s,a) - V_{\pi',t}(s)$. Then $J(\pi) = J(\pi') + \mathbb{E}_{d_{\pi}} \mathbb{E}_{\pi}[A_{\pi'}].$

Given the equality in Lemma 1, the performance difference between π and π^* can then be upper-bounded as

$$J(\pi) - J(\pi^*) = \mathbb{E}_{d_\pi} \mathbb{E}_{\pi}[A_{\pi^*}] \le C_{\pi^*} \mathbb{E}_{(s,t)\sim d_\pi}[D_t(\pi_s^*||\pi_s)]$$

for some positive constant C_{π^*} and function D_t , which is often derived from statistical distances such as KL divergence (Cheng et al., 2018). When $A_{\pi^*,t}$ is available, we can also set $D_t(\pi_s^*||\pi_s) = \mathbb{E}_{a \sim \pi_s}[A_{\pi^*,t}(s, a)]$, as in value aggregation (AGGREVATE) (Ross & Bagnell, 2014).

Without loss of generality, let us suppose $D_t(\pi_s^*||\pi_s) = \mathbb{E}_{a \sim \pi_s}[\bar{c}_t(s, a)]$ for some \bar{c}_t . Online IL converts policy optimization into online learning with per-round loss

$$l_n(\pi) \coloneqq \mathbb{E}_{d_{\pi_n}} \mathbb{E}_{\pi}[\bar{c}]. \tag{4}$$

By the inequality above, it holds that $J(\pi_n) - J(\pi^*) \le C_{\pi^*} l_n(\pi_n)$ for every *n*, establishing the reduction below.

Lemma 2. (Cheng et al., 2019) For l_n defined in (4), $\mathbb{E}\left[\sum_{n=1}^{N} \frac{w_n J(\pi_n)}{w_{1:N}}\right] \leq J(\pi^*) + C_{\pi^*} \mathbb{E}\left[\epsilon_{\Pi,N}(l) + \frac{Regret_N(\tilde{l})}{w_{1:N}}\right],$ where the expectation is due to sampling \tilde{l}_n .

That is, when a no-regret algorithm is used, the performance concentrates toward $J(\pi^*) + C_{\pi^*} \mathbb{E}[\epsilon_{\Pi,N}(l)]$.

3.2. RL as Online Learning

Can we also formulate RL as online learning? Here we propose a new perspective on RL using Lemma 1. Given a policy π_n in round *n*, we define a per-round loss

$$l_n(\pi) \coloneqq \mathbb{E}_{d_{\pi_n}} \mathbb{E}_{\pi}[A_{\pi_{n-1}}]. \tag{5}$$

which describes how well a policy π performs relative to the previous policy π_{n-1} under the state distribution of π_n . By Lemma 1, for l_n defined in (5), $l_n(\pi_n) = J(\pi_n) -$ $J(\pi_{n-1})$ for every *n*, similar to the pointwise inequality of l_n that Lemma 2 is based on. With this observation, we derive the reduction below (proved in Appendix B).

Lemma 3. Suppose $\frac{w_{n+k}}{w_n} \leq \frac{w_{m+k}}{w_m}$, for all $n \geq m \geq 1$ and $k \geq 0$. For (5) and any π_0 , $\mathbb{E}[\sum_{n=1}^N \frac{w_n J(\pi_n)}{w_{1:N}}] \leq J(\pi_0) + \sum_{n=1}^N \frac{w_{N-n+1}}{w_{1:N}} \mathbb{E}[Regret_n(\tilde{l}) + w_{1:n}\epsilon_{\Pi,n}(l)]$, where the expectation is due to sampling \tilde{l}_n .

3.2.1. INTERPRETATIONS

Lemma 3 is a policy improvement lemma, which shows that when the learning algorithm is no-regret, the policy sequence improves on-average from the initial reference policy π_0 that defines l_1 . This is attributed to an important property of the definition in (5) that $\min_{\pi \in \Pi} l_n(\pi) \leq 0$. To see this, suppose $\mathbb{E}[\epsilon_{\Pi,n}(l)] \leq -\Omega(1)$ (i.e. there is a policy that is better than all previous n policies); this is true for small n or when the policy sequence is concentrated. Under this assumption, if $w_n = 1$ and $\text{Regret}_n(\tilde{l}) \leq O(\sqrt{n})$, then the average performance improves roughly $N\mathbb{E}[\epsilon_{\Pi,N}(l)]$ away from $J(\pi_0)$.

While it is unrealistic to expect $\mathbb{E}[\epsilon_{\Pi,n}(l)] \leq 0$ for large n, we can still use Lemma 3 to comprehend *global* properties of policy improvement, for two reasons. First, the inequality in Lemma 3 holds for any interval of the policy sequence. Second, as we show in Appendix B, the Lemma 3 also applies to dynamic regret (Zinkevich, 2003), with respect to which $\mathbb{E}[\epsilon_{\Pi,n}(l)]$ is always negative. Therefore, if an algorithm is strongly-adaptive (Daniely et al., 2015) (i.e. it is no-regret for any interval) or has sublinear dynamic regret (Jadbabaie et al., 2015), then its generated policy sequence will strictly, non-asymptotically improve. In other words, for algorithms with a stronger notion of convergence, Lemma 3 describes the global improvement rate.

3.2.2. CONNECTIONS

The choice of per-round loss in (5) has an interesting relationship to both actor-critic in RL (Konda & Tsitsiklis, 2000) and AGGREVATE in IL (Ross & Bagnell, 2014).

Relationship to Actor-Critic Although actor-critic methods, theoretically, use $\mathbb{E}_{d_{\pi_n}}(\nabla \mathbb{E}_{\pi})[A_{\pi_n}]|_{\pi=\pi_n}$ to update policy π_n , in practice, they use $\mathbb{E}_{d_{\pi_n}}(\nabla \mathbb{E}_{\pi})[A_{\pi_{n-1}}]|_{\pi=\pi_n}$, because the advantage/value function estimate in round nis updated after the policy update in order to prevent bias due to over-fitting on finite samples (Sutton & Barto, 1998). This practical gradient is *exactly* $\nabla \tilde{l}_n(\pi_n)$, the sampled gradient of (5). Therefore, Lemma 3 explains the properties of these practical modifications.

Relationship to Value Aggregation AGGREVATE (Ross & Bagnell, 2014) can be viewed as taking a policy improvement step from some reference policy: e.g., with the

per-round loss $\mathbb{E}_{d_{\pi_n}}\mathbb{E}_{\pi}[A_{\pi^*}]$, it improves one step from π^* . Realizing this one step improvement in AGGREVATE, however, requires solving multiple rounds of online learning, as it effectively solves an equilibrium point problem (Cheng & Boots, 2018). Therefore, while ideally one can solve multiple AGGREVATE problems (one for each policy improvement step) to optimize policies, computationally this can be very challenging. Minimizing the loss in (5) can be viewed as an approximate policy improvement step in the AGGREVATE style. Rather than waiting until convergence in each AGGREVATE policy improvement step, it performs only a single policy update and then switches to the next AGGREVATE problem with a new reference policy (i.e. the latest policy π_{n-1}). This connection is particularly tightened if we choose $\pi_0 = \pi^*$ and the bound in Lemma 3 becomes relative to $J(\pi^*)$.

3.3. Predictability

An important property of the above online learning problems is that they are not completely adversarial, as pointed out by Cheng & Boots (2018) for IL. This can be seen from the definitions of l_n in (4) and (5), respectively. For example, suppose the cost c_t in the original RL problem (1) is known; then the information unknown before playing the decision π_n in the environment is only the state distribution d_{π_n} . Therefore, the per-round loss cannot be truly adversarial, as the same dynamics and cost functions are used across different rounds. That is, in an idealized case where the true dynamics and cost functions are exactly known, using the policy returned from a model-based RL algorithm would incur zero regret, since only the interactions with the real MDP environment, not the model, counts as rounds. We will exploit this property to design PICCOLO.

4. Predictor-Corrector Learning

We showed that the performance of RL and IL can be bounded by the regret of properly constructed predictable online learning problems. These results provide a foundation for designing policy optimization algorithms: efficient learning algorithms for policy optimization can be constructed from powerful online learning algorithms that achieve small regret. This perspective explains why common methods (e.g. mirror descent) based on gradients of (4) and (5) work well in IL and RL. However, the predictable nature of policy optimization problems suggests that directly applying these standard online learning algorithms designed for adversarial settings is *suboptimal*. The predictable information must be considered to achieve optimal convergence.

One way to include predictable information is to develop specialized two-step algorithms based on, e.g., mirror-prox or FTRL-prediction (Juditsky et al., 2011; Rakhlin & Sridharan, 2013a; Ho-Nguyen & Kılınç-Karzan, 2018). For IL, MOBIL was recently proposed (Cheng et al., 2019), which updates policies by approximate Be-the-Leader (Kalai & Vempala, 2005) and provably achieves faster convergence than previous methods. However, these two-step algorithms often have obscure and non-sequential update rules, and their adaptive and accelerated versions are less accessible (Diakonikolas & Orecchia, 2017). This can make it difficult to implement and tune them in practice.

Here we take an alternative, reduction-based approach. We present PICCOLO, a general first-order framework for solving predictable online learning problems. PICCOLO is a meta-algorithm that turns a base algorithm designed for adversarial problems into a new algorithm that can leverage the predictable information to achieve better performance. As a result, we can adopt sophisticated first-order adaptive algorithms to optimally learn policies, without reinventing the wheel. Specifically, given any first-order base algorithm belonging to the family of (adaptive) mirror descent and FTRL algorithms, we show how one can "PICCOLO it" to achieve a faster convergence rate without introducing additional performance bias due to prediction errors. Most first-order policy optimization algorithms belong to this family (Cheng et al., 2018), so we can PICCOLO these model-free algorithms into new hybrid algorithms that can robustly use (imperfect) predictive models, such as off-policy gradients and simulated gradients, to improve policy learning.

4.1. The PICCOLO Idea

The design of PICCOLO is based on the observation that an N-round predictable online learning problem can be written as a new adversarial problems with 2N rounds. To see this, let $\{l_n\}_{n=1}^N$ be the original predictable loss sequence. Suppose, before observing l_n , we have access to a model loss \hat{l}_n that contains the predictable information of l_n . Define $\delta_n = l_n - \hat{l}_n$. We can then write the accumulated loss (which regret concerns) as $\sum_{n=1}^N l_n(\pi_n) = \sum_{n=1}^N \hat{l}_n(\pi_n) + \delta_n(\pi_n)$. That is, we can view the predictable problem with $\{l_n\}_{n=1}^N$ as a new adversarial online learning problem with a loss sequence $\hat{l}_1, \delta_1, \hat{l}_2, \delta_2, \dots, \hat{l}_N, \delta_N$.

The idea of PICCOLO is to apply standard online learning algorithms designed for adversarial settings to this new 2N-round problem. This would create a new set of decision variables $\{\hat{\pi}_n\}_{n=1}^N$, in which $\hat{\pi}_n$ denotes the decision made before seeing \hat{l}_n , and leads to the following sequence $\pi_1, \delta_1, \hat{\pi}_2, \hat{l}_2, \pi_2, \delta_2, \ldots$ (in which we define $\delta_1 = l_1$). We show that when the base algorithm is optimal in adversarial settings, this simple strategy results in a decision sequence $\{\pi_n\}_{n=1}^N$ whose regret with respect to $\{l_n\}_{n=1}^N$ is optimal, just as those specialized two-step algorithms (Juditsky et al., 2011; Rakhlin & Sridharan, 2013a; Ho-Nguyen & Kılınç-Karzan, 2018). In Appendix A, we show PICCOLO unifies and generalize these two-step algorithms to be adaptive.

4.2. The Meta Algorithm PICCOLO

We provide details to realize this reduction. We suppose, in round n, the model loss is given as $\hat{l}_n(\pi) = \langle \hat{g}_n, \pi \rangle$ for some vector \hat{g}_n , and stochastic first-order feedback $g_n = \nabla \tilde{l}_n(\pi_n)$ from l_n is received. Though this linear form of model loss seems restrictive, later in Section 4.2.3 we will show that it is sufficient to represent predictable information.

4.2.1. BASE ALGORITHMS

We first give a single description of different base algorithms for the formal definition of the reduction steps. Here we limit our discussions to mirror descent and postpone the FTRL case to Appendix C. We assume that II is a convex compact subset in some normed space with norm $\|\cdot\|$, and we use $B_R(\pi || \pi') = R(\pi) - R(\pi') - \langle \nabla R(\pi'), \pi - \pi' \rangle$ to denote a Bregman divergence generated by a strictly convex function R, called the distance generator.

Mirror descent updates decisions based on proximal maps. In round n, given direction g_n and weight w_n , it executes

$$\pi_{n+1} = \arg\min_{\pi \in \Pi} \langle w_n g_n, \pi \rangle + B_{R_n}(\pi || \pi_n) \qquad (6)$$

where R_n is a strongly convex function; (6) reduces to gradient descent with step size η_n when $R_n(\cdot) = \frac{1}{2\eta_n} || \cdot ||^2$. More precisely, (6) is composed of two steps: 1) the update of the distance generator to R_n , and 2) the update of the decision to π_{n+1} ; different mirror descent algorithms differ in how the regularization is selected and adapted.

PICCOLO explicitly treats a base algorithm as the composition of two basic operations (this applies also to FTRL)

$$H_n = \operatorname{adapt}(h_n, H_{n-1}, g_n, w_n)$$

$$h_{n+1} = \operatorname{update}(h_n, H_n, g_n, w_n)$$
(7)

so that later it can recompose them to generate the new algorithm. For generality, we use h and H to denote the abstract representations of the decision variable and the regularization, respectively. In mirror descent, h is exactly the decision variable, H is the distance generator, and we can write update $(h, H, g, w) = \arg \min_{\pi' \in \Pi} \langle wg, \pi' \rangle + B_H(\pi'||h)$. The operation adapt denotes the algorithm-specific scheme for the regularization update (e.g. changing the step size), which in general updates the size of regularization to grow slowly and inversely proportional to the norm of g_n .

4.2.2. THE PICCOLOED ALGORITHM

PICCOLO generates decisions by applying a given base algorithm in (7) to the new problem with losses $\delta_1, \hat{l}_2, \delta_2, \ldots$. This is accomplished by recomposing the basic operations in (7) into the Prediction and the Correction Steps:

$$h_n = update(h_n, H_{n-1}, \hat{g}_n, w_n)$$
[Prediction]
$$H_n = adapt(h_n, H_{n-1}, e_n, w_n)$$
$$\hat{h}_{n+1} = update(h_n, H_n, e_n, w_n)$$
[Correction]

where \hat{h}_n is the abstract representation of $\hat{\pi}_n$, and $e_n = g_n - \hat{g}_n$ is the error direction. We can see that the Prediction and Correction Steps are exactly the update rules resulting from applying (7) to the new adversarial problem, except that only h_n is updated in the Prediction Step, *not* the regularization (i.e. the step size). This asymmetry design is important for achieving optimal regret, because in the end we care only about the regret of $\{\pi_n\}$ on the original loss sequence $\{l_n\}$.

In round n, the "PICCOLOed" algorithm first performs the Prediction Step using \hat{g}_n to generate the learner's decision (i.e. π_n) and runs this new policy in the environment to get the true gradient g_n . Using this feedback, the algorithm performs the Correction Step to amend the bias of using \hat{g}_n . This is done by first adapting the regularization to H_n and then updating π_n to $\hat{\pi}_{n+1}$ along the error $e_n = g_n - \hat{g}_n$.

4.2.3. MODEL LOSSES AND PREDICTIVE MODELS

The Prediction Step of PICCOLO relies on the vector \hat{g}_n to approximate the future gradient g_n . Here we discuss different ways to specify \hat{g}_n based on the concept of predictive models (Cheng et al., 2019). A *predictive model* Φ_n is a first-order oracle such that $\Phi_n(\cdot)$ approximates $\nabla l_n(\cdot)$. In practice, a predictive model can be a simulator with an (online learned) dynamics model (Tan et al., 2018; Deisenroth & Rasmussen, 2011), or a neural network trained to predict the required gradients (Silver et al., 2017; Oh et al., 2017). An even simpler heuristic is to construct predictive models by *off-policy* gradients $\Phi_n(\cdot) = \sum_{m=n-K}^{n-1} \nabla \tilde{l}_m(\cdot)$ where K is the buffer size.

In general, we wish to set \hat{g}_n to be close to g_n , as we will later show in Section 5 that the convergence rate of PIC-CoLO depends on their distance. However, even when we have perfect predictive models, this is still a non-trivial task. We face a chicken-or-the-egg problem: g_n depends on π_n , which in turn depends on \hat{g}_n from the Prediction Step.

Cheng et al. (2019) show one effective heuristic is to set $\hat{g}_n = \Phi_n(\hat{\pi}_n)$, because we may treat $\hat{\pi}_n$ as an estimate of π_n . However, due to the mismatch between $\hat{\pi}_n$ and π_n , this simple approach has errors even when the predictive model is perfect. To better leverage a given predictive model, we propose to solve for \hat{g}_n and π_n simultaneously. That is, we wish to solve a fixed-point problem, finding h_n such that

$$h_n = update(h_n, H_{n-1}, \Phi_n(\pi_n(h_n)), w_n)$$
(8)

The exact formulation of the fixed-point problem depends on the class of base algorithms. For mirror descent, it is a variational inequality: find $\pi_n \in \Pi$ such that $\forall \pi \in \Pi$, $\langle \Phi_n(\pi_n) + \nabla R_{n-1}(\pi_n) - \nabla R_{n-1}(\hat{\pi}_n), \pi - \pi_n \rangle \ge 0$. In a special case when $\Phi_n = \nabla f_n$ for some function f_n , the above variational inequality is equivalent to finding a stationary point of the optimization problem $\min_{\pi \in \Pi} f_n(\pi) + B_{R_{n-1}}(\pi || \hat{\pi}_n)$. In other words, one way to implement the

Algorithm 1 PICCOLO

Input: policy π_1 , cost sequence $\{\psi_n\}$, regularization H_0 , model Φ_1 , iteration N, exponent p

- **Output:** $\bar{\pi}_N$
- 1: Set $\hat{\pi}_1 = \pi_1$ and weights $w_n = n^p$
- 2: Sample integer $K \in [1, N]$ with $P(K = n) \propto w_n$
- 3: for $n = 1 \dots K 1^{\dagger}$ do
- 4: $\pi_n, \hat{g}_n = \operatorname{PredictionStep}(\hat{\pi}_n, \Phi_n, H_{n-1}, w_n)$
- 5: $\mathcal{D}_n, g_n = \text{DataCollection}(\pi_n)$ 6: $H_n, \hat{\pi}_{n+1} = \text{CorrectionStep}(\pi_n, e_n, H_{n-1}, w_n),$
- where $e_n = g_n \hat{g}_n$. 7: $\Phi_{n+1} = \text{ModelUpdate}(\Phi_n, \mathcal{D})$, where $\mathcal{D} = \mathcal{D} \bigcup \mathcal{D}_n$.
- 8: end for
- 9: Set $\bar{\pi}_N = \pi_{K-1}$

Prediction Step is to solve the above minimization problem for π_n and use $\nabla f_n(\pi_n)$ as the effective prediction \hat{g}_n .

4.3. Summary: Why Does PICCOLO Work?

We provide a summary of the full algorithm for policy optimization in Algorithm 1. We see that PICCOLO uses the predicted gradient to take an extra step to accelerate learning, and, meanwhile, to prevent the error accumulation, it adaptively adjusts the step size (i.e. the regularization) based on the prediction error and corrects for the bias on the policy right away. To gain some intuition, let us consider ADAGRAD (Duchi et al., 2011) as a base algorithm¹:

$$G_n = G_{n-1} + \operatorname{diag}(w_n g_n \odot w_n g_n)$$

$$\pi_{n+1} = \operatorname*{arg\,min}_{\pi \in \Pi} \langle w_n g_n, \pi \rangle + \frac{1}{2\eta} (\pi - \pi_n)^\top G_n^{1/2} (\pi - \pi_n)$$

where $G_0 = \epsilon I$ and $\eta, \epsilon > 0$, and \odot denotes elementwise multiplication. This update has an adapt operation as adapt $(h, H, g, w) = G + \text{diag}(wg \odot wg)$ which updates the Bregman divergence based on the gradient size.

PICCOLO transforms ADAGRAD into a new algorithm. In the Prediction Step, it performs

$$\pi_n = \operatorname*{arg\,min}_{\pi \in \Pi} \langle w_n \hat{g}_n, \pi \rangle + \frac{1}{2\eta} (\pi - \pi_{n-1})^\top G_{n-1}^{1/2} (\pi - \pi_{n-1})$$

In the Correction Step, it performs

$$G_n = G_{n-1} + \operatorname{diag}(w_n e_n \odot w_n e_n)$$
$$\hat{\pi}_{n+1} = \operatorname*{arg\,min}_{\pi \in \Pi} \langle w_n e_n, \pi \rangle + \frac{1}{2\eta} (\pi - \hat{\pi}_n)^\top G_n^{1/2} (\pi - \hat{\pi}_n)$$

We see that the PICCOLO-ADAGRAD updates G_n proportional to the prediction error e_n instead of g_n . It takes larger steps when models are accurate, and decreases the step size once the prediction deviates. As a result, PICCOLO is robust to model quality: it accelerates learning when the model is informative, and prevents inaccurate (potentially adversarial) models from hurting the policy. We will further demonstrate this in theory and in the experiments.

¹We provide another example in Appendix E.

[†]Here we assume project is automatically performed inside PredictionStep and CorrectionStep.

5. Theoretical Analysis

In this section, we show that PICCOLO has two major benefits over previous approaches: 1) it accelerates policy learning when the models predict the required gradient well on average; and 2) it does not bias the performance of the policy, even when the prediction is incorrect.

To analyze PICCOLO, we introduce an assumption to quantify the adapt operator of a base algorithm.

Assumption 1. adapt chooses a regularization sequence such that, for some $M_N = o(w_{1:N})$, $||H_0||_{\mathcal{R}} + \sum_{n=1}^N ||H_n - H_{n-1}||_{\mathcal{R}} \le M_N$ for some norm $|| \cdot ||_{\mathcal{R}}$ which measures the size of regularization.

This assumption, which requires the regularization to increase slower than the growth of $w_{1:N}$, is satisfied by most reasonably-designed base algorithms. For example, in a uniformly weighted problem, gradient descent with a decaying step size $O(\frac{1}{\sqrt{n}})$ has $M_N = O(\sqrt{N})$. In general, for stochastic problems, an optimal base algorithm would ensure $M_N = O(\frac{w_{1:N}}{\sqrt{N}})$.

5.1. Convergence Properties

Now we state the main result, which quantifies the regret of PICCOLO with respect to the sequence of linear loss functions that it has access to. The proof is given in Appendix F.

Theorem 1. Suppose H_n defines a strongly convex function with respect to $\|\cdot\|_n$. Under Assumption 1, running PICCOLO ensures $\sum_{n=1}^N \langle w_n g_n, \pi_n - \pi \rangle \leq M_N + \sum_{n=1}^N \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - \frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2$, for all $\pi \in \Pi$.

The term $||e_n||_{*,n}^2$ in Theorem 1 says that the performance of PICCOLO depends on how well the base algorithm adapts to the error e_n through the adapt operation in the Correction Step. Usually adapt updates H_n gradually (Assumption 1) while minimizing $\frac{1}{2} ||e_n||_{*,n}^2$, like we showed in ADAGRAD.

In general, when the base algorithm is adaptive and optimal for adversarial problems, we show in Appendix G that its PICCOLOed version guarantees that $\mathbb{E}[\sum_{n=1}^{N} \langle w_n g_n, \pi_n - \pi \rangle] \leq O(1) + C_{\Pi,\Phi} \frac{w_{1:N}}{\sqrt{N}}$, where $C_{\Pi,\Phi} = O(|\Pi| + E_{\Phi} + \sigma_g^2 + \sigma_{\hat{g}}^2)$ is some constant related to the diameter of Π (denoted as $|\Pi|$), the model bias E_{Φ} , and the sampling variance σ_g^2 and $\sigma_{\hat{g}}^2$ of g_n and \hat{g}_n , respectively. Through Lemma 2 and 3, this bound directly implies accelerated and bias-free policy performance.

Theorem 2. Suppose \tilde{l}_n is convex³ and $w_n \ge \Omega(1)$. Then running PICCOLO yields $\mathbb{E}[Regret_n(\tilde{l})/w_{1:N}] = O(\frac{C_{\Pi,\Phi}}{\sqrt{N}})$, where $C_{\Pi,\Phi} = O(|\Pi| + E_{\Phi} + \sigma_g^2 + \sigma_{\hat{q}}^2) = O(1)$.

³The convexity assumption is standard, as used in (Duchi et al., 2011; Ross et al., 2011; Kingma & Ba, 2015; Cheng & Boots,

UPPER BOUNDS IN BIG-O
$\frac{1}{\sqrt{N}}\left(\Pi + \sigma_g^2 + \sigma_{\hat{g}}^2 + E_{\Phi}\right)$
$\frac{1}{\sqrt{N}}\left(\Pi +G_g^2+\sigma_g^2\right)$
$\frac{1}{\sqrt{N}} \left(\Pi + G_{\hat{g}}^2 + \sigma_{\hat{g}}^2 \right) + E_{\Phi}$
$\frac{1}{\sqrt{2N}} \left(\Pi + \frac{1}{2} \left(G_g^2 + G_{\hat{g}}^2 + \sigma_g^2 + \sigma_{\hat{g}}^2 \right) + E_{\Phi} \right)$

Table 1: Upper bounds of the average regret of different policy optimization algorithms.

5.2. Comparison

To appreciate the advantages of PICCOLO, we review several policy optimization algorithms and compare their regret. We show that they can be viewed as incomplete versions of PICCOLO, which only either result in accelerated learning *or* are unbiased, but not both (see in Table 1).

We first consider the common model-free approach (Sutton et al., 2000; Kakade, 2002; Peters & Schaal, 2008; Peters et al., 2010; Silver et al., 2014; Sun et al., 2017; Cheng et al., 2018), i.e. applying the base algorithm with g_n . To make the comparison concrete, suppose $||\mathbb{E}[g_n]||_*^2 \leq G_g^2$ for some constant G_g , where we recall g_n is the sampled true gradient. As the model-free approach is equivalent to setting $\hat{g}_n = 0$ in PICCOLO, by Theorem 1 (with $e_n = g_n$), the constant C_{Π} in Theorem 2 would become $O(|\Pi| + G_g^2 + \sigma_g^2)$. In other words, PICCOLOing the base algorithm improves the constant factor from G_g^2 to $\sigma_{\hat{g}}^2 + E_{\Phi}$. Therefore, while the model-free approach is bias-free, its convergence can be further improved by PICCOLO, as long as the models { Φ_n } are reasonably accurate on average.⁴

Next we consider the pure model-based approach with a model that is potentially learned online (Jacobson & Mayne, 1970; Todorov & Li, 2005; Deisenroth & Rasmussen, 2011; Pan & Theodorou, 2014; Levine & Koltun, 2013; Sun et al., 2018). As this approach is equivalent to only performing the Prediction Step⁵, its performance suffers from any modeling error. Specifically, suppose $||\mathbb{E}[\hat{g}_n]||_*^2 \leq G_{\hat{g}}^2$ for some constant $G_{\hat{g}}$. One can show that the bound in Theorem 2 would become $O((|\Pi| + G_{\hat{g}}^2 + \sigma_{\hat{g}}^2)/\sqrt{N} + E_{\Phi})$, introducing a constant bias in $O(E_{\Phi})$.

A hybrid heuristic to combine the model-based and modelfree updates is DYNA (Sutton, 1991; Sutton et al., 2012), which interleaves the two steps during policy optimization. This is equivalent to applying g_n , instead of the error e_n , in the Correction Step of PICCOLO. Following a similar

⁵These algorithms can be realized by the fixed-point formulation of the Prediction Step with (arbitrarily small) regularization.



Figure 1: Performance of PICCOLO with different predictive models. x axis is iteration number and y axis is sum of rewards. The curves are the median among 8 runs with different seeds, and the shaded regions account for 25% percentile. ADAM is used as the base algorithm, and the update rule, by default, is PICCOLO; e.g. TRUEDYN in (a) refers to PICCOLO with TRUEDYN predictive model. (a) Comparison of PICCOLO and DYNA with adversarial model. (b) PICCOLO with the fixed-point setting (8) with dynamics model in different fidelities. BIASEDDYN0.8 indicates that the mass of each individual robot link is either increased or decreased by 80% with probability 0.5 respectively.

analysis as above, one can show that the convergence rate in Theorem 2 would become $O((|\Pi| + G^2 + \sigma^2)/\sqrt{2N} + E_{\Phi})$, where $G^2 = \frac{1}{2}(G_g^2 + G_{\hat{g}}^2)$ and $\sigma^2 = \frac{1}{2}(\sigma_g^2 + \sigma_{\hat{g}}^2)$. Therefore, DYNA is effectively twice as fast as the pure model-free approach when the model is accurate. However, it would eventually suffer from the performance bias due model error, as reflected in the term E_{Φ} . We will demonstrate this property experimentally in Figure 1.

Finally, we note that the idea of using Φ_n as control variate (Chebotar et al., 2017; Grathwohl et al., 2018; Papini et al., 2018) is orthogonal to the setups considered above, and it can be naturally combined with PICCOLO. For example, we can also use Φ_n to compute a better sampled gradient g_n with smaller variance (line 5 of Algorithm 1). This would improve σ_g^2 in the bounds of PICCOLO to a smaller $\tilde{\sigma}_a^2$, the size of reduced variance.

6. Experiments

We corroborate our theoretical findings with experiments⁶ in learning neural network policies to solve robot RL tasks (CartPole, Hopper, Snake, and Walker3D) from OpenAI Gym (Brockman et al., 2016) with the DART physics engine (Lee et al., 2018)⁷. The aim is to see if PICCOLO improves the performance of a base algorithm, even though in these experiments the convexity assumption in the theory does not hold. We choose several popular first-order mirror

^{2018),} which holds for tabular problems as well as some special cases, like continuous-time problems (cf. (Cheng & Boots, 2018)).

⁴It can be shown that if the model is learned online with a no-regret algorithm, it would perform similarly to the best model in the hindsight (cf. Appendix G.4)

⁶The codes are available at https://github.com/gtrll/rlfamily.

⁷The environments are defined in DartEnv, hosted at https://github.com/DartEnv.



Figure 2: Performance of PICCOLO in various tasks. x axis is iteration number and y axis is sum of rewards. The curves are the median among 8 runs with different seeds, and the shaded regions account for 25% percentile.

descent base algorithms (ADAM (Kingma & Ba, 2015), natural gradient descent NATGRAD (Kakade, 2002), and trust-region optimizer TRPO (Schulman et al., 2015)). We compute g_n by GAE (Schulman et al., 2016). For predictive models, we consider off-policy gradients (with the samples of the last iteration LAST or a replay buffer REPLAY) and gradients computed through simulations with the true or biased dynamics models (TRUEDYN or BIASEDDYN). We will label a model with FP if \hat{g}_n is determined by the fixedpoint formulation (8)⁸; otherwise, $\hat{g}_n = \Phi_n(\hat{\pi}_n)$. Please refer to Appendix H for the details.

In Figure 1, we first use CartPole to study Theorem 2, which suggests that PICCOLO is unbiased and improves the performance when the prediction is accurate. Here we additionally consider an extremely bad model, ADVERSARIAL, that predicts the gradients adversarially.⁹ Figure 1 (a) illustrates the performance of PICCOLO and DYNA, when ADAM is chosen as the base algorithm. We observe that PICCOLO improves the performance when the model is accurate (i.e. TRUEDYN). Moreover, PICCOLO is robust to modeling errors. It still converges when the model is adversarially attacking the algorithm, whereas DYNA fails completely. In Figure 1 (b), we conduct a finer comparison of the effects of different model accuracies (BIASEDDYN-FP), when \hat{q}_n is computed using (8). To realize inaccurate dynamics models to be used in the Prediction step, we change the mass of links of the robot by a certain factor, e.g. BIASEDDYN0.8 indicates that the mass of each individual link is either increased or decreased by 80% with probability 0.5, respectively. We see that the fixed-point formulation (8), which makes multiple queries of Φ_n for computing \hat{g}_n , performs much better than the heuristic of setting $\hat{g}_n = \Phi(\hat{\pi}_n)$, even when the latter is using the true model (TRUEDYN). Overall, we see PICCOLO with BIASEDDYN-FP is able to accelerate learning, though with a degree varying with model accuracies; but even for models with a large bias, it still converges

⁸In implementation, we solve the corresponding optimization problem with a few number of iterations. For example, BIASEDDYN-FP is approximatedly solved with 5 iterations. unbiasedly, as we previously observed in Figure 1 (a),

In Figure 2, we study the performance of PICCOLO in a range of environments. In general, we find that PICCOLO indeed improves the performance¹⁰ though the exact degree depends on how \hat{g}_n is computed. In Figure 2 (a) and (b), we show the results of using ADAM as the base algorithm. We observe that, while setting $\hat{g}_n = \Phi_n(\hat{\pi}_n)$ is already an effective heuristic, the performance of PICCOLO can be further and largely improved if we adopt the fixed-point strategy in (8), as the latter allows the learner to take more globally informed update directions. Finally, to demonstrate the flexibility of the proposed framework, we also "PICCOLO" two other base algorithms, NATGRAD and TRPO, in Figure 2 (c) and (d), respectively. The complete set of experimental results can be found in Appendix H.

7. Conclusion

PICCOLO is a general reduction-based framework for solving predictable online learning problems. It can be viewed as an automatic strategy for generating new algorithms that can leverage prediction to accelerate convergence. Furthermore, PICCOLO uses the Correction Step to recover from the mistake made in the Prediction Step, so the presence of modeling errors does not bias convergence, as we show in both the theory and experiments. The design of PICCOLO leaves open the question of how to design good predictive models. While PICCOLO is robust against modeling error, the accuracy of a predictive model can affect its effectiveness. PICCOLO only improves the performance when the model can make non-trivial predictions. In the experiments, we found that off-policy and simulated gradients are often useful, but they are not perfect. It would be interesting to see whether a predictive model that is trained to directly minimize the prediction error can further help policy learning. Finally, we note that, despite the focus of this paper on policy optimization, PICCOLO can naturally be applied to other optimization and learning problems.

⁹We set $\hat{g}_{n+1} = -(\max_{m=1,...,n} \|g_m\| / \|g_n\|) g_n$.

¹⁰Note that different base algorithms are not directly comparable, as further fine-tuning of step sizes is required.

Acknowledgements

This research is supported in part by NSF NRI 1637758 and NSF CAREER 1750483.

References

- Amari, S.-I. Natural gradient works efficiently in learning. *Neural computation*, 10(2):251–276, 1998.
- Amos, B., Jimenez, I., Sacks, J., Boots, B., and Kolter, J. Z. Differentiable MPC for end-to-end planning and control. In Advances in Neural Information Processing Systems, pp. 8299–8310, 2018.
- Anthony, T., Tian, Z., and Barber, D. Thinking fast and slow with deep learning and tree search. In *Advances in Neural Information Processing Systems*, pp. 5360–5370, 2017.
- Beck, A. and Teboulle, M. Mirror descent and nonlinear projected subgradient methods for convex optimization. *Operations Research Letters*, 31(3):167–175, 2003.
- Brockman, G., Cheung, V., Pettersson, L., Schneider, J., Schulman, J., Tang, J., and Zaremba, W. OpenAI Gym. *arXiv preprint arXiv:1606.01540*, 2016.
- Chebotar, Y., Hausman, K., Zhang, M., Sukhatme, G., Schaal, S., and Levine, S. Combining model-based and model-free updates for trajectory-centric reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 703–711, 2017.
- Cheng, C.-A. and Boots, B. Convergence of value aggregation for imitation learning. In *International Conference on Artificial Intelligence and Statistics*, volume 84, pp. 1801–1809, 2018.
- Cheng, C.-A., Yan, X., Wagener, N., and Boots, B. Fast policy learning through imitation and reinforcement. In *Proceedings of the 34th Conference on Uncertanty in Artificial Intelligence*, pp. 845–855, 2018.
- Cheng, C.-A., Yan, X., Theodorou, E., and Boots, B. Accelerating imitation learning with predictive models. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2019.
- Chiang, C.-K., Yang, T., Lee, C.-J., Mahdavi, M., Lu, C.-J., Jin, R., and Zhu, S. Online optimization with gradual variations. In *Conference on Learning Theory*, pp. 6–1, 2012.
- Daniely, A., Gonen, A., and Shalev-Shwartz, S. Strongly adaptive online learning. In *International Conference on Machine Learning*, pp. 1405–1411, 2015.

- Deisenroth, M. and Rasmussen, C. E. Pilco: A modelbased and data-efficient approach to policy search. In *International Conference on machine learning*, pp. 465– 472, 2011.
- Diakonikolas, J. and Orecchia, L. Accelerated extra-gradient descent: A novel accelerated first-order method. *arXiv* preprint arXiv:1706.04680, 2017.
- Duan, Y., Chen, X., Houthooft, R., Schulman, J., and Abbeel, P. Benchmarking deep reinforcement learning for continuous control. In *International Conference on Machine Learning*, pp. 1329–1338, 2016.
- Duchi, J., Hazan, E., and Singer, Y. Adaptive subgradient methods for online learning and stochastic optimization. *Journal of Machine Learning Research*, 12(Jul):2121– 2159, 2011.
- Gordon, G. J. Regret bounds for prediction problems. In *Annual Conference on Computational Learning Theory*, pp. 29–40. ACM, 1999.
- Grathwohl, W., Choi, D., Wu, Y., Roeder, G., and Duvenaud, D. Backpropagation through the void: Optimizing control variates for black-box gradient estimation. In *International Conference on Learning Representations*, 2018.
- Gupta, V., Koren, T., and Singer, Y. A unified approach to adaptive regularization in online and stochastic optimization. *arXiv preprint arXiv:1706.06569*, 2017.
- Hazan, E., Agarwal, A., and Kale, S. Logarithmic regret algorithms for online convex optimization. *Machine Learning*, 69(2-3):169–192, 2007.
- Hazan, E. et al. Introduction to online convex optimization. Foundations and Trends® in Optimization, 2(3-4):157– 325, 2016.
- Ho-Nguyen, N. and Kılınç-Karzan, F. Exploiting problem structure in optimization under uncertainty via online convex optimization. *Mathematical Programming*, pp. 1–35, 2018.
- Jacobson, D. H. and Mayne, D. Q. Differential dynamic programming. 1970.
- Jadbabaie, A., Rakhlin, A., Shahrampour, S., and Sridharan, K. Online optimization: Competing with dynamic comparators. In *Artificial Intelligence and Statistics*, pp. 398–406, 2015.
- Juditsky, A., Nemirovski, A., and Tauvel, C. Solving variational inequalities with stochastic mirror-prox algorithm. *Stochastic Systems*, 1(1):17–58, 2011.

- Kakade, S. and Langford, J. Approximately optimal approximate reinforcement learning. In *International Conference* on Machine Learning, volume 2, pp. 267–274, 2002.
- Kakade, S. M. A natural policy gradient. In Advances in neural information processing systems, pp. 1531–1538, 2002.
- Kalai, A. and Vempala, S. Efficient algorithms for online decision problems. *Journal of Computer and System Sciences*, 71(3):291–307, 2005.
- Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.
- Konda, V. R. and Tsitsiklis, J. N. Actor-critic algorithms. In Advances in neural information processing systems, pp. 1008–1014, 2000.
- Korpelevich, G. The extragradient method for finding saddle points and other problems. *Matecon*, 12:747–756, 1976.
- Lee, J., Grey, M. X., Ha, S., Kunz, T., Jain, S., Ye, Y., Srinivasa, S. S., Stilman, M., and Liu, C. K. DART: Dynamic animation and robotics toolkit. *The Journal of Open Source Software*, 3(22):500, feb 2018.
- Levine, S. and Koltun, V. Guided policy search. In *In*ternational Conference on Machine Learning, pp. 1–9, 2013.
- McMahan, H. B. A survey of algorithms and analysis for adaptive online learning. *The Journal of Machine Learning Research*, 18(1):3117–3166, 2017.
- McMahan, H. B. and Streeter, M. Adaptive bound optimization for online convex optimization. In COLT 2010 - The 23rd Conference on Learning Theory, 2010.
- Mnih, V., Kavukcuoglu, K., Silver, D., Graves, A., Antonoglou, I., Wierstra, D., and Riedmiller, M. Playing atari with deep reinforcement learning. *arXiv preprint* arXiv:1312.5602, 2013.
- Nemirovski, A. Prox-method with rate of convergence o (1/t) for variational inequalities with lipschitz continuous monotone operators and smooth convex-concave saddle point problems. *SIAM Journal on Optimization*, 15(1): 229–251, 2004.
- Nesterov, Y. *Introductory lectures on convex optimization: A basic course*, volume 87. Springer Science & Business Media, 2013.
- Oh, J., Singh, S., and Lee, H. Value prediction network. In *Advances in Neural Information Processing Systems*, pp. 6120–6130, 2017.

- Pan, Y. and Theodorou, E. Probabilistic differential dynamic programming. In Advances in Neural Information Processing Systems, pp. 1907–1915, 2014.
- Papini, M., Binaghi, D., Canonaco, G., Pirotta, M., and Restelli, M. Stochastic variance-reduced policy gradient. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 4023–4032, 2018.
- Pascanu, R., Li, Y., Vinyals, O., Heess, N., Buesing, L., Racanière, S., Reichert, D., Weber, T., Wierstra, D., and Battaglia, P. Learning model-based planning from scratch. *arXiv preprint arXiv:1707.06170*, 2017.
- Peters, J. and Schaal, S. Natural actor-critic. *Neurocomput*ing, 71(7-9):1180–1190, 2008.
- Peters, J., Mülling, K., and Altun, Y. Relative entropy policy search. In *AAAI*, pp. 1607–1612. Atlanta, 2010.
- Rakhlin, A. and Sridharan, K. Online learning with predictable sequences. In COLT 2013 - The 26th Annual Conference on Learning Theory, pp. 993–1019, 2013a.
- Rakhlin, S. and Sridharan, K. Optimization, learning, and games with predictable sequences. In Advances in Neural Information Processing Systems, pp. 3066–3074, 2013b.
- Reddi, S. J., Kale, S., and Kumar, S. On the convergence of adam and beyond. In *International Conference on Learning Representations*, 2018.
- Ross, S. and Bagnell, J. A. Reinforcement and imitation learning via interactive no-regret learning. *arXiv preprint arXiv:1406.5979*, 2014.
- Ross, S., Gordon, G., and Bagnell, D. A reduction of imitation learning and structured prediction to no-regret online learning. In *International conference on artificial intelligence and statistics*, pp. 627–635, 2011.
- Schulman, J., Levine, S., Abbeel, P., Jordan, M., and Moritz, P. Trust region policy optimization. In *International Conference on Machine Learning*, pp. 1889–1897, 2015.
- Schulman, J., Moritz, P., Levine, S., Jordan, M., and Abbeel, P. High-dimensional continuous control using generalized advantage estimation. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2016.
- Silver, D., Lever, G., Heess, N., Degris, T., Wierstra, D., and Riedmiller, M. Deterministic policy gradient algorithms. In *Proceedings of the 31th International Conference on Machine Learning*, pp. 387–395, 2014.
- Silver, D., van Hasselt, H., Hessel, M., Schaul, T., Guez, A., Harley, T., Dulac-Arnold, G., Reichert, D., Rabinowitz, N., Barreto, A., et al. The predictron: End-to-end learning and planning. In *Proceedings of the 34th International Conference on Machine Learning*, 2017.

- Silver, D., Hubert, T., Schrittwieser, J., Antonoglou, I., Lai, M., Guez, A., Lanctot, M., Sifre, L., Kumaran, D., Graepel, T., Lillicrap, T., Simonyan, K., and Hassabis, D. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362 (6419):1140–1144, 2018. ISSN 0036-8075.
- Srinivas, A., Jabri, A., Abbeel, P., Levine, S., and Finn, C. Universal planning networks: Learning generalizable representations for visuomotor control. In *Proceedings of the 35th International Conference on Machine Learning*, 2018.
- Sun, W., Venkatraman, A., Gordon, G. J., Boots, B., and Bagnell, J. A. Deeply aggrevated: Differentiable imitation learning for sequential prediction. In *Proceedings of the 34th International Conference on Machine Learning*, pp. 3309–3318, 2017.
- Sun, W., Gordon, G. J., Boots, B., and Bagnell, J. A. Dual policy iteration. In *Advances in Neural Information Processing Systems 31*, pp. 7059–7069, 2018.
- Sutton, R. S. Dyna, an integrated architecture for learning, planning, and reacting. *ACM SIGART Bulletin*, 2(4): 160–163, 1991.
- Sutton, R. S. and Barto, A. G. Introduction to reinforcement learning, volume 135. MIT press Cambridge, 1998.
- Sutton, R. S., McAllester, D. A., Singh, S. P., and Mansour, Y. Policy gradient methods for reinforcement learning with function approximation. In *Advances in Neural Information Processing Systems*, pp. 1057–1063, 2000.
- Sutton, R. S., Szepesvári, C., Geramifard, A., and Bowling, M. P. Dyna-style planning with linear function approximation and prioritized sweeping. arXiv preprint arXiv:1206.3285, 2012.
- Tan, J., Zhang, T., Coumans, E., Iscen, A., Bai, Y., Hafner, D., Bohez, S., and Vanhoucke, V. Sim-to-real: Learning agile locomotion for quadruped robots. In *Robotics: Science and Systems XIV*, 2018.
- Tieleman, T. and Hinton, G. Lecture 6.5-rmsprop: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural networks for machine learning*, 4 (2):26–31, 2012.
- Todorov, E. and Li, W. A generalized iterative LQG method for locally-optimal feedback control of constrained nonlinear systems. In *American Control Conference*, pp. 300–306. IEEE, 2005.
- Zeiler, M. D. Adadelta: an adaptive learning rate method. *arXiv preprint arXiv:1212.5701*, 2012.

Zinkevich, M. Online convex programming and generalized infinitesimal gradient ascent. In *International Conference* on Machine Learning, pp. 928–936, 2003.

A. Relationship between PICCOLO and Existing Algorithms

We discuss how the framework of PICCOLO unifies existing online learning algorithms and provides their natural adaptive generalization. To make the presentation clear, we summarize the effective update rule of PICCOLO when the base algorithm is mirror descent

$$\pi_{n} = \underset{\pi \in \Pi}{\arg\min} \langle w_{n}\hat{g}_{n}, \pi \rangle + B_{R_{n-1}}(\pi || \hat{\pi}_{n})$$

$$\hat{\pi}_{n+1} = \underset{\pi \in \Pi}{\arg\min} \langle w_{n}e_{n}, \pi \rangle + B_{R_{n}}(\pi || \pi_{n})$$
(9)

and that when the base algorithm is FTRL,

$$\pi_{n} = \underset{\pi \in \Pi}{\operatorname{arg\,min}} \langle w_{n} \hat{g}_{n}, \pi \rangle + \sum_{m=1}^{n-1} \langle w_{m} g_{m}, \pi \rangle + B_{r_{m}}(\pi || \pi_{m})$$

$$\hat{\pi}_{n+1} = \underset{\pi \in \Pi}{\operatorname{arg\,min}} \langle w_{n} e_{n}, \pi \rangle + B_{r_{n}}(\pi || \pi_{n}) + \langle w_{n} \hat{g}_{n}, \pi \rangle + \sum_{m=1}^{n-1} \langle w_{m} g_{m}, \pi \rangle + B_{r_{m}}(\pi || \pi_{m})$$
(10)

Because $e_n = g_n - \hat{g}_n$, PICCOLO with FTRL exactly matches the update rule (MOBIL) proposed by Cheng et al. (2018)

$$\pi_{n} = \underset{\pi \in \Pi}{\operatorname{arg\,min}} \langle w_{n} \hat{g}_{n}, \pi \rangle + \sum_{m=1}^{n-1} \langle w_{m} g_{m}, \pi \rangle + B_{r_{m}}(\pi || \pi_{m})$$

$$\hat{\pi}_{n+1} = \underset{\pi \in \Pi}{\operatorname{arg\,min}} \sum_{m=1}^{n} \langle w_{m} g_{m}, \pi \rangle + B_{r_{m}}(\pi || \pi_{m})$$
(11)

As comparisons, we consider existing two-step update rules, which in our notation can be written as follows:

• Extragradient descent (Korpelevich, 1976), mirror-prox (Nemirovski, 2004; Juditsky et al., 2011) or optimistic mirror descent (Chiang et al., 2012; Rakhlin & Sridharan, 2013a)

$$\pi_{n} = \underset{\pi \in \Pi}{\arg\min} \langle \hat{g}_{n}, \pi \rangle + B_{R}(\pi || \hat{\pi}_{n})$$

$$\hat{\pi}_{n+1} = \underset{\pi \in \Pi}{\arg\min} \langle g_{n}, \pi \rangle + B_{R}(\pi || \hat{\pi}_{n})$$
(12)

• FTRL-with-Prediction/optimistic FTRL (Rakhlin & Sridharan, 2013a)

$$\pi_n = \operatorname*{arg\,min}_{\pi \in \Pi} R(\pi) + \langle \hat{g}_n, \pi \rangle + \sum_{m=1}^{n-1} \langle w_m g_m, \pi \rangle \tag{13}$$

Let us first review the previous update rules. Originally extragradient descent (Korpelevich, 1976) and mirror prox (Nemirovski, 2004; Juditsky et al., 2011) were proposed to solve VIs (the latter is an extension to consider general Bregman divergences). As pointed out by Cheng et al. (2019), when applied to an online learning problem, these algorithms effectively assign \hat{g}_n to be the online gradient as if the learner plays a decision at $\hat{\pi}_n$. On the other hand, in the online learning literature, optimistic mirror descent (Chiang et al., 2012) was proposed to use $\hat{g}_n = g_{n-1}$. Later (Rakhlin & Sridharan, 2013a) generalized it to use some arbitrary sequence \hat{g}_n , and provided a FTRL version update rule in (13). However, it is unclear in (Rakhlin & Sridharan, 2013a) where the prediction \hat{g}_n comes from in general, though they provide an example in the form of learning from experts.

Recently Cheng et al. (2018) generalized the FTRL version of these ideas to design MOBIL, which introduces extra features 1) use of weights 2) non-stationary Bregman divergences (i.e. step size) and 3) the concept of predictive models ($\Phi_n \approx \nabla l_n$). The former two features are important to speed up the convergence rate of IL. With predictive models, they propose a conceptual idea (inspired by Be-the-Leader) which solves for π_n by the VI of finding π_n such that

$$\left\langle w_n \Phi_n(\pi_n) + \sum_{m=1}^n w_m g_m, \pi' - \pi_n \right\rangle \ge 0 \qquad \forall \pi' \in \Pi$$
(14)

and a more practical version (11) which sets $\hat{g}_n = \Phi_n(\pi_n)$. Under proper assumptions, they prove that the practical version achieves the same rate of non-asymptotic convergence as the conceptual one, up to constant factors.

PICCOLO unifies and generalizes the above update rules. We first notice that when the weight is constant, the set Π is unconstrained, and the Bregman divergence is constant, PICCOLO with mirror descent in (9) is the same as (12), i.e.,

$$\hat{\pi}_{n+1} = \underset{\pi \in \Pi}{\arg\min} \langle e_n, \pi \rangle + B_R(\pi || \pi_n)$$

$$= \underset{\pi \in \Pi}{\arg\min} \langle e_n, \pi \rangle + R(\pi) - \langle \nabla R(\pi_n), \pi \rangle$$

$$= \underset{\pi \in \Pi}{\arg\min} \langle g_n - \hat{g}_n, \pi \rangle + R(\pi) - \langle \nabla R(\hat{\pi}_n) - \hat{g}_n, \pi \rangle$$

$$= \underset{\pi \in \Pi}{\arg\min} \langle g_n, \pi \rangle + R(\pi) - \langle \nabla R(\hat{\pi}_n), \pi \rangle$$

$$= \underset{\pi \in \Pi}{\arg\min} \langle g_n, \pi \rangle + B_R(\pi || \hat{\pi}_n)$$

Therefore, PICCOLO with mirror descent includes previous two-step algorithms with proper choices of \hat{g}_n . On the other hand, we showed above that PICCOLO with FTRL (10) recovers exactly (11).

PICCOLO further generalizes these updates in two important aspects. First, it provides a systematic way to make these mirror descent and FTRL algorithms *adaptive*, by the reduction that allows reusing existing adaptive algorithm designed for adversarial settings. By contrast, all the previous update schemes discussed above (even MOBIL) are based on constant or pre-scheduled Bregman divergences, which requires the knowledge of several constants of problem properties that are usually unknown in practice. The use of adaptive schemes more amenable to hyperparameter tuning in practice.

Second, PICCOLO generalize the use of predictive models from the VI formulation in (14) to the *fixed-point* formulation in (8). One can show that when the base algorithm is FTRL and we remove the Bregman divergence¹¹, (8) is the same as (14). In other words, (14) essentially can be viewed as a mechanism to find \hat{g}_n for (11). But importantly, the fixed-point formulation is method agnostic and therefore applies to also the mirror descent case. In particular, in Section 4.2.3, we point out that when Φ_n is a gradient map, the fixed-point problem reduces to finding a stationary point¹² of a non-convex optimization problem. This observation makes implementation of the fixed-point idea much easier and more stable in practice (as we only require the function associated with Φ_n to be lower bounded to yield a stable problem).

B. Proof of Lemma 3

Without loss of generality we suppose $w_1 = 1$ and $J(\pi) \ge 0$ for all π . And we assume the weighting sequence $\{w_n\}$ satisfies, for all $n \ge m \ge 1$ and $k \ge 0$, $\frac{w_{n+k}}{w_n} \le \frac{w_{m+k}}{w_m}$. This means $\{w_n\}$ is an non-decreasing sequence and it does not grow faster than exponential (for which $\frac{w_{n+k}}{w_n} = \frac{w_{m+k}}{w_m}$). For example, if $w_n = n^p$ with $p \ge 0$, it easy to see that

$$\frac{(n+k)^p}{n^p} \le \frac{(m+k)^p}{m^p} \iff \frac{n+k}{n} \le \frac{m+k}{m} \iff \frac{k}{n} \le \frac{k}{m}$$

For simplicity, let us first consider the case where l_n is deterministic. Given this assumption, we bound the performance in terms of the weighted regret below. For l_n defined in (5), we can write

$$\sum_{n=1}^{N} w_n J(\pi_n)$$

= $\sum_{n=1}^{N} w_n J(\pi_{n-1}) + w_n \mathbb{E}_{d_{\pi_n}} \mathbb{E}_{\pi_n} [A_{\pi_{n-1}}]$
= $\sum_{n=1}^{N} w_n J(\pi_{n-1}) + w_n l_n(\pi_n)$

¹¹Originally the conceptual MOBIL algorithm is based on the assumption that l_n is strongly convex and therefore does not require extra Bregman divergence. Here PICCOLO with FTRL provides a natural generalization to online convex problems.

¹²Any stationary point will suffice.

$$\begin{split} &= w_1 J(\pi_0) + \sum_{n=1}^{N-1} w_{n+1} J(\pi_n) + \sum_{n=1}^{N} w_n l_n(\pi_n) \\ &= w_1 J(\pi_0) + \sum_{n=1}^{N-1} w_{n+1} J(\pi_{n-1}) + \sum_{n=1}^{N-1} w_{n+1} l_n(\pi_n) + \sum_{n=1}^{N} w_n l_n(\pi_n) \\ &= (w_1 + w_2) J(\pi_0) + \sum_{n=1}^{N-2} w_{n+2} J(\pi_n) + \sum_{n=1}^{N-1} w_{n+1} l_n(\pi_n) + \sum_{n=1}^{N} w_n l_n(\pi_n) \\ &= w_{1:N} J(\pi_0) + \left(w_N l_1(\pi_1) + \sum_{n=1}^{2} w_{n+N-2} l_n(\pi_n) + \dots + \sum_{n=1}^{N-1} w_{n+1} l_n(\pi_n) + \sum_{n=1}^{N} w_n l_n(\pi_n) \right) \\ &= w_{1:N} J(\pi_0) + \left(w_N l_1(\pi_1) + \sum_{n=1}^{2} \frac{w_{n+N-2}}{w_n} w_n l_n(\pi_n) + \dots + \sum_{n=1}^{N-1} \frac{w_{n+1}}{w_n} w_n l_n(\pi_n) + \sum_{n=1}^{N} w_n l_n(\pi_n) \right) \\ &\leq w_{1:N} J(\pi_0) + \left(w_N l_1(\pi_1) + \frac{w_{N-1}}{w_1} \sum_{n=1}^{2} w_n l_n(\pi_n) + \dots + \frac{w_2}{w_1} \sum_{n=1}^{N-1} w_n l_n(\pi_n) + \sum_{n=1}^{N} w_n l_n(\pi_n) \right) \\ &= w_{1:N} J(\pi_0) + \left(w_N l_1(\pi_1) + \frac{w_{N-1}}{w_1} \sum_{n=1}^{2} w_n l_n(\pi_n) + \dots + w_2 \sum_{n=1}^{N-1} w_n l_n(\pi_n) + \sum_{n=1}^{N} w_n l_n(\pi_n) \right) \end{split}$$

where the inequality is due to the assumption on the weighting sequence.

We can further rearrange the second term in the final expression as

$$\begin{split} w_N l_1(\pi_1) + w_{N-1} \sum_{n=1}^2 w_n l_n(\pi_n) + \dots + w_2 \sum_{n=1}^{N-1} w_n l_n(\pi_n) + \sum_{n=1}^N w_n l_n(\pi_n) \\ = & w_N \left(l_1(\pi_1) - \min_{\pi \in \Pi} l_1(\pi) + \min_{\pi \in \Pi} l_1(\pi) \right) \\ & + w_{N-1} \left(\sum_{n=1}^2 w_n l_n(\pi_n) - \min_{\pi \in \Pi} \sum_{n=1}^2 w_n l_n(\pi) + \min_{\pi \in \Pi} \sum_{n=1}^2 w_n l_n(\pi) \right) \\ & + \dots + \sum_{n=1}^N w_n l_n(\pi_n) - \min_{\pi \in \Pi} \sum_{n=1}^N w_n l_n(\pi) + \min_{\pi \in \Pi} \sum_{n=1}^N w_n l_n(\pi) \\ & = \sum_{n=1}^N w_{N-n+1} \left(\operatorname{Regret}_n(f) + w_{1:n} \epsilon_n(f) \right) \end{split}$$

where the last equality is due to the definition of *static* regret and ϵ_n .

Likewise, we can also write the above expression in terms of dynamic regret

$$w_{N}l_{1}(\pi_{1}) + w_{N-1}\sum_{n=1}^{2}w_{n}l_{n}(\pi_{n}) + \dots + w_{2}\sum_{n=1}^{N-1}w_{n}l_{n}(\pi_{n}) + \sum_{n=1}^{N}w_{n}l_{n}(\pi_{n})$$
$$= w_{N}\left(l_{1}(\pi_{1}) - \min_{\pi\in\Pi}l_{1}(\pi) + \min_{\pi\in\Pi}l_{1}(\pi)\right)$$
$$+ w_{N-1}\left(\sum_{n=1}^{2}w_{n}l_{n}(\pi_{n}) - \sum_{n=1}^{2}w_{n}\min_{\pi\in\Pi}l_{n}(\pi) + \sum_{n=1}^{2}\min_{\pi\in\Pi}w_{n}l_{n}(\pi)\right)$$
$$+ \dots + \sum_{n=1}^{N}w_{n}l_{n}(\pi_{n}) - \sum_{n=1}^{N}\min_{\pi\in\Pi}w_{n}l_{n}(\pi) + \sum_{n=1}^{N}\min_{\pi\in\Pi}w_{n}l_{n}(\pi)$$
$$= \sum_{n=1}^{N}w_{N-n+1}\left(\operatorname{Regret}_{n}^{d}(l) + w_{1:n}\epsilon_{n}^{d}(l)\right)$$

in which we define the weighted dynamic regret as

Regret_n^d(l) =
$$\sum_{m=1}^{n} w_m l_m(\pi_m) - \sum_{m=1}^{n} w_m \min_{\pi \in \Pi} l_m(\pi)$$

and an expressive measure based on dynamic regret

$$\epsilon_n^d = \frac{1}{w_{1:n}} \sum_{m=1}^n w_m \min_{\pi \in \Pi} l_m(\pi) \le 0$$

For stochastic problems, because π_n does not depends on \tilde{l}_n , the above bound applies to the performance in expectation. Specifically, let h_{n-1} denote all the random variables observed before making decision π_n and seeing \tilde{l}_n . As π_n is made independent of \tilde{l}_n , we have, for example,

$$\mathbb{E}[l_n(\pi_n)|h_{n-1}] = \mathbb{E}[l_n(\pi_n)|h_{n-1}] - \mathbb{E}[l_n(\pi_n^*)|h_{n-1}] + \mathbb{E}[l_n(\pi_n^*)|h_{n-1}] \\ = \mathbb{E}[\tilde{l}_n(\pi_n)|h_{n-1}] - \mathbb{E}[\tilde{l}_n(\pi_n^*)|h_{n-1}] + \mathbb{E}[l_n(\pi_n^*)|h_{n-1}] \\ \le \mathbb{E}[\tilde{l}_n(\pi_n) - \min_{\pi \in \Pi} \tilde{l}_n(\pi)|h_{n-1}] + \mathbb{E}[l_n(\pi_n^*)|h_{n-1}]$$

where $\pi_n^* = \arg \min_{\pi \in \Pi} l_n(\pi)$. By applying a similar derivation as above recursively, we can extend the previous deterministic bounds to bounds in expectation (for both the static or the dynamic regret case), proving the desired statement.

C. The Basic Operations of Base Algorithms

We provide details of the abstract basic operations shared by different base algorithms. In general, the update rule of any base mirror-descent or FTRL algorithm can be represented in terms of the three basic operations

$$h \leftarrow \text{update}(h, H, g, w), \quad H \leftarrow \text{adapt}(h, H, g, w), \quad \pi \leftarrow \text{project}(h, H)$$
(15)

where update and project can be identified standardly, for mirror descent as,

$$update(h, H, g, w) = \arg\min_{\pi' \in \Pi} \langle wg, \pi' \rangle + B_H(\pi || h), \quad project(h, H) = h$$
(16)

and for FTRL as,

$$update(h, H, g, w) = h + wg, \qquad project(h, H) = \arg\min_{\pi' \in \Pi} \langle h, \pi' \rangle + H(\pi')$$
(17)

We note that in the main text of this paper the operation project is omitted for simplicity, as it is equal to the identify map for mirror descent. In general, it represents the decoding from the abstract representation of the decision h to π . The main difference between and h and π is that h represents the sufficient information that defines the state of the base algorithm.

While update and project are defined standardly, the exact definition of adapt depends on the specific base algorithm. Particularly, adapt may depend also on whether the problem is weighted, as different base algorithms may handle weighted problems differently. Based on the way weighted problems are handled, we roughly categorize the algorithms (in both mirror descent and FTRL families) into two classes: the *stationary* regularization class and the *non-stationary* regularization class. Here we provide more details into the algorithm-dependent adapt operation, through some commonly used base algorithms as examples.

Please see also Appendix A for connection between PICCOLO and existing two-step algorithms, like optimistic mirror descent (Rakhlin & Sridharan, 2013b).

C.1. Stationary Regularization Class

The adapt operation of these base algorithms features two major functions: 1) a moving-average adaptation and 2) a step-size adaption. The moving-average adaptation is designed to estimate some statistics G such that $||g||_* = O(G)$ (which is an important factor in regret bounds), whereas the step-size adaptation updates a scalar multiplier η according to the weight w to ensure convergence.

This family of algorithms includes basic mirror descent (Beck & Teboulle, 2003) and FTRL (McMahan & Streeter, 2010; McMahan, 2017) with a scheduled step size, and adaptive algorithms based on moving average e.g. RMSPROP (Tieleman & Hinton, 2012) ADADELTA (Zeiler, 2012), ADAM (Kingma & Ba, 2015), AMSGRAD (Reddi et al., 2018), and the adaptive NATGRAD we used in the experiments. Below we showcase how adapt is defined using some examples.

C.1.1. BASIC MIRROR DESCENT (BECK & TEBOULLE, 2003)

We define G to be some constant such that $G \ge \sup \|g_n\|_*$ and define

$$\eta_n = \frac{\eta}{1 + cw_{1:n}/\sqrt{n}},\tag{18}$$

as a function of the iteration counter n, where $\eta > 0$ is a step size multiplier and c > 0 determines the decaying rate of the step size. The choice of hyperparameters η , c pertains to how far the optimal solution is from the initial condition, which is related to the size of Π . In implementation, adapt updates the iteration counter n and updates the multiplier η_n using w_n in (18).

Together (n, G, η_n) defines $H_n = R_n$ in the mirror descent update rule (6) through setting $R_n = \frac{G}{\eta_n}R$, where R is a strongly convex function. That is, we can write (6) equivalently as

$$\pi_{n+1} = \operatorname*{arg\,min}_{\pi \in \Pi} \langle w_n g_n, \pi \rangle + \frac{G}{\eta_n} B_R(\pi || \pi_n)$$
$$= \operatorname*{arg\,min}_{\pi \in \Pi} \langle w_n g_n, \pi \rangle + B_{H_n}(\pi || \pi_n)$$
$$= \operatorname{update}(h_n, H_n, g_n, w_n)$$

When the weight is constant (i.e. $w_n = 1$), we can easily see this update rule is equivalent to the classical mirror descent with a step size $\frac{\eta/G}{1+c\sqrt{n}}$, which is the optimal step size (McMahan, 2017). For general $w_n = \Theta(n^p)$ with some p > -1, it can viewed as having an effective step size $\frac{w_n\eta_n}{G} = O(\frac{1}{G\sqrt{n}})$, which is optimal in the weighted setting. The inclusion of the constant G makes the algorithm invariant to the scaling of loss functions. But as the same G is used across all the iterations, the basic mirror descent is conservative.

C.1.2. BASIC FTRL (MCMAHAN, 2017)

We provide details of general FTRL

$$\pi_{n+1} = \underset{\pi \in \Pi}{\arg\min} \sum_{m=1}^{n} \langle g_m, \pi \rangle + B_{r_m}(\pi || \pi_m)$$
(19)

where $B_{r_m}(\cdot || \pi_m)$ is a Bregman divergence centered at π_m .

We define, in the *n*th iteration, h_n , H_n , and project of FTRL in (17) as

$$h_n = \sum_{m=1}^n w_m g_m, \qquad H_n(\pi) = \sum_{m=1}^n B_{r_m}(\pi || \pi_n), \qquad \text{project}(h, H) = \operatorname*{arg\,min}_{\pi' \in \Pi} \langle h, \pi' \rangle + H(\pi')$$

Therefore, we can see that $\pi_{n+1} = \text{project}(h_n, H_n)$ indeed gives the update (19):

$$\pi_{n+1} = \operatorname{project}(h_n, H_n)$$

= $\operatorname{project}(\sum_{m=1}^n w_m g_m, \sum_{m=1}^n B_{r_m}(\pi || \pi_n))$
= $\operatorname{arg\,min}_{\pi \in \Pi} \sum_{m=1}^n \langle w_m g_m, \pi \rangle + B_{r_m}(\pi || \pi_m)$

For the basic FTRL, the adapt operator is similar to the basic mirror descent, which uses a constant G and updates the memory (n, η_n) using (18). The main differences are how (G, η_n) is mapped to H_n and that the basic FTRL updates H_n

also using h_n (i.e. π_n). Specifically, it performs $H_n \leftarrow \text{adapt}(h_n, H_{n-1}, g_n, w_n)$ through the following:

$$H_n(\cdot) = H_{n-1}(\cdot) + B_{r_n}(\cdot||\pi_n)$$

where following (McMahan, 2017) we set

$$B_{r_n}(\pi || \pi_n) = G(\frac{1}{\eta_n} - \frac{1}{\eta_{n-1}})B_R(\pi || \pi_n)$$

and η_n is updated using some scheduled rule.

One can also show that the choice of η_n scheduling in (18) leads to an optimal regret. When the problem is uniformly weighted (i.e. $w_n = 1$), this gives exactly the update rule in (McMahan, 2017). For general $w_n = \Theta(n^p)$ with p > -1, a proof of optimality can be found, for example, in the appendix of (Cheng et al., 2019).

C.1.3. ADAM (KINGMA & BA, 2015) AND AMSGRAD (REDDI ET AL., 2018)

As a representing mirror descent algorithm that uses moving-average estimates, ADAM keeps in the memory of the statistics of the first-order information that is provided in update and adapt. Here we first review the standard description of ADAM and then show how it is summarized in

$$H_n = \operatorname{adapt}(h_n, H_{n-1}, g_n, w_n), \qquad h_{n+1} = \operatorname{update}(h_n, H_n, g_n, w_n) \tag{7}$$

using properly constructed update, adapt, and project operations.

The update rule of ADAM proposed by Kingma & Ba (2015) is originally written as, for $n \ge 1$,¹³

$$m_{n} = \beta_{1}m_{n-1} + (1 - \beta_{1})g_{n}$$

$$v_{n} = \beta_{2}v_{n-1} + (1 - \beta_{2})g_{n} \odot g_{n}$$

$$\hat{m}_{n} = m_{n}/(1 - \beta_{1}^{n})$$

$$\hat{v}_{n} = v_{n}/(1 - \beta_{2}^{n})$$

$$\pi_{n+1} = \pi_{n} - \eta_{n}\hat{m}_{n} \oslash (\sqrt{\hat{v}_{n}} + \epsilon)$$
(20)

where $\eta_n > 0$ is the step size, $\beta_1, \beta_2 \in [0, 1)$ (default $\beta_1 = 0.9$ and $\beta_2 = 0.999$) are the mixing rate, and $0 < \epsilon \ll 1$ is some constant for stability (default $\epsilon = 10^{-8}$), and $m_0 = v_0 = 0$. The symbols \odot and \oslash denote element-wise multiplication and division, respectively. The third and the forth steps are designed to remove the 0-bias due to running moving averages starting from 0.

The above update rule can be written in terms of the three basic operations. First, we define the memories $h_n = (m_n, \pi_n)$ for policy and (v_n, η_n, n) for regularization that is defined as

$$H_n(\pi) = \frac{1}{2\eta_n} \pi^\top (\operatorname{diag}(\sqrt{\hat{v}_n}) + \epsilon I)\pi$$
(21)

where \hat{v}_n is defined in the original ADAM equation in (20).

The adapt operation updates the memory to (v_n, η_n, n) in the step

$$H_n \leftarrow \text{adapt}(h_n, H_{n-1}, g_n, w_n)$$

It updates the iteration counter n and η_n in the same way in the basic mirror descent using (18), and update v_n (which along with n defines \hat{v}_n used in (21)) using the original ADAM equation in (20).

For update, we slightly modify the definition of update in (16) (replacing g_n with \hat{m}_n) to incorporate the moving average and write

$$update(h_n, H_n, g_n, w_n) = \underset{\pi' \in \Pi}{\arg\min} \langle w_n \hat{m}_n, \pi' \rangle + B_{H_n}(\pi' || \pi)$$
(22)

¹³We shift the iteration index so it conforms with our notation in online learning, in which π_1 is the initial policy before any update.

where m_n and \hat{m}_n are defined the same as in the original ADAM equations in (20). One can verify that, with these definitions, the update rule in (7) is equivalent to the update rule (20), when the weight is uniform (i.e. $w_n = 1$).

Here the $\sqrt{\hat{v}_n}$ plays the role of G as in the basic mirror descent, which can be viewed as an estimate of the upper bound of $||g_n||_*$. ADAM achieves a better performance because a coordinate-wise online estimate is used. With this equivalence in mind, we can easily deduct that using the same scheduling of η_n as in the basic mirror descent would achieve an optimal regret (cf. (Kingma & Ba, 2015; Reddi et al., 2018)). We note that ADAM may fail to converge in some particular problems due to the moving average (Reddi et al., 2018). AMSGRAD (Reddi et al., 2018) modifies the moving average and uses strictly increasing estimates. However in practice AMSGRAD behaves more conservatively.

For weighted problems, we note one important nuance in our definition above: it separates the weight w_n from the moving average and considers w_n as part of the η_n update, because the growth of w_n in general can be much faster than the rate the moving average converges. In other words, the moving average can only be used to estimate a stationary property, not a time-varying one like w_n . Hence, we call this class of algorithms, the *stationary* regularization class.

C.1.4. Adaptive Natgrad

Given first-order information g_n and weight w_n , we consider an update rule based on Fisher information matrix:

$$\pi_{n+1} = \operatorname*{arg\,min}_{\pi \in \Pi} \langle w_n g_n, \pi \rangle + \frac{\sqrt{\hat{G}_n}}{2\eta_n} (\pi - \pi_n)^\top F_n(\pi - \pi_n)$$
(23)

where F_n is the Fisher information matrix of policy π_n (Amari, 1998) and \hat{G}_n is an adaptive multiplier for the step size which we will describe. When $\hat{G}_n = 1$, the update in (23) gives the standard natural gradient descent update with step size η_n (Kakade, 2002).

The role of \hat{G}_n is to adaptively and *slowly* changes the step size to minimize $\sum_{n=1}^{N} \frac{\eta_n}{\sqrt{G_n}} ||g_n||_{F_n,*}^2$, which plays an important part in the regret bound (see Section 5, Appendix F, and e.g. (McMahan, 2017) for details). Following the idea in ADAM, we update \hat{G}_n by setting (with $G_0 = 0$)

$$G_n = \beta_2 G_n + (1 - \beta_2) \frac{1}{2} g_n^\top F_n^{-1} g_n$$

$$\hat{G}_n = G_n / (1 - \beta_2^n)$$
(24)

similar to the concept of updating v_n and \hat{v}_n in ADAM in (20), and update η_n in the same way as in the basic mirror descent using (18). Consequently, this would also lead to a regret like ADAM but in terms of a different local norm.

The update operation of adaptive NATGRAD is defined standardly in (6) (as used in the experiments). The adapt operation updates n and η_n like in ADAM and updates G_n through (24).

C.2. Non-Stationary Regularization Class

The algorithms in the non-stationary regularization class maintains a regularization that is increasing over the number of iterations. Notable examples of this class include ADAGRAD (Duchi et al., 2011) and ONLINE NEWTON STEP (Hazan et al., 2007), and its regularization function is updated by applying BTL in a secondary online learning problem whose loss is an upper bound of the original regret (see (Gupta et al., 2017) for details). Therefore, compared with the previous stationary regularization class, the adaption property of η_n and G_n exchanges: η_n here becomes constant and G_n becomes time-varying. This will be shown more clearly in the ADAGRAD example below. We note while these algorithms are designed to be optimal in the convex, they are often too conservative (e.g. decaying the step size too fast) for non-convex problems.

C.2.1. Adagrad

The update rule of the diagonal version of ADAGRAD in (Duchi et al., 2011) is given as

$$G_n = G_{n-1} + \operatorname{diag}(g_n \odot g_n)$$

$$\pi_{n+1} = \operatorname*{arg\,min}_{\pi \in \Pi} \langle g_n, \pi \rangle + \frac{1}{2\eta} (\pi - \pi_n)^\top (\epsilon I + G_n)^{1/2} (\pi - \pi_n)$$
(25)

where $G_0 = 0$ and $\eta > 0$ is a constant. ADAGRAD is designed to be optimal for online linear optimization problems. Above we provide the update equations of its mirror descent formulation in (25); a similar FTRL is also available (again the difference only happens when Π is constrained).

In terms of our notation, its update and project are defined standardly as in (16), i.e.

$$update(h_n, H_n, g_n, w_n) = \arg\min_{\pi' \in \Pi} \langle w_n g_n, \pi' \rangle + B_{H_n}(\pi' || \pi_n)$$
(26)

and its adapt essentially only updates G_n :

$$adapt(h_n, H_{n-1}, g_n, w_n): G_n = G_{n-1} + diag(w_n g_n \odot w_n g_n)$$

where the regularization is defined the updated G_n and the constant η as

$$H_n(\pi) = \frac{1}{2\eta} \pi^\top (\epsilon I + G_n)^{1/2} \pi.$$

One can simply verify the above definitions of update and adapt agrees with (25).

D. A Practical Variation of PICCOLO

In Section 4.2.2, we show that, given a base algorithm in mirror descent/FTRL, PICCOLO generates a new first-order update rule by recomposing the three basic operations into

$$h_n = update(h_n, H_{n-1}, \hat{g}_n, w_n)$$
 [Prediction] (27)

$$H_n = \operatorname{adapt}(h_n, H_{n-1}, e_n, w_n)$$

$$\hat{h}_{n+1} = \operatorname{update}(h_n, H_n, e_n, w_n)$$
[Correction] (28)

where $e_n = g_n - \hat{g}_n$ and \hat{g}_n is an estimate of g_n given by a predictive model Φ_n .

Here we propose a slight variation which introduces another operation shift inside the Prediction Step. This leads to the new set of update rules:

$$\dot{H}_n = \text{shift}(h_n, H_{n-1})
 h_n = \text{update}(\hat{h}_n, \hat{H}_n, \hat{g}_n, w_n)$$
(29)

$$H_n = \text{adapt}(h_n, H_n, e_n, w_n)$$

$$\hat{h}_{n+1} = \text{update}(h_n, H_n, e_n, w_n)$$
[Correction] (30)

The new shift operator additionally changes the regularization based on \hat{h}_n the current representation of the policy in the Prediction Step, *independent* of the predicted gradient \hat{g}_n and weight w_n . The main purpose of including this additional step is to deal with numerical difficulties, such as singularity of H_n . For example, in natural gradient descent, the Fisher information of some policy can be close to being singular along the direction of the gradients that are evaluated at different policies. As a result, in the original Prediction Step of PICCOLO, H_{n-1} which is evaluated at π_{n-1} might be singular in the direction of \hat{g}_n which is evaluated $\hat{\pi}_n$.

The new operator shift brings in an extra degree of freedom to account for such issue. Although from a theoretical point of view (cf. Appendix F) the use of shift would only increase regrets and should be avoided if possible, in practice, its merits in handling numerical difficulties can out weight the drawback. Because shift does not depend on the size of \hat{g}_n and w_n , the extra regrets would only be proportional to $O(\sum_{n=1}^N ||\pi_n - \hat{\pi}_n||_n)$, which can be smaller than other terms in the regret bound (see Appendix F).

E. Example: PICCOLOing Natural Gradient Descent

We give an alternative example to illustrate how one can use the above procedure to "PICCOLO" a base algorithm into a new algorithm. Here we consider the adaptive natural gradient descent rule in Appendix C as the base algorithm, which

(given first-order information g_n and weight w_n) updates the policy through

$$\pi_{n+1} = \arg\min_{\pi \in \Pi} \langle w_n g_n, \pi \rangle + \frac{\sqrt{\hat{G}_n}}{2\eta_n} (\pi - \pi_n)^\top F_n(\pi - \pi_n)$$
(31)

where F_n is the Fisher information matrix of policy π_n (Amari, 1998), η_n a scheduled learning rate, and \hat{G}_n is an adaptive multiplier for the step size which we will shortly describe. When $\hat{G}_n = 1$, the update in (31) gives the standard natural gradient descent update with step size η_n (Kakade, 2002).

The role of \hat{G}_n is to adaptively and *slowly* changes the step size to minimize $\sum_{n=1}^{N} \frac{\eta_n}{\sqrt{G_n}} ||g_n||_{F_n,*}^2$, which plays an important part in the regret bound (see Section 5, Appendix F, and e.g. (McMahan, 2017) for details). To this end, we update \hat{G}_n by setting (with $G_0 = 0$)

$$G_n = \beta_2 G_{n-1} + (1 - \beta_2) \frac{1}{2} g_n^\top F_n^{-1} g_n, \qquad \hat{G}_n = G_n / (1 - \beta_2^n)$$
(32)

similar to the moving average update rule in ADAM, and update η_n in the same way as in the basic mirror descent algorithm (e.g. $\eta_n = O(1/\sqrt{n})$). As a result, this leads to a similar regret like ADAM with $\beta_1 = 0$, but in terms of a local norm specified by the Fisher information matrix.

Now, let's see how to PICCOLO the adaptive natural gradient descent rule above. First, it is easy to see that the adaptive natural gradient descent rule is an instance of mirror descent (with $h_n = \pi_n$ and $H_n(g) = \frac{\sqrt{\hat{G}_n}}{2\eta_n} g^\top F_n g$), so the update and project operations are defined in the standard way, as in Section 4.2.2. The adapt operation updates the iteration counter n, the learning rate η_n , and updates \hat{G}_n through (32).

To be more specific, let us explicitly write out the Prediction Step and the Correction Step of the PICCOLOed adaptive natural gradient descent rule in closed form as below: e.g. if $\eta_n = \frac{1}{\sqrt{n}}$, then we can write them as

[Prediction]
$$\pi_n = \arg\min_{\pi \in \Pi} \langle w_n \hat{g}_n, \pi \rangle + \frac{\sqrt{\hat{G}_{n-1}}}{2\eta_{n-1}} (\pi - \hat{\pi}_n)^\top F_{n-1} (\pi - \hat{\pi}_n)$$

[Correction]

$$\eta_n = 1/\sqrt{n}$$

$$G_n = \beta_2 G_{n-1} + (1 - \beta_2) \frac{1}{2} g_n^\top F_n^{-1} g_n$$

$$\hat{G}_n = G_n/(1 - \beta_2^n)$$

$$\hat{\pi}_{n+1} = \arg\min_{\pi \in \Pi} \langle w_n e_n, \pi \rangle + \frac{\sqrt{\hat{G}_n}}{2\eta_n} (\pi - \pi_n)^\top F_n(\pi - \pi_n)$$

F. Regret Analysis of PICCOLO

The main idea of PICCOLO is to achieve optimal performance in predictable online learning problems by *reusing* existing adaptive, optimal first-order algorithms that are designed for adversarial online learning problems. This is realized by the reduction techniques presented in this section.

Here we prove the performance of PICCOLO in general predictable online learning problems, independent of the context of policy optimization. In Appendix F.1, we first show an elegant reduction from predictable problems to adversarial problems. Then we prove Theorem 1 in Appendix F.2, showing how the optimal regret bound for predictable linear problems can be achieved by PICCOLOing mirror descent and FTRL algorithms. Note that we will abuse the notation l_n to denote the per-round losses in this general setting.

F.1. Reduction from Predictable Online Learning to Adversarial Online Learning

Consider a predictable online learning problem with per-round losses $\{l_n\}$. Suppose in round n, before playing π_n and revealing l_n , we have access to some prediction of l_n , called \hat{l}_n . In particular, we consider the case where $\hat{l}_n(\pi) = \langle \hat{g}_n, \pi \rangle$ for some vector \hat{g}_n . Running an (adaptive) online learning algorithm designed for the general adversarial setting is not optimal here, as its regret would be in $O(\sum_{n=1}^N \|\nabla l_n\|_{n,*}^2)$, where $\|\cdot\|_n$ is some local norm chosen by the algorithm and $\|\cdot\|_{n,*}$ is its dual norm. Ideally, we would only want to pay for the information that is unpredictable. Specifically, we wish to achieve an optimal regret in $O(\sum_{n=1}^N \|\nabla l_n - \nabla \hat{l}_n\|_{n,*}^2)$ instead (Rakhlin & Sridharan, 2013a).

To achieve the optimal regret bound yet without referring to specialized, nested two-step algorithms (e.g. mirror-prox (Juditsky et al., 2011), optimistic mirror descent (Rakhlin & Sridharan, 2013b), FTRL-prediction (Rakhlin & Sridharan, 2013a)), we consider decomposing a *predictable* problem with N rounds into an *adversarial* problem with 2N rounds:

$$\sum_{n=1}^{N} l_n(\pi_n) = \sum_{n=1}^{N} \hat{l}_n(\pi_n) + \delta_n(\pi_n)$$
(33)

where $\delta_n = l_n - \hat{l}_n$. Therefore, we can treat the predictable problem as a new adversarial online learning problem with a loss sequence $\hat{l}_1, \delta_1, \hat{l}_2, \delta_2, \dots, \hat{l}_N, \delta_N$ and consider solving this new problem with some standard online learning algorithm designed for the adversarial setting.

Before analysis, we first introduce a new decision variable $\hat{\pi}_n$ and denote the decision sequence in this new problem as $\hat{\pi}_1, \pi_1, \hat{\pi}_2, \pi_2, \dots, \hat{\pi}_N, \pi_N$, so the definition of the variables are consistent with that in the problem before. Because this new problem is unpredictable, the optimal regret of this new decision sequence is

$$\sum_{n=1}^{N} \hat{l}_n(\hat{\pi}_n) + \delta_n(\pi_n) - \min_{\pi \in \Pi} \sum_{n=1}^{N} \hat{l}_n(\pi) + \delta_n(\pi) = O(\sum_{n=1}^{N} \|\nabla \hat{l}_n\|_{n,*}^2 + \|\nabla \delta_n\|_{n+1/2,*}^2)$$
(34)

where the subscript n + 1/2 denotes the extra round due to the reduction.

At first glance, our reduction does not meet the expectation of achieving regret in $O(\sum_{n=1}^{N} \|\nabla l_n - \nabla \hat{l}_n\|_{n,*}^2) = O(\sum_{n=1}^{N} \|\nabla \delta_n\|_{n,*}^2)$. However, we note that the regret for the new problem is too loose for the regret of the original problem, which is

$$\sum_{n=1}^{N} \hat{l}_n(\pi_n) + \delta_n(\pi_n) - \min_{\pi \in \Pi} \sum_{n=1}^{N} \hat{l}_n(\pi) + \delta_n(\pi)$$

where the main difference is that originally we care about $\hat{l}_n(\pi_n)$ rather than $\hat{l}_n(\hat{\pi}_n)$. Specifically, we can write

$$\sum_{n=1}^{N} l_n(\pi_n) = \sum_{n=1}^{N} \hat{l}_n(\pi_n) + \delta_n(\pi_n)$$
$$= \left(\sum_{n=1}^{N} \hat{l}_n(\hat{\pi}_n) + \delta_n(\pi_n)\right) + \left(\sum_{n=1}^{N} \hat{l}_n(\pi_n) - \hat{l}_n(\hat{\pi}_n)\right)$$

Therefore, if the update rule for generating the decision sequence $\hat{\pi}_1, \pi_1, \hat{\pi}_2, \pi_2, \dots, \hat{\pi}_N, \pi_N$ contributes sufficient negativity in the term $\hat{l}_n(\pi_n) - \hat{l}_n(\hat{\pi}_n)$ compared with the regret of the new adversarial problem, then the regret of the original problem can be smaller than (34). This is potentially possible, as π_n is made after \hat{l}_n is revealed. Especially, in the fixed-point formulation of PICCOLO, π_n and \hat{l}_n can be decided simultaneously.

In the next section, we show that when the base algorithm, which is adopted to solve the new adversarial problem given by the reduction, is in the family of mirror descent and FTRL. Then the regret bound of PICCOLO with respect to the original predictable problem is optimal.

F.2. Optimal Regret Bounds for Predictable Problems

We show that if the base algorithm of PICCOLO belongs to the family of optimal mirror descent and FTRL designed for adversarial problems, then PICCOLO can achieve the optimal regret of predictable problems. In this subsection, we assume the loss sequence is linear, i.e. $l_n(\pi) = \langle g_n, \pi \rangle$ for some g_n , and the results are summarized as Theorem 1 in the main paper (in a slightly different notation).

F.2.1. MIRROR DESCENT

First, we consider mirror descent as the base algorithm. In this case, we can write the PICCOLO update rule as

$$\pi_n = \operatorname*{arg\,min}_{\pi \in \Pi} \left\langle \nabla \hat{l}_n(\hat{\pi}_n), x \right\rangle + B_{H_{n-1}}(\pi || \hat{\pi}_n)$$
 [Prediction]

$$\hat{\pi}_{n+1} = \operatorname*{arg\,min}_{\pi \in \Pi} \langle \nabla \delta_n(\pi_n), \pi \rangle + B_{H_n}(\pi || \pi_n)$$
 [Correction]

where H_n can be updated based on $e_n \coloneqq \nabla \delta_n(\pi_n) = \nabla l_n(\pi_n) - \nabla \hat{l}_n(\hat{\pi}_n)$ (recall by definition $\nabla l_n(\pi_n) = g_n$ and $\nabla \hat{l}_n(\hat{\pi}_n) = \nabla \hat{l}_n(\pi_n) = \hat{g}_n$). Notice that in the Prediction Step, PICCOLO uses the regularization from the previous Correction Step.

To analyze the performance, we use a lemma of the mirror descent's properties. The proof is a straightforward application of the optimality condition of the proximal map (Nesterov, 2013). We provide a proof here for completeness.

Lemma 4. Let \mathcal{K} be a convex set. Suppose R is 1-strongly convex with respect to norm $\|\cdot\|$. Let g be a vector in some Euclidean space and let

$$y = \operatorname*{arg\,min}_{z \in \mathcal{K}} \langle g, z \rangle + \frac{1}{\eta} B_R(z||x)$$

Then for all $z \in \mathcal{K}$

$$\eta \langle g, y - z \rangle \le B_R(z||x) - B_R(z||y) - B_R(y||x) \tag{35}$$

which implies

$$\eta \langle g, x - z \rangle \le B_R(z||x) - B_R(z||y) + \frac{\eta^2}{2} \|g\|_*^2$$
(36)

Proof. Recall the definition $B_R(z||x) = R(z) - R(x) - \langle \nabla R(x), z - x \rangle$. The optimality of the proximal map can be written as

$$\langle \eta g + \nabla R(y) - \nabla R(x), y - z \rangle \le 0, \qquad \forall z \in \mathcal{K}$$

By rearranging the terms, we can rewrite the above inequality in terms Bregman divergences as follows and derive the first inequality (35):

$$\begin{aligned} \langle \eta g, y - z \rangle &\leq \langle \nabla R(x) - \nabla R(y), y - z \rangle \\ &= B_R(z||x) - B_R(z||y) + \langle \nabla R(x) - \nabla R(y), y \rangle - \langle \nabla R(x), x \rangle + \langle \nabla R(y), y \rangle + R(x) - R(y) \\ &= B_R(z||x) - B_R(z||y) + \langle \nabla R(x), y - x \rangle + R(x) - R(y) \\ &= B_R(z||x) - B_R(z||y) - B_R(y||x) \end{aligned}$$

The second inequality is the consequence of (35). First, we rewrite (35) as

$$\langle \eta g, x - z \rangle = B_R(z||x) - B_R(z||y) - B_R(y||x) + \langle \eta g, x - y \rangle$$

Then we use the fact that B_R is 1-strongly convex with respect to $\|\cdot\|$, which implies

$$-B_R(y||x) + \langle \eta g, x - y \rangle \le -\frac{1}{2} ||x - y||^2 + \langle \eta g, x - y \rangle \le \frac{\eta^2}{2} ||g||_*^2$$

Combining the two inequalities yields (36).

Lemma 4 is usually stated with (36), which concerns the decision made before seeing the per-round loss (as in the standard adversarial online learning setting). Here, we additionally concern $\hat{l}_n(\pi_n)$, which is the decision made after seeing \hat{l}_n , so we need a tighter bound (35).

Now we show that the regret bound of PICCOLO in the predictable linear problems when the base algorithm is mirror descent.

Proposition 1. Assume the base algorithm of PICCOLO is mirror descent satisfying the Assumption 1. Let $g_n = \nabla l_n(\pi_n)$ and $e_n = g_n - \hat{g}_n$. Then it holds that, for any $\pi \in \Pi$,

$$\sum_{n=1}^{N} w_n \left\langle g_n, \pi_n - \pi \right\rangle \le M_N + \sum_{n=1}^{N} \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - \frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2$$

Proof. Suppose R_n , which is defined by H_n , is 1-strongly convex with respect to $\|\cdot\|_n$. Then by Lemma 4, we can write, for all $\pi \in \Pi$,

$$w_{n} \langle g_{n}, \pi_{n} - \pi \rangle = w_{n} \langle \hat{g}_{n}, \pi_{n} - \pi \rangle + w_{n} \langle e_{n}, \pi_{n} - \pi \rangle$$

$$\leq B_{R_{n-1}}(\pi || \hat{\pi}_{n}) - B_{R_{n-1}}(\pi || \pi_{n}) - B_{R_{n-1}}(\pi_{n} || \hat{\pi}_{n})$$

$$+ B_{R_{n}}(\pi || \pi_{n}) - B_{R_{n}}(\pi || \hat{\pi}_{n+1}) + \frac{w_{n}^{2}}{2} || e_{n} ||_{*,n}^{2}$$
(37)

where we use (35) for \hat{g}_n and (36) for the loss e_n .

To show the regret bound of the original (predictable) problem, we first notice that

$$\sum_{n=1}^{N} B_{R_{n-1}}(\pi || \hat{\pi}_n) - B_{R_{n-1}}(\pi || \pi_n) + B_{R_n}(\pi || \pi_n) - B_{R_n}(\pi || \hat{\pi}_{n+1})$$

$$= B_{R_0}(\pi || \hat{\pi}_1) - B_{R_N}(\pi || \hat{\pi}_{N+1}) + \sum_{n=1}^{N} B_{R_{n-1}}(\pi || \hat{\pi}_n) - B_{R_{n-1}}(\pi || \pi_n) + B_{R_n}(\pi || \pi_n) - B_{R_{n-1}}(\pi || \hat{\pi}_n)$$

$$= B_{R_0}(\pi || \hat{\pi}_1) - B_{R_N}(\pi || \hat{\pi}_{N+1}) + \sum_{n=1}^{N} B_{R_n}(\pi || \pi_n) - B_{R_{n-1}}(\pi || \pi_n) \le M_N$$

where the last inequality follows from the assumption on the base algorithm. Therefore, by telescoping the inequality in (37) and using the strong convexity of R_n , we get

$$\sum_{n=1}^{N} w_n \langle g_n, \pi_n - \pi \rangle \le M_N + \sum_{n=1}^{N} \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - B_{R_{n-1}}(\pi_n \|\hat{\pi}_n)$$
$$\le M_N + \sum_{n=1}^{N} \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - \frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2 \qquad \blacksquare$$

F.2.2. FOLLOW-THE-REGULARIZED-LEADER

We consider another type of base algorithm, FTRL, which is mainly different from mirror descent in the way that constrained decision sets are handled (McMahan, 2017). In this case, the exact update rule of PICCOLO can be written as

$$\pi_n = \underset{\pi \in \Pi}{\operatorname{arg\,min}} \langle w_n \hat{g}_n, \pi \rangle + \sum_{m=1}^{n-1} \langle w_m g_m, \pi \rangle + B_{r_m}(\pi || \pi_m)$$

$$\hat{\pi}_{n+1} = \underset{\pi \in \Pi}{\operatorname{arg\,min}} \sum_{m=1}^n \langle w_m g_m, \pi \rangle + B_{r_m}(\pi || \pi_m)$$
[Correction]

From the above equations, we verify that MOBIL (Cheng et al., 2019) is indeed a special case of PICCOLO, when the base algorithm is FTRL.

We show PICCOLO with FTRL has the following guarantee.

Proposition 2. Assume the base algorithm of PICCOLO is FTRL satisfying the Assumption 1. Then it holds that, for any $\pi \in \Pi$,

$$\sum_{n=1}^{N} w_n \left\langle g_n, \pi_n - \pi \right\rangle \le M_N + \sum_{n=1}^{N} \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - \frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2$$

We show the above results of PICCOLO using a different technique from (Cheng et al., 2019). Instead of developing a specialized proof like they do, we simply use the properties of FTRL on the 2*N*-step new adversarial problem!

To do so, we recall some facts of the base algorithm FTRL. First, FTRL in (19) is equivalent to Follow-the-Leader (FTL) on a surrogate problem with the per-round loss is $\langle g_n, \pi \rangle + B_{r_n}(\pi || \pi_n)$. Therefore, the regret of FTRL can be bounded

by the regret of FTL in the surrogate problem plus the size of the additional regularization $B_{r_n}(\pi || \pi_n)$. Second, we recall a standard techniques in proving FTL, called Strong FTL Lemma (see e.g. (McMahan, 2017)), which is proposed for *adversarial* online learning.

Lemma 5 (Strong FTL Lemma (McMahan, 2017)). *For any sequence* $\{\pi_n \in \Pi\}$ *and* $\{l_n\}$ *,*

$$Regret_N(l) \coloneqq \sum_{n=1}^N l_n(\pi_n) - \min_{\pi \in \Pi} \sum_{n=1}^N l_n(\pi) \le \sum_{n=1}^N l_{1:n}(\pi_n) - l_{1:n}(\pi_n^*)$$

where $\pi_n^{\star} \in \arg \min_{\pi \in \Pi} l_{1:n}(\pi)$.

Using the decomposition idea above, we show the performance of PICCOLO following sketch below: first, we show a bound on the regret in the surrogate predictable problem with per-round loss $\langle g_n, \pi \rangle + B_{r_n}(\pi || \pi_n)$; second, we derive the bound for the original predictable problem with per-round loss $\langle g_n, \pi \rangle$ by considering the effects of $B_{r_n}(\pi || \pi_n)$. We will prove the first step by applying FTL on the transformed 2*N*-step adversarial problem of the original *N*-step predictable surrogate problem and then showing that PICCOLO achieves the optimal regret in the original *N*-step predictable surrogate problem. Interestingly, we recover the bound in the stronger FTL Lemma (Lemma 6) by Cheng et al. (2019), which they suggest is necessary for proving the improved regret bound of their FTRL-prediction algorithm (MOBIL).

Lemma 6 (Stronger FTL Lemma (Cheng et al., 2019)). For any sequence $\{\pi_n\}$ and $\{l_n\}$,

$$Regret_{N}(l) = \sum_{n=1}^{N} l_{1:n}(\pi_{n}) - l_{1:n}(\pi_{n}^{\star}) - \Delta_{n}$$

where $\Delta_{n+1} := l_{1:n}(\pi_{n+1}) - l_{1:n}(\pi_n^*) \ge 0$ and $\pi_n^* \in \arg \min_{\pi \in \Pi} l_{1:n}(\pi)$.

Our new reduction-based regret bound is presented below.

Proposition 3. Let $\{l_n\}$ be a predictable loss sequence with predictable information $\{\hat{l}_n\}$. Suppose the decision sequence $\hat{\pi}_1, \pi_1, \hat{\pi}_2, \ldots, \hat{\pi}_N, \pi_N$ is generated by running FTL on the transformed adversarial loss sequence $\hat{l}_1, \delta_1, \hat{l}_2, \ldots, \hat{l}_N, \delta_N$, then the bound in the Stonger FTL Lemma holds. That is, $\text{Regret}_N(l) \leq \sum_{n=1}^N l_{1:n}(\pi_n) - l_{1:n}(\pi_n^*) - \Delta_n$, where $\Delta_{n+1} := l_{1:n}(\pi_{n+1}) - l_{1:n}(\pi_n^*) \geq 0$ and $\pi_n^* \in \arg \min_{\pi \in \Pi} l_{1:n}(\pi)$.

Proof. First, we transform the loss sequence and write

λī

$$\sum_{n=1}^{N} l_n(\pi_n) = \sum_{n=1}^{N} \hat{l}_n(\pi_n) + \delta_n(\pi_n) = \left(\sum_{n=1}^{N} \hat{l}_n(\hat{\pi}_n) + \delta_n(\pi_n)\right) + \left(\sum_{n=1}^{N} \hat{l}_n(\pi_n) - \hat{l}_n(\hat{\pi}_n)\right)$$

Then we apply standard Strong FTL Lemma on the new adversarial problem in the left term.

$$\sum_{n=1}^{N} \hat{l}_{n}(\hat{\pi}_{n}) + \delta_{n}(\pi_{n})$$

$$\leq \sum_{n=1}^{N} (\hat{l} + \delta)_{1:n}(\pi_{n}) - \min_{\pi \in \Pi} (\hat{l} + \delta)_{1:n}(\pi) + \sum_{n=1}^{N} ((\hat{l} + \delta)_{1:n-1} + \hat{l}_{n})(\hat{\pi}_{n}) - \min_{\pi \in \Pi} ((\hat{l} + \delta)_{1:n-1} + \hat{l}_{n})(\pi)$$

$$= \sum_{n=1}^{N} l_{1:n}(\pi_{n}) - \min_{\pi \in \Pi} l_{1:n}(\pi) + \sum_{n=1}^{N} (l_{1:n-1} + \hat{l}_{n})(\hat{\pi}_{n}) - (l_{1:n-1} + \hat{l}_{n})(\pi_{n})$$

where the first inequality is due to Strong FTL Lemma and the second equality is because FTL update assumption. Now we observe that if we add the second term above and $\sum_{n=1}^{N} \hat{l}_n(\pi_n) - \hat{l}_n(\hat{\pi}_n)$ together, we have

$$\sum_{n=1}^{N} (l_{1:n-1} + \hat{l}_n)(\hat{\pi}_n) - (l_{1:n-1} + \hat{l}_n)(\pi_n) + (\hat{l}_n(\pi_n) - \hat{l}_n(\hat{\pi}_n))$$
$$= \sum_{n=1}^{N} (l_{1:n-1})(\hat{\pi}_n) - l_{1:n-1}(\pi_n) = \Delta_n$$

Thus, combing previous two inequalities, we have the bound in the Stronger FTL Lemma:

$$\sum_{n=1}^{N} l_n(\pi_n) \le \sum_{n=1}^{N} l_{1:n}(\pi_n) - \min_{\pi \in \Pi} l_{1:n}(\pi) - \Delta_n$$

Using Proposition 3, we can now bound the regret of PICCOLO in Proposition 2 easily.

Proof of Proposition 2. Suppose $\sum_{m=1}^{n} B_{r_m}(\cdot || \pi_m)$ is 1-strongly convex with respect to some norm $\|\cdot\|_n$. Let $f_n = \langle w_n g_n, \pi_n \rangle + B_{r_n}(\pi || \pi_m)$. Then by a simple convexity analysis (see e.g. see (McMahan, 2017)) and Proposition 3, we can derive

$$\operatorname{Regret}_{N}(f) \leq \sum_{n=1}^{N} (f_{1:n}(\pi_{n}) - \min_{\pi \in \Pi} f_{1:n}(\pi)) - (f_{1:n-1}(\pi_{n}) - f_{1:n-1}(\hat{\pi}_{n}))$$
$$\leq \sum_{n=1}^{N} \frac{w_{n}^{2}}{2} \|e_{n}\|_{n,*}^{2} - \frac{1}{2} \|\pi_{n} - \hat{\pi}_{n}\|_{n-1}^{2}$$

Finally, because r_n is proximal (i.e. $B_{r_n}(\pi_n || \pi_n) = 0$), we can bound the original regret: for any $\pi \in \Pi$, it satisfies that

$$\sum_{n=1}^{N} w_n \langle g_n, \pi_n - \pi \rangle \leq \sum_{n=1}^{N} f_n(\pi_n) - f_n(\pi) + B_{r_n}(\pi || \pi_n)$$
$$\leq M_N + \sum_{n=1}^{N} \frac{w_n^2}{2} ||e_n||_{*,n}^2 - \frac{1}{2} ||\pi_n - \hat{\pi}_n||_{n-1}^2$$

where we use Assumption 1 and the bound of $\operatorname{Regret}_N(f)$ in the second inequality.

G. Policy Optimization Analysis of PICCOLO

In this section, we discuss how to interpret the bound given in Theorem 1

$$\sum_{n=1}^{N} w_n \left\langle g_n, \pi_n - \pi \right\rangle \le M_N + \sum_{n=1}^{N} \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - \frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2$$

in the context of policy optimization and show exactly how the optimal bound

$$\mathbb{E}\left[\sum_{n=1}^{N} \left\langle w_n g_n, \pi_n - \pi \right\rangle\right] \le O(1) + C_{\Pi, \Phi} \frac{w_{1:N}}{\sqrt{N}}$$
(38)

is derived. We will discuss how model learning can further help minimize the regret bound later in Appendix G.4.

G.1. Assumptions

We introduce some assumptions to characterize the sampled gradient g_n . Recall $g_n = \nabla \tilde{l}_n(\pi_n)$.

Assumption 2. $\|\mathbb{E}[g_n]\|_*^2 \leq G_g^2$ and $\|g_n - \mathbb{E}[g_n]\|_*^2 \leq \sigma_g^2$ for some finite constants G_g and σ_g .

Similarly, we consider properties of the predictive model Φ_n that is used to estimate the gradient of the next per-round loss. Let \mathcal{P} denote the class of these models (i.e. $\Phi_n \in \mathcal{P}$), which can potentially be *stochastic*. We make assumptions on the size of \hat{g}_n and its variance.

Assumption 3. $\|\mathbb{E}[\hat{g}_n]\|_*^2 \leq G_{\hat{g}}^2$ and $\mathbb{E}[\|\hat{g}_n - \mathbb{E}[\hat{g}_n]\|_*^2] \leq \sigma_{\hat{g}}^2$ for some finite constants $G_{\hat{g}}$ and $\sigma_{\hat{g}}$.

Additionally, we assume these models are Lipschitz continuous.

Assumption 4. There is a constant $L \in [0, \infty)$ such that, for any instantaneous cost ψ and any $\Phi \in \mathcal{P}$, it satisfies $\|\mathbb{E}[\Phi(\pi)] - \mathbb{E}[\Phi(\pi')]\|_* \leq L \|\pi - \pi'\|.$

Lastly, as PICCOLO is agnostic to the base algorithm, we assume the local norm $\|\cdot\|_n$ chosen by the base algorithm at round n satisfies $\|\cdot\|_n^2 \ge \alpha_n \|\cdot\|^2$ for some $\alpha_n > 0$. This condition implies that $\|\cdot\|_{n,*}^2 \le \frac{1}{\alpha_n} \|\cdot\|_{*}^2$. In addition, we assume α_n is non-decreasing so that $M_N = O(\alpha_N)$ in Assumption 1, where the leading constant in the bound $O(\alpha_N)$ is proportional to $|\Pi|$, as commonly chosen in online convex optimization.

G.2. A Useful Lemma

We study the bound in Theorem 1 under the assumptions made in the previous section. We first derive a basic inequality, following the idea in (Cheng et al., 2019, Lemma 4.3).

Lemma 7. Under Assumptions 2, 3, and 4, it holds

$$\mathbb{E}[\|e_n\|_{*,n}^2] = \mathbb{E}[\|g_n - \hat{g}_n\|_{*,n}^2] \le \frac{4}{\alpha_n} \left(\sigma_g^2 + \sigma_{\hat{g}}^2 + L_n^2 \|\pi_n - \hat{\pi}_n\|_n^2 + E_n(\Phi_n)\right)$$

where $E_n(\Phi_n) = \|\mathbb{E}[g_n] - \mathbb{E}[\Phi_n(\pi_n, \psi_n)]\|_*^2$ is the prediction error of model Φ_n .

Proof. Recall $\hat{g}_n = \Phi_n(\hat{\pi}_n, \psi_n)$. Using the triangular inequality, we can simply derive

$$\begin{split} & \mathbb{E}[\|g_{n} - \hat{g}_{n}\|_{*,n}^{2}] \\ & \leq 4 \left(\mathbb{E}[\|g_{n} - \mathbb{E}[g_{n}]\|_{*,n}^{2}] + \|\mathbb{E}[g_{n}] - \mathbb{E}[\Phi_{n}(\pi_{n},\psi_{n})]\|_{*,n}^{2} + \|\mathbb{E}[\Phi_{n}(\pi_{n},\psi_{n})] - \mathbb{E}[\hat{g}_{n}]\|_{*,n}^{2} + \mathbb{E}[\|\mathbb{E}[\hat{g}_{n}] - \hat{g}_{n}\|_{*,n}^{2}]\right) \\ & = 4 \left(\mathbb{E}[\|g_{n} - \mathbb{E}[g_{n}]\|_{*,n}^{2}] + \|\mathbb{E}[g_{n}] - \mathbb{E}[\Phi_{n}(\pi_{n},\psi_{n})]\|_{*,n}^{2} + \|\mathbb{E}[\Phi_{n}(\pi_{n},\psi_{n})] - \mathbb{E}[\Phi_{n}(\hat{\pi}_{n},\psi_{n})]\|_{*,n}^{2} + \mathbb{E}[\|\mathbb{E}[\hat{g}_{n}] - \hat{g}_{n}\|_{*,n}^{2}]\right) \\ & \leq 4 \left(\frac{1}{\alpha_{n}}\sigma_{g}^{2} + \frac{1}{\alpha_{n}}E_{n}(\Phi_{n}) + \|\mathbb{E}[\Phi_{n}(\pi_{n},\psi_{n})] - \mathbb{E}[\Phi_{n}(\hat{\pi}_{n},\psi_{n})]\|_{*,n}^{2} + \frac{1}{\alpha_{n}}\sigma_{g}^{2}\right) \\ & \leq \frac{4}{\alpha_{n}} \left(\sigma_{g}^{2} + \sigma_{g}^{2} + L^{2}\|\pi_{n} - \hat{\pi}_{n}\|_{n}^{2} + E_{n}(\Phi_{n})\right) \end{split}$$

where the last inequality is due to Assumption 4.

G.3. Optimal Regret Bounds

We now analyze the regret bound in Theorem 1

$$\sum_{n=1}^{N} w_n \left\langle g_n, \pi_n - \pi \right\rangle \le M_N + \sum_{n=1}^{N} \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - \frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2$$
(39)

We first gain some intuition about the size of

$$M_N + \mathbb{E}\left[\sum_{n=1}^N \frac{w_n^2}{2} \|e_n\|_{*,n}^2\right].$$
(40)

Because when $adapt(h_n, H_{n-1}, e_n, w_n)$ is called in the Correction Step in (28) with the error gradient e_n as input, an optimal base algorithm (e.g. all the base algorithms listed in Appendix C) would choose a local norm sequence $\|\cdot\|_n$ such that (40) is optimal. For example, suppose $\|e_n\|_*^2 = O(1)$ and $w_n = n^p$ for some p > -1. If the base algorithm is basic mirror descent (cf. Appendix C), then $\alpha_n = O(\frac{w_{1:n}}{\sqrt{n}})$. By our assumption that $M_N = O(\alpha_N)$, it implies (40) can be upper bounded by

$$M_N + \mathbb{E}\left[\sum_{n=1}^N \frac{w_n^2}{2} \|e_n\|_{*,n}^2\right] \le O\left(\frac{w_{1:N}}{\sqrt{N}}\right) + \left[\sum_{n=1}^N \frac{w_n^2 \sqrt{n}}{2w_{1:n}} \|e_n\|_{*}^2\right] \\ \le O\left(\frac{w_{1:N}}{\sqrt{N}} + \sum_{n=1}^N \frac{w_n^2 \sqrt{n}}{w_{1:n}}\right) = O\left(N^{p+1/2}\right)$$

which will lead to an optimal weighted average regret in $O(\frac{1}{\sqrt{N}})$.

PICCOLO actually has a better regret than the simplified case discussed above, because of the negative term $-\frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2$ in (39). To see its effects, we combine Lemma 7 with (39) to reveal some insights:

$$\mathbb{E}\left[\sum_{n=1}^{N} w_n \left\langle g_n, \pi_n - \pi \right\rangle\right] \leq O(\alpha_N) + \mathbb{E}\left[\sum_{n=1}^{N} \frac{w_n^2}{2} \|e_n\|_{*,n}^2 - \frac{1}{2} \|\pi_n - \hat{\pi}_n\|_{n-1}^2\right] \tag{41}$$

$$\leq O(\alpha_N) + \mathbb{E}\left[\sum_{n=1}^{N} \frac{2w_n^2}{\alpha_n} \left(\sigma_g^2 + \sigma_{\hat{g}}^2 + L^2 \|\pi_n - \hat{\pi}_n\|_n^2 + E_n(\Phi_n)\right) - \frac{\alpha_{n-1}}{2} \|\pi_n - \hat{\pi}_n\|_n^2\right]$$

$$= \left(O(\alpha_N) + \mathbb{E}\left[\sum_{n=1}^{N} \frac{2w_n^2}{\alpha_n} \left(\sigma_g^2 + \sigma_{\hat{g}}^2 + E_n(\Phi_n)\right)\right]\right) + \left(\mathbb{E}\left[\sum_{n=1}^{N} \left(\frac{2w_n^2}{\alpha_n}L^2 - \frac{\alpha_{n-1}}{2}\right) \|\pi_n - \hat{\pi}_n\|_n^2\right]\right)$$

$$\tag{41}$$

The first term in (42) plays the same role as (40); when the base algorithm has an optimal adapt operation and $w_n = n^p$ for some p > -1, it would be in $O(N^{p+1/2})$. Here we see that the constant factor in this bound is proportional to $\sigma_g^2 + \sigma_{\hat{g}}^2 + E_n(\Phi_n)$. Therefore, if the variances $\sigma_g^2, \sigma_{\hat{g}}^2$ of the gradients are small, the regret would mainly depend on the prediction error $E_n(\Phi_n)$ of Φ_n . In the next section (Appendix G.4), we will show that when Φ_n is learned online (as the authors in (Cheng et al., 2019) suggest), on average the regret is close to the regret of using the best model in the hindsight. The second term in (42) contributes to O(1) in the regret, when the base algorithm adapts properly to w_n . For example, when $\alpha_n = \Theta(\frac{w_{1:n}}{\sqrt{n}})$ and $w_n = n^p$ for some p > -1, then

$$\sum_{n=1}^{N} \frac{2w_n^2}{\alpha_n} L^2 - \frac{\alpha_{n-1}}{2} = \sum_{n=1}^{N} O(n^{p-1/2} - n^{p+1/2}) = O(1)$$

In addition, because $\|\pi_n - \hat{\pi}_n\|$ would converge to zero, the effects of the second term in (42) becomes even minor. In summary, for a reasonable base algorithm and $w_n = n^p$ with p > -1, running PICCOLO has the regret bound

$$\mathbb{E}\left[\sum_{n=1}^{N} w_n \left\langle g_n, \pi_n - \pi \right\rangle\right] = O(\alpha_N) + O\left(\frac{w_{1:N}}{\sqrt{N}}(\sigma_g^2 + \sigma_{\hat{g}}^2)\right) + O(1) + \mathbb{E}\left[\sum_{n=1}^{N} \frac{2w_n^2}{\alpha_n} E_n(\Phi_n)\right]$$
(43)

Suppose $\alpha_n = \Theta(|\Pi| \frac{w_{1:n}}{\sqrt{n}})$ and $w_n = n^p$ for some p > -1, This implies the inequality

$$\mathbb{E}\left[\sum_{n=1}^{N} \left\langle w_n g_n, \pi_n - \pi \right\rangle\right] \le O(1) + C_{\Pi, \Phi} \frac{w_{1:N}}{\sqrt{N}}$$
(38)

where $C_{\Pi,\Phi} = O(|\Pi| + \sigma_g^2 + \sigma_{\hat{g}}^2 + \sup_n E_n(\Phi_n))$. The use of non-uniform weights can lead to a faster on average decay of the standing O(1) term in the final weighted average regret bound, i.e.

$$\frac{1}{w_{1:N}} \mathbb{E}\left[\sum_{n=1}^{N} \left\langle w_n g_n, \pi_n - \pi \right\rangle\right] \le O\left(\frac{1}{w_{1:N}}\right) + \frac{C_{\Pi,\Phi}}{\sqrt{N}}$$

In general, the authors in (Cheng et al., 2018; 2019) recommend using $p \ll N$ (e.g. in the range of [0, 5]) to remove the undesirable constant factor, yet without introducing large multiplicative constant factor.

G.4. Model Learning

The regret bound in (43) reveals an important factor that is due to the prediction error $\mathbb{E}\left[\sum_{n=1}^{N} \frac{2w_n^2}{\alpha_n} E_n(\Phi_n)\right]$, where we recall $E_n(\Phi_n) = \|\mathbb{E}[g_n] - \mathbb{E}[\Phi_n(\pi_n)]\|_*^2$. Cheng et al. (2019) show that, to minimize this error sum through model learning, a secondary online learning problem with per-round loss $E_n(\cdot)$ can be considered. Note that this is a standard weighted adversarial online learning problem (weighted by $\frac{2w_n^2}{\alpha_n}$), because $E_n(\cdot)$ is revealed after one commits to using model Φ_n .

While in implementation the exact function $E_n(\cdot)$ is unavailable (as it requires infinite data), we can adopt an unbiased upper bound. For example, Cheng et al. (2019) show that $E_n(\cdot)$ can be upper bounded by the single- or multi-step prediction error of a transition dynamics model. More generally, we can learn a neural network to minimize the gradient prediction error directly. As long as this secondary online learning problem is solved by a no-regret algorithm, the error due to online model learning would contribute a term in $O(w_{1:N}\epsilon_{\mathcal{P},N}/\sqrt{N}) + o(w_{1:N}/\sqrt{N})$ in (43), where $\epsilon_{\mathcal{P},N}$ is the minimal error achieved by the best model in the model class \mathcal{P} (see (Cheng et al., 2019) for details).

H. Experimental Details

H.1. Algorithms

Base Algorithms In the experiments, we consider three commonly used first-order online learning algorithms: ADAM, NATGRAD, and TRPO, all of which adapt the regularization online to alleviate the burden of learning rate tuning. We provide the decomposition of ADAM into the basic three operations in Appendix C, and that of NATGRAD in Appendix E. In particular, the adaptivity of NATGRAD is achieved by adjusting the step size based on a moving average of the dual norm of the gradient. TRPO adjusts the step size to minimize a given cost function (here it is a linear function defined by the first-order oracle) within a pre-specified KL divergence centered at the current decision. While greedily changing the step size in every iteration makes TRPO an inappropriate candidate for adversarial online learning. Nonetheless, it can still be written in the form of mirror descent and allows a decomposition using the three basic operators; its adapt operator can be defined as the process of finding the maximal scalar step along the natural gradient direction such that the updated decision stays within the trust region. For all the algorithms, a decaying step size multiplier in the form $\eta/(1 + \alpha \sqrt{n})$ is also used; for TRPO, it is used to specify the size of trust regions. The values chosen for the hyperparameters η and α can be found in Table 2. To the best of our knowledge, the conversion of these approaches into unbiased model-based algorithms is novel.

Reinforcement Learning Per-round Loss In iteration n, in order to compute the online gradient (5), GAE (Schulman et al., 2016) is used to estimate the advantage function $A_{\pi_{n-1}}$. More concretely, this advantage estimate utilizes an estimate of value function $V_{\pi_{n-1}}$ (which we denote $\hat{V}_{\pi_{n-1}}$) and on-policy samples. We chosen $\lambda = 0.98$ in GAE to reduce influence of the error in $V_{\pi_{n-1}}$, which can be catastrophic. Importance sampling can be used to estimate $A_{\pi_{n-1}}$ in order to leverage data that are collected on-policy by running π_n . However, since we select a large λ , importance sampling can lead to vanishing importance weights, making the gradient extremely noisy. Therefore, in the experiments, importance sampling is not applied.

Gradient Computation and Control Variate The gradients are computed using likelihood-ratio trick and the associated advantage function estimates described above. A scalar control variate is further used to reduce the variance of the sampled gradient, which is set to the mean of the advantage estimates evaluated on newly collected data.

Policies and Value Networks Simple feed-forward neural networks are used to construct all of the function approximators (policy and value function) in the tasks. They have 1 hidden layer with 32 tanh units for all policy networks, and have 2 hidden layers with 64 tanh units for value function networks. Gaussian stochastic policies are considered, i.e., for any state $s \in \mathbb{S}$, π_s is Gaussian, and the mean of π_s is modeled by the policy network, whereas the diagonal covariance matrix is state independent (which is also learned). Initial value of $\log \sigma$ of the Gaussian policies -1.0, the standard deviation for initializing the output layer is 0.01, and the standard deviation for initialization hidden layer is 1.0. After the policy update, a new value function estimate \hat{V}_{π_n} is computed by minimizing the mean of squared difference between \hat{V}_{π_n} and $\hat{V}_{\pi_{n-1}} + \hat{A}_{\pi_n}$, where \hat{A}_{π_n} is the GAE estimate using $\hat{V}_{\pi_{n-1}}$ and $\lambda = 0.98$, through ADAM with batch size 128, number of batches 2048, and learning rate 0.001. Value function is pretrained using examples collected by executing the randomly initialized policy.

Computing Model Gradients We compute \hat{g}_n in two ways. The first approach is to use the simple heuristic that sets $\hat{g}_n = \Phi_n(\hat{\pi}_n)$, where Φ_n is some predictive models depending on the exact experimental setup. The second approach is to use the fixed-point formulation (8). This is realized by solving the equivalent optimization problem mentioned in the paper. In implementation, we only solves this problem approximately using some finite number of gradient steps; though this is insufficient to yield a stationary point as desired in the theory, we experimentally find that it is sufficient to yield improvement over the heuristic $\hat{g}_n = \Phi_n(\hat{\pi}_n)$.

Approximate Solution to Fixed-Point Problems of PICCOLO PICCOLO relies on the predicted gradient \hat{g}_n in the Prediction Step. Recall ideally we wish to solve the fixed-point problem that finds h_n^* such that

$$h_n^* = \text{update}(\hat{h}_n, H_{n-1}, \Phi_n(\pi_n(h_n^*)), w_n)$$
 (44)

and then apply $\hat{g}_n = \Phi_n(\pi_n(h_n^*))$ in the Prediction Step to get h_n , i.e.,

$$h_n = update(\hat{h}_n, H_{n-1}, \hat{g}_n, w_n)$$

Because h_n^* is the solution to the fixed-point problem, we have $h_n = h_n^*$. Such choice of \hat{g}_n will fully leverage the information provided by Φ_n , as it does not induce additional linearization due to evaluating Φ_n at points different from h_n .

Exactly solving the fixed-point problem is difficult. In the experiments, we adopt a heuristic which computes an approximation to h_n^* as follows. We suppose $\Phi_n = \nabla f_n$ for some function f_n , which is the case e.g. when Φ_n is the simulated gradient based on some (biased) dynamics model. This restriction makes the fixed-point problem as finding a stationary point of the optimization problem $\min_{\pi \in \Pi} f_n(\pi) + B_{R_{n-1}}(\pi || \hat{\pi}_n)$. In implementation, we initialize the iterate in this subproblem as $\operatorname{update}(\hat{h}_n, H_{n-1}, \Phi_n(\hat{\pi}_n), w_n)$, which is the output of the Prediction Step if we were to use $\hat{g}_n = \Phi_n(\hat{\pi}_n)$. We made this choice in initializing the subproblem, as we know that using $\hat{g}_n = \Phi_n(\hat{\pi}_n)$ in PICCOLO already works well (see the experiments) and it can be viewed as the solution to the fixed-point problem with respect to the linearized version of Φ_n at $\hat{\pi}_n$. Given the this initialization point, we proceed to compute the approximate solution to the fixed-point by applying the given base algorithm for 5 iterations and then return the last iterate as the approximate solution. For example, if the base algorithm is natural gradient descent, we fixed the Bregman divergence (i.e. its the Fisher information matrix as $\hat{\pi}_n$) and only updated the scalar stepsize adaptively along with the policy in solving this *regularized model-based RL problem* (i.e. $\min_{\pi \in \Pi} f_n(\pi) + B_{R_{n-1}}(\pi || \hat{\pi}_n)$). While such simple implementation is not ideal, we found it works in practice, though we acknowledge that a better implementation of the subproblem solver would improve the results.

H.2. Tasks

The robotic control tasks that are considered in the experiments are CartPole, Hopper, Snake, and Walker3D from OpenAI Gym (Brockman et al., 2016) with the DART physics engine (Lee et al., 2018)¹⁴. CartPole is a classic control problem, and its goal is to keep a pole balanced in a upright posture, by only applying force to the cart. Hopper, Snake, and Walker3D are locomotion tasks, of which the goal is to control an agent to move forward as quickly as possible without falling down (for Hopper and Walker3D) or deviating too much from moving forward (for Snake). Hopper is monopedal and Walker3D is bipedal, and both of them are subjected to significant contact discontinuities that are hard or even impossible to predict.

H.3. Full Experimental Results

In Figure 3, we empirically study the properties of PICCOLO that are predicted by theory on CartPole environment. In Figure 4, we "PICCOLO" three base algorithms: ADAM, NATGRAD, TRPO, and apply them on four simulated environments: Cartpole, Hopper, Snake, and Walker3D.

H.4. Experiment Hyperparameters

The hyperparameters used in the experiments and the basic attributes of the environments are detailed in Table 2.

¹⁴The environments are defined in DartEnv, hosted at https://github.com/DartEnv.

 $^{^{15}\}alpha$ and η appear in the decaying step size multiplier for all the algorithms in the form $\eta/(1 + \alpha\sqrt{n})$. α influences how fast the step size decays. We chose α in the experiments based on the number of iterations.



Figure 3: Performance of PICCOLO with different predictive models on CartPole. x axis is iteration number and y axis is sum of rewards. The curves are the median among 8 runs with different seeds, and the shaded regions account for 25% percentile. The update rule, by default, is PICCOLO. For example TRUEDYN in (a) refers to PICCOLO with TRUEDYN predictive model. (a), (b): Comparison of PICCOLO and DYNA with adversarial model using NATGRAD and TRPO as base algorithms. (c), (d): PICCOLO with the fixed-point setting (8) with dynamics model in different fidelities. BIASEDDYN0.8 indicates that the mass of each individual robot link is either increased or decreased by 80% with probablity 0.5 respectively.

	CartPole	Hopper	Snake	Walker3D
Observation space dimension	4	11	17	41
Action space dimension	1	3	6	15
State space dimension	4	12	18	42
Number of samples from env. per iteration	4k	16k	16k	32k
Number of samples from model dyn. per iteration	4k	16k	16k	32k
Length of horizon	1,000	1,000	1,000	1,000
Number of iterations	100	200	200	1,000
Number of iterations of samples for REPLAY buffer	5	4	3	2 (3 for ADAM)
α ¹⁵	0.1	0.1	0.1	0.01
η in Adam	0.005	0.005	0.002	0.01
η in NATGRAD	0.05	0.05	0.2	0.2
η in TRPO	0.002	0.002	0.01	0.04

Table 2: Tasks specifics and hyperparameters.



Figure 4: The performance of PICCOLO with different predictive models on various tasks, compared to base algorithms. The rows use ADAM, NATGRAD, and TRPO as the base algorithms, respectively. x axis is iteration number and y axis is sum of rewards. The curves are the median among 8 runs with different seeds, and the shaded regions account for 25% percentile.